

Network Working Group  
Internet-Draft  
Obsoletes: [4008](#) (if approved)  
Intended status: Standards Track  
Expires: April 22, 2015

S. Perreault  
Viagenie  
T. Tsou  
Huawei Technologies (USA)  
S. Sivakumar  
Cisco Systems  
T. Taylor  
PT Taylor Consulting  
October 19, 2014

Deprecation of MIB Module NAT-MIB (Managed Objects for Network Address  
Translators (NAT))  
draft-perrault-behave-deprecate-nat-mib-v1-00

## Abstract

This memo deprecates MIB module NAT-MIB, a portion of the Management Information Base (MIB) previously defined in [RFC 4008](#) for devices implementing Network Address Translator (NAT) function. A companion document defines a new version, NAT-MIB-V2, which responds to deficiencies found in module NAT-MIB and adds new capabilities.

This document obsoletes [RFC 4008](#).

## Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <http://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on April 22, 2015.

## Copyright Notice

Copyright (c) 2014 IETF Trust and the persons identified as the document authors. All rights reserved.

Internet-Draft

Deprecation of NAT MIB v1

October 2014

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

## Table of Contents

<a href="#">1.</a>	Introduction . . . . .	<a href="#">2</a>
<a href="#">2.</a>	The Internet-Standard Management Framework . . . . .	<a href="#">3</a>
<a href="#">3.</a>	Motivation For Deprecating NAT-MIB . . . . .	<a href="#">3</a>
<a href="#">3.1.</a>	Deprecated Features . . . . .	<a href="#">3</a>
<a href="#">3.2.</a>	Desirable New Features . . . . .	<a href="#">4</a>
<a href="#">4.</a>	Definitions . . . . .	<a href="#">5</a>
<a href="#">5.</a>	Security Considerations . . . . .	<a href="#">55</a>
<a href="#">6.</a>	IANA Considerations . . . . .	<a href="#">57</a>
<a href="#">7.</a>	References . . . . .	<a href="#">58</a>
<a href="#">7.1.</a>	Normative References . . . . .	<a href="#">58</a>
<a href="#">7.2.</a>	Informative References . . . . .	<a href="#">59</a>
	Authors' Addresses . . . . .	<a href="#">59</a>

## [1.](#) Introduction

This memo deprecates a portion of the Management Information Base (MIB), MIB module NAT-MIB, for devices implementing the Network Address Translator (NAT) function. New implementations are encouraged to base themselves upon the second version of this MIB module, NAT-MIB-V2, defined in [[I-D.ietf-behave-nat-mib-v2](#)]. NAT types and their characteristics are defined in [[RFC2663](#)]. Traditional NAT function, in particular is defined in [[RFC3022](#)]. Neither NAT-MIB nor NAT-MIB-V2 addresses the firewall functions and neither can be used for configuring or monitoring them.

[Section 2](#) provides references to the SNMP management framework, which was used as the basis for the original MIB module definition and its deprecation. [Section 3](#) provides motivation for the deprecation of module NAT-MIB and its replacement by module NAT-MIB-V2. [Section 4](#) has the complete NAT-MIB module definition, with the STATUS of all objects changed to deprecated. [Section 5](#) describes security

considerations relating to NAT-MIB, basically elaborating on the security considerations in [\[RFC4008\]](#).

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "NOT RECOMMENDED", "MAY", and

Perreault, et al.

Expires April 22, 2015

[Page 2]

---

Internet-Draft

Deprecation of NAT MIB v1

October 2014

"OPTIONAL" in this document are to be interpreted as described in [\[RFC2119\]](#).

## [2.](#) The Internet-Standard Management Framework

For a detailed overview of the documents that describe the current Internet-Standard Management Framework, please refer to [Section 7 of \[RFC3410\]](#).

Managed objects are accessed via a virtual information store, termed the Management Information Base or MIB. MIB objects are generally accessed through the Simple Network Management Protocol (SNMP). Objects in the MIB are defined using the mechanisms defined in the Structure of Management Information (SMI). This memo specifies a MIB module that is compliant to the SMIV2, which is described in STD 58, [\[RFC2578\]](#), STD 58, [\[RFC2579\]](#) and STD 58, [\[RFC2580\]](#).

## [3.](#) Motivation For Deprecating NAT-MIB

This section provides the motivation for deprecating the NAT-MIB module and its replacement by a new version.

### [3.1.](#) Deprecated Features

All objects defined in [\[RFC4008\]](#) have been marked with "STATUS deprecated" for the following reasons:

**Writability:** Experience with NAT has shown that implementations vary tremendously. The NAT algorithms and data structures have little in common across devices, and this results in wildly incompatible configuration parameters. Therefore, few implementations were ever able to claim full compliance.

**Lesson learned:** the MIB should be read-only as much as possible.

**Exposing configuration parameters:** Even in read-only mode, many

configuration parameters were exposed by [\[RFC4008\]](#) (e.g. timeouts). Since implementations vary wildly in their sets of configuration parameters, few implementations could claim even basic compliance.

Lesson learned: the NAT MIB's purpose is not to expose configuration parameters.

Interfaces: Objects from [\[RFC4008\]](#) tie NAT state with interfaces (e.g. the interface table, the way map entries are grouped by interface). Many NAT implementations either never keep track of the interface or associate a mapping to a set of interfaces.

Since interfaces are at the core of [\[RFC4008\]](#), many NAT devices were unable to have a proper implementation.

Lesson learned: NAT is a logical function that may be independent of interfaces. Do not tie NAT state with interfaces.

NAT service types: [\[RFC4008\]](#) used four categories of NAT service: basicNat, napt, bidirectionalNat, twiceNat. These are ill-defined and many implementations either use different categories or do not use categories at all.

Lesson learned: do not try to categorize NAT types.

Limited transport protocol set: The set of transport protocols was defined as: other, icmp, udp, tcp. Furthermore, the numeric values corresponding to those labels were arbitrary, without relation to the actual standard protocol numbers. This meant that NAT implementations were limited to those protocols and were unable to expose information about DCCP, SCTP, etc.

Lesson learned: use standard transport protocol numbers.

### [3.2.](#) Desirable New Features

A number of desirable new features have been identified that are not present in NAT-MIB:

- o Additional protective limits on the quantity of state data stored by the NAT device.

- o As a result of the deployment of Carrier Grade NAT (CGN), support for retrieval of subscriber specific statistics and limits on subscriber activity.
- o Support for pools of external addresses and ports. These are often used in enterprise and ISP settings.
- o Efficient determination of the internal address that is mapped to a given external address and port, without having to iterate over all mappings.
- o Replacement of the arbitrary categories of napt, bidirectionalNat, twiceNat with explicit specification of the internal and external realm for each mapping, allowing the NAT to serve many realms.
- o [\[RFC4787\]](#) terminology: indication of the mapping behavior, the filtering behavior, and the address pooling behavior that were used to create a mapping.

- o Support for multiple NAT instances running on a single device.

#### [4.](#) Definitions

This MIB module IMPORTs objects from [\[RFC2578\]](#), [\[RFC2579\]](#), and [\[RFC4001\]](#).

NAT-MIB DEFINITIONS ::= BEGIN

IMPORTS

MODULE-IDENTITY,  
 OBJECT-TYPE,  
 Integer32,  
 Unsigned32,  
 Gauge32,  
 Counter64,  
 TimeTicks,  
 mib-2,  
 NOTIFICATION-TYPE  
     FROM SNMPv2-SMI  
 TEXTUAL-CONVENTION,  
 DisplayString,

```

StorageType,
RowStatus
    FROM SNMPv2-TC
MODULE-COMPLIANCE,
NOTIFICATION-GROUP,
OBJECT-GROUP
    FROM SNMPv2-CONF
ifIndex,
ifCounterDiscontinuityGroup,
InterfaceIndex
    FROM IF-MIB
SnmpAdminString
    FROM SNMP-FRAMEWORK-MIB
InetAddressType,
InetAddress,
InetAddressPrefixLength,
InetPortNumber
    FROM INET-ADDRESS-MIB
VPNIdOrZero
    FROM VPN-TC-STD-MIB;

natMIB MODULE-IDENTITY
    LAST-UPDATED "201410180000Z"
-- RFC Ed.: set to publication date
    ORGANIZATION
        "IETF Behavior Engineering for Hindrance Avoidance

```

Perreault, et al.

Expires April 22, 2015

[Page 5]

Internet-Draft

Deprecation of NAT MIB v1

October 2014

```

    (BEHAVE) Working Group"
CONTACT-INFO
    "Working Group Email: behave@ietf.org

    Simon Perreault
    Viagenie
    246 Aberdeen
    Quebec, QC G1R 2E1
    Canada

    Phone: +1 418 656 9254
    Email: simon.perreault@viagenie.ca
    URI: http://viagenie.ca

```

Tina Tsou  
Huawei Technologies (USA)  
2330 Central Expressway  
Santa Clara, CA 95050  
USA

Phone: +1 408 330 4424  
Email: tina.tsou.zouting@huawei.com

Senthil Sivakumar  
Cisco Systems  
7100-8 Kit Creek Road  
Research Triangle Park, North Carolina 27709  
USA

Phone: +1 919 392 5158  
Email: ssenthil@cisco.com"

DESCRIPTION

"This MIB module defines the generic managed objects  
for NAT.

Copyright (C) The Internet Society (2014). This  
version of this MIB module is part of RFC yyyy; see  
the RFC itself for full legal notices."

-- RFC Ed.: replace yyyy with actual RFC number & remove this note"

REVISION "201410180000Z"

-- RFC Ed.: set to publication date

DESCRIPTION

"Deprecation, published as RFC yyyy."

-- RFC Ed.: replace yyyy with actual RFC number & set date"

REVISION "200503210000Z" -- 21th March 2005

DESCRIPTION

Perreault, et al.

Expires April 22, 2015

[Page 6]

---

Internet-Draft

Deprecation of NAT MIB v1

October 2014

"Initial version, published as [RFC 4008](#)."  
::= { mib-2 123 }

natMIBObjects OBJECT IDENTIFIER ::= { natMIB 1 }

NatProtocolType ::= TEXTUAL-CONVENTION

STATUS deprecated

DESCRIPTION

"A list of protocols that support the network address translation. Inclusion of the values is not intended to imply that those protocols need to be supported. Any change in this TEXTUAL-CONVENTION should also be reflected in the definition of NatProtocolMap, which is a BITS representation of this."

```
SYNTAX  INTEGER {
        none (1),  -- not specified
        other (2), -- none of the following
        icmp (3),
        udp (4),
        tcp (5)
    }
```

NatProtocolMap ::= TEXTUAL-CONVENTION

STATUS deprecated

DESCRIPTION

"A bitmap of protocol identifiers that support the network address translation. Any change in this TEXTUAL-CONVENTION should also be reflected in the definition of NatProtocolType."

```
SYNTAX  BITS {
        other (0),
        icmp (1),
        udp (2),
        tcp (3)
    }
```

NatAddrMapId ::= TEXTUAL-CONVENTION

DISPLAY-HINT "d"

STATUS deprecated

DESCRIPTION

"A unique id that is assigned to each address map by a NAT enabled device."

```
SYNTAX  Unsigned32 (1..4294967295)
```

NatBindIdOrZero ::= TEXTUAL-CONVENTION

DISPLAY-HINT "d"

STATUS deprecated



"A unique id that is assigned to each bind by a NAT enabled device. The bind id will be zero in the case of a Symmetric NAT."  
SYNTAX Unsigned32 (0..4294967295)

NatBindId ::= TEXTUAL-CONVENTION  
DISPLAY-HINT "d"  
STATUS deprecated  
DESCRIPTION  
"A unique id that is assigned to each bind by a NAT enabled device."  
SYNTAX Unsigned32 (1..4294967295)

NatSessionId ::= TEXTUAL-CONVENTION  
DISPLAY-HINT "d"  
STATUS deprecated  
DESCRIPTION  
"A unique id that is assigned to each session by a NAT enabled device."  
SYNTAX Unsigned32 (1..4294967295)

NatBindMode ::= TEXTUAL-CONVENTION  
STATUS deprecated  
DESCRIPTION  
"An indication of whether the bind is an address bind or an address port bind."  
SYNTAX INTEGER {  
addressBind (1),  
addressPortBind (2)  
}

NatAssociationType ::= TEXTUAL-CONVENTION  
STATUS deprecated  
DESCRIPTION  
"An indication of whether the association is static or dynamic."  
SYNTAX INTEGER {  
static (1),  
dynamic (2)  
}

NatTranslationEntity ::= TEXTUAL-CONVENTION  
STATUS deprecated  
DESCRIPTION  
"An indication of a) the direction of a session for which an address map entry, address bind or port bind is applicable, and b) the entity (source or

```

        destination) within the session that is subject to
        translation."
SYNTAX    BITS {
            inboundSrcEndPoint (0),
            outboundDstEndPoint(1),
            inboundDstEndPoint (2),
            outboundSrcEndPoint(3)
        }

--
-- Default Values for the Bind and NAT Protocol Timers
--

natDefTimeouts OBJECT IDENTIFIER ::= { natMIBObjects 1 }

natNotifCtrl OBJECT IDENTIFIER ::= { natMIBObjects 2 }

--
-- Address Bind and Port Bind related NAT configuration
--

natBindDefIdleTimeout OBJECT-TYPE
    SYNTAX      Unsigned32  (0..4294967295)
    UNITS        "seconds"
    MAX-ACCESS   read-write
    STATUS       deprecated
    DESCRIPTION
        "The default Bind (Address Bind or Port Bind) idle
        timeout parameter.

        If the agent is capable of storing non-volatile
        configuration, then the value of this object must be
        restored after a re-initialization of the management
        system."
    DEFVAL { 0 }
    ::= { natDefTimeouts 1 }

--
-- UDP related NAT configuration
--

natUdpDefIdleTimeout OBJECT-TYPE
    SYNTAX      Unsigned32  (1..4294967295)
    UNITS        "seconds"
    MAX-ACCESS   read-write
```

STATUS deprecated  
DESCRIPTION

Perreault, et al.

Expires April 22, 2015

[Page 9]

Internet-Draft

Deprecation of NAT MIB v1

October 2014

"The default UDP idle timeout parameter.

If the agent is capable of storing non-volatile configuration, then the value of this object must be restored after a re-initialization of the management system."

DEFVAL { 300 }

::= { natDefTimeouts 2 }

--

-- ICMP related NAT configuration

--

natIcmpDefIdleTimeout OBJECT-TYPE

SYNTAX Unsigned32 (1..4294967295)

UNITS "seconds"

MAX-ACCESS read-write

STATUS deprecated

DESCRIPTION

"The default ICMP idle timeout parameter.

If the agent is capable of storing non-volatile configuration, then the value of this object must be restored after a re-initialization of the management system."

DEFVAL { 300 }

::= { natDefTimeouts 3 }

--

-- Other protocol parameters

--

natOtherDefIdleTimeout OBJECT-TYPE

SYNTAX Unsigned32 (1..4294967295)

UNITS "seconds"

MAX-ACCESS read-write

STATUS deprecated

DESCRIPTION

"The default idle timeout parameter for protocols

represented by the value other (2) in  
NatProtocolType.

If the agent is capable of storing non-volatile  
configuration, then the value of this object must be  
restored after a re-initialization of the management  
system."

```
DEFVAL { 60 }  
::= { natDefTimeouts 4 }
```

```
--  
-- TCP related NAT Timers  
--
```

natTcpDefIdleTimeout OBJECT-TYPE

SYNTAX Unsigned32 (1..4294967295)

UNITS "seconds"

MAX-ACCESS read-write

STATUS deprecated

DESCRIPTION

"The default time interval that a NAT session for an  
established TCP connection is allowed to remain  
valid without any activity on the TCP connection.

If the agent is capable of storing non-volatile  
configuration, then the value of this object must be  
restored after a re-initialization of the management  
system."

```
DEFVAL { 86400 }
```

```
::= { natDefTimeouts 5 }
```

natTcpDefNegTimeout OBJECT-TYPE

SYNTAX Unsigned32 (1..4294967295)

UNITS "seconds"

MAX-ACCESS read-write

STATUS deprecated

DESCRIPTION

"The default time interval that a NAT session for a TCP  
connection that is not in the established state  
is allowed to remain valid without any activity on  
the TCP connection.

If the agent is capable of storing non-volatile configuration, then the value of this object must be restored after a re-initialization of the management system."

DEFVAL { 60 }

::= { natDefTimeouts 6 }

natNotifThrottlingInterval OBJECT-TYPE

SYNTAX Integer32 (0 | 5..3600)

UNITS "seconds"

MAX-ACCESS read-write

STATUS deprecated

DESCRIPTION

"This object controls the generation of the natPacketDiscard notification.

If this object has a value of zero, then no natPacketDiscard notifications will be transmitted by the agent.

If this object has a non-zero value, then the agent must not generate more than one natPacketDiscard 'notification-event' in the indicated period, where a 'notification-event' is the generation of a single notification PDU type to a list of notification destinations. If additional NAT packets are discarded within the throttling period, then notification-events for these changes must be suppressed by the agent until the current throttling period expires.

If natNotifThrottlingInterval notification generation is enabled, the suggested default throttling period is 60 seconds, but generation of the natPacketDiscard notification should be disabled by default.

If the agent is capable of storing non-volatile configuration, then the value of this object must be restored after a re-initialization of the management system.

The actual transmission of notifications is controlled

```

        via the MIB modules in RFC 3413."
DEFVAL { 0 }
 ::= { natNotifCtrl 1 }

--
-- The NAT Interface Table
--

natInterfaceTable OBJECT-TYPE
    SYNTAX      SEQUENCE OF NatInterfaceEntry
    MAX-ACCESS   not-accessible
    STATUS       deprecated
    DESCRIPTION
        "This table specifies the attributes for interfaces on a
         device supporting NAT function."
    ::= { natMIBObjects 3 }

natInterfaceEntry OBJECT-TYPE
    SYNTAX      NatInterfaceEntry
    MAX-ACCESS   not-accessible
    STATUS       deprecated
    DESCRIPTION

```

Perreault, et al. Expires April 22, 2015 [Page 12]

---

Internet-Draft Deprecation of NAT MIB v1 October 2014

"Each entry in the natInterfaceTable holds a set of parameters for an interface, instantiated by ifIndex. Therefore, the interface index must have been assigned, according to the applicable procedures, before it can be meaningfully used. Generally, this means that the interface must exist.

When natStorageType is of type nonVolatile, however, this may reflect the configuration for an interface whose ifIndex has been assigned but for which the supporting implementation is not currently present."

```

INDEX { ifIndex }
 ::= { natInterfaceTable 1 }

NatInterfaceEntry ::= SEQUENCE {
    natInterfaceRealm      INTEGER,
    natInterfaceServiceType BITS,
    natInterfaceInTranslates Counter64,

```

```

        natInterfaceOutTranslates    Counter64,
        natInterfaceDiscards         Counter64,
        natInterfaceStorageType      StorageType,
        natInterfaceRowStatus         RowStatus
    }

natInterfaceRealm OBJECT-TYPE
    SYNTAX      INTEGER {
                    private (1),
                    public (2)
                }
    MAX-ACCESS  read-create
    STATUS      deprecated
    DESCRIPTION
        "This object identifies whether this interface is
        connected to the private or the public realm."
    DEFVAL      { public }
    ::= { natInterfaceEntry 1 }

natInterfaceServiceType OBJECT-TYPE
    SYNTAX      BITS {
                    basicNat (0),
                    napt (1),
                    bidirectionalNat (2),
                    twiceNat (3)
                }
    MAX-ACCESS  read-create
    STATUS      deprecated
    DESCRIPTION
        "An indication of the direction in which new sessions

```

```

        are permitted and the extent of translation done within
        the IP and transport headers."
    ::= { natInterfaceEntry 2 }

```

```

natInterfaceInTranslates OBJECT-TYPE
    SYNTAX      Counter64
    MAX-ACCESS  read-only
    STATUS      deprecated
    DESCRIPTION
        "Number of packets received on this interface that
        were translated.

```

Discontinuities in the value of this counter can occur at reinitialization of the management system and at other times as indicated by the value of ifCounterDiscontinuityTime on the relevant interface."

```
::= { natInterfaceEntry 3 }
```

natInterfaceOutTranslates OBJECT-TYPE

SYNTAX Counter64  
MAX-ACCESS read-only  
STATUS deprecated  
DESCRIPTION

"Number of translated packets that were sent out this interface.

Discontinuities in the value of this counter can occur at reinitialization of the management system and at other times as indicated by the value of ifCounterDiscontinuityTime on the relevant interface."

```
::= { natInterfaceEntry 4 }
```

natInterfaceDiscards OBJECT-TYPE

SYNTAX Counter64  
MAX-ACCESS read-only  
STATUS deprecated  
DESCRIPTION

"Number of packets that had to be rejected/dropped due to a lack of resources for this interface.

Discontinuities in the value of this counter can occur at reinitialization of the management system and at other times as indicated by the value of ifCounterDiscontinuityTime on the relevant interface."

```
::= { natInterfaceEntry 5 }
```

natInterfaceStorageType OBJECT-TYPE

SYNTAX StorageType  
MAX-ACCESS read-create

STATUS deprecated

DESCRIPTION

"The storage type for this conceptual row.  
Conceptual rows having the value 'permanent'



need not allow write-access to any columnar objects  
in the row."

REFERENCE

"Textual Conventions for SMIV2, [Section 2](#)."

DEFVAL { nonVolatile }

::= { natInterfaceEntry 6 }

natInterfaceRowStatus OBJECT-TYPE

SYNTAX RowStatus

MAX-ACCESS read-create

STATUS deprecated

DESCRIPTION

"The status of this conceptual row.

Until instances of all corresponding columns are  
appropriately configured, the value of the  
corresponding instance of the natInterfaceRowStatus  
column is 'notReady'.

In particular, a newly created row cannot be made  
active until the corresponding instance of  
natInterfaceServiceType has been set.

None of the objects in this row may be modified  
while the value of this object is active(1)."

REFERENCE

"Textual Conventions for SMIV2, [Section 2](#)."

::= { natInterfaceEntry 7 }

--

-- The Address Map Table

--

natAddrMapTable OBJECT-TYPE

SYNTAX SEQUENCE OF NatAddrMapEntry

MAX-ACCESS not-accessible

STATUS deprecated

DESCRIPTION

"This table lists address map parameters for NAT."

::= { natMIBObjects 4 }

natAddrMapEntry OBJECT-TYPE

SYNTAX NatAddrMapEntry

MAX-ACCESS not-accessible  
STATUS deprecated  
DESCRIPTION  
    "This entry represents an address map to be used for  
    NAT and contributes to the dynamic and/or static  
    address mapping tables of the NAT device."  
INDEX { ifIndex, natAddrMapIndex }  
 ::= { natAddrMapTable 1 }

NatAddrMapEntry ::= SEQUENCE {  
    natAddrMapIndex  
    natAddrMapName  
    natAddrMapEntryType  
    natAddrMapTranslationEntity  
    natAddrMapLocalAddrType  
    natAddrMapLocalAddrFrom  
    natAddrMapLocalAddrTo  
    natAddrMapLocalPortFrom  
    natAddrMapLocalPortTo  
    natAddrMapGlobalAddrType  
    natAddrMapGlobalAddrFrom  
    natAddrMapGlobalAddrTo  
    natAddrMapGlobalPortFrom  
    natAddrMapGlobalPortTo  
    natAddrMapProtocol  
    natAddrMapInTranslates  
    natAddrMapOutTranslates  
    natAddrMapDiscards  
    natAddrMapAddrUsed  
    natAddrMapStorageType  
    natAddrMapRowStatus  
    NatAddrMapId,  
    SnmpAdminString,  
    NatAssociationType,  
    NatTranslationEntity,  
    InetAddressType,  
    InetAddress,  
    InetAddress,  
    InetPortNumber,  
    InetPortNumber,  
    InetAddressType,  
    InetAddress,  
    InetAddress,  
    InetPortNumber,  
    InetPortNumber,  
    NatProtocolMap,  
    Counter64,  
    Counter64,  
    Counter64,  
    Gauge32,  
    StorageType,  
    RowStatus  
}

natAddrMapIndex OBJECT-TYPE  
SYNTAX NatAddrMapId  
MAX-ACCESS not-accessible  
STATUS deprecated  
DESCRIPTION  
    "Along with ifIndex, this object uniquely  
    identifies an entry in the natAddrMapTable.  
    Address map entries are applied in the order  
    specified by natAddrMapIndex."  
 ::= { natAddrMapEntry 1 }

natAddrMapName OBJECT-TYPE  
SYNTAX SnmpAdminString (SIZE(1..32))  
MAX-ACCESS read-create

DESCRIPTION

"Name identifying all map entries in the table associated with the same interface. All map entries with the same ifIndex MUST have the same map name."

::= { natAddrMapEntry 2 }

natAddrMapEntryType OBJECT-TYPE

SYNTAX NatAssociationType

MAX-ACCESS read-create

STATUS deprecated

DESCRIPTION

"This parameter can be used to set up static or dynamic address maps."

::= { natAddrMapEntry 3 }

natAddrMapTranslationEntity OBJECT-TYPE

SYNTAX NatTranslationEntity

MAX-ACCESS read-create

STATUS deprecated

DESCRIPTION

"The end-point entity (source or destination) in inbound or outbound sessions (i.e., first packets) that may be translated by an address map entry.

Session direction (inbound or outbound) is derived from the direction of the first packet of a session traversing a NAT interface.

NAT address (and Transport-ID) maps may be defined to effect inbound or outbound sessions.

Traditionally, address maps for Basic NAT and NAPT are configured on a public interface for outbound sessions, effecting translation of source end-point. The value of this object must be set to outboundSrcEndPoint for those interfaces.

Alternately, if address maps for Basic NAT and NAPT were to be configured on a private interface, the desired value for this object for the map entries would be inboundSrcEndPoint (i.e., effecting translation

of source end-point for inbound sessions).

If TwiceNAT were to be configured on a private interface, the desired value for this object for the map entries would be a bitmask of inboundSrcEndPoint and inboundDstEndPoint."

::= { natAddrMapEntry 4 }

natAddrMapLocalAddrType OBJECT-TYPE

SYNTAX InetAddressType

MAX-ACCESS read-create

STATUS deprecated

DESCRIPTION

"This object specifies the address type used for natAddrMapLocalAddrFrom and natAddrMapLocalAddrTo."

::= { natAddrMapEntry 5 }

natAddrMapLocalAddrFrom OBJECT-TYPE

SYNTAX InetAddress

MAX-ACCESS read-create

STATUS deprecated

DESCRIPTION

"This object specifies the first IP address of the range of IP addresses mapped by this translation entry. The value of this object must be less than or equal to the value of the natAddrMapLocalAddrTo object.

The type of this address is determined by the value of the natAddrMapLocalAddrType object."

::= { natAddrMapEntry 6 }

natAddrMapLocalAddrTo OBJECT-TYPE

SYNTAX InetAddress

MAX-ACCESS read-create

STATUS deprecated

DESCRIPTION

"This object specifies the last IP address of the range of IP addresses mapped by this translation entry. If only a single address is being mapped, the value of this object is equal to the value of natAddrMapLocalAddrFrom. For a static NAT, the number of addresses in the range

defined by natAddrMapLocalAddrFrom and natAddrMapLocalAddrTo must be equal to the number of addresses in the range defined by natAddrMapGlobalAddrFrom and natAddrMapGlobalAddrTo. The value of this object must be greater than or equal to the value of the natAddrMapLocalAddrFrom object.

The type of this address is determined by the value of the natAddrMapLocalAddrType object."

::= { natAddrMapEntry 7 }

natAddrMapLocalPortFrom OBJECT-TYPE

SYNTAX InetPortNumber

MAX-ACCESS read-create

STATUS deprecated

Perreault, et al.

Expires April 22, 2015

[Page 18]

---

Internet-Draft

Deprecation of NAT MIB v1

October 2014

#### DESCRIPTION

"If this conceptual row describes a Basic NAT address mapping, then the value of this object must be zero. If this conceptual row describes NAPT, then the value of this object specifies the first port number in the range of ports being mapped.

The value of this object must be less than or equal to the value of the natAddrMapLocalPortTo object. If the translation specifies a single port, then the value of this object is equal to the value of natAddrMapLocalPortTo."

DEFVAL { 0 }

::= { natAddrMapEntry 8 }

natAddrMapLocalPortTo OBJECT-TYPE

SYNTAX InetPortNumber

MAX-ACCESS read-create

STATUS deprecated

#### DESCRIPTION

"If this conceptual row describes a Basic NAT address mapping, then the value of this object must be zero. If this conceptual row describes NAPT, then the value of this object specifies the last port number in the range of ports being mapped.

The value of this object must be greater than or equal to the value of the natAddrMapLocalPortFrom object. If the translation specifies a single port, then the value of this object is equal to the value of natAddrMapLocalPortFrom."

DEFVAL { 0 }

::= { natAddrMapEntry 9 }

natAddrMapGlobalAddrType OBJECT-TYPE

SYNTAX InetAddressType

MAX-ACCESS read-create

STATUS deprecated

DESCRIPTION

"This object specifies the address type used for natAddrMapGlobalAddrFrom and natAddrMapGlobalAddrTo."

::= { natAddrMapEntry 10 }

natAddrMapGlobalAddrFrom OBJECT-TYPE

SYNTAX InetAddress

MAX-ACCESS read-create

STATUS deprecated

DESCRIPTION

"This object specifies the first IP address of the range of IP addresses being mapped to. The value of this object must be less than or equal to the value of the natAddrMapGlobalAddrTo object.

The type of this address is determined by the value of the natAddrMapGlobalAddrType object."

::= { natAddrMapEntry 11 }

natAddrMapGlobalAddrTo OBJECT-TYPE

SYNTAX InetAddress

MAX-ACCESS read-create

STATUS deprecated

DESCRIPTION

"This object specifies the last IP address of the range of IP addresses being mapped to. If only a single address is being mapped to, the value of this object is equal to the value of natAddrMapGlobalAddrFrom. For a static NAT, the number of addresses in the range defined

by natAddrMapGlobalAddrFrom and natAddrMapGlobalAddrTo must be equal to the number of addresses in the range defined by natAddrMapLocalAddrFrom and natAddrMapLocalAddrTo. The value of this object must be greater than or equal to the value of the natAddrMapGlobalAddrFrom object.

The type of this address is determined by the value of the natAddrMapGlobalAddrType object."

::= { natAddrMapEntry 12 }

natAddrMapGlobalPortFrom OBJECT-TYPE

SYNTAX InetPortNumber

MAX-ACCESS read-create

STATUS deprecated

DESCRIPTION

"If this conceptual row describes a Basic NAT address mapping, then the value of this object must be zero. If this conceptual row describes NAPT, then the value of this object specifies the first port number in the range of ports being mapped to.

The value of this object must be less than or equal to the value of the natAddrMapGlobalPortTo object. If the translation specifies a single port, then the value of this object is equal to the value natAddrMapGlobalPortTo."

DEFVAL { 0 }

::= { natAddrMapEntry 13 }

natAddrMapGlobalPortTo OBJECT-TYPE

SYNTAX InetPortNumber

MAX-ACCESS read-create

STATUS deprecated

DESCRIPTION

"If this conceptual row describes a Basic NAT address mapping, then the value of this object must be zero. If this conceptual row describes NAPT, then the value of this object specifies the last port number in the range of ports being mapped to.

The value of this object must be greater than or equal to the value of the natAddrMapGlobalPortFrom object. If the translation specifies a single port, then the value of this object is equal to the value of natAddrMapGlobalPortFrom."

DEFVAL { 0 }

::= { natAddrMapEntry 14 }

natAddrMapProtocol OBJECT-TYPE

SYNTAX NatProtocolMap

MAX-ACCESS read-create

STATUS deprecated

DESCRIPTION

"This object specifies a bitmap of protocol identifiers."

::= { natAddrMapEntry 15 }

natAddrMapInTranslates OBJECT-TYPE

SYNTAX Counter64

MAX-ACCESS read-only

STATUS deprecated

DESCRIPTION

"The number of inbound packets pertaining to this address map entry that were translated.

Discontinuities in the value of this counter can occur at reinitialization of the management system and at other times, as indicated by the value of ifCounterDiscontinuityTime on the relevant interface."

::= { natAddrMapEntry 16 }

natAddrMapOutTranslates OBJECT-TYPE

SYNTAX Counter64

MAX-ACCESS read-only

STATUS deprecated

DESCRIPTION

"The number of outbound packets pertaining to this address map entry that were translated.

Discontinuities in the value of this counter can occur at reinitialization of the management system and at



other times, as indicated by the value of  
ifCounterDiscontinuityTime on the relevant interface."  
 ::= { natAddrMapEntry 17 }

natAddrMapDiscards OBJECT-TYPE

SYNTAX Counter64

MAX-ACCESS read-only

STATUS deprecated

DESCRIPTION

"The number of packets pertaining to this address map entry that were dropped due to lack of addresses in the address pool identified by this address map. The value of this object must always be zero in case of static address map.

Discontinuities in the value of this counter can occur at reinitialization of the management system and at other times, as indicated by the value of  
ifCounterDiscontinuityTime on the relevant interface."

::= { natAddrMapEntry 18 }

natAddrMapAddrUsed OBJECT-TYPE

SYNTAX Gauge32

MAX-ACCESS read-only

STATUS deprecated

DESCRIPTION

"The number of addresses pertaining to this address map that are currently being used from the NAT pool. The value of this object must always be zero in the case of a static address map."

::= { natAddrMapEntry 19 }

natAddrMapStorageType OBJECT-TYPE

SYNTAX StorageType

MAX-ACCESS read-create

STATUS deprecated

DESCRIPTION

"The storage type for this conceptual row. Conceptual rows having the value 'permanent' need not allow write-access to any columnar objects in the row."

REFERENCE

"Textual Conventions for SMIV2, [Section 2](#)."

```

    DEFVAL { nonVolatile }
    ::= { natAddrMapEntry 20 }

natAddrMapRowStatus OBJECT-TYPE
    SYNTAX      RowStatus
    MAX-ACCESS   read-create
    STATUS       deprecated
    DESCRIPTION
        "The status of this conceptual row.

        Until instances of all corresponding columns are
        appropriately configured, the value of the
        corresponding instance of the natAddrMapRowStatus
        column is 'notReady'.

        None of the objects in this row may be modified
        while the value of this object is active(1)."
```

REFERENCE

```

        "Textual Conventions for SMIV2, Section 2."
    ::= { natAddrMapEntry 21 }

--
-- Address Bind section
--

natAddrBindNumberOfEntries OBJECT-TYPE
    SYNTAX      Gauge32
    MAX-ACCESS   read-only
    STATUS       deprecated
    DESCRIPTION
        "This object maintains a count of the number of entries
        that currently exist in the natAddrBindTable."
    ::= { natMIBObjects 5 }

--
-- The NAT Address BIND Table
--

natAddrBindTable OBJECT-TYPE
    SYNTAX      SEQUENCE OF NatAddrBindEntry
    MAX-ACCESS   not-accessible
    STATUS       deprecated
    DESCRIPTION
        "This table holds information about the currently
        active NAT BINDs."
    ::= { natMIBObjects 6 }

natAddrBindEntry OBJECT-TYPE

```

Internet-Draft

Deprecation of NAT MIB v1

October 2014

SYNTAX NatAddrBindEntry

MAX-ACCESS not-accessible

STATUS deprecated

DESCRIPTION

"Each entry in this table holds information about an active address BIND. These entries are lost upon agent restart.

This row has indexing which may create variables with more than 128 subidentifiers. Implementers of this table must be careful not to create entries that would result in OIDs which exceed the 128 subidentifier limit. Otherwise, the information cannot be accessed using SNMPv1, SNMPv2c or SNMPv3."

INDEX { ifIndex,  
natAddrBindLocalAddrType,  
natAddrBindLocalAddr }

::= { natAddrBindTable 1 }

NatAddrBindEntry ::= SEQUENCE {  
natAddrBindLocalAddrType InetAddressType,  
natAddrBindLocalAddr InetAddress,  
natAddrBindGlobalAddrType InetAddressType,  
natAddrBindGlobalAddr InetAddress,  
natAddrBindId NatBindId,  
natAddrBindTranslationEntity NatTranslationEntity,  
natAddrBindType NatAssociationType,  
natAddrBindMapIndex NatAddrMapId,  
natAddrBindSessions Gauge32,  
natAddrBindMaxIdleTime TimeTicks,  
natAddrBindCurrentIdleTime TimeTicks,  
natAddrBindInTranslates Counter64,  
natAddrBindOutTranslates Counter64  
}

natAddrBindLocalAddrType OBJECT-TYPE

SYNTAX InetAddressType

MAX-ACCESS not-accessible

STATUS deprecated

DESCRIPTION

"This object specifies the address type used for

```
        natAddrBindLocalAddr."  
 ::= { natAddrBindEntry 1 }
```

```
natAddrBindLocalAddr OBJECT-TYPE  
    SYNTAX      InetAddress (SIZE (4|16))  
    MAX-ACCESS  not-accessible
```

Perreault, et al.

Expires April 22, 2015

[Page 24]

---

Internet-Draft

Deprecation of NAT MIB v1

October 2014

```
STATUS      deprecated
```

```
DESCRIPTION
```

```
    "This object represents the private-realm specific  
    network layer address, which maps to the public-realm  
    address represented by natAddrBindGlobalAddr.
```

```
    The type of this address is determined by the value of  
    the natAddrBindLocalAddrType object."
```

```
 ::= { natAddrBindEntry 2 }
```

```
natAddrBindGlobalAddrType OBJECT-TYPE
```

```
    SYNTAX      InetAddressType
```

```
    MAX-ACCESS  read-only
```

```
    STATUS      deprecated
```

```
    DESCRIPTION
```

```
    "This object specifies the address type used for  
    natAddrBindGlobalAddr."
```

```
 ::= { natAddrBindEntry 3 }
```

```
natAddrBindGlobalAddr OBJECT-TYPE
```

```
    SYNTAX      InetAddress
```

```
    MAX-ACCESS  read-only
```

```
    STATUS      deprecated
```

```
    DESCRIPTION
```

```
    "This object represents the public-realm network layer  
    address that maps to the private-realm network layer  
    address represented by natAddrBindLocalAddr.
```

```
    The type of this address is determined by the value of  
    the natAddrBindGlobalAddrType object."
```

```
 ::= { natAddrBindEntry 4 }
```

```
natAddrBindId OBJECT-TYPE
```

```
    SYNTAX      NatBindId
```

```
    MAX-ACCESS  read-only
```

STATUS deprecated

DESCRIPTION

"This object represents a bind id that is dynamically assigned to each bind by a NAT enabled device. Each bind is represented by a bind id that is unique across both, the natAddrBindTable and the natAddrPortBindTable."

::= { natAddrBindEntry 5 }

natAddrBindTranslationEntity OBJECT-TYPE

SYNTAX NatTranslationEntity

MAX-ACCESS read-only

STATUS deprecated

DESCRIPTION

"This object represents the direction of sessions for which this bind is applicable and the endpoint entity (source or destination) within the sessions that is subject to translation using the BIND.

Orientation of the bind can be a superset of translationEntity of the address map entry which forms the basis for this bind.

For example, if the translationEntity of an address map entry is outboundSrcEndPoint, the translationEntity of a bind derived from this map entry may either be outboundSrcEndPoint or it may be bidirectional (a bitmask of outboundSrcEndPoint and inboundDstEndPoint)."

::= { natAddrBindEntry 6 }

natAddrBindType OBJECT-TYPE

SYNTAX NatAssociationType

MAX-ACCESS read-only

STATUS deprecated

DESCRIPTION

"This object indicates whether the bind is static or dynamic."

::= { natAddrBindEntry 7 }

natAddrBindMapIndex OBJECT-TYPE

SYNTAX       NatAddrMapId  
MAX-ACCESS read-only  
STATUS       deprecated  
DESCRIPTION

"This object is a pointer to the natAddrMapTable entry (and the parameters of that entry) which was used in creating this BIND. This object, in conjunction with the ifIndex (which identifies a unique addrMapName) points to a unique entry in the natAddrMapTable."

::= { natAddrBindEntry 8 }

natAddrBindSessions OBJECT-TYPE

SYNTAX       Gauge32  
MAX-ACCESS read-only  
STATUS       deprecated  
DESCRIPTION

"Number of sessions currently using this BIND."

::= { natAddrBindEntry 9 }

natAddrBindMaxIdleTime OBJECT-TYPE

SYNTAX       TimeTicks  
MAX-ACCESS read-only  
STATUS       deprecated  
DESCRIPTION

"This object indicates the maximum time for which this bind can be idle with no sessions attached to it.

The value of this object is of relevance only for dynamic NAT."

::= { natAddrBindEntry 10 }

natAddrBindCurrentIdleTime OBJECT-TYPE

SYNTAX       TimeTicks  
MAX-ACCESS read-only  
STATUS       deprecated  
DESCRIPTION

"At any given instance, this object indicates the time that this bind has been idle without any sessions attached to it.

The value of this object is of relevance only for  
dynamic NAT."  
 ::= { natAddrBindEntry 11 }

natAddrBindInTranslates OBJECT-TYPE

SYNTAX Counter64

MAX-ACCESS read-only

STATUS deprecated

DESCRIPTION

"The number of inbound packets that were successfully  
translated by using this bind entry.

Discontinuities in the value of this counter can occur  
at reinitialization of the management system and at  
other times, as indicated by the value of  
ifCounterDiscontinuityTime on the relevant interface."

::= { natAddrBindEntry 12 }

natAddrBindOutTranslates OBJECT-TYPE

SYNTAX Counter64

MAX-ACCESS read-only

STATUS deprecated

DESCRIPTION

"The number of outbound packets that were successfully  
translated using this bind entry.

Discontinuities in the value of this counter can occur

at reinitialization of the management system and at  
other times as indicated by the value of  
ifCounterDiscontinuityTime on the relevant interface."  
 ::= { natAddrBindEntry 13 }

--

-- Address Port Bind section

--

natAddrPortBindNumberOfEntries OBJECT-TYPE

SYNTAX Gauge32

MAX-ACCESS read-only

STATUS deprecated

DESCRIPTION

```

        "This object maintains a count of the number of entries
        that currently exist in the natAddrPortBindTable."
 ::= { natMIBObjects 7 }

--
-- The NAT Address Port Bind Table
--

natAddrPortBindTable OBJECT-TYPE
    SYNTAX      SEQUENCE OF NatAddrPortBindEntry
    MAX-ACCESS  not-accessible
    STATUS      deprecated
    DESCRIPTION
        "This table holds information about the currently
        active NAPT BINDs."
 ::= { natMIBObjects 8 }

natAddrPortBindEntry OBJECT-TYPE
    SYNTAX      NatAddrPortBindEntry
    MAX-ACCESS  not-accessible
    STATUS      deprecated
    DESCRIPTION
        "Each entry in the this table holds information
        about a NAPT bind that is currently active.
        These entries are lost upon agent restart.

        This row has indexing which may create variables with
        more than 128 subidentifiers. Implementers of this
        table must be careful not to create entries which would
        result in OIDs that exceed the 128 subidentifier limit.
        Otherwise, the information cannot be accessed using
        SNMPv1, SNMPv2c or SNMPv3."
    INDEX      { ifIndex, natAddrPortBindLocalAddrType,
                natAddrPortBindLocalAddr, natAddrPortBindLocalPort,

```

```

        natAddrPortBindProtocol }
 ::= { natAddrPortBindTable 1 }

NatAddrPortBindEntry ::= SEQUENCE {
    natAddrPortBindLocalAddrType      InetAddressType,
    natAddrPortBindLocalAddr          InetAddress,
    natAddrPortBindLocalPort          InetPortNumber,

```



```

natAddrPortBindProtocol          NatProtocolType,
natAddrPortBindGlobalAddrType    InetAddressType,
natAddrPortBindGlobalAddr        InetAddress,
natAddrPortBindGlobalPort        InetPortNumber,
natAddrPortBindId                NatBindId,
natAddrPortBindTranslationEntity NatTranslationEntity,
natAddrPortBindType              NatAssociationType,
natAddrPortBindMapIndex          NatAddrMapId,
natAddrPortBindSessions          Gauge32,
natAddrPortBindMaxIdleTime       TimeTicks,
natAddrPortBindCurrentIdleTime   TimeTicks,
natAddrPortBindInTranslates      Counter64,
natAddrPortBindOutTranslates     Counter64
}

natAddrPortBindLocalAddrType OBJECT-TYPE
    SYNTAX      InetAddressType
    MAX-ACCESS   not-accessible
    STATUS      deprecated
    DESCRIPTION
        "This object specifies the address type used for
         natAddrPortBindLocalAddr."
    ::= { natAddrPortBindEntry 1 }

natAddrPortBindLocalAddr OBJECT-TYPE
    SYNTAX      InetAddress (SIZE(4|16))
    MAX-ACCESS   not-accessible
    STATUS      deprecated
    DESCRIPTION
        "This object represents the private-realm specific
         network layer address which, in conjunction with
         natAddrPortBindLocalPort, maps to the public-realm
         network layer address and transport id represented by
         natAddrPortBindGlobalAddr and natAddrPortBindGlobalPort
         respectively.

         The type of this address is determined by the value of
         the natAddrPortBindLocalAddrType object."
    ::= { natAddrPortBindEntry 2 }

```

natAddrPortBindLocalPort OBJECT-TYPE

SYNTAX InetPortNumber

MAX-ACCESS not-accessible

STATUS deprecated

DESCRIPTION

"For a protocol value TCP or UDP, this object represents the private-realm specific port number. On the other hand, for ICMP a bind is created only for query/response type ICMP messages such as ICMP echo, Timestamp, and Information request messages, and this object represents the private-realm specific identifier in the ICMP message, as defined in [RFC 792](#) for ICMPv4 and in [RFC 2463](#) for ICMPv6.

This object, together with natAddrPortBindProtocol, natAddrPortBindLocalAddrType, and natAddrPortBindLocalAddr, constitutes a session endpoint in the private realm. A bind entry binds a private realm specific endpoint to a public realm specific endpoint, as represented by the tuple of (natAddrPortBindGlobalPort, natAddrPortBindProtocol, natAddrPortBindGlobalAddrType, and natAddrPortBindGlobalAddr)."

::= { natAddrPortBindEntry 3 }

natAddrPortBindProtocol OBJECT-TYPE

SYNTAX NatProtocolType

MAX-ACCESS not-accessible

STATUS deprecated

DESCRIPTION

"This object specifies a protocol identifier. If the value of this object is none(1), then this bind entry applies to all IP traffic. Any other value of this object specifies the class of IP traffic to which this BIND applies."

::= { natAddrPortBindEntry 4 }

natAddrPortBindGlobalAddrType OBJECT-TYPE

SYNTAX InetAddressType

MAX-ACCESS read-only

STATUS deprecated

DESCRIPTION

"This object specifies the address type used for natAddrPortBindGlobalAddr."

::= { natAddrPortBindEntry 5 }

natAddrPortBindGlobalAddr OBJECT-TYPE

SYNTAX InetAddress

Internet-Draft

Deprecation of NAT MIB v1

October 2014

MAX-ACCESS read-only

STATUS deprecated

DESCRIPTION

"This object represents the public-realm specific network layer address that, in conjunction with natAddrPortBindGlobalPort, maps to the private-realm

network layer address and transport id represented by natAddrPortBindLocalAddr and natAddrPortBindLocalPort, respectively.

The type of this address is determined by the value of the natAddrPortBindGlobalAddrType object."

::= { natAddrPortBindEntry 6 }

natAddrPortBindGlobalPort OBJECT-TYPE

SYNTAX InetPortNumber

MAX-ACCESS read-only

STATUS deprecated

DESCRIPTION

"For a protocol value TCP or UDP, this object represents the public-realm specific port number. On the other hand, for ICMP a bind is created only for query/response type ICMP messages such as ICMP echo, Timestamp, and Information request messages, and this object represents the public-realm specific identifier in the ICMP message, as defined in [RFC 792](#) for ICMPv4 and in [RFC 2463](#) for ICMPv6.

This object, together with natAddrPortBindProtocol, natAddrPortBindGlobalAddrType, and natAddrPortBindGlobalAddr, constitutes a session endpoint in the public realm. A bind entry binds a public realm specific endpoint to a private realm specific endpoint, as represented by the tuple of (natAddrPortBindLocalPort, natAddrPortBindProtocol, natAddrPortBindLocalAddrType, and natAddrPortBindLocalAddr)."

::= { natAddrPortBindEntry 7 }

natAddrPortBindId OBJECT-TYPE

SYNTAX NatBindId

MAX-ACCESS read-only

STATUS deprecated

DESCRIPTION

"This object represents a bind id that is dynamically assigned to each bind by a NAT enabled device. Each bind is represented by a unique bind id across both

Perreault, et al.

Expires April 22, 2015

[Page 31]

---

Internet-Draft

Deprecation of NAT MIB v1

October 2014

the natAddrBindTable and the natAddrPortBindTable."  
 ::= { natAddrPortBindEntry 8 }

natAddrPortBindTranslationEntity OBJECT-TYPE

SYNTAX NatTranslationEntity

MAX-ACCESS read-only

STATUS deprecated

DESCRIPTION

"This object represents the direction of sessions for which this bind is applicable and the entity (source or destination) within the sessions that is subject to translation with the BIND.

Orientation of the bind can be a superset of the translationEntity of the address map entry that forms the basis for this bind.

For example, if the translationEntity of an address map entry is outboundSrcEndPoint, the translationEntity of a bind derived from this map entry may either be outboundSrcEndPoint or may be bidirectional (a bitmask of outboundSrcEndPoint and inboundDstEndPoint)."

::= { natAddrPortBindEntry 9 }

natAddrPortBindType OBJECT-TYPE

SYNTAX NatAssociationType

MAX-ACCESS read-only

STATUS deprecated

DESCRIPTION

"This object indicates whether the bind is static or dynamic."

::= { natAddrPortBindEntry 10 }

natAddrPortBindMapIndex OBJECT-TYPE

SYNTAX NatAddrMapId

MAX-ACCESS read-only  
STATUS deprecated  
DESCRIPTION

"This object is a pointer to the natAddrMapTable entry (and the parameters of that entry) used in creating this BIND. This object, in conjunction with the ifIndex (which identifies a unique addrMapName), points to a unique entry in the natAddrMapTable."

::= { natAddrPortBindEntry 11 }

natAddrPortBindSessions OBJECT-TYPE

SYNTAX Gauge32

Perreault, et al.

Expires April 22, 2015

[Page 32]

---

Internet-Draft

Deprecation of NAT MIB v1

October 2014

MAX-ACCESS read-only  
STATUS deprecated  
DESCRIPTION

"Number of sessions currently using this BIND."

::= { natAddrPortBindEntry 12 }

natAddrPortBindMaxIdleTime OBJECT-TYPE

SYNTAX TimeTicks  
MAX-ACCESS read-only  
STATUS deprecated

DESCRIPTION

"This object indicates the maximum time for which this bind can be idle without any sessions attached to it.

The value of this object is of relevance only for dynamic NAT."

::= { natAddrPortBindEntry 13 }

natAddrPortBindCurrentIdleTime OBJECT-TYPE

SYNTAX TimeTicks  
MAX-ACCESS read-only  
STATUS deprecated  
DESCRIPTION

"At any given instance, this object indicates the time that this bind has been idle without any sessions attached to it.

The value of this object is of relevance

```
        only for dynamic NAT."
 ::= { natAddrPortBindEntry 14 }
```

natAddrPortBindInTranslates OBJECT-TYPE

SYNTAX Counter64

MAX-ACCESS read-only

STATUS deprecated

DESCRIPTION

"The number of inbound packets that were translated as per this bind entry.

Discontinuities in the value of this counter can occur at reinitialization of the management system and at other times, as indicated by the value of ifCounterDiscontinuityTime on the relevant interface."

```
 ::= { natAddrPortBindEntry 15 }
```

natAddrPortBindOutTranslates OBJECT-TYPE

SYNTAX Counter64

MAX-ACCESS read-only

STATUS deprecated

DESCRIPTION

"The number of outbound packets that were translated as per this bind entry.

Discontinuities in the value of this counter can occur at reinitialization of the management system and at other times, as indicated by the value of ifCounterDiscontinuityTime on the relevant interface."

```
 ::= { natAddrPortBindEntry 16 }
```

--

-- The Session Table

--

natSessionTable OBJECT-TYPE

SYNTAX SEQUENCE OF NatSessionEntry

MAX-ACCESS not-accessible

STATUS deprecated

DESCRIPTION

"The (conceptual) table containing one entry for each

NAT session currently active on this NAT device."  
 ::= { natMIBObjects 9 }

natSessionEntry OBJECT-TYPE

SYNTAX NatSessionEntry

MAX-ACCESS not-accessible

STATUS deprecated

DESCRIPTION

"An entry (conceptual row) containing information  
about an active NAT session on this NAT device.  
These entries are lost upon agent restart."

INDEX { ifIndex, natSessionIndex }

::= { natSessionTable 1 }

NatSessionEntry ::= SEQUENCE {

natSessionIndex	NatSessionId,
natSessionPrivateSrcEPBindId	NatBindIdOrZero,
natSessionPrivateSrcEPBindMode	NatBindMode,
natSessionPrivateDstEPBindId	NatBindIdOrZero,
natSessionPrivateDstEPBindMode	NatBindMode,
natSessionDirection	INTEGER,
natSessionUpTime	TimeTicks,
natSessionAddrMapIndex	NatAddrMapId,
natSessionProtocolType	NatProtocolType,
natSessionPrivateAddrType	InetAddressType,
natSessionPrivateSrcAddr	InetAddress,

natSessionPrivateSrcPort	InetPortNumber,
natSessionPrivateDstAddr	InetAddress,
natSessionPrivateDstPort	InetPortNumber,
natSessionPublicAddrType	InetAddressType,
natSessionPublicSrcAddr	InetAddress,
natSessionPublicSrcPort	InetPortNumber,
natSessionPublicDstAddr	InetAddress,
natSessionPublicDstPort	InetPortNumber,
natSessionMaxIdleTime	TimeTicks,
natSessionCurrentIdleTime	TimeTicks,
natSessionInTranslates	Counter64,
natSessionOutTranslates	Counter64

}

natSessionIndex OBJECT-TYPE

SYNTAX        NatSessionId  
 MAX-ACCESS not-accessible  
 STATUS        deprecated  
 DESCRIPTION  
               "The session ID for this NAT session."  
 ::= { natSessionEntry 1 }

natSessionPrivateSrcEPBindId OBJECT-TYPE  
 SYNTAX        NatBindIdOrZero  
 MAX-ACCESS read-only  
 STATUS        deprecated  
 DESCRIPTION  
               "The bind id associated between private and public  
                   source end points. In the case of Symmetric-NAT,  
                   this should be set to zero."  
 ::= { natSessionEntry 2 }

natSessionPrivateSrcEPBindMode OBJECT-TYPE  
 SYNTAX        NatBindMode  
 MAX-ACCESS read-only  
 STATUS        deprecated  
 DESCRIPTION  
               "This object indicates whether the bind indicated  
                   by the object natSessionPrivateSrcEPBindId  
                   is an address bind or an address port bind."  
 ::= { natSessionEntry 3 }

natSessionPrivateDstEPBindId OBJECT-TYPE  
 SYNTAX        NatBindIdOrZero  
 MAX-ACCESS read-only  
 STATUS        deprecated  
 DESCRIPTION  
               "The bind id associated between private and public

                  destination end points."  
 ::= { natSessionEntry 4 }

natSessionPrivateDstEPBindMode OBJECT-TYPE  
 SYNTAX        NatBindMode  
 MAX-ACCESS read-only  
 STATUS        deprecated  
 DESCRIPTION



"This object indicates whether the bind indicated  
by the object natSessionPrivateDstEPBindId  
is an address bind or an address port bind."  
::= { natSessionEntry 5 }

natSessionDirection OBJECT-TYPE

SYNTAX INTEGER {  
inbound (1),  
outbound (2)  
}

MAX-ACCESS read-only

STATUS deprecated

DESCRIPTION

"The direction of this session with respect to the  
local network. 'inbound' indicates that this session  
was initiated from the public network into the private  
network. 'outbound' indicates that this session was  
initiated from the private network into the public  
network."

::= { natSessionEntry 6 }

natSessionUpTime OBJECT-TYPE

SYNTAX TimeTicks

MAX-ACCESS read-only

STATUS deprecated

DESCRIPTION

"The up time of this session in one-hundredths of a  
second."

::= { natSessionEntry 7 }

natSessionAddrMapIndex OBJECT-TYPE

SYNTAX NatAddrMapId

MAX-ACCESS read-only

STATUS deprecated

DESCRIPTION

"This object is a pointer to the natAddrMapTable entry  
(and the parameters of that entry) used in  
creating this session. This object, in conjunction with  
the ifIndex (which identifies a unique addrMapName),

```

::= { natSessionEntry 8 }

natSessionProtocolType OBJECT-TYPE
    SYNTAX      NatProtocolType
    MAX-ACCESS  read-only
    STATUS      deprecated
    DESCRIPTION
        "The protocol type of this session."
    ::= { natSessionEntry 9 }

natSessionPrivateAddrType OBJECT-TYPE
    SYNTAX      InetAddressType
    MAX-ACCESS  read-only
    STATUS      deprecated
    DESCRIPTION
        "This object specifies the address type used for
         natSessionPrivateSrcAddr and natSessionPrivateDstAddr."
    ::= { natSessionEntry 10 }

natSessionPrivateSrcAddr OBJECT-TYPE
    SYNTAX      InetAddress
    MAX-ACCESS  read-only
    STATUS      deprecated
    DESCRIPTION
        "The source IP address of the session endpoint that
         lies in the private network.

        The value of this object must be zero only when the
        natSessionPrivateSrcEPBindId object has a zero value.
        When the value of this object is zero, the NAT session
        lookup will match any IP address to this field.

        The type of this address is determined by the value of
        the natSessionPrivateAddrType object."
    ::= { natSessionEntry 11 }

natSessionPrivateSrcPort OBJECT-TYPE
    SYNTAX      InetPortNumber
    MAX-ACCESS  read-only
    STATUS      deprecated
    DESCRIPTION
        "When the value of protocol is TCP or UDP, this object
         represents the source port in the first packet of
         session while in private-realm. On the other hand, when
         the protocol is ICMP, a NAT session is created only for
         query/response type ICMP messages such as ICMP echo,
         Timestamp, and Information request messages, and this

```

object represents the private-realm specific identifier in the ICMP message, as defined in [RFC 792](#) for ICMPv4 and in [RFC 2463](#) for ICMPv6.

The value of this object must be zero when the natSessionPrivateSrcEPBindId object has zero value and value of natSessionPrivateSrcEPBindMode is addressPortBind(2). In such a case, the NAT session lookup will match any port number to this field.

The value of this object must be zero when the object is not a representative field (SrcPort, DstPort, or ICMP identifier) of the session tuple in either the public realm or the private realm."

::= { natSessionEntry 12 }

natSessionPrivateDstAddr OBJECT-TYPE

SYNTAX InetAddress

MAX-ACCESS read-only

STATUS deprecated

DESCRIPTION

"The destination IP address of the session endpoint that lies in the private network.

The value of this object must be zero when the natSessionPrivateDstEPBindId object has a zero value. In such a scenario, the NAT session lookup will match any IP address to this field.

The type of this address is determined by the value of the natSessionPrivateAddrType object."

::= { natSessionEntry 13 }

natSessionPrivateDstPort OBJECT-TYPE

SYNTAX InetPortNumber

MAX-ACCESS read-only

STATUS deprecated

DESCRIPTION

"When the value of protocol is TCP or UDP, this object represents the destination port in the first packet of session while in private-realm. On the other hand, when the protocol is ICMP, this object is not relevant and should be set to zero.

The value of this object must be zero when the natSessionPrivateDstEPBindId object has a zero

value and natSessionPrivateDstEPBindMode is set to addressPortBind(2). In such a case, the NAT session

lookup will match any port number to this field.

The value of this object must be zero when the object is not a representative field (SrcPort, DstPort, or ICMP identifier) of the session tuple in either the public realm or the private realm."

::= { natSessionEntry 14 }

natSessionPublicAddrType OBJECT-TYPE

SYNTAX InetAddressType

MAX-ACCESS read-only

STATUS deprecated

DESCRIPTION

"This object specifies the address type used for natSessionPublicSrcAddr and natSessionPublicDstAddr."

::= { natSessionEntry 15 }

natSessionPublicSrcAddr OBJECT-TYPE

SYNTAX InetAddress

MAX-ACCESS read-only

STATUS deprecated

DESCRIPTION

"The source IP address of the session endpoint that lies in the public network.

The value of this object must be zero when the natSessionPrivateSrcEPBindId object has a zero value. In such a scenario, the NAT session lookup will match any IP address to this field.

The type of this address is determined by the value of the natSessionPublicAddrType object."

::= { natSessionEntry 16 }

natSessionPublicSrcPort OBJECT-TYPE

SYNTAX InetPortNumber

MAX-ACCESS read-only

STATUS deprecated

DESCRIPTION

"When the value of protocol is TCP or UDP, this object represents the source port in the first packet of session while in public-realm. On the other hand, when protocol is ICMP, a NAT session is created only for query/response type ICMP messages such as ICMP echo, Timestamp, and Information request messages, and this object represents the public-realm specific identifier in the ICMP message, as defined in [RFC 792](#) for ICMPv4 and in [RFC 2463](#) for ICMPv6.

The value of this object must be zero when the natSessionPrivateSrcEPBindId object has a zero value and natSessionPrivateSrcEPBindMode is set to addressPortBind(2). In such a scenario, the NAT session lookup will match any port number to this field.

The value of this object must be zero when the object is not a representative field (SrcPort, DstPort or ICMP identifier) of the session tuple in either the public realm or the private realm."

::= { natSessionEntry 17 }

natSessionPublicDstAddr OBJECT-TYPE

SYNTAX InetAddress

MAX-ACCESS read-only

STATUS deprecated

DESCRIPTION

"The destination IP address of the session endpoint that lies in the public network.

The value of this object must be non-zero when the natSessionPrivateDstEPBindId object has a non-zero value. If the value of this object and the corresponding natSessionPrivateDstEPBindId object value is zero, then the NAT session lookup will match any IP address to this field.

The type of this address is determined by the value of the natSessionPublicAddrType object."

::= { natSessionEntry 18 }

natSessionPublicDstPort OBJECT-TYPE

SYNTAX InetPortNumber

MAX-ACCESS read-only

STATUS deprecated

DESCRIPTION

"When the value of protocol is TCP or UDP, this object represents the destination port in the first packet of session while in public-realm. On the other hand, when the protocol is ICMP, this object is not relevant for translation and should be zero.

The value of this object must be zero when the natSessionPrivateDstEPBindId object has a zero value and natSessionPrivateDstEPBindMode is addressPortBind(2). In such a scenario, the NAT session lookup will match any port number to this

Perreault, et al.

Expires April 22, 2015

[Page 40]

---

Internet-Draft

Deprecation of NAT MIB v1

October 2014

field.

The value of this object must be zero when the object is not a representative field (SrcPort, DstPort, or ICMP identifier) of the session tuple in either the public realm or the private realm."

::= { natSessionEntry 19 }

natSessionMaxIdleTime OBJECT-TYPE

SYNTAX TimeTicks

MAX-ACCESS read-only

STATUS deprecated

DESCRIPTION

"The max time for which this session can be idle without detecting a packet."

::= { natSessionEntry 20 }

natSessionCurrentIdleTime OBJECT-TYPE

SYNTAX TimeTicks

MAX-ACCESS read-only

STATUS deprecated

DESCRIPTION

"The time since a packet belonging to this session was last detected."

::= { natSessionEntry 21 }

natSessionInTranslates OBJECT-TYPE

SYNTAX Counter64

MAX-ACCESS read-only

STATUS deprecated

DESCRIPTION

"The number of inbound packets that were translated for this session.

Discontinuities in the value of this counter can occur at reinitialization of the management system and at other times, as indicated by the value of ifCounterDiscontinuityTime on the relevant interface."

::= { natSessionEntry 22 }

natSessionOutTranslates OBJECT-TYPE

SYNTAX Counter64

MAX-ACCESS read-only

STATUS deprecated

DESCRIPTION

"The number of outbound packets that were translated for this session.

Discontinuities in the value of this counter can occur at reinitialization of the management system and at other times, as indicated by the value of ifCounterDiscontinuityTime on the relevant interface."

::= { natSessionEntry 23 }

--

-- The Protocol table

--

natProtocolTable OBJECT-TYPE

SYNTAX SEQUENCE OF NatProtocolEntry

MAX-ACCESS not-accessible

STATUS deprecated

DESCRIPTION

"The (conceptual) table containing per protocol NAT statistics."

::= { natMIBObjects 10 }

```

natProtocolEntry OBJECT-TYPE
    SYNTAX      NatProtocolEntry
    MAX-ACCESS  not-accessible
    STATUS      deprecated
    DESCRIPTION
        "An entry (conceptual row) containing NAT statistics
        pertaining to a particular protocol."
    INDEX       { natProtocol }
    ::= { natProtocolTable 1 }

```

```

NatProtocolEntry ::= SEQUENCE {
    natProtocol          NatProtocolType,
    natProtocolInTranslates Counter64,
    natProtocolOutTranslates Counter64,
    natProtocolDiscards Counter64
}

```

```

natProtocol OBJECT-TYPE
    SYNTAX      NatProtocolType
    MAX-ACCESS  not-accessible
    STATUS      deprecated
    DESCRIPTION
        "This object represents the protocol pertaining to which
        parameters are reported."
    ::= { natProtocolEntry 1 }

```

```

natProtocolInTranslates OBJECT-TYPE
    SYNTAX      Counter64
    MAX-ACCESS  read-only

```

```

STATUS      deprecated
DESCRIPTION
    "The number of inbound packets pertaining to the protocol
    identified by natProtocol that underwent NAT.

    Discontinuities in the value of this counter can occur
    at reinitialization of the management system and at
    other times, as indicated by the value of
    ifCounterDiscontinuityTime on the relevant interface."
    ::= { natProtocolEntry 2 }

```



natProtocolOutTranslates OBJECT-TYPE

SYNTAX Counter64

MAX-ACCESS read-only

STATUS deprecated

DESCRIPTION

"The number of outbound packets pertaining to the protocol identified by natProtocol that underwent NAT.

Discontinuities in the value of this counter can occur at reinitialization of the management system and at other times, as indicated by the value of ifCounterDiscontinuityTime on the relevant interface."

::= { natProtocolEntry 3 }

natProtocolDiscards OBJECT-TYPE

SYNTAX Counter64

MAX-ACCESS read-only

STATUS deprecated

DESCRIPTION

"The number of packets pertaining to the protocol identified by natProtocol that had to be rejected/dropped due to lack of resources. These rejections could be due to session timeout, resource unavailability, lack of address space, etc.

Discontinuities in the value of this counter can occur at reinitialization of the management system and at other times, as indicated by the value of ifCounterDiscontinuityTime on the relevant interface."

::= { natProtocolEntry 4 }

--

-- Notifications section

--

natMIBNotifications OBJECT IDENTIFIER ::= { natMIB 0 }

--

-- Notifications

--

```

natPacketDiscard NOTIFICATION-TYPE
  OBJECTS { ifIndex }
  STATUS deprecated
  DESCRIPTION
    "This notification is generated when IP packets are
    discarded by the NAT function; e.g., due to lack of
    mapping space when NAT is out of addresses or ports.

    Note that the generation of natPacketDiscard
    notifications is throttled by the agent, as specified
    by the 'natNotifThrottlingInterval' object."
  ::= { natMIBNotifications 1 }

```

```

--
-- Conformance information.
--

```

```

natMIBConformance OBJECT IDENTIFIER ::= { natMIB 2 }

```

```

natMIBGroups          OBJECT IDENTIFIER ::= { natMIBConformance 1 }
natMIBCompliances OBJECT IDENTIFIER ::= { natMIBConformance 2 }

```

```

--
-- Units of conformance
--

```

```

natConfigGroup OBJECT-GROUP
  OBJECTS { natInterfaceRealm,
    natInterfaceServiceType,
    natInterfaceStorageType,
    natInterfaceRowStatus,
    natAddrMapName,
    natAddrMapEntryType,
    natAddrMapTranslationEntity,
    natAddrMapLocalAddrType,
    natAddrMapLocalAddrFrom,
    natAddrMapLocalAddrTo,
    natAddrMapLocalPortFrom,
    natAddrMapLocalPortTo,
    natAddrMapGlobalAddrType,
    natAddrMapGlobalAddrFrom,
    natAddrMapGlobalAddrTo,
  }

```

```
        natAddrMapGlobalPortFrom,
        natAddrMapGlobalPortTo,
        natAddrMapProtocol,
        natAddrMapStorageType,
        natAddrMapRowStatus,
        natBindDefIdleTimeout,
        natUdpDefIdleTimeout,
        natIcmpDefIdleTimeout,
        natOtherDefIdleTimeout,
        natTcpDefIdleTimeout,
        natTcpDefNegTimeout,
        natNotifThrottlingInterval }
STATUS deprecated
DESCRIPTION
    "A collection of configuration-related information
    required to support management of devices supporting
    NAT."
 ::= { natMIBGroups 1 }

natTranslationGroup OBJECT-GROUP
    OBJECTS { natAddrBindNumberOfEntries,
        natAddrBindGlobalAddrType,
        natAddrBindGlobalAddr,
        natAddrBindId,
        natAddrBindTranslationEntity,
        natAddrBindType,
        natAddrBindMapIndex,
        natAddrBindSessions,
        natAddrBindMaxIdleTime,
        natAddrBindCurrentIdleTime,
        natAddrBindInTranslates,
        natAddrBindOutTranslates,
        natAddrPortBindNumberOfEntries,
        natAddrPortBindGlobalAddrType,
        natAddrPortBindGlobalAddr,
        natAddrPortBindGlobalPort,
        natAddrPortBindId,
        natAddrPortBindTranslationEntity,
        natAddrPortBindType,
        natAddrPortBindMapIndex,
        natAddrPortBindSessions,
        natAddrPortBindMaxIdleTime,
        natAddrPortBindCurrentIdleTime,
        natAddrPortBindInTranslates,
        natAddrPortBindOutTranslates,
        natSessionPrivateSrcEPBindId,
        natSessionPrivateSrcEPBindMode,
```

natSessionPrivateDstEPBindId,

Internet-Draft

Deprecation of NAT MIB v1

October 2014

```
natSessionPrivateDstEPBindMode,
natSessionDirection,
natSessionUpTime,
natSessionAddrMapIndex,
natSessionProtocolType,
natSessionPrivateAddrType,
natSessionPrivateSrcAddr,
natSessionPrivateSrcPort,
natSessionPrivateDstAddr,
natSessionPrivateDstPort,
natSessionPublicAddrType,
natSessionPublicSrcAddr,
natSessionPublicSrcPort,
natSessionPublicDstAddr,
natSessionPublicDstPort,
natSessionMaxIdleTime,
natSessionCurrentIdleTime,
natSessionInTranslates,
natSessionOutTranslates }
```

STATUS deprecated

DESCRIPTION

"A collection of BIND-related objects required to support management of devices supporting NAT."

::= { natMIBGroups 2 }

natStatsInterfaceGroup OBJECT-GROUP

```
OBJECTS { natInterfaceInTranslates,
          natInterfaceOutTranslates,
          natInterfaceDiscards }
```

STATUS deprecated

DESCRIPTION

"A collection of NAT statistics associated with the interface on which NAT is configured, to aid troubleshooting/monitoring of the NAT operation."

::= { natMIBGroups 3 }

natStatsProtocolGroup OBJECT-GROUP

```
OBJECTS { natProtocolInTranslates,
          natProtocolOutTranslates,
```

```

        natProtocolDiscards }
STATUS deprecated
DESCRIPTION
    "A collection of protocol specific NAT statistics,
    to aid troubleshooting/monitoring of NAT operation."
::= { natMIBGroups 4 }

```

natStatsAddrMapGroup OBJECT-GROUP

Perreault, et al.

Expires April 22, 2015

[Page 46]

Internet-Draft

Deprecation of NAT MIB v1

October 2014

```

OBJECTS { natAddrMapInTranslates,
          natAddrMapOutTranslates,
          natAddrMapDiscards,
          natAddrMapAddrUsed }
STATUS deprecated
DESCRIPTION
    "A collection of address map specific NAT statistics,
    to aid troubleshooting/monitoring of NAT operation."
::= { natMIBGroups 5 }

```

natMIBNotificationGroup NOTIFICATION-GROUP

```

NOTIFICATIONS { natPacketDiscard }
STATUS deprecated
DESCRIPTION
    "A collection of notifications generated by
    devices supporting this MIB."
::= { natMIBGroups 6 }

```

```

--
-- Compliance statements
--

```

natMIBFullCompliance MODULE-COMPLIANCE

```

STATUS deprecated
DESCRIPTION
    "When this MIB is implemented with support for
    read-create, then such an implementation can claim
    full compliance. Such devices can then be both
    monitored and configured with this MIB.

```

The following index objects cannot be added as OBJECT clauses but nevertheless have the compliance

requirements:

```
"
-- OBJECT  natAddrBindLocalAddrType
-- SYNTAX  InetAddressType { ipv4(1), ipv6(2) }
-- DESCRIPTION
--          "An implementation is required to support
--          global IPv4 and/or IPv6 addresses, depending
--          on its support for IPv4 and IPv6."

-- OBJECT  natAddrBindLocalAddr
-- SYNTAX  InetAddress (SIZE(4|16))
-- DESCRIPTION
--          "An implementation is required to support
--          global IPv4 and/or IPv6 addresses, depending
--          on its support for IPv4 and IPv6."
```

Perreault, et al.

Expires April 22, 2015

[Page 47]

---

Internet-Draft

Deprecation of NAT MIB v1

October 2014

```
-- OBJECT  natAddrPortBindLocalAddrType
-- SYNTAX  InetAddressType { ipv4(1), ipv6(2) }
-- DESCRIPTION
--          "An implementation is required to support
--          global IPv4 and/or IPv6 addresses, depending
--          on its support for IPv4 and IPv6."

-- OBJECT  natAddrPortBindLocalAddr
-- SYNTAX  InetAddress (SIZE(4|16))
-- DESCRIPTION
--          "An implementation is required to support
--          global IPv4 and/or IPv6 addresses, depending
--          on its support for IPv4 and IPv6."
```

MODULE IF-MIB -- The interfaces MIB, [RFC2863](#)

```
MANDATORY-GROUPS {
    ifCounterDiscontinuityGroup
}
```

MODULE -- this module

```
MANDATORY-GROUPS { natConfigGroup, natTranslationGroup,
                    natStatsInterfaceGroup }
```

GROUP natStatsProtocolGroup

DESCRIPTION

"This group is optional."

GROUP natStatsAddrMapGroup  
DESCRIPTION  
"This group is optional."  
GROUP natMIBNotificationGroup  
DESCRIPTION  
"This group is optional."

OBJECT natAddrMapLocalAddrType  
SYNTAX InetAddressType { ipv4(1), ipv6(2) }  
DESCRIPTION  
"An implementation is required to support global IPv4 and/or IPv6 addresses, depending on its support for IPv4 and IPv6."

OBJECT natAddrMapLocalAddrFrom  
SYNTAX InetAddress (SIZE(4|16))  
DESCRIPTION  
"An implementation is required to support global IPv4 and/or IPv6 addresses, depending on its support for IPv4 and IPv6."

OBJECT natAddrMapLocalAddrTo

SYNTAX InetAddress (SIZE(4|16))  
DESCRIPTION  
"An implementation is required to support global IPv4 and/or IPv6 addresses, depending on its support for IPv4 and IPv6."

OBJECT natAddrMapGlobalAddrType  
SYNTAX InetAddressType { ipv4(1), ipv6(2) }  
DESCRIPTION  
"An implementation is required to support global IPv4 and/or IPv6 addresses, depending on its support for IPv4 and IPv6."

OBJECT natAddrMapGlobalAddrFrom  
SYNTAX InetAddress (SIZE(4|16))  
DESCRIPTION  
"An implementation is required to support global IPv4 and/or IPv6 addresses, depending on its support for IPv4 and IPv6."

OBJECT natAddrMapGlobalAddrTo  
SYNTAX InetAddress (SIZE(4|16))  
DESCRIPTION  
"An implementation is required to support global IPv4 and/or IPv6 addresses, depending on its support for IPv4 and IPv6."

OBJECT natAddrBindGlobalAddrType  
SYNTAX InetAddressType { ipv4(1), ipv6(2) }  
DESCRIPTION  
"An implementation is required to support global IPv4 and/or IPv6 addresses, depending on its support for IPv4 and IPv6."

OBJECT natAddrBindGlobalAddr  
SYNTAX InetAddress (SIZE(4|16))  
DESCRIPTION  
"An implementation is required to support global IPv4 and/or IPv6 addresses, depending on its support for IPv4 and IPv6."

OBJECT natAddrPortBindGlobalAddrType  
SYNTAX InetAddressType { ipv4(1), ipv6(2) }  
DESCRIPTION  
"An implementation is required to support global IPv4 and/or IPv6 addresses, depending on its support for IPv4 and IPv6."

OBJECT natAddrPortBindGlobalAddr  
SYNTAX InetAddress (SIZE(4|16))  
DESCRIPTION  
"An implementation is required to support global IPv4 and/or IPv6 addresses, depending on its support for IPv4 and IPv6."

OBJECT natSessionPrivateAddrType  
SYNTAX InetAddressType { ipv4(1), ipv6(2) }  
DESCRIPTION  
"An implementation is required to support global IPv4 and/or IPv6 addresses, depending on its support



for IPv4 and IPv6."

OBJECT natSessionPrivateSrcAddr

SYNTAX InetAddress (SIZE(4|16))

DESCRIPTION

"An implementation is required to support global IPv4 and/or IPv6 addresses, depending on its support for IPv4 and IPv6."

OBJECT natSessionPrivateDstAddr

SYNTAX InetAddress (SIZE(4|16))

DESCRIPTION

"An implementation is required to support global IPv4 and/or IPv6 addresses, depending on its support for IPv4 and IPv6."

OBJECT natSessionPublicAddrType

SYNTAX InetAddressType { ipv4(1), ipv6(2) }

DESCRIPTION

"An implementation is required to support global IPv4 and/or IPv6 addresses, depending on its support for IPv4 and IPv6."

OBJECT natSessionPublicSrcAddr

SYNTAX InetAddress (SIZE(4|16))

DESCRIPTION

"An implementation is required to support global IPv4 and/or IPv6 addresses, depending on its support for IPv4 and IPv6."

OBJECT natSessionPublicDstAddr

SYNTAX InetAddress (SIZE(4|16))

DESCRIPTION

"An implementation is required to support global IPv4 and/or IPv6 addresses, depending on its support

for IPv4 and IPv6."

::= { natMIBCompliances 1 }

natMIBReadOnlyCompliance MODULE-COMPLIANCE

STATUS deprecated

DESCRIPTION

"When this MIB is implemented without support for read-create (i.e., in read-only mode), then such an implementation can claim read-only compliance. Such a device can then be monitored but cannot be configured with this MIB.

The following index objects cannot be added as OBJECT clauses but nevertheless have the compliance requirements:

```
"
-- OBJECT  natAddrBindLocalAddrType
-- SYNTAX  InetAddressType { ipv4(1), ipv6(2) }
-- DESCRIPTION
--      "An implementation is required to support
--      global IPv4 and/or IPv6 addresses, depending
--      on its support for IPv4 and IPv6."

-- OBJECT  natAddrBindLocalAddr
-- SYNTAX  InetAddress (SIZE(4|16))

-- DESCRIPTION
--      "An implementation is required to support
--      global IPv4 and/or IPv6 addresses, depending
--      on its support for IPv4 and IPv6."

-- OBJECT  natAddrPortBindLocalAddrType
-- SYNTAX  InetAddressType { ipv4(1), ipv6(2) }
-- DESCRIPTION
--      "An implementation is required to support
--      global IPv4 and/or IPv6 addresses, depending
--      on its support for IPv4 and IPv6."
-- OBJECT  natAddrPortBindLocalAddr
-- SYNTAX  InetAddress (SIZE(4|16))
-- DESCRIPTION
--      "An implementation is required to support
--      global IPv4 and/or IPv6 addresses, depending
--      on its support for IPv4 and IPv6."
```

MODULE IF-MIB -- The interfaces MIB, [RFC2863](#)

```
MANDATORY-GROUPS {
    ifCounterDiscontinuityGroup
```

}

MODULE -- this module

MANDATORY-GROUPS { natConfigGroup, natTranslationGroup,  
natStatsInterfaceGroup }

GROUP natStatsProtocolGroup

DESCRIPTION

"This group is optional."

GROUP natStatsAddrMapGroup

DESCRIPTION

"This group is optional."

GROUP natMIBNotificationGroup

DESCRIPTION

"This group is optional."

OBJECT natInterfaceRowStatus

SYNTAX RowStatus { active(1) }

MIN-ACCESS read-only

DESCRIPTION

"Write access is not required, and active is the only  
status that needs to be supported."

OBJECT natAddrMapLocalAddrType

SYNTAX InetAddressType { ipv4(1), ipv6(2) }

MIN-ACCESS read-only

DESCRIPTION

"Write access is not required. An implementation is  
required to support global IPv4 and/or IPv6 addresses,  
depending on its support for IPv4 and IPv6."

OBJECT natAddrMapLocalAddrFrom

SYNTAX InetAddress (SIZE(4|16))

MIN-ACCESS read-only

DESCRIPTION

"Write access is not required. An implementation is  
required to support global IPv4 and/or IPv6 addresses,  
depending on its support for IPv4 and IPv6."

OBJECT natAddrMapLocalAddrTo

SYNTAX InetAddress (SIZE(4|16))

MIN-ACCESS read-only

DESCRIPTION

"Write access is not required. An implementation is  
required to support global IPv4 and/or IPv6 addresses,  
depending on its support for IPv4 and IPv6."

OBJECT natAddrMapGlobalAddrType

SYNTAX InetAddressType { ipv4(1), ipv6(2) }

Internet-Draft

Deprecation of NAT MIB v1

October 2014

MIN-ACCESS read-only

DESCRIPTION

"Write access is not required. An implementation is required to support global IPv4 and/or IPv6 addresses, depending on its support for IPv4 and IPv6."

OBJECT natAddrMapGlobalAddrFrom

SYNTAX InetAddress (SIZE(4|16))

MIN-ACCESS read-only

DESCRIPTION

"Write access is not required. An implementation is required to support global IPv4 and/or IPv6 addresses, depending on its support for IPv4 and IPv6."

OBJECT natAddrMapGlobalAddrTo

SYNTAX InetAddress (SIZE(4|16))

MIN-ACCESS read-only

DESCRIPTION

"Write access is not required. An implementation is required to support global IPv4 and/or IPv6 addresses, depending on its support for IPv4 and IPv6."

OBJECT natAddrMapRowStatus

SYNTAX RowStatus { active(1) }

MIN-ACCESS read-only

DESCRIPTION

"Write access is not required, and active is the only status that needs to be supported."

OBJECT natAddrBindGlobalAddrType

SYNTAX InetAddressType { ipv4(1), ipv6(2) }

DESCRIPTION

"An implementation is required to support global IPv4 and/or IPv6 addresses, depending on its support for IPv4 and IPv6."

OBJECT natAddrBindGlobalAddr

SYNTAX InetAddress (SIZE(4|16))

DESCRIPTION

"An implementation is required to support global IPv4 and/or IPv6 addresses, depending on its support for IPv4 and IPv6."

OBJECT natAddrPortBindGlobalAddrType  
SYNTAX InetAddressType { ipv4(1), ipv6(2) }  
DESCRIPTION  
"An implementation is required to support global IPv4  
and/or IPv6 addresses, depending on its support for

IPv4 and IPv6."

OBJECT natAddrPortBindGlobalAddr  
SYNTAX InetAddress (SIZE(4|16))  
DESCRIPTION  
"An implementation is required to support global IPv4  
and/or IPv6 addresses, depending on its support for  
IPv4 and IPv6."

OBJECT natSessionPrivateAddrType  
SYNTAX InetAddressType { ipv4(1), ipv6(2) }  
DESCRIPTION  
"An implementation is required to support global IPv4  
and/or IPv6 addresses, depending on its support for  
IPv4 and IPv6."

OBJECT natSessionPrivateSrcAddr  
SYNTAX InetAddress (SIZE(4|16))  
DESCRIPTION  
"An implementation is required to support global IPv4  
and/or IPv6 addresses, depending on its support for  
IPv4 and IPv6."

OBJECT natSessionPrivateDstAddr  
SYNTAX InetAddress (SIZE(4|16))  
DESCRIPTION  
"An implementation is required to support global IPv4  
and/or IPv6 addresses, depending on its support for  
IPv4 and IPv6."

OBJECT natSessionPublicAddrType  
SYNTAX InetAddressType { ipv4(1), ipv6(2) }  
DESCRIPTION  
"An implementation is required to support global IPv4  
and/or IPv6 addresses, depending on its support for

IPv4 and IPv6."

OBJECT natSessionPublicSrcAddr

SYNTAX InetAddress (SIZE(4|16))

DESCRIPTION

"An implementation is required to support global IPv4 and/or IPv6 addresses, depending on its support for IPv4 and IPv6."

OBJECT natSessionPublicDstAddr

SYNTAX InetAddress (SIZE(4|16))

DESCRIPTION

"An implementation is required to support global IPv4

Perreault, et al.

Expires April 22, 2015

[Page 54]

---

Internet-Draft

Deprecation of NAT MIB v1

October 2014

and/or IPv6 addresses, depending on its support for IPv4 and IPv6."

::= { natMIBCompliances 2 }

END

## [5.](#) Security Considerations

The threats that need to be addressed are described in [Section 1.4 of \[RFC3411\]](#). They include modification of information, masquerade, message stream modification and disclosure. No protection is needed against denial of service and traffic analysis.

There are a number of management objects defined in this MIB module with a MAX-ACCESS clause of read-write and/or read-create. Such objects may be considered sensitive or vulnerable in some network environments. The support for SET operations in a non-secure environment without proper protection can have a negative effect on network operations. These are the tables and objects and their sensitivity/vulnerability:

Timers: An attacker setting very low timer values can easily cause a denial-of-service situation. NAT-MIB has the following read-write timers:

- \* natBindDefIdleTimeout

- \* natUdpDefIdleTimeout
- \* natIcmpDefIdleTimeout
- \* natOtherDefIdleTimeout
- \* natTcpDefIdleTimeout
- \* natTcpDefNegTimeout

Notification throttling: An attacker setting a very low throttling interval can cause many useless notifications to be generated. Disabling notifications could be used to hide another attack. Notification throttling is controlled by the object natNotifThrottlingInterval.

Other configuration: The following tables provide write access, at least in part:

- \* Rows of the natInterfaceTable are read-create, and the columnar objects indicating realm and service type are read-write. An attacker could deny service by modifying interface configuration, for instance by changing the realm from public to private where the interface is actually on the public side of the NAT.
- \* Similarly (to support static mapping), rows of the natAddrMapTable are read-create and thus potentially modifiable by an attacker.

Some of the readable objects in this MIB module (i.e., objects with a MAX-ACCESS other than not-accessible) may be considered sensitive or vulnerable in some network environments. It is thus important to control even GET and/or NOTIFY access to these objects and possibly to even encrypt the values of these objects when sending them over the network via SNMP. These are the tables and objects and their sensitivity/vulnerability:

Objects that reveal host identities: Various objects can reveal the identity of private hosts that are engaged in a session with

external end nodes. A curious outsider could monitor these to assess the number of private hosts being supported by the NAT device. The outsider could use the information to break into specific private hosts by intercepting the existing sessions or originating new sessions into the host. This applies to the address and port related objects within the following tables:

- \* natAddrMapTable
- \* natAddrBindTable
- \* natAddrPortBindTable
- \* natSessionTable

Other objects that reveal NAT state: Other managed objects in this MIB may contain information that may be sensitive from a business perspective, in that they may represent NAT state information. This applies to the following counters:

- \* natAddrBindNumberOfEntries
- \* natAddrPortBindNumberOfEntries
- \* natInterfaceTable: natInterfaceInTranslates, natInterfaceOutTranslates, and natInterfaceDiscards

- \* natAddrMapTable: natAddrMapInTranslates, natAddrMapOutTranslates, natAddrMapDiscards, and natAddrMapAddrUsed
- \* natAddrBindTable: natAddrBindSessions, natAddrBindInTranslates, natAddrBindOutTranslates
- \* natAddrPortBindTable: natAddrPortBindSessions, natAddrPortBindInTranslates, natAddrPortBindOutTranslates
- \* natSessionTable: natSessionInTranslates, natSessionOutTranslates
- \* natProtocolTable: natProtocolInTranslates,



natProtocolOutTranslates, natProtocolDiscards

There are no objects that are sensitive in their own right, such as passwords or monetary amounts.

SNMP versions prior to SNMPv3 did not include adequate security. Even if the network itself is secure (for example by using IPsec), there is no control as to who on the secure network is allowed to access and GET/SET (read/change/create/delete) the objects in this MIB module.

Implementations SHOULD provide the security features described by the SNMPv3 framework (see [RFC3410]), and implementations claiming compliance to the SNMPv3 standard MUST include full support for authentication and privacy via the User-based Security Model (USM) [RFC3414] with the AES cipher algorithm [RFC3826]. Implementations MAY also provide support for the Transport Security Model (TSM) [RFC5591] in combination with a secure transport such as SSH [RFC5592] or TLS/DTLS [RFC6353].

Further, deployment of SNMP versions prior to SNMPv3 is NOT RECOMMENDED. Instead, it is RECOMMENDED to deploy SNMPv3 and to enable cryptographic security. It is then a customer/operator responsibility to ensure that the SNMP entity giving access to an instance of this MIB module is properly configured to give access to the objects only to those principals (users) that have legitimate rights to indeed GET or SET (change/create/delete) them.

## 6. IANA Considerations

IANA has assigned object identifier 123 to the natMIB module, with prefix iso.org.dod.internet.mgmt.mib-2 in the Network Management Parameters registry [[SMI-NUMBERS](#)].

Perreault, et al. Expires April 22, 2015 [Page 57]

---

Internet-Draft Deprecation of NAT MIB v1 October 2014

No IANA actions are required by this document.

## 7. References

### 7.1. Normative References

[RFC2119] Bradner, S., "Key words for use in RFCs to Indicate

Requirement Levels", [BCP 14](#), [RFC 2119](#), March 1997.

- [RFC2578] McCloghrie, K., Ed., Perkins, D., Ed., and J. Schoenwaelder, Ed., "Structure of Management Information Version 2 (SMIv2)", STD 58, [RFC 2578](#), April 1999.
- [RFC2579] McCloghrie, K., Ed., Perkins, D., Ed., and J. Schoenwaelder, Ed., "Textual Conventions for SMIv2", STD 58, [RFC 2579](#), April 1999.
- [RFC2580] McCloghrie, K., Perkins, D., and J. Schoenwaelder, "Conformance Statements for SMIv2", STD 58, [RFC 2580](#), April 1999.
- [RFC3411] Harrington, D., Presuhn, R., and B. Wijnen, "An Architecture for Describing Simple Network Management Protocol (SNMP) Management Frameworks", STD 62, [RFC 3411](#), December 2002.
- [RFC3414] Blumenthal, U. and B. Wijnen, "User-based Security Model (USM) for version 3 of the Simple Network Management Protocol (SNMPv3)", STD 62, [RFC 3414](#), December 2002.
- [RFC3826] Blumenthal, U., Maino, F., and K. McCloghrie, "The Advanced Encryption Standard (AES) Cipher Algorithm in the SNMP User-based Security Model", [RFC 3826](#), June 2004.
- [RFC4001] Daniele, M., Haberman, B., Routhier, S., and J. Schoenwaelder, "Textual Conventions for Internet Network Addresses", [RFC 4001](#), February 2005.
- [RFC4787] Audet, F. and C. Jennings, "Network Address Translation (NAT) Behavioral Requirements for Unicast UDP", [BCP 127](#), [RFC 4787](#), January 2007.
- [RFC5591] Harrington, D. and W. Hardaker, "Transport Security Model for the Simple Network Management Protocol (SNMP)", STD 78, [RFC 5591](#), June 2009.

- [RFC5592] Harrington, D., Salowey, J., and W. Hardaker, "Secure Shell Transport Model for the Simple Network Management Protocol (SNMP)", [RFC 5592](#), June 2009.
- [RFC6353] Hardaker, W., "Transport Layer Security (TLS) Transport Model for the Simple Network Management Protocol (SNMP)", STD 78, [RFC 6353](#), July 2011.

## 7.2. Informative References

- [I-D.ietf-behave-nat-mib-v2]  
Perrault, S., Tsou, T., Sivakumar, S., and T. Taylor,  
"Definitions of Managed Objects for Network Address  
Translators (NAT), Version 2", October 2014.
- [RFC2663] Srisuresh, P. and M. Holdrege, "IP Network Address  
Translator (NAT) Terminology and Considerations", [RFC  
2663](#), August 1999.
- [RFC3022] Srisuresh, P. and K. Egevang, "Traditional IP Network  
Address Translator (Traditional NAT)", [RFC 3022](#), January  
2001.
- [RFC3410] Case, J., Mundy, R., Partain, D., and B. Stewart,  
"Introduction and Applicability Statements for Internet-  
Standard Management Framework", [RFC 3410](#), December 2002.
- [RFC4008] Rohit, R., Srisuresh, P., Raghunarayan, R., Pai, N., and  
C. Wang, "Definitions of Managed Objects for Network  
Address Translators (NAT)", [RFC 4008](#), March 2005.
- [SMI-NUMBERS]  
"Network Management Parameters registry at IANA",  
<<http://www.iana.org/assignments/smi-numbers>>.

## Authors' Addresses

Simon Perreault  
Viagenie  
246 Aberdeen  
Quebec, QC G1R 2E1  
Canada

Phone: +1 418 656 9254  
Email: [simon.perreault@viagenie.ca](mailto:simon.perreault@viagenie.ca)  
URI: <http://viagenie.ca>

Internet-Draft

Deprecation of NAT MIB v1

October 2014

Tina Tsou  
Huawei Technologies (USA)  
2330 Central Expressway  
Santa Clara, CA 95050  
USA

Phone: +1 408 330 4424  
Email: tina.tsou.zouting@huawei.com

Senthil Sivakumar  
Cisco Systems  
7100-8 Kit Creek Road  
Research Triangle Park, North Carolina 27709  
USA

Phone: +1 919 392 5158  
Email: ssenthil@cisco.com

Tom Taylor  
PT Taylor Consulting  
Ottawa  
Canada

Email: tom.taylor.stds@gmail.com

