Workgroup: Network Working Group

Internet-Draft:

draft-peterson-stir-certificates-shortlived-03

Published: 21 April 2022

Intended Status: Standards Track

Expires: 23 October 2022 Authors: J. Peterson

Neustar

Short-Lived Certificates for Secure Telephone Identity

#### Abstract

When certificates are used as credentials to attest the assignment of ownership of telephone numbers, some mechanism is required to provide certificate freshness. This document specifies short-lived certificates as a means of guaranteeing certificate freshness for secure telephone identity (STIR), in particular relying on the Automated Certificate Management Environment (ACME) to allow signers to acquire certificates as needed.

## Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of BCP 78 and BCP 79.

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <a href="https://datatracker.ietf.org/drafts/current/">https://datatracker.ietf.org/drafts/current/</a>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on 23 October 2022.

# Copyright Notice

Copyright (c) 2022 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to BCP 78 and the IETF Trust's Legal Provisions Relating to IETF Documents

(<a href="https://trustee.ietf.org/license-info">https://trustee.ietf.org/license-info</a>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Revised BSD License text as described in

Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Revised BSD License.

### Table of Contents

- 1. Introduction
- 2. Terminology
- Short-lived certificates for STIR
- 4. Certificate Acquisition with ACME
- 5. IANA Considerations
- 6. Privacy Considerations
- 7. Security Considerations
- 8. Acknowledgments
- 9. References
  - 9.1. Normative References
  - 9.2. Informative References

Author's Address

#### 1. Introduction

The STIR problem statement [RFC7340] discusses many attacks on the telephone network that are enabled by impersonation, including various forms of robocalling, voicemail hacking, and swatting. One of the most important components of a system to prevent impersonation is the implementation of credentials which identify the parties who control telephone numbers. The STIR certificates [RFC8226] specification describes a credential system based on [X.509] version 3 certificates in accordance with [RFC5280] for that purpose. Those credentials can then be used by STIR authentication services [RFC8224] to sign PASSporT objects [RFC8225] carried in a SIP [RFC3261] request.

The STIR certificates document specifies an extension to X.509 that defines a Telephony Number (TN) Authorization List that may be included by certificate authorities in certificates. This extension provides additional information that relying parties can use when validating transactions with the certificate: either in the form of Service Provider Codes (SPCs) or telephone numbers. Telephone numbers or number ranges are commonly used in delegate STIR certificates [RFC9060]. When a SIP request, for example, arrives at a terminating administrative domain, the calling number attested by the SIP request can be compared to the TN Authorization List of the delegate certificate that signed the request to determine if the caller is authorized to use that calling number in SIP.

No specific recommendation is made in the STIR certificates document for a means of determining the freshness of certificates with a TN Authorization List. This document explores how short-lived certificates could be used as a means of preserving that freshness. Short-lived certificates also have a number of other desirable properties that fulfill important operational requirements for network operators. The use of the <u>Automated Certificate Management Environment (ACME) [RFC8555]</u> to manage these short-lived certificates is the focus of the architecture specified, in particular adapting the <u>Short-Term Automatically Renewed (STAR) [RFC8739]</u> mechanism to STIR. The interaction of STIR with ACME has already been explored in [<u>I-D.ietf-acme-authority-token-tnauthlist</u>].

# 2. Terminology

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "NOT RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in BCP 14 [RFC2119] [RFC8174] when, and only when, they appear in all capitals, as shown here.

## 3. Short-lived certificates for STIR

While there is no easy definition of what constitutes a "short-lived" certificate, the term typically refers to certificates that are valid only for days or even hours, as opposed to the months or years common in traditional public key infrastructures. When the private keying material associated with that has an expiry of months or years is compromised by an adversary, the issuing authority must revoke the certificate, which requires relying parties to review certificate revocation lists or to access real-time status information with protocols such as OCSP. Short-lived certificates offer an alternative where, if compromised, certificates will shortly expire anyway, and rather than revoking and reissuing the certificate in response to a crisis, certificates routinely roll-over and cannot be cached for a long term by relying parties, minimizing their value to attackers.

One of the additional benefits of using short-lived certificates is that they do not require relying parties to perform any certificate freshness check. The trade-off is that the signer must acquire new certificates frequently, so the cost of round-trip times to the certificate authority is paid on the signer's side rather than the verifier's side; however, in environments where many parties may rely on a single certificate, or at least where a single certificate will be used to sign many transactions during its short lifetime, the overall architecture will incur fewer round-trip times to the certificate authority and thus less processing delay.

In the STIR context, the TN Authorization List defined in [RFC8226] adds a new wrinkle to the behavior of short-lived certificates, especially when it is populated with telephone numbers or number ranges instead of Service Provider Codes (SPCs). A subject may have

authority over multiple telephone numbers, but a particular certificate issued to that subject could attest the authority over all, some, or just one of those telephone numbers. Short-lived certificates permit a more on-demand certification process, where subjects acquire certificates as needed, potentially in reaction to calls being placed. A STIR authentication service could even acquire a new certificate on a per-call basis that can only sign for the calling party number of the call in question. At the other end of the spectrum, a large enterprise service provider could acquire a certificate valid for millions of numbers, but expire the certificate after a very short duration - on the order of hours - to reduce the risk that the certificate would be compromised.

This inherent flexibility in the short-lived certificate architecture would also permit authentication services to implement very narrow policies for certificate usage. A large service provider who wanted to avoid revealing which phone numbers they controlled, for example, could provide no information in the certificate that signs a call other than just the single telephone number that corresponds to the calling party's number. How frequently the service provider feels that they need to expire that certificate and acquire a new one is entirely a matter of policy to them. This makes it much harder for entities monitoring signatures over calls to guess who owns which numbers, and provides a much more complicated threat surface for attackers trying to compromise the service.

In order to reduce the burden on verification services, an authentication service could also piggyback a short-lived certificate onto the signed SIP request, so that no network lookup and consequent round-trip delay would be required on the terminating side to acquire the new certificate. [RFC8224] already provides a way of pointing to a certificate in a MIME body associated with the SIP request. Future work could specify other means of carrying certificates within SIP requests via a header rather than a body, to optimize for intermediaries adding and extracting these certificates.

### 4. Certificate Acquisition with ACME

One of the primary challenges facing short-lived certificates is building an operational system that allows signers to acquire new certificates and put them to immediate use. ACME [RFC8555] is designed for exactly this purpose. After a client registers with an ACME server, and the authority of the client for the names in question is established (through means such as [I-D.ietf-acme-authority-token-tnauthlist]), the client can at any time apply for a certificate to be issued by sending an appropriate JSON request to the server. That request will contain a CSR [RFC2986] indicating the intended scope of authority as well the validity interval of the

certificate in question. Ultimately, this will enable the client to download the certificate from a certificate URL designated by the server.

ACME is based on the concept that clients establish accounts at an ACME server, and that through challenges, the server learns which identifiers it will issue for certificates requested for an account. Any given certificate issued for an account can be for just one of those identifiers, or potentially for more: this is determined by the CSR that an ACME client creates for a particular order. Thus, a service provider with authority for millions of identifiers - that is, millions of telephone numbers - could create a CSR for an ACME order that requests a certificate only associated with one of those telephone numbers if it so desired. The same would be true of certificates based on Service Provider Codes (SPCs) as described in [RFC8226]: a service provider might have just one SPC or perhaps many. ACME thus puts needed flexibility into the hands of the clients requesting certificates to determine how much of their authority they want to invest in any given certificate.

ACME also provides a mechanism that allows the assignee of a number to delegate temporary authority for it to a user. ACME Short-Term Automatically-Renewed (STAR [RFC8739]) certificates provide a property of automatic renewal for ACME orders, one that assumes that certificates issuance is based on a hierarchical delegation. A short-term certificate attesting authority for a particular identifier might be issued for an interval of 72 hours, for example, by the owner of the identifier to a delegate. In the STAR model, the interface used by the owner of the identifier and the delegate is out of the scope of ACME, as it would be for an adaptation of STAR to telephone numbers (likely it would be an interface similar to MODERN [RFC8396]). STAR permits the delegate to acquire new certificates directly from the ACME server at each renewal interval. Because the owner of the identifier in STAR actually fulfills the ACME challenge and retrieves the Order ID for the certificate, the owner may at any time send a certificate termination request to the ACME server, which will prevent the certificate from being renewed by the delegate at the next renewal interval.

[I-D.ietf-acme-authority-token-tnauthlist] uses the ATC framework of [I-D.ietf-acme-authority-token] to generate tokens that are provided to the CA in response to ACME challenges. For a usage with short-term certificates, it may make sense for the ATC tokens to have a relatively long expiry, so that the ACME client does not have to constantly return to the Token Authority for new tokens.

[TBD: More alignment on ACME and STAR in particular]

### 5. IANA Considerations

This document contains no actions for the IANA.

# 6. Privacy Considerations

Short-lived certificates provide attractive privacy properties when compared to real-time status query protocols like OCSP, which require relying parties to perform a network dip that can reveal a great deal about the source and destination of communications. For STIR, these problems are compounded by the presence of the TN Authorization List extension to certificates. Short-lived certificates can minimize the data that needs to appear in the TN Authorization List, and consequently reduce the amount of information about the caller leaked by certificate usage to an amount equal to what is leaked by the call signaling itself.

[More TBD]

## 7. Security Considerations

This document is entirely about security. For further information on certificate security and practices, see [RFC5280], in particular its Security Considerations.

## 8. Acknowledgments

Stephen Farrell provided key input to the discussions leading to this document.

## 9. References

### 9.1. Normative References

- [ATIS-0300251] ATIS Recommendation 0300251, "Codes for Identification of Service Providers for Information Exchange", 2007.
- [DSS] National Institute of Standards and Technology, U.S.
  Department of Commerce | NIST FIPS PUB 186-4, "Digital
  Signature Standard, version 4", 2013.
- [I-D.ietf-acme-authority-token] Peterson, J., Barnes, M., Hancock,
   D., and C. Wendt, "ACME Challenges Using an Authority
   Token", Work in Progress, Internet-Draft, draft-ietf acme-authority-token-07, 25 October 2021, <a href="https://">https://</a>

www.ietf.org/archive/id/draft-ietf-acme-authoritytoken-07.txt>.

- [RFC2818] Rescorla, E., "HTTP Over TLS", RFC 2818, DOI 10.17487/
  RFC2818, May 2000, <a href="https://www.rfc-editor.org/info/rfc2818">https://www.rfc-editor.org/info/rfc2818</a>>.
- [RFC2986] Nystrom, M. and B. Kaliski, "PKCS #10: Certification
  Request Syntax Specification Version 1.7", RFC 2986, DOI
  10.17487/RFC2986, November 2000, <a href="https://www.rfc-editor.org/info/rfc2986">https://www.rfc-editor.org/info/rfc2986</a>.
- [RFC3261]
- Rosenberg, J., Schulzrinne, H., Camarillo, G., Johnston, A., Peterson, J., Sparks, R., Handley, M., and E. Schooler, "SIP: Session Initiation Protocol", RFC 3261, DOI 10.17487/RFC3261, June 2002, <a href="https://www.rfc-editor.org/info/rfc3261">https://www.rfc-editor.org/info/rfc3261</a>.
- [RFC3447] Jonsson, J. and B. Kaliski, "Public-Key Cryptography Standards (PKCS) #1: RSA Cryptography Specifications Version 2.1", RFC 3447, DOI 10.17487/RFC3447, February 2003, <a href="https://www.rfc-editor.org/info/rfc3447">https://www.rfc-editor.org/info/rfc3447</a>.
- [RFC3986] Berners-Lee, T., Fielding, R., and L. Masinter, "Uniform
  Resource Identifier (URI): Generic Syntax", STD 66, RFC
  3986, DOI 10.17487/RFC3986, January 2005, <a href="https://www.rfc-editor.org/info/rfc3986">https://www.rfc-editor.org/info/rfc3986</a>>.
- [RFC4055] Schaad, J., Kaliski, B., and R. Housley, "Additional
   Algorithms and Identifiers for RSA Cryptography for use
   in the Internet X.509 Public Key Infrastructure
   Certificate and Certificate Revocation List (CRL)

- Profile", RFC 4055, DOI 10.17487/RFC4055, June 2005, <a href="https://www.rfc-editor.org/info/rfc4055">https://www.rfc-editor.org/info/rfc4055</a>.
- [RFC5280] Cooper, D., Santesson, S., Farrell, S., Boeyen, S.,
  Housley, R., and W. Polk, "Internet X.509 Public Key
  Infrastructure Certificate and Certificate Revocation
  List (CRL) Profile", RFC 5280, DOI 10.17487/RFC5280, May
  2008, <a href="https://www.rfc-editor.org/info/rfc5280">https://www.rfc-editor.org/info/rfc5280</a>.
- [RFC5912] Hoffman, P. and J. Schaad, "New ASN.1 Modules for the Public Key Infrastructure Using X.509 (PKIX)", RFC 5912, DOI 10.17487/RFC5912, June 2010, <a href="https://www.rfc-editor.org/info/rfc5912">https://www.rfc-editor.org/info/rfc5912</a>.
- [RFC6818] Yee, P., "Updates to the Internet X.509 Public Key
  Infrastructure Certificate and Certificate Revocation
  List (CRL) Profile", RFC 6818, DOI 10.17487/RFC6818,
  January 2013, <a href="https://www.rfc-editor.org/info/rfc6818">https://www.rfc-editor.org/info/rfc6818</a>>.
- [RFC7030] Pritikin, M., Ed., Yee, P., Ed., and D. Harkins, Ed.,
   "Enrollment over Secure Transport", RFC 7030, DOI
   10.17487/RFC7030, October 2013, <a href="https://www.rfc-editor.org/info/rfc7030">https://www.rfc-editor.org/info/rfc7030</a>.
- [RFC7093] Turner, S., Kent, S., and J. Manger, "Additional Methods for Generating Key Identifiers Values", RFC 7093, DOI 10.17487/RFC7093, December 2013, <a href="https://www.rfc-editor.org/info/rfc7093">https://www.rfc-editor.org/info/rfc7093</a>>.

## [RFC7519]

- Jones, M., Bradley, J., and N. Sakimura, "JSON Web Token (JWT)", RFC 7519, DOI 10.17487/RFC7519, May 2015, <a href="https://www.rfc-editor.org/info/rfc7519">https://www.rfc-editor.org/info/rfc7519</a>.
- [RFC8174] Leiba, B., "Ambiguity of Uppercase vs Lowercase in RFC
  2119 Key Words", BCP 14, RFC 8174, DOI 10.17487/RFC8174,
  May 2017, <a href="https://www.rfc-editor.org/info/rfc8174">https://www.rfc-editor.org/info/rfc8174</a>.
- [RFC8224] Peterson, J., Jennings, C., Rescorla, E., and C. Wendt,
   "Authenticated Identity Management in the Session
   Initiation Protocol (SIP)", RFC 8224, DOI 10.17487/
   RFC8224, February 2018, <a href="https://www.rfc-editor.org/info/rfc8224">https://www.rfc-editor.org/info/rfc8224</a>.

- [RFC8739] Sheffer, Y., Lopez, D., Gonzalez de Dios, O., Pastor
  Perales, A., and T. Fossati, "Support for Short-Term,
  Automatically Renewed (STAR) Certificates in the
  Automated Certificate Management Environment (ACME)", RFC
  8739, DOI 10.17487/RFC8739, March 2020, <a href="https://www.rfc-editor.org/info/rfc8739">https://www.rfc-editor.org/info/rfc8739</a>.
- [X.509] ITU-T Recommendation X.509 (10/2012) | ISO/IEC 9594-8,
   "Information technology Open Systems Interconnection The Directory: Public-key and attribute certificate
   frameworks", 2012.

### 9.2. Informative References

- [RFC2046] Freed, N. and N. Borenstein, "Multipurpose Internet Mail
  Extensions (MIME) Part Two: Media Types", RFC 2046, DOI
  10.17487/RFC2046, November 1996, <a href="https://www.rfc-editor.org/info/rfc2046">https://www.rfc-editor.org/info/rfc2046</a>.
- [RFC3647] Chokhani, S., Ford, W., Sabett, R., Merrill, C., and S.
  Wu, "Internet X.509 Public Key Infrastructure Certificate
  Policy and Certification Practices Framework", RFC 3647,
  DOI 10.17487/RFC3647, November 2003, <a href="https://www.rfc-editor.org/info/rfc3647">https://www.rfc-editor.org/info/rfc3647</a>>.
- [RFC5055] Freeman, T., Housley, R., Malpani, A., Cooper, D., and W.
  Polk, "Server-Based Certificate Validation Protocol
  (SCVP)", RFC 5055, DOI 10.17487/RFC5055, December 2007,
  <https://www.rfc-editor.org/info/rfc5055>.
- [RFC6961] Pettersen, Y., "The Transport Layer Security (TLS)
   Multiple Certificate Status Request Extension", RFC 6961,
   DOI 10.17487/RFC6961, June 2013, <a href="https://www.rfc-editor.org/info/rfc6961">https://www.rfc-editor.org/info/rfc6961</a>.
- [RFC7340] Peterson, J., Schulzrinne, H., and H. Tschofenig, "Secure Telephone Identity Problem Statement and Requirements", RFC 7340, DOI 10.17487/RFC7340, September 2014, <a href="https://www.rfc-editor.org/info/rfc7340">https://www.rfc-editor.org/info/rfc7340</a>.

# [X.520]

ITU-T Recommendation X.520 (10/2012)  $\mid$  ISO/IEC 9594-6, "Information technology - Open Systems Interconnection - The Directory: Selected Attribute Types", 2012.

# **Author's Address**

Jon Peterson Neustar, Inc.

Email: jon.peterson@team.neustar