

**Generalized Multi-Protocol Label Switching (GMPLS) Extensions for
Synchronous Optical Network (SONET) and Synchronous Digital Hierarchy
(SDH) Control**

[draft-rabbat-ccamp-rfc3946bis-00](#)

Status of this Memo

By submitting this Internet-Draft, each author represents that any applicable patent or other IPR claims of which he or she is aware have been or will be disclosed, and any of which he or she becomes aware will be disclosed, in accordance with [Section 6 of BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF), its areas, and its working groups. Note that other groups may also distribute working documents as Internet-Drafts.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

The list of current Internet-Drafts can be accessed at
<http://www.ietf.org/ietf/1id-abstracts.txt>.

The list of Internet-Draft Shadow Directories can be accessed at
<http://www.ietf.org/shadow.html>.

This Internet-Draft will expire on February 22, 2006.

Copyright Notice

Copyright (C) The Internet Society (2005).

Source of this document

This document provides minor updates for clarification to [RFC 3946](#). [RFC 3946](#) was originally published in October 2004. It was produced by the CCAMP working of the IETF and was jointly edited by Eric Mannie and Dimitri Papadimitriou. The RFC was based on work by the following list of co-contributors: Stefan Ansorge, Peter Ashwood-Smith, Ayan Banerjee, Lou Berger, Greg Bernstein, Angela Chiu, John Drake, Yanhe Fan, Michele Fontana, Gert Grammel, Juergen Heiles,

Suresh Katukam, Kireeti Kompella, Jonathan P. Lang, Fong Liaw, Zhi-Wei Lin, Ben Mack-Crane, Dimitrios Pendarakis, Mike Raftelis, Bala Rajagopalan, Yakov Rekhter, Debanjan Saha, Vishal Sharma, George Swallow, Z. Bo Tang, Eve Varma, and Yangguang Xu.

Abstract

This document is a companion to the Generalized Multi-Protocol Label Switching (GMPLS) signaling. It defines the Synchronous Optical Network (SONET)/Synchronous Digital Hierarchy (SDH) technology specific information needed when using GMPLS signaling.

Table of Contents

1.	Introduction	3
2.	SONET and SDH Traffic Parameters	3
2.1.	SONET/SDH Traffic Parameters	4
2.2.	RSVP-TE Details	10
2.3.	CR-LDP Details	11
3.	SONET and SDH Labels	12
4.	Acknowledgements	17
5.	Security Considerations	18
6.	IANA Considerations	18
7.	Normative References	18
	Appendix 1 - Signal Type Values Extension for VC-3	19
	Annex 1 - Examples	20
	Editors of RFC 3946	22
	Author's Address	23
	Intellectual Property and Copyright Statements	24

1. Introduction

As described in [\[RFC3945\]](#), Generalized MPLS (GMPLS) extends MPLS from supporting packet (Packet Switching Capable - PSC) interfaces and switching to include support of four new classes of interfaces and switching: Layer-2 Switch Capable (L2SC), Time-Division Multiplex (TDM), Lambda Switch Capable (LSC) and Fiber-Switch Capable (FSC). A functional description of the extensions to MPLS signaling needed to support the new classes of interfaces and switching is provided in [\[RFC3471\]](#). [\[RFC3473\]](#) describes RSVP-TE specific formats and mechanisms needed to support all five classes of interfaces, and CR-LDP extensions can be found in [\[RFC3472\]](#). This document presents details that are specific to Synchronous Optical Network (SONET)/Synchronous Digital Hierarchy (SDH). Per [\[RFC3471\]](#), SONET/SDH specific parameters are carried in the signaling protocol in traffic parameter specific objects.

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [RFC 2119](#) [\[RFC2119\]](#).

Moreover, the reader is assumed to be familiar with the terminology in ANSI [\[T1.105\]](#), ITU-T [\[G.707\]](#) as well as [\[RFC3471\]](#), [\[RFC3472\]](#), and [\[RFC3473\]](#). The following abbreviations are used in this document:

DCC: Data Communications Channel.
LOVC: Lower Order Virtual Container
HOVC: Higher Order Virtual Container
MS: Multiplex Section.
MSOH: Multiplex Section overhead.
POH: Path overhead.
RS: Regenerator Section.
RSOH: Regenerator section overhead.
SDH: Synchronous digital hierarchy.
SOH: Section overhead.
SONET: Synchronous Optical Network.
SPE: Synchronous Payload Envelope.
STM(-N): Synchronous Transport Module (-N) (SDH).
STS(-N): Synchronous Transport Signal-Level N (SONET).
VC-n: Virtual Container-n (SDH).
VTn: Virtual Tributary-n (SONET).

2. SONET and SDH Traffic Parameters

This section defines the GMPLS traffic parameters for SONET/SDH. The protocol specific formats, for the SONET/SDH-specific RSVP-TE objects and CR-LDP TLVs are described in sections [2.2](#) and [2.3](#) respectively.

These traffic parameters specify indeed a base set of capabilities for SONET ANSI [T1.105] and SDH ITU-T [G.707] such as concatenation and transparency. Other documents may further enhance this set of capabilities in the future. For instance, signaling for SDH over PDH ITU-T G.832 or sub-STM-0 ITU-T G.708 interfaces could be defined.

The traffic parameters defined hereafter (see [Section 2.1](#)) MUST be used when the label is encoded as SUKLM as defined in this memo (see [Section 3](#)). They MUST also be used when requesting one of Section/RS or Line/MS overhead transparent STS-1/STM-0, STS-3*N/STM-N (N=1, 4, 16, 64, 256) signals.

The traffic parameters and label encoding defined in [\[RFC3471\]](#), [Section 3.2](#), MUST be used for fully transparent STS-1/STM-0, STS-3*N/STM-N (N=1, 4, 16, 64, 256) signal requests. A fully transparent signal is one for which all overhead is left unmodified by intermediate nodes, i.e., when all defined Transparency (T) bits would be set if the traffic parameters defined in [section 2.1](#) were used.

2.1. SONET/SDH Traffic Parameters

The traffic parameters for SONET/SDH are organized as follows:

0								1								2								3							
0	1	2	3	4	5	6	7	8	9	0	1	2	3	4	5	6	7	8	9	0	1	2	3	4	5	6	7	8	9	0	1
+	-	+	-	+	-	+	-	+	-	+	-	+	-	+	-	+	-	+	-	+	-	+	-	+	-	+	-	+	-	+	-
Signal Type								RCC								NCC															
+	-	+	-	+	-	+	-	+	-	+	-	+	-	+	-	+	-	+	-	+	-	+	-	+	-	+	-	+	-	+	-
								NVC								Multiplier (MT)															
+	-	+	-	+	-	+	-	+	-	+	-	+	-	+	-	+	-	+	-	+	-	+	-	+	-	+	-	+	-	+	-
								Transparency (T)																							
+	-	+	-	+	-	+	-	+	-	+	-	+	-	+	-	+	-	+	-	+	-	+	-	+	-	+	-	+	-	+	-
								Profile (P)																							
+	-	+	-	+	-	+	-	+	-	+	-	+	-	+	-	+	-	+	-	+	-	+	-	+	-	+	-	+	-	+	-

Annex 1 lists examples of SONET and SDH signal coding.

Signal Type (ST): 8 bits

This field indicates the type of Elementary Signal that comprises the requested LSP. Several transforms can be applied successively on the Elementary Signal to build the Final Signal being actually requested for the LSP.

Each transform application is optional and must be ignored if zero, except the Multiplier (MT) that cannot be zero and is ignored if equal to one.

Transforms must be applied strictly in the following order:

- o First, contiguous concatenation (by using the RCC and NCC fields) can be optionally applied on the Elementary Signal, resulting in a contiguously concatenated signal.
- o Second, virtual concatenation (by using the NVC field) can be optionally applied on the Elementary Signal resulting in a virtually concatenated signal.
- o Third, some transparency (by using the Transparency field) can be optionally specified when requesting a frame as signal rather than an SPE or VC based signal.
- o Fourth, a multiplication (by using the Multiplier field) can be optionally applied either directly on the Elementary Signal, or on the contiguously concatenated signal obtained from the first phase, or on the virtually concatenated signal obtained from the second phase, or on these signals combined.

Permitted Signal Type values for SONET/SDH are:

Value	Type (Elementary Signal)
-----	-----
1	VT1.5 SPE / VC-11
2	VT2 SPE / VC-12
3	VT3 SPE
4	VT6 SPE / VC-2
5	STS-1 SPE / VC-3
6	STS-3c SPE / VC-4
7	STS-1 / STM-0 (only when requesting transparency)
8	STS-3 / STM-1 (only when requesting transparency)
9	STS-12 / STM-4 (only when requesting transparency)
10	STS-48 / STM-16 (only when requesting transparency)
11	STS-192 / STM-64 (only when requesting transparency)
12	STS-768 / STM-256 (only when requesting transparency)

A dedicated signal type is assigned to a SONET STS-3c SPE instead of coding it as a contiguous concatenation of three STS-1 SPEs. This is done in order to provide easy interworking between SONET and SDH signaling.

Appendix 1 adds one signal type (optional) to the above values.

Requested Contiguous Concatenation (RCC): 8 bits

This field is used to request the optional SONET/SDH contiguous concatenation of the Elementary Signal.

This field is a vector of flags. Each flag indicates the support of a particular type of contiguous concatenation. Several flags can be set at the same time to indicate a choice.

These flags allow an upstream node to indicate to a downstream node the different types of contiguous concatenation that it supports. However, the downstream node decides which one to use according to its own rules.

A downstream node receiving simultaneously more than one flag chooses a particular type of contiguous concatenation, if any supported, and based on criteria that are out of this document scope. A downstream node that doesn't support any of the concatenation types indicated by the field must refuse the LSP request. In particular, it must refuse the LSP request if it doesn't support contiguous concatenation at all.

When several flags have been set, the upstream node retrieves the (single) type of contiguous concatenation the downstream node has selected by looking at the position indicated by the first label and the number of label(s) as returned by the downstream node (see also [Section 3](#)).

The entire field is set to zero to indicate that no contiguous concatenation is requested at all (default value). A non-zero field indicates that some contiguous concatenation is requested.

The following flag is defined:

Flag 1 (bit 1): Standard contiguous concatenation.

Flag 1 indicates that the standard SONET/SDH contiguous concatenation as defined in [\[T1.105\]](#)/[\[G.707\]](#) is supported. Note that bit 1 is the low order bit. Other flags are reserved for extensions, if not used they must be set to zero when sent, and should be ignored when received.

See note 1 hereafter in the section on the NCC about the SONET contiguous concatenation of STS-1 SPEs when the number of components is a multiple of three.

Number of Contiguous Components (NCC): 16 bits

This field indicates the number of identical SONET SPEs/SDH VCs (i.e., Elementary Signal) that are requested to be concatenated, as specified in the RCC field.

Note 1: when requesting a SONET STS-Nc SPE with $N=3 \times X$, the Elementary Signal to use must always be an STS-3c_SPE signal type and the value of NCC must always be equal to X. This allows also facilitating the interworking between SONET and SDH. In particular, it means that the contiguous concatenation of three STS-1 SPEs can not be requested because according to this specification, this type of signal must be coded using the STS-3c SPE signal type.

Note 2: when requesting a transparent STS-N/STM-N signal limited to a single contiguously concatenated STS-Nc_SPE/VC-4-Nc, the signal type must be STS-N/STM-N, RCC with flag 1 and NCC set to 1.

Note 3: in following the rules in this document, implementations choose the values of $NCC = RCC = 0$ for a VC-4 signal and $NCC = RCC = 1$ for an STS-3c signal (refer to Annex 1). In order to facilitate interworking of SONET and SDH, implementations of GMPLS protocols should be liberal in what they receive and therefore SHOULD accept either set of values for signal type 6 (STS-3c SPE / VC-4) as reflective of the LSP originating node's transport protocol (SONET or SDH). Topics related to the difference in performance monitoring for these 2 "equivalent" signal types are outside the scope of GMPLS and this document and MAY be communicated to the management system that may deal with it.

<BEGIN NOTE for explanation. To be removed before publication as an RFC>

This note is an update to [RFC 3946](#) in order to explain a circuit setup in a mixed environment with SONET-capable and SDH-capable nodes when setting up an STS-3c or VC-4 circuit. It gives guidance to accept either values of NCC and RCC for these signal types to resolve an interworking question raised during interoperability testing at the Optical Interworking Forum.

<END NOTE>

The NCC value must be consistent with the type of contiguous concatenation being requested in the RCC field. In particular, this field is irrelevant if no contiguous concatenation is requested ($RCC = 0$), in that case it must be set to zero when sent, and should be ignored when received. A RCC value different from 0 must imply a number of contiguous components greater than or equal to 1.

<BEGIN NOTE for explanation. To be removed before publication as an RFC>

The update from [RFC 3946](#) from "greater than 1" to "greater than or

equal to 1" makes sure that we can choose the values $NCC = RCC = 1$ for signal type STS-3c. It was the intent of the original authors that the previous text was not to be interpreted as "strictly greater". This text clarifies their intent.

<END NOTE>

Number of Virtual Components (NVC): 16 bits

This field indicates the number of signals that are requested to be virtually concatenated. These signals are all of the same type by definition. They are Elementary Signal SPEs/VCs for which signal types are defined in this document, i.e., VT1.5_SPE/VC-11, VT2_SPE/VC-12, VT3_SPE, VT6_SPE/VC-2, STS-1_SPE/VC-3 or STS-3c_SPE/VC-4.

This field is set to 0 (default value) to indicate that no virtual concatenation is requested.

Multiplier (MT): 16 bits

This field indicates the number of identical signals that are requested for the LSP, i.e., that form the Final Signal. These signals can be either identical Elementary Signals, or identical contiguously concatenated signals, or identical virtually concatenated signals. Note that all these signals belong thus to the same LSP.

The distinction between the components of multiple virtually concatenated signals is done via the order of the labels that are specified in the signaling. The first set of labels must describe the first component (set of individual signals belonging to the first virtual concatenated signal), the second set must describe the second component (set of individual signals belonging to the second virtual concatenated signal) and so on.

This field is set to one (default value) to indicate that exactly one instance of a signal is being requested. Intermediate and egress nodes MUST verify that the node itself and the interfaces on which the LSP will be established can support the requested multiplier value. If the requested values can not be supported, the receiver node MUST generate a PathErr/NOTIFICATION message (see [Section 2.2/2.3](#), respectively).

Zero is an invalid value. If received, the node MUST generate a PathErr/NOTIFICATION message (see [Section 2.2/2.3](#), respectively).

Note 1: when requesting a transparent STS-N/STM-N signal limited to a single contiguously concatenated STS-Nc-SPE/VC-4-Nc, the multiplier

field MUST be equal to 1 (only valid value).

Transparency (T): 32 bits

This field is a vector of flags that indicates the type of transparency being requested. Several flags can be combined to provide different types of transparency. Not all combinations are necessarily valid. The default value for this field is zero, i.e., no transparency requested.

Transparency, as defined from the point of view of this signaling specification, is only applicable to the fields in the SONET/SDH frame overheads. In the SONET case, these are the fields in the Section Overhead (SOH), and the Line Overhead (LOH). In the SDH case, these are the fields in the Regenerator Section Overhead (RSOH), the Multiplex Section overhead (MSOH), and the pointer fields between the two. With SONET, the pointer fields are part of the LOH.

Note as well that transparency is only applicable when using the following Signal Types: STS-1/STM-0, STS-3/STM-1, STS-12/STM-4, STS-48/STM-16, STS-192/STM-64 and STS-768/STM-256. At least one transparency type must be specified when requesting such a signal type.

Transparency indicates precisely which fields in these overheads must be delivered unmodified at the other end of the LSP. An ingress LSR requesting transparency will pass these overhead fields that must be delivered to the egress LSR without any change. From the ingress and egress LSRs point of views, these fields must be seen as unmodified.

Transparency is not applied at the interfaces with the initiating and terminating LSRs, but is only applied between intermediate LSRs.

The transparency field is used to request an LSP that supports the requested transparency type; it may also be used to setup the transparency process to be applied at each intermediate LSR.

The different transparency flags are the following:

Flag 1 (bit 1): Section/Regenerator Section layer.

Flag 2 (bit 2): Line/Multiplex Section layer.

Where bit 1 is the low order bit. Other flags are reserved, they should be set to zero when sent, and should be ignored when received. A flag is set to one to indicate that the corresponding transparency is requested.

Intermediate and egress nodes MUST verify that the node itself and

the interfaces on which the LSP will be established can support the requested transparency. If the requested flags can not be supported, the receiver node MUST generate a PathErr/NOTIFICATION message (see [Section 2.2/2.3](#), respectively).

Section/Regenerator Section layer transparency means that the entire frames must be delivered unmodified. This implies that pointers cannot be adjusted. When using Section/Regenerator Section layer transparency all other flags MUST be ignored.

Line/Multiplex Section layer transparency means that the LOH/MSOH must be delivered unmodified. This implies that pointers cannot be adjusted.

Profile (P): 32 bits

This field is intended to indicate particular capabilities that must be supported for the LSP, for example monitoring capabilities.

No standard profile is currently defined and this field SHOULD be set to zero when transmitted and SHOULD be ignored when received.

In the future TLV based extensions may be created.

2.2. RSVP-TE Details

For RSVP-TE, the SONET/SDH traffic parameters are carried in the SONET/SDH SENDER_TSPEC and FLOWSPEC objects. The same format is used both for SENDER_TSPEC object and FLOWSPEC objects. The content of the objects is defined above in [Section 2.1](#). The objects have the following class and type:

For SONET ANSI T1.105 and SDH ITU-T G.707:

SONET/SDH SENDER_TSPEC object: Class = 12, C-Type = 4

SONET/SDH FLOWSPEC object: Class = 9, C-Type = 4

There is no Adspec associated with the SONET/SDH SENDER_TSPEC. Either the Adspec is omitted or an int-serv Adspec with the Default General Characterization Parameters and Guaranteed Service fragment is used, see [[RFC2210](#)].

For a particular sender in a session the contents of the FLOWSPEC object received in a Resv message SHOULD be identical to the contents of the SENDER_TSPEC object received in the corresponding Path message. If the objects do not match, a ResvErr message with a "Traffic Control Error/Bad Flowspec value" error SHOULD be generated.

NOTIFICATION message with a "Resource Unavailable" status code (see [\[RFC3212\]](#)).

Intermediate and egress nodes MUST verify that the node itself and the interfaces on which the LSP will be established can support the requested Signal Type, RCC, NCC, NVC and Multiplier (as defined in [Section 2.1](#)). If the requested value(s) can not be supported, the receiver node MUST generate a PathErr message with a "Traffic Control Error/ Service unsupported" indication (see [\[RFC2205\]](#)).

3. SONET and SDH Labels

SONET and SDH each define a multiplexing structure. Both structures are trees whose roots are respectively an STS-N or an STM-N; and whose leaves are the signals that can be transported via the time-slots and switched between time-slots within an ingress port and time-slots within an egress port, i.e., a VTx SPE, an STS-x SPE or a VC-x. A SONET/SDH label will identify the exact position (i.e., first time-slot) of a particular VTx SPE, STS-x SPE or VC-x signal in a multiplexing structure. SONET and SDH labels are carried in the Generalized Label per [\[RFC3473\]](#) and [\[RFC3472\]](#).

Note that by time-slots we mean the time-slots as they appear logically and sequentially in the multiplex, not as they appear after any possible interleaving.

These multiplexing structures will be used as naming trees to create unique multiplex entry names or labels. The same format of label is used for SONET and SDH. As explained in [\[RFC3471\]](#), a label does not identify the "class" to which the label belongs. This is implicitly determined by the link on which the label is used.

In case of signal concatenation or multiplication, a list of labels can appear in the Label field of a Generalized Label.

In case of contiguous concatenation, only one label appears in the Label field. This label identifies the lowest time-slot occupied by the contiguously concatenated signal. By lowest time-slot we mean the one having the lowest label (value) when compared as integer values, i.e., the time-slot occupied by the first component signal of the concatenated signal encountered when descending the tree.

In case of virtual concatenation, the explicit ordered list of all labels in the concatenation is given. Each label indicates the first time-slot occupied by a component of the virtually concatenated signal. The order of the labels must reflect the order of the payloads to concatenate (not the physical order of time-slots). The

The standard definition for virtual concatenation allows each virtual concatenation components to travel over diverse paths. Within GMPLS, virtual concatenation components must travel over the same (component) link if they are part of the same LSP. This is due to the way that labels are bound to a (component) link. Note however, that the routing of components on different paths is indeed equivalent to establishing different LSPs, each one having its own route. Several LSPs can be initiated and terminated between the same nodes and their corresponding components can then be associated together (i.e., virtually concatenated).

The format of the label for SONET and/or SDH TDM-LSR link is:

This is an extension of the numbering scheme defined in [G.707] sections 7.3.7 to 7.3.13, i.e., the (K, L, M) numbering. Note that the higher order numbering scheme defined in [G.707] sections 7.3.1 to 7.3.6 is not used here.

When a hierarchy of SONET/SDH LSPs is used, a higher order LSP with a

given bandwidth can be used to carry lower order LSPs. Remember here that a higher order LSP is established through a SONET/SDH higher order path layer network and a lower order LSP, through a SONET/SDH lower order path layer network (see also ITU-T G.803, [Section 3](#) for the corresponding definitions). In this context, the higher order SONET/SDH LSP behaves as a "virtual link" with a given bandwidth (e.g., VC-3), it may also be used as a Forwarding Adjacency. A lower order SONET/SDH LSP can be established through that higher order LSP. Since a label is local to a (virtual) link, the highest part of that label (i.e., the S, U and K fields) is non-significant and is set to zero, i.e., the label is "0,0,0,L,M". Similarly, if the structure of the lower order LSP is unknown or not relevant, the lowest part of that label (i.e., the L and M fields) is non-significant and is set to zero, i.e., the label is "S,U,K,0,0".

For instance, a VC-3 LSP can be used to carry lower order LSPs. In that case the labels allocated between the two ends of the VC-3 LSP for the lower order LSPs will have S, U and K set to zero, i.e., non-significant, while L and M will be used to indicate the signal allocated in that VC-3.

In case of tunneling such as VC-4 containing VC-3 containing VC-12/VC-11 where the SUKLM structure is not adequate to represent the full signal structure, a hierarchical approach must be used, i.e., per layer network signaling.

The possible values of S, U, K, L and M are defined as follows:

1. S=1->N is the index of a particular STS-3/AUG-1 inside an STS-N/STM-N multiplex. S is only significant for SONET STS-N (N>1) and SDH STM-N (N>0). S must be 0 and ignored for STS-1 and STM-0.
2. U=1->3 is the index of a particular STS-1_SPE/VC-3 within an STS-3/AUG-1. U is only significant for SONET STS-N (N>1) and SDH STM-N (N>0). U must be 0 and ignored for STS-1 and STM-0.
3. K=1->3 is the index of a particular TUG-3 within a VC-4. K is only significant for an SDH VC-4 structured in TUG-3s. K must be 0 and ignored in all other cases.
4. L=1->7 is the index of a particular VT_Group/TUG-2 within an STS-1_SPE/TUG-3 or VC-3. L must be 0 and ignored in all other cases.
5. M is the index of a particular VT1.5_SPE/VC-11, VT2_SPE/VC-12 or VT3_SPE within a VT_Group/TUG-2. M=1->2 indicates a specific VT3 SPE inside the corresponding VT Group, these values MUST NOT be used for SDH since there is no equivalent of VT3 with SDH. M=3->5 indicates a specific VT2_SPE/VC-12 inside the

corresponding VT_Group/TUG-2. M=6->9 indicates a specific VT1.5_SPE/VC-11 inside the corresponding VT_Group/TUG-2.

Note that a label always has to be interpreted according the SONET/SDH traffic parameters, i.e., a label by itself does not allow knowing which signal is being requested (a label is context sensitive).

The label format defined in this section, referred to as SUKLM, MUST be used for any SONET/SDH signal requests that are not transparent i.e., when all Transparency (T) bits defined in [section 2.1](#) are set to zero. Any transparent STS-1/STM-0/STS-3*N/STM-N (N=1, 4, 16, 64, 256) signal request MUST use a label format as defined in [[RFC3471](#)].

The S encoding is summarized in the following table:

S	SDH	SONET

0	other	other
1	1st AUG-1	1st STS-3
2	2nd AUG-1	2nd STS-3
3	3rd AUG-1	3rd STS-3
4	4rd AUG-1	4rd STS-3
:	:	:
N	Nth AUG-1	Nth STS-3

The U encoding is summarized in the following table:

U	SDH AUG-1	SONET STS-3

0	other	other
1	1st VC-3	1st STS-1 SPE
2	2nd VC-3	2nd STS-1 SPE
3	3rd VC-3	3rd STS-1 SPE

Moreover, the reader is assumed to be familiar with the terminology in ANSI , ITU-T as well as , , and . The following abbreviations are used in this document:

The K encoding is summarized in the following table:

K	SDH VC-4

0	other
1	1st TUG-3
2	2nd TUG-3
3	3rd TUG-3

The L encoding is summarized in the following table:

L	SDH TUG-3	SDH VC-3	SONET STS-1 SPE

0	other	other	other
1	1st TUG-2	1st TUG-2	1st VTG
2	2nd TUG-2	2nd TUG-2	2nd VTG
3	3rd TUG-2	3rd TUG-2	3rd VTG
4	4th TUG-2	4th TUG-2	4th VTG
5	5th TUG-2	5th TUG-2	5th VTG
6	6th TUG-2	6th TUG-2	6th VTG
7	7th TUG-2	7th TUG-2	7th VTG

The M encoding is summarized in the following table:

M	SDH TUG-2	SONET VTG

0	other	other
1	-	1st VT3 SPE
2	-	2nd VT3 SPE
3	1st VC-12	1st VT2 SPE
4	2nd VC-12	2nd VT2 SPE
5	3rd VC-12	3rd VT2 SPE
6	1st VC-11	1st VT1.5 SPE
7	2nd VC-11	2nd VT1.5 SPE
8	3rd VC-11	3rd VT1.5 SPE
9	4th VC-11	4th VT1.5 SPE

Examples of labels:

Example 1: the label for the STS-3c_SPE/VC-4 in the Sth STS-3/AUG-1 is: S>0, U=0, K=0, L=0, M=0.

Example 2: the label for the VC-3 within the Kth-1 TUG-3 within the VC-4 in the Sth AUG-1 is: S>0, U=0, K>0, L=0, M=0.

Example 3: the label for the Uth-1 STS-1_SPE/VC-3 within the Sth STS-3/AUG-1 is: S>0, U>0, K=0, L=0, M=0.

Example 4: the label for the VT6/VC-2 in the Lth-1 VT Group/TUG-2 in the Uth-1 STS-1_SPE/VC-3 within the Sth STS-3/AUG-1 is: S>0, U>0, K=0, L>0, M=0.

Example 5: the label for the 3rd VT1.5_SPE/VC-11 in the Lth-1 VT Group/TUG-2 within the Uth-1 STS-1_SPE/VC-3 within the Sth STS-3/AUG-1 is: S>0, U>0, K=0, L>0, M=8.

Example 6: the label for the STS-12c/VC-4-4c which uses the 9th STS-3/AUG-1 as its first timeslot is: S=9, U=0, K=0, L=0, M=0.

In case of contiguous concatenation, the label that is used is the lowest label (value) of the contiguously concatenated signal as explained before. The higher part of the label indicates where the signal starts and the lowest part is not significant.

In case of STM-0/STS-1, the values of S, U and K must be equal to zero according to the field coding rules. For instance, when requesting a VC-3 in an STM-0 the label is S=0, U=0, K=0, L=0, M=0. When requesting a VC-11 in a VC-3 in an STM-0 the label is S=0, U=0, K=0, L>0, M=6..9.

Note: when a Section/RS or Line/MS transparent STS-1/STM-0/STS-3*N/STM-N (N=1, 4, 16, 64, 256) signal is requested, the SUKLM label format and encoding is not applicable and the label encoding MUST follow the rules defined in [\[RFC3471\] Section 3.2](#).

4. Acknowledgements

This document was originally published as [RFC 3946](#) in October 2004. It was produced by the CCAMP working of the IETF and was jointly edited Eric Mannie and Dimitri Papadimitriou. The RFC was based on work by the following list of co-contributors: Stefan Ansorge, Peter Ashwood-Smith, Ayan Banerjee, Lou Berger, Greg Bernstein, Angela Chiu, John Drake, Yanhe Fan, Michele Fontana, Gert Grammel, Juergen Heiles, Suresh Katukam, Kireeti Kompella, Jonathan P. Lang, Fong Liaw, Zhi-Wei Lin, Ben Mack-Crane, Dimitrios Pendarakis, Mike Raftelis, Bala Rajagopalan, Yakov Rekhter, Debanjan Saha, Vishal Sharma, George Swallow, Z. Bo Tang, Eve Varma, and Yangguang Xu. The ideas and text in RFC were reviewed and commented on by the CCAMP working group, and the original RFC editors acknowledged "outstanding discussions" that took place on the CCAMP mailing list. The revisions in this document arose from discussions and interoperability testing at the Optical Interworking Forum. Valuable input to the changes was received from Greg Bernstein, Dimitri Papadimitriou, Adrian Farrel and Ben Mack-Crane.

5. Security Considerations

This document introduces no new security considerations to either [RFC3473] or [RFC3472]. GMPLS security is described in [section 11 of \[RFC3471\]](#) and refers to [RFC3209] for RSVP-TE and to [RFC3212] for CR-LDP.

6. IANA Considerations

Three values have been defined by IANA for use in [RFC 3946](#). This revision makes no new requests for IANA action.

Two RSVP C-Types in registry:

<http://www.iana.org/assignments/rsvp-parameters>

- A SONET/SDH SENDER_TSPEC object: Class = 12, C-Type = 4 (see [section 2.2](#))
- A SONET/SDH FLOWSPEC object: Class = 9, C-Type = 4 (see [section 2.2](#)).

One LDP TLV Type in registry:

<http://www.iana.org/assignments/ldp-namespaces>

- A type field for the SONET/SDH Traffic Parameters TLV (see [section 2.3](#)).

7. Normative References

- [G.707] ITU-T Recommendation G.707, "Network Node Interface for the Synchronous Digital Hierarchy", October 2000.
- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), March 1997.
- [RFC2205] Braden, B., Zhang, L., Berson, S., Herzog, S., and S. Jamin, "Resource ReSerVation Protocol (RSVP) -- Version 1 Functional Specification", [RFC 2205](#), September 1997.
- [RFC2210] Wroclawski, J., "The Use of RSVP with IETF Integrated Services", [RFC 2210](#), September 1997.
- [RFC3209] Awduche, D., Berger, L., Gan, D., Li, T., Srinivasan, V., and G. Swallow, "RSVP-TE: Extensions to RSVP for LSP Tunnels", [RFC 3209](#), December 2001.

- [RFC3212] Jamoussi, B., Andersson, L., Callon, R., Dantu, R., Wu, L., Doolan, P., Worster, T., Feldman, N., Fredette, A., Girish, M., Gray, E., Heinanen, J., Kilty, T., and A. Malis, "Constraint-Based LSP Setup using LDP", [RFC 3212](#), January 2002.
- [RFC3471] Berger, L., "Generalized Multi-Protocol Label Switching (GMPLS) Signaling Functional Description", [RFC 3471](#), January 2003.
- [RFC3472] Ashwood-Smith, P. and L. Berger, "Generalized Multi-Protocol Label Switching (GMPLS) Signaling Constraint-based Routed Label Distribution Protocol (CR-LDP) Extensions", [RFC 3472](#), January 2003.
- [RFC3473] Berger, L., "Generalized Multi-Protocol Label Switching (GMPLS) Signaling Resource ReserVation Protocol-Traffic Engineering (RSVP-TE) Extensions", [RFC 3473](#), January 2003.
- [RFC3945] Mannie, E., "Generalized Multi-Protocol Label Switching (GMPLS) Architecture", [RFC 3945](#), October 2004.
- [T1.105] ANSI T1.105, "Synchronous Optical Network (SONET): Basic Description Including Multiplex Structure, Rates, and Formats", October 2000.

Appendix 1 - Signal Type Values Extension for VC-3

This appendix defines the following optional additional Signal Type value for the Signal Type field of [section 2.1](#):

Value	Type
-----	-----
20	"VC-3 via AU-3 at the end"

According to the ITU-T [\[G.707\]](#) recommendation a VC-3 in the TU-3/TUG-3/VC-4/AU-4 branch of the SDH multiplex cannot be structured in TUG-2s, however a VC-3 in the AU-3 branch can be. In addition, a VC-3 could be switched between the two branches if required.

A VC-3 circuit could be terminated on an ingress interface of an LSR (e.g., forming a VC-3 forwarding adjacency). This LSR could then want to demultiplex this VC-3 and switch internal low order LSPs. For implementation reasons, this could be only possible if the LSR receives the VC-3 in the AU-3 branch. E.g., for an LSR not able to switch internally from a TU-3 branch to an AU-3 branch on its incoming interface before demultiplexing and then switching the

content with its switch fabric.

In that case it is useful to indicate that the VC-3 LSP must be terminated at the end in the AU-3 branch instead of the TU-3 branch.

This is achieved by using the "VC-3 via AU-3 at the end" signal type. This information can be used, for instance, by the penultimate LSR to switch an incoming VC-3 received in any branch to the AU-3 branch on the outgoing interface to the destination LSR.

The "VC-3 via AU-3 at the end" signal type does not imply that the VC-3 must be switched via the AU-3 branch at some other places in the network. The VC-3 signal type just indicates that a VC-3 in any branch is suitable.

Annex 1 - Examples

This annex defines examples of SONET and SDH signal coding. Their objective is to help the reader to understand how works the traffic parameter coding and not to give examples of typical SONET or SDH signals.

As stated above, signal types are Elementary Signals to which successive concatenation, multiplication and transparency transforms can be applied to obtain Final Signals.

1. A VC-4 signal is formed by the application of RCC with value 0, NCC with value 0, NVC with value 0, MT with value 1 and T with value 0 to a VC-4 Elementary Signal.
2. A VC-4-7v signal is formed by the application of RCC with value 0, NCC with value 0, NVC with value 7 (virtual concatenation of 7 components), MT with value 1 and T with value 0 to a VC-4 Elementary Signal.
3. A VC-4-16c signal is formed by the application of RCC with flag 1 (standard contiguous concatenation), NCC with value 16, NVC with value 0, MT with value 1 and T with value 0 to a VC-4 Elementary Signal.
4. An STM-16 signal with Multiplex Section layer transparency is formed by the application of RCC with value 0, NCC with value 0, NVC with value 0, MT with value 1 and T with flag 2 to an STM-16 Elementary Signal.
5. An STM-4 signal with Multiplex Section layer transparency is formed by the application of RCC with flag 0, NCC with value 0,

- NVC with value 0, MT with value 1 and T with flag 2 applied to an STM-4 Elementary Signal.
6. An STM-256 signal with Multiplex Section layer transparency is formed by the application of RCC with flag 0, NCC with value 0, NVC with value 0, MT with value 1 and T with flag 2 applied to an STM-256 Elementary Signal.
 7. An STS-1 SPE signal is formed by the application of RCC with value 0, NCC with value 0, NVC with value 0, MT with value 1 and T with value 0 to an STS-1 SPE Elementary Signal.
 8. An STS-3c SPE signal is formed by the application of RCC with value 1 (standard contiguous concatenation), NCC with value 1, NVC with value 0, MT with value 1 and T with value 0 to an STS-3c SPE Elementary Signal.
 9. An STS-48c SPE signal is formed by the application of RCC with flag 1 (standard contiguous concatenation), NCC with value 16, NVC with value 0, MT with value 1 and T with value 0 to an STS-3c SPE Elementary Signal.
 10. An STS-1-3v SPE signal is formed by the application of RCC with value 0, NVC with value 3 (virtual concatenation of 3 components), MT with value 1 and T with value 0 to an STS-1 SPE Elementary Signal.
 11. An STS-3c-9v SPE signal is formed by the application of RCC with value 1, NCC with value 1, NVC with value 9 (virtual concatenation of 9 STS-3c), MT with value 1 and T with value 0 to an STS-3c SPE Elementary Signal.
 12. An STS-12 signal with Section layer (full) transparency is formed by the application of RCC with value 0, NVC with value 0, MT with value 1 and T with flag 1 to an STS-12 Elementary Signal.
 13. 3 x STS-768c SPE signal is formed by the application of RCC with flag 1, NCC with value 256, NVC with value 0, MT with value 3, and T with value 0 to an STS-3c SPE Elementary Signal.
 14. 5 x VC-4-13v composed signal is formed by the application of RCC with value 0, NVC with value 13, MT with value 5 and T with value 0 to a VC-4 Elementary Signal.

The encoding of these examples is summarized in the following table:

Signal	ST	RCC	NCC	NVC	MT	T

VC-4	6	0	0	0	1	0
VC-4-7v	6	0	0	7	1	0
VC-4-16c	6	1	16	0	1	0
STM-16 MS transparent	10	0	0	0	1	2
STM-4 MS transparent	9	0	0	0	1	2
STM-256 MS transparent	12	0	0	0	1	2
STS-1 SPE	5	0	0	0	1	0
STS-3c SPE	6	1	1	0	1	0
STS-48c SPE	6	1	16	0	1	0
STS-1-3v SPE	5	0	0	3	1	0
STS-3c-9v SPE	6	1	1	9	1	0
STS-12 Section transparent	9	0	0	0	1	1
3 x STS-768c SPE	6	1	256	0	3	0
5 x VC-4-13v	6	0	0	13	5	0

Editors of [RFC 3946](#)

Eric Mannie (Consultant)
Avenue de la Folle Chanson, 2
B-1050 Brussels, Belgium
Phone: +32 2 648-5023
Mobile: +32 (0)495-221775

EMail: eric_mannie@hotmail.com

Dimitri Papadimitriou (Alcatel)
Francis Wellesplein 1,
B-2018 Antwerpen, Belgium
Phone: +32 3 240-8491

EMail: dimitri.papadimitriou@alcatel.be

Author's Address

Richard Rabbat
Fujitsu
1240 East Arques Ave, MS 345
Sunnyvale, California 94085
USA

Phone: +1-408-530-4537
Fax: +1-408-530-4515
Email: richard@us.fujitsu.com

Intellectual Property Statement

The IETF takes no position regarding the validity or scope of any Intellectual Property Rights or other rights that might be claimed to pertain to the implementation or use of the technology described in this document or the extent to which any license under such rights might or might not be available; nor does it represent that it has made any independent effort to identify any such rights. Information on the procedures with respect to rights in RFC documents can be found in [BCP 78](#) and [BCP 79](#).

Copies of IPR disclosures made to the IETF Secretariat and any assurances of licenses to be made available, or the result of an attempt made to obtain a general license or permission for the use of such proprietary rights by implementers or users of this specification can be obtained from the IETF on-line IPR repository at <http://www.ietf.org/ipr>.

The IETF invites any interested party to bring to its attention any copyrights, patents or patent applications, or other proprietary rights that may cover technology that may be required to implement this standard. Please address the information to the IETF at ietf-ipr@ietf.org.

Disclaimer of Validity

This document and the information contained herein are provided on an "AS IS" basis and THE CONTRIBUTOR, THE ORGANIZATION HE/SHE REPRESENTS OR IS SPONSORED BY (IF ANY), THE INTERNET SOCIETY AND THE INTERNET ENGINEERING TASK FORCE DISCLAIM ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY WARRANTY THAT THE USE OF THE INFORMATION HEREIN WILL NOT INFRINGE ANY RIGHTS OR ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

Copyright Statement

Copyright (C) The Internet Society (2005). This document is subject to the rights, licenses and restrictions contained in [BCP 78](#), and except as set forth therein, the authors retain all their rights.

Acknowledgment

Funding for the RFC Editor function is currently provided by the Internet Society.

