PCE Working Group Internet-Draft Intended status: Standards Track Expires: May 3, 2018 A. Raghuram A. Goddard C. Yadlapalli AT&T J. Karthik S. Sivabalan J. Parker Cisco Systems, Inc. D. Dhody Huawei Technologies October 30, 2017

Ability for a stateful PCE to request and obtain control of a LSP draft-raghu-pce-lsp-control-request-05

Abstract

The stateful Path Computation Element (PCE) communication Protocol (PCEP) extensions provide stateful control of Multiprotocol Label Switching (MPLS) Traffic Engineering Label Switched Paths (TE LSP) via PCEP, for a model where a Path Computation Client (PCC) delegates control over one or more locally configured LSPs to a stateful PCE. There are use-cases in which a stateful PCE may wish to request and obtain control of one or more LSPs from a PCC. This document describes a simple extension to stateful PCEP to achieve such an objective.

Requirements Language

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "NOT RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in <u>BCP</u> <u>14</u> [<u>RFC2119</u>] [<u>RFC8174</u>] when, and only when, they appear in all capitals, as shown here.

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of <u>BCP 78</u> and <u>BCP 79</u>.

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <u>https://datatracker.ietf.org/drafts/current/</u>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any

Raghuram, et al.

Expires May 3, 2018

time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on May 3, 2018.

Copyright Notice

Copyright (c) 2017 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to <u>BCP 78</u> and the IETF Trust's Legal Provisions Relating to IETF Documents (<u>https://trustee.ietf.org/license-info</u>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

Table of Contents

$\underline{1}$. Introduction	<u>2</u>
<u>2</u> . Terminology	<u>3</u>
$\underline{3}$. LSP Control Request Flag	<u>4</u>
$\underline{4}$. Operation	<u>4</u>
5. Security Considerations	<u>5</u>
<u>6</u> . IANA Considerations	<u>5</u>
<u>6.1</u> . SRP Object Flags	<u>5</u>
<u>7</u> . Manageability Considerations	<u>6</u>
<u>7.1</u> . Control of Function and Policy	<u>6</u>
7.2. Information and Data Models	<u>6</u>
7.3. Liveness Detection and Monitoring	<u>6</u>
<u>7.4</u> . Verify Correct Operations	<u>6</u>
<u>7.5</u> . Requirements On Other Protocols	<u>6</u>
7.6. Impact On Network Operations	<u>6</u>
<u>8</u> . Acknowledgements	<u>6</u>
<u>9</u> . References	7
<u>9.1</u> . Normative References	7
<u>9.2</u> . Informative References	7
Authors' Addresses	<u>8</u>

<u>1</u>. Introduction

Stateful PCEP extensions [<u>RFC8231</u>] specifies a set of extensions to PCEP [<u>RFC5440</u>] to enable stateful control of TE LSPs between and across PCEP sessions in compliance with [<u>RFC4657</u>]. It includes mechanisms to effect LSP state synchronization between PCCs and PCEs,

[Page 2]

LSP Control Request

delegation of control of LSPs to PCEs, and PCE control of timing and sequence of path computations within and across PCEP sessions. The stateful PCEP defines the following two useful network operations:

- o Delegation: As per [<u>RFC8051</u>], an operation to grant a PCE temporary rights to modify a subset of LSP parameters on one or more LSPs of a PCC. LSPs are delegated from a PCC to a PCE and are referred to as "delegated" LSPs.
- o Revocation: As per [<u>RFC8231</u>], an operation performed by a PCC on a previously delegated LSP. Revocation revokes the rights granted to the PCE in the delegation operation.

For Redundant Stateful PCEs (<u>section 5.7.4. of [RFC8231]</u>), during a PCE failure, one of the redundant PCE could request to take control over an LSP. The redundant PCEs MAY use a local policy or a proprietary election mechanism to decide which PCE would take control. In this case, a mechanism is needed for a stateful PCE to request control of one or more LSPs from a PCC, so that a newly elected primary PCE can request to take over control.

In case of virtualized PCEs (vPCE) running as virtual network function (VNF), as the computation load in the network increases, a new instance of vPCE could be instantiated to balance the current load. The PCEs could use proprietary algorithm to decide which LSPs to be assigned to the new vPCE. Thus having a mechanism for the PCE to request control of some LSPs is needed.

In some deployments, the operator would like to use stateful PCE for global optimization algorithms but would still like to keep the control of the LSP at the PCC. In such cases, a stateful PCE could request to take control during the global optimization and return the delegation once done.

This specification provides a simple extension, by using this a PCE can request control of one or more LSPs from any PCC over the stateful PCEP channel. The procedures for granting and relinquishing control of the LSPs are specified in accordance with the specification [<u>RFC8231</u>].

2. Terminology

The following terminologies are used in this document:

- PCC: Path Computation Client.
- PCE: Path Computation Element

[Page 3]

PCEP: Path Computation Element communication Protocol.

PCRpt: Path Computation State Report message.

PCUpd: Path Computation Update Request message.

PLSP-ID: A PCEP-specific identifier for the LSP.

3. LSP Control Request Flag

The Stateful PCE Request Parameters (SRP) object is defined in [<u>RFC8231</u>], it includes a Flags field. [<u>I-D.ietf-pce-pce-initiated-lsp</u>] defines a R (LSP-REMOVE) flag.

A new flag, the "LSP Control Request Flag" (C), is introduced in the SRP object. On a PCUpd message, a PCE sets the C Flag to 1 to indicate that, it wishes to gain control of LSP(s). The LSP is identified by the LSP object. A PLSP-ID of value other than 0 and 0xFFFFF is used to identify the LSP for which the PCE requests control. The PLSP-ID value of 0 indicates that the PCE is requesting control of all LSPs originating from the PCC that it wishes to delegate. The flag has no meaning in the PCRpt and PCInitiate message and SHOULD be set to 0 on transmission and MUST be ignored on receipt.

4. Operation

During normal operation, a PCC that wishes to delegate the control of an LSP sets the D Flag (delegate) to 1 in all PCRpt messages pertaining to the LSP. The PCE confirms the delegation by setting D Flag to 1 in all PCUpd messages pertaining to the LSP. The PCC revokes the control of the LSP from the PCE by setting D Flag to 0 in PCRpt messages pertaining to the LSP. If the PCE wishes to relinquish the control of the LSP, it sets D Flag to 0 in all PCUpd messages pertaining to the LSP.

If a PCE wishes to gain control over an LSP, it sends a PCUpd message with C Flag set to 1 in SRP object. The LSP for which the PCE requests control is identified by the PLSP-ID. The PLSP-ID of 0 indicates that the PCE wants control over all LSPs originating from the PCC. If the LSP(s) is/are already delegated to the PCE making the request, the PCC ignores the C Flag. A PCC can decide to delegate the control of the LSP at its own discretion. If the PCC grants or denies the control, it sends PCRpt message with D Flag set to 1 and 0 respectively in accordance with according with stateful PCEP [<u>RFC8231</u>]. If the PCC does not grant the control, it MAY choose to not respond, and the PCE may choose to retry requesting the

control preferably using exponentially increasing timer. A PCE ignores the C Flag on the PCRpt message.

In case multiple PCEs request control over an LSP, and if the PCC is willing to grant the control, the LSP MUST be delegated to only one PCE chosen by the PCC based on its local policy.

It should be noted that a legacy implementation of PCC, that does not understand the C flag in PCUpd message, would simply ignore the flag and the request to grant control over the LSP.

[I-D.ietf-pce-pce-initiated-lsp] describes the setup, maintenance and teardown of PCE-initiated LSPs under the stateful PCE model. It also specify how a PCE MAY obtain control over an orphaned LSP that was PCE-initiated. A PCE implementation can apply the mechanism described in this document in conjunction with those in [I-D.ietf-pce-pce-initiated-lsp].

<u>5</u>. Security Considerations

The security considerations listed in [RFC8231] apply to this document as well. However, this document also introduces a new attack vectors. An attacker may flood the PCC with request to delegate all its LSPs at a rate which exceeds the PCC's ability to process them, either by spoofing messages or by compromising the PCE itself. The PCC can simply ignore these messages with no extra actions. Securing the PCEP session using mechanism like Transport Layer Security (TLS) [RFC8253] is RECOMMENDED.

<u>6</u>. IANA Considerations

This document requests IANA actions to allocate code points for the protocol elements defined in this document.

6.1. SRP Object Flags

The SRP object is defined in [<u>RFC8231</u>] and the registry to manage the Flag field of the SRP object is requested in [<u>I-D.ietf-pce-pce-initiated-lsp</u>]. IANA is requested to make the following allocation in the aforementioned registry.

Bit	Description	Reference
TBD	LSP Control Request Flag (c-bit)	This document

[Page 5]

7. Manageability Considerations

All manageability requirements and considerations listed in [RFC5440] and [RFC8231] apply to PCEP protocol extensions defined in this document. In addition, requirements and considerations listed in this section apply.

7.1. Control of Function and Policy

A PCE or PCC implementation SHOULD allow the operator to configure the policy based on which it honor the request to control the LSPs. Further, the operator MAY be to be allowed to trigger the LSP control request at the PCE.

7.2. Information and Data Models

The PCEP YANG module [<u>I-D.ietf-pce-pcep-yang</u>] could be extended to include mechanism to trigger the LSP control request.

7.3. Liveness Detection and Monitoring

Mechanisms defined in this document do not imply any new liveness detection and monitoring requirements in addition to those already listed in [<u>RFC5440</u>].

7.4. Verify Correct Operations

Mechanisms defined in this document do not imply any new operation verification requirements in addition to those already listed in [RFC5440] and [RFC8231].

7.5. Requirements On Other Protocols

Mechanisms defined in this document do not imply any new requirements on other protocols.

7.6. Impact On Network Operations

Mechanisms defined in [RFC5440] and [RFC8231] also apply to PCEP extensions defined in this document. Further, the mechanism described in this document can help the operator to request control of the LSPs at a particular PCE.

8. Acknowledgements

Thanks to Jonathan Hardwick to remind the authors to not use suggested values in IANA section.

Raghuram, et al.Expires May 3, 2018[Page 6]

9. References

<u>9.1</u>. Normative References

- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", <u>BCP 14</u>, <u>RFC 2119</u>, DOI 10.17487/RFC2119, March 1997, <https://www.rfc-editor.org/info/rfc2119>.
- [RFC5440] Vasseur, JP., Ed. and JL. Le Roux, Ed., "Path Computation Element (PCE) Communication Protocol (PCEP)", <u>RFC 5440</u>, DOI 10.17487/RFC5440, March 2009, <<u>https://www.rfc-editor.org/info/rfc5440</u>>.
- [RFC8174] Leiba, B., "Ambiguity of Uppercase vs Lowercase in <u>RFC</u> 2119 Key Words", <u>BCP 14</u>, <u>RFC 8174</u>, DOI 10.17487/RFC8174, May 2017, <<u>https://www.rfc-editor.org/info/rfc8174</u>>.
- [RFC8231] Crabbe, E., Minei, I., Medved, J., and R. Varga, "Path Computation Element Communication Protocol (PCEP) Extensions for Stateful PCE", <u>RFC 8231</u>, DOI 10.17487/RFC8231, September 2017, <<u>https://www.rfc-editor.org/info/rfc8231</u>>.

<u>9.2</u>. Informative References

[I-D.ietf-pce-pce-initiated-lsp] Crabbe, E., Minei, I., Sivabalan, S., and R. Varga, "PCEP Extensions for PCE-initiated LSP Setup in a Stateful PCE Model", <u>draft-ietf-pce-pce-initiated-lsp-11</u> (work in progress), October 2017.

[I-D.ietf-pce-pcep-yang]

Dhody, D., Hardwick, J., Beeram, V., and j. jefftant@gmail.com, "A YANG Data Model for Path Computation Element Communications Protocol (PCEP)", <u>draft-ietf-pce-pcep-yang-05</u> (work in progress), June 2017.

- [RFC4657] Ash, J., Ed. and J. Le Roux, Ed., "Path Computation Element (PCE) Communication Protocol Generic Requirements", <u>RFC 4657</u>, DOI 10.17487/RFC4657, September 2006, <<u>https://www.rfc-editor.org/info/rfc4657</u>>.
- [RFC8051] Zhang, X., Ed. and I. Minei, Ed., "Applicability of a Stateful Path Computation Element (PCE)", <u>RFC 8051</u>, DOI 10.17487/RFC8051, January 2017, <<u>https://www.rfc-editor.org/info/rfc8051</u>>.

[RFC8253] Lopez, D., Gonzalez de Dios, O., Wu, Q., and D. Dhody, "PCEPS: Usage of TLS to Provide a Secure Transport for the Path Computation Element Communication Protocol (PCEP)", <u>RFC 8253</u>, DOI 10.17487/RFC8253, October 2017, <<u>https://www.rfc-editor.org/info/rfc8253</u>>.

Authors' Addresses

Aswatnarayan Raghuram AT&T 200 S Laurel Aevenue Middletown, NJ 07748 USA Email: ar2521@att.com Al Goddard AT&T 200 S Laurel Aevenue Middletown, NJ 07748 USA Email: ag6941@att.com Chaitanya Yadlapalli AT&T 200 S Laurel Aevenue Middletown, NJ 07748 USA Email: cy098d@att.com Jay Karthik Cisco Systems, Inc. 125 High Street Boston, Massachusetts 02110 USA

Email: jakarthi@cisco.com

Raghuram, et al.Expires May 3, 2018[Page 8]

Siva Sivabalan Cisco Systems, Inc. 2000 Innovation Drive Kanata, Ontario K2K 3E8 Canada

Email: msiva@cisco.com

Jon Parker Cisco Systems, Inc. 2000 Innovation Drive Kanata, Ontario K2K 3E8 Canada

Email: jdparker@cisco.com

Dhruv Dhody Huawei Technologies Divyashree Techno Park, Whitefield Bangalore, Karnataka 560066 India

Email: dhruv.ietf@gmail.com

Raghuram, et al. Expires May 3, 2018 [Page 9]