

BGP Extended Communities Attribute

[draft-ramachandra-bgp-ext-communities-02.txt](#)

1. Status of this Memo

This document is an Internet-Draft and is in full conformance with all provisions of [Section 10 of RFC2026](#) except that the right to produce derivative works is not granted.

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF), its areas, and its working groups. Note that other groups may also distribute working documents as Internet-Drafts.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as ``work in progress.''

The list of current Internet-Drafts can be accessed at <http://www.ietf.org/ietf/1id-abstracts.txt>

The list of Internet-Draft Shadow Directories can be accessed at <http://www.ietf.org/shadow.html>.

2. Abstract

This document describes an extension to BGP [[BGP-4](#)] which may be used to provide flexible control over the distribution of routing information.

3. Introduction

The Extended Community Attribute provides two important enhancements over the existing BGP Community Attribute:

- It provides an extended range, ensuring that communities can be assigned for a plethora of uses, without fear of overlap.
- The addition of a Type field provides structure for the community space.

The addition of structure allows the application of policy based on the application for which the community value will be used. For example, one can filter out all communities of a particular type, or allow only certain values for a particular type of community. Without structure this can only be accomplished by explicitly enumerating all community values which will be denied or allowed.

4. BGP Extended Communities Attribute

The Extended Communities Attribute is a transitive optional BGP attribute. The attribute consists of a set of "extended communities". Each extended community is coded as an eight octet value. All routes with the Extended Communities attribute belong to the communities listed in the attribute.

The Extended Communities Attribute has Type Code 16.

Each Extended Community is encoded as an eight octet quantity, as follows:

- Type Field: 2 octets

Types 0 through 0x7fff inclusive are assignable by IANA. Types 0x8000 through 0xffff inclusive are vendor-specific.

- Value Field: 6 octets

When the high-order octet of the Type field is 0x00, the Value field consists of two subfields:

Administrator: 2 octets

This subfield contains an Autonomous System number assigned by IANA.

Assigned Number subfield: 4 octets

This subfield contains a number from a numbering space which is administered by the organization to which the Autonomous System number in the Administrator subfield has been assigned by IANA.

When the high-order octet of the Type field is 0x01, the Value field consists of two subfields:

Administrator: 4 octets

This subfield contains an IPv4 address assigned by IANA.

Assigned Number subfield: 2 octets

This subfield contains a number from a numbering space which is administered by the organization to which the IPv4 address in the Administrator subfield has been assigned by IANA.

5. Route Origin Community

The Route Origin Community identifies one or more routers that inject a set of routes (that carry this Community) into BGP.

The Type field for the Route Origin Community is 0x0001 or 0x0101.

6. Route Target Community

The Route Target Community identifies one or more routers that may receive a set of routes (that carry this Community) carried by BGP.

The Type field for the Route Target Community is 0x0002 or 0x0102.

7. Operations

A BGP speaker may use the Extended Communities attribute to control which routing information it accepts, prefers or distributes to its peers.

A BGP speaker receiving a route that doesn't have the Extended Communities attribute may append this attribute to the route when propagating it to its peers.

A BGP speaker receiving a route with the Extended Communities attribute may modify this attribute according to the local policy.

A route may carry both the BGP Communities attribute as defined in [RFC1997]), and the Extended BGP Communities attribute. In this case the BGP Communities attribute is handled as specified in [RFC1997], and the Extended BGP Communities attribute is handled as specified in this document.

8. Security Considerations

This extension to BGP does not change the underlying security issues.

9. Acknowledgements

To be supplied.

10. References

[BGP-4] Rekhter, Y., and T. Li, "A Border Gateway Protocol 4 (BGP-4)", [RFC 1771](#), March 1995.

[RFC1997] Chandra, R., Traina, P., Li, T., "BGP Communities Attribute", [RFC1997](#), August 1996.

11. Author Information

Srihari Ramachandra
Cisco Systems, Inc.
170 West Tasman Drive
San Jose, CA 95134
e-mail: rsrihari@cisco.com

Dan Tappan
Cisco Systems, Inc.
250 Apollo Drive
Chelmsford, MA, 01824
e-mail: tappan@cisco.com