

INTERNET-DRAFT
Intended Status: Standard Track
Expires: April 20, 2014

Khuzema Pithewan
Rajan Rao
Infinera
October 17, 2013

**OSPF-TE extensions for MLNMRN based on OTN
draft-rao-ccamp-mlnmrn-otn-ospfte-ext-03.txt**

Abstract

This document specifies OSPF extensions for multi-layer/multi-region where one of the regions is multi-layer e.g. OTN, SONET/SDH.

Status of this Memo

This Internet-Draft is submitted to IETF in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF), its areas, and its working groups. Note that other groups may also distribute working documents as Internet-Drafts.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

The list of current Internet-Drafts can be accessed at <http://www.ietf.org/lid-abstracts.html>

The list of Internet-Draft Shadow Directories can be accessed at <http://www.ietf.org/shadow.html>

Copyright and License Notice

Copyright (c) 2013 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents

carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

Table of Contents

| | | |
|---------------------|--|-------------------|
| 1 | Introduction | 3 |
| 2 | Layer Identification | 3 |
| 3 | OTN Layer ID | 4 |
| 4 | SONET/SDH Layer Identification | 6 |
| 5 | Procedure | 6 |
| 6 | Examples | 6 |
| 6.1 | Ethernet and OTN | 7 |
| 6.2 | OTN and FlexGrid | 7 |
| 6.3 | OTN and SONET/SDH | 8 |
| 6.4 | OTN and OTN | 8 |
| 7 | IANA Considerations | 8 |
| 8 | Security Considerations | 9 |
| 9 | References | 9 |
| 10 | Authors' Addresses | 9 |

1 Introduction

In order to do end-to-end path computation, where a path may involve more than one region and part of single routing domain, TE Links connecting the two regions need to have bandwidth capacity advertised for the switch that connects the two regions. This document specifies the OSPF extensions that are required if any of the region is a multi-layer network. The specification is based on the requirement as specified in [RFC 5212](#). As per the said RFC, ISCD characterizes the information associated to one or more network layers. Same RFC also says that the information about the adjustment capabilities of the nodes in the network allow the path computation process to select an end-to-end multi-layer or multi-region path that includes links with different switching capabilities joined by LSRs that can adapt (i.e., adjust) the signal between the links. By inference, information about the adjustment capabilities should be able to identify a layer in ISCD, if ISCD specifies more than one layer.

[RFC6001](#) specifies how to advertise adjustment capabilities between two switching regions. IACD definition has provision to extend it for a specific technology through Adjustment Capability Specific information (ACSI) field, if required. ACSI field can be used to identify a layer in the multi-layer ISCD.

While OTN multi-layer technology is a primary driver for this extension, the extensions in this document does cover specifications for multi-layer technologies in general. To make sure the extensions are extensible to other multi-layer technologies as well, this document covers SDH/SONET as well.

2 Layer Identification

Multi-region path computation requires to identify a layer in the multi-layer region. This mandates layer identification along with identification of technology in the region. The technology identification is done via Switching capability and Encoding type.

IACD needs to be extended to be able to carry layer identification. the layer Identification is OPTIONAL and used only when interface supports layer multiplexing and hence creating a need to identify a layer. A new Layer ID Sub-TLV has been defined to carry layer identification.

[illegible]

Type : Type field is used to identify a particular structure of variable size field, which is specific to the particular Switching Capability and Encoding type combination

R : This bit is used to make sense whether the Layer ID is for Lower region or upper region. 1 means upper region and 0 means lower.

IACD can have at-most 2 Layer ID TLVs, if both the regions are multi-layer.

Next two sections specifies Layer ID for two multi-layer technologies namely, OTN and SONET/SDH

3 OTN Layer ID

[RFC6001](#) defines IACD sub-TLV as follows. Please refer to the RFC for definition of individual fields of the sub-TLV.

| 0 | | | | | | | | | | 1 | | | | | | | | | | 2 | | | | | | | | | | 3 | | | | | | | | | |
|---------------------------------|---|---|---|---|---|---|---|---|---|----------------|---|---|---|---|---|---|---|---|---|----------|---|---|---|---|---|---|---|---|---|----------------|---|---|---|---|---|---|---|---|---|
| 0 | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 0 | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 0 | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 0 | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 |
| Lower SC | | | | | | | | | | Lower Encoding | | | | | | | | | | Upper SC | | | | | | | | | | Upper Encoding | | | | | | | | | |
| Max LSP Bandwidth at priority 0 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Max LSP Bandwidth at priority 1 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Max LSP Bandwidth at priority 2 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Max LSP Bandwidth at priority 3 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Max LSP Bandwidth at priority 4 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Max LSP Bandwidth at priority 5 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Max LSP Bandwidth at priority 6 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Max LSP Bandwidth at priority 7 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |


```

+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+
|           Adjustment Capability-specific information           |
|                               (variable)                       |
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+

```

[GMPLS-OTN-OSPF] defines attributes that identifies a layer in multi-layer OTN ISCD. These attributes are part of Bandwidth sub-TLV in Switch capability specific information of ISCD. These attributes are reproduced here for completeness sake.

- * Signal Type: Layer for which bandwidth is being advertised.
- * Hierarchy : also called as multiplexing branch that specifies all the layers between server layer and signal type.
- * TSG : Time Slot Granularity

Adjustment Capability-specific information abbreviated as ACSI henceforth for OTN G.709v3 carries LayerID Sub-TLV which is defined as follows

```

0           1           2           3
0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+
| Type = 1      |R|  Reserved   |           Length           |
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+
|  Signal type  | Num of stages |TSG |    Res    |   Stage#1    |
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+
|   Stage#2    |      ...      | Stage#N   |   Padding   |
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+

```

This LayerID sub-TLV is applicable only when one of the regions is OTN, which means either lower or upper SC and Encoding type MUST have Switch Cap as OTN-TDM and encoding type as G.709 ODUk.

R bit is used to make sense whether the Layer ID is for Lower region or upper region. 1 means upper region and 0 means lower.

The 8 priorities of the BW as defined in main IACD structure, is adjustment capability between the two regions where one of the region is identifies by LayerID sub-TLV.

Absence of this sub-TLV for OTN means that the OTN ISCD doesn't support multiplexing.

4 SONET/SDH Layer Identification

G.707 defines the structure of SDH multiplexing hierarchy and [RFC 4606](#) defines generalized label structure needed to fully specify SONET/SDH multiplexing hierarchy. This Label structure also referred as SUKLM structure identifies all the layers of the multiplexing hierarchy along with time slots. For the purpose of this draft, only layer identification is needed, hence each layer can be identified by a bit. Bit value 1 signifies presence of the layer and 0, its absence. 5 Bits, each representing one layer is sufficient to fully identify the SONET/SDH multiplexing hierarchy.

Layer ID sub TLV for SONET/SDH is defined as follows

```

      0               1               2               3
0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+
| Type = 2      |R|  Reserved  |                Length          |
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+
|S|U|K|L|M|                Padding                            |
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+

```

SUKLM bits signifies the presence of SONET/SDH layers and these bits together fully specifies the multiplexing hierarchy. Refer to [Section 3 of RFC 4606](#) for full specification of SUKLM bits.

Absence of sub-TLV means that the SONET/SDH ISCD doesn't support multiplexing and needs only transparent mapping to other Interface.

5 Procedure

A node advertising IACD for the bandwidth between regions where one or both of them are hierarchical i.e. OTN or SONET/SDH, MUST include the Layer ID sub-TLV as part of ACSI as defined above.

For multi-region path computation, the path computing node MUST look at the LayerID sub-TLV (in ACSI part of IACD) if lower/upper {SC,Enc} is {OTN-TDM,G.7090DUK} or {TDM,SONET/SDH} to identify the layer for correct layer for BW check.

6 Examples

This section exemplifies TLV values for various technology region combinations, where one of the region is OTN

6.3. OTN and SONET/SDH

| 0 | | | | | | | | | | 1 | | | | | | | | | | 2 | | | | | | | | | | 3 | | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 0 | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 0 | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 0 | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 0 | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 0 | 1 |
| + - | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |

6.4. OTN and OTN

| 0 | | | | | | | | | | 1 | | | | | | | | | | 2 | | | | | | | | | | 3 | | | | | | | | | | | | | | | | | | | |
|-------------|---|---|---|---|---|---|---|---|---|---------------------------------|---|---|---|---|---|---|---|---|---|---------|---|---|---|---|---|---|---|---|---|------------|---|---|---|---|---|---|---|---|---|---|---|--|--|--|--|--|--|--|--|
| 0 | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 0 | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 0 | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 0 | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 0 | 1 | | | | | | | | |
| OTN-TDM | | | | | | | | | | G.709 ODUk | | | | | | | | | | OTN-TDM | | | | | | | | | | G.709 ODUk | | | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | Max LSP Bandwidth at priority 0 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | / / / / / / / / / / / / / / / | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | Max LSP Bandwidth at priority 7 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Type = 1 | | | | | | | | | | 0 Reserved | | | | | | | | | | Length | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Signal type | | | | | | | | | | Num of stages TSG | | | | | | | | | | Res | | | | | | | | | | Stage#1 | | | | | | | | | | | | | | | | | | | |
| Stage#2 | | | | | | | | | | ... | | | | | | | | | | Stage#N | | | | | | | | | | Padding | | | | | | | | | | | | | | | | | | | |
| Type = 1 | | | | | | | | | | 1 Reserved | | | | | | | | | | Length | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Signal type | | | | | | | | | | Num of stages TSG | | | | | | | | | | Res | | | | | | | | | | Stage#1 | | | | | | | | | | | | | | | | | | | |
| Stage#2 | | | | | | | | | | ... | | | | | | | | | | Stage#N | | | | | | | | | | Padding | | | | | | | | | | | | | | | | | | | |

7 IANA Considerations

TBD

8 Security Considerations

TBD

9 References

- [RFC5212] K. Shiomoto, Papadimitriou, D., JL. Le Roux, Vigoureux, M., Brungard, D., "Requirements for GMPLS-Based Multi-Layer and Multi-Region Networks (MLN/ MRN)", [RFC 5212](#), July 2008.
- [RFC6001] Papadimitriou, D., Vigoureux, M., Shiomoto, K., Brungard, D., and JL. Le Roux, "Generalized MPLS (GMPLS) Protocol Extensions for Multi-Layer and Multi-Region Networks (MLN/MRN)", [RFC 6001](#), October 2010.
- [RFC4606] E. Mannie, Perceval, D. Papadimitriou, "Generalized Multi-Protocol Label Switching (GMPLS) Extensions for Synchronous Optical Network (SONET) and Synchronous Digital Hierarchy (SDH) Control", [RFC 4606](#), Aug 2006
- [GMPLS-OTN-OSPF] Traffic Engineering Extensions to OSPF for Generalized MPLS (GMPLS)Control of Evolving G.709 OTN Networks

10. Authors' Addresses

Khuzema Pithewan
Infinera
140 Caspian Ct., Sunnyvale, CA 94089
Email: kpithewan@infinera.com

Rajan Rao
Infinera
140 Caspian Ct., Sunnyvale, CA 94089
Email: rrao@infinera.com

