6tisch Working Group Internet-Draft

Intended status: Informational

Expires: August 18, 2018

M. Richardson Sandelman Software Works P. van der Stok vanderstok consultancy P. Kampanakis Cisco Systems February 14, 2018

Constrained Voucher Profile for Bootstrapping Protocols draft-richardson-anima-ace-constrained-voucher-03

Abstract

This document defines a strategy to securely assign a pledge to an owner, using an artifact signed, directly or indirectly, by the pledge's manufacturer. This artifact is known as a "voucher".

This document builds upon the work in [I-D.ietf-anima-voucher], encoding the resulting artifact in CBOR. Use with two signature technologies are described.

Additionally, this document explains how constrained vouchers may be transported in the [<u>I-D.vanderstok-ace-coap-est</u>] protocol.

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of BCP 78 and BCP 79.

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at https://datatracker.ietf.org/drafts/current/.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on August 18, 2018.

Copyright Notice

Copyright (c) 2018 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to BCP 78 and the IETF Trust's Legal Provisions Relating to IETF Documents (https://trustee.ietf.org/license-info) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

Table of Contents

| introduction | <u> 3</u> |
|--|---------------|
| <u>2</u> . Terminology | <u>3</u> |
| 3. Requirements Language | 4 |
| 4. Survey of Voucher Types | |
| $\underline{5}$. Discovery and URI | <u>4</u> |
| <u>6</u> . Artifacts | |
| <u>6.1</u> . Voucher Request artifact | <u>6</u> |
| <u>6.1.1</u> . Tree Diagram | <u>6</u> |
| <u>6.1.2</u> . SID values | <u>6</u> |
| <u>6.1.3</u> . YANG Module | |
| 6.1.4. Example voucher request artifacts | |
| 6.2. Voucher artifact | |
| 6.3. Tree Diagram | |
| 6.4. SID values | |
| 6.5. YANG Module | |
| 6.5.1. Example voucher artifacts | |
| 6.6. CMS format voucher and voucher-request artifacts | 12 |
| 6.7. COSE format voucher and voucher-request artifacts | |
| 7. Design Considerations | |
| 8. Security Considerations | |
| 8.1. Clock Sensitivity | |
| 8.2. Protect Voucher PKI in HSM | |
| 8.3. Test Domain Certificate Validity when Signing | |
| 9. IANA Considerations | |
| 9.1. The IETF XML Registry | |
| 9.2. The YANG Module Names Registry | |
| 9.3. The SMI Security for S/MIME CMS Content Type Registry | |
| 9.4. The SID registry | |
| 9.5. Media-Type Registry | |
| 9.6. CoAP Content-Format Registry | |
| 10. Acknowledgements | |
| 11. References | |
| 11.1. Normative References | |
| 11.2. Informative References | |
| Appendix A. EST messages to EST-coaps | |
| A.1. enrollstatus | |
| | |

| <u>A.2</u> . | voucher_status | | | | | | | | | | | 19 |
|--------------|-----------------|--|--|--|--|--|--|--|--|--|--|----|
| <u>A.3</u> . | requestvoucher | | | | | | | | | | | 19 |
| <u>A.4</u> . | requestauditing | | | | | | | | | | | 19 |
| ithors' | Δddresses | | | | | | | | | | | 10 |

1. Introduction

Enrollment of new nodes into constrained networks with constrained nodes present unique challenges.

There are bandwidth and code space issues to contend. A solution such as [I-D.ietf-anima-bootstrapping-keyinfra] may be too large in terms of code space or bandwidth required.

This document defines a constrained version of [I-D.ietf-anima-voucher]. Rather than serializing the YANG definition in JSON, it is serialized into CBOR ([RFC7049]).

This document follows a similar, but not identical structure as [I-D.ietf-anima-voucher]. Some sections are left out entirely. Additional sections to [I-D.ietf-anima-voucher] concern: - Addition of voucher-request specification as defined in [I-D.ietf-anima-bootstrapping-keyinfra], - Addition to [I-D.vanderstok-ace-coap-est] of voucher transport requests over coap.

The CBOR definitions for this constrained voucher format are defined using the mechanism describe in [I-D.ietf-core-yang-cbor] using the SID mechanism explained in [I-D.ietf-core-sid]. As the tooling to convert YANG documents into an list of SID keys is still in its infancy, the table of SID values presented here should be considered normative rather than the output of the pyang tool.

Two methods of signing the resulting CBOR object are described in this document. One is CMS [RFC5652]. The other is COSE [RFC8152] signatures.

2. Terminology

The following terms are defined in [I-D.ietf-anima-voucher], and are used identically as in that document: artifact, imprint, domain, Join Registrar/Coordinator (JRC), Manufacturer Authorized Signing Authority (MASA), pledge, Trust of First Use (TOFU), and Voucher.

3. Requirements Language

In this document, the key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" are to be interpreted as described in BCP 14, RFC 2119 and indicate requirement levels for compliant STUPiD implementations.

4. Survey of Voucher Types

[I-D.ietf-anima-voucher] provides for vouchers that assert proximity, that authenticate the registrar and that include different amounts of anti-replay protection.

This document does not make any extensions to the types of vouchers.

Time based vouchers are included in this definition, but given that constrained devices are extremely unlikely to know the correct time, their use is very unlikely. Most users of these constrained vouchers will be online and will use live nonces to provide anti-replay protection.

[I-D.ietf-anima-voucher] defined only the voucher artifact, and not the Voucher Request artifact, which was defined in [I-D.ietf-anima-bootstrapping-keyinfra].

This document defines both a constrained voucher and a constrained voucher-request. They are presented in the order voucher-request, followed by voucher response as this is the time order that they occur.

Discovery and URI

This section describes the BRSKI extensions to EST-coaps [I-D.vanderstok-ace-coap-est] to transport the voucher between registrar, proxy and pledge over CoAP.

The extension is targeted to low-resource networks with small packets. Saving header space is important and the EST-coaps URI is shorter than the EST URI.

The presence and location of (path to) the management data are discovered by sending a GET request to "/.well-known/core" including a resource type (RT) parameter with the value "ace.est" [RFC6690]. Upon success, the return payload will contain the root resource of the EST resources. It is up to the implementation to choose its root resource; throughout this document the example root resource /est is

used. The example below shows the discovery of the presence and location of voucher resources.

```
REQ: GET /.well-known/core?rt=ace.est

RES: 2.05 Content
</est>; rt="ace.est"
```

The EST-coaps server URIs differ from the EST URI by replacing the scheme https by coaps and by specifying shorter resource path names:

```
coaps://www.example.com/est/short-name
```

Figure 5 in <u>section 3.2.2 of [RFC7030]</u> enumerates the operations and corresponding paths which are supported by EST. Table 1 provides the mapping from the BRSKI extension URI path to the EST-coaps URI path.

| + | ++ |
|-----------------------|-----------|
| BRSKI | EST-coaps |
| /requestvoucher | /rv |
| /voucher-status | /vs |
| /enrollstatus | |
| /requestauditlog | |
| + | ++ |

Table 1: BRSKI path to EST-coaps path

/requestvoucher and /enrollstatus are needed between pledge and Registrar.

When discovering the root path for the EST resources, the server MAY return the full resource paths and the used content types. This is useful when multiple content types are specified for EST-coaps server. For example, the following more complete response is possible.

```
REQ: GET /.well-known/core?rt=ace.est

RES: 2.05 Content
</est>; rt="ace.est"
</est/rv>; rt="ace.est";ct=50 TBD2 16
</est/vs>; rt="ace.est";ct=50
</est/es>; rt="ace.est";ct=50
</est/ra>; rt="ace.est";ct=50
```

ct=50 stands for the Content-Format "application/json", ct=16 stands for the Content-Format "application/cose", and ct=TBD2 stands for Content-Format "application/voucher-cms+cbor defined in this document.

The return of the content-types allows the client to choose the most appropriate one from multiple content types.

6. Artifacts

This section describes the abstract (tree) definition as explained in [<u>I-D.ietf-netmod-yang-tree-diagrams</u>] first. This provides a high-level view of the contents of each artifact.

Then the assigned SID values are presented. These have been assigned using the rules in [I-D.ietf-core-yang-cbor], with an allocation that was made via the http://comi.space service.

((EDNOTE: it is unclear if there is further IANA work))

6.1. Voucher Request artifact

6.1.1. Tree Diagram

```
module: ietf-cwt-voucher-request
  grouping voucher-request-cwt-grouping
    +---- voucher
       +---- created-on
              vang:date-and-time
       +---- expires-on?
              yang:date-and-time
       +---- assertion
               enumeration
       +---- serial-number
                                                             string
       +---- idevid-issuer?
                                                             binary
       +---- pinned-domain-cert
                                                             binary
       +---- domain-cert-revocation-checks?
                                                             boolean
       +---- nonce?
                                                             binary
       +---- last-renewal-date?
               yang:date-and-time
       +---- proximity-registrar-subject-public-key-info?
                                                             binary
```

6.1.2. SID values

[EDNote: the appropriate generation of the SID values is under discussion]

SID Assigned to

```
_____
    1001150 module ietf-cwt-voucher-request
    1001151 module ietf-restconf
    1001152 module ietf-voucher
    1001153 module ietf-yang-types
    1001154 data .../ietf-cwt-voucher-request:voucher
    1001155 data .../assertion
    1001156 data .../created-on
    1001157 data .../domain-cert-revocation-checks
    1001158 data .../expires-on
    1001159 data .../idevid-issuer
    1001160 data .../last-renewal-date
    1001161 data .../nonce
    1001162 data .../pinned-domain-cert
    1001163 data .../proximity-registrar-subject-public-key-info
    1001164 data .../serial-number
6.1.3. YANG Module
   [EDNote: the appropriate syntax of the module is under discussion]
<CODE BEGINS> file "ietf-cwt-voucher-request@2017-12-11.yang"
/* -*- C -*- */
module ietf-cwt-voucher-request {
 yang-version 1.1;
 namespace
   "urn:ietf:params:xml:ns:yang:ietf-cwt-voucher-request";
 prefix "vcwt";
 import ietf-voucher {
   prefix "v";
 }
 organization
  "IETF 6tisch Working Group";
 contact
   "WG Web: < http://tools.ietf.org/wg/6tisch/>
   WG List: <mailto:6tisch@ietf.org>
   Author:
             Michael Richardson
             <mailto:mcr+ietf@sandelman.ca>";
 description
  "This module defines the format for a voucher, which is produced by
   a pledge's manufacturer or delegate (MASA) to securely assign one
   or more pledges to an 'owner', so that the pledges may establish a
```

secure connection to the owner's network infrastructure. This version provides a very restricted subset appropriate for very constrained devices. In particular, it assumes that nonce-ful operation is always required, that expiration dates are rather weak, as no clocks can be assumed, and that the Registrar is identified by a pinned Raw Public Key. The key words 'MUST', 'MUST NOT', 'REQUIRED', 'SHALL', 'SHALL NOT', 'SHOULD', 'SHOULD NOT', 'RECOMMENDED', 'MAY', and 'OPTIONAL' in the module text are to be interpreted as described in RFC 2119."; revision "2017-12-11" { description "Initial version"; reference "RFC XXXX: Voucher Profile for Constrained Devices"; } // Grouping defined for future usage grouping voucher-request-cwt-grouping { description "Grouping to allow reuse/extensions in future work."; uses v:voucher-artifact-grouping { augment "voucher" { description "Base the CWT voucher-request upon the regular one"; leaf proximity-registrar-subject-public-key-info { type binary; description "The proximity-registrar-subject-public-key-info replaces the proximit-registrar-cert in constrained uses of the voucher-request. The proximity-registrar-subject-public-key-info is the Raw Public Key of the Registrar. This field is encoded as specified in RFC7250, section 3. The ECDSA algorithm MUST be supported. The EdDSA algorithm as specified in <u>draft-ietf-tls-rfc4492bis-17</u> SHOULD be supported. Support for the DSA algorithm is not recommended. Support for the RSA algorithm is a MAY."; } } } } <CODE ENDS>

6.1.4. Example voucher request artifacts

TBD

6.2. Voucher artifact

The voucher's primary purpose is to securely assign a pledge to an owner. The voucher informs the pledge which entity it should consider to be its owner.

This document defines a voucher that is a CBOR encoded instance of the YANG module defined in $\underline{\text{Section 5.3}}$ that has been signed with CMS or with COSE.

6.3. Tree Diagram

```
module: ietf-cwt-voucher
  grouping voucher-cwt-grouping
    +---- voucher
       +---- created-on
             yang:date-and-time
       +---- expires-on?
              yang:date-and-time
       +--- assertion
                                                      enumeration
       +---- serial-number
                                                      string
       +---- idevid-issuer?
                                                      binary
       +---- pinned-domain-cert
                                                      binary
       +---- domain-cert-revocation-checks?
                                                      boolean
       +---- nonce?
                                                      binary
       +---- last-renewal-date?
             yang:date-and-time
       +---- pinned-domain-subject-public-key-info? binary
```

6.4. SID values

[EDNote: the appropriate generation of the SID values is under discussion]

```
SID Assigned to
   _____
    1001100 module ietf-cwt-voucher
    1001101 module ietf-restconf
    1001102 module ietf-voucher
    1001103 module ietf-yang-types
    1001104 data .../ietf-cwt-voucher:voucher
    1001105 data .../assertion
    1001106 data .../created-on
    1001107 data .../domain-cert-revocation-checks
    1001108 data .../expires-on
    1001109 data .../idevid-issuer
    1001110 data .../last-renewal-date
    1001111 data .../nonce
    1001112 data .../pinned-domain-cert
    1001113 data .../pinned-domain-subject-public-key-info
    1001114 data .../serial-number
6.5. YANG Module
  [EDNote: the appropriate syntax of the module is under discussion]
<CODE BEGINS> file "ietf-cwt-voucher@2017-12-11.yang"
/* -*- C -*- */
module ietf-cwt-voucher {
  yang-version 1.1;
  namespace
    "urn:ietf:params:xml:ns:yang:ietf-cwt-voucher";
  prefix "vcwt";
  import ietf-voucher {
    prefix "v";
  }
  organization
   "IETF 6tisch Working Group";
  contact
   "WG Web: <http://tools.ietf.org/wg/6tisch/>
    WG List: <mailto:6tisch@ietf.org>
    Author: Michael Richardson
              <mailto:mcr+ietf@sandelman.ca>";
  description
   "This module defines the format for a voucher, which is produced by
    a pledge's manufacturer or delegate (MASA) to securely assign one
    or more pledges to an 'owner', so that the pledges may establish a
```

}

<CODE ENDS>

```
secure connection to the owner's network infrastructure.
 This version provides a very restricted subset appropriate
  for very constrained devices.
  In particular, it assumes that nonce-ful operation is
  always required, that expiration dates are rather weak, as no
  clocks can be assumed, and that the Registrar is identified
  by a pinned Raw Public Key.
  The key words 'MUST', 'MUST NOT', 'REQUIRED', 'SHALL', 'SHALL NOT',
  'SHOULD', 'SHOULD NOT', 'RECOMMENDED', 'MAY', and 'OPTIONAL' in
  the module text are to be interpreted as described in RFC 2119.";
revision "2017-12-11" {
  description
  "Initial version";
  reference
   "RFC XXXX: Voucher Profile for Constrained Devices";
}
// Grouping defined for future usage
grouping voucher-cwt-grouping {
  description
    "Grouping to allow reuse/extensions in future work.";
  uses v:voucher-artifact-grouping {
    augment "voucher" {
      description "Base the CWT voucher upon the regular one";
      leaf pinned-domain-subject-public-key-info {
        type binary;
        description
          "The pinned-domain-subject replaces the
       pinned-domain-certificate in constrained uses of
       the voucher. The pinned-domain-public-key-info is the
       Raw Public Key of the Registrar. This field is encoded
       as specified in RFC7250, section 3.
       The ECDSA algorithm MUST be supported.
       The EdDSA algorithm as specified in
       <u>draft-ietf-tls-rfc4492bis-17</u> SHOULD be supported.
       Support for the DSA algorithm is not recommended.
       Support for the RSA algorithm is a MAY.";
      }
   }
 }
}
```

6.5.1. Example voucher artifacts

TBD

6.6. CMS format voucher and voucher-request artifacts

The IETF evolution of PKCS#7 is CMS [RFC5652]. The CMS signed voucher is much like the equivalent voucher defined in [I-D.ietf-anima-voucher].

A different eContentType of TBD1 is used to indicate that the contents are in a different format than in [I-D.ietf-anima-voucher].

The ContentInfo structure contains a payload consisting of the CBOR encoded voucher. The [I-D.ietf-core-yang-cbor] use of delta encoding creates a canonical ordering for the keys on the wire. This canonical ordering is not important as there is no expectation that the content will be reproduced during the validation process.

Normally the recipient is the pledge and the signer is the MASA.

[I-D.ietf-anima-bootstrapping-keyinfra] supports both signed and unsigned voucher requests from the pledge to the JRC. In this specification, voucher-request artifact is not signed from the pledge to the registrar. From the JRC to the MASA, the voucher-request artifact MUST be signed by the domain owner key which is requesting ownership.

The considerations of [RFC5652] section 5.1, concerning validating CMS objects which are really PKCS7 objects (cmsVersion=1) applies.

The CMS structure SHOULD also contain all the certificates leading up to and including the signer's trust anchor certificate known to the recipient. The inclusion of the trust anchor is unusual in many applications, but without it third parties can not accurately audit the transaction.

The CMS structure MAY also contain revocation objects for any intermediate certificate authorities (CAs) between the voucher-issuer and the trust anchor known to the recipient. However, the use of CRLs and other validity mechanisms is discouraged, as the pledge is unlikely to be able to perform online checks, and is unlikely to have a trusted clock source. As described below, the use of short-lived vouchers and/or pledge provided nonce provides a freshness guarantee.

6.7. COSE format voucher and voucher-request artifacts

This section to be added.

7. Design Considerations

The design considerations for the CBOR encoding of vouchers is much the same as for $[\underline{I-D.ietf-anima-voucher}]$.

One key difference is that the names of the leaves in the YANG does not have a material effect on the size of the resulting CBOR, as the SID translation process assigns integers to the names.

8. Security Considerations

8.1. Clock Sensitivity

TBD.

8.2. Protect Voucher PKI in HSM

TBD.

8.3. Test Domain Certificate Validity when Signing

TBD.

9. IANA Considerations

9.1. The IETF XML Registry

This document registers two URIs in the IETF XML registry [$\frac{RFC3688}{RFC3688}$]. Following the format in [$\frac{RFC3688}{RFC3688}$], the following registration is requested:

```
URI: urn:ietf:params:xml:ns:yang:ietf-cwt-voucher
Registrant Contact: The ANIMA WG of the IETF.
XML: N/A, the requested URI is an XML namespace.
```

URI: urn:ietf:params:xml:ns:yang:ietf-cwt-voucher-request Registrant Contact: The ANIMA WG of the IETF. XML: N/A, the requested URI is an XML namespace.

9.2. The YANG Module Names Registry

This document registers two YANG modules in the YANG Module Names registry [RFC6020]. Following the format defined in [RFC6020], the the following registration is requested:

name: ietf-cwt-voucher

namespace: urn:ietf:params:xml:ns:yang:ietf-cwt-voucher

prefix: vch
reference: RFC XXXX

name: ietf-cwt-voucher-request

namespace: urn:ietf:params:xml:ns:yang:ietf-cwt-voucher-request

prefix: vch
reference: RFC XXXX

9.3. The SMI Security for S/MIME CMS Content Type Registry

This document registers an OID in the "SMI Security for S/MIME CMS Content Type" registry (1.2.840.113549.1.9.16.1), with the value:

| Decimal | Description | References |
|---------|------------------------|------------|
| | | |
| TBD1 | id-ct-animaCBORVoucher | [ThisRFC] |

EDNOTE: should a separate value be used for Voucher Requests?

9.4. The SID registry

The SID range 1001100 was allocated by comi.space to the IETF-CWT-VOUCHER yang module.

The SID range 1001150 was allocated by comi.space to the IETF-CWT-VOUCHER-REQUEST yang module.

EDNOTE: it is unclear if there is further IANA work required.

9.5. Media-Type Registry

This section registers the 'application/voucher-cms+cbor' media type in the "Media Types" registry. These media types are used to indicate that the content is a CBOR voucher signed with a cms structure.

Type name: application

Subtype name: voucher-cms+cbor Required parameters: none Optional parameters: none

Encoding considerations: CMS-signed CBOR vouchers are CBOR

encoded.

Security considerations: See Security Considerations, Section Interoperability considerations: The format is designed to be broadly interoperable.

Published specification: THIS RFC.

Applications that use this media type: ANIMA, 6tisch, and other

zero-touch imprinting systems

Additional information:
 Magic number(s): None
 File extension(s): .cbor

Macintosh file type code(s): none

Person & email address to contact for further information: IETF

ANIMA WG

Intended usage: LIMITED
Restrictions on usage: NONE

Author: ANIMA WG

Change controller: IETF

Provisional registration? (standards tree only): NO

9.6. CoAP Content-Format Registry

Additions to the sub-registry "CoAP Content-Formats", within the "CoRE Parameters" registry are needed for the below media types. These can be registered either in the Expert Review range (0-255) or IETF Review range (256-9999). Addition: Type name: application Subtype name: voucher-cms+cbor ID: TBD2 Required parameters: None Optional parameters: None Encoding considerations: CBOR Security considerations: As defined in this specification Published specification: this document Applications that use this media type: ANIMA bootstrap (BRSKI)

10. Acknowledgements

TBD

11. References

11.1. Normative References

```
[I-D.ietf-ace-cbor-web-token]

Jones, M., Wahlstroem, E., Erdtman, S., and H. Tschofenig,

"CBOR Web Token (CWT)", <a href="mailto:draft-ietf-ace-cbor-web-token-12">draft-ietf-ace-cbor-web-token-12</a>
(work in progress), February 2018.
```

[I-D.ietf-anima-bootstrapping-keyinfra]

Pritikin, M., Richardson, M., Behringer, M., Bjarnason, S., and K. Watsen, "Bootstrapping Remote Secure Key Infrastructures (BRSKI)", draft-ietf-anima-bootstrapping-keyinfra-09 (work in progress), October 2017.

[I-D.ietf-anima-voucher]

Watsen, K., Richardson, M., Pritikin, M., and T. Eckert, "Voucher Profile for Bootstrapping Protocols", <u>draft-ietf-anima-voucher-07</u> (work in progress), January 2018.

[I-D.ietf-core-object-security]

Selander, G., Mattsson, J., Palombini, F., and L. Seitz, "Object Security for Constrained RESTful Environments (OSCORE)", draft-ietf-core-object-security-08 (work in progress), January 2018.

[I-D.ietf-core-sid]

Veillette, M. and A. Pelov, "YANG Schema Item iDentifier (SID)", <u>draft-ietf-core-sid-03</u> (work in progress), December 2017.

[I-D.ietf-core-yang-cbor]

Veillette, M., Pelov, A., Somaraju, A., Turner, R., and A. Minaburo, "CBOR Encoding of Data Modeled with YANG", draft-ietf-core-yang-cbor-06 (work in progress), February 2018.

[I-D.vanderstok-ace-coap-est]

Stok, P., Kampanakis, P., Kumar, S., Richardson, M., Furuhed, M., and S. Raza, "EST over secure CoAP (EST-coaps)", draft-vanderstok-ace-coap-est-04 (work in progress), January 2018.

[ieee802-1AR]

IEEE Standard, ., "IEEE 802.1AR Secure Device Identifier",
2009, <http://standards.ieee.org/findstds/
standard/802.1AR-2009.html>.

- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate
 Requirement Levels", BCP 14, RFC 2119,
 DOI 10.17487/RFC2119, March 1997,
 <https://www.rfc-editor.org/info/rfc2119>.

- [RFC7049] Bormann, C. and P. Hoffman, "Concise Binary Object
 Representation (CBOR)", RFC 7049, DOI 10.17487/RFC7049,
 October 2013, https://www.rfc-editor.org/info/rfc7049>.
- [RFC7250] Wouters, P., Ed., Tschofenig, H., Ed., Gilmore, J.,
 Weiler, S., and T. Kivinen, "Using Raw Public Keys in
 Transport Layer Security (TLS) and Datagram Transport
 Layer Security (DTLS)", RFC 7250, DOI 10.17487/RFC7250,
 June 2014, https://www.rfc-editor.org/info/rfc7250.

11.2. Informative References

[duckling]

Stajano, F. and R. Anderson, "The resurrecting duckling: security issues for ad-hoc wireless networks", 1999, https://www.cl.cam.ac.uk/~fms27/
papers/1999-StajanoAnd-duckling.pdf>.

- [I-D.ietf-netmod-yang-tree-diagrams]
 Bjorklund, M. and L. Berger, "YANG Tree Diagrams", draft ietf-netmod-yang-tree-diagrams-05 (work in progress),
 January 2018.
- [RFC6690] Shelby, Z., "Constrained RESTful Environments (CORE) Link Format", <u>RFC 6690</u>, DOI 10.17487/RFC6690, August 2012, https://www.rfc-editor.org/info/rfc6690.
- [RFC7030] Pritikin, M., Ed., Yee, P., Ed., and D. Harkins, Ed.,
 "Enrollment over Secure Transport", RFC 7030,
 DOI 10.17487/RFC7030, October 2013,
 https://www.rfc-editor.org/info/rfc7030.

Appendix A. EST messages to EST-coaps

This section extends the examples from $\underline{\mathsf{Appendix}\ \mathsf{A}}$ of $[\underline{\mathsf{I-D.vanderstok-ace-coap-est}}]$. The CoAP headers are only worked out for the enrollstatus example.

A.1. enrollstatus

```
A coaps enrollstatus message can be :
    GET coaps://[192.0.2.1:8085]/est/es
The corresponding coap header fields are shown below.
 Ver = 1
 T = 0 (CON)
  Code = 0x01 (0.01 is GET)
  Options
  Option1 (Uri-Host)
     Option Delta = 0x3 (option nr = 3)
     Option Length = 0x9
     Option Value = 192.0.2.1
  Option2 (Uri-Port)
     Option Delta = 0x4 (option nr = 4+3=7)
     Option Length = 0x4
     Option Value = 8085
  Option3 (Uri-Path)
     Option Delta = 0x4 (option nr = 7+4=11)
     Option Length = 0x7
     Option Value = /est/es
  Payload = [Empty]
A 2.05 Content response with an unsigned JSON voucher (ct=50) will
then be:
  2.05 Content (Content-Format: application/json)
     {payload}
With CoAP fields and payload:
  Ver=1
  T=2 (ACK)
  Code = 0x45 (2.05 Content)
    Option1 (Content-Format)
    Option Delta = 0xC (option nr 12)
     Option Length = 0x2
     Option Value = 0x32 (application/json)
     Payload =
    [EDNOTE: put here voucher payload ]
```

A.2. voucher_status

```
A coaps voucher_status message can be :

GET coaps://[2001:db8::2:1]:61616]/est/vs

A 2.05 Content response with a non signed JSON voucher (ct=50) will then be:

2.05 Content (Content-Format: application/json)
Payload =
[EDNOTE: put here voucher payload]
```

A.3. requestvoucher

```
A coaps requestvoucher message can be :
```

```
GET coaps://[2001:db8::2:1]:61616]/est/rv
```

A 2.05 Content response returning CBOR voucher signed with a cms structure(ct=TBD2) will then be:

```
2.05 Content (Content-Format: application/voucher-cms+cbor)
Payload =
[EDNOTE: put here encrypted voucher payload ]
```

A.4. requestauditing

```
A coaps requestauditing message can be:
```

```
GET coaps://[2001:db8::2:1]:61616]/est/ra
```

A 2.05 Content response with a COSE voucher (ct=16) will then be:

```
2.05 Content (Content-Format: application/cose)
Payload =
[EDNOTE: put here COSE voucher payload ]
```

Authors' Addresses

```
Michael Richardson
Sandelman Software Works
```

Email: mcr+ietf@sandelman.ca

Peter van der Stok vanderstok consultancy

Email: consultancy@vanderstok.org

Panos Kamapanakis Cisco Systems

Email: pkampana@cisco.com