

LAMPS Working Group  
Internet-Draft  
Intended status: Standards Track  
Expires: May 6, 2020

M. Richardson  
Sandelman Software Works  
T. Werner  
Siemens  
W. Pan  
Huawei Technologies  
November 03, 2019

**Clarification of Enrollment over Secure Transport (EST): transfer  
encodings and ASN.1  
draft-richardson-lamps-rfc7030est-clarify-05**

**Abstract**

This document updates [RFC7030](#): Enrollment over Secure Transport (EST) to resolve some errata that was reported, and which has proven to have interoperability when [RFC7030](#) has been extended.

This document deprecates the specification of "Content-Transfer-Encoding" headers for EST endpoints, providing a way to do this in an upward compatible way. This document additionally defines a GRASP discovery mechanism for EST endpoints, and specifies requirements for them.

Finally, this document fixes some syntactical errors in ASN.1 that was presented.

**Status of This Memo**

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <https://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on May 6, 2020.

## Copyright Notice

Copyright (c) 2019 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<https://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

## Table of Contents

<a href="#">1.</a>	Introduction . . . . .	<a href="#">2</a>
<a href="#">2.</a>	Terminology . . . . .	<a href="#">3</a>
<a href="#">3.</a>	Requirements Language . . . . .	<a href="#">3</a>
<a href="#">4.</a>	Changes to EST endpoint processing . . . . .	<a href="#">3</a>
<a href="#">5.</a>	Clarification of ASN.1 for Certificate Attribute set. . . . .	<a href="#">4</a>
<a href="#">5.1.</a>	CSR Attributes Response . . . . .	<a href="#">4</a>
<a href="#">6.</a>	Clarification of error messages for certificate enrollment operations . . . . .	<a href="#">6</a>
<a href="#">7.</a>	Privacy Considerations . . . . .	<a href="#">6</a>
<a href="#">8.</a>	Security Considerations . . . . .	<a href="#">6</a>
<a href="#">9.</a>	IANA Considerations . . . . .	<a href="#">6</a>
<a href="#">10.</a>	Acknowledgements . . . . .	<a href="#">6</a>
<a href="#">11.</a>	References . . . . .	<a href="#">6</a>
<a href="#">11.1.</a>	Normative References . . . . .	<a href="#">6</a>
<a href="#">11.2.</a>	Informative References . . . . .	<a href="#">7</a>
<a href="#">Appendix A.</a>	ASN.1 Module . . . . .	<a href="#">8</a>
	Authors' Addresses . . . . .	<a href="#">9</a>

## [1.](#) Introduction

[RFC7030] defines the Enrollment over Secure Transport, or EST protocol.

This specification defines a number of HTTP end points for certificate enrollment and management. The details of the transaction were defined in terms of MIME headers as defined in [\[RFC2045\]](#), rather than in terms of the HTTP protocol as defined in [\[RFC2616\]](#) and [\[RFC7230\]](#).

[RFC2616] and later [\[RFC7231\]](#) [Appendix A.5](#) has text specifically deprecating Content-Transfer-Encoding.



[RFC7030] calls it out this header incorrectly.

[I-D.ietf-anima-bootstrapping-keyinfra] extends [RFC7030], adding new functionality, and interop testing of the protocol has revealed that unusual processing called out in [RFC7030] causes confusion.

EST is currently specified as part of IEC 62351, and is widely used in Government, Utilities and Financial markets today.

Changes to [RFC7030] to bring it inline with typical HTTP processing would change the on-wire protocol in a way that is not backwards compatible. Reports from the field suggest that many implementations do not send the Content-Transfer-Encoding, and many of them ignore it.

This document therefore revises [RFC7030] to reflect the field reality, deprecating the extraneous field.

This document deals with errata numbers [errata4384], [errata5107], and [errata5108].

## **2. Terminology**

The abbreviation "CTE" is used to denote the Content-Transfer-Encoding header, and the abbreviation "CTE-base64" is used to denote a request or response whose Content-Transfer-Encoding header contains the value "base64".

## **3. Requirements Language**

In this document, the key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" are to be interpreted as described in [BCP 14](#), [RFC 2119](#) [RFC2119] and indicate requirement levels for compliant STuPiD implementations.

## **4. Changes to EST endpoint processing**

The [RFC7030] sections [4.1.3](#) (CA Certificates Response, /cacerts), 4.3.1/4.3.2 (Full CMC, /fullcmc), 4.4.2 (Server-Side Key Generation, /serverkeygen), and 4.5.2 (CSR Attributes, /csrattrs) specify the use of base64 encoding with a Content-Transfer-Encoding for requests and response.

This document updates [RFC7030] to require the POST request and payload response of all endpoints in to be [RFC4648] [section 4](#) Base64 encoded DER. This format is to be used regardless of whether there



is any Content-Transfer-Encoding header, and any value in that header is to be ignored.

## **5. Clarification of ASN.1 for Certificate Attribute set.**

[Section 4.5.2 of \[RFC7030\]](#) is to be replaced with the following text:

### **5.1. CSR Attributes Response**

If locally configured policy for an authenticated EST client indicates a CSR Attributes Response is to be provided, the server response MUST include an HTTP 200 response code. An HTTP response code of 204 or 404 indicates that a CSR Attributes Response is not available. Regardless of the response code, the EST server and CA MAY reject any subsequent enrollment requests for any reason, e.g., incomplete CSR attributes in the request.

Responses to attribute request messages MUST be encoded as the content-type of "application/csrattrs", and are to be "base64" [\[RFC2045\]](#) encoded. The syntax for application/csrattrs body is as follows:

```
CsrAttrs ::= SEQUENCE SIZE (0..MAX) OF AttrOrOID
```

```
AttrOrOID ::= CHOICE {  
    oid          OBJECT IDENTIFIER,  
    attribute    Attribute {{AttrSet}} }
```

```
AttrSet ATTRIBUTE ::= { AttributesDefinedInRFC7030, ... }
```

An EST server includes zero or more OIDs or attributes [\[RFC2986\]](#) that it requests the client to use in the certification request. The client MUST ignore any OID or attribute it does not recognize. When the server encodes CSR Attributes as an empty SEQUENCE, it means that the server has no specific additional information it desires in a client certification request (this is functionally equivalent to an HTTP response code of 204 or 404).

If the CA requires a particular crypto system or use of a particular signature scheme (e.g., certification of a public key based on a certain elliptic curve, or signing using a certain hash algorithm) it MUST provide that information in the CSR Attribute Response. If an EST server requires the linking of identity and POP information (see [Section 3.5](#)), it MUST include the challengePassword OID in the CSR Attributes Response.

The structure of the CSR Attributes Response SHOULD, to the greatest extent possible, reflect the structure of the CSR it is requesting.



Requests to use a particular signature scheme (e.g. using a particular hash function) are represented as an OID to be reflected in the SignatureAlgorithm of the CSR. Requests to use a particular crypto system (e.g., certification of a public key based on a certain elliptic curve) are represented as an attribute, to be reflected as the AlgorithmIdentifier of the SubjectPublicKeyInfo, with a type indicating the algorithm and the values indicating the particular parameters specific to the algorithm. Requests for descriptive information from the client are made by an attribute, to be represented as Attributes of the CSR, with a type indicating the [RFC2985] extensionRequest and the values indicating the particular attributes desired to be included in the resulting certificate's extensions.

The sequence is Distinguished Encoding Rules (DER) encoded [X690] and then base64 encoded (Section 4 of [RFC4648]). The resulting text forms the application/csrattr body, without headers.

For example, if a CA requests a client to submit a certification request containing the challengePassword (indicating that linking of identity and POP information is requested; see Section 3.5), an extensionRequest with the Media Access Control (MAC) address ([RFC2307]) of the client, and to use the secp384r1 elliptic curve and to sign with the SHA384 hash function. Then, it takes the following:

```
OID:      challengePassword (1.2.840.113549.1.9.7)

Attribute: type = extensionRequest (1.2.840.113549.1.9.14)
           value = macAddress (1.3.6.1.1.1.1.22)

Attribute: type = id-ecPublicKey (1.2.840.10045.2.1)
           value = secp384r1 (1.3.132.0.34)

OID:      ecdsaWithSHA384 (1.2.840.10045.4.3.3)
```

and encodes them into an ASN.1 SEQUENCE to produce: ~~~ 30 41 06 09 2a 86 48 86 f7 0d 01 09 07 30 12 06 07 2a 86 48 ce 3d 02 01 31 07 06 05 2b 81 04 00 22 30 16 06 09 2a 86 48 86 f7 0d 01 09 0e 31 09 06 07 2b 06 01 01 01 01 16 06 08 2a 86 48 ce 3d 04 03 03 ~~~

and then base64 encodes the resulting ASN.1 SEQUENCE to produce:

```
MEEGCSqGSib3DQIEJBzASBgqhkhjOPQIBMQcGBSuBBAAiMBYGCSqGSib3DQIEJDJEJ
BgcrBgEBAQEWBggqhkhjOPQQDAw==
```





## **6. Clarification of error messages for certificate enrollment operations**

errata 5108.

## **7. Privacy Considerations**

This document does not disclose any additional identifies to either active or passive observer would see with [[RFC7030](#)].

## **8. Security Considerations**

This document clarifies an existing security mechanism. An option is introduced to the security mechanism using an implicit negotiation.

## **9. IANA Considerations**

The ASN.1 module in [Appendix A](#) of this document makes use of object identifiers (OIDs). This document requests that IANA register an OID in the SMI Security for PKIX Arc in the Module identifiers subarc (1.3.6.1.5.5.7.0) for the ASN.1 module. The OID for the Asymmetric Decryption Key Identifier (1.2.840.113549.1.9.16.2.54) was previously defined in [[RFC7030](#)]. IANA is requested to update the "Reference" column for the Asymmetric Decryption Key Identifier attribute to also include a reference to this document.

## **10. Acknowledgements**

This work was supported by the Huawei Technologies.

The ASN.1 Module was assembled by Russ Housley and formatted by Sean Turner.

## **11. References**

### **11.1. Normative References**

- [I-D.ietf-anima-bootstrapping-keyinfra]  
Pritikin, M., Richardson, M., Eckert, T., Behringer, M.,  
and K. Watsen, "Bootstrapping Remote Secure Key  
Infrastructures (BRSKI)", [draft-ietf-anima-bootstrapping-keyinfra-29](#) (work in progress), October 2019.
- [RFC2045] Freed, N. and N. Borenstein, "Multipurpose Internet Mail  
Extensions (MIME) Part One: Format of Internet Message  
Bodies", [RFC 2045](#), DOI 10.17487/RFC2045, November 1996,  
<<https://www.rfc-editor.org/info/rfc2045>>.



- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), DOI 10.17487/RFC2119, March 1997, <<https://www.rfc-editor.org/info/rfc2119>>.
- [RFC2986] Nystrom, M. and B. Kaliski, "PKCS #10: Certification Request Syntax Specification Version 1.7", [RFC 2986](#), DOI 10.17487/RFC2986, November 2000, <<https://www.rfc-editor.org/info/rfc2986>>.
- [RFC4648] Josefsson, S., "The Base16, Base32, and Base64 Data Encodings", [RFC 4648](#), DOI 10.17487/RFC4648, October 2006, <<https://www.rfc-editor.org/info/rfc4648>>.
- [RFC7030] Pritikin, M., Ed., Yee, P., Ed., and D. Harkins, Ed., "Enrollment over Secure Transport", [RFC 7030](#), DOI 10.17487/RFC7030, October 2013, <<https://www.rfc-editor.org/info/rfc7030>>.
- [X680] ITU-T, "Information technology - Abstract Syntax Notation One.", ISO/IEC 8824-1:2002, 2002.
- [X681] ITU-T, "Information technology - Abstract Syntax Notation One: Information Object Specification.", ISO/IEC 8824-2:2002, 2002.
- [X682] ITU-T, "Information technology - Abstract Syntax Notation One: Constraint Specification.", ISO/IEC 8824-2:2002, 2002.
- [X683] ITU-T, "Information technology - Abstract Syntax Notation One: Parameterization of ASN.1 Specifications.", ISO/IEC 8824-2:2002, 2002.
- [X690] ITU-T, "Information technology - ASN.1 encoding Rules: Specification of Basic Encoding Rules (BER), Canonical Encoding Rules (CER) and Distinguished Encoding Rules (DER).", ISO/IEC 8825-1:2002, 2002.

## **11.2. Informative References**

- [errata4384] "EST errata 4384: ASN.1 encoding error", n.d., <<https://www.rfc-editor.org/errata/eid4384>>.
- [errata5107] "EST errata 5107: use Content-Transfer-Encoding", n.d., <<https://www.rfc-editor.org/errata/eid5107>>.



**[errata5108]**

"EST errata 5108: use of Content-Type for error message",  
n.d., <<https://www.rfc-editor.org/errata/eid5108>>.

[RFC2307] Howard, L., "An Approach for Using LDAP as a Network  
Information Service", [RFC 2307](#), DOI 10.17487/RFC2307,  
March 1998, <<https://www.rfc-editor.org/info/rfc2307>>.

[RFC2616] Fielding, R., Gettys, J., Mogul, J., Frystyk, H.,  
Masinter, L., Leach, P., and T. Berners-Lee, "Hypertext  
Transfer Protocol -- HTTP/1.1", [RFC 2616](#),  
DOI 10.17487/RFC2616, June 1999,  
<<https://www.rfc-editor.org/info/rfc2616>>.

[RFC2985] Nystrom, M. and B. Kaliski, "PKCS #9: Selected Object  
Classes and Attribute Types Version 2.0", [RFC 2985](#),  
DOI 10.17487/RFC2985, November 2000,  
<<https://www.rfc-editor.org/info/rfc2985>>.

[RFC7230] Fielding, R., Ed. and J. Reschke, Ed., "Hypertext Transfer  
Protocol (HTTP/1.1): Message Syntax and Routing",  
[RFC 7230](#), DOI 10.17487/RFC7230, June 2014,  
<<https://www.rfc-editor.org/info/rfc7230>>.

[RFC7231] Fielding, R., Ed. and J. Reschke, Ed., "Hypertext Transfer  
Protocol (HTTP/1.1): Semantics and Content", [RFC 7231](#),  
DOI 10.17487/RFC7231, June 2014,  
<<https://www.rfc-editor.org/info/rfc7231>>.

**[Appendix A](#). ASN.1 Module**

This annex provides the normative ASN.1 definitions for the  
structures described in this specification using ASN.1 as defined in  
[\[X680\]](#) through [\[X683\]](#).

There is no ASN.1 Module in [RFC 7030](#). This module has been created  
by combining the lines that are contained in the document body.

PKIXEST-2019

```
{ iso(1) identified-organization(3) dod(6)
  internet(1) security(5) mechanisms(5) pkix(7) id-mod(0)
  id-mod-est-2019(TBD) }
```

DEFINITIONS IMPLICIT TAGS ::=
BEGIN

-- EXPORTS ALL --



## IMPORTS

## Attribute

```
FROM CryptographicMessageSyntax-2010 -- [RFC6268]
    { iso(1) member-body(2) us(840) rsadsi(113549)
      pkcs(1) pkcs-9(9) smime(16) modules(0)
      id-mod-cms-2009(58) }
```

## ATTRIBUTE

```
FROM PKIX-CommonTypes-2009
    { iso(1) identified-organization(3) dod(6) internet(1) security(5)
      mechanisms(5) pkix(7) id-mod(0) id-mod-pkixCommon-02(57) } ;
```

```
-- CSR Attributes
```

```
CsrAttrs ::= SEQUENCE SIZE (0..MAX) OF AttrOrOID
```

```
AttrOrOID ::= CHOICE {
    oid          OBJECT IDENTIFIER,
    attribute    Attribute {{AttrSet}} }
```

```
AttrSet ATTRIBUTE ::= { AttributesDefinedInRFC7030, ... }
```

```
-- Asymmetric Decrypt Key Identifier Attribute
```

```
AttributesDefinedInRFC7030 ATTRIBUTE ::= { aa-asymmDecryptKeyID, ... }
```

```
aa-asymmDecryptKeyID ATTRIBUTE ::=
    { TYPE AsymmetricDecryptKeyIdentifier
      IDENTIFIED BY id-aa-asymmDecryptKeyID }
```

```
id-aa-asymmDecryptKeyID OBJECT IDENTIFIER ::= { iso(1) member-body(2)
    us(840) rsadsi(113549) pkcs(1) pkcs9(9) smime(16) aa(2) 54 }
```

```
AsymmetricDecryptKeyIdentifier ::= OCTET STRING
```

```
END
```

## Authors' Addresses

Michael Richardson  
Sandelman Software Works  
  
Email: mcr+ietf@sandelman.ca





Thomas Werner  
Siemens

Email: [thomas-werner@siemens.com](mailto:thomas-werner@siemens.com)

Wei Pan  
Huawei Technologies

Email: [william.panwei@huawei.com](mailto:william.panwei@huawei.com)