

Internet Engineering Task Force  
Internet-Draft  
Intended status: Standards Track  
Expires: April 19, 2015

E. Rosen, Ed.  
Juniper Networks, Inc.  
M. Sivakumar  
IJ. Wijnands  
Cisco Systems, Inc.  
S. Aldrin  
Huawei Technologies  
A. Dolganow  
Alcatel-Lucent  
T. Przygienda  
Ericsson  
October 16, 2014

Multicast VPN Using BIER  
draft-rosen-l3vpn-mvpn-bier-01

## Abstract

The Multicast Virtual Private Network (MVPN) specifications require the use of multicast tunnels ("P-tunnels") that traverse a Service Provider's backbone network. The P-tunnels are used for carrying multicast traffic across the backbone. A variety of P-tunnel types are supported. Bit Index Explicit Replication (BIER) is a new architecture that provides optimal multicast forwarding through a "multicast domain", without requiring intermediate routers to maintain any per-flow state or to engage in an explicit tree-building protocol. This document specifies the protocol and procedures that allow MVPN to use BIER as the method of carrying multicast traffic over an SP backbone network.

## Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <http://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on April 19, 2015.

Internet-Draft

MVPN with BIER

October 2014

## Copyright Notice

Copyright (c) 2014 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

## Table of Contents

<a href="#">1.</a>	Introduction . . . . .	<a href="#">2</a>
<a href="#">2.</a>	Use of the PMSI Tunnel Attribute . . . . .	<a href="#">4</a>
<a href="#">3.</a>	Explicit Tracking . . . . .	<a href="#">6</a>
<a href="#">4.</a>	Data Plane . . . . .	<a href="#">6</a>
<a href="#">5.</a>	IANA Considerations . . . . .	<a href="#">7</a>
<a href="#">6.</a>	Security Considerations . . . . .	<a href="#">7</a>
<a href="#">7.</a>	References . . . . .	<a href="#">7</a>
<a href="#">7.1.</a>	Normative References . . . . .	<a href="#">7</a>
<a href="#">7.2.</a>	Informative References . . . . .	<a href="#">8</a>
	Authors' Addresses . . . . .	<a href="#">8</a>

[1.](#) Introduction

[RFC6513] and [[RFC6514](#)] specify the protocols and procedures that a Service Provider (SP) can use to provide Multicast Virtual Private Network (MVPN) service to its customers. Multicast tunnels are created through an SP's backbone network; these are known as "P-tunnels". The P-tunnels are used for carrying multicast traffic across the backbone. The MVPN specifications allow the use of several different kinds of P-tunnel technology.

Bit Index Explicit Replication (BIER) ([\[BIER\\_ARCH\]](#)) is an architecture that provides optimal multicast forwarding through a "multicast domain", without requiring intermediate routers to maintain any per-flow state or to engage in an explicit tree-building protocol. The purpose of the current document is to specify the

protocols and procedures needed in order to provide MVPN service using BIER to transport the multicast traffic over the backbone.

Although BIER does not explicitly build and maintain multicast tunnels, one can think of BIER as using a number of implicitly

created tunnels through a "BIER domain". In particular, one can think of there as being one Point-to-Multipoint (P2MP) tunnel from each "Bit Forwarding Ingress Router" (BFIR) to all the "Bit Forwarding Egress Routers" (BFERs) in the BIER domain, where a BIER domain is generally co-extensive with an IGP network. These "tunnels" are not specific to any particular VPN. However, the MVPN architecture provides protocols and procedures that allow the traffic of multiple MVPNs to be aggregated on a single P-tunnel. In this document, we specify how to use these multi-VPN aggregation procedures to enable BIER to transport traffic from multiple MVPNs.

MVPN traffic must sometimes traverse more than one IGP domain, whereas BIER only carries multicast traffic within a single IGP domain. However, the MVPN specifications allow P-tunnels to be "segmented", where the segmentation points may either be Autonomous System Border Routers (ASBRs), as described in [[RFC6514](#)], or Area Border Routers (ABRs), as described in [[SEAMLESS MCAST](#)]. As long as the segmentation points are capable of acting as BFIRs and BFERs, BIER can be used to provide some or all of the segments of a P-tunnel.

This document uses the following terminology from [[BIER ARCH](#)]:

- o BFR: Bit-Forwarding Router.
- o BFIR: Bit-Forwarding Ingress Router.
- o BFER: Bit-Forwarding Egress Router.

This document uses the following terminology from [[RFC6513](#)]:

- o MVPN: Multicast Virtual Private Network -- a VPN [L3VPN] in which multicast service is offered.
- o P-tunnel. A multicast tunnel through the network of one or more SPs. P-tunnels are used to transport MVPN multicast data

- o C-S: A multicast source address, identifying a multicast source located at a VPN customer site.
- o C-G: A multicast group address used by a VPN customer.
- o C-flow: A customer multicast flow. Each C-flow is identified by the ordered pair (source address, group address), where each address is in the customer's address space. The identifier of a particular C-flow is usually written as (C-S,C-G). Sets of C-flows can be identified by the use of the "C-\*" wildcard (see [[RFC6625](#)]), e.g., (C-\*,C-G).

- o I-PMSI A-D Route: Inclusive Provider Multicast Service Interface Auto-Discovery route. Carried in BGP Update messages, these routes are used to advertise the "default" P-tunnel for a particular MVPN.
- o S-PMSI A-D route: Selective Provider Multicast Service Interface Auto-Discovery route. Carried in BGP Update messages, these routes are used to advertise the fact that particular C-flows are bound to (i.e., are traveling through) particular P-tunnels.
- o PMSI Tunnel attribute (PTA). This BGP attribute carried is used to identify a particular P-tunnel. When C-flows of multiple VPNs is carried in a single P-tunnel, this attribute also carries the information needed to multiplex and demultiplex the C-flows.

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [RFC 2119](#) [[RFC2119](#)].

## [2.](#) Use of the PMSI Tunnel Attribute

As defined in [[RFC6514](#)], the PMSI Tunnel attribute is used to identify the particular P-tunnel to which one or more multicast flows are being assigned.

The PMSI Tunnel attribute (PTA) contains the following fields:

- o "Tunnel Type". IANA is requested to assign a new tunnel type codepoint for "BIER". This codepoint will be used to indicate

that the PMSI is instantiated by BIER.

- o "Tunnel Identifier". When the "tunnel type" field is "BIER", this field contains the BFR-Prefix (see [[BIER\\_ARCH](#)]) of the originator of the route that is carrying the PMSI Tunnel attribute. This will either be a /32 IPv4 address or a /128 IPv6 address. Whether the address is IPv4 or IPv6 can be inferred from the total length of the PMSI Tunnel attribute.
- o "MPLS label". This field contains an upstream-assigned MPLS label. It is assigned by the router that originates the BGP route to which the PTA is attached. Constraints on the way in which the originating router selects this label are discussed below.
- o "Leaf Info Required Bit". The setting of this bit depends upon the type of route and the NLRI of the route that carries the PTA.
  - \* In an I-PMSI A-D route or a (C-\*,C-\*) S-PMSI A-D route, the bit SHOULD be clear.

- \* In other S-PMSI A-D routes, the bit SHOULD be set.

Note that if a PTA specifying "BIER" is attached to an I-PMSI or S-PMSI A-D route, the route MUST NOT be distributed beyond the boundaries of a BIER domain. That is, any routers that receive the route must be in the same BIER domain as the originator of the route. If the originator is in more than one BIER domain, the route must be distributed only within the BIER domain in which the BFR-Prefix in the PTA uniquely identifies the originator. As with all MVPN routes, distribution of these routes is controlled by the provisioning of Route Targets.

Suppose an ingress PE originates two x-PMSI A-D routes, where we use the term "x-PMSI" to mean "I-PMSI or S-PMSI". Suppose both routes carry a PTA, and the PTA of each route specifies "BIER".

- o If the two routes do not carry the same set of Route Targets (RTs), then their respective PTAs MUST contain different MPLS label values.
- o If the ingress PE is supporting MVPN extranet ([[EXTRANET](#)]) functionality, and if the two routes originate from different

VRFs, then the respective PTAs of the two routes MUST contain different MPLS label values.

- o If the ingress PE is supporting the "Extranet Separation" feature of MVPN extranet (see Section 7.3 of [[EXTRANET](#)], section ), and if one of the routes carries the "Extranet Separation" extended community and the other does not, then the respective PTAs of the two routes MUST contain different MPLS label values.

When segmented P-tunnels are being used, an ABR or ASBR may receive, from a BIER domain, an x-PMSI A-D route whose PTA specifies "BIER". This means that BIER is being used for one segment of a segmented P-tunnel. The ABR/ASBR may in turn need to originate an x-PMSI A-D route whose PTA identifies the next segment of the P-tunnel. The next segment may also be "BIER". Suppose an ASBR receives x-PMSI A-D routes R1 and R2, and as a result originates x-PMSI A-D routes R3 and R4 respectively, where the PTAs of each of the four routes specify a BIER.. Then the PTAs of R3 and R4 MUST NOT specify the same MPLS label, UNLESS both of the following conditions hold:

- o R1 and R2 have the same "originating router" in their respective NLRIs.
- o R1 and R2 specify the same MPLS label in their respective PTAs.

### [3.](#) Explicit Tracking

When using BIER to transport an MVPN data packet through a BIER domain, an ingress PE functions as a BFIR (see [[BIER ARCH](#)]). The BFIR must determine the set of BFERs to which the packet needs to be delivered. This is done by using the explicit tracking mechanism specified in [[RFC6513](#)] and [[RFC6514](#)].

To determine the set of BFERs to which a given MVPN data packet needs to be delivered, the BFIR originating an S-PMSI A-D route sets the LIR bit in the route's PTA. Per [[RFC6514](#)], the BFERs will respond with Leaf A-D routes. By matching the received Leaf A-D routes to the originated S-PMSI A-D routes, the originator of the S-PMSI A-D route determines the set of BFERs that need to receive the multicast data flow (or flows) that is (are) identified in the NLRI of the of

the S-PMSI A-D route.

This requires that each BFIR originate an S-PMSI A-D route for each C-flow for which it serves as BFIR. The BFIR MAY include, in each such route, a PTA as described in [Section 2](#). However, if the BFIR has originated an I-PMSI A-D route or a wildcard S-PMSI A-D route that "matches" (according to the rules of [\[RFC6625\]](#)) a particular C-flow, then it may do explicit tracking for that C-flow by originating an S-PMSI A-D route for that C-flow, but including a PTA that specifies "no tunnel type".

#### [4.](#) Data Plane

The MVPN application plays the role of the "multicast flow layer" as described in [\[BIER ARCH\]](#).

To transmit an MVPN data packet, an ingress PE follows the rules of [\[RFC6625\]](#) to find the S-PMSI A-D route or I-PMSI A-D route that is a "match for transmission" for that packet. (In applying the rules of [\[RFC6625\]](#), any S-PMSI A-D route with a PTA specifying "no tunnel information" is ignored.) If the matching route has a PTA specifying a "BIER", the (upstream-assigned) MPLS label from that PTA is pushed on the packet's label stack. Then the packet is forwarded according to the procedures of [\[BIER ARCH\]](#) and [\[BIER ENCAPS\]](#). (See especially [Section 4](#), "Imposing and Processing the BIER Encapsulation", of [\[BIER ENCAPS\]](#).) Since the "payload" (as defined in [\[BIER ENCAPS\]](#)) is an MPLS packet with an upstream-assigned label, the BIER header MUST have the "I bit" set, and the BFIR-id MUST be included in the BIER header.

When a BFER receives an MVPN multicast data packet that has been BIER-encapsulated, the BIER layer passes the following information to the multicast flow layer:

- o The BFR-prefix corresponding to the BFR-id in the BIER header.
- o The "payload", which is an MPLS packet whose top label is an upstream-assigned label. The BFR-prefix provides the "context" in which the upstream-assigned label is interpreted.

#### [5.](#) IANA Considerations

IANA is requested to assign a value for "BIER" from the "P-Multicast Service Interface Tunnel (PMSI Tunnel) Tunnel Types" registry. The reference should be this document.

## 6. Security Considerations

The security considerations of [[BIER\\_ARCH](#)], [[BIER\\_ENCAPS](#)], [[RFC6513](#)] and [[RFC6514](#)] are applicable.

## 7. References

### 7.1. Normative References

[BIER\_ARCH]

Wijnands, IJ., "Multicast using Bit Index Explicit Replication Architecture", internet-draft [draft-wijnands-bier-architecture-00](#), September 2014.

[BIER\_ENCAPS]

Wijnands, IJ., "Multicast using Bit Index Explicit Replication Architecture", internet-draft [draft-wijnands-mpls-bier-encapsulation-00](#), September 2014.

[RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), March 1997.

[RFC6513] Rosen, E. and R. Aggarwal, "Multicast in MPLS/BGP IP VPNs", [RFC 6513](#), February 2012.

[RFC6514] Aggarwal, R., Rosen, E., Morin, T., and Y. Rekhter, "BGP Encodings and Procedures for Multicast in MPLS/BGP IP VPNs", [RFC 6514](#), February 2012.

[RFC6625] Rosen, E., Rekhter, Y., Hendrickx, W., and R. Qiu, "Wildcards in Multicast VPN Auto-Discovery Routes", [RFC 6625](#), May 2012.

### 7.2. Informative References



[EXTRANET]

Rekhter, Y. and E. Rosen, "Extranet Multicast in BGP/IP MPLS VPNs", internet-draft [draft-ietf-l3vpn-mvpn-extranet-05](#), July 2014.

[SEAMLESS\_MCAST]

Rekhter, Y., Aggarwal, R., Morin, T., Grosclaude, I., Leymann, N., and S. Saad, "Inter-Area P2MP Segmented LSPs", internet-draft [draft-ietf-mpls-seamless-mcast-14](#), June 2014.

Authors' Addresses

Eric C. Rosen (editor)  
Juniper Networks, Inc.  
10 Technology Park Drive  
Westford, Massachusetts 01886  
US

Email: [erosen@juniper.net](mailto:erosen@juniper.net)

Mahesh Sivakumar  
Cisco Systems, Inc.  
510 McCarthy Blvd  
Milpitas, California 95035  
US

Email: [masivaku@cisco.com](mailto:masivaku@cisco.com)

IJsbrand Wijnands  
Cisco Systems, Inc.  
De Kleetlaan 6a  
Diegem 1831  
BE

Email: [ice@cisco.com](mailto:ice@cisco.com)

Sam K Aldrin  
Huawei Technologies  
2330 Central Express Way  
Santa Clara, California  
US

Email: [aldrin.ietf@gmail.com](mailto:aldrin.ietf@gmail.com)

Andrew Dolganow  
Alcatel-Lucent  
600 March Rd.  
Ottawa, Ontario K2K 2E6  
CA

Email: [andrew.dolganow@alcatel-lucent.com](mailto:andrew.dolganow@alcatel-lucent.com)

Tony Przygienda  
Ericsson  
300 Holger Way  
San Jose, California 95134  
US

Email: [antoni.przygienda@ericsson.com](mailto:antoni.przygienda@ericsson.com)

