

Calendar and Scheduling
Internet-Draft
Expires: February 9, 2006

D. Royer
IntelliCal, LLC
G. Babics
Oracle
P. Hill
Massachusetts Institute of
Technology
S. Mansour
AOL/Netscape
August 8, 2005

Calendar Access Protocol (CAP)
draft-royer-calsch-cap-03

Status of this Memo

By submitting this Internet-Draft, each author represents that any applicable patent or other IPR claims of which he or she is aware have been or will be disclosed, and any of which he or she becomes aware will be disclosed, in accordance with [Section 6 of BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF), its areas, and its working groups. Note that other groups may also distribute working documents as Internet-Drafts.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

The list of current Internet-Drafts can be accessed at
<http://www.ietf.org/ietf/lid-abstracts.txt>.

The list of Internet-Draft Shadow Directories can be accessed at
<http://www.ietf.org/shadow.html>.

This Internet-Draft will expire on February 9, 2006.

Copyright Notice

Copyright (C) The Internet Society (2005).

Abstract

The Calendar Access Protocol (CAP) is an Internet protocol described in this memo that permits a Calendar User (CU) to utilize a Calendar

Internet-Draft

Calendar Access Protocol (CAP)

August 2005

User Agent (CUA) to access an [[iCAL](#)] based Calendar Store (CS).

At the time of this writing there are three vendors implementing CAP. It has already been determined that some changes are needed. In order to get implementation experience the participants felt that CAP needed to be released so that many years of work could be preserved. Many properties in CAP can be used by other iCalendar protocols and have had many years of debate.

Table of Contents

1.	Introduction	5
1.1	Formatting Conventions	5
1.2	Related Documents	6
1.3	Definitions	7
2.	Additions to iCalendar	12
2.1	New Value Types (summary)	15
2.1.1	New Parameters (summary)	15
2.1.2	New or Updated Properties (summary)	16
2.1.3	New Components (summary)	18
2.2	Relationship of RFC-2446 (ITIP) and CAP	19
3.	CAP Design	22
3.1	System Model	22
3.2	Calendar Store Object Model	22
3.3	Protocol Model	23
3.3.1	Use of BEEP, MIME and iCalendar	24
4.	Security Model	26
4.1	Calendar User and UPNs	26
4.1.1	UPNs and Certificates	26
4.1.2	Anonymous Users and Authentication	27
4.1.3	User Groups	27
4.2	Access Rights	28
4.2.1	Access Control and NOCONFLICT	28
4.2.2	Predefined VCARS	28
4.2.3	Decreed VCARS	30
4.3	CAP Session Identity	31
5.	CAP URL and Calendar Address	33
6.	New Value Types	35
6.1	Property Value Data Types	35
6.1.1	CAL-QUERY Value Type	35
6.1.2	UPN Value Type	51
6.1.3	UPN-FILTER Value	52
7.	New Parameters	55

7.1	ACTION Parameter	55
7.2	ENABLE Parameter	55
7.3	ID Parameter	56
7.4	LATENCY Parameter	57
7.5	LOCAL Parameter	58

7.6	LOCALIZE Parameter	58
7.7	OPTIONS Parameter	59
8.	New Properties	61
8.1	ALLOW-CONFLICT Property	61
8.2	ATT-COUNTER Property	61
8.3	CALID Property	62
8.4	CALMASTER Property	63
8.5	CAP-VERSION Property	63
8.6	CARID Property	64
8.7	CAR-LEVEL Property	65
8.8	COMPONENTS Property	65
8.9	CSID Property	67
8.10	DECREED Property	67
8.11	DEFAULT-CHARSET Property	68
8.12	DEFAULT-LOCALE Property	69
8.13	DEFAULT-TZID Property	70
8.14	DEFAULT-VCARS Property	71
8.15	DENY Property	72
8.16	EXPAND property	72
8.17	GRANT Property	73
8.18	ITIP-VERSION Property	74
8.19	MAX-COMP-SIZE Property	74
8.20	MAXDATE Property	75
8.21	MINDATE Property	76
8.22	MULTIPART Property	76
8.23	NAME Property	77
8.24	OWNER Property	78
8.25	PERMISSION Property	79
8.26	QUERY property	79
8.27	QUERYID property	80
8.28	QUERY-LEVEL Property	81
8.29	RECUR-ACCEPTED Property	81
8.30	RECUR-LIMIT Property	82
8.31	RECUR-EXPAND Property	83
8.32	RESTRICTION Property	83
8.33	SCOPE Property	84

8.34	STORES-EXPANDED Property	85
8.35	TARGET Property	86
8.36	TRANSP Property	86
9.	New Components	88
9.1	VAGENDA Component	88
9.2	VCALSTORE Component	90
9.3	VCAR Component	92
9.4	VRIGHT Component	95
9.5	VREPLY Component	96
9.6	VQUERY Component	96
10.	Commands and Responses	98
10.1	CAP Commands (CMD)	98

10.1.1	Bounded Latency	99
10.2	ABORT Command	101
10.3	CONTINUE Command	102
10.4	CREATE Command	103
10.5	DELETE Command	109
10.6	GENERATE-UID Command	112
10.7	GET-CAPABILITY Command	114
10.8	IDENTIFY Command	117
10.9	MODIFY Command	120
10.10	MOVE Command	124
10.11	REPLY Response to a Command	127
10.12	SEARCH Command	128
10.12.1	Searching for VFREEBUSY	131
10.13	SET-LOCALE Command	132
10.14	TIMEOUT Command	134
10.15	Response Codes	134
11.	Object Registration	137
11.1	Registration of New and Modified Entities	137
11.2	Post the item definition	137
11.3	Allow a comment period	137
11.4	Release a new RFC	137
12.	BEEP and CAP	138
12.1	BEEP Profile Registration	138
12.2	BEEP Exchange Styles	140
12.3	BEEP connection details	140
13.	IANA Considerations	143
14.	Security Considerations	144
	Authors' Addresses	145
A.	Acknowledgments	146

B.	Bibliography	147
	Intellectual Property and Copyright Statements	149

[1.](#) Introduction

This document specifies how a Calendar CUA interacts with a CS to manage calendar information. In particular, it specifies how to query, create, modify, and delete iCalendar components (e.g., events, to-dos, or daily journal entries). It further specifies how to search for available busy time information. Synchronization with CUAs is not covered and believed to be possible using CAP.

CAP is specified as a [\[BEEP\]](#) "profile". As such, many aspects of the protocol (e.g., authentication and privacy) are provided within [\[BEEP\]](#). The protocol data units leverage the standard iCalendar format [\[iCAL\]](#) to convey calendar related information.

CAP can also be used to store and fetch [\[iTIP\]](#) objects and when those objects are used in this memo, they mean exactly the same as defined in [\[iTIP\]](#). When iCalendar objects are transferred between the CUA and a CS, some additional properties and parameters may be added and the CUA is responsible for correctly generating iCalendar objects to non CAP processes.

The definition of new components, properties, parameter's, and value

types are broken into two parts. The first part summarizes and defines the new objects. The second part provides the detail and any ABNF for those objects. The ABNF in CAP as in other iCalendar specifications is order independent. That is properties in a component may occur in any order and parameters in any property may occur in any order.

1.1 Formatting Conventions

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY" and "OPTIONAL" in this document are to be interpreted as described in [[RFCWORDS](#)].

Calendaring and scheduling roles are referred to in quoted-strings of text with the first character of each word in upper case. For example, "Organizer" refers to a role of a "Calendar User" (CU) within the protocol defined by [[iTIP](#)]. Calendar components defined by [[iCAL](#)] are referred to with capitalized, quoted-strings of text. All iCalendar components should start with the letter "V". For example, "VEVENT" refers to the event calendar component, "VTODO" refers to the to-do component and "VJOURNAL" refers to the daily journal component.

Scheduling methods defined by [[iTIP](#)], are referred to with capitalized, quoted-strings of text. For example, "REPLY" refers to the method for replying to a "REQUEST".

CAP commands are referred to by upper-case, quoted-strings of text, followed by the word "command". For example, "CREATE" command refers to the command for creating a calendar entry, "SEARCH" command refers to the command for reading calendar components. CAP Commands are named using the "CMD" property.

Properties defined by this memo are referred to with capitalized, quoted-strings of text, followed by the word "property". For example, "ATTENDEE" property refers to the iCalendar property used to convey the calendar address that has been invited to a "VEVENT" or "VTODO" component.

Property parameters defined by this memo are referred to with capitalized, quoted-strings of text, followed by the word "parameter". For example, "PARTSTAT" parameter refers to the

iCalendar property parameter used to specify the participation status of an attendee. Enumerated values defined by this memo are referred to with capitalized text, either alone or followed by the word "value".

Object states defined by this memo are referred to with capitalized, quoted-strings of text, followed by the word "state". For example, "BOOKED" state refers to an object in the booked state.

Within a query, the different parts are referred to as a "clause" and its value as "clause value" and the clause name will be in uppercase enclosed in quotes. Example, The "SELECT" clause or if the "SELECT" clause value contains ...

In tables, the quoted-string text is specified without quotes in order to minimize the table length.

[1.2](#) Related Documents

Implementers will need to be familiar with several other memos that, along with this one, describe the Internet calendaring and scheduling standards. These documents are:

[iCAL] - ([RFC2445](#)) Which specifies the objects, data types, properties and property parameters used in the protocols, along with the methods for representing and encoding them.

[iTIP] - ([RFC2446](#)) Which specifies an interoperability protocol for scheduling between different installations.

[iMIP] - ([RFC2447](#)) Which specifies the Internet email binding for [[iTIP](#)].

[GUIDE] - ([RFC3283](#)), a guide to implementers and describes the elements of a calendaring system, how they interact with each other, how they interact with end users, and how the standards and protocols are used.

This memo does not attempt to repeat the specification of concepts and definitions from these other memos. Where possible, references are made to the memo that provides for the specification of these concepts and definitions.

1.3 Definitions

BOOKED - An object in the calendar store has one of three conceptual states. It is in the "UNPROCESSED" state, "BOOKED" state, or marked for deletion which is the "DELETED" state. How the implementation stores the state of any object is not a protocol issues and is not discussed. An object can be said to be booked, unprocessed, or marked for delete.

1. An "UNPROCESSED" state scheduling object has been stored in the calendar store but has not been acted on by a CU or CUA. All scheduled entries are [[iTIP](#)] objects. All [[iTIP](#)] objects in the store are not in the "BOOKED" state. To retrieve any [[iTIP](#)] object, simply do a query asking for any objects that are stored in the "UNPROCESSED" state.
2. A "BOOKED" state entry is stored with the "CREATE" command. It is an object that has been acted on by a CU or CUA and there has been a decision to store an object. To retrieve any booked object, simply do a query asking for any objects that were stored in the "BOOKED" state.
3. A "DELETED" state entry is created by sending a "DELETE" command with the "OPTION" parameter value set to "MARK". To retrieve any deleted object, simply do a query asking for any objects that were stored in the "DELETED" state. By default objects marked for delete are not returned. The CUA must specifically ask for marked for delete objects. You can not ask for components in the "DELETED" state and in other states in the same "VQUERY" component, as there would be no way to distinguish between them in the reply.

each of which may be associated with a calendar date and possibly time of day. These entities can include calendar properties or components. In addition, a calendar might be related to other calendars with the "RELATED-TO" property. A calendar is identified by its unique calendar identifier. The [[iCAL](#)] defines the initial calendar properties, calendar components and properties that make up the contents of a calendar.

Calendar Access Protocol (CAP) - The standard Internet protocol that permits a CUA to access and manipulate calendars residing on a Calendar Store. (this memo)

Calendar Access Rights (VCAR) - The mechanism for specifying the CAP operations ("PERMISSION") that a particular calendar user ("UPN") is granted or denied permission to perform on a given calendar object ("SCOPE"). The calendar access rights are specified with a "VCAR" component. ([Section 9.3.](#))

Calendar Address - Also See Calendar URL - they are one in the same for CAP addresses. The calendar address can also be the value to the "ATTENDEE" and "ORGANIZER" properties as defined in [[iCAL](#)].

Calendar URL - A calendar URL is a URL defined in this memo that specifies the address of a CS or Calendar.

Component- Any object that conforms to the iCalendar object format and that is either defined in an internet draft, registered with IANA, or is an experimental object that is prefixed with "x-". Some types of components include calendars, events, to-dos, journals, alarms, and time zones. A component consists of properties and possibly other contained components. For example, an event may contain an alarm component.

Container - This is a generic name for VCALSTORE or VAGENDA.

Properties - An attribute of a particular component. Some properties are applicable to different types of components. For example, the "DTSTART" property is applicable to the "VEVENT", "VTODO", and "VJOURNAL" components. Other components are applicable only to an individual type of calendar component. For example, the "TZURL" property may only be applicable to the "VTIMEZONE" components.

Calendar Identifier (CALID) - A globally unique identifier associated with a calendar. Calendars reside within a CS. See Qualified Calendar Identifier and Relative Calendar Identifier. All CALIDs start with "cap:".

Calendar Policy - A CAP operational restriction on the access or manipulation of a calendar. These may be outside of the scope of the CAP protocol. An example of an implementation or site policy is, "events MUST BE scheduled in unit intervals of one hour".

Calendar Property - An attribute of a calendar ("VAGENDA"). The attribute applies to the calendar, as a whole. For example, the "CALSCALE" property specifies the calendar scale (e.g., the "GREGORIAN" value) for the all entries within the calendar.

Calendar Store (CS) - The data and service model definition for a Calendar Store as defined in this memo. This memo does not specify how the CS is implemented.

Calendar Server - An implementation of a Calendar Store (CS) that manages one or more calendars.

Calendar Store Identifier (CSID) - The globally unique identifier for an individual CS. A CSID consists of the host and port portions of a "Common Internet Scheme Syntax" part of a URL, as defined by [\[URL\]](#). The CSID excludes any reference to a specific calendar. ([Section 8.9](#))

Calendar Store Components - Components maintained in a CS specify a grouping of calendar store-wide information.

Calendar Store Properties - Properties maintained in a Calendar Store calendar store-wide information.

Calendar User (CU) - An entity (often biological) that uses a calendaring system.

Calendar User Agent (CUA) - The client application that a CU utilizes to access and manipulate a calendar.

CAP Session - An open communication channel between a CUA and a CS. If the CAP session is authenticated, the CU is "authenticated" and it is an "authenticated CAP session".

Contained Component / Contained Properties - A component or property that is contained inside of another component. A "VALARM" component for example may be contained inside of a "VEVENT" component. And a "TRIGGER" property could be a contained property of a "VALARM" component.

Internet-Draft

Calendar Access Protocol (CAP)

August 2005

Delegate - A CU (sometimes called the delegatee) who has been assigned participation in a scheduled component (e.g., VEVENT) by one of the attendees in the scheduled component (sometimes called the delegator). An example of a delegate is a team member told to go to a particular meeting in place of another Attendee who is unable to attend.

Designate - A CU who is authorized to act on behalf of another CU. An example of a designate is an assistant.

Experimental - The CUA and CS may implement experimental extensions to the protocol. They also might have experimental components, properties, and parameters. These extensions **MUST** start with "x-" (or "X-") and should include a vendor prefix (such as "x-myvendor-"). There is no guarantee that these experimental extensions will interoperate with other implementations. There is no guarantee that they will not interact in unpredictable ways with other vendor experimental extensions. There is no guarantee that the same specific experimental extension is not used by multiple vendors in incompatible ways. Implementations should limit sending those extensions to other implementations.

Object - A generic name for any component, property, parameter, or value type to be used in iCalendar.

Overlapped Booking - A policy which indicates whether or not components with a "TRANSP" property not set to "TRANSPARENT-NOCONFLICT" or "OPAQUE-NOCONFLICT" value can overlap one another. When the policy is applied to a calendar it indicates whether or not the time span of any component (VEVENT, VTODO, ...) in the calendar can overlap the time span of any other component in the same calendar. When applied to an individual object, it indicates whether or not any other component's time span can overlap that individual component. If the CS does not allow overlapped booking, then the CS is unwilling to allow any overlapped bookings within any calendar or entry in the CS.

Owner - One or more CUs or UGs that are listed in the "OWNER" property in a calendar. There can be more than one owner.

Qualified Calendar Identifier (Qualified CALID) - A CALID in which both the scheme and CSID of the CAP URI are present.

Realm - A collection of calendar user accounts, identified by a string. The name of the Realm is only used in UPNs. In order to avoid namespace conflict, the Realm SHOULD be postfixed with an appropriate DNS domain name. (e.g., the foobar Realm could be called foobar.example.com).

Royer, et al.

Expires February 9, 2006

[Page 10]

Internet-Draft

Calendar Access Protocol (CAP)

August 2005

Relative Calendar Identifier (Relative CALID) - An identifier for an individual calendar in a calendar store. It MUST BE unique within a calendar store. A Relative CALID consists of the "URL path" of the "Common Internet Scheme Syntax" portion of a URL, as defined by [[URI](#)] and [[URLGUIDE](#)].

Session Identity - A UPN associated with a CAP session. A session gains an identity after successful authentication. The identity is used in combination with VCAR to determine access to data in the CS.

User Group (UG) - A collection of Calendar Users and/or User Groups. These groups are expanded by the CS and may reside either locally or in an external database or directory. The group membership may be fixed or dynamic over time.

Username - A name which denotes a Calendar User within a Realm. This is part of a UPN.

User Principal Name (UPN) - A unique identifier that denotes a CU or a group of CU. ([Section 6.1.2](#))

2. Additions to iCalendar

Several new components, properties, parameters, and value types are added in CAP. This section summarizes those new objects.

This memo extends the properties that can go into 'calprops' as defined in [[iCAL](#)] [section 4.6](#) page 51 to allow [[iTIP](#)] objects transmitted between a CAP aware CUA and the CS to contain the "TARGET" and "CMD" properties. This memo also adds to the [[iCAL](#)] ABNF to allow IANA and experimental extensions. This memo does not address how a CUA transmits [[iTIP](#)] or [[iMIP](#)] objects to non CAP programs. (What follows is ABNF as described in [[ABNF](#)])

```
calprops    = 2*(
    ; 'prodid' and 'version' are both REQUIRED,
    ; but MUST NOT occur more than once.
    ;
    prodid /version /
    ;
    ; These are optional, but MUST NOT occur
    ; more than once.
    ;
    calscale          /
```

```

        method      /
        cmd          /
    ;
    ; Target is optional, and may occur more
    ; than once.
    ;
    target / other-props )
    ;
other-props = *(x-prop) *(iana-prop) *(other-props)
    ;
iana-prop  = ; Any property registered by IANA directly or
    ; included in an RFC that may be applied to
    ; the component and within the rules published.
    ;
x-prop     = ; As defined in [iCAL]
    ;
methodp    = ; As defined in [iCAL]
    ;
prodid     = ; As defined in [iCAL]
    ;
calscale   = ; As defined in [iCAL]
    ;

```

Another change is that the 'component' part of the 'icalbody' ABNF as described in [[iCAL](#)] [section 4.6](#) is optional when sending a command as shown in the following updated ABNF:

```
icalbody = calprops component
```

```

    ; If the "VCALENDAR" component contains the "CMD"
    ; property then the 'component' is optional:
    ;
    / calprops      ; Which MUST include a "CMD" property
    ;
component = ; As defined in [iCAL]

```

In addition a problem exists with the control of "VALARM" components and their "TRIGGER" properties. A CU may wish to set their own alarm (local alarms) on components. These local alarms are not to be

forwarded to other CUs, CUAs, or CSs as are the "SEQUENCE" property and the "ENABLE" parameter. So for the protocol between a CUA and a CS, the following changes apply to the CAP protocol from [[iCAL](#) [section 4.6.6](#) page 67]:

```
alarmc      = "BEGIN" ":" "VALARM" CRLF
              alarm-seq
              other-props
              (audioprop / dispprop / emailprop / procprop)
              "END" ":" "VALARM" CRLF
emailprop   = ; As defined in [iCAL]
procprop    = ; As defined in [iCAL]
dispprop    = ; As defined in [iCAL]
```

```

        ;
audioprop    = ; As defined in [iCAL]
        ;
alarm-seq    = "SEQUENCE" alarmseqparams ":" posint0 CRLF
        ;
alarmseqparams = other-params [";" local-param] other-params
        ;
        ; Where DIGIT is defined in [iCAL]
        ;
posint0      = 1*DIGIT
posint1      = posintfirst 1*DIGIT
        ;
        ; A number starting with 1 through 9.
        ;
posintfirst  = %x31-39
        ;
other-params = *(";" xparam) *(";" iana-params) *(";" other-params)
        ;
iana-params  = ; Any parameter registered by IANA directly or
        ; included in an RFC that may be applied to
        ; the property and within the rules published.
        ;
xparam       ; As defined in [iCAL]
        ;

```

The CUA adds a "SEQUENCE" property to each "VALARM" component as it books the component. This property along with the "LOCAL" and "ENABLE" parameters allow the CUA to uniquely identify any VALARM in any component. The CUA should remove those before forwarding to non CAP aware CUAs.

In addition, if a CUA wished to ignore a "TRIGGER" property in a "VALARM" component that was supplied to it by the "Organizer", the CUA needs a common way to tag that trigger as disabled. So the following is a modification to [[iCAL](#)] [section 4.8.6.3](#) page 127:

```

trigger      = "TRIGGER" 1*(";" enable-param) (trigrel / trigabs)
        ;
trigrel      = ; As defined in [iCAL]
        ;

```


trigabs = ; As defined in [[iCAL](#)]

[Section 7.2](#) and [Section 7.5](#).

[2.1](#) New Value Types (summary)

UPN The UPN value type is text value type restricted to only UPN values. ([Section 6.1.2](#))

UPN-FILTER Like the UPN value type, but also includes filter rules that allow wildcards. ([Section 6.1.3](#))

CALQUERY The "CAL-QUERY" value type is a query syntax that is used by the CUA to specify the rules that apply to a CAP command. ([Section 6.1.1](#))

[2.1.1](#) New Parameters (summary)

ACTION - The "ACTION" parameter informs the endpoint if it should abort or ask to continue on timeout. ([Section 7.1](#)).

ENABLE - The "ENABLE" parameter in CAP is used to tag a property in a component as disabled or enabled. ([Section 7.2](#)).

ID - The "ID" parameter specifies a unique identifier to be used for any outstanding commands.

LATENCY - The "LATENCY" parameter supplies the timeout value for command completion to the other endpoint. ([Section 7.4](#)).

LOCAL - The "LOCAL" parameter in CAP is used to tag a property in a component to signify that the component is local or to be distributed. ([Section 7.5](#)).

LOCALIZE - The "LOCALIZE" parameter specifies the locale to be used in error and warning messages.

OPTIONS - The "OPTIONS" parameter passes optional information for the command being sent.

[2.1.2](#) New or Updated Properties (summary)

ALLOW-CONFLICT - Some entries in a calendar might not be valid if other entries were allowed to overlap the same time span.
([Section 8.1](#))

ATT-COUNTER - When storing a "METHOD" property with the "COUNTER" method, there needs to be a way to remember the "ATTENDEE" value that sent the COUNTER. ([Section 8.2](#))

CAP-VERSION - The version of CAP the implementation supports.
([Section 8.5](#))

CAR-LEVEL - The level of calendar access level supported.
([Section 8.7](#))

COMPONENTS - The list of components supported. ([Section 8.8](#))

CSID - The Calendar Store IDentifier (CSID) uniquely identifies a CAP server. ([Section 8.9](#))

CALID - Each calendar within a CS needs to be uniquely identifiable. The "CALID" property identifies a unique calendar within a CS. It can be a full CALID or a relative CALID. ([Section 8.3](#))

CALMASTER - The "CALMASTER" property specifies the contact information for the CS. ([Section 8.4](#))

CARID - Access rights can be saved and fetched by unique ID - the "CARID" property. ([Section 8.6](#))

CMD - The CAP commands, as well as replies are transmitted using the "CMD" property. ([Section 10.1](#))

DECREED - Some access rights are not changeable by the CUA. When that is the case, the "DECREED" property value in the "VCAR" component will be "TRUE". ([Section 8.10](#))

DEFAULT-CHARSET - The list of charsets supported by the CS. The first entry is the default for the CS. ([Section 8.11](#))

DEFAULT-LOCALE - The list of locales supported by the CS. The first entry in the list is the default locale. ([Section 8.12](#))

DEFAULT-TZID - This is the list of known timezones supported. The first entry is the default. ([Section 8.13](#))

Internet-Draft

Calendar Access Protocol (CAP)

August 2005

DEFAULT-VCARS - A list of the "CARID" properties that will be used to create new calendars. ([Section 8.14](#))

DENY - The UPNs listed in the "DENY" property of a "VCAR" component will denied access as described in the "VRIGHT" component. ([Section 8.15](#))

EXPAND - This property tells the CS if the query reply should expand components into multiple instances. The default is "FALSE" and is ignored for CSs that can not expand recurrence rules. ([Section 8.16](#))

GRANT - The UPNs listed in the "GRANT" property of a "VCAR" component will allowed access as described in the "VRIGHT" component. ([Section 8.17](#))

ITIP-VERSION - The version of [[iTIP](#)] supported. ([Section 8.18](#))

MAXDATE - The maximum date supported by the CS. ([Section 8.20](#))

MAX-COMP-SIZE - The largest component size allowed in the implementation including attachments in octets. ([Section 8.19](#))

MINDATE - The minimum date supported by the CS. ([Section 8.21](#))

MULTIPART - Passed in the capability messages to indicate which MIME multipart types the sender supports. ([Section 8.22](#))

NAME - The "NAME" property is used to add locale specific descriptions into components. ([Section 8.23](#))

OWNER - Each calendar has at least one "OWNER" property. (xref target="OWNER"/>) Related to the "CAL-OWNERS()" ([Section 6.1.1.1](#)) query clause.

PERMISSION - This property specifies the permission being granted or denied. Examples are the "SEARCH" and "MODIFY" values. ([Section 8.25](#))

QUERY - Used to hold the CAL-QUERY ([Section 8.26](#)) for the component.

QUERYID - A unique id for a stored query. ([Section 8.27](#))

QUERY-LEVEL - The level of the query language supported.
([Section 8.28](#))

Royer, et al.

Expires February 9, 2006

[Page 17]

Internet-Draft

Calendar Access Protocol (CAP)

August 2005

RECUR-ACCEPTED - If the implementation support recurrence rules.
([Section 8.29](#))

RECUR-EXPAND - If the implementation support expanding recurrence rules. ([Section 8.31](#))

RECUR-LIMIT - Any maximum limit on the number of instances the implementation will expand recurring objects. ([Section 8.30](#))

REQUEST-STATUS - The [[iCAL](#)] "REQUEST-STATUS" property is extended to include new error numbers.

RESTRICTION - In the final check when granting calendar access requests, the CS test the results to the value of the "RESTRICTION" property in the corresponding "VRIGHT" component to determine if the access meets that restriction. ([Section 8.32](#))

SCOPE - The "SCOPE" property is used in "VRIGHT"s component to select the subset of data that may be acted upon when checking access rights. ([Section 8.33](#))

SEQUENCE - When the "SEQUENCE" property is used in a "VALARM" component it uniquely identifies the instances of the "VALARM" within that component.

STORES-EXPANDED - Specifies if the implementation stores recurring object expanded or not. ([Section 8.34](#))

TARGET - The new "VCALENDAR" component property "TARGET" ([Section 8.35](#)) is used to specify which calendar(s) will be the subject of the CAP command.

TRANSP - This is a modification the [[iCAL](#)] "TRANSP" property and it

allows more values. The new values are related to conflict control. ([Section 8.36](#))

[2.1.3](#) New Components (summary)

VAGENDA - CAP allows the fetching and storing of the entire contents of a calendar. The "VCALENDAR" component is not sufficient to encapsulate all of the needed data that describes a calendar. The "VAGENDA" component is the encapsulating object for an entire calendar. ([Section 9.1](#))

Royer, et al.

Expires February 9, 2006

[Page 18]

Internet-Draft

Calendar Access Protocol (CAP)

August 2005

VCALSTORE - Each CS contains one or more calendars (VAGENDAs), the "VCALSTORE" component is the encapsulating object that can hold all of the "VAGENDA" components along with any components and properties that are unique to the store level. ([Section 9.2](#))

VCAR - Calendar Access Rights are specified and encapsulated in the new iCalendar "VCAR" component. The "VCAR" component holds some new properties and at least one "VRIGHT" component. ([Section 9.3](#))

VRIGHT - This component encapsulates a set of instructions to the CS that define the rights or restrictions needed. ([Section 9.4](#))

VREPLY - This component encapsulates a set of data that can consist of an arbitrary amounts of properties and components. Its contents is dependent on the command that was issued. ([Section 9.5](#))

VQUERY - The search operation makes use of a new component, called "VQUERY" and a new value type "CAL-QUERY" ([Section 6.1.1](#)). The "VQUERY" component is used to fetch objects from the CS. ([Section 9.6](#))

[2.2](#) Relationship of [RFC-2446](#) (ITIP) and CAP

[iTIP] describes scheduling methods which result in indirect

manipulation of components. In CAP, the "CREATE" command is used to deposit entities into the store. Other CAP commands such as "DELETE", "MODIFY" and "MOVE" command values provide direct manipulation of components. In the CAP calendar store model, scheduling messages are conceptually kept separate from other components by their state.

All scheduling operations are as defined in [\[iTIP\]](#). This memo makes no changes to any of the methods or procedures described in [\[iTIP\]](#). In this memo referring to the presence of the "METHOD" property in an object is the same as saying an [\[iTIP\]](#) object.

A CUA may create a "BOOKED" state object by depositing an iCalendar object into the store. This is done by depositing an object that does not have a "METHOD" property. The CS then knows to set the state of the object to the "BOOKED" state. If the object has a "METHOD" property then the object is stored in the "UNPROCESSED" state.

If existing "UNPROCESSED" state objects exist in the CS for the same UID (UID is defined in [\[iCAL\]](#)) then a CUA may wish to consolidate the objects in to one "BOOKED" state object. The CUA would fetch the

"UNPROCESSED" state objects for that UID and process them in the CUA as described in [\[iTIP\]](#). Then if the CUA wished to book the UID, the CUA would issue a "CREATE" command to create the new "BOOKED" state object in the CS, followed by a "DELETE" command to remove any related old [\[iTIP\]](#) objects from the CS. And it might also involve having the CUA send some [\[iMIP\]](#) objects or contacting other CSs and performing CAP operations on those CSs.

The CUA could also decide not to book the object. In which case the "UNPROCESSED" state objects could be removed from the CS or the CUA could set those object to the marked for delete state. The CUA could also ignore objects for later processing.

The marked for delete state is used to keep the object around so that the CUA can process duplicate requests automatically. If a duplicate [\[iTIP\]](#) object is deposited into the CS and there exists identical marked for delete objects, then a CUA acting on behalf of the "OWNER" can silently drop those duplicate entries.

Another purpose for the marked for delete state is so that when a CU decides they do not wish to have the object show in their calendar, the CUA can book the object; changing the "PARTSTAT" parameter to "DECLINED" in the "ATTENDEE" property that corresponds to their UPN. Then perform an [\[iTIP\]](#) processing such as sending back a decline. Then mark that object as marked for delete. Their CUA might be configurable to automatically drop any updates for that object knowing the CU has already declined.

When synchronizing with multiple CUAs, the marked for delete state could be used to inform the synchronization process that an object is to be deleted. How synchronization is done is not specified in this memo.

Several "UNPROCESSED" state entries can be in the CS for the same UID. However once consolidated, then only one object exists in the CS and that is the booked object. The others MUST BE removed, or have their state changed to "DELETED".

There MUST NOT BE more than one "BOOKED" state object in a calendar for the same "UID". The "ADD" method value may create multiple objects all in the "BOOKED" state for the same UID, however for the purpose of this memo, they are the same object that simply have multiple "VCALENDAR" components.

For example, if you were on vacation, you could have received a "REQUEST" method to attend a meeting and several updates to that meeting. Your CUA would have to issue "SEARCH" commands to find them in the CS using CAP, process them, determine what the final state of

the object from a possible combination of user input and programmed logic. Then the CUA would instruct the CS to create a new booked object from the consolidated results. Finally, the CUA could do a "DELETE" command to remove the related "UNPROCESSED" state objects. See [\[iTIP\]](#) for details on resolving multiple [\[iTIP\]](#) scheduling entries.

[3.](#) CAP Design

[3.1](#) System Model

The system model describes the high level components of a calendar

system and how they interact with each other.

CAP is used by a CUA to send commands to and receive responses from a CS.

The CUA prepares a [\[MIME\]](#) encapsulated message, sends it to the CS, and receives a [\[MIME\]](#) encapsulated response. The calendaring related information within these messages are represented by iCalendar objects. In addition the "GET-CAPABILITY" command can be sent from the CS to the CUA.

There are two distinct protocols in operation to accomplish this exchange. [\[BEEP\]](#) is the transport protocol used to move these encapsulations between a CUA and a CS. CAP's [\[BEEP\]](#) profile defines the application protocol where the content and semantics of the messages sent between the CUA and the CS are specified.

[3.2](#) Calendar Store Object Model

[\[iCAL\]](#) describes components such as events, todos, alarms, and timezones. [\[CAP\]](#) requires additional object infrastructure. In particular, detailed definitions of the containers for events and todos (calendars), access control objects, and a query language.

The conceptual model for a calendar store is shown below. The calendar store (VCALSTORE - [Section 9.2](#)) contains "VCAR"s, "VQUERY"s, "VTIMEZONE"s, "VAGENDA"s and calendar store properties.

Calendars (VAGENDAs) contain "VEVENT"s, "VTODO"s, "VJOURNAL"s, "VCAR"s, "VTIMEZONE"s, "VFREEBUSY", "VQUERY"s and calendar properties.

The component "VCALSTORE" is used to denote the a root of the calendar store and contains all of the calendars.

Calendar Store

```
VCALSTORE
|
+-- properties
+-- VCARS
+-- VQUERYs
+-- VTIMEZONES
+-- VAGENDA
|   |
|   +--properties
|   +--VEVENTs
|   |   |
|   |   +--VALARMS
|   +--VTODOs
|   |   |
|   |   +--VALARMS
|   +--VJOURNALS
|   +--VCARS
|   +--VTIMEZONES
|   +--VQUERYs
|   +--VFREEBUSYs
|   |
|   ...
.
.
+-- VAGENDA
.   .
.   .
.   .
```

Calendars within a Calendar Store are identified by their unique Relative CALID.

[3.3](#) Protocol Model

CAP uses [\[BEEP\]](#) as the transport and authentication protocol.

The initial charset MUST BE UTF-8 for the session in an unknown locale. If the CS supplied the [\[BEEP\]](#) 'localize' attribute in the [\[BEEP\]](#) 'greeting' then the CUA may tell the CS to switch locales for the session by issuing the "SET-LOCALE" CAP command and supplying one of the locales supplied by the [\[BEEP\]](#) 'localize' attribute. If supplied the first locale in the [\[BEEP\]](#) 'localize' attribute is the default locale of the CS. The locale is switched only after a successful reply.

The "DEFAULT-CHARSET" property of the CS contains the list of charsets supported by the CS with the first value being the default for new calendars. If the CUA wishes to switch to one of those charsets for the session, the CUA issues the "SET-LOCALE" command. The CUA would have to first perform a "GET-CAPABILITY" command on the CS to get the list of charsets supported by the CS. The charset is switched only after a successful reply.

The CUA may switch locales and charsets as needed. There is no requirement that a CS support multiple locales or charsets.

[3.3.1](#) Use of BEEP, MIME and iCalendar

CAP uses the [\[BEEP\]](#) application protocol over TCP. (refer to [\[BEEP\]](#) and [\[BEEPTCP\]](#) for more information). The default port that the CS listens for connections is on user port 1026.

The [\[BEEP\]](#) data exchanged in CAP is a iCalendar MIME content that fully conforms to [\[iCAL\]](#) iCalendar format.

This example tells the CS to generate and return 10 UIDs to be used by the CUA. Note throughout this memo, 'C:' refers to what the CUA sends, 'S:' refers to what the CS sends, 'I:' refers to what the initiator sends, and 'L:' refers to what the listener sends. Where initiator and listener are used as defined in [\[BEEP\]](#).

```
C: MSG 1 2 . 432 62
C: Content-Type: text/calendar
C:
C: BEGIN:VCALENDAR
C: VERSION:2.0
C: PRODID:-//someone's prodid
C: CMD;ID=unique-per-cua-123;OPTIONS=10:GENERATE-UID
C: END:VCALENDAR
```

NOTE: The following examples will not include the [\[BEEP\]](#) header and footer information. Only the iCalendar objects that are sent between the CUA and CS will be shown as the [\[BEEP\]](#) payload boundaries are independent of CAP.

The commands listed below are used to manipulate or access the data on the calendar store:

ABORT - Sent to halt the processing of some of the commands.
([Section 10.2](#))

CONTINUE - Sent to continue processing a command that has had its specified timeout time reached. ([Section 10.3](#))

CREATE - Create a new object on the CS. Initiated by the CUA only.
([Section 10.4](#))

SET-LOCALE - Tell the CS to use any named locale and charset supplied. Initiated by the CUA only. ([Section 10.13](#))

DELETE - Delete objects from the CS. Initiated by the CUA only.
Can also be used to mark an object for deletion. ([Section 10.5](#))

GENERATE-UID - Generate one or more unique ids. Initiated by the CUA only. ([Section 10.6](#))

GET-CAPABILITY - Query the capabilities the other end point of the session. ([Section 10.7](#))

IDENTIFY - Set a new identity for the session. Initiated by the CUA only. ([Section 10.8](#))

MODIFY - Modify components. Initiated by the CUA only.
([Section 10.9](#))

MOVE - Move components to another container. Initiated by the CUA only. ([Section 10.10](#))

REPLY - When replying to a command, the "CMD" value will be set to "REPLY" so that it will not be confused with a new command.
([Section 10.11](#))

SEARCH - Search for components. Initiated by the CUA only.

([Section 10.12](#))

TIMEOUT - Sent when a specified amount of time has lapsed and a command has not finished. ([Section 10.14](#))

[4.](#) Security Model

The [[BEEP](#)] transport performs all session authentication.

[4.1](#) Calendar User and UPNs

A CU is an entity that can be authenticated. It is represented in CAP as a UPN, which is a key part of access rights. The UPN representation is independent of the authentication mechanism used during a particular CUA/CS interaction. This is because UPNs are used within VCARS. If the UPN were dependent on the authentication mechanism, a VCAR could not be consistently evaluated. A CU may use one mechanism while using one CUA but the same CU may use a different authentication mechanism when using a different CUA, or while connecting from a different location.

The user may also have multiple UPNs for various purposes.

Note that the immutability of the user's UPN may be achieved by using SASL's authorization identity feature. (The transmitted authorization identity may be different than the identity in the client's authentication credentials.) [[SASL](#), [section 3](#)]. This also permits a CU to authenticate using their own credentials, yet request the access privileges of the identity for which they are proxying SASL. Also, the form of authentication identity supplied by a service like TLS may not correspond to the UPNs used to express a server's access rights, requiring a server specific mapping to be done. The method by which a server determines a UPN, based on the

authentication credentials supplied by a client, is implementation specific. See [[BEEP](#)] for authentication details; [[BEEP](#)] relies on SASL.

[4.1.1](#) UPNs and Certificates

When using X.509 certificates for purposes of CAP authentication, the UPN should appear in the certificate. Unfortunately there is no single correct guideline for which field should contain the UPN.

From [RFC-2459, section 4.1.2.6](#) (Subject):

If subject naming information is present only in the subjectAltName extension (e.g., a key bound only to an email address or URI), then the subject name MUST be an empty sequence and the subjectAltName extension MUST BE critical.

Implementations of this specification MAY use these comparison rules to process unfamiliar attribute types (i.e., for name chaining). This allows implementations to process certificates

Royer, et al.

Expires February 9, 2006

[Page 26]

Internet-Draft

Calendar Access Protocol (CAP)

August 2005

with unfamiliar attributes in the subject name.

In addition, legacy implementations exist where an [RFC 2822](#) name is embedded in the subject distinguished name as an EmailAddress attribute. The attribute value for EmailAddress is of type IA5String to permit inclusion of the character '@', which is not part of the PrintableString character set. EmailAddress attribute values are not case sensitive (e.g., "fanfeedback@redsox.example.com" is the same as "FANFEEDBACK@REDSOX.EXAMPLE.COM").

Conforming implementations generating new certificates with electronic mail addresses MUST use the rfc822Name in the subject alternative name field (see sec. 4.2.1.7 of [[X509CRL](#)]) to describe such identities. Simultaneous inclusion of the EmailAddress attribute in the subject distinguished name to support legacy implementations is deprecated but permitted.

Since no single method of including the UPN in the certificate will work in all cases, CAP implementations MUST support the ability to configure what the mapping will be by the CS administrator.

Implementations MAY support multiple mapping definitions, for example, the UPN may be found in either the subject alternative name field, or the UPN may be embedded in the subject distinguished name as an EmailAddress attribute.

Note: If a CS or CUA is validating data received via [[iMIP](#)], if the "ORGANIZER" or "ATTENDEE" properties said (e.g.) "ATTENDEE;CN=Joe Random User:MAILTO:juser@example.com" then the email address should be checked against the UPN. This is so the "ATTENDEE" property cannot be changed to something misleading like "ATTENDEE;CN=Joe Rictus User:MAILTO:jrictus@example.com" and have it pass validation. Note that it is the email addresses that miscompare, the CN miscompare is irrelevant.

[4.1.2](#) Anonymous Users and Authentication

Anonymous access is often desirable. For example an organization may publish calendar information that does not require any access control for viewing or login. Conversely, a user may wish to view unrestricted calendar information without revealing their identity.

[4.1.3](#) User Groups

A User Group is used to represent a collection of CUs or other UGs that can be referenced in VCARS. A UG is represented in CAP as a UPN. The CUA cannot distinguish between a UPN that represents a CU or a UG.

UGs are expanded as necessary by the CS. The CS MAY expand a UG (including nested UGs) to obtain a list of unique CUs. Duplicate UPNs are filtered during expansion.

How the UG expansion is maintained across commands is implementation specific. A UG may reference a static list of members, or it may represent a dynamic list. Operations SHOULD recognize changes to UG membership.

CAP does not define commands or methods for managing UGs.

[4.2](#) Access Rights

Access rights are used to grant or deny access to calendars,

components, properties, and parameters in a CS to a CU. CAP defines a new component type called a Calendar Access Right (VCAR). Specifically, a "VCAR" component grants, or denies, UPNs the right to search and write components, properties, and parameters on calendars within a CS.

The "VCAR" component model does not put any restriction on the sequence in which the object and access rights are created. That is, an object associated with a particular "VCAR" component might be created before or after the actual "VCAR" component is defined. In addition, the "VCAR" and "VEVENT" components might be created in the same iCalendar object and passed together in a single object.

All rights MUST BE denied unless specifically granted.

If two rights specified in "VCAR" components are in conflict, the right that denies access always takes precedence over the right that grants access. Any attempt to create a "VCAR" component that conflicts with a "VCAR" components with a "DECREED" property set to the "TRUE" value must fail.

[4.2.1](#) Access Control and NOCONFLICT

The "TRANSP" property can take on values "TRANSPARENT-NOCONFLICT" and "OPAQUE-NOCONFLICT" that prohibit other components from overlapping it. This setting overrides access. The "ALLOW-CONFLICT" CS, Calendar or component setting may also prevent overlap, returning an error code "6.3".

[4.2.2](#) Predefined VCARS

Predefined calendar access CARIDs that MUST BE implemented are:

CARID:READBUSYTIMEINFO - Specifies the "GRANT" and "DENY" rules that allow UPNs to search "VFREEBUSY" components. An example definition for this VCAR is:


```

BEGIN:VCAR
CARID:READBUSYTIMEINFO
BEGIN:VRIGHT
GRANT:*
PERMISSION:SEARCH
SCOPE:SELECT * FROM VFREEBUSY WHERE STATE() = 'BOOKED'
END:VRIGHT
END:VCAR

```

CARID:REQUESTONLY - Specifies the "GRANT" and "DENY" rules to UPNs other than the owner of the calendar the ability to write new objects with the property "METHOD" property set to the "REQUEST" value. This CARID allows the owner to specify which UPNs are allowed to make scheduling requests. An example definition for this VCAR is:

```

BEGIN:VCAR
CARID:REQUESTONLY
BEGIN:VRIGHT
GRANT:NON CAL-OWNERS()
PERMISSION:CREATE
RESTRICTION:SELECT VEVENT FROM VAGENDA WHERE METHOD = 'REQUEST'
RESTRICTION:SELECT VTOD0 FROM VAGENDA WHERE METHOD = 'REQUEST'
RESTRICTION:SELECT VJOURNAL FROM VAGENDA WHERE METHOD = 'REQUEST'
END:VRIGHT
END:VCAR

```

CARID:UPDATEPARTSTATUS - Grants to authenticated users the right to modify the instances of the "ATTENDEE" property set to one of their calendar addresses in any components for any booked component containing an "ATTENDEE" property. This allows (or denies) a CU the ability to update their own participation status in a calendar where they might not otherwise have "MODIFY" command access. They are not allowed to change the "ATTENDEE" property value. An example definition for this VCAR is (This example only affects the "VEVENT" components):

```

BEGIN:VCAR
CARID:UPDATEPARTSTATUS
BEGIN:VRIGHT
GRANT:*
PERMISSION:MODIFY
SCOPE:SELECT ATTENDEE FROM VEVENT
  WHERE ATTENDEE = SELF()
  AND ORGANIZER = CURRENT-TARGET()
  AND STATE() = 'BOOKED'
RESTRICTION:SELECT * FROM VEVENT
  WHERE ATTENDEE = SELF()
END:VRIGHT
END:VCAR

```

CARID:DEFAULTOWNER - Grants to any owner the permission they have for the target. An example definition for this VCAR is:

```

BEGIN:VCAR
CARID:DEFAULTOWNER
BEGIN:VRIGHT
GRANT:CAL-OWNERS()
PERMISSION:*
SCOPE:SELECT * FROM VAGENDA
END:VRIGHT
END:VCAR

```

[4.2.3](#) Decreed VCARS

A CS MAY choose to implement and allow persistent immutable VCARS that may be configured by the CS administrator. A reply from the CS may dynamically create "VCAR" components that are decreed depending on the implementation. To the CUA any "VCAR" component with the "DECREED" property set to "TRUE" can not be changed by the currently authenticated UPN, and depending on the implementation and other "VCAR" components; might not be able to be changed by any UPN using CAP, and never when the CUA gets a "DECREED:TRUE" VCAR.

When a user attempts to modify or override a decreed "VCAR" component rules an error will be returned indicating that the user has

Internet-Draft

Calendar Access Protocol (CAP)

August 2005

insufficient authorization to perform the operation. The reply to the CUA MUST BE the same as if a non-decreed VCAR caused the failure.

The CAP protocol does not define the semantics used to initially create a decreed VCAR. This administrative task is outside the scope of the CAP protocol.

For example; an implementation or a CS administrator may wish to define a VCAR that will always allow the calendar owners to have full access to their own calendars.

Decreed "VCAR" components MUST BE readable by the calendar owner in standard "VCAR" component format.

[4.3](#) CAP Session Identity

A [\[BEEP\]](#) session has an associated set of authentication credentials, from which is derived a UPN. This UPN is the identity of the CAP session, and is used to determine access rights for the session.

The CUA may change the identity of a CAP session by calling the "IDENTIFY" command. The CS only permits the operation if the session's authentication credentials are good for the requested identity. The method of checking this permission is implementation dependent, but may be thought of as a mapping from authentication credentials to UPNs. The "IDENTIFY" command allows a single set of authentication credentials to choose from multiple identities, and allows multiple sets of authentication credentials to assume the same identity.

For anonymous access the identity of the session is "@". A UPN with a null Username and null Realm is anonymous. A UPN with a null Username, but non-null Realm, such as "@example.com" may be used to mean any identity from that Realm, which is useful to grant access rights to all users in a given Realm. A UPN with a non-null Username and null Realm, such as "bob@" could be a security risk and MUST NOT be used.

As the UPN includes Realm information it may be used to govern calendar store access rights across Realms. However, governing access rights across Realms is only useful if login access is available. This could be done through a trusted server relationship or a temporary account. Note that trusted server relationships are

outside the scope of [CAP].

The "IDENTIFY" command also provides for a weak group implementation. By allowing multiple sets of authentication credentials belonging to different users to identify as the same UPN, that UPN essentially

Royer, et al.

Expires February 9, 2006

[Page 31]

Internet-Draft

Calendar Access Protocol (CAP)

August 2005

identifies a group of people, and may be used for group calendar ownership, or the granting of access rights to a group.

5. CAP URL and Calendar Address

The CAP URL scheme is used to designate calendar stores and calendars accessible using the CAP protocol.

The CAP URL scheme conform to the generic URL syntax, defined in [RFC 2396](#), and follows the Guidelines for URL Schemes, set forth in [RFC 2718](#).

A CAP URL begins with the protocol prefix "cap" and is defined by the following grammar.

```
capurl   = "cap://" csidpart [ "/" relcalid ]  
                ;  
csidpart = hostport    ; As defined in Section 3.2.2 of RFC 2396  
                ;  
relcalid = *uric       ; As defined in Section 2 of RFC 2396
```

A 'relcalid' is an identifier that uniquely identifies a calendar on a particular calendar store. There is no implied structure in a Relative CALID (relcalid). It may refer to the calendar of a user or of a resource such as a conference room. It MUST BE unique within the calendar store.

Examples:

cap://cal.example.com
cap://cal.example.com/Company/Holidays
cap://cal.example.com/abcd1234Usr

A 'relcalid' is permitted and is resolved according to the rules defined in [Section 5 of RFC 2396](#).

Examples of valid relative CAP URLs:

opqaueXzz123String
UserName/Personal

A Calendar addresses can be described as qualified or relative CAP URLs.

For a user currently authenticated to the CS on cal.example.com,

these two example calendar addresses refer to the same calendar:

cap://cal.example.com/abcd1234USR
abcd1234USR

[6.](#) New Value Types

The following sections contains new components, properties, parameters, and value definitions.

The purpose of these is to extend the iCalendar objects in a compatible way so that existing iCalendar "VERSION" property "2.0" value parsers can still parse the objects without modification.

[6.1](#) Property Value Data Types

[6.1.1](#) CAL-QUERY Value Type

Subject: Registration of text/calendar MIME value type CAL-QUERY

Value Name: CAL-QUERY

Value Type Purpose: This value type is used to identify values and contains query statements targeted at locating those values.

This is based on [[SQL92](#)] and [[SQLCOM](#)].

1. For the purpose of a query, all components should be handled as tables, and the properties of those components, should be handled as columns.
2. All VAGENDAs and CSs look like tables for the purpose of a QUERY. And all of their properties look like columns in those tables.
3. You CAN NOT do any cross component-type joins. And that means you can ONLY have one component, OR one "VAGENDA" component OR one "VCALSTORE" component in the "FROM" clause.
4. Everything in the "SELECT" clause and "WHERE" clauses in MUST BE from the same component type, or "VAGENDA" component OR "VCALSTORE" component in the "FROM" clause.
5. When multiple "QUERY" properties are supplied in a single "VQUERY" component, the results returned are the same as the results returned for multiple "VQUERY" components having each a single "QUERY" property.
6. The '.' is used to separate the table name (component) and column name (property or component) when selecting a property that is contained inside of a component that is targeted in the TARGET property.

7. A contained component without a '.' is not the same as "component-name.*". If given as "component-name" (no dot) the encapsulating BEGIN/END statement will be supplied for "component-name".:

In this example the '.' is used to separate the "TRIGGER" property from its contained component (VALARM). Which is contained in any "VEVENT" component in the selected "TARGET" property value (a

relcalid). All "TRIGGER" properties in any "VEVENT" component in relcalid would be returned.

```
TARGET:relcalid
QUERY:SELECT VALARM.TRIGGER FROM VEVENT
```

```
SELECT VALARM FROM VEVENT WHERE UID = "123"
```

This returns one BEGIN/END "VALARM" component for each "VALARM" component in the matching "VEVENT" component. As there is no '.' (dot) in the VALARM after the SELECT above:

```
BEGIN:VALARM
TRIGGER;RELATED=END:PT5M
REPEAT:4
...
END:VALARM
BEGIN:VALARM
TRIGGER;RELATED=START:PT5M
DURATION:PT10M
...
END:VALARM
...
...
```

If provided as "component-name.*", then only the properties and any contained components will be returned:

```
SELECT VALARM.* FROM VEVENT WHERE UID = "123"
```

Will return all of the properties in each "VALARM" component in the matching "VEVENT" component:

```
TRIGGER;RELATED=END:PT5M
REPEAT:4
...
TRIGGER;RELATED=START:PT5M
DURATION:PT10M
...
...
```

- (a) SELECT <a-property-name> FROM VEVENT
- (b) SELECT VALARM FROM VEVENT
- (c) SELECT VALARM.* FROM VEVENT
- (d) SELECT * FROM VEVENT
- (e) SELECT * FROM VEVENT WHERE
VALARM.TRIGGER < '20020201T000000Z'
AND VALARM.TRIGGER > '20020101T000000Z'

Note:

- (a) Selects all instances of <a-property-name> from all "VEVENT" components.
- (b) and (c) Select all "VALARM" components from all "VEVENT" components. (b) would return then in BEGIN/END VALARM tags. (c) would return all of the properties without BEGIN/END VALARM tags.
- (d) Selects every property and every component that is in any "VEVENT" component, with each "VEVENT" component wrapped in a BEGIN/END VEVENT tags.
- (e) Selects all properties and all contained components in all "VEVENT" components that have a "VALARM" component with a "TRIGGER" property value between the provided dates and times, with each "VEVENT" component wrapped in a BEGIN/END VEVENT tags.

NOT VALID:

- (f) SELECT VEVENT.VALARM.TRIGGER FROM VEVENT
- (g) SELECT DTSTART,UID FROM VEVENT WHERE
VTOD0.SUMMERY = "Fix typo in CAP"

Note: (f) Is NOT valid because it contains two '.' characters in the "SELECT" clause.

- (g) Is NOT valid because it mixes VEVENT and VTOD0 properties in the same VQUERY.

Formal Definition: The value type is defined by the following notation:

```
cal-query  = "SELECT"  SP  cap-val  SP
             "FROM"    SP  comp-name SP
             "WHERE"   SP  cap-expr

             / "SELECT" SP cap-cols SP
             "FROM"   SP comp-name
             ;
cap-val    = cap-cols / param
             / ( cap-val "," cap-val )
             ;
             ; NOTE: there is NO space around the "," on
             ; the next line
cap-cols   = cap-col / ( cap-cols "," cap-col )
             / "*"
             / ".*" ; only valid when the target is a "VAGENDA"
             ;
             ; A 'cap-col' is:
             ;
             ; Any property name ('cap-prop') found in the component
             ; named in the 'comp-name' used in the "FROM" clause.
             ;
             ;   SELECT ORGANIZER FROM VEVENT ...
             ;
             ; OR
             ;
             ; A component name ('comp-name') of an existing component
             ; contained inside of the 'comp-name' used in the "FROM"
             ; clause.
             ;
             ;   SELECT VALARM FROM VEVENT ...
             ;
             ; OR
             ;
             ; A component name ('comp-name') of an existing
             ; component contained inside of the 'comp-name' used
             ; in the "FROM" clause followed by a property
             ; name ('cap-prop') to be selected from that component.
             ; (comp-name "." cap-prop)
             ;
```

```

; SELECT VALARM.TRIGGER FROM VEVENT ...
;
cap-col = comp-name
/ comp-name "." cap-prop
/ cap-prop
;
comp-name = "VEVENT" / "VTOD0" / "VJOURNAL" / "VFREEBUSY"
/ "VALARM" / "DAYLIGHT" / "STANDARD" / "VAGENDA"
/ "VCAR" / "VCALSTORE" / "VQUERY" / "VTIMEZONE"

```

```

/ "VRIGHT" / x-comp / iana-comp
;
cap-prop = ; A property that may be in the 'cap-comp' named
; in the "SELECT" clause.
;
cap-expr = "(" cap-expr ")"
/ cap-term
;
cap-term = cap-expr SP cap-logical SP cap-expr
/ cap-factor
;
cap-logical = "AND" / "OR"
;
cap-factor = cap-colval SP cap-oper SP col-value
/ cap-colval SP "LIKE" SP col-value
/ cap-colval SP "NOT LIKE" SP col-value
/ cap-colval SP "IS NULL"
/ cap-colval SP "IS NOT NULL"
/ col-value SP "IN" cap-colval
/ col-value SP "NOT IN" cap-colval
/ "STATE()" "=" ( "BOOKED"
/ "UNPROCESSED"
/ "DELETED"
/ iana-state
/ x-state )
;
iana-state = ; Any state registered by IANA directly or
; included in an RFC that may be applied to
; the component and within the rules published.
;
x-state = ; Any experimental state that starts with
; "x-" or "X-".

```

```

;
cap-colval = cap-col / param
;
param      = "PARAM(" cap-col "," cap-param ")"
;
cap-param  = ; Any parameter that may be contained in the cap-col
; in the supplied PARAM() function
;
col-value  = col-literal
            / "SELF()"
            / "CAL-OWNERS()"
            / "CAL-OWNERS(" cal-address ")"
            / "CURRENT-TARGET()"
;
cal-address = ; A CALID as define by CAP
;

```

```

col-literal = "'" literal-data "'"
;
literal-data = ; Any data that matches the value type of the
; column that is being compared. That is you can
; not compare PRIORITY to "some string" because
; PRIORITY has a value type of integer. If it is
; not preceded by the LIKE element, any '%' and '_'
; characters in the literal data are not treated as
; wildcard characters and do not have to be backslash
; escaped.
;
; OR
;
; If the literal-data is preceded by the LIKE
; element it may also contain the '%' and '_'
; wildcard characters. And if the literal data
; that is comparing contains any '%' or '_'
; characters, they MUST BE backslash escaped as
; described in the notes below in order for them not
; to be treated as wildcard characters.
;
; And if the literal data contains any characters
; that would have to be backslash escaped if
; a property or parameter value then they must
; be backslash escaped in the literal-data.

```

```

; PLUS the quote character (') must be backslash
; escaped. Example:
;
; ... WHERE SUBJECT = 'It\'s time to ski'
;
cap-oper      = "="
               / "!="
               / "<"
               / ">"
               / "<="
               / ">="
               ;
SP            = ; A single white space ASCII character
               ; (value in HEX %x20).
               ;
x-comp       = ; As defined in [iCAL] section 4.6
               ;
iana-comp    = ; As defined in [iCAL] section 4.6

```

[6.1.1.1](#) [NOT] CAL-OWNERS()

This function returns the list of "OWNER" properties for the named calendar when used in the "SELECT" clause.

If called as 'CAL-OWNERS()', it is equivalent to the comma separated list of all of the owners of the calendar that match the provided "TARGET" property value. If the target is a "VCALSTORE", it returns the "CALMASTER" property.

If called as 'CAL-OWNERS(cal-address)', then it is the equivalent to the comma separated list of owners for the named calendar id. If 'cal-address' is a CS, it returns the "CALMASTER" property.

If used in the "WHERE" clause it then returns true if the currently authenticated UPN is an owner of the currently selected object matched in the provided "TARGET" property. Used in a CAL-QUERY "WHERE" clause and in the UPN-FILTER.

[6.1.1.2](#) CURRENT-TARGET()

Is equivalent to the value of the "TARGET" property in the current command. Used in a CAL-QUERY "WHERE" clause.

[6.1.1.3](#) PARAM()

Used in a CAL-QUERY. Returns or tests for the value of the named parameter from the named property.

[6.1.1.3.1](#) PARAM() in SELECT

When used in a "SELECT" clause, it returns the entire property and all of that properties parameters (the result is not limited to the supplied parameter). If the property does not contain the named parameter, then the property is not returned (It could however be returned as a result of another "SELECT" clause value.) If multiple properties of the supplied name have the named parameter, all properties with that named parameter are returned. If multiple PARAM() clauses in a single "SELECT" CLAUSE match the same property, then the single matching property is returned only once.

Also note that many parameters have default values defined in [[iCAL](#)] that must be treated as existing with their default value in the properties as defined in [[iCAL](#)] even when not explicitly present. So for example if a query were performed with PARAM(ATTENDEE,ROLE) then ALL "ATTENDEE" properties would match because even when they do not explicitly contain the "ROLE" parameter, it has a default value and therefore must match.

So when PARAM() is used in a "SELECT" clause, then it is more accurate to say that it means return the property if it contains the named parameter explicitly in the property or simply because the parameter has a default for that property.

[6.1.1.3.2](#) PARAM() in WHERE

When used in the "WHERE" clause, a match is true when the parameter value matches the compare clause according to the supplied WHERE values. If multiple named properties contain the named parameter, then each parameter value is compared in turn to the condition and if

any match, then the results would be true for that condition the same as if only one had existed. Each matching properties or components are returned only once.

As a parameter may be multivalued then the comparison might need to be done with an "IN" or "NOT IN" comparator.

Given the following query:

```
ATTENDEE;PARTSTAT=ACCEPTED:cap://host.com/joe
```

```
SELECT VEVENT FROM VAGENDA
WHERE PARAM(ATTENDEE,PARTSTAT) = 'ACCEPTED'
```

Then all "VEVENT" components that contain one or more "ATTENDEE" properties that have a "PARTSTAT" parameter with a "ACCEPTED" value would be returned. And each uniquely matching VEVENT would only be returned once no matter how many "ATTENDEE" properties had matching roles in each unique "VEVENT" component.

Also note that many parameters have default values defined in [\[iCAL\]](#). So if the following query were performed on the "ATTENDEE" property in the above example:

```
SELECT VEVENT FROM VAGENDA
WHERE PARAM(ATTENDEE,ROLE) = 'REQ-PARTICIPANT'
```

It would return the "ATTENDEE" property exemplified above because the default value for the "ROLE" parameter is "REQ-PARTICIPANT".

[6.1.1.4](#) SELF()

Used in a CAL-QUERY "WHERE" clause. Returns the UPN of the currently authenticated UPN or their current UPN as a result of an IDENTIFY command.

[6.1.1.5](#) STATE()

Returns one of three values, "BOOKED", "UNPROCESSED", or "DELETED" depending on the state of the object. Where "DELETED" is a component

in the marked for delete state. Components that have been removed from the store are never returned.

If not specified in a query then both "BOOKED" and "UNPROCESSED" data is returned. Each unique "METHOD" property must be in a separate MIME object per the [\[iCAL\]](#) [section 3.2](#) restriction.

[6.1.1.6](#) Use of single quote

All literal values are surrounded by single quotes ('), not double quotes ("), and not without any quotes. If the value contains quotes or any other ESCAPED-CHAR, they MUST BE backslash escaped as described in [section 4.3.11](#) "Text" of [\[iCAL\]](#). Any "LIKE" clause wildcard characters that are part of any literal data that is preceded by a "LIKE" clause or "NOT LIKE" clause and is not intended to mean wildcard search MUST BE escaped as described in note (7) below.

[6.1.1.7](#) Comparing DATE and DATE-TIME values

When comparing "DATE-TIME" values to "DATE" values and when comparing "DATE" values to "DATE-TIME" values, the result will be true if the "DATE" value is on the same day as the "DATE-TIME" value. And they are compared in UTC no matter what time zone the data may actual have been stored in.

Local time event as descibed in section 4.2.19 of [\[iCAL\]](#) must be considered to be in the CUA default timezone that was supplied by the CUA in the "CAPABILITY" exchange.

VALUE-1	VALUE-2	Compare Results
20020304 (in UTC-3)	20020304T123456 (in UTC-3)	TRUE
20020304 (in UTC)	20020304T003456 (in UTC-4)	FALSE
20020304T003456Z (in UTC-0)	20020205T003456 (in UTC-7)	FALSE

When comparing "DATE" values and "DATE-TIME" values with the "LIKE"

clause the comparison will be done as if the value is a [[iCAL](#)] DATE or DATE-TIME string value.

LIKE '2002%' will match anything in the year 2002.

LIKE '200201%' will match anything in January 2002.

LIKE '%T000000' will match anything at midnight.

LIKE '____01__T%' will match anything for any year or time that is in January.
(Four '_', '01', two '_' 'T%').

Using a "LIKE" clause value of "%00%", would return any value that contained two consecutive zeros.

All comparisons will be done in UTC.

[6.1.1.8](#) DTEND and DURATION

The "DTEND" property value is not included in the time occupied by the component. That is a "DTEND" property value of 20030614T12000 includes all of the time up to but not including noon on that day.

The "DURATION" property value end time is also not inclusive. So an object with a "DTSTART" property value of 20030514T110000 and a "DURATION" property value of "1H" does not include noon on that day.

When a "QUERY" property value contains a "DTEND" value, then the CS MUST also evaluate any existing "DURATION" property value and determine if it has an effective end time that matches the "QUERY" property supplied "DTEND" value or any range of values supplied by the "QUERY" property.

When a "QUERY" property contains a "DURATION" value, then the CS MUST also evaluate any existing "DTEND" property values and determine if they have an effective duration that matches the "QUERY" property value supplied "DURATION" value or any range of values supplied by the "QUERY" property.

[6.1.1.9](#) [NOT] LIKE

The pattern matching characters are the '%' that matches zero or more characters, and '_' that matches exactly one character (where character does not always mean octet).

"LIKE" clause pattern matches always cover the entire string. To match a pattern anywhere within a string, the pattern must start and end with a percent sign.

To match a '%' or '_' in the data and not have it interpreted as a wildcard character, they MUST BE backslash escaped. That is to search for a '%' or '_' in the string:

LIKE '%\%%'	Matches any string with a '%' in it.
LIKE '%_%'	Matches any string with a '_' in it.

Strings compared using the "LIKE" clause MUST BE performed using case in-sensitive comparisons when the locale allows. (Example: in US-ASCII the compare assumes 'a' = 'A').

If the "LIKE" clause is preceded by 'NOT' then there is a match when the string compare fails.

Some property values (such as the 'recur' value type), contain commas and are not multi valued. The CS must understand the objects being compared and understand how to determine how any multi valued or multi instances properties or parameter values are separated, quoted, and backslash escaped and perform the comparisons as if each value existed by itself and not quoted or backslash escaped when comparing using the LIKE element.

See related examples in [Section 6.1.1.11](#)

[6.1.1.10](#) Empty vs. NULL

When used in a CAL-QUERY value, "NULL" means that the property or parameter is not present in the object. Parameters that are not provided and have a default value in the property are considered to exist with their default value and will not be "NULL".

If the property exists but has no value then "NULL" MUST NOT match.
If the parameter exists but has no value then "NULL" MUST NOT match.
If the parameter not present and has a default value then "NULL" MUST

NOT match.

If the property (or parameter) exists, but has no value then it matches the empty string '' (quote quote).

[6.1.1.11](#) [NOT] IN

This is similar to the "LIKE" clause, except it does value matching

Royer, et al.

Expires February 9, 2006

[Page 46]

Internet-Draft

Calendar Access Protocol (CAP)

August 2005

and not string comparison matches.

Some iCalendar objects can be multi instance and multi valued. The "IN" clause will return a match if the literal value supplied as part of the "IN" clause is contained in the value of any instance of the named property or parameter, or is in any of the multiple values in the named property or parameter. Unlike the "LIKE" clause, the '%' and '_' matching characters are not used with the "IN" clause and have no special meaning.

BEGIN:A-COMPONENT		
a	property:value1,value2	One property, two values.
b	property:"value1,value2"	One property, one value.
c	property:parameter=1,2:x	One parameter, two values.
d	property:parameter="1,2",3:y	One parameter, one value.
e	property:parameter=",":z	One parameter, one value.
f	property:x,y,z	One property, three values
END:A-COMPONENT		
	'value1' IN property	would match (a) only.
	'value1,value2' IN property	would match (b) only.
	'value%' IN property	would NOT match any.
	',' IN property	would NOT match any.
	',' IN property	would NOT match any.
	'x' IN property	would match (f) and (c).
	'2' IN parameter	would match (c) only.
	'1,2' IN parameter	would match (d) only.
	',' IN parameter	would match (e) only.
	',' IN parameter	would NOT match any.
	property LIKE 'value1%'	would match (a) and (b).
	property LIKE 'value%'	would match (a) and (b).

property LIKE 'x'	would match (f) and (c).
parameter LIKE '1%'	would match (c) and (d).
parameter LIKE '%2%'	would match (c) and (d).
parameter LIKE ','	would match (e) only.

Some property values (such as the "RECUR" value type), contain commas and are not multi valued. The CS must understand the objects being compared and understand how to determine how any multi valued or multi instances properties or parameter values are separated, quoted, and backslash escaped and perform the comparisons as if each value existed by itself and not quoted or backslash escaped when comparing using the IN element.

If the "IN" clause is preceded by 'NOT' then there is a match when

Royer, et al.

Expires February 9, 2006

[Page 47]

Internet-Draft

Calendar Access Protocol (CAP)

August 2005

the value does not exist in the property or parameter value.

[6.1.1.12](#) DATE-TIME and TIME values in a WHERE clause

All "DATE-TIME" and "TIME" literal values supplied in a "WHERE" clause MUST BE terminated with 'Z'. That means that the CUA MUST supply the values in UTC.

Valid:

```
WHERE alarm.TRIGGER < '20020201T000000Z'
AND alarm.TRIGGER > '20020101T000000Z'
```

Not valid and it is a syntax error and the CS MUST reject the QUERY.

```
WHERE alarm.TRIGGER < '20020201T000000'
AND alarm.TRIGGER > '20020101T000000'
```

[6.1.1.13](#) Multiple contained components

If a query references a component and a component or property

contained in the component, any clauses referring to the contained component or property must be evaluated on all of the contained components or properties. If any of the contained components or properties match the query, and the conditions on the containing component are also true, the component matches the query.

For example, in the query below, if a BOOKED VEVENT contains multiple VALARMS, and the VALARM.TRIGGER clause is true for any of the VALARMS in the VEVENT, then the UID, SUMMARY, and DESCRIPTION of this VEVENT would be included in the QUERY results.

```
BEGIN:VQUERY
EXPAND:TRUE
QUERY:SELECT UID,SUMMARY,DESCRIPTION FROM VEVENT
WHERE VALARM.TRIGGER >= '20000101T030405Z'
AND VALARM.TRIGGER <= '20001231T235959Z'
AND STATE() = 'BOOKED'
END:VQUERY
```

[6.1.1.14](#) Example, Query by UID

The following example would match the entire content of a "VEVENT" or "VTODO" component with the "UID" property equal to "uid123" and not expand any multiple instances of the component. If the CUA does not know if "uid123" was a "VEVENT", "VTODO", "VJOURNAL", or any other component, then all components that the CUA supports MUST BE supplied in a QUERY property. This example assumes the CUA is only interested in "VTODO" and "VEVENT" components.

If the results were empty it could also mean that "uid123" was a property in a component other than a VTODO or VEVENT.

```
BEGIN:VQUERY
QUERY:SELECT * FROM VTODO WHERE UID = 'uid123'
QUERY:SELECT * FROM VEVENT WHERE UID = 'uid123'
END:VQUERY
```

[6.1.1.15](#) Query by Date-Time range

This query selects the entire content of every booked "VEVENT" component that has an instance greater than or equal to July 1st, 2000 00:00:00 UTC and less than or equal to July 30st, 2000 23:59:59 UTC. This includes single instance "VEVENT" components that do not explicitly contain any recurrence properties or "RECURRENCE-ID" properties. This works only for CSs that have the "RECUR-EXPAND" property value set to "TRUE" in the "GET-CAPABILITY" exchange.

```
BEGIN:VQUERY
EXPAND:TRUE
QUERY:SELECT * FROM VEVENT
WHERE RECURRENCE-ID >= '20000701T000000Z'
AND RECURRENCE-ID <= '20000730T235959Z'
AND STATE() = 'BOOKED'
END:VQUERY
```

[6.1.1.16](#) Query for all Unprocessed Entries

The following example selects the entire contents of all non-booked "VTOD0" and "VEVENT" components in the "UNPROCESSED" state. The default for the "EXPAND" property is "FALSE", so the recurrence rules will not be expanded.

```
BEGIN:VQUERY
QUERYID:Fetch VEVENT and VTOD0 iTIP components
QUERY:SELECT * FROM VEVENT WHERE STATE() = 'UNPROCESSED'
QUERY:SELECT * FROM VTOD0 WHERE STATE() = 'UNPROCESSED'
END:VQUERY
```

The following example fetches all "VEVENT" and "VTOD0" components in the "BOOKED" state.

```
BEGIN:VQUERY
```



```
QUERYID:Fetch All Booked VEVENT and VTOD0 components
QUERY:SELECT * FROM VEVENT WHERE STATE() = 'BOOKED'
QUERY:SELECT * FROM VTOD0 WHERE STATE() = 'BOOKED'
END:VQUERY
```

The following fetches the "UID" property for all "VEVENT" and "VTOD0" components that have been marked for delete.

```
BEGIN:VQUERY
QUERYID:Fetch UIDs of marked for delete VEVENTs and VTOD0s
QUERY:SELECT UID FROM VEVENT WHERE STATE() = 'DELETED'
QUERY:SELECT UID FROM VTOD0 WHERE STATE() = 'DELETED'
END:VQUERY
```

[6.1.1.17](#) Query with Subset of Properties by Date/Time

In this example only the named properties will be selected and all booked and non-booked components will be selected that have a "DTSTART" value from February 1st to February 10th 2000 (in UTC).

```
BEGIN:VQUERY
QUERY:SELECT UID,DTSTART,DESCRIPTION,SUMMARY FROM VEVENT
WHERE DTSTART >= '20000201T000000Z'
AND DTSTART <= '20000210T235959Z'
END:VQUERY
```

[6.1.1.18](#) Query with Components and Alarms In A Range

This example fetches all booked "VEVENT" components with an alarm

that triggers within the specified time range. In this case only the "UID", "SUMMARY", and "DESCRIPTION" properties will be selected for all booked "VEVENTS" components that have an alarm between the two date-times supplied.

```

BEGIN:VQUERY
EXPAND:TRUE
QUERY:SELECT UID,SUMMARY,DESCRIPTION FROM VEVENT
WHERE VALARM.TRIGGER >= '20000101T030405Z'
AND VALARM.TRIGGER <= '20001231T235959Z'
AND STATE() = 'BOOKED'
END:VQUERY

```

[6.1.2](#) UPN Value Type

Value Name: UPN

Purpose: This value type is used to identify values that contain user principal name of CU or group of CU.

Formal Definition: The value type is defined by the following notation:

```

upn      ;
         = "@"
         / [ dot-atom-text ] "@" dot-atom-text
         ;
         ; dot-atom-text is defined in RFC 2822
         ;
         ;
dot-atom-text = ; As defined in [iCAL]

```

Description: This data type is an identifier that denotes a CU or a group of CU. A UPN is a [RFC 2822](#) compliant email address, with exceptions listed below, and in most cases it is deliverable to the CU. In some cases it is identical to the CU's well known email address. A CU's UPN MUST never be an e-mail address that is deliverable to a different person. And there is no requirement that a person's UPN MUST BE their e-mail address. A UPN is formatted as a user name followed by "@" followed by a Realm in the form of a valid, and unique, DNS domain name. The user name MUST BE unique within the Realm. In it's simplest form it looks like "user@example.com".

In certain cases a UPN will not be [RFC 2822](#) compliant. When

anonymous authentication is used, or anonymous authorization is being defined, the special UPN "@" will be used. When authentication MUST BE used, but unique identity MUST BE obscured, a UPN of the form @DNS-domain-name may be used. For example, "@example.com".

Example:

The following is a UPN for a CU:

jdoh@example.com

The following is a example of a UPN that could be for a group of CU:

staff@example.com

The following is a UPN for an anonymous CU belonging to a specific realm or when used as a UPN-FILTER it specifies that it applies to all UPNs in a specific realm:

@example.com

The following is a UPN for an anonymous CU:

@

[6.1.3](#) UPN-FILTER Value

Value Name: UPN-FILTER

Purpose: This value type is used to identify values that contain a user principal name filter.

Formal Definition: The value type is defined by the following notation:

Internet-Draft

Calendar Access Protocol (CAP)

August 2005

```

;
; NOTE: "CAL-OWNERS(cal-address)"
;       and "NOT CAL-OWNERS(cal-address)"
;       are both NOT allowed below.
;
upn-filter = "CAL-OWNERS()" /
             "NOT CAL-OWNERS()" /
             "*" /
             [ "*" / dot-atom-text ] "@" ( "*" / dot-atom-text )
;
; dot-atom-text is defined in RFC 2822
```

Description: The value is used to match user principal names (UPNs). For "CAL-OWNERS()" and "NOT CAL-OWNERS()", see [Section 8.24](#).

*	Matches all UPNs.
@	Matches the UPN of anonymous CUs belonging to the null realm
@*	Matches the UPN of anonymous CUs belonging to any non-null realm
@realm	Matches the UPN of anonymous CUs belonging to the specified realm.
@	Matches the UPN of non-anonymous CUs belonging to any non-null realm
*@realm	Matches the UPN of non-anonymous CUs belonging to the specified realm
user@realm	Matches the UPN of the specified CU belonging to the specified realm
user@*	Not allowed.
user@	Not allowed.

Example: The following are examples of this value type:

Royer, et al.

Expires February 9, 2006

[Page 53]

Internet-Draft

Calendar Access Protocol (CAP)

August 2005

DENY:NON CAL-OWNERS()
DENY:@hackers.example.com
DENY:*@hackers.example.com
GRANT:sam@example.com

[7.](#) New Parameters

[7.1](#) ACTION Parameter

Parameter Name: ACTION

Purpose: This parameter indicates the action to be taken when a timeout occurs.

Value Type: TEXT

Conformance: This property can be specified in the "CMD" property.

When present in a "CMD" property the "ACTION" parameter specifies the action to be taken when the command timeout expires.

Formal Definition: The parameter is defined by the following notation:

```
action-param      = ";" "ACTION" "=" ( "ASK" / "ABORT" )  
                  ; If 'action-param' is supplied then  
                  ; 'latency-param' MUST BE supplied.
```

Example: The following is an example of this parameter:

CMD;LATENCY=10;ACTION=ASK:CREATE

[7.2](#) ENABLE Parameter

Parameter Name: ENABLE

Purpose: This parameter indicates whether or not the property should be ignored. Example if a "TRIGGER" property in a "VALARM" component should be ignored.

Value Type: BOOLEAN

Conformance: This property can be specified in the "TRIGGER" properties.

Description: When a non owner sends an [iTIP](#) "REQUEST" to a calendar that object might contain a "VALARM" component. The owner may wish to have local control over their own CUA and when or how alarms are

Royer, et al.

Expires February 9, 2006

[Page 55]

Internet-Draft

Calendar Access Protocol (CAP)

August 2005

triggered.

A CUA may add the "ENABLE" parameter to any "TRIGGER" property before booking the component. If the "ENABLE" parameter is set to "FALSE", then the alarm will be ignored by the CUA. If set to "TRUE", or if the "ENABLE" property is not in the "TRIGGER" property, the alarm is enabled. This parameter may not be known by pre-CAP implementations and should not be an issue as it conforms to an 'ianaparam' as defined in [iCAL](#).

Formal Definition: The property is defined by the following notation:

```
enable-param      = "ENABLE" "=" boolean
                   ;
boolean           = ; As defined in iCAL
```

Example: The following is an example of this property for a "VAGENDA" component:

TRIGGER;ENABLE=FALSE;RELATED=END:PT5M

[7.3](#) ID Parameter

Parameter Name: ID

Purpose: When used in a "CMD" component provides a unique identifier.

Value Type: TEXT

Conformance: This parameter can be specified in the "CMD" property.

Description: If there is more than one command sent then the "ID" parameter is used to uniquely identify the command.

A CUA may add the "ID" parameter to any "CMD" property before sending the command. There must not be more than one outstanding command tagged with the same "ID" parameter value.

Formal Definition: The property is defined by the following notation:

Royer, et al.

Expires February 9, 2006

[Page 56]

Internet-Draft

Calendar Access Protocol (CAP)

August 2005

```
id-param      = ";" "ID" "=" unique-id
               ; The text value supplied is a unique value
               ; shared between the CUA and CS to uniquely
               ; identify the instance of command in the
               ; the current CUA session. The value has
               ; no meaning to other CUAs or other sessions.
               ;
unique-id      = ; text
               ;
text          = ; As defined in [iCAL].
```

Example: The following is an example of this parameter component:

CMD;UD=some-unique-value:CREATE

[7.4](#) LATENCY Parameter

Parameter Name: LATENCY

Purpose: This parameter indicates time in seconds for when a timeout occurs.

Value Type: TEXT

Conformance: This property can be specified in the "CMD" property.

When present in a "CMD" property the "LATENCY" parameter specifies the time in seconds when the command timeout expires.

Formal Definition: The parameter is defined by the following notation:

```
latency-param    = ";" "LATENCY" "=" latency-sec
                  ; The value supplied in the time in seconds.
                  ; If 'latency-param' is supplied then
                  ; 'action-param' MUST BE supplied.
                  ;
latency-sec      = posint1

; Default is zero (0) meaning no timeout.
```

Example: The following is an example of this parameter:

CMD;LATENCY=10;ACTION=ASK:CREATE

[7.5](#) LOCAL Parameter

Parameter Name: LOCAL

Purpose: Indicates if the named component should be exported to any non-organizer calendar.

Value Type: BOOLEAN

Conformance: This parameter can be specified in the "SEQUENCE" properties in a "VALARM" component.

Description: When a non owner sends an [iTIP](#) "REQUEST" to a calendar that object might contain a "VALARM" component. The owner may wish to have local control over their own CUA and when or how alarms are triggered.

A CUA may add the "LOCAL" parameter to the "SEQUENCE" property before booking the component. If the "LOCAL" parameter is set to "TRUE", then the alarm MUST NOT be forwarded to any other calendar. If set to "FALSE", or if the "LOCAL" parameter is not in the "SEQUENCE" property, the alarm is global.

Formal Definition: The property is defined by the following notation:

local-param = "LOCAL" "=" boolean

Example: The following is an example of this parameter:

SEQUENCE;LOCAL=TRUE:4

[7.6](#) LOCALIZE Parameter

Parameter Name: LOCALIZE

Purpose: If provided the "LOCALIZE" parameter specifies the desired

language for error and warning messages.

Value Type: TEXT

Conformance: This parameter can be specified in the "CMD" properties.

When the "LOCALIZE" parameter is supplied then its value MUST BE one of the values listed in the initial [\[BEEP\]](#) greeting 'localize' attribute.

A CUA may add the "LOCALIZE" parameter to the "CMD" property to specify the language of any error or warning messages.

Formal Definition: The property is defined by the following notation:

```
localize-param    = ";" "LOCALIZE" "=" beep-localize
                    ;
beep-localize     = text ; As defined in \[BEEP\]
                    ; The value supplied MUST BE one value from the initial
                    ; \[BEEP\] greeting 'localize' attribute specifying
                    ; the locale to use for error messages during
                    ; this instance of the command sent.
```

Example: The following is an example of this parameter:

```
CMD;LOCALIZE=fr_CA:CREATE
```

[7.7](#) OPTIONS Parameter

Parameter Name: OPTIONS

Purpose: If provided the "OPTIONS" parameter specifies some "CMD" property specific options.

Value Type: TEXT

Conformance: This parameter can be specified in the "CMD" properties.

A CUA adds the "OPTIONS" parameter to the "CMD" property when the command needs extra values.

Formal Definition: The property is defined by the following notation:

Internet-Draft

Calendar Access Protocol (CAP)

August 2005

```
option-param    = ";" "OPTIONS" "=" cmd-specific
                  ;
cmd-specific     = ; The value supplied is dependent on the
                  ; CMD value. See the specific CMDs for the
                  ; correct values to use for each CMD.
```

Example: The following is an example of this parameter:

```
CMD;OPTIONS=10:GENERATE-UID
```

Internet-Draft

Calendar Access Protocol (CAP)

August 2005

[8.](#) New Properties

[8.1](#) ALLOW-CONFLICT Property

Property Name: ALLOW-CONFLICT

Purpose: This property indicates whether or not the calendar and CS supports component conflicts. That is, whether or not any of the components in the calendar can overlap.

Value Type: BOOLEAN

Property Parameters: Non-standard property parameters can be specified on this property.

Conformance: This property can be specified in "VAGENDA" and "VCALSTORE" component.

Description: This property is used to indicate whether components may conflict. That is, if their expanded instances may share the same time or overlap the same time periods. If it has a value of "TRUE", then conflicts are allowed. If "FALSE", then no two components may conflict.

If "FALSE" in the "VCALSTORE" component, then all "VAGENDA" component "ALLOW-CONFLICT" property values MUST BE "FALSE" in the CS.

Formal Definition: The property is defined by the following notation:

```
allow-conflict      = "ALLOW-CONFLICT" other-params ":" boolean CRLF
```

Example: The following is an example of this property for a "VAGENDA" component:

ALLOW-CONFLICT:FALSE

[8.2](#) ATT-COUNTER Property

Property Name: ATT-COUNTER

Property Parameters: Non-standard property parameters can be specified on this property.

Royer, et al.

Expires February 9, 2006

[Page 61]

Internet-Draft

Calendar Access Protocol (CAP)

August 2005

Conformance: This property MUST be specified in an iCalendar object that specifies counter proposal to a group scheduled calendar entity. When storing a "METHOD" property with the "COUNTER" method, there needs to be a way to remember who sent the COUNTER. The ATT-COUNTER property MUST BE added to all "COUNTER" [[iTIP](#)] components by the CUA before storing in a CS.

Description: This property is used to identify the CAL-ADDRESS of the entity that sent the "COUNTER" [[iTIP](#)] object.

Formal Definition: The property is defined by the following notation:

attcounter = "ATT-COUNTER" other-params ":" cal-address CRLF

Examples:

ATT-COUNTER:cap:example.com/Doug

ATT-COUNTER:mailto:Doug@Example.com

[8.3](#) CALID Property

Property Name: CALID

Property Parameters: Non-standard property parameters can be specified on this property.

Conformance: This property can be specified in the "VAGENDA" component.

Description: This property is used to specify a fully qualified CALID.

Formal Definition: The property is defined by the following notation:

```
calid    = "CALID" other-params ":" relcalid CRLF
```

Example:

```
CALID:cap://cal.example.com/sdfifgty4321
```

[8.4](#) CALMASTER Property

Property Name: CALMASTER

Purpose: The property specifies an e-mail address of a person responsible for the calendar store.

Value Type: URI

Property Parameters: Non-standard property parameters can be specified on this property.

Conformance: The property can be specified in a "VCALSTORE" component.

Description: The parameter value SHOULD BE a MAILTO URI as defined in [\[URL\]](#). It MUST BE a contact URI such as a MAILTO URI and not a home page or file URI that describes how to contact the calmasters.

Formal Definition: The property is defined by the following notation:

```
calmaster = "CALMASTER" other-params ":" uri CRLF
;
uri       = ; IANA registered uri as defined in [iCAL]
```

Example: The following is an example of this property:

CALMASTER:mailto:administrator@example.com

[8.5](#) CAP-VERSION Property

Property Name: CAP-VERSION

Purpose: This property specifies the version of CAP supported.

Value Type: TEXT

Property Parameters: Non-standard property parameters can be specified on this property.

Conformance: This property is specified in the "VREPLY" component that is sent in response to a "GET-CAPABILITY" command.

Description: This specifies the version of CAP that the endpoint supports. The list is a comma separated list of RFC numbers supported. The list MUST contain at least XXXX (NOTE 'XXXX' WILL BE

REPLACED WITH THE RFC NUMBER OF THIS DOCUMENT).

Formal Definition: The property is defined by the following notation:

```
cap-version = "CAP-VERSION" other-params ":" text CRLF
```

Example: The following are examples of this property:

CAP-VERSION:XXXX

[8.6](#) CARID Property

Property Name: CARID

Purpose: This property specifies the identifier for an access right component.

Value Type: TEXT

Property Parameters: Non-standard property parameters can be specified on this property.

Conformance: This property MUST BE specified once in a "VCAR" component.

Description: This property is used in the "VCAR" component to specify an identifier. A "CARID" property value is unique per container.

Formal Definition: The property is defined by the following notation:

```
carid      = "CARID" other-params ":" text CRLF
```

Example: The following are examples of this property:

```
CARID:xyzzzy-007  
CARID:User Rights
```

[8.7](#) CAR-LEVEL Property

Property Name: CAR-LEVEL

Purpose: The property specifies the level of VCAR supported.

Value Type: TEXT

Property Parameters: Non-standard property parameters can be specified on this property.

Conformance: The property can be specified in a "VREPLY" component that is sent in response to a "GET-CAPABILITY" command.

Description: The value is one from a list of "CAR-NONE", "CAR-MIN", or "CAR-FULL-1". If "CAR-FULL-1" is supplied then "CAR-MIN" is also available. A "CAR-MIN" implementation only supported the "DEFAULT-VCARS" property values listed in the "VCALSTORE" component and a "CAR-MIN" implementation does not support the creation or modification of "VCAR" components from the CUA.

Formal Definition: The property is defined by the following notation:

```
car-level      = "CAR-LEVEL" ":" other-params ":" car-level-values
                ;
car-level-values = ( "CAR-NONE" / "CAR-MIN" / "CAR-FULL-1"
                    / other-levels )
                ;
other-levels    = ; Any name published in an RFC for a "CAR-LEVEL"
                ; property value.
```

Example: The following is an example of this property:

CAR-LEVEL:CAR-FULL-1

[8.8](#) COMPONENTS Property

Property Name: COMPONENTS

Purpose: The property specifies a the list of components supported by the endpoint.

Value Type: TEXT

Property Parameters: Non-standard property parameters can be

specified on this property.

Conformance: The property can be specified in a "VREPLY" component in response to a "GET-CAPABILITY" command.

Description: A comma separated list of components supported by the endpoint. If not in the list sent from the endpoint then they are not supported by that endpoint. Sending an unsupported component results in unpredictable results. This includes any components inside of other components (VALARM for example). The recommended list is "VCALSTORE,VCALENDAR,VREPLY,VAGENDA,VEVENT,VALARM,VTIMEZONE,VJOURNAL,VTODO,VALARM,DAYLIGHT,STANDARD,VCAR,VRIGHT,VQUERY"

Formal Definition: The property is defined by the following notation:

```
components      = "COMPONENTS" other-params ":" comp-list CRLF
                  ;
                  ; All of these MUST BE supplied only once.
                  ;
comp-list-req    = "VCALSTORE" "," "VCALENDAR" "," "VTIMEZONE" ","
                  "VREPLY"      "," "VAGENDA"      "," "STANDARD"      ","
                  "DAYLIGHT"
                  ; At least one MUST BE supplied. The same value
                  ; MUST NOT occur more than once.
                  ;
comp-list-min    = ( "," "VEVENT" ) / ( "," "VTODO" ) / ( "," "VJOURNAL" )
                  ; The same value MUST NOT occur
                  ; more than once. If "VCAR" is supplied then
                  ; "VRIGHT" must be supplied.
                  ;
comp-list-opt    = ( "," "VFREEBUSY" ) / ( "," "VALARM" )
                  / ( "," "VCAR" )      / ( "," "VRIGHT" )
                  / ( "," "VQUERY" )    / ( "," x-comp )
                  / ( "," iana-comp )
                  ;
comp-list        = comp-list-req 1*3comp-list-min *(comp-list-opt)
```

Example: The following is an example of this property:

```
COMPONENTS:VCALSTORE,VCALENDAR,VREPLY,VAGENDA,
VEVENT,VALARM,VTIMEZONE,VJOURNAL,VTODO,
DAYLIGHT,STANDARD,VFREEBUSY,VCAR,VRIGHT,VQUERY
```

[8.9](#) CSID Property

Property Name: CSID

Purpose: The property specifies a the globally unique identifier for the calendar store.

Value Type: URI

Property Parameters: Non-standard property parameters can be specified on this property.

Conformance: The property can be specified in a "VCALSTORE" component.

Description: The identifier MUST BE globally unique. Each CS needs its own unique identifier. The "CSID" property is the official unique identifier for the CS. If the [\[BEEP\]](#) 'serverName' attribute was supplied in the [\[BEEP\]](#) 'start' message, then the CSID will be mapped to the virtual host name supplied and the host name part of the CSID MUST BE the same as the 'serverName' value. This allows one CS implementation to service multiple virtual hosts. CS's are not required to support virtual hosting. If a CS does not support virtual hosting then it must ignore the [\[BEEP\]](#) 'serverName' attribute.

Formal Definition: The property is defined by the following notation:

```
csid = "CSID" other-params ":" capurl CRLF
```

Example: The following is an example of this property:

```
CSID:cap://calendar.example.com
```

[8.10](#) DECREED Property

Property Name: DECREED

Purpose: This property specifies if an access right calendar component is decreed or not.

Value Type: BOOLEAN

Royer, et al.

Expires February 9, 2006

[Page 67]

Internet-Draft

Calendar Access Protocol (CAP)

August 2005

Property Parameters: Non-standard property parameters can be specified on this property.

Conformance: This property MAY be specified once in a "VCAR" component.

Description: This property is used in the "VCAR" component to specify whether the component is decreed or not. If the "DECREED" property value is "TRUE" then the CUA will be unable to change the contents of the "VCAR" component and any attempt will fail with an error.

Formal Definition: The property is defined by the following notation:

decreed = "DECREED" other-params ":" boolean CRLF

Example: The following is an example of this property:

DECREED:TRUE

[8.11](#) DEFAULT-CHARSET Property

Property Name: DEFAULT-CHARSET

Purpose: This property indicates the default charset.

Value Type: TEXT

Property Parameters: Non-standard property parameters can be specified on this property.

Conformance: This property can be specified in "VAGENDA" and "VCALSTORE" calendar component.

Description: In a "VAGENDA" component this property is used to

indicate the charset of calendar. If not specified, the default is the first value in the "VCALSTORE" components "DEFAULT-CHARSET" property value list. The value MUST BE an IANA registered character set as defined in [[CHARREG](#)].

In a "VCALSTORE" component it is a comma separated list of charsets supported by the CS. The first entry is the default entry for all newly created "VAGENDA" components. The "UTF-8" value MUST BE in the "VCALSTORE" component "DEFAULT-CHARSET" property list. All compliant

Royer, et al.

Expires February 9, 2006

[Page 68]

Internet-Draft

Calendar Access Protocol (CAP)

August 2005

CAP implementations (CS and CUA) MUST support at least the "UTF-8" charset.

If a charset name contains a comma (,), then that comma must be backslashed escaped in the value.

Formal Definition: The property is defined by the following notation:

```
default-charset      = "DEFAULT-CHARSET" other-params ":" text
                      *( "," text) CRLF
```

Example: The following is an example of this property for a "VAGENDA" component:

```
DEFAULT-CHARSET:Shift_JIS,UTF-8
```

[8.12](#) DEFAULT-LOCALE Property

Property Name: DEFAULT-LOCALE

Purpose: This property specifies the default language for text values.

Value Type: TEXT

Property Parameters: Non-standard property parameters can be specified on this property.

Conformance: This property can be specified in "VAGENDA" and "VCALSTORE" components.

Description: In a "VAGENDA" component, the "DEFAULT-LOCALE" property is used to indicate the locale of the calendar. The full locale SHOULD be used. The default and minimum locale is POSIX (aka the 'C' locale).

In a "VCALSTORE" component it is a comma separated list of locales supported by the CS. The first value in the list is the default for all newly created VAGENDAs. "POSIX" MUST BE in the list.

Formal Definition: The property is defined by the following notation:

Royer, et al. Expires February 9, 2006 [Page 69]

Internet-Draft Calendar Access Protocol (CAP) August 2005

```
default-locale      = "DEFAULT-LOCALE" other-params ":" language
                      *( "," language) CRLF
                      ;
language = ; Text identifying a locale, as defined in [CHARPOL]
```

Example: The following is an example of this property:

DEFAULT-LOCALE:en-US.iso-8859-1,POSIX

[8.13](#) DEFAULT-TZID Property

Property Name: DEFAULT-TZID

Purpose: This property specifies the text value that specifies the time zones.

Value Type: TEXT

Property Parameters: Non-standard property parameters can be specified on this property.

Conformance: This property may be specified once in a "VAGENDA" and "VCALSTORE" components.

Description: A multi valued property that lists the known time zones. The first is the default. Where "TZID" property values are the same as the "TZID" property as defined in [[iCAL](#)].

If in a "VCALSTORE" component it is a comma separated list of TZIDs known to the CS. The entry is used as the default TZID list for all newly created calendars. The list MUST contain at least "UTC". A "VCALSTORE" components MUST have one "VTIMEZONE" component contained in it for each value in the "DEFAULT-TZID" property value.

If in a "VAGENDA" component it is a comma separated list of "TZID" property values naming the time zones known to the calendar. The first time zone in the list is the default and is used as the localtime for objects that contain a date or date-time value without a time zone. All "VAGENDA" components MUST have one "VTIMEZONE" component contained for each value in the "DEFAULT-TZID" property value.

If a "TZID" property value contains a comma (,), the comma must be backslash escaped.

Formal Definition: This property is defined by the following notation:

```
default-tzid      = "DEFAULT-TZID" other-params
                  ":" [tzidprefix] text
                  *("," [tzidprefix] text) CRLF
                  ;
tzidprefix         = ; As defined in [iCAL]
```

Example: The following is an example of this property:

DEFAULT-TZID:US/Mountain,UTC

[8.14](#) DEFAULT-VCARS Property

Property Name: DEFAULT-VCARS

Purpose: This property is used to specify the "CARID" property ids of the default "VCAR" components for newly created "VAGENDA" components.

Value Type: TEXT

Property Parameters: Non-standard property parameters can be specified on this property.

Conformance: This property MUST BE specified in "VCALSTORE" calendar component and MUST at least specify the following values: "READBUSYTIMEINFO", "REQUESTONLY", "UPDATEPARTSTATUS", and "DEFAULTOWNER".

Description: This property is used in the "VCALSTORE" component to specify the "CARID" value of the "VCAR" components that MUST BE copied into new "VAGENDA" components at creation time by the CS. All "DEFAULT-VCAR" values must have "VCARS" components stored in the "VCALSTORE".

Formal Definition: The property is defined by the following notation:

```
defaultl-vcars      = "DEFAULT-VCARS" other-params ":" text
                      *( " ," text ) CRLF
```

Example: The following is an example of this property:

```
DEFAULT-VCARS:READBUSYTIMEINFO,REQUESTONLY,
UPDATEPARTSTATUS,DEFAULTOWNER
```

[8.15](#) DENY Property

Property Name: DENY

Purpose: This property identifies the UPN(s) being denied access in the "VRIGHT" component.

Value Type: UPN-FILTER

Property Parameters: Non-standard property parameters can be specified on this property.

Conformance: This property can be specified in "VRIGHT" components.

Description: This property is used in the "VRIGHT" component to define the CU or UG being denied access.

Formal Definition: The property is defined by the following notation:

deny = "DENY" other-params ":" upn-filter CRLF

Example: The following are examples of this property:

DENY:*

DENY:bob@example.com

[8.16](#) EXPAND property

Property Name: EXPAND

Purpose: This property is to notify the CS if it should or should not expand any component with recurrence rules into multiple instances in a query reply.

Value Type: BOOLEAN

Property Parameters: Non-standard property parameters can be specified on this property.

Conformance: This property can be specified in "VQUERY" components.

Description: If a CUA wishes to see all of the instances of a recurring component the CUA sets EXPAND=TRUE in the "VQUERY" component. If not specified, the default is "FALSE". Note that if the CS has its "RECUR-EXPAND" CS property value set to "FALSE" then the "EXPAND" property will be ignored and the result will be as if the "EXPAND" value was set to "FALSE". The results will be bounded by any date range or other limits in the query.

Formal Definition: The property is defined by the following notation:

expand = "EXPAND" other-params ":" ("TRUE" / "FALSE") CRLF

Example: The following are examples of this property:

EXPAND:FALSE
EXPAND:TRUE

[8.17](#) GRANT Property

Property Name: GRANT

Purpose: This property identifies the UPN(s) being granted access in the "VRIGHT" component.

Value Type: UPN-FILTER

Property Parameters: Non-standard property parameters can be specified on this property.

Conformance: This property can be specified in "VRIGHT" calendar components.

Description: This property is used in the "VRIGHT" component to specify the CU or UG being granted access.

Formal Definition: The property is defined by the following notation:

grant = "GRANT" other-params ":" upn-filter CRLF

Example: The following are examples of this property:

GRANT:*

GRANT:bob@example.com

[8.18](#) ITIP-VERSION Property

Property Name: ITIP-VERSION

Purpose: This property specifies the version of ITIP supported.

Value Type: TEXT

Property Parameters: Non-standard property parameters can be specified on this property.

Conformance: This property is specified in the "VREPLY" component that is sent in response to a "GET-CAPABILITY" command.

Description: This specifies the version of ITIP that the endpoint supports. The list is a comma separated list of RFC numbers supported. The list MUST contain at least 2446 to mean [[iTIP](#)]

Formal Definition: The property is defined by the following notation:

itip-version = "ITIP-VERSION" other-params ":" text CRLF

Example: The following are examples of this property:

ITIP-VERSION:2446

[8.19](#) MAX-COMP-SIZE Property

Property Name: MAX-COMP-SIZE

Purpose: This property specifies the largest size of any object

accepted.

Value Type: TEXT

Property Parameters: Non-standard property parameters can be specified on this property.

Conformance: This property is specified in the "VREPLY" component that is sent in response to a "GET-CAPABILITY" command.

Description: A positive integer value that specifies the size of the largest iCalendar object that can be accepted in octets. Objects larger than this will be rejected. A value of zero (0) means no limit. This is also the maximum value of any [BEEP](#) payload that will be accepted or sent.

Formal Definition: The property is defined by the following notation:

max-comp-size = "MAX-COMP-SIZE" other-params ":" posint0 CRLF

Example: The following are examples of this property:

MAX-COMP-SIZE:1024

[8.20](#) MAXDATE Property

Property Name: MAXDATE

Purpose: This property specifies the date/time in the future beyond which the CS or CUA cannot represent.

Value Type: DATE-TIME

Property Parameters: Non-standard property parameters can be specified on this property.

Conformance: The property can be specified in the "VCALSTORE" component.

Description: The date and time MUST BE a UTC value and end with 'Z'.

Formal Definition: The property is defined by the following notation:

Royer, et al.

Expires February 9, 2006

[Page 75]

Internet-Draft

Calendar Access Protocol (CAP)

August 2005

maxdate = "MAXDATE" other-params ":" date-time CRLF

Example: The following is an example of this property:

MAXDATE:20990101T000000Z

[8.21](#) MINDATE Property

Property Name: MINDATE

Purpose: This property specifies the date/time in the past prior to which the server cannot represent.

Value Type: DATE-TIME

Property Parameters: Non-standard property parameters can be specified on this property.

Conformance: The property can be specified in the "VCALSTORE" component.

Description: The date and time MUST BE a UTC value and end with 'Z'.

Formal Definition: The property is defined by the following notation:

mindate = "MINDATE" other-params ":" date-time CRLF
;
date-time = ; As defined in [[iCAL](#)]

Example: The following is an example of this property:

MINDATE:19710101T000000Z

[8.22](#) MULTIPART Property

Property Name: MULTIPART

Purpose: This property provides a comma separated list of supported MIME multipart types supported by the sender.

Royer, et al. Expires February 9, 2006 [Page 76]

Internet-Draft Calendar Access Protocol (CAP) August 2005

Value Type: TEXT

Property Parameters: Non-standard property parameters can be specified on this property.

Conformance: This property is specified in the "VREPLY" component that is sent in response to a "GET-CAPABILITY" command.

Description: This property is used in the in the "GET-CAPABILITY" command reply to indicated the MIME multipart types supported. A CS and CUA SHOULD support all registered MIME multipart types.

Formal Definition: The property is defined by the following notation:

multipart = "MULTIPART" other-params ":" text *("," text) CRLF

Example: The following is an example of this property:

MULTIPART:related,alternate,mixed

[8.23](#) NAME Property

Property Name: NAME

Purpose: This property provides a localizable display name for a component.

Value Type: TEXT

Property Parameters: Non-standard property parameters can be specified on this property.

Conformance: This property can be specified in a component.

Description: This property is used in the in component to specify a localizable display name. If more than one "NAME" properties are in a component, then they MUST have unique "LANG" parameters. If the "LANG" parameter is not supplied, then it defaults to the "VAGENDA" components "DEFAULT-LOCALE" first value as the default. If the component is a "VAGENDA" then the default value is the "VAGENDA"s components "DEFAULT-LOCALE" first value as the default. A "VCALSTORE" components "DEFAULT-LOCALE" first value is the default if the component is stored at the "VCALSTORE" level.

Royer, et al.

Expires February 9, 2006

[Page 77]

Internet-Draft

Calendar Access Protocol (CAP)

August 2005

Formal Definition: The property is defined by the following notation:

```
name          = "NAME" nameparam ":" text CRLF
                ;
nameparam      = other-params [ ";" languageparam ] other-params
                ;
languageparam  = ; As defined in [iCAL].
```

Example: The following is an example of this property:

NAME:Restrict Guests From Creating VALARMS On VEVENTs

Property Name: OWNER

Purpose: The property specifies an owner of the component.

Value Type: UPN

Property Parameters: Non-standard, alternate text representation and language property parameters can be specified on this property.

Conformance: The property MUST BE specified at in a "VAGENDA" component.

Description: A multi-instanced property indicating the calendar owner.

Formal Definition: The property is defined by the following notation:

```
owner = "OWNER" other-params ":" upn CRLF
```

Example: The following is an example of this property:

```
OWNER:jsmith@example.com
```

```
OWNER:jdough@example.com
```

[8.25](#) PERMISSION Property

Property Name: PERMISSION

Purpose: This property defines a permission that is granted or denied in a "VRIGHT" component.

Value Type: TEXT

Property Parameters: Non-standard property parameters can be specified on this property.

Conformance: This property can be specified in "VRIGHT" components.

Description: This property is used in the "VRIGHT" component to define a permission that is granted or denied.

Formal Definition: The property is defined by the following notation:

```
permmision = "PERMISSION" other-params ":" permvalue CRLF
           ;
permvalue = ( "SEARCH" / "CREATE" / "DELETE"
             / "MODIFY" / "MOVE" / all
             / iana-cmd / x-cmd )
           ;
all        = "*"
           ;
iana-cmd   = ; Any command registered by IANA directly or
           ; included in an RFC that may be applied as
           ; a command.
           ;
x-cmd      = ; Any experimental command that starts with
           ; "x-" or "X-".
```

Example: The following is an example of this property:

PERMISSION:SEARCH

[8.26](#) QUERY property

Property Name: QUERY

Purpose: Specifies the query for the component.

Value Type: CAL-QUERY

Property Parameters: Non-standard property parameters can be specified on this property.

Conformance: This property can be specified in "VQUERY" components.

Description: A "QUERY" is used to specify the "CAL-QUERY" ([Section 6.1.1](#) for the query.

Formal Definition: The property is defined by the following notation:

```
query      = "QUERY" other-params ":" cal-query CRLF
```

Example: The following is an example of this property:

```
QUERY:SELECT * FROM VEVENT
```

[8.27](#) QUERYID property

Property Name: QUERYID

Purpose: Specifies a unique ID for a query in the targeted container.

Value Type: TEXT

Property Parameters: Non-standard property parameters are specified on this property.

Conformance: This property can be specified in "VQUERY" components.

Description: A "QUERYID" property is used to specify the unique id for a query. A "QUERYID" property value is unique per container.

Formal Definition: The property is defined by the following notation:

```
queryid    = "QUERYID" other-params ":" text CRLF
```

Example: The following are examples of this property:

QUERYID:Any Text String
QUERYID:fetchUnProcessed

[8.28](#) QUERY-LEVEL Property

Property Name: QUERY-LEVEL

Purpose: This property specifies the level of query supported.

Value Type: TEXT

Property Parameters: Non-standard property parameters can be specified on this property.

Conformance: The property can be specified in the "VREPLY" component in response to a "GET-CAPABILITY" command.

Description: Indicates level of query support. CAL-QL-NONE is for CS's that allow ITIP methods only to be deposited and nothing else.

Formal Definition: The property is defined by the following notation:

```
query-level = "QUERY-LEVEL" other-params  
              ":" ( "CAL-QL-1" / "CAL-QL-NONE") CRLF
```

Example: The following is an example of this property:

QUERY-LEVEL:CAL-QL-1

[8.29](#) RECUR-ACCEPTED Property

Property Name: RECUR-ACCEPTED

Purpose: This property specifies if the endpoint supports recurring instances.

Value Type: BOOLEAN

Property Parameters: Non-standard property parameters can be specified on this property.

Internet-Draft

Calendar Access Protocol (CAP)

August 2005

Conformance: The property can be specified in the "VREPLY" component in response to a "GET-CAPABILITY" command.

Description: Indicates if recurrence rules are supported. If "FALSE" then the endpoint can not process any kind of recurring rules.

Formal Definition: The property is defined by the following notation:

recur-accepted = "RECUR-ACCEPTED" other-params ":" boolean CRLF

Example: The following is an example of this property:

```
RECUR-ACCEPTED:TRUE  
RECUR-ACCEPTED:FALSE
```

[8.30](#) RECUR-LIMIT Property

Property Name: RECUR-LIMIT

Purpose: This property specifies the maximum number of instances the endpoint will expand instances into at query or storage time.

Value Type: INTEGER

Property Parameters: Non-standard property parameters can be specified on this property.

Conformance: The property can be specified in the "VREPLY" component in response to a "GET-CAPABILITY" command.

Description: For implementations that have the "STORES-EXPANDED" value set to "TRUE", then this value specifies the maximum number of instances that will be stored and fetched. For all implementations this is the maximum number of instances that will be returned when the "EXPAND" parameter is specified as "TRUE" and the results contain a infinite or large number of recurring instances.

Formal Definition: The property is defined by the following notation:

```
recur-limit = "RECUR-LIMIT" other-params ":" posint1 CRLF
```

Royer, et al.

Expires February 9, 2006

[Page 82]

Internet-Draft

Calendar Access Protocol (CAP)

August 2005

Example: The following is an example of this property:

```
RECUR-LIMIT:1000
```

[8.31](#) RECUR-EXPAND Property

Property Name: RECUR-EXPAND

Purpose: This property specifies if the endpoint can expand recurrences into multiple objects.

Value Type: BOOLEAN

Property Parameters: Non-standard property parameters can be specified on this property.

Conformance: The property can be specified in the "VREPLY" component in response to a "GET-CAPABILITY" command.

Description: If "TRUE" then the endpoint can expand an object into multiple instances as defined by its recurrence rules when the "EXPAND" property is supplied. If "FALSE" then the endpoint ignores the "EXPAND" property.

Formal Definition: The property is defined by the following notation:

```
recur-expand = "RECUR-EXPAND" other-params ":" boolean CRLF
```

Example: The following is an example of this property:

RECUR-EXPAND:TRUE
RECUR-EXPAND:FALSE

[8.32](#) RESTRICTION Property

Property Name: RESTRICTION

Purpose: This property defines restrictions on the result value of new or existing components.

Royer, et al.

Expires February 9, 2006

[Page 83]

Internet-Draft

Calendar Access Protocol (CAP)

August 2005

Value Type: CAL-QUERY

Property Parameters: Non-standard property parameters can be specified on this property.

Conformance: This property can be specified in "VRIGHT" components, but only when the "PERMISSION" property is set to "CREATE", "MODIFY", or "*" property value.

Description: This property is used in the "VRIGHT" component to define restrictions on the components that can be written (i.e., by using the "CREATE" or "MOVE" commands) as well as on the values that may take existent calendar store properties, calendar properties, components, and properties (i.e., by using the "MODIFY" command). Accepted values MUST match any specified "RESTRICTION" property values.

Formal Definition: The property is defined by the following notation:

restriction = "RESTRICTION" other-params ":" cal-query CRLF

Example: The following are examples of this property:

RESTRICTION:SELECT * FROM VCALENDAR WHERE METHOD = 'REQUEST'

RESTRICTION:SELECT * FROM VEVENT WHERE
SELF() IN ORGANIZER

RESTRICTION:SELECT * FROM VEVENT WHERE 'BUSINESS' IN
CATEGORIES

[8.33](#) SCOPE Property

Property Name: SCOPE

Purpose: This property identifies the objects in the CS to which the access rights applies.

Value Type: CAL-QUERY

Property Parameters: Non-standard property parameters can be specified on this property.

Royer, et al.

Expires February 9, 2006

[Page 84]

Internet-Draft

Calendar Access Protocol (CAP)

August 2005

Conformance: This property can be specified in "VRIGHT" components.

Description: This property is used in the "VRIGHT" component to define the set of objects subject to the access right being defined.

Formal Definition: The property is defined by the following notation:

scope = "SCOPE" other-params ":" cal-query CRLF

Example: The following is an example of this property:

SCOPE:SELECT DTSTART,DTEND FROM VEVENT WHERE CLASS = 'PUBLIC'

[8.34](#) STORES-EXPANDED Property

Property Name: STORES-EXPANDED

Purpose: This property specifies if the sending endpoint expands recurrence rules prior to storing them into the CS.

Value Type: BOOLEAN

Property Parameters: Non-standard property parameters can be specified on this property.

Conformance: This property can be specified in a "VREPLY" component in response to a "GET-CAPABILITY" command.

Description: If the value is "TRUE" then the endpoint expands recurrence rules and then stores the results into the CS. If this is "TRUE" then the "RECUR-LIMIT" property is significant because an infinitely recurring appointment will be stored no more than "RECUR-LIMIT" property values into the CS and all other instances will be lost.

Formal Definition: The property is specified by the following notation:

stores-expanded = "STORES-EXPANDED" other-params ":" boolean CRLF

The following is an example of this property:

STORES-EXPANDED:TRUE
STORES-EXPANDED:FALSE

[8.35](#) TARGET Property

Property Name: TARGET

Purpose: This property defines the container that the command that is

issued will act upon. Its value is a capurl as defined in [Section 5](#).

Value Type: URI

Property Parameters: Non-standard property parameters can be specified on this property.

Conformance: This property can be specified in a command component.

Description: This property value is used to specify the container that the command will effect. When used in a command, the command will be performed on the container which has a capurl matching the value.

Formal Definition: The property is specified by the following notation:

```
target    = "TARGET" other-params ":" ( capurl / relcalid ) CRLF
```

The following is an example of this property:

```
TARGET:cap://mycal.example.com  
TARGET:SomeRelCalid
```

[8.36](#) TRANSP Property

Property Name: TRANSP

Royer, et al.

Expires February 9, 2006

[Page 86]

Internet-Draft

Calendar Access Protocol (CAP)

August 2005

Purpose: This property defines whether an component is transparent or not to busy time searches. This is a modification to [\[iCAL\]](#) "TRANSP" property in that it adds some values.

Value Type: TEXT

Property Parameters: Non-standard property parameters can be

specified on this property.

Conformance: This property can be specified in a component.

Description: Time Transparency is the characteristic of an object that determines whether it appears to consume time on a calendar. Objects that consume actual time for the individual or resource associated with the calendar SHOULD be recorded as "OPAQUE", allowing them to be detected by free-busy time searches. Other objects, which do not take up the individual's (or resource's) time SHOULD be recorded as "TRANSPARENT", making them invisible to free-busy time searches.

Formal Definition: The property is specified by the following notation:

```
transp      = "TRANSP" other-params ":" transvalue CRLF
              ;
transvalue   = "OPAQUE" ;Blocks or opaque on busy time searches.
              / "TRANSPARENT" ;Transparent on busy time searches.
              / "TRANSPARENT-NOCONFLICT" ; Transparent on busy time
              ; searches and no other OPAQUE or OPAQUE-NOCONFLICT objects
              ; can overlap it.
              ;
              / "OPAQUE-NOCONFLICT" ; Opaque on busy time
              ; searches and no other OPAQUE or OPAQUE-NOCONFLICT objects
              ; can overlap it.
              ;
              ; Default value is OPAQUE
```

The following is an example of this property for an object that is opaque or blocks on free/busy time searches plus no other object can overlap it:

TRANSP:OPAQUE-NOCONFLICT

9. New Components

9.1 VAGENDA Component

Component Name: VAGENDA

Purpose: Provide a grouping of properties that defines an agenda.

Formal Definition: There are two formats of the "VAGENDA" component. (1) When it is being created, and (2) how it exists in the "VCALSTORE" component.

A "VAGENDA" component in a "VCALSTORE" component is defined by the following notes and ABNF notation:

CALSCALE - The value MUST BE from the "VCALSTORE" "CALSCALE" property list. The default is the first entry in the VCALSTORE CALSCALE list.

CREATED - The timestamp of the calendar's create date. This is a READ ONLY property in a "VAGENDA".

LAST-MODIFIED - The timestamp of any change to the "VAGENDA" properties or when any component was last created, modified, or deleted.

Internet-Draft

Calendar Access Protocol (CAP)

August 2005

```
agenda      = "BEGIN" ":" "VAGENDA" CRLF
              agendaprop
              *(icalobject)      ; as defined in [iCAL]
              "END" ":" "VAGENDA" CRLF
              ;
agendaprop   = *(
              ; The following MUST occur exactly once.
              ;
              allow-conflict / relcalid / calscale / created
              / default-charset / default-locale
              / default-tzid / last-mod
              ;
              ; The following MUST occur at least once.
              ; and the value MUST NOT be empty.
              ;
              / owner
              ;
              ; The following are optional,
              ; and MAY occur more than once.
              ;
              / name / related-to / other-props / x-comp
              )

icalobject = ; As defined in [iCAL]
            ;
created    = ; As defined in [iCAL]
            ;
related-to = ; As defined in [iCAL]
```

When creating a VAGENDA, use the following notation:

```
agendac      = "BEGIN" ":" "VAGENDA" CRLF
               agendacprop
               *(icalobject)      ; as defined in [iCAL]
               "END" ":" "VAGENDA" CRLF
               ;
agendacprop  = *(
               ; The following MUST occur exactly once.
               ;
               allow-conflict / relcalid / calscale
               / default-charset / default-locale
               / default-tzid
               ;
               ; The following MUST occur at least once.
               ; and the value MUST NOT be empty.
               ;
               / owner
               ;
               ; The following are optional,
               ; and MAY occur more than once.
               ;
               / name / related-to / other-props / x-comp
               )
```

To fetch all of the properties from the targeted "VAGENDA" component.
This does not fetch any components:

```
SELECT * FROM VAGENDA
```

To fetch all of the properties from the targeted VAGENDA and all of
the contained components, use the special '*' value:

SELECT *.* FROM VAGENDA

[9.2](#) VCALSTORE Component

Component Name: VCALSTORE

Purpose: Provide a grouping of properties that defines a calendar store.

Royer, et al.

Expires February 9, 2006

[Page 90]

Internet-Draft

Calendar Access Protocol (CAP)

August 2005

Formal Definition: A "VCALSTORE" component is defined by the following table and ABNF notation. The creation of a "VCALSTORE" component is an administrative task and not part of the CAP protocol.

The following are notes to some of the properties in the "VCALSTORE" component.

CALSCALE - A comma separated list of CALSCALEs supported by this CS. All "VAGENDA" component calendar CALSCALE properties MUST BE from this list. This list MUST contain at least "GREGORIAN". The default for newly created "VAGENDA" components is the first entry.

RELATED-TO - This is a multiple instance property. There must be a "RELATED-TO" property MUST for each of the "VAGENDA" components contained in the "VCALSTORE" component each with the "RELTYPE" parameter value set to "CHILD". Other "RELATED-TO" properties may be included.

CREATED - The timestamp of the CS creation time. This is a READ ONLY property.

CSID - The CSID of this calendar store. MUST NOT be empty. How this property is set in the VCALSTORE is an administrative or implementation specific issue and is not covered in CAP. This is a READ ONLY property. A suggested value is the fully qualified host name or a fully qualified virtual host name supported by the system.

LAST-MODIFIED - The timestamp when the Properties of the "VCALSTORE"

component were last updated or calendars were created or deleted.
This is a READ ONLY PROPERTY.

```
calstorec      = "BEGIN" ":" "VCALSTORE" CRLF
                 calstoreprop
                 *(vagendac)
                 "END" ":" "VCALSTORE" CRLF
                 ;
calstoreprop   = *(
                 ; the following MUST occur exactly once
                 ;
                 allow-conflict / calscale / calmaster
                 / created / csid / default-charset
                 / default-locale / default-vcars
                 / default-tzid / last-mod / maxdate / mindate
                 ;
                 ; the following are optional,
                 ; and MAY occur more than once
                 ;
                 / name / related-to / other-props / x-comp
                 )
                 ;
vagendac       = ; As defined in [iCAL].
                 ;
last-mod       = ; As defined in [iCAL].
```


To fetch all of the properties from the targeted VCALSTORE and not fetch the calendars that it contains:

```
SELECT * FROM VCALSTORE
```

To fetch all of the properties from the targeted "VCALSTORE" component and all of the contained calendars and all of those calendars contained properties and components, use the special '*.*' value:

```
SELECT *.* FROM VCALSTORE
```

[9.3](#) VCAR Component

Component Name: VCAR

Purpose: Provide a grouping of calendar access rights.

Royer, et al.

Expires February 9, 2006

[Page 92]

Internet-Draft

Calendar Access Protocol (CAP)

August 2005

Formal Definition: A "VCAR" component is defined by the following notation:

```
carc      = "BEGIN" ":" "VCAR" CRLF
            carprop 1*rightc
            "END" ":" "VCAR" CRLF
            ;
carprop = 1*(
            ;
            ; 'carid' is REQUIRED,
            ; but MUST NOT occur more than once
            ;
            carid /
            ;
            )
```

```
; the following are OPTIONAL,  
; and MAY occur more than once  
;  
name / decreed / other-props  
)
```

Description: A "VCAR" component is a grouping of properties, and "VRIGHT" components, that represents access rights granted or denied to UPNs.

The "CARID" property specifies the local identifier for the "VCAR" component. The "NAME" property specifies a localizable display name.

Example: In the following example, the UPN "foo@example.com" is given search access to the "DTSTART" and "DTEND" VEVENT properties. No other access is specified:

```
BEGIN:VCAR  
CARID:View Start and End Times  
NAME:View Start and End Times  
BEGIN:VRIGHT  
GRANT:foo@example.com  
PERMISSION:SEARCH  
SCOPE:SELECT DTSTART,DTEND FROM VEVENT  
END:VRIGHT  
END:VCAR
```

In this example, all UPNs are given search access to "DTSTART" and "DTEND" properties of VEVENT components. "All CUs and UGs" are specified by the UPN value "*". Note that this enumerated UPN value

is not in quotes:

```
BEGIN:VCAR  
CARID:ViewStartEnd2  
NAME:View Start and End Times 2  
BEGIN:VRIGHT  
GRANT:*
```

```
PERMISSION:SEARCH
SCOPE:SELECT DTSTART,DTEND FROM VEVENT
END:VRIGHT
END:VCAR
```

In these examples, full calendar access rights are given to the CAL-OWNERS(), and a hypothetical administrator is given access rights to specify calendar access rights. If no other rights are specified, only these two UPNs can specify calendar access rights:

```
BEGIN:VCAR
CARID:some-id-3
NAME:Only OWNER or ADMIN Settable VCARS
BEGIN:VRIGHT
GRANT:CAL-OWNERS()
PERMISSION:*
SCOPE:SELECT * FROM VAGENDA
END:VRIGHT
BEGIN:VRIGHT
GRANT:cal-admin@example.com
PERMISSION:*
SCOPE:SELECT * FROM VCAR
RESTRICTION:SELECT * FROM VCAR
END:VRIGHT
END:VCAR
```

In this example, rights to write, search, modify or delete calendar access rights are denied to all UPNs. This example would disable providing different access rights to the calendar store or calendar. This calendar access right should be specified with great care, as it removes the ability to change calendar access; even for the owner or administrator. It could be used by small devices that do not support the changing of any VCAR:

```
BEGIN:VCAR
```

```
CARID:VeryRestrictiveVCAR-2
NAME:No CAR At All
BEGIN:VRIGHT
DENY:*
PERMISSION:*
SCOPE:SELECT * FROM VCAR
END:VRIGHT
END:VCAR
```

[9.4](#) VRIGHT Component

Component Name: "VRIGHT"

Purpose: Provide a grouping of properties that describe an access right (granted or denied).

Formal Definition: A "VRIGHT" component is defined by the following notation:

```
rightc      = "BEGIN" ":" "VRIGHT" CRLF
              rightprop
              "END" ":" "VRIGHT" CRLF
              ;
rightprop = 2*(
              ;
              ; either 'grant' or 'deny' MUST
              ; occur at least once
              ; and MAY occur more than once
              ;
              grant / deny /
              ;
              ; 'permission' MUST occur at least once
              ; and MAY occur more than once
              ;
              permission /
              ;
              ; the following are optional,
              ; and MAY occur more than once
              ;
              scope / restriction / other-props
              )
```

Description: A "VRIGHT" component is a grouping of calendar access

right properties.

The "GRANT" property specifies the UPN that is being granted access. The "DENY" property specifies the UPN is being denied access. The "PERMISSION" property specifies the actual permission being set. The "SCOPE" property identifies the calendar store properties, calendar properties, components, or properties to which the access right applies. The "RESTRICTION" property specifies restriction on the value that may take calendar store properties, calendar properties, calendar components, and properties after a "CREATE" or "MODIFY" command. Values MUST match all the instances of the "RESTRICTION" property to be valid.

[9.5](#) VREPLY Component

Component Name: "VREPLY"

Purpose: Provide a grouping of arbitrary properties and components that are the data set result from an issued command.

Formal Definition: A "VREPLY" component is defined by the following notation:

```
replc          = "BEGIN" ":" "VREPLY" CRLF
                  any-prop-or-comp
                  "END" ":" "VREPLY" CRLF
                  ;
any-prop-or-comp = ; Zero or more iana or experimental
                  ; properties and components, in any order.
```

Description: Provide a grouping of arbitrary properties and components that are the data set result from an issued command.

A query can return a predictable set of arbitrary properties and components. This component is used by query and other commands to return data that does not fit into any other component. It may contain any valid property or component, even if they are not registered.

[9.6](#) VQUERY Component

Component Name: VQUERY

Purpose: A component describes a set of objects to be acted upon.

Formal Definition: A "VQUERY" component is defined by the following

notation:

```
queryc      = "BEGIN" ":" "VQUERY" CRLF
              queryprop
              "END" ":" "VCAR" CRLF
              ;
queryprop = 1*(
              ;
              ; 'queryid' is OPTIONAL but MUST NOT occur
              ; more than once. If the "TARGET" property
              ; is supplied then the "QUERYID" property
              ; MUST BE supplied.
              ;
              queryid / target
              ;
              ; 'expand' is OPTIONAL but MUST NOT occur
              ; more than once.
              ;
              expand
              ;
              ; the following are OPTIONAL, and MAY occur
              ; more than once
              ;
              / name / other-props
              ;
              ; the following MUST occur at least once if
              ; queryid is not supplied.
              ;
              / query
              )
```

Description: A "VQUERY" contains properties that describe which properties and components the CS is requested to act upon.

The "QUERYID" property specifies the local identifier for a "VQUERY" component.

For a search, if the "TARGET" property is supplied in a "VQUERY" component, then the CS is to search for the query in the CALID supplied by the "TARGET" property value.

For a create the "TARGET" property MUST NOT be supplied as the destination container is already supplied in the "TARGET" property of the "VCALENDAR" component.

For examples, see [Section 6.1.1](#).

Royer, et al.

Expires February 9, 2006

[Page 97]

Internet-Draft

Calendar Access Protocol (CAP)

August 2005

[10](#). Commands and Responses

CAP commands and responses are described in this section.

[10.1](#) CAP Commands (CMD)

All commands are send using the CMD property.

Property Name: CMD

Purpose: The property defines the command to be sent.

Value Type: TEXT

Property Parameters: Non-standard, id, localize, latency, action or options.

Conformance: This property is the method used to specify the commands to a CS and can exist in any object sent to the CS.

Description: All of the commands to the CS are supplied in this property. The "OPTIONS" parameter is overloaded and its meaning is dependent on the CMD value supplied.

Formal Definition: The property is defined by the following notation:

```
cmd          = "CMD" (  
              abort-cmd  
              / continue-cmd  
              / create-cmd  
              / delete-cmd
```

```

        / generate-uid-cmd
        / get-capability-cmd
        / identify-cmd
        / modify-cmd
        / move-cmd
        / reply-cmd
        / search-cmd
        / set-locale-cmd
        / iana-cmd
        / x-cmd
        ) CRLF
;
option-value = "OPTION" "=" paramtext
;
paramtext    ; As defined in [iCAL]

```

Calendaring commands allow a CUA to directly manipulate a calendar.

Calendar access rights can be granted or denied for any commands.

[10.1.1](#) Bounded Latency

A CAP command can have an associated maximum latency time by specifying the "LATENCY" parameter. If the command is unable to be completed in the specified amount of time (as specified by the "LATENCY" parameter value with an "ACTION" parameter set to the "ASK" value), then a "TIMEOUT" command MUST BE sent on the same channel to which there MUST BE a an "ABORT" or a "CONTINUE" command reply. If the CUA initiated the original command, then the CS would issue the "TIMEOUT" command and the CUA would then have to issue an "ABORT" or "CONTINUE" command. If the CS initiated the original command then the CUA would have to issue the "TIMEOUT" and the CS would send the "ABORT" or "CONTINUE".

Upon receiving an "ABORT" command, the command must then be terminated. Only the "ABORT", "TIMEOUT", "REPLY, and "CONTINUE" commands can not be aborted. The "ABORT", "TIMEOUT", and "REPLY" commands MUST NOT have latency set.

Upon receiving a "CONTINUE" command the work continues as if it had not been delayed or stopped. Note that a new latency time MAY BE

included in a "CONTINUE" command indicating to continue the original command until the "LATENCY" parameter value expires or the results of the original command can be returned.

Both the "LATENCY" parameter and the "ACTION" parameter MUST BE supplied to any "CMD" property, or neither can be added to the "CMD" property. The "LATENCY" parameter MUST BE set to the maximum latency time in seconds. The "ACTION" parameter accepts the following values: "ASK" and "ABORT" parameters.

If the maximum latency time is exceeded and the "ACTION" parameter is set to the "ASK" value, then "TIMEOUT" command MUST BE sent. Otherwise if the "ACTION" parameter is set to the "ABORT" value then the command MUST BE terminated and return a REQUEST-STATUS code of 2.0.3 for the original command.

If a CS can both start sending the reply to a command and guarantee that all of the results can be sent from a command (short of something like network or power failure) prior to the "LATENCY" timeout value then the "LATENCY" time has not expired.

Example:

In this example the initiator asks for the listeners capabilities.

```
I: Content-Type: text/calendar
I:
I: BEGIN:VCALENDAR
I: VERSION:2.0
I: PRODID:The CUA's PRODID
I: CMD;ID=xyz12346;LATENCY=3;ACTION=ask:GET-CAPABILITY
I: END:VCALENDAR
```

After 3 seconds

```
L: Content-Type: text/calendar
L:
L: BEGIN:VCALENDAR
L: PRODID:-//someone's prodid
L: VERSION:2.0
```

L: CMD;ID=xyz12346:TIMEOUT
L: END:VCALENDAR

In order to continue and give the CS more time then the CUA would issue a "CONTINUE" command:

I: Content-Type: text/calendar
I:
I: BEGIN:VCALENDAR
I: VERSION:2.0
I: PRODID:-//someone's prodid
I: CMD;ID=xyz12346;LATENCY=3;ACTION=ask:CONTINUE
I: END:VCALENDAR

L: Content-Type: text/calendar
L:
L: BEGIN:VCALENDAR
L: VERSION:2.0
L: PRODID:-//someone's prodid
L: CMD;ID=xyz12346:REPLY
L: BEGIN:VREPLY
L: REQUEST-STATUS:2.0.3;Continued for 3 more seconds
L: END:VREPLY
L: END:VCALENDAR

Above the "2.0.3" status is returned because it is not an error, it is a progress status sent in reply to the "CONTINUE" command.

To abort the command and not wait any further then issue an "ABORT" command:

I: Content-Type: text/calendar
I:
I: BEGIN:VCALENDAR
I: VERSION:2.0
I: PRODID:-//someone's prodid
I: CMD;ID=xyz12346:ABORT
I: END:VCALENDAR

Which would result in a 2.0.3 reply.

```
L: Content-Type: text/calendar
L:
L: BEGIN:VCALENDAR
L: VERSION:2.0
L: PRODID:-//someone's prodid
L: CMD;ID=xyz12346:REPLY
L: BEGIN:VREPLY
L: REQUEST-STATUS:2.0.3;Aborted As Requested.
L: END:VREPLY
L: END:VCALENDAR
```

If the "ACTION" value had been set to "ABORT", then the listener would send a "7.0" error on timeout in the reply to the command that initiated the command that timed out.

[10.2](#) ABORT Command

CMD: ABORT

Purpose: The "ABORT" command is sent to request that the named or only in process command be aborted. Latency MUST not be supplied with the "ABORT" command.

Formal Definition: An "ABORT" command is defined by the following notation:

```
abort-cmd    = abortparam ":" "ABORT"
              ;
abortparam    = *(
```

```

; the following are optional,
; but MUST NOT occur more than once
;
  id-param
/ localize-param
;
; the following is optional,
; and MAY occur more than once
;
/ other-params
)

```

The REPLY of any "ABORT" command is:

```

abort-reply = "BEGIN" ":" "VCALENDAR" CRLF
             calprops
             abort-vreply
             "END" ":" "VCALENDAR" CRLF
;
abort-vreply = "BEGIN" ":" "VREPLY" CRLF
              rstatus
              other-props
              "END" ":" "VREPLY" CRLF

```

[10.3](#) CONTINUE Command

CMD: CONTINUE

Purpose: The "CONTINUE" command is only sent after a "TIMEOUT" command has been received to inform the other end of the session to resume working on a command.

Formal Definition: A "CONTINUE" command is defined by the following notation:

```
continue-cmd    = continueparam ":" "CONTINUE"
                  ;
continueparam    = *(
                  ;
                  ; the following are optional,
                  ; but MUST NOT occur more than once
                  ;
                  id-param
                  / localize-param
                  / latency-param
                  ;
                  ; the following MUST occur exactly once and only
                  ; when the latency-param has been supplied and
                  ; MUST NOT be supplied if the latency-param is
                  ; not supplied.
                  ;
                  / action-param
                  ;
                  ; the following are optional,
                  ; and MAY occur more than once
                  ;
                  / other-params
                  )
```

The REPLY of any "CONTINUE" command is:

```
continue-reply   = "BEGIN" ":" "VCALENDAR" CRLF
                  calprops
                  continue-vreply
                  "END" ":" "VCALENDAR" CRLF
                  ;
continue-vreply   = "BEGIN" ":" "VREPLY" CRLF
                  rstatus
                  other-props
                  "END" ":" "VREPLY" CRLF
```

[10.4](#) CREATE Command

CMD: CREATE

Purpose: The "CREATE" command is used to create one or more iCalendar objects in the store in the "BOOKED" or "UNPROCESSED" state.

A CUA MAY send a "CREATE" command to a CS. The "CREATE" command MUST

BE implemented by all CSs.

The CS MUST NOT send a "CREATE" command to any CUA.

Formal Definition: A "CREATE" command is defined by the following notation and the hierarchy restrictions as defined in [Section 3.2](#):

```
create-cmd      = createparam ":" "CREATE"
                  ;
createparam     = *(
                  ;
                  ; the following are optional,
                  ; but MUST NOT occur more than once
                  ;
                  id-param
                  / localize-param
                  / latency-param
                  ;
                  ; the following MUST occur exactly once and only
                  ; when the latency-param has been supplied and
                  ; MUST NOT be supplied if the latency-param is
                  ; not supplied.
                  ;
                  / action-param
                  ;
                  ; the following is optional,
                  ; and MAY occur more than once
                  ;
                  / other-params
                  )
```

Response:

One iCalendar object per TARGET property MUST BE returned.

The REPLY of any "CREATE" command is:

Restriction Table for the iCalendar section of a reply that contains

an iCalendar object is any valid [[iTIP](#)] response plus any from this ABNF:

```
create-reply    = "BEGIN" ":" "VCALENDAR" CRLF
                  creply-props
                  1*(create-vreply)
                  "END" ":" "VCALENDAR" CRLF
                  ;
create-vreply   = "BEGIN" ":" "VREPLY" CRLF
                  created-id
                  rstatus
                  other-props
                  "END" ":" "VREPLY" CRLF
                  ;
                  ; Where the id is appropriate for the
                  ; type of object created:
                  ;
                  ; VAGENDA = relcalid
                  ; VALARM = sequence
                  ; VCAR = carid
                  ; VEVENT, VFREEBUSY, VJOURNAL, VTOD0 = uid
                  ; VQUERY = queryid
                  ; VTIMEZONE = tzid
                  ; x-comp = x-id
                  ;
created-id      = ( relcalid / carid / uid / queryid /
                    tzid / sequence / x-id )
                  ;
tzid            = ; As defined in [iCAL]
                  ;
sequence       = ; As defined in [iCAL]
                  ;
uid            = ; As defined in [iCAL]
                  ;
x-id           = ; An ID for an x-component.
                  ;
```

```

creply-props = 4*(
    ; These are REQUIRED and MUST NOT occur
    ; more than once.
    ;
    prodid /version / target / reply-cmd
    ;
    ; These are optional, and may occur more
    ; than once.
    ;
    other-props )

```

For a "CREATE" command the "TARGET" property specifies the containers where the components will be created.

If the iCalendar object being created does not have a "METHOD" property, then is not an [\[iTIP\]](#) object, then its state will be "BOOKED". Use the "DELETE" command to set the state of an object to the "DELETED" state (tagged for deletion). A CUA can not use the "CREATE" command to create an object in the "DELETED" state.

If the intention is to book an [\[iTIP\]](#) object then the "METHOD" property MUST NOT BE supplied. Otherwise any [\[iTIP\]](#) object MUST have a valid [\[iTIP\]](#) "METHOD" property value and it is a scheduling request being deposited into the CS and will have its state set to "UNPROCESSED" state.

ABNF for a "CREATE" object is:

```

create-object = "BEGIN" ":" "VCALENDAR" CRLF
    ; If 'calprops' contain the "METHOD" property
    ; then this 'create-object' component MUST
    ; conform to \[iTIP\] restrictions.
    ;
    ; calprops MUST include 'create-cmd'
    ;
    calprops
    other-props
    1*(create-comp)
    "END" ":" "VCALENDAR" CRLF

```



```

; NOTE: The 'VCALSTORE' component is not included in
; 'create-comp' as it is out of scope for CAP to create
; a new CS.
;
create-comp =  agendac / carc / queryc
               / timezonec / freebusyc
               / eventc / todoc / journalc
               / iana-comp / x-comp
;
freebusyc    = ; As defined in [iCAL]
;
eventc       = ; As defined in [iCAL]
;
journalc     = ; As defined in [iCAL]
;
timezonec    = ; As defined in [iCAL]
;
todoc        = ; As defined in [iCAL]

```

In the following example two new top level "VAGENDA" components are

created. Note that the "CSID" value of the server is cal.example.com which is where the new "VAGENDA" components are going to be created.

```

C: Content-Type: text/calendar
C:
C: BEGIN:VCALENDAR
C: PRODID:-//someone's prodid
C: VERSION:2.0
C: CMD;ID=creation01:CREATE
C: TARGET:cal.example.com
C: BEGIN:VAGENDA                                <- data for 1st new calendar
C: CALID:relcalz1
C: NAME;LANGUAGE=en_US:Bill's Soccer Team
C: OWNER:bill
C: CALMASTER:mailto:bill@example.com
C: TZID:US/Pacific
C: END:VAGENDA

```

```

C: BEGIN:VAGENDA                                <- data for 2nd new calendar
C: CALID:relcalz2
C: NAME;LANGUAGE=EN-us:Mary's personal calendar
C: OWNER:mary
C: CALMASTER:mailto:mary@example.com
C: TZID:US/Pacific
C: END:VAGENDA
C: END:VCALENDAR

S: Content-Type: text/calendar
S:
S: BEGIN:VCALENDAR
S: VERSION:2.0
S: PRODID:-//someone's prodid
S: CMD;ID=creation01:REPLY
S: TARGET:cal.example.com
S: BEGIN:VREPLY                                <- Reply for 1st calendar create
S: CALID:relcalz1
S: REQUEST-STATUS:2.0
S: END:REPLY
S: BEGIN:VREPLY                                <- Reply for 2nd calendar create
S: CALID:relcalz2
S: REQUEST-STATUS:2.0
S: END:VREPLY
S: END:VCALENDAR

```

To create a new component in multiple containers simply name all of the containers in the "TARGET" in the create command. Here a new

"VEVENT" component is created in two TARGET components. In this example, the "VEVENT" component is one new [\[iTIP\]](#) "REQUEST" to be stored in two calendars. The results would be iCalendar objects that conform to the [\[iTIP\]](#) replies as defined in [\[iTIP\]](#).

This example shows two [\[iTIP\]](#) "VEVENT" components being created in each of the two supplied "TARGET" properties and as it contains the "METHOD" property they will be stored in the "UNPROCESSED" state:

```

C: Content-Type: text/calendar
C:

```

```
C: BEGIN:VCALENDAR
C: VERSION:2.0
C: PRODID:-//someone's prodid
C: CMD;ID=creation02:CREATE
C: METHOD:REQUEST
C: TARGET:relcalz1
C: TARGET:relcalz2
C: BEGIN:VEVENT
C: DTSTART:20030307T180000Z
C: UID:FirstInThisExample-1
C: DTEND:20030307T190000Z
C: SUMMARY:Important Meeting
C: END:VEVENT
C: BEGIN:VEVENT
C: DTSTART:20040307T180000Z
C: UID:SecondInThisExample-2
C: DTEND:20040307T190000Z
C: SUMMARY:Important Meeting
C: END:VEVENT
C: END:VCALENDAR
```

The CS sends the "VREPLY" commands in separate MIME objects, one per supplied "TARGET" property value.

```
S: Content-Type: text/calendar
S:
S: BEGIN:VCALENDAR
S: VERSION:2.0
S: PRODID:-//someone's prodid
```

```

S: CMD;ID=creation02:REPLY
S: TARGET:relcalz1      <- 1st TARGET listed.
S: BEGIN:REPLY          <- Reply for 1st VEVENT create in 1st TARGET.
S: UID:FirstInThisExample-1
S: REQUEST-STATUS:2.0
S: END:VREPLY
S: BEGIN:REPLY          <- Reply for 2nd VEVENT crate in 1st TARGET.
S: UID:SecondInThisExample-2
S: REQUEST-STATUS:2.0
S: END:VREPLY
S: END:VCALENDAR

```

And the second reply for the 2nd TARGET:

```

S: Content-Type: text/calendar
S:
S: BEGIN:VCALENDAR
S: VERSION:2.0
S: PRODID:-//someone's prodid
S: CMD;ID=creation02:REPLY
S: TARGET:relcalz2      <- 2nd TARGET listed
S: BEGIN:REPLY          <- Reply for 1st VEVENT create in 2nd TARGET.
S: UID:FirstInThisExample-1
S: REQUEST-STATUS:2.0
S: END:VREPLY
S: BEGIN:REPLY          <- Reply for 2nd VEVENT crate in 2nd TARGET.
S: UID:SecondInThisExample-2
S: REQUEST-STATUS:2.0
S: END:VREPLY
S: END:VCALENDAR

```

[10.5](#) DELETE Command

CMD: DELETE

Purpose: The "DELETE" command physically removes the QUERY result from the store or marks it for deletion.

A CUA MAY send a "DELETE" command to a CS. The "DELETE" command MUST

BE implemented by all CSs.

The CS MUST NOT send a "DELETE" command to any CUA.

Formal Definition: A "DELETE" command is defined by the following notation:

```
delete-cmd    = deleteparam ":" "DELETE"
                ;
deleteparam   = *(
                ;
                ; the following are optional,
                ; but MUST NOT occur more than once
                ;
                id-param
                / localize-param
                / latency-param
                / option-param "MARK"
                ;
                ; The following MUST occur exactly once and only
                ; when the latency-param has been supplied and
                ; MUST NOT be supplied if the latency-param is
                ; not supplied.
                ;
                / action-param
                ;
                ; the following is optional,
                ; and MAY occur more than once
                ;
                / other-params
                )
```

The "DELETE" command is used to delete calendars or components. The included "VQUERY" component(s) specifies the container(s) to delete.

If a component is to be marked for delete and not physically removed, then include the "OPTIONS" parameter with its value set to the "MARK" value in order to alter its state to "DELETED".

When components are deleted, only the top most component "REQUEST-STATUS" properties are returned. No "REQUEST-STATUS" properties are returned for components inside of the selected components. There MUST BE one "VREPLY" component returned for each object that is deleted or marked for delete. Note that if no "VREPLY" components are returned then nothing matched and nothing was deleted.

Internet-Draft

Calendar Access Protocol (CAP)

August 2005

Restriction Table for the "REPLY" command for any "DELETE" command.

```
delete-reply    = "BEGIN" ":" "VCALENDAR" CRLF
                  calprops    ; MUST include 'reply-cmd'
                  *(delete-vreply)
                  "END" ":" "VCALENDAR" CRLF
delete-vreply   = "BEGIN" ":" "VREPLY" CRLF
                  deleted-id
                  rstatus
                  "END" ":" "VREPLY" CRLF
                  ;
                  ; Where the id is appropriate for the
                  ; type of object deleted:
                  ;
                  ; VAGENDA = relcalid
                  ; VCAR = carid
                  ; VEVENT, VFREEBUSY, VJOURNAL, VTOD = uid
                  ; VQUERY = queryid
                  ; ALARM = sequence
                  ; VTIMEZONE = tzid
                  ; x-comp = x-id
                  ; An instance = uid recurid
                  ;
deleted-id       = ( relcalid / carid / uid / uid recurid
                    / queryid / tzid / sequence / x-id )
```

Example to delete a "VEVENT" component with "UID" value of 'abcd12345' from the calendar "relcald-22" from the current CS:

```
C: Content-Type: text/calendar
C:
C: BEGIN:VCALENDAR
C: TARGET:relcalid-22
C: CMD;ID:"random but unique per CUA":DELETE
C: BEGIN:VQUERY
C: QUERY:SELECT VEVENT FROM VAGENDA WHERE UID = 'abcd12345'
C: END:VQUERY
C: END:VCALENDAR

S: BEGIN:VCALENDAR
S: TARGET:relcalid-22
S: CMD;ID:"random but unique per CUA":REPLY
S: BEGIN:VREPLY
S: UID:abcd12345
S: REQUEST-STATUS:3.0
S: END:VREPLY
S: END:VCALENDAR
```

One or more iCalendar objects will be returned that contain a "REQUEST-STATUS" properties for the deleted components. There could have been more than one component deleted. Any booked and any number of unprocessed [[iTIP](#)] scheduling components that matched the QUERY value in the above example. Each unique "METHOD" property value that was deleted from the store MUST BE in a separate iCalendar object. This is because only one "METHOD" property is allowed in a single "VCALENDAR" BEGIN/END block.

[10.6](#) GENERATE-UID Command

CMD: GENERATE-UID

Purpose: The "GENERATE-UID" command returns one or more unique identifiers which MUST BE globally unique.

The "GENERATE-UID" command MAY BE sent to any CS. The "GENERATE-UID" command MUST BE implemented by all CSs.

The "GENERATE-UID" command MUST NOT be sent to a CUA.

Formal Definition: A "GENERATE-UID" command is defined by the following notation:

```
generate-uid-cmd = gnuuidparam ":" "GENERATE-UID"
;
gnuuidparam      = *(
;
; The following are optional,
; but MUST NOT occur more than once.
;
; id-param
/ localize-param
/ latency-param
;
; The following MUST occur exactly once and only
; when the latency-param has been supplied and
; MUST NOT be supplied if the latency-param is
; not supplied.
;
/ action-param
;
; The following is optional,
; and MAY occur more than once.
;
/ other-params
;
; The following MUST BE supplied exactly once.
; The value specifies the number of UIDs to
; be returned.
;
/ option-param posint1
```


)

Response:

```
gen-reply    = "BEGIN" ":" "VCALENDAR" CRLF
               calprops           ; Which MUST include 'reply-cmd'
               1*(gen-vreply)
               "END" ":" "VCALENDAR" CRLF
```

```
gen-vreply   = "BEGIN" ":" "VREPLY" CRLF
               1*(uid)
               rstatus
               "END" ":" "VREPLY" CRLF
```

Example:

```
C: BEGIN:VCALENDAR
C: VERSION:2.0
C: PRODID:-//someone's prodid
C: CMD;ID=unique-per-cua-124;OPTIONS=5:GENERATE-UID
C: END:VCALENDAR
```

```
S: Content-Type: text/calendar
S:
S: BEGIN:VCALENDAR
S: VERSION:2.0
S: PRODID:-//someone's prodid
S: CMD;ID=unique-per-cua-124:REPLY
S: BEGIN:VREPLY
S: UID:20011121T120000Z-12340@cal.example.com
S: UID:20011121T120000Z-12341@cal.example.com
S: UID:20011121T120000Z-12342@cal.example.com
S: UID:20011121T120000Z-12343@cal.example.com
S: UID:20011121T120000Z-12344@cal.example.com
S: REQUEST-STATUS:2.0
S: END:VREPLY
S: END:VCALENDAR
```

[10.7](#) GET-CAPABILITY Command

CMD: GET-CAPABILITY

Purpose: The "GET-CAPABILITY" command returns the capabilities of the other end point of the session.

A CUA MUST send a "GET-CAPABILITY" command to a CS after the initial connection. A CS MUST send a "GET-CAPABILITY" command to a CUA after the initial connection. The "GET-CAPABILITY" command and reply MUST BE implemented by all CSs and CUAs.

Formal Definition: A "GET-CAPABILITY" command is defined by the following notation:

```
get-capability-cmd  = capibiltyparam ":" "GET-CAPABILITY"
                      ;
capibiltyparam      = *(
                      ;
                      ; the following are optional,
                      ; but MUST NOT occur more than once
                      ;
                      id-param / localize-param / latency-param
                      ;
                      ; the following MUST occur exactly once and only
                      ; when the latency-param has been supplied and
                      ; MUST NOT be supplied if the latency-param is
                      ; not supplied.
                      ;
```

```

/ action-param
;
; the following is optional,
; and MAY occur more than once
;
/ other-params
)

```

Response:

The "GET-CAPABILITY" command returns information about the Calendar other end of the session given the current state of the connection. The values returned may differ depending on current user identify and the security level of the connection.

Client implementations SHOULD NOT require any capability element beyond those defined in this specification or future RFC publications, and MAY ignore any nonstandard, experimental capability elements. The "GET-CAPABILITY" reply may return different results depending on the UPN and if the UPN is authenticated.

When sending a reply to a "GET-CAPABILITY" command, all of these MUST BE supplied. The following properties are returned in response to a "GET-CAPABILITY" command:

```

cap-vreply      = "BEGIN" ":" "VCALENDAR" CRLF
                  ; The following properties may be in any order.
                  ;
                  prodid
                  version
                  reply-cmd
                  other-props

```

```

"BEGIN" ":" "VREPLY" CRLF
; The following properties may be in any order.
;
cap-version
car-level
components
stores-expanded

```

maxdate
mindate
itip-version
max-comp-size
multipart
query-level
recur-accepted
recur-expand
recur-limit
other-props
"END" ":" "VREPLY" CRLF
"END" ":" "VCALENDAR" CRLF

Example:

I: Content-Type: text/calendar
I:
I: BEGIN:VCALENDAR
I: VERSION:2.0
I: PRODID:-//someone's prodid
I: CMD;ID=unique-per-cua-125:GET-CAPABILITY
I: END:VCALENDAR

L: Content-Type: text/calendar
L:
L: BEGIN:VCALENDAR
L: VERSION:2.0
L: PRODID:-//someone's prodid
L: CMD;ID=unique-per-cua-125:REPLY
L: BEGIN:VREPLY
L: CAP-VERSION:1.0
L: PRODID:The CS prodid
L: QUERY-LEVEL:CAL-QL-1
L: CAR-LEVEL:CAR-FULL-1
L: MAXDATE:99991231T235959Z
L: MINDATE:00000101T000000Z
L: MAX-COMPONENT-SIZE:0
L: COMPONENTS:VCALENDAR,VTOD, VJOURNAL,VEVENT,VCAR,
L: VALARM,VFREEBUSY,VTIMEZONE,STANDARD,DAYLIGHT,VREPLY
L: ITIP-VERSION:2446
L: RECUR-ACCEPTED:TRUE

L: RECUR-EXPAND:TRUE
L: RECUR-LIMIT:0
L: STORES-EXPANDED:FALSE
L: X-INET-PRIVATE-COMMANDS:1.0
L: END:VREPLY
L: END:VCALENDAR

[10.8](#) IDENTIFY Command

CMD: IDENTIFY

Purpose: The "IDENTIFY" command allows the CUA to set a new identity to be used for calendar access.

A CUA MAY send an "IDENTIFY" command to a CS. The "IDENTIFY" command MUST BE implemented by all CSs. A CS implementation MAY reject all "IDENTIFY" commands.

The CS MUST NOT send a "IDENTIFY" command to any CUA.

Formal Definition: A "IDENTIFY" command is defined by the following notation:

Internet-Draft

Calendar Access Protocol (CAP)

August 2005

```
identify-cmd    = identifyparam ":" "IDENTIFY"
;
identifyparam   = *(
;
; the following are optional,
; but MUST NOT occur more than once
;
; id-param
/ localize-param
/ latency-param
;
; the following MUST occur exactly once and only
; when the latency-param has been supplied and
; MUST NOT be supplied if the latency-param is
; not supplied.
;
/ action-param
;
; the following is optional,
; and MAY occur more than once
;
/ other-params
;
; The value is the UPN of the requested
; identity. If option is not supplied it is
; a request to return to the original authenticated
; identity.
;
/ option-param upn
)
```

Response:

A "REQUEST-STATUS" property wrapped in a "VREPLY" component with one request-status codes:

2.0 Successful.

6.4 Identity not permitted. VCAR restriction.

The CS determines through an internal mechanism if the credentials supplied at authentication permit the operation as the selected

identity. If they do, the session assumes the new identity, otherwise a security error is returned.

Example:

```
C: Content-Type: text/calendar
C:
C: BEGIN:VCALENDAR
C: VERSION:2.0
C: PRODID:-//someone's prodid
C: CMD;ID=unique-per-cua-999;OPTIONS=newUserId:IDENTIFY
C: END:VCALENDAR
```

```
S: Content-Type: text/calendar
S:
S: BEGIN:VCALENDAR
S: VERSION:2.0
S: PRODID:-//someone's prodid
S: BEGIN:VREPLY
S: REQUEST-STATUS:2.0;Request Approved
S: END:VREPLY
S: END:VCALENDAR
```

Or if denied:

```
S: Content-Type: text/calendar
S:
S: BEGIN:VCALENDAR
S: PRODID:-//someone's prodid
S: VERSION:2.0
S: BEGIN:VREPLY
S: REQUEST-STATUS:6.4;Request Denied
S: END:VREPLY
S: END:VCALENDAR
```

And for the CUA to return to its original authenticated identity the OPTIONS parameter is omitted:

```
C: Content-Type: text/calendar
C:
C: BEGIN:VCALENDAR
```

C: VERSION:2.0
C: PROPID:-//someone's proid
C: CMD;ID=unique-per-cua-995:IDENTIFY
C: END:VCALENDAR

The CS may accept (2.0) or deny (6.4) the request to return to the original identity.

If a CS considers the "IDENTIFY" command an attempt to violate security, the CS MAY terminate the [BEEP] session without any further notice to the CUA after sending the "REQUEST-STATUS" 6.4 reply.

Royer, et al. Expires February 9, 2006 [Page 119]

Internet-Draft Calendar Access Protocol (CAP) August 2005

[10.9](#) MODIFY Command

CMD: MODIFY

Purpose: The "MODIFY" command is used to modify existing components.

A CUA MAY send a "MODIFY" command to a CS. The "MODIFY" command MUST BE implemented by all CSs.

The CS MUST NOT send a "MODIFY" command to any CUA.

Formal Definition: A "MODIFY" command is defined by the following notation:

```
modify-cmd    = modifyparam ":" "MODIFY"
               ;
modifyparam   = *(
               ;
               ; the following are optional,
               ; but MUST NOT occur more than once
               ;
               id-param
               / localize-param
               / latency-param
               ;
               ; the following MUST occur exactly once and only
               ; when the latency-param has been supplied and
               ; MUST NOT be supplied if the latency-param is
```



```
; not supplied.  
;  
/ action-param  
;  
; the following is optional,  
; and MAY occur more than once  
;  
/ other-params  
)
```

The "MODIFY" command is used to modify existing components. The TARGET property specifies the calendars where the components exist that are going to be modified.

The format of the request is three components inside of "VCALENDAR" component:

```
BEGIN:VCALENDAR  
...  
BEGIN:VQUERY  
...  
END:VQUERY  
BEGIN:XXX  
...old-values...  
END:XXX  
BEGIN:XXX  
...new-values...  
END:XXX  
END:VCALENDAR
```

The "VQUERY" component selects the components that are to be modified.

Where "XXX" above is a named component type (VEVENT, VTODO, ...). Both the old and new components MUST BE of the same type.

The old-values is a component and the contents of that component are going to change and may contain information that helps uniquely

identify the original component (SEQUENCE in the example below). If the CS can not find a component that matches the QUERY and does not have at least all of the OLD-VALUES, then a 6.1 error is returned.

The new-values is a component of the same type as old-values and new-values contains the new data for each selected component. Any data that is in old-values and not in new-values is deleted from the selected component. Any values in new-values that was not in old-values is added to the component.

In this example the "VEVENT" component with a "UID" property value of 'unique-58' has; the "LOCATION" property and "LAST-MODIFIED" property changed, the "VALARM" component with the "SEQUENCE" property with a value of "3" has its "TRIGGER" property disabled, the "X-LOCAL" property is removed from the "VEVENT" component, and a "COMMENT" property is added.

Because "SEQUENCE" property is used to locate the "VALARM" component in this example, both the old-values and the new-values contain the "SEQUENCE" property with a value of "3" and if the "SEQUENCE" property were to be left out of new-values, it would have been deleted.

Example:

```
C: Content-Type: text/calendar
C:
C: BEGIN:VCALENDAR
C: VERSION:2.0
C: PRODID:-//someone's prodid
C: TARGET:my-cal
C: CMD:ID=unique-mod:MODIFY
C: BEGIN:VQUERY                                <- Query to select data set.
C: QUERY:SELECT * FROM VEVENT WHERE UID = 'unique-58'
C: END:VQUERY
C: BEGIN:VEVENT                                <- Start of old data.
C: LOCATION:building 3
C: LAST-MODIFIED:20020101T123456Z
```

```

C: X-LOCAL:some private stuff
C: BEGIN:VALARM
C: SEQUENCE:3
C: TRIGGER;RELATED=END:PT5M
C: END:VALARM
C: END:VEVENT                <- End of old data.
C: BEGIN:VEVENT              <- Start of new data.
C: LOCATION:building 4
C: LAST-MODIFIED:20020202T010203Z
C: COMMENT:Ignore global trigger.
C: BEGIN:VALARM
C: SEQUENCE:3
C: TRIGGER;ENABLE=FALSE:RELATED=END:PT5M
C: END:VALARM
C: END:VEVENT                <- End of new data.
C: END:VCALENDAR

```

The "X-LOCAL" property was not supplied in the new-values, so it was deleted. The "LOCATION" property value was altered, as was the "LAST-MODIFIED" value. The "VALARM" component with a "SEQUENCE" property value of "3" had its "TRIGGER" property disabled, and the "SEQUENCE" property value did not change so it was not effected. The "COMMENT" property was added.

When it comes to inline ATTACHMENTS, the CUA only needs to uniquely identify the contents of the ATTACHMENT value in the old-values in order to delete them. When the CS compares the attachment data it is compared in its binary form. The ATTACHMENT value supplied by the CUA MUST BE valid encoded information.

For example, to delete the same huge inline attachment from every VEVENT in 'my-cal' that has an "ATTACH" property value with the old-

values:

```

BEGIN:VCALENDAR
VERSION:2.0
PRODID:-//someone's prodid
TARGET:my-cal
CMD:MODIFY

```

```

BEGIN:VQUERY
QUERY:SELECT ATTACH FROM VEVENT
END:VQUERY
BEGIN:VEVENT
ATTACH;FMTTYPE=image/basic;ENCODING=BASE64;VALUE=BINARY:
  MIICajCCAdOgAwIBAgICBEUwDQYJKoZIhvcNAQEEBQAwdzELMAkGA1U
  EBhMCVVMxLDAqBgNVBAoTI05ldHNjYXBlIENvbW11bmljYXRpb25zIE
  ...< remainder of attachment data NOT supplied >....
END:VEVENT
BEGIN:VEVENT
END:VEVENT
END:VCALENDAR

```

Above the new-values is empty, so everything in the old-values is deleted.

Furthermore, the following additional restrictions apply:

1. One can not change the "UID" property of a component.
2. If a contained component is changed inside of a selected component, and that contained component has multiple instances, then old-values MUST contain information that uniquely identifies the instance or instances that are changing. It is valid to change more than one. As all contained components that match old-values will be modified. In the first modify example above, if "SEQUENCE" properties were to be deleted from both the old-values and new-values, then all "TRIGGER" properties that matched the old-values in all "VALARM" components in the selected "VEVENT" components would be disabled.
3. The result of the modify MUST BE a valid iCalendar object.

Response:

A "VCALENDAR" component is returned with one or more "REQUEST-STATUS" property values.

If any error occurred:

No component will be changed at all. That is, it will appear just

as it was prior to the modify and the CAP server SHOULD return a "REQUEST-STATUS" property for each error that occurred.

There MUST BE at least one error reported.

If multiple components are selected, then what uniquely identified the component MUST BE returned (UID, QUERYID, ...) if the component contains a unique identifier. If not, sufficient information to uniquely identify the modified components MUST BE returned in the reply.

```
S: Content-Type: text/calendar
S:
S: BEGIN:VCALENDAR
S: TARGET:relcalid
S: CMD;ID=delete#1:REPLY
S: BEGIN:VREPLY
S: BEGIN:VEVENT
S: UID:123
S: REQUEST-STATUS:2.0
S: END:VEVENT
S: END:VREPLY
S: END:VCALENDAR
```

[10.10](#) MOVE Command

CMD: MOVE

Purpose: The "MOVE" command is used to move components within the CS.

A CUA MAY send a "MOVE" command to a CS. The "MOVE" command MUST BE implemented by all CSs.

The CS MUST NOT send a "MOVE" command to any CUA.

Formal Definition: A "MOVE" command is defined by the following notation:

```
move-cmd    = moveparam ":" "MOVE"
              ;
moveparam    = *(
              ;
              ; the following are optional,
              ; but MUST NOT occur more than once
              ;
              id-param
              / localize-param
              / latency-param
              ;
              ; the following MUST occur exactly once and only
              ; when the latency-param has been supplied and
              ; MUST NOT be supplied if the latency-param is
              ; not supplied.
              ;
              / action-param
              ;
              ; the following is optional,
              ; and MAY occur more than once
              ;
              / other-params
              ;
              )
```

Response:

The REQUEST-STATUS in a VCALENDAR object.

The content of each "result" is subject to the result restriction table defined below.

The access control on the "VAGENDA" component after it has been moved to its new location in the calstore MUST BE at least as secure as it was prior to the move. If the CS is not able to ensure the same level of security, a permission denied "REQUEST-STATUS" property value MUST BE returned and the "MOVE" command not performed.

The "TARGET" property value specifies the new location, and the "VQUERY" component specifies the old location.

Restriction Table for the "REPLY" command of any "MOVE" command.

```
move-reply = "BEGIN" ":" "VCALENDAR" CRLF
             calprops
             1*(move-vreply)
             "END" ":" "VCALENDAR" CRLF
```

```
move-vreply = "BEGIN" ":" "VREPLY" CRLF
              move-id
              rstatus
              "END" ":" "VREPLY" CRLF
```

```
; Where the id is appropriate for the
; type of object moved:
;
; VAGENDA = relcalid
; VCAR = carid
; VEVENT, VFREEBUSY, VJOURNAL, VTODOLIST = uid
; VQUERY = queryid
; ALARM = sequence
; An instance = uid recurid
; x-comp = x-id
;
```

```
move-id      = ( relcalid / carid / uid / uid recurid
                 / queryid / tzid / sequence / x-id)
```

Example: moving the VAGENDA Nellis to Area-51

```
C: Content-Type: text/calendar
C:
C: BEGIN:VCALENDAR
C: VERSION:2.0
C: PRODID:-//someone's prodid
C: CMD:MOVE
C: TARGET:Area-51
C: BEGIN:VQUERY
C: QUERY: SELECT * FROM VAGENDA WHERE CALID='Nellis'
C: END:VQUERY
C: END:VCALENDAR
```

```
S: Content-Type: text/calendar
S:
S: BEGIN:VCALENDAR
S: VERSION:2.0
S: PRODID:-//someone's prodid
S: TARGET:Area-51
S: BEGIN:VREPLY
S: CALID:Nellis
S: REQUEST-STATUS: 2.0
S: END:VREPLY
S: END:VCALENDAR
```

[10.11](#) REPLY Response to a Command

CMD: REPLY

Purpose: The "REPLY" value to the "CMD" property is used to return the results of all other commands to the CUA.

A CUA MUST send a "REPLY" command to a CS for any command a CS MAY send to the CUA. The "REPLY" command MUST BE implemented by all CUAs that support getting the "GET-CAPABILITY" command.

A CS MUST send a "REPLY" command to a CUA for any command a CUA MAY send to the CS. The "REPLY" command MUST BE implemented by all CSs.

Formal Definition: A "REPLY" command is defined by the following notation:

```
reply-cmd    = replyparam ":" "REPLY"
              ;
replyparam    = *(
              ;
              ; The 'id' parameter value MUST BE exactly the
              ; same as the value sent in the original
              ; CMD property. If the original CMD did
              ; not have an 'id' parameter, then the 'id'
              ; MUST NOT be supplied in the REPLY.
              ;
              id-param
              ;
              ; the following is optional,
              ; and MAY occur more than once
              ;
              / other-params
              )
```

[10.12](#) SEARCH Command

CMD: SEARCH

Purpose: The "SEARCH" command is used to return selected components

to the CUA.

A CUA MAY send a "SEARCH" command to a CS. The "SEARCH" command MUST BE implemented by all CSs.

The CS MUST NOT send a "SEARCH" command to any CUA.

Formal Definition: A "SEARCH" command is defined by the following notation:

```
search-cmd  = searchparam ":" "SEARCH"
;
searchparam = *(
;
; the following are optional,
; but MUST NOT occur more than once
;
; id-param
/ localize-param
/ latency-param
;
; the following MUST occur exactly once and only
; when the latency-param has been supplied and
; MUST NOT be supplied if the latency-param is
; not supplied.
;
/ action-param
;
```

```
; the following is optional,  
; and MAY occur more than once  
;  
/ other-params  
)
```

The format of the request is the search command (search-cmd) followed by one or more (query) "VQUERY" components

Response:

The data in each result set contains one or more iCalendar components composed of all the selected results enclosed in a single "VREPLY" component per "QUERY".

Only "REQUEST-STATUS" property and the properties mentioned in the "SELECT" clause of the QUERY are included in the components. Each "VCALENDAR" component is tagged with the "TARGET" property.

Searching for objects

In the example below objects on March 10,1999 between 080000Z and 190000Z are read. In this case only 4 properties for each objects are returned. Two calendars are specified. Only booked (vs scheduled) entries are to be returned (this example only selected VEVENT objects):

```
C: Content-Type: text/calendar  
C:  
C: BEGIN:VCALENDAR  
C: VERSION:2.0  
C: PRODID:-//someone's prodid  
C: CMD:SEARCH  
C: TARGET:relcal2  
C: TARGET:relcal3  
C: BEGIN:VQUERY  
C: QUERY:SELECT DTSTART,DTEND,SUMMARY,UID  
C: FROM VEVENT
```

```
C: WHERE DTEND >= '19990310T080000Z'
C: AND DTSTART <= '19990310T190000Z'
C: AND STATE() = 'BOOKED'
C: END:VQUERY
C: END:VCALENDAR
```

The return values are subject to VCAR filtering. That is, if the request contains properties to which the UPN does not have access, those properties will not appear in the return values. If the UPN has access to at least one property of the component, but has been denied access to all properties called out in the request, the response will contain a single "REQUEST-STATUS" property indicating the error.

Here the request was successful, however one of the "VEVENT" components contents were not accessible (4.1).

```
S: Content-Type: text/calendar
S:
S: BEGIN:VCALENDAR
S: TARGET:relcalid
S: CMD:REPLY
S: VERSION:2.0
S: PRODID:-//someone's prodid
S: BEGIN:VREPLY
S: BEGIN:VEVENT
S: REQUEST-STATUS:4.1
S: END:VEVENT
S: BEGIN:VEVENT
S: REQUEST-STATUS:2.0
S: UID:123
S: DTEND:19990310T080000Z
S: DSTART:19990310T190000Z
S: SUMMARY: Big meeting
S: END:VEVENT
```

```
S: END:VREPLY
S: END:VCALENDAR
```

If the UPN has no access to any components at all, the response will simply be an empty data set. The response looks the same if there the particular components did not exist.

```
S: Content-Type: text/calendar
S:
S: BEGIN:VCALENDAR
S: VERSION:2.0
S: PRODID:-//someone's prodid
S: CMD:REPLY
S: TARGET:ralcalid
S: BEGIN:VREPLY
S: REQUEST-STATUS:2.0
S: END:VREPLY
S: END:VCALENDAR
```

If there are multiple targets, each iCalendar reply is contained within its own iCalendar object.

[10.12.1](#) Searching for VFREEBUSY

If a CS sets the "RECUR-EXPAND" property to "TRUE" and contains the "VFREEBUSY" component in the "COMPONENTS" value in a reply to the "GET-CAPABILITY" command, then it is the CS's responsibility and not the CUA's responsibility to provide the correct "VFREEBUSY" information for a calendar.

If a CUA issues a "CREATE" "VFREEBUSY", such a CS MUST return success and not store the "VFREEBUSY" component as the results would never be used.

Such a CS MUST dynamically create the results of a search for "VFREEBUSY" components at search time when searching for STATE() = 'BOOKED' items.

If a CUA searches for "VFREEBUSY" components with STATE() = 'UNPROCESSED', such a CS MUST return a "VREPLY" with no components.

If a CUA searches for "VFREEBUSY" components without specifying the STATE, such a CS MUST return the same result as if STATE()='BOOKED' had been specified.

For CSs that set the "CAPABILITY" "RECUR-EXPAND" property to "FALSE" and have the "VFREEBUSY" component in the "COMPONENTS" value in the "CAPABILITY" reply, a CUA MAY store the "VFREEBUSY" information on the CS. These CSs then MUST return a "VFREEBUSY" component calculated from the stored components. If no "VFREEBUSY" information is available for the "TARGET" calendar, then a "VFREEBUSY" with no blocked out time will be returned with a success code. A CUA sets the "VFREEBUSY" time on a those calendars by creating a "VFREEBUSY" component without a "METHOD" creating a "BOOKED" entry.

If a CS does not set the "VFREEBUSY" value in the "COMPONENTS" "CAPABILITY" value, the CS does not support the "VFREEBUSY" component and all creation and searching for a "VFREEBUSY" component MUST fail. Examples of calendars that may be in this category are public event calendars that will never require scheduling with other UPNs.

[10.13](#) SET-LOCALE Command

CMD: SET-LOCALE

Purpose: The "SET-LOCALE" command is used to select the locale that will be used in error codes used in the "REQUEST-STATUS" property.

A CUA MAY send a "SET-LOCALE" command to a CS. The SET-LOCALE command MUST BE implemented by all CSs.

The CS MUST NOT send a "SET-LOCALE" command to any CUA.

Formal Definition: A "SET-LOCALE" command is defined by the following notation:

```
setlocale-cmd    = setlocaleparam ":" "SET-LOCALE"
                  ;
setlocaleparam   = *(
                  ;
                  ; the following are optional,
                  ; but MUST NOT occur more than once
                  ;
                  id-param
                  / localize-param
                  / latency-param
                  / setlocale-option
                  ;
                  ; the following MUST occur exactly once and only
                  ; when the latency-param has been supplied and
                  ; MUST NOT be supplied if the latency-param is
                  ; not supplied.
                  ;
                  / action-param
                  ;
                  ; the following is optional,
                  ; and MAY occur more than once
                  ;
                  / other-params )

setlocale-option = option-param newlocale
                  ;
newlocale        = ; Any locale supplied in the initial [BEEP]
                  ; "greeting" "localize" parameter and
                  ; and any charset supported by the CS
                  ; and listed in the DEFAULT-CHARSET property
                  ; of the VCALSTORE.
```

Examples:

```
CMD:OPTIONS=en_US.UTF-8:SET-LOCALE
CMD:OPTIONS=th_TH.ISO8859-11:SET-LOCALE
CMD:OPTIONS=es_MX.ISO8859-1:SET-LOCALE
```

Restriction Table for the "REPLY" command of any "SET-LOCAL" command.

Royer, et al.

Expires February 9, 2006

[Page 133]

Internet-Draft

Calendar Access Protocol (CAP)

August 2005

```
setlocale-reply = "BEGIN" ":" "VCALENDAR" CRLF
                 calprops
                 1*(setlocale-vreply)
                 "END" ":" "VCALENDAR" CRLF
```

```
setlocale-vreply = "BEGIN" ":" "VREPLY" CRLF
                  rstatus
                  "END" ":" "VREPLY" CRLF
```

10.14 TIMEOUT Command

CMD: TIMEOUT

Purpose: The "TIMEOUT" command is only sent after a command has been sent with a latency value set. When received it means the command could not be completed in the time allowed.

Formal Definition: A "TIMEOUT" command is defined by the following notation:

```
timeout-cmd    = timeoutparam ":" "TIMEOUT"

timeoutparam   = *(
                ; the following are optional,
                ; but MUST NOT occur more than once
                id-param
                / localize-param
                / other-params
                )
```


[10.15](#) Response Codes

Numeric response codes are returned using the "REQUEST-STATUS" property.

The format of these codes is described in [[iCAL](#)], and extend in [[iTIP](#)] and [[iMIP](#)]. The following describes new codes added to this set and how existing codes apply to CAP.

At the application layer response codes are returned as the value of a "REQUEST-STATUS" property. The value type of this property is modified from that defined in [[iCAL](#)], in order to make the accompanying "REQUEST-STATUS" property text optional.

Royer, et al.

Expires February 9, 2006

[Page 134]

Internet-Draft

Calendar Access Protocol (CAP)

August 2005

Code	Description
2.0	Success. The parameters vary with the operation and are specified.
2.0.3	In response to the client issuing an "abort" reply, this reply code indicates that any command currently underway was successfully aborted.
3.1.4	Capability not supported.
4.1	Calendar store access denied.
6.1	Container not found.
6.2	Attempt to create or modify an object such that it would overlap another object in either of the following two circumstances: (a) One of the objects has a TRANSP property set to OPAQUE-NOCONFLICT or TRANSPARENT-NOCONFLICT. (b) The calendar's ALLOW-CONFLICT property is set to FALSE.

- 6.3 Bad args.
- 6.4 Permission denied - VCAR restriction.
A VCAR exists and the CS will not perform the operation.
- 7.0 A timeout has occurred. The server was unable to complete the operation in the requested time.
- 8.0 A failure has occurred in the CS that prevents the operation from succeeding.
- 8.1 A query was performed and the query is too complex for the CS. The operation was not performed.
- 8.2 Used to signal that an iCalendar object has exceeded the server's size limit

- 8.3 A DATETIME value was too far in the future represented on this Calendar.
- 8.4 A DATETIME value was too far in the past to be represented on this Calendar.
- 8.5 An attempt was made to create a new object but the unique UID specified is already in use.
- 9.0 An unrecognized command was received.
Or an unsupported command was received.
- 10.4 The operation has not been performed because it would cause the resources (memory, disk, CPU, etc) to exceed the allocated quota.

Royer, et al.

Expires February 9, 2006

[Page 136]

Internet-Draft

Calendar Access Protocol (CAP)

August 2005

[11.](#) Object Registration

This section provides the process for registration of new or modified properties, parameters, commands, or other modifications, additions, or deletions to objects.

[11.1](#) Registration of New and Modified Entities

New objects are registered by the publication of an IETF Request for Comment (RFC). Changes to a objects are registered by the publication of a revision to the RFC in a new RFC.

[11.2](#) Post the item definition

The object description MUST BE posted to the new object discussion list: ietf-calendar@imc.org.

[11.3](#) Allow a comment period

Discussion on a new object MUST BE allowed to take place on the list for a minimum of two weeks. Consensus MUST BE reached on the object before proceeding to the next step.

[11.4](#) Release a new RFC

The new object will be submitted for publication as any other internet draft requesting RFC status.

[12.](#) BEEP and CAP

[12.1](#) BEEP Profile Registration

Beep replies will be one to one (1:1 MSG/RPY) if possible and one to

many (1:many MSG/ANS) when the "TARGET" property value changes. No more than one "TARGET" property value per reply.

Profile Identification: specify a [URI] that authoritatively identifies this profile.

<http://iana.org/beep/cap/1.0>

Message Exchanged during Channel Creation:

CUAs SHOULD supply the BEEP "localize" attributes in the BEEP "greeting" messages.

CSs SHOULD supply the BEEP "localize" attributes in the BEEP "greeting" messages.

CUAs SHOULD supply the BEEP "serverName" attribute at channel creation time to the CS so that if the CS is performing virtual hosting the CS can determine the intended virtual host. CSs that do not support virtual hosting may ignore the BEEP "serverName" attribute.

Messages starting one-to-one exchanges:

The initial message after authentication each direction MUST BE single "text/calendar" object containing a CAP "CAPABILITY" CMD and must not be part of a MIME multipart message.

After the initial message then a BEEP "MSG" may contain one or more MIME objects at least one of which MUST be "text/calendar" and each "text/calendar" MIME object MUST contain a CAP "CMD" property.

Multiple iCal objects may be sent in a single BEEP message by either representing them as separate MIME text/calendar parts contained within a MIME multipart/mixed part or by simple concatenation within a single text/calendar MIME object.

In either case, all iCal objects transmitted together must have the same TARGET property.

The sending of multipart MIME entities over BEEP is not permitted for CAP unless the other endpoint has indicated its ability to accept them via the appropriate CAPABILITY.

Messages in positive replies:

After the initial message then a BEEP "RPY" may contain one or more MIME objects at least one of which MUST be "text/calendar" and each "text/calendar" MIME object MUST contain a CAP "CMD" property. All "text/calendar" MIME objects in a single BEEP "RPY" messages MUST have the same "TARGET" property value.

Multiple iCal objects may be sent in a single BEEP message by either representing them as separate MIME text/calendar parts contained within a MIME multipart/mixed part or by simple concatenation within a single text/calendar MIME object.

In either case, all iCal objects transmitted together must have the same TARGET property.

The sending of multipart MIME entities over BEEP is not permitted for CAP unless the other endpoint has indicated its ability to accept them via the appropriate CAPABILITY.

Messages in negative replies:

Any valid "text/calendar" MIME object that contains CAP "REQUEST-STATUS" property and a CAP "CMD" property with a property value of "REPLY". And where the CS has determined the requested operation to be a fatal error. And when the CS has performed NO operation that effected the contents of any part of the CS or any calendar controlled by the CS.

Messages in one-to-many exchanges:

After the initial message then a BEEP "MSG" may contain one or more MIME objects at least one of which MUST be "text/calendar" and each "text/calendar" MIME object MUST contain a CAP "CMD" property.

The BEEP "MSG" messages can only contain MIME "multipart" MIME objects if the other endpoint has received a CAP "CAPABILITY" indicating the other endpoint supports multipart MIME objects. This does not prevent the endpoint from sending multiple [[iCAL](#)] 'icalobject' objects in a single BEEP "MSG" so long as all of them have the same "TARGET" property value.

Multiple iCal objects may be sent in a single BEEP message by either representing them as separate MIME text/calendar parts contained within a MIME multipart/mixed part or by simple concatenation within a single text/calendar MIME object.

In either case, all iCal objects transmitted together must have the

Internet-Draft

Calendar Access Protocol (CAP)

August 2005

same TARGET property.

The sending of multipart MIME entities over BEEP is not permitted for CAP unless the other endpoint has indicated its ability to accept them via the appropriate CAPABILITY.

Message Syntax:

They are CAP "text/calendar" MIME objects as specified in this memo.

Message Semantics:

As defined in this memo.

[12.2](#) BEEP Exchange Styles

[BEEP] defines three styles of message exchange:

MSG/ANS,ANS,...,NUL - For one to many exchanges.

MSG/RPY - For one to one exchanges.

MSG/ERR - For requests that cannot be processed due to an error.

A CAP request targeted at more than one containers, MAY use a one-to-many exchange, with a distinct answer associated with each target. CAP request targeted at a single container MAY use a one-to-one exchange or a one-to-many exchange. "MSG/ERR" MAY only be used when an error condition prevents the execution of the request on all the targeted calendars.

[12.3](#) BEEP connection details

All CAP communications must be done securely. So the initial greeting includes the TLS profile.

```
L: <wait for incoming connection>

I: <open connection>

L: RPY 0 0 . 0 110
L: Content-Type: application/beep+xml
L:
L: <greeting>
L:   <profile uri='http://iana.org/beep/TLS' />
L: </greeting>
L: END

I: RPY 0 0 . 0 52
I: Content-Type: application/beep+xml
I:
I: <greeting/>
I: END
```

At this point the connection is secure. The TLS profile 'resets' the connection, so it resends the greetings. And advertise the CAP profiles supported. And reply with the profile selected (only one profile exists at this time):

```
L: <wait for incoming connection>

I: <open connection>

L: RPY 0 0 . 0 110
L: Content-Type: application/beep+xml
L:
L: <greeting>
L:   <profile uri='http://iana.org/beep/cap/1.0' />
```



```

L: </greeting>
L: END

I: RPY 0 0 . 0 110
I: Content-Type: application/beep+xml
I:
I: <greeting>
I:   <profile uri='http://iana.org/beep/cap/1.0'/>
I: </greeting>
I: END

```

Then each channel must be authenticated before work can start. Now

Royer, et al. Expires February 9, 2006 [Page 141]

Internet-Draft Calendar Access Protocol (CAP) August 2005

starting a channel involves authentication. Any SASL profile may be included such as these:

```

<profile uri='http://iana.org/beep/SASL/OTP'/>
<profile uri='http://iana.org/beep/SASL/DIGEST-MD5'/>
<profile uri='http://iana.org/beep/SASL/ANONYMOUS'/>

```

Example of anonymous channel:

```

C: <start number='1'>
C:   <profile uri='http://iana.org/beep/SASL/ANONYMOUS'/>
C: </start>

S: RPY 0 1 . 221 87
S: Content-Type: application/beep+xml
S:
S:

S: END

```

Example of DIGEST-MD5 channel:

```

C: <start number='1'>

```

```
C:    <profile uri='http://iana.org/beep/SASL/DIGEST-MD5'/>
C: </start>

S: RPY 0 1 . 221 87
S: Content-Type: application/beep+xml
S:
S:

S: END
```

Piggybacking the "CAPABILITY" command. The "CAPABILITY" reply may be included during channel start (see [RFC3080, section 2.3.1.2](#)) as BEEP allows for the start command to include the initial data transfer. This reduces the number of round trips to initiate a CAP session.

[13.](#) IANA Considerations

This memo defines IANA registered extensions to the attributes defined by iCalendar, as defined in [\[iCAL\]](#), and [\[iTIP\]](#).

IANA registration proposals for iCalendar and [\[iTIP\]](#) are to be mailed to the registration agent for the "text/calendar" [\[MIME\]](#) content-type, <MAILTO: ietf-calendar@imc.org> using the format defined in section 7 of [\[iCAL\]](#).

If the IESG approves this memo for publication, then the IANA registers the profile specified in [Section 12.1](#), and selects an IANA-specific URI, e.g., <http://iana.org/beep/cap/1.0>.

14. Security Considerations

Access rights should be granted cautiously. Without careful planning it is possible to open up access to a greater degree than desired.

The "IDENTIFY" command should be carefully implemented. If done incorrectly UPNs may gain access as other unintended UPSs. The "IDENTIFY" command may not chain, that is the identity is always validated against the original UPN and not the new UPN.

In addition, since CAP is a profile of [\[BEEP\]](#), consult [\[BEEP\]](#)'s [Section 9](#) for a discussion of BEEP-specific security issues.

There are risks of allowing anonymous UPNs to deposit REQUEST and

REFRESH objects. (calendar spam and denial of service for example)
So implementations should consider methods to restrict anonymous requests to within acceptable usages.

CS implementations might consider automatically creating VCARS that allow CAP ATTENDEES in booked objects to deposit REFRESH and REPLY objects for those UIDs if they otherwise do not have access rather than opening up world access. And they may consider also allowing COUNTER objects for those ATTENDEES.

When an object is booked by a CUA the CS reply may wish to include warning messages to the CUA for ATTENDEES that have CAP urls that do not have local UPNs as those ATTENDEES may be unable to REPLY or REFRESH. Some CSs may wish this to be an error.

Although service provisioning is a policy matter, at a minimum, all implementations must provide the following tuning profiles:

for authentication: <http://iana.org/beep/SASL/DIGEST-MD5>

for confidentiality: <http://iana.org/beep/TLS> (using the TLS_RSA_WITH_3DES_EDE_CBC_SHA cipher)

for both: <http://iana.org/beep/TLS> (using the TLS_RSA_WITH_3DES_EDE_CBC_SHA cipher supporting client-side certificates)

Authors' Addresses

Doug Royer
IntelliCal, LLC
267 Kentlands Blvd. #3041
Gaithersburg, MD 20878
US

Phone: +1-866-594-8574
Fax: +1-866-594-8574
Email: Doug@IntelliCal.com
URI: <http://Royer.com/People/Doug>

George Babics
Oracle
2000 Peel Street
Montreal, Quebec H3A 2W5
CA

Phone: +1-514-733-8500 x4201
Fax: +1-514-733-8878
Email: George.Babics@Oracle.com

Paul Hill
Massachusetts Institute of Technology
W92-172
77 Massachusetts Avenue
Cambridge, MA 02139
US

Phone: +1-617-253-0124
Fax: +1-617-258-8736
Email: phb@mit.edu

Steve Mansour
AOL/Netscape
466 Ellis Road
Mountain View, CA 94043
US

Phone: +1-650-937-3351
Email: sman@netscape.com

[Appendix A](#). Acknowledgments

The following individuals were major contributors in the drafting and discussion of this memo and are greatly appreciated:

Alan Davies, Andrea Campi, Andre Courtemanche, Andrew Davison, Anil Srivastava, ArentJan Banck, Arnaud Quillaud, Benjamin Sonntag, Bernard Desruisseaux, Bertrand Guiheneuf, Bob Mahoney, Bob Morgan, Bruce Kahn, Chris Dudding, Chris Olds, Christopher Apple, Cortlandt Winters, Craig Johnson, Cyrus Daboo, Damon Chaplin, Dan Hickman, Dan Kohn, Dan Winship, Darryl Champagne, David C. Thewlis, David Nicol, David Nusbaum, David West, Derik Stenerson, Eric R. Plamondon, Frank Dawson, Frank Nitsch, Gary Frederick, Gary McGath, Gilles Fortin, Graham Gilmore, Greg Barnes, Greg FitzPatrick, Harald Alvestrand, Harrie Hazewinkel, Helge Hess, Jagan Garimella, Jay Parker, Jim Ray, Jim Smith, Joerg Reichelt, John Berthels, John Smith, John Stracke, Jonathan Lennox, JP Rosevear, Karen Chu, Katie Capps Parlante, Kees Cook, Ken Crawford, Ki Wong, Lars Eggert, Lata Kannan, Lawrence Greenfield, Libby Miller, Lisa Dusseault, Lyndon Nerenberg, Mark Davidson, Mark Paterson, Mark Smith, Mark Swanson, Mark Tearle, Marshall Rose, Martijn van Beers, Martin Jackson, Matthias Laabs, Max Froumentin, Micah Gorrell, Michael Fair, Mike Higginbottom, Mike Hixson, Murata Makoto, Natalia Syracuse, Nathaniel Borenstein, Ned Freed, Olivier Gutknecht, Patrice Lapierre, Patrice Scattolin, Paul Hoffman, Paul Sharpe, Payod Deshpande, Pekka Pessi, Peter Thompson, Preston Stephenson, Prometeo Sandino Roman Corral, Ralph Patterson, Robert Lusardi, Robert Ransdell, Rob Siemborski, Satyanarayana Vempati, Satya Vempati, Scott Hollenbeck, Seamus Garvey, Shannon Clark, Shriram Vishwanathan, Steve Coya, Steve Mansour, Steve Miller, Steve Vinter, Stuart Guthrie, Suchet Singh Khalsa, Ted Hardie, Tim Hare, Timo Sirainen, Vicky Oliver, Yael Shaham-Gafni

Internet-Draft

Calendar Access Protocol (CAP)

August 2005

[Appendix B](#). Bibliography

- [ABNF] Crocker, D., Overell, P., "Augmented BNF for Syntax Specification", [RFC 2234](#), November 1997
<ftp://ftp.isi.edu/in-notes/rfc2234.txt>
- [BEEP] Rose, M., "The Block Extensible Exchange Protocol Core", [RFC 3080](#), March 2001
<ftp://ftp.isi.edu/in-notes/rfc3080.txt>
- [BEEPTCP] Rose, M., "Mapping the BEEP Core onto TCP", [RFC 3081](#), March 2001
<ftp://ftp.isi.edu/in-notes/rfc3081.txt>
- [BEEPGUIDE] Rose, M., "BEEP, The Definitive Guide", ISBN 0-596-00244-0, O'Reilly & Associates, Inc.
- [CHARREG] Freed, N., Postel, J., "IANA Charset Registration Procedures", [RFC 2278](#), January 1998,
<ftp://ftp.isi.edu/in-notes/rfc2278.txt>
- [CHARPOL] Alvestrand, H., "IETF Policy on Character Sets and Languages", [RFC 2277](#), January 1998,
<ftp://ftp.isi.edu/in-notes/rfc2277.txt>
- [GUIDE] Mahoney, B., Babics, G., Taler, A. "Guide to Internet Calendaring", [RFC 3283](#), June 2002,
<ftp://ftp.isi.edu/in-notes/rfc3283.txt>
- [iCAL] Dawson, F. and Stenerson, D., "Internet Calendaring and Scheduling Core Object Specification (iCalendar)", [RFC 2445](#), November 1998 <ftp://ftp.isi.edu/in-notes/rfc2445.txt>
- [iTIP] Silverberg, S., Mansour, S., Dawson, F. and Hopson, R., "iCalendar Transport-Independent Interoperability Protocol (iTIP) Events, BusyTime, To-dos and Journal Entries", [RFC 2446](#), November 1998 <ftp://ftp.isi.edu/in-notes/rfc2446.txt>
- [iMIP] Dawson, F., Mansour, S. and Silverberg, "iCalendar Message-Based Interoperability Protocol (iMIP)", [RFC 2447](#), November 1998 <ftp://ftp.isi.edu/in-notes/rfc2447.txt>

[MIME] Borenstein, N. and Freed, N., "Multipurpose Internet Mail Extensions (MIME) Part One: Format of Internet Message Bodies", [RFC 2045](#), November 1996
<ftp://ftp.isi.edu/in-notes/rfc2045.txt>

Royer, et al.

Expires February 9, 2006

[Page 147]

Internet-Draft

Calendar Access Protocol (CAP)

August 2005

[RFCWORDS] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [RFC 2119](#), [BCP 14](#), March 1997
<ftp://ftp.isi.edu/in-notes/rfc2119.txt>

[SASL] Myers, J., "Simple Authentication and Security Layer (SASL)", [RFC 2222](#), October 1997
<ftp://ftp.isi.edu/in-notes/rfc2222.txt>

[SQL92] "Database Language SQL", ANSI/ISO/IEC 9075: 1992, aka ANSI X3.135-1992, aka FIPS PUB 127-2

[SQLCOM] ANSI/ISO/IEC 9075:1992/TC-1-1995, Technical corrigendum 1 to ISO/IEC 9075: 1992, also adopted as Amendment 1 to ANSI X3.135.1992

[URLGUIDE] Masinter, L., Alvestrand, H., Zigmond, D., Petke, R., "Guidelines for new URL Schemes", [RFC 2718](#), November 1999
<ftp://ftp.isi.edu/in-notes/rfc2718.txt>

[URI] Berners-Lee, T., Fielding, R. and Masinter, L., "Uniform Resource Identifiers (URI): Generic Syntax", [RFC 2396](#), August 1998
<ftp://ftp.isi.edu/in-notes/rfc2396.txt>

[URL] Berners-Lee, T., Masinter, L. and McCahil, M., "Uniform Resource Locators (URL)", [RFC 1738](#), December 1994
<ftp://ftp.isi.edu/in-notes/rfc1738.txt>

[X509CRL] Housley, R., Ford, W., Polk, W., Solo, D. "Internet X.509 Public Key Infrastructure, Certificate and CRL Profile", [RFC 2459](#), January 1999,
<ftp://ftp.isi.edu/in-notes/rfc2459.txt>

Intellectual Property Statement

The IETF takes no position regarding the validity or scope of any Intellectual Property Rights or other rights that might be claimed to pertain to the implementation or use of the technology described in this document or the extent to which any license under such rights might or might not be available; nor does it represent that it has made any independent effort to identify any such rights. Information on the procedures with respect to rights in RFC documents can be found in [BCP 78](#) and [BCP 79](#).

Copies of IPR disclosures made to the IETF Secretariat and any assurances of licenses to be made available, or the result of an attempt made to obtain a general license or permission for the use of such proprietary rights by implementers or users of this specification can be obtained from the IETF on-line IPR repository at <http://www.ietf.org/ipr>.

The IETF invites any interested party to bring to its attention any copyrights, patents or patent applications, or other proprietary rights that may cover technology that may be required to implement this standard. Please address the information to the IETF at ietf-ipr@ietf.org.

Disclaimer of Validity

This document and the information contained herein are provided on an "AS IS" basis and THE CONTRIBUTOR, THE ORGANIZATION HE/SHE REPRESENTS

OR IS SPONSORED BY (IF ANY), THE INTERNET SOCIETY AND THE INTERNET ENGINEERING TASK FORCE DISCLAIM ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY WARRANTY THAT THE USE OF THE INFORMATION HEREIN WILL NOT INFRINGE ANY RIGHTS OR ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

Copyright Statement

Copyright (C) The Internet Society (2005). This document is subject to the rights, licenses and restrictions contained in [BCP 78](#), and except as set forth therein, the authors retain all their rights.

Acknowledgment

Funding for the RFC Editor function is currently provided by the Internet Society.