

Network Working Group
Internet-Draft
Intended status: Standards Track
Expires: 16 February 2023

V. Rajaguru, Ed.
Cisco Systems
15 August 2022

YANG Data Model for Bidirectional Forwarding Detection (BFD) Hardware
Offloaded Session
draft-rvelucha-bfd-offload-yang-03

Abstract

This document defines a extension YANG data model that can be used to manage Hardware Offloaded Bidirectional Forwarding Detection (BFD).

This document specially talks about BFD sessions that are offloaded to hardware.

The YANG modules in this document conform to the Network Management Datastore Architecture (NMDA).

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <https://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on 16 February 2023.

Copyright Notice

Copyright (c) 2022 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<https://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components

extracted from this document must include Revised BSD License text as described in Section 4.e of the [Trust Legal Provisions](#) and are provided without warranty as described in the Revised BSD License.

Table of Contents

- [1.](#) Introduction [2](#)
- [1.1.](#) Requirements Language [2](#)
- [1.2.](#) Tree Diagrams [2](#)
- [2.](#) Design of the Data Model [3](#)
- [3.](#) BFD IP single-hop-ext hierarchy [3](#)
- [4.](#) BFD IP multi-hop-ext hierarchy [3](#)
- [5.](#) BFD Over LAG-ext hierarchy [4](#)
- [6.](#) BFD IP single-hop ext YANG Module [4](#)
- [7.](#) BFD IP multi-hop ext YANG Module [6](#)
- [8.](#) BFD Over LAG ext YANG Module [8](#)
- [9.](#) Security Considerations [9](#)
- [10.](#) IANA Considerations [9](#)
- [11.](#) Acknowledgements [9](#)
- [12.](#) Normative References [10](#)
- [Appendix A.](#) Change log [10](#)
- Author's Address [10](#)

[1.](#) Introduction

This document defines an extension YANG data model to base model [\[RFC9127\]](#) that can be used to manage BFD sessions that are offloaded to hardware. BFD is a network protocol which is used for liveness detection of arbitrary paths between systems.

[1.1.](#) Requirements Language

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [BCP 14](#) [\[RFC2119\]](#) [\[RFC8174\]](#) when, and only when, they appear in all capitals, as shown here.

[1.2.](#) Tree Diagrams

This document uses the graphical representation of data models defined in [\[RFC8340\]](#).

[2.](#) Design of the Data Model

This yang model which is extension to base BFD yang mode been designed to manage BFD HW offloaded sessions. This new "bfd" container is augmented by all the YANG modules for their respective specific information:

1. ietf-bfd-ip-sh-ext.yang augments "/routing/control-plane-protocols/control-plane-protocol/bfd/ip-sh/sessions/session" with the "session-offloaded" leaf for BFD sessions over IP single-hop extension.
2. ietf-bfd-ip-mh-ext.yang augments "/routing/control-plane-protocols/control-plane-protocol/bfd/ip-mh/sessions-groups/session-group" with the "session-offloaded" leaf for BFD sessions over IP multi-hop extension.
3. ietf-bfd-lag-ext.yang augments "/routing/control-plane-protocols/control-plane-protocol/bfd/bfd-lag/sessions/session" with the "ession-offloaded" leaf for BFD sessions over LAG extension.

[3.](#) BFD IP single-hop-ext hierarchy

An "ip-sh-ext" node is added under "bfd" node in control-plane-protocol. The operational state data for each BFD IP single-hop session is under this "ip-sh-ext" node.

```
module: ietf-bfd-ip-sh-ext
augment /rt:routing/rt:control-plane-protocols
  /rt:control-plane-protocol/bfd:bfd/bfd-ip-sh:ip-sh
  /bfd-ip-sh:sessions/bfd-ip-sh:session:
  +--rw ip-sh-ext
    +--ro session-running-ext
      +--ro session-offloaded?   boolean
```

[4.](#) BFD IP multi-hop-ext hierarchy

An "ip-mh-ext" node is added under "bfd" node in control-plane-protocol. The operational state data for each BFD IP multi-hop session is under this "ip-mh-ext" node.

```
module: ietf-bfd-ip-mh-ext
augment /rt:routing/rt:control-plane-protocols
    /rt:control-plane-protocol/bfd:bfd/bfd-ip-mh:ip-mh
    /bfd-ip-mh:session-groups/bfd-ip-mh:session-group:
        +rw session-offloaded?  boolean
```

[5.](#) BFD Over LAG-ext hierarchy

An "lag-ext" node is added under "bfd" node in control-plane-protocol. The operational state data for each BFD Over LAG session is under this "lag-ext" node.

```
module: ietf-bfd-lag-ext
augment /rt:routing/rt:control-plane-protocols
    /rt:control-plane-protocol/bfd:bfd/bfd-lag:lag
    /bfd-lag:sessions/bfd-lag:session:
        +rw session-offloaded?  boolean
```

[6.](#) BFD IP single-hop ext YANG Module

This YANG module imports "ietf-bfd-ip-sh" from [RFC9127](#) and augments.

```
<CODE BEGINS> file "ietf-bfd-ip-sh-ext@2022-02-22.yang"
    module ietf-bfd-ip-sh-ext {
        yang-version 1.1;
```

```
namespace "urn:ietf:params:xml:ns:yang:ietf-bfd-ip-sh-ext";

prefix "bfd-ip-sh-ext";

import ietf-bfd {
  prefix "bfd";
  reference
    "RFC 9127: A YANG Data Model for Bidirectional Forwarding
    Detection (BFD)";
}

import ietf-routing {
  prefix "rt";
  reference
    "RFC 8349: A YANG Data Model for Routing Management
    (NMDA version)";
}

import ietf-bfd-ip-sh {
```

```
  prefix "bfd-ip-sh";
  reference
    "RFC 9127: A YANG Data Model for Bidirectional Forwarding
    Detection (BFD)";
}
```

```
organization "IETF BFD Working Group";
contact
  "WG Web:   <http://tools.ietf.org/wg/bfd>
  WG List:  <rtg-bfd@ietf.org>
```

```
  Editors:  Rajaguru Veluchamy (rvelucha@cisco.com);
```

```
description
```

```
"This module contains the YANG definition for BFD IP single-hop
as per RFC 5881 with some extended info.
```

```
Copyright (c) 2018 IETF Trust and the persons
identified as authors of the code. All rights reserved.
```

```
Redistribution and use in source and binary forms, with or
without modification, is permitted pursuant to, and subject
```

to the license terms contained in, the Simplified BSD License set forth in [Section 4.c](#) of the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>).

This version of this YANG module is part of RFC XXXX; see the RFC itself for full legal notices.";

reference

```
"RFC 5881: Bidirectional Forwarding Detection (BFD)
for IPv4 and IPv6 (Single Hop)
RFC 9127: YANG Data Model for Bidirectional Forwarding
Detection (BFD)";
```

```
revision 2022-02-18 {
```

```
  description "Initial revision.";
```

```
  reference
```

```
    "RFC XXXX: A YANG data model for BFD IP single-hop extension";
```

```
}
```

```
/*
```

```
 * Augments
```

```
*/
```

```
augment "/rt:routing/rt:control-plane-protocols/"
```

```
  + "rt:control-plane-protocol/bfd:bfd/bfd-ip-sh:ip-sh/"
```

```
  + "bfd-ip-sh:sessions/bfd-ip-sh:session" {
```

```
  description "BFD augmentation for IP single-hop-ext";
```

```
  leaf session-offloaded {
```

```
    type boolean;
```

```
    description
```

```
      "Indicates whether BFD session is running in hardware";
```

```
  }
```

```
}
```

```
}
```

```
<CODE ENDS>
```

[7](#). BFD IP multi-hop ext YANG Module

This YANG module imports "ietf-bfd-ip-mh" from [RFC9127](#) and augments.

```
<CODE BEGINS> file "ietf-bfd-ip-mh-ext@2022-02-22.yang"
module ietf-bfd-ip-mh-ext {
  yang-version 1.1;
  namespace "urn:ietf:params:xml:ns:yang:ietf-bfd-ip-mh-ext";
  prefix "bfd-ip-mh-ext";

  import ietf-bfd {
    prefix "bfd";
    reference
      "RFC 9127: A YANG Data Model for Bidirectional Forwarding
      Detection (BFD)";
  }

  import ietf-routing {
    prefix "rt";
    reference
      "RFC 8349: A YANG Data Model for Routing Management
      (NMDA version)";
  }

  import ietf-bfd-ip-mh {
    prefix "bfd-ip-mh";
    reference
      "RFC 9127: A YANG Data Model for Bidirectional Forwarding
      Detection (BFD)";
  }

  organization "IETF BFD Working Group";
  contact
    "WG Web: <http://tools.ietf.org/wg/bfd>
    WG List: <rtg-bfd@ietf.org>

    Editors: Rajaguru Veluchamy (rvelucha@cisco.com)";
```

description

"This module contains the YANG definition for BFD IP single-hop as per [RFC 5881](#) with some extended info.

Copyright (c) 2018 IETF Trust and the persons identified as authors of the code. All rights reserved.

Redistribution and use in source and binary forms, with or

without modification, is permitted pursuant to, and subject to the license terms contained in, the Simplified BSD License set forth in [Section 4.c](#) of the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>).

This version of this YANG module is part of RFC XXXX; see the RFC itself for full legal notices.";

```
reference
  "RFC 5881: Bidirectional Forwarding Detection (BFD)
  for IPv4 and IPv6 (Single Hop)
  RFC 9127: YANG Data Model for Bidirectional Forwarding
  Detection (BFD)";

revision 2022-02-18 {
  description "Initial revision.";
  reference
    "RFC XXXX: A YANG data model for BFD IP single-hop extension";
}

/*
 * Augments
 */
augment "/rt:routing/rt:control-plane-protocols/"
  + "rt:control-plane-protocol/bfd:bfd/bfd-ip-mh:ip-mh/"
  + "bfd-ip-mh:session-groups/bfd-ip-mh:session-group" {
  description "BFD augmentation for IP multi-hop-ext";
  leaf session-offloaded {
    type boolean;
    description
      "Indicates whether BFD session is running in hardware";
  }
}
}
}
<CODE ENDS>
```


This YANG module imports "ietf-bfd-lag" from [RFC9127](#) and augments.

```
<CODE BEGINS> file "ietf-bfd-lag-ext@2022-02-22.yang"
module ietf-bfd-lag-ext {
  yang-version 1.1;
  namespace "urn:ietf:params:xml:ns:yang:ietf-bfd-lag-ext";
  prefix "bfd-lag-ext";

  import ietf-bfd {
    prefix "bfd";
    reference
      "RFC 9127: A YANG Data Model for Bidirectional Forwarding
      Detection (BFD)";
  }

  import ietf-routing {
    prefix "rt";
    reference
      "RFC 8349: A YANG Data Model for Routing Management
      (NMDA version)";
  }

  import ietf-bfd-lag {
    prefix "bfd-lag";
    reference
      "RFC 9127: A YANG Data Model for Bidirectional Forwarding
      Detection (BFD)";
  }

  organization "IETF BFD Working Group";
  contact
    "WG Web: <http://tools.ietf.org/wg/bfd>
    WG List: <rtg-bfd@ietf.org>

    Editors: Rajaguru Veluchamy (rvelucha@cisco.com)";

  description
    "This module contains the YANG definition for BFD IP single-hop
    as per RFC 5881 with some extended info.

    Copyright (c) 2018 IETF Trust and the persons
    identified as authors of the code. All rights reserved.

    Redistribution and use in source and binary forms, with or
    without modification, is permitted pursuant to, and subject
```

to the license terms contained in, the Simplified BSD License set forth in [Section 4.c](#) of the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>).

This version of this YANG module is part of RFC XXXX; see the RFC itself for full legal notices.";

reference

"[RFC 5881](#): Bidirectional Forwarding Detection (BFD) for IPv4 and IPv6 (Single Hop)
[RFC 9127](#): YANG Data Model for Bidirectional Forwarding Detection (BFD)";

```
revision 2022-02-18 {  
  description "Initial revision.";  
  reference  
    "RFC XXXX: A YANG data model for BFD IP single-hop extension";  
}
```

```
/*
```

```
 * Augments
```

```
*/
```

```
augment "/rt:routing/rt:control-plane-protocols/"  
  + "rt:control-plane-protocol/bfd:bfd/bfd-lag:lag/"  
  + "bfd-lag:sessions/bfd-lag:session" {  
  description "BFD augmentation for LAG ext";  
  leaf session-offloaded {  
    type boolean;  
    description  
      "Indicates whether BFD session is running in hardware";  
  }  
}
```

```
<CODE ENDS>
```

[9](#). Security Considerations

TBD.

[10](#). IANA Considerations

None.

[11](#). Acknowledgements

I would like to thank Vengada Prasad Govindan for his support and guidance on this work.

12. Normative References

- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), DOI 10.17487/RFC2119, March 1997, <<https://www.rfc-editor.org/info/rfc2119>>.
- [RFC5880] Katz, D. and D. Ward, "Bidirectional Forwarding Detection (BFD)", [RFC 5880](#), DOI 10.17487/RFC5880, June 2010, <<https://www.rfc-editor.org/info/rfc5880>>.
- [RFC5881] Katz, D. and D. Ward, "Bidirectional Forwarding Detection (BFD) for IPv4 and IPv6 (Single Hop)", [RFC 5881](#), DOI 10.17487/RFC5881, June 2010, <<https://www.rfc-editor.org/info/rfc5881>>.
- [RFC8174] Leiba, B., "Ambiguity of Uppercase vs Lowercase in [RFC 2119](#) Key Words", [BCP 14](#), [RFC 8174](#), DOI 10.17487/RFC8174, May 2017, <<https://www.rfc-editor.org/info/rfc8174>>.
- [RFC8340] Bjorklund, M. and L. Berger, Ed., "YANG Tree Diagrams", [BCP 215](#), [RFC 8340](#), DOI 10.17487/RFC8340, March 2018, <<https://www.rfc-editor.org/info/rfc8340>>.
- [RFC9127] Rahman, R., Ed., Zheng, L., Ed., Jethanandani, M., Ed., Pallagatti, S., and G. Mirsky, "YANG Data Model for Bidirectional Forwarding Detection (BFD)", [RFC 9127](#), DOI 10.17487/RFC9127, October 2021, <<https://www.rfc-editor.org/info/rfc9127>>.

Appendix A. Change log

RFC Editor: Remove this section upon publication as an RFC.

Author's Address

Rajaguru Veluchamy (editor)
Cisco Systems
India

Email: rvelucha@cisco.com

Rajaguru

Expires 16 February 2023

[Page 10]