

Network Working Group
Internet-Draft
Intended status: Informational
Expires: February 1, 2013

P. Saint-Andre
Cisco Systems, Inc.
July 31, 2012

**A Uniform Resource Name (URN) Namespace for Examples
draft-saintandre-urn-example-00**

Abstract

This document defines a Uniform Resource Name (URN) namespace identifier enabling generation of URNs that are appropriate for use in private testing, as examples in documentation, and the like.

Status of this Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <http://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on February 1, 2013.

Copyright Notice

Copyright (c) 2012 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

Table of Contents

1.	Introduction	3
2.	Specification Template	3
3.	Namespace Considerations	4
4.	Community Considerations	5
5.	Security Considerations	5
6.	IANA Considerations	5
7.	References	6
7.1.	Normative References	6
7.2.	Informative References	6
	Author's Address	6

1. Introduction

The Uniform Resource Name (URN) technology [[RFC2141](#)] provides a way to generate persistent, location-independent, resource identifiers. The primary "scope" of a URN is provided by its namespace identifier (NID). As described in the specification for namespace definition mechanisms [[RFC3406](#)], there are three kinds of NIDs: formal, informal, and experimental. Most of the NIDs registered to date are formal: as far as is known the few informal namespaces have not been widely used, and the experimental namespaces are by definition unregistered.

In particular, the experimental namespaces take the form "X-NID" (where "NID" is the desired namespace identifier). Since the "x-" convention has been deprecated in general [[RFC6648](#)], it seems sensible to define a dedicated namespace identifier for use in private testing, as examples in documentation, and the like (similar to "example.com" and other domain names [[RFC2606](#)]). Therefore this document registers "example" as a formal namespace identifier. Although publication of this document might make it possible to deprecate the class of experimental namespace identifiers, that is not its primary intent.

2. Specification Template

2.1. Namespace ID

The Namespace ID "example" is requested.

2.2. Registration Information

Version 1

Date: 2012-07-11

2.3. Declared Registrant of the Namespace

Registering organization: IETF

Designated contact: IESG, iesg@ietf.org

2.4. Declaration of Syntactic Structure

The Namespace Specific String (NSS) of all URNs that use the "example" NID shall have the following structure:

urn:example:{NSS}

Saint-Andre

Expires February 1, 2013

[Page 3]

The NSS is a mandatory string of ASCII characters [[RFC20](#)] that conforms to the URN syntax requirements [[RFC2141](#)] and that provides a name that is useful within the relevant documentation example, test suite, or other application.

[2.5.](#) Relevant Ancillary Documentation

See [[RFC6648](#)] for information about deprecation of the "x-" convention in protocol parameters and identifiers.

[2.6.](#) Identifier Uniqueness Considerations

Those who mint example URNs ought to strive for uniqueness in the namespace specific string portion of the URN.

[2.7.](#) Identifier Persistence Considerations

Once minted, an example URN is immutable. However, it is simply a string and there is no guarantee that the documentation, test suite, or other application using the URN is immutable.

[2.8.](#) Process for Identifier Resolution

Example URNs are not intended to be resolved, and the namespace is not and probably never will be registered with a Resolution Discovery System.

[2.9.](#) Rules for Lexical Equivalence

No special considerations; the rules for lexical equivalence specified in [[RFC2141](#)] apply.

[2.10.](#) Conformance with URN Syntax

No special considerations

[2.11.](#) Validation Mechanism

None

[2.12.](#) Scope

Global

[3.](#) Namespace Considerations

No existing formal namespace enables entities to generate URNs that

are appropriate for use in private testing, as examples in documentation, and the like. It could be argue that no such formal namespace is needed, given that experimental namespaces can be minted at will. However, experimental namespaces run afoul of the trend away from using the "x-" convention in the names of protocol parameters and identifiers [[RFC6648](#)]. Additionally, in practice specification authors often mint examples using fake NIDs that go unregistered because they are never intended to be used; to minimize the possibility of confusion, it seems preferable to create a dedicated namespace that can be used to generate example URNs.

4. Community Considerations

The "example" NID is intended to provide a clean, easily-recognizable space for minting examples to be used in documentation, in private testing, and the like. The Namespace Specific String (NSS) needs to be a unique string, generated by the person, organization, or other entity that creates the documentation, test suite, or other application. There is no issuing authority for example URNs and they cannot be resolved in any way.

Note well that the example NID does not obviate the need to coordinate with issuing authorities for existing namespaces (e.g., minting "urn:example:xmpp:foo" instead of requesting issuance of "urn:xmpp:foo"), to register new namespace identifiers if existing namespaces do not match one's desired functionality (e.g., minting "urn:example:sha-1:29ead03e784b2f636a23ffff95ed12b56e2f2637" instead of registering the "urn:sha-1" namespace), or to respect to the basic spirit of URN NID assignment (e.g., setting up shadow NIDs such as "urn:example:MyCompany:*" instead of using HTTP URIs or other formats).

5. Security Considerations

This document introduces no additional security considerations beyond those associated with the use and resolution of URNs in general.

6. IANA Considerations

This document defines a URN NID registration of "example", to be added to the formal namespace registration; the completed registration template can be found under [Section 2](#).

7. References

7.1. Normative References

- [RFC20] Cerf, V., "ASCII format for network interchange", [RFC 20](#), October 1969.
- [RFC2141] Moats, R., "URN Syntax", [RFC 2141](#), May 1997.
- [RFC3406] Daigle, L., van Gulik, D., Iannella, R., and P. Faltstrom, "Uniform Resource Names (URN) Namespace Definition Mechanisms", [BCP 66](#), [RFC 3406](#), October 2002.
- [RFC6648] Saint-Andre, P., Crocker, D., and M. Nottingham, "Deprecating the "X-" Prefix and Similar Constructs in Application Protocols", [BCP 178](#), [RFC 6648](#), June 2012.

7.2. Informative References

- [RFC2606] Eastlake, D. and A. Panitz, "Reserved Top Level DNS Names", [BCP 32](#), [RFC 2606](#), June 1999.

Author's Address

Peter Saint-Andre
Cisco Systems, Inc.
1899 Wynkoop Street, Suite 600
Denver, CO 80202
USA

Email: psaintan@cisco.com

