

**JSON Metadata for OAuth Responses**  
**draft-sakimura-oauth-meta-00**

Abstract

This specification defines an extensible metadata member that may be inserted into the OAuth 2.0 responses to assist the clients to process those responses. It is expressed as a member called "\_links" that is inserted as the top level member in the responses. It will allow the client to learn where the members in the response could be used and how, etc. Since it is just a member, any client that does not understand this extension should not break and work normally while supporting clients can utilize the metadata to its advantage.

Status of this Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <http://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on June 15, 2013.

Copyright Notice

Copyright (c) 2012 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must

include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

## Table of Contents

<a href="#">1.</a>	Introduction . . . . .	<a href="#">3</a>
<a href="#">2.</a>	Requirements . . . . .	<a href="#">3</a>
<a href="#">3.</a>	JSON Meta Object . . . . .	<a href="#">3</a>
<a href="#">3.1.</a>	_links Member . . . . .	<a href="#">4</a>
<a href="#">3.1.1.</a>	href . . . . .	<a href="#">4</a>
<a href="#">3.1.2.</a>	method . . . . .	<a href="#">5</a>
<a href="#">3.1.3.</a>	params . . . . .	<a href="#">5</a>
<a href="#">3.1.4.</a>	content-type . . . . .	<a href="#">5</a>
<a href="#">3.1.5.</a>	Authorize . . . . .	<a href="#">5</a>
<a href="#">4.</a>	Application to the OAuth 2.0 Token Endpoint References . . . . .	<a href="#">5</a>
<a href="#">4.1.</a>	Successful Responses . . . . .	<a href="#">5</a>
<a href="#">4.1.1.</a>	self . . . . .	<a href="#">6</a>
<a href="#">4.1.2.</a>	describedby . . . . .	<a href="#">6</a>
<a href="#">4.1.3.</a>	Protected Resources . . . . .	<a href="#">6</a>
<a href="#">4.2.</a>	Error Responses . . . . .	<a href="#">7</a>
<a href="#">4.2.1.</a>	self . . . . .	<a href="#">7</a>
<a href="#">4.2.2.</a>	describedby . . . . .	<a href="#">7</a>
<a href="#">5.</a>	IANA Considerations . . . . .	<a href="#">7</a>
<a href="#">5.1.</a>	Link Type Registration . . . . .	<a href="#">7</a>
<a href="#">5.1.1.</a>	OAuth 2 Registrations . . . . .	<a href="#">7</a>
<a href="#">6.</a>	Security Considerations . . . . .	<a href="#">8</a>
<a href="#">6.1.</a>	href tampering . . . . .	<a href="#">8</a>
<a href="#">7.</a>	Acknowledgements . . . . .	<a href="#">8</a>
<a href="#">8.</a>	References . . . . .	<a href="#">8</a>
<a href="#">8.1.</a>	Normative References . . . . .	<a href="#">8</a>
<a href="#">8.2.</a>	Informational References . . . . .	<a href="#">9</a>
	Author's Address . . . . .	<a href="#">9</a>



## **1. Introduction**

Although OAuth 2.0 [[RFC6749](#)] has been known for its REST friendliness, OAuth itself is not RESTful, as it heavily relies on out-of-band information to drive the interactions. This situation can be eased by hypertext-enabling the JSON responses through the introduction of a member that represents such hypertext and other metadata. To achieve this, this specification introduces a top level member `"_links"` that represents various link relationships and other metadata.

## **2. Requirements**

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [RFC 2119](#) [[RFC2119](#)].

## **3. JSON Meta Object**

A JSON Meta Object uses the format described in [[RFC4627](#)] and is intended to be inserted into a JSON document to express some of the metadata associated with it as `"_links"` member.

The value of the `"_links"` member is a JSON object that expresses link relationships (`"rel"`), which in turn holds an object with `"href"` and other members or an array of such objects.

Following non-normative schematic example should help envisage what it would look like the following. (Note: line-wraps are for display purpose only.)



```
{
  "_links":{
    "self":{"href":"https://example.com/token?code=123"},
    "http://openid.net/specs/connect/1.0/#userinfo_ep":[
      {
        "href":"https://example.com/user/{user_id}",
        "method":"GET",
        "Authorize":"{token_type} {access_token}"
      },
      {
        "href":"https://example.com/user/{user_id}",
        "method":"POST",
        "Authorize":"{token_type} {access_token}",
        "params":[
          "name","birthday"
        ]
      }
    ],
    "token_type":"Bearer",
    "access_token":"aCeSsToKeN"
  }
}
```

Here, we have "\_links" member that expresses various "relations" such as "self" and "http://openid.net/specs/connect/1.0/#userinfo\_ep". Each relationships has either a link relations object or an array of link relations objects as its value. The link relations objects holds various members such as "href". They are explained in the next section.

### **3.1. \_links Member**

"\_links" member holds exactly one object that contains the following members with relation as the "string" defined in [RFC4627]. The "string" SHOULD be a link relation type that is either defined in the IANA registry defined in Web Linking [RFC5988] or a URI that describes the relation.

Each relation member holds exactly one object or one array, whose items are objects. Each object has following members, which are all optional.

#### **3.1.1. href**

The value of the "href" member is a URI Template [RFC6570] that the relation points to. The values for template parameters SHOULD be taken from the value of the top-level members in the including JSON object whose "string" matches the template variable name.



### **3.1.2. method**

The value of the "method" member is the HTTP method defined in Hypertext Transfer Protocol -- HTTP/1.1 [[RFC2616](#)][RFC2616] that can be used to the URL described in the "href". e.g., GET, POST, PUT, DELETE.

### **3.1.3. params**

The "params" member describes the parameters to be sent to the URL expressed in "href". The "value" is an array of "pairs" whose string corresponds to the parameter names of the parameters that are to be sent to the URL. The "value" of the "pair" is an "object" with following "members" . All "members" are optional.

required Boolean. true or false. Indicates whether this parameter is required to be sent with the request.

description Human readable description of the variable.

### **3.1.4. content-type**

The content-type to be used when the parameters are sent to the URL.

e.g., "application/x-www-form-urlencoded", "multipart/form-data", "application/json".

### **3.1.5. Authorize**

The HTTP Authorize header defined in Hypertext Transfer Protocol -- HTTP/1.1 [[RFC2616](#)] to be used when accessing the resource identified by href. It is templated in exactly the same syntax as in URI Template [[RFC6570](#)] except that it is applied to the Authorization request header than the URI.

## **4. Application to the OAuth 2.0 Token Endpoint References**

To create the [Section 3](#) should be used in the token endpoint responses of the OAuth 2.0 Authorization Framework [[RFC6749](#)], following relations SHOULD be included.

### **4.1. Successful Responses**

In the case of the Successful Response described in [section 5.1. of \[RFC6749\]](#), the following member SHOULD be present in the value of the [Section 3.1](#).





#### **4.1.1. self**

An object with the following members.

href REQUIRED. The URI that resulted in this response.

#### **4.1.2. describedby**

An object with the following members.

href REQUIRED. The value is one of the following URIs:

"http://tools.ietf.org/html/rfc6749#section-4.1.4",  
"http://tools.ietf.org/html/rfc6749#section-4.3.3",  
"http://tools.ietf.org/html/rfc6749#section-4.4.3".

#### **4.1.3. Protected Resources**

Each protected resources MUST provide a unique Relation Name by either registering to the Link Relation Type Registry defined in [section 6.2 of \[RFC5988\]](#) or providing an absolute URI that provides a collision resistant name. The value is an array of objects that has the following members.

href REQUIRED. The URI template that describes the request to the resource as described in [section 3.1.1](#). ([Section 3.1.1](#)).

method OPTIONAL. HTTP request method to be used as described in [section 3.1.2](#). ([Section 3.1.2](#)). Defaults to "GET". Semantics of the HTTP methods in this case SHOULD map as follows: "GET" means reading the resource. "POST" means creating or updating the resource with supplied parameters in "params" member below. "DELETE" means deleting the corresponding resource. "PUT" means the complete replacement of the resource by the body of the request. The resource MUST support "GET" method. The support of other methods are OPTIONAL.

params OPTIONAL. Parameters to be sent as described in [section 3.1.3](#). ([Section 3.1.3](#)).

content-type OPTIONAL. As described in [section 3.1.4](#). ([Section 3.1.4](#)).

Authorize OPTIONAL. HTTP Authorization header to be sent when accessing the resource. This is described in [section 3.1.5](#). ([Section 3.1.5](#)). If this member is not available, then the client SHOULD access the expanded "href" value to obtain the Authorization header response to learn what authorization scheme it should use.



## **[4.2.](#) Error Responses**

In the case of the Error Response described in [section 5.2. of \[RFC6749\]](#), the following member SHOULD be present.

### **[4.2.1.](#) self**

An object with the following members.

href REQUIRED. The URI that resulted in this response.

### **[4.2.2.](#) describedby**

An object with the following members.

href REQUIRED. The value is  
"http://tools.ietf.org/html/rfc6749#section-5.2".

## **[5.](#) IANA Considerations**

This document makes no request of IANA.

Note to RFC Editor: this section may be removed on publication as an RFC.

## **[5.1.](#) Link Type Registration**

Pursuant to [\[RFC5988\]](#), the following link type registrations [[will be]] registered by mail to link-relations@ietf.org.

### **[5.1.1.](#) OAuth 2 Registrations**

The section 3 of the OAuth 2.0 Authorization Framework [\[RFC6749\]](#) defines two endpoints that may be discovered through this specification. These are the user Authorization Endpoint and the Token Endpoint.

#### **[5.1.1.1.](#) Authorization Endpoint**

- o Relation Name: oauth2-authorize
- o Description: An OAuth 2.0 Authorization Endpoint specified in [section 3.1 of \[RFC6749\]](#)
- o Reference: [\[RFC6749\]](#)



#### **5.1.1.2. Token Endpoint**

- o Relation Name: oauth2-token
- o Description: An OAuth 2.0 Token Endpoint specified in [section 3.2 of \[RFC6749\]](#).
- o Reference: [[RFC6749](#)]

### **6. Security Considerations**

#### **6.1. href tampering**

Unless integrity protected channel is used, an attacker may be able to tamper the value of the href thereby causing the receiver of the JSON response to send a request to the URL under the attacker's control with potentially confidential information contained in the parameters. To mitigate this risk, an integrity protected channel such as TLS protected channel should be used.

### **7. Acknowledgements**

This specification borrows heavily from [[HAL](#)]. The Link type registration is taken from [[oauth-1rdd](#)].

[todo]

### **8. References**

#### **8.1. Normative References**

- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), March 1997.
- [RFC2616] Fielding, R., Gettys, J., Mogul, J., Frystyk, H., Masinter, L., Leach, P., and T. Berners-Lee, "Hypertext Transfer Protocol -- HTTP/1.1", [RFC 2616](#), June 1999.
- [RFC4627] Crockford, D., "The application/json Media Type for JavaScript Object Notation (JSON)", [RFC 4627](#), July 2006.
- [RFC5988] Nottingham, M., "Web Linking", [RFC 5988](#), October 2010.
- [RFC6570] Gregorio, J., Fielding, R., Hadley, M., Nottingham, M., and D. Orchard, "URI Template", [RFC 6570](#), March 2012.



- [RFC6749] Hardt, D., "The OAuth 2.0 Authorization Framework", [RFC 6749](#), October 2012.
- [RFC6750] Jones, M. and D. Hardt, "The OAuth 2.0 Authorization Framework: Bearer Token Usage", [RFC 6750](#), October 2012.

## **8.2. Informational References**

- [HAL] Kelly, M., "JSON Hypermedia API Language", 07 2012.
- [oauth-lrdd] Mills, W., "Link Type Registrations for OAuth 2", October 2012.

### Author's Address

Nat Sakimura (editor)  
Nomura Research Institute  
  
Email: sakimura@gmail.com



