

masque
Internet-Draft
Intended status: Standards Track
Expires: 25 March 2022

B. Schwartz
Google LLC
21 September 2021

HTTP Datagram PING
draft-schwartz-masque-h3-datagram-ping-00

Abstract

This draft defines an HTTP Datagram Format Type for measuring the functionality of a Datagram path.

Discussion Venues

This note is to be removed before publishing as an RFC.

Discussion of this document takes place on the mailing list (masque@ietf.org), which is archived at <https://mailarchive.ietf.org/arch/browse/masque/>.

Source for this draft and an issue tracker can be found at <https://github.com/bemasc/h3-datagram-ping>.

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <https://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on 25 March 2022.

Copyright Notice

Copyright (c) 2021 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<https://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the [Trust Legal Provisions](#) and are provided without warranty as described in the Simplified BSD License.

Table of Contents

1.	Conventions and Definitions	2
2.	PING Datagram Format Type	2
2.1.	Format	2
2.2.	Use	3
3.	Use cases	3
4.	IANA considerations	3
5.	References	3
5.1.	Normative References	3
5.2.	Informative References	4
	Acknowledgments	4
	Author's Address	4

[1.](#) Conventions and Definitions

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "NOT RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [BCP 14](#) [[RFC2119](#)] [[RFC8174](#)] when, and only when, they appear in all capitals, as shown here.

[2.](#) PING Datagram Format Type

PING is an HTTP Datagram Format Type [I-D.[draft-ietf-masque-h3-datagram](#)].

[2.1.](#) Format

PING Datagrams have the following format:

```
PING {
  Sequence Number (i),
  Opaque Data (..),
```

}

Figure 1: PING Datagram Format

The "Opaque Data" field contents are unconstrained.

[2.2.](#) Use

We define the "Requester" as the peer that registered this PING Datagram Context, and the "Responder" as the other peer.

The Requester initiates a ping by sending a PING Datagram with any "Sequence Number" and "Opaque Data". The Responder MUST reply with a PING Datagram in the same context, with the same "Sequence Number" and empty "Opaque Data".

Intermediaries MUST forward PING Datagrams without modification, just like any other HTTP Datagram.

[3.](#) Use cases

PING Datagrams can be used to characterize the end-to-end HTTP Datagram path associated with an HTTP request. For example, HTTP endpoints can easily use PING Datagrams to estimate the round-trip time and loss rate of the HTTP Datagram path.

PING Datagrams are also suitable for use as DPLPMTUD Probe Packets [[RFC8899](#)]. This enables endpoints to estimate the HTTP Datagram MTU of each Datagram path, in order to avoid sending HTTP Datagrams that will be dropped.

Note that these path characteristics can differ from those inferred from the underlying transport (e.g. QUIC), if the HTTP request traverses one or more HTTP intermediaries (see [Section 3.7](#) of [I-D.[draft-ietf-httpbis-semantic](#)]).

[4.](#) IANA considerations

IANA is directed to add the following entry to the "HTTP Datagram Format Types" registry:

* Type: PING

- * Value: TBD
- * Reference: (This document)

5. References

5.1. Normative References

[I-D.[draft-ietf-masque-h3-datagram](#)]

Schinazi, D. and L. Pardue, "Using Datagrams with HTTP", Work in Progress, Internet-Draft, [draft-ietf-masque-h3-](#)

Schwartz

Expires 25 March 2022

[Page 3]

Internet-Draft

HTTP Datagram PING

September 2021

datagram-03, 12 July 2021,

<<https://datatracker.ietf.org/doc/html/draft-ietf-masque-h3-datagram-03>>.

[RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), DOI 10.17487/RFC2119, March 1997, <<https://www.rfc-editor.org/rfc/rfc2119>>.

[RFC8174] Leiba, B., "Ambiguity of Uppercase vs Lowercase in [RFC 2119](#) Key Words", [BCP 14](#), [RFC 8174](#), DOI 10.17487/RFC8174, May 2017, <<https://www.rfc-editor.org/rfc/rfc8174>>.

5.2. Informative References

[I-D.[draft-ietf-httpbis-semantic](#)s]

Fielding, R. T., Nottingham, M., and J. Reschke, "HTTP Semantics", Work in Progress, Internet-Draft, [draft-ietf-httpbis-semantic](#)s-19, 12 September 2021, <[\[RFC8899\] Fairhurst, G., Jones, T., Tüxen, M., Rüngeler, I., and T. Völker, "Packetization Layer Path MTU Discovery for Datagram Transports", \[RFC 8899\]\(#\), DOI 10.17487/RFC8899, September 2020, <<https://www.rfc-editor.org/rfc/rfc8899>>.](https://datatracker.ietf.org/doc/html/draft-ietf-httpbis-semantics-19>.</p></div><div data-bbox=)

Acknowledgments

TODO

Author's Address

Benjamin Schwartz
Google LLC

Email: bemasc@google.com

Schwartz

Expires 25 March 2022

[Page 4]