

Network Working Group  
Internet-Draft  
Intended Status: Informational  
Expires: October 10, 2016

S. Leonard  
Penango, Inc.  
April 8, 2016

Windows Image Media Types  
draft-seantek-windows-image-03

## Abstract

This document registers media types for certain image formats promulgated in Microsoft Windows, namely image/wmf, image/x-wmf, image/emf, image/x-emf, and image/bmp for use with Windows Metafile, Enhanced Metafile, and Windows Bitmap formats. Originally designed for Microsoft Windows 2.0 and 3.0, these image files are intended to be portable between applications and devices, and may contain both vector and raster graphics.

## Status of this Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <http://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

## Copyright Notice

Copyright (c) 2016 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

## 1. Introduction

### 1.1. Windows Metafiles

Long before the invention of Scalable Vector Graphics, Microsoft Corporation recognized the value of recording images in a format that its applications and operating systems could easily render irrespective of the output device. With the release of Windows 3.0, Microsoft released its Windows Metafile (WMF) format, which can contain vector and raster graphics in one package. As a binary format that needed to work on 16-bit machines, WMF is comprised of a sequence of record structures. Each record contains drawing commands, object definitions, and configuration settings. When a metafile is processed, the image can be rendered on a display, output to a printer or plotter, stored in memory, or saved to some persistent storage. Reflecting the relationship to the Windows Graphics Device Interface (GDI) API, WMF metafiles are "played" to a playback device context in the same manner that PostScript content is treated as an executable program that results in the output of the original document.

As Microsoft's first 32-bit operating system, Windows NT 3.1 introduced an overhaul to the Windows API ("Win32") and the in-memory formats upon which those APIs relied. The Enhanced Metafile (EMF) format was created at this time, using 32-bit values instead of WMF's 16-bit values. In Windows XP, Microsoft extended EMF with "EMF+", adding support for Windows GDI+.

Many implementations of WMF and EMF were created because of Windows' commercial success in the 1990s. A large body of free and commercially available clip art and other artwork exists in this format. Furthermore, WMF content appears non-normatively in certain standards (e.g., [[OOXML](#)]); the usage is common enough that an implementer would almost certainly need to support it for basic interoperability.

Microsoft publicly documented the WMF format as early as the 1992 Windows 3.1 SDK. Since 2007 Microsoft has released the format specifications [[MS-WMF](#)], [[MS-EMF](#)], and [MS-EMF+] under its Open Specification Promise [[MS-OSP](#)].

### 1.2. Windows Bitmaps

Long before the invention of Portable Network Graphics (PNG), Microsoft Corporation and IBM Corporation needed to record images in a format that their applications and operating systems could easily render on low-end machines (Intel 80286). The resulting "BMP" format contains a single raster graphic with basic header fields that can be

easily mapped (or "blitted") to locations in memory. As computing moved from 16-bit to 32-bit, BMP evolved to contain 32-bit structures. As the 90s wore on, the venerable BMP got boosts with support for additional color spaces, color profiles, and compression formats. The same basic format can be used to convey 2-bit black-and-white bitmaps with a 1-bit alpha mask from the '80s, and full-color Ultra HD images on leading-edge displays. BMP is a building block of other formats, including Windows Metafiles, Windows Icons, and Windows Cursors.

Many implementations of BMP were created because of Windows' commercial success in the 1990s. Usage of the format for interchange has declined since the advent of PNG (for lossless raster graphics) and JPEG (for lossy raster graphics); however, a large body of free and commercially available BMP artwork exists. Since Windows Icons are a building block of "favicon.ico" Web technology, an implementer would almost certainly need to support this format for basic interoperability.

Microsoft publicly documented the BMP format as early as the 1992 Windows 3.1 SDK (in the Windows Metafile documentation). Since 2007 Microsoft has released the format specification [[MS-WMF](#)], which includes most components of the Windows Bitmap format, under its Open Specification Promise [[MS-OSP](#)]. See Section 2.2.2.9 of [[MS-WMF](#)] (DeviceIndependentBitmap Object). BMP data begins with a BITMAPFILEHEADER and is followed by one of the bitmap headers (BITMAPINFOHEADER, BITMAPV4HEADER, or BITMAPV5HEADER), optional color table data, bitmap data, and optional profile data, in that order [[BMPSTOR](#)].

## [2.](#) Windows Metafile Media Type Registration Application

Type name: image

Subtype name: wmf

Required parameters: None.

Optional parameters:

DEFAULT\_CHARSET: The character set intended when the CharSet Enumeration (see the WMF specification) specifies DEFAULT\_CHARSET. The value of this parameter is a charset name defined in accordance to the procedures laid out in [RFC 2978](#). When this parameter is not specified, DEFAULT\_CHARSET has the following meaning in the WMF specification: "a character set based on the current system locale; for example, when the system locale is United States English, the default character set is ANSI\_CHARSET" (which is Windows-1252,

Leonard

Exp. October 10, 2016

[Page 3]

---

Internet-Draft

Windows Image Media Types

April 2016

more-or-less). I.e., when not specified, the default character set is system-dependent. As this optional parameter is novel, EMF instead of WMF (or if necessary under the circumstances, embedded EMF within WMF) is a more sensible choice when text is present.

Encoding considerations: Binary.

Security considerations:

The Windows Metafile format's security history is punctuated in 2005-2006 with the disclosure of the Metafile Image Code Execution vulnerability, codenamed MICE. MICE won the 2007 Pwnie Award for "Mass 0wnage" and "Breaking the Internet". The official Microsoft security bulletin describes that the flaw occurs because Windows Metafiles can set the SETABORTPROC value of the MetafileEscapes enumeration (accessible via the META\_ESCAPE record), allowing for arbitrary code execution, i.e., "active content".

Windows Metafiles can contain Enhanced Metafiles using the META\_ESCAPE\_ENHANCED\_METAFILE record; thus, the security considerations of EMF apply to WMF.

Windows Metafiles are historically very buggy. As the original intent was to replicate Windows GDI calls, flaws in GDI, or in a display or printer driver implementing the back-end to GDI, could be exploitable. WMF implementations not backed by Windows GDI have different risks: namely, while a malicious WMF author may not consider the non-Windows GDI implementation as a primary target, WMF has many "corner case" records for which an implementation's

processing may not have received the same level of scrutiny as the Windows implementation. "Fuzzing" the implementation is appropriate.

#### Interoperability considerations:

Windows Metafile is the original 16-bit metafile format; it was released in 1990 at what some computer historians might consider the "zenith" of the desktop publishing revolution. Accordingly, there is a large body of free and commercially available clip art that is still in use, either independently or embedded in productivity documents (word processing documents, desktop publishing documents, slideshows and presentations, and spreadsheets and workbooks). For example, references to WMF content appear (non-normatively) in Office Open XML. To say that support for this format is necessary for interoperability would not be an understatement.

Accommodations for comments or arbitrary data storage in Windows

Leonard

Exp. October 10, 2016

[Page 4]

---

Internet-Draft

Windows Image Media Types

April 2016

Metafiles are virtually non-existent. However, Windows Metafiles can contain Enhanced Metafiles using the META\_ESCAPE\_ENHANCED\_METAFILE record, so an implementation that handles Windows Metafiles is also expected to handle enhanced metafile content. Windows Metafiles can store and output text strings (see META\_TEXTOUT and META\_EXTTEXTOUT records), but the encodings of the strings may be ambiguous. Unicode encodings are not possible without the DEFAULT\_CHARSET parameter defined in this registration.

The previously unregistered type "image/x-wmf" is also in wide use. Accordingly, it is registered as a deprecated alias. See [Appendix A](#) and [Section 4.2.9 of \[RFC6838\]](#).

#### Published specification:

WMF: Microsoft Corporation, "Windows Metafile Format", [[MS-WMF](#)], v20140502 (Rev 11.1), May 2014, <<http://msdn.microsoft.com/library/cc250370>>.

MICE: Microsoft Corporation, "Vulnerability in Graphics Rendering Engine Could Allow Remote Code Execution (912919)", MS06-001, V1.0,

January 2006, <<https://technet.microsoft.com/library/security/ms06-001>>..

Applications that use this media type:

Office productivity applications; clip art applications; desktop publishing applications; some Web browsers (e.g., Internet Explorer).

Fragment identifier considerations: None.

Additional information:

Deprecated alias names for this type: image/x-wmf

Magic number(s): D7 CD C6 9A (little-endian DWORD 0x9AC6CDD7)

File extension(s): .wmf

Macintosh file type code(s):

None. A uniform type identifier (UTI) of "com.microsoft.wmf" is RECOMMENDED.

Person & email address to contact for further information:

Sean Leonard <dev+ietf@seantek.com>

Restrictions on usage: None.

Author/Change controller: Sean Leonard <dev+ietf@seantek.com>

Intended usage: COMMON

Provisional registration? No

### 3. Enhanced Metafile Media Type Registration Application

Type name: image

Subtype name: emf

Required parameters: None.

Optional parameters: None.

Encoding considerations: Binary.

Security considerations:

Enhanced Metafiles are not afflicted with the Metafile Image Code Execution vulnerability, codenamed MICE. There has been no public disclosure of vulnerabilities specific to EMF or EMF+ to date. Neither EMF nor EMF+ are designed to contain "active content". Nonetheless:

Enhanced Metafiles can contain Encapsulated PostScript (EPS) data; thus the security considerations of PostScript processing may also apply to EMF.

As the original intent was to replicate Windows GDI calls, flaws in GDI, or in a display or printer driver implementing the back-end to GDI, could be exploitable with maliciously crafted EMF content. EMF implementations not backed by Windows GDI have different risks: namely, while a malicious EMF author may not consider the non-Windows GDI implementation as a primary target, EMF has many "corner case" records for which an implementation's processing may not have received the same level of scrutiny as the Windows implementation. "Fuzzing" the implementation is appropriate. It is also possible that EMF+ data is "safe" while EMF data contains an exploit (or vice-versa); the EMF+-aware implementation (such as an application designed for GDI+ on Windows XP or above) would skip the "unsafe" data while another implementation would fall prey to the exploit.

Interoperability considerations:

Enhanced Metafile is the 32-bit metafile format; it was released in

1992 along with Windows NT 3.1. There is a large body of free and commercially available clip art that is still in use, either independently or embedded in productivity documents (word processing documents, desktop publishing documents, slideshows and presentations, and spreadsheets and workbooks). To say that support for this format is necessary for interoperability would not be an understatement.

Enhanced Metafiles have extensive accommodations for comments and arbitrary data storage. Enhanced Metafiles can store and output text strings. Mercifully, the encodings of these strings are well-defined. Record examples include EMR\_EXTTEXTOUTA (US-ASCII), EMR\_EXTTEXTOUTW (UTF16-LE), EMR\_POLYTEXTOUTA (US-ASCII), EMR\_POLYTEXTOUTW (UTF16-LE), and EMR\_SMALLTEXTOUT (UTF16-LE or the low-order 8 bits of UTF16-LE--effectively ISO-8859-1--depending on ETO\_SMALL\_CHARS).

Enhanced Metafiles can contain Encapsulated PostScript (EPS) data in the EpsData object. The FormatSignature EPS\_SIGNATURE (0x46535045, in little-endian) is used instead of ENHMETA\_SIGNATURE (0x464D4520, in little-endian) in such a case.

Windows XP introduced the GDI+ API, along with EMF+. EMF+ is actually an embedded format in which GDI+ commands are stored as EMF comment records (EMR\_COMMENT\_EMFPLUS record type). Content containing EMF+ data can be identified as "EMF+ Only" (only EMF+; the EMF records are not sufficient to reconstitute the drawing) or "EMF+ Dual" (both EMF records alone or EMF+ records alone, when played back, are sufficient to reconstitute the drawing). Support for EMF+ records may not be as extensive as support for the original EMF records.

The previously unregistered type "image/x-emf" is also in wide use. Accordingly, it is registered as a deprecated alias.

Published specification:

EMF: Microsoft Corporation, "Enhanced Metafile Format", [MS-EMF], v20140502 (Rev 10.0), May 2014, <<http://msdn.microsoft.com/library/cc230514>>.

EMF+: Microsoft Corporation, "Enhanced Metafile Format Plus Extensions", [MS-EMFPLUS], v20140502 (Rev 13.0), May 2014, <<http://msdn.microsoft.com/library/cc230724>>.

Applications that use this media type:

Office productivity applications; clip art applications; desktop



Explorer).

Fragment identifier considerations: None.

Additional information:

Deprecated alias names for this type: image/x-emf

Magic number(s): 01 00 00 00 (little-endian DWORD 0x00000001),  
corresponding to the EMR\_HEADER Type field.  
The next field (EMR\_HEADER Size) should be  
at least 88 (little-endian DWORD 0x00000050).

File extension(s): .emf  
(for both EMF and EMF+ content)

Macintosh file type code(s):

None. A uniform type identifier (UTI) of "com.microsoft.emf" is  
RECOMMENDED.

Person & email address to contact for further information:

Sean Leonard <dev+ietf@seantek.com>

Restrictions on usage: None.

Author/Change controller: Sean Leonard <dev+ietf@seantek.com>

Intended usage: COMMON

Provisional registration? No

#### [4.](#) Windows Bitmap Media Type Registration Application

Type name: image

Subtype name: bmp

Required parameters: None.

Optional parameters: None.

Encoding considerations: Binary.

Security considerations:

Bitmaps have a mostly unremarkable security history.

Because BMP data can encapsulate JPEG or PNG data (BI\_JPEG, BI\_PNG values of the Compression enumeration in [Section 2.1.1.7](#) of the WMF

specification), the security considerations of JPEG and PNG processing may also apply to BMP.

#### Interoperability considerations:

Uncompressed Windows Bitmaps can be rather large. If there is a need to compress an image, modern applications SHOULD consider emitting JPEG or PNG data instead of embedding them in BMP payloads.

#### Published specification:

WMF: Microsoft Corporation, "Windows Metafile Format", [[MS-WMF](#)], v20140502 (Rev 11.1), May 2014, <<http://msdn.microsoft.com/library/cc250370>>.

BMP: Microsoft Corporation, "Bitmap Storage", MSDN ID dd183391, 2014, <<http://msdn.microsoft.com/library/dd183391>>..

#### Applications that use this media type:

Office productivity applications; clip art applications; desktop publishing applications; Web browsers; graphics processing applications.

#### Fragment identifier considerations: None.

#### Additional information:

Magic number(s): 42 4D ("BM"), meaning "bitmap". The next field (BITMAPFILEHEADER bfSize) is a little-endian DWORD indicating the size of the bitmap content in bytes.

File extension(s): .bmp, .dib

Macintosh file type code(s):

"BMP ", "BMPf", or "BMPP". Apple has promulgated a uniform type identifier (UTI) of "com.microsoft.bmp".

#### Person & email address to contact for further information:

Sean Leonard <[dev+iETF@seantek.com](mailto:dev+iETF@seantek.com)>

#### Restrictions on usage: None.

Author/Change controller: Sean Leonard <[dev+iETF@seantek.com](mailto:dev+iETF@seantek.com)>

Provisional registration? No

## [5.](#) IANA Considerations

IANA is asked to register the media types `image/wmf`, `image/x-wmf`, `image/emf`, `image/x-emf`, and `image/bmp` in the Standards tree using the applications provided in Sections [2](#), [3](#), and [4](#) of this document.

## [5.](#) Security Considerations

See the registration templates for their respective security considerations.

As "basic" image formats, these formats provide no facilities for privacy or integrity.

The Metafile Image Code Execution (MICE) vulnerability won the 2007 Pwnie Award for "Mass 0wnage" and "Breaking the Internet" [[PWNIES07](#)].

## [6.](#) References

### [6.1.](#) Normative References

- [BMPSTOR] Microsoft Corporation, "Bitmap Storage", MSDN ID dd183391, 2014, <<http://msdn.microsoft.com/library/dd183391>>.
- [MS-WMF] Microsoft Corporation, "Windows Metafile Format", [[MS-WMF](#)], v20140502 (Rev 11.1), May 2014, <<http://msdn.microsoft.com/library/cc250370>>.
- [MS-EMF] Microsoft Corporation, "Enhanced Metafile Format", [[MS-EMF](#)], v20140502 (Rev 10.0), May 2014, <<http://msdn.microsoft.com/library/cc230514>>.
- [MS-EMF+] Microsoft Corporation, "Enhanced Metafile Format Plus Extensions", [[MS-EMFPLUS](#)], v20140502 (Rev 13.0), May 2014, <<http://msdn.microsoft.com/library/cc230724>>.

- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), March 1997.
- [RFC2978] Freed, N. and J. Postel, "IANA Charset Registration Procedures", [BCP 19](#), [RFC 2978](#), October 2000.
- [RFC6838] Freed, N., Klensin, J., and T. Hansen, "Media Type Specifications and Registration Procedures", [BCP 13](#), [RFC 6838](#), January 2013.

Leonard

Exp. October 10, 2016

[Page 10]

---

Internet-Draft

Windows Image Media Types

April 2016

## [6.2](#). Informative References

- [MICE] Microsoft Corporation, "Vulnerability in Graphics Rendering Engine Could Allow Remote Code Execution (912919)", MS06-001, V1.0, January 2006, <<https://technet.microsoft.com/library/security/ms06-001>>.
- [MS-OSP] Microsoft Corporation, "Open Specification Promise", February 2007, <<http://www.microsoft.com/interop/osp/default.mspx>>.
- [OOXML] Ecma International, "Office Open XML File Formats", Standard ECMA-376, Fourth Edition, ISO/IEC 29500, December 2012, <<http://www.ecma-international.org/publications/standards/Ecma-376.htm>>.
- [PWNIES07] Pwnie Awards LLC, "Pwnie Awards 2007", 2007, <<http://pwnies.com/archive/2007/winners/>>.

## Author's Address

Sean Leonard  
Penango, Inc.  
5900 Wilshire Boulevard  
21st Floor  
Los Angeles, CA 90036  
USA

EMail: [dev+iETF@seantek.com](mailto:dev+iETF@seantek.com)

URI: <http://www.penango.com/>

Leonard

Exp. October 10, 2016

[Page 11]