

Interdomain Routing
Internet-Draft
Intended status: Informational
Expires: December 16, 2015

A. Shaikh, Ed.
Google
R. Shakir, Ed.
BT
K. Patel, Ed.
Cisco
S. Hares, Ed.
Huawei
K. D'Souza
AT&T
D. Bansal
Microsoft
A. Clemm
A. Zhdankin
Cisco
M. Jethanandani
Ciena
X. Liu
Ericsson
June 14, 2015

BGP Model for Service Provider Networks
draft-shaikh-idr-bgp-model-02

Abstract

This document defines a YANG data model for configuring and managing BGP, including protocol, policy, and operational aspects based on data center, carrier and content provider operational requirements.

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <http://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on December 16, 2015.

Internet-Draft

BGP Model

June 2015

Copyright Notice

Copyright (c) 2015 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

1. Introduction

YANG [[RFC6020](#)] is a data modeling language that was introduced to define the contents of a conceptual data store that allows networked devices to be managed using NETCONF [[RFC6241](#)]. YANG is proving relevant beyond its initial confines, as bindings to other interfaces (e.g. ReST) and encodings other than XML (e.g. JSON) are being defined. Furthermore, YANG data models can be used as the basis of implementation for a number of interfaces, such as CLIs and programmatic APIs.

This document describes a YANG data model for the BGP [[RFC4271](#)] protocol, including various protocol extensions, policy configuration, as well as defining key operational state data. The model is intended to be vendor-neutral, in order to allow operators to manage BGP configuration in heterogeneous environments with routers supplied by multiple vendors. The model is also intended to be readily mapped to existing implementations to facilitate support from as large a set of routing hardware and software vendors as possible.

1.1. Goals and approach

The model covers the base BGP features that are deployed across major implementations and the common BGP configurations in use across a number of operator network deployments. In particular, this model attempts to cover BGP features defined in [[RFC4271](#)], [[RFC1997](#)], [[RFC4456](#)], [[RFC4760](#)], [[RFC3065](#)], [[RFC2439](#)], [[RFC4724](#)], and [[RFC6811](#)].

Along with configuration of base BGP features, this model also addresses policy configuration, by providing "hooks" for applying policies, and also defining BGP-specific policy features. The BGP policy features are intended to be used with the general routing

policy model defined in [[I-D.shaikh-rtgwg-policy-model](#)]. The model also supports operational state data to enable a common model for reading BGP-related state from a BGP speaker.

For the base BGP features, the focus of the model described in this document is on providing configuration and operational state information relating to:

- o The global BGP instance, and neighbors whose configuration is specified individually, or templated with the use of peer-groups.
- o The address families that are supported by peers, and the global configuration which relates to them.
- o The policy configuration "hooks" and BGP-specific policy features that relate to a neighbor - controlling the import and export of NLRIs.

As mentioned earlier, any configuration items that are deemed to be widely available in existing major BGP implementations are included in the model. Additional, more esoteric, configuration items that are not commonly used, or only available from a single implementation, are omitted from the model with an expectation that they will be available in companion modules that augment the current model. This allows clarity in identifying data that is part of the vendor-neutral base model.

Where possible, naming in the model follows conventions used in available standards documents, and otherwise tries to be self-explanatory with sufficient descriptions of the intended behavior. Similarly, configuration data value constraints and default values, where used, are based on recommendations in current standards documentation. Since implementations vary widely in this respect, this version of the model specifies only a limited set of defaults and ranges with the expectation of being more prescriptive in future versions based on actual operator use.

2. Model overview

The BGP model is defined across several YANG modules but at a high level is organized into Six elements:

- o base protocol configuration -- configuration affecting BGP protocol-related operations, defined at various levels of hierarchy.
- o multiprotocol configuration -- configuration affecting individual address-families within BGP [[RFC4760](#)].

Shaikh, et al.

Expires December 16, 2015

[Page 3]

Internet-Draft

BGP Model

June 2015

- o neighbor configuration -- configuration affecting an individual neighbor within BGP.
- o neighbor multiprotocol configuration -- configuration affecting individual address-families for a neighbor within BGP.
- o policy configuration -- hooks for application of the policies defined in [[I-D.shaikh-rtgwg-policy-model](#)] that act on routes sent (received) to (from) peers or other routing protocols and BGP-specific policy features.
- o operational state -- variables used for monitoring, management, etc. of BGP operations.

These modules also make use of standard Internet types, such as IP addresses and prefixes, autonomous system numbers, etc., defined in [RFC 6991](#) [[RFC6991](#)].

Throughout the model, the approach described in [[I-D.openconfig-netmod-opstate](#)] is used to represent configuration (intended state), operational and derived state data. That is to say, that each container holds a "config" and "state" sub-container - with the config container being used for configurable parameters, and the state container container holding representing both the operational state of configurable leaves, and derived counters and statistical information.

2.1. BGP protocol configuration

The BGP protocol configuration model is organized hierarchically, much like the majority of router implementations. That is, configuration items can be specified at multiple levels, as shown below.

```
+--rw bgp!  
  +--rw global  
  |   +-- (global-configuration-options)  
  +--rw neighbors  
  |   +--rw neighbor* [neighbor-address]  
  |   +-- (neighbor-configuration-options)  
  +--rw peer-groups  
  |   +--rw peer-group* [peer-group-name]  
  |   +-- (neighbor-configuration-options)
```

Users may specify configuration at a higher level and have it apply to all lower-level items, or provide overriding configuration at a lower level of the hierarchy. Overriding configuration items are optional, with neighbor specific configuration being the most

specific or lowest level, followed by peer-group, and finally global. Global configuration options reflect a subset of the peer-group or neighbor specific configuration options which are relevant to the entire BGP instance.

The model makes the simplifying assumption that most of the configuration items are available at all levels of the hierarchy. That is, very little configuration is specific to a particular level in the hierarchy, other than obvious items such as "group-name" only being available for the peer group-level config. A notable exception is for sub-address family configuration where some items are only applicable for a given AFI-SAFI combination.

In order to allow common configuration to be applied to a set of neighbors, all neighbor configuration options are available within a peer-group. A neighbor is associated to a particular peer-group through the use of a peer-group leaf (which provides a reference to a configured item in the peer-group list).

Address-family configuration is made available in multiple points within the model - primarily within the global container, where instance-wide configuration can be set (for example, global protocol

parameters, the BGP best path route selection options, or global policies relating to the address-family); and on a per-neighbor or per-peer-group basis, where address-families can be enabled or disabled, and policy associated with the parent entity applied. Within the afi-safi container, generic configuration that applies to all address-families (e.g., whether the AFI-SAFI is enabled) is presented at the top-level, with address-family specific containers made available for options relating to only that AFI-SAFI. Within the current revision of the model a generic set of address-families, and common configuration and state options are included - further work is expected to add additional parameters to this area of the model.

The following address-families are currently supported by the model:

```
+--rw bgp!  
  +--rw global  
    +--rw afi-safis  
      +--rw afi-safi* [afi-safi-name]  
        +--rw afi-safi-name    -> ../config/afi-safi-name  
        |  
        +--rw ipv4-unicast  
        |    ...  
        +--rw ipv6-unicast  
        |    ...  
        +--rw ipv4-labelled-unicast  
        |    ...  
        +--rw ipv6-labelled-unicast  
        |    ...  
        +--rw l3vpn-ipv4-unicast
```

```

|      ...
+--rw l3vpn-ipv6-unicast
|      ...
+--rw l3vpn-ipv4-multicast
|      ...
+--rw l3vpn-ipv6-multicast
|      ...
+--rw l2vpn-vpls
|      ...
+--rw l2vpn-evpn
|      ...

```

2.2. Policy configuration overview

The BGP policy configuration model references the generic YANG routing policy model described in [[I-D.shaikh-rtgwg-policy-model](#)], which represents a condition-action policy framework for routing. This model adds BGP-specific conditions (e.g., matching on the community attribute), and actions (e.g., setting local preference) to the generic policy framework.

Policies that are defined in the routing-policy model are referenced in multiple places within the model:

- o within the global instance, where a policy applies to all address-families for all peers.
- o on a global AFI-SAFI basis, where policies apply to all peers for a particular address-family.
- o on a per-peer-group or per-neighbor basis - where the policy applies to all address-families for the particular parent entity.

- o on a per-afi-safi basis within a neighbor or peer-group context, where the policy is specific to the AFI-SAFI for a a specific neighbor or group.

```

+--rw bgp
  +--rw global
    | +--rw afi-safi
    | | +--rw afi-safi* [afi-safi-name]

```

```

| |      +--rw apply-policy
| +--rw apply-policy
+--rw neighbors
| +--rw neighbor* [neighbor-address]
|   +--rw afi-safi
|     | +--rw afi-safi* [afi-safi-name]
|     |   +--rw apply-policy
|     +--rw apply-policy
+--rw peer-groups
   +--rw peer-group* [peer-group-name]
     +--rw afi-safi
       | +--rw afi-safi* [afi-safi-name]
       |   +--rw apply-policy
       +--rw apply-policy

```

[2.3.](#) Operational data overview

The BGP operational model contains a set of parameters which relate to the operational state of the various elements of the BGP router. As noted in [Section 2](#) - the approach described in [\[I-D.openconfig-netmod-opstate\]](#) is utilized for the inclusion of operational and statistical data. To this end, the "_state" groupings (those that contain derived operational parameters) are contained within the BGP operational model - and included within the relevant "state" containers throughout the core BGP model. In some cases, operational information may be relevant to one instance of a common grouping, but not another - for example, the number of received, advertised, and installed prefixes is relevant on a per-neighbor-basis, but is not required (or meaningful) in the peer-group context. To enable state to be added to particular contexts, the tree is augmented through the base BGP module to add these variables, without requiring separate groupings.

[3.](#) Security Considerations

BGP configuration has a significant impact on network operations, and as such any related protocol or model carries potential security risks.

protocol over an SSH transport. This provides an authenticated and secure channel over which to transfer BGP configuration and operational data. Note that use of alternate transport or data encoding (e.g., JSON over HTTPS) would require similar mechanisms for authenticating and securing access to configuration data.

Most of the data elements in the configuration model could be considered sensitive from a security standpoint. Unauthorized access or invalid data could cause major disruption.

[4.](#) IANA Considerations

This YANG data model and the component modules currently use a temporary ad-hoc namespace. If and when it is redirected for the standards track, an appropriate namespace URI will be registered in the IETF XML Registry" [[RFC3688](#)]. The BGP YANG modules will be registered in the "YANG Module Names" registry [[RFC6020](#)].

[5.](#) YANG modules

The modules comprising the BGP configuration and operational model are described by the YANG modules in the sections below. The base module imports the other modules to create the overall model.

[5.1.](#) BGP base items

```
<CODE BEGINS> file bgp.yang
module bgp {

    yang-version "1";

    // namespace
    namespace "http://openconfig.net/yang/bgp";

    prefix "bgp";

    // import some basic inet types
    import ietf-inet-types { prefix inet; }
    import bgp-multiprotocol { prefix bgp-mp; }
    import routing-policy { prefix rpol; }
    import bgp-types { prefix bgp-types; }
    import bgp-operational { prefix bgp-op; }

    // meta
    organization
        "OpenConfig working group";
```

```
contact
```

```
  "OpenConfig working group  
  netopenconfig@googlegroups.com";
```

```
description
```

```
"This module describes a YANG model for BGP protocol  
configuration. It is a limited subset of all of the configuration  
parameters available in the variety of vendor implementations,  
hence it is expected that it would be augmented with vendor-  
specific configuration data as needed. Additional modules or  
submodules to handle other aspects of BGP configuration,  
including policy, VRFs, VPNs, and additional address families  
are also expected.
```

This model supports the following BGP configuration level hierarchy:

```
BGP  
|  
+--> [ global BGP configuration ]  
  +--> AFI / SAFI global  
  +--> peer group  
    +--> [ peer group config ]  
    +--> AFI / SAFI [ per-AFI overrides ]  
  +--> neighbor  
    +--> [ neighbor config ]  
    +--> [ optional pointer to peer-group ]  
    +--> AFI / SAFI [ per-AFI overrides ]";
```

```
revision "2015-05-15" {  
  description  
    "";  
  reference "TBD";  
}
```

```
grouping bgp-global_config {  
  description
```

```
    "Global configuration options for the BGP router.";
```

```
  leaf as {
```

```
    type inet:as-number;  
    mandatory "true";
```

```
    description
```

```
      "Local autonomous system number of the router. Uses  
      the 32-bit as-number type from the model in RFC 6991.";
```

```
  }
```

```
leaf router-id {
  type inet:ipv4-address;
```

```
    description
      "Router id of the router, expressed as an
       32-bit value, IPv4 address.";
  }
}

grouping bgp-default-route-distance_config {
  description
    "Configuration options relating to the administrative distance
     (or preference) assigned to routes received from different
     sources (external, internal, and local).";

  leaf external-route-distance {
    type uint8 {
      range "1..255";
    }
    description
      "Administrative distance for routes learned from external
       BGP (eBGP).";
  }
  leaf internal-route-distance {
    type uint8 {
      range "1..255";
    }
    description
      "Administrative distance for routes learned from internal
       BGP (iBGP).";
  }
}

grouping bgp-confederation_config {
  description
    "Configuration options specifying parameters when the local
     router is within an autonomous system which is part of a BGP
     confederation.";

  leaf enabled {
    type boolean;
    description
```

```
        "When this leaf is set to true it indicates that
        the local-AS is part of a BGP confederation";
    }

    leaf identifier {
        type inet:as-number;
        description
            "Confederation identifier for the autonomous system.";
    }
}
```

```
    leaf-list member-as {
        type inet:as-number;
        description
            "Remote autonomous systems that are to be treated
            as part of the local confederation.";
    }
}

grouping bgp-neighbor_config {
    description
        "Neighbor level configuration items.";

    leaf peer-as {
        type inet:as-number;
        description
            "AS number of the peer.";
    }

    leaf local-as {
        type inet:as-number;
        description
            "The local autonomous system number that is to be used
            when establishing sessions with the remote peer or peer
            group, if this differs from the global BGP router
            autonomous system number.";
    }

    leaf peer-type {
        type bgp-types:peer-type;
        description
            "Explicitly designate the peer or peer group as internal
            (iBGP) or external (eBGP).";
    }
}
```

```

}

leaf auth-password {
    type string;
    description
        "Configures an MD5 authentication password for use with
        neighboring devices.";
}

leaf remove-private-as {
    // could also make this a container with a flag to enable
    // remove-private and separate option. here, option implies
    // remove-private is enabled.
    type bgp-types:remove-private-as-option;
    description
        "Remove private AS numbers from updates sent to peers.";
}

```

```

}

leaf route-flap-damping {
    type boolean;
    default false;
    description
        "Enable route flap damping.";
}

leaf send-community {
    type bgp-types:community-type;
    default "NONE";
    description
        "Specify which types of community should be sent to the
        neighbor or group. The default is to not send the
        community attribute";
}

leaf description {
    type string;
    description
        "An optional textual description (intended primarily for use
        with a peer or group";
}
}

```

```

grouping bgp-neighbor-timers_config {
  description
    "Config parameters related to timers associated with the BGP
    peer";

  leaf connect-retry {
    type decimal64 {
      fraction-digits 2;
    }
    default 30;
    description
      "Time interval in seconds between attempts to establish a
      session with the peer.";
  }

  leaf hold-time {
    type decimal64 {
      fraction-digits 2;
    }
    default 90;
    description
      "Time interval in seconds that a BGP session will be

```

```

    considered active in the absence of keepalive or other
    messages from the peer. The hold-time is typically
    set to 3x the keepalive-interval.";
  reference
    "RFC 4271 - A Border Gateway Protocol 4, Sec. 10";
  }

  leaf keepalive-interval {
    type decimal64 {
      fraction-digits 2;
    }
    default 30;
    description
      "Time interval in seconds between transmission of keepalive
      messages to the neighbor. Typically set to 1/3 the
      hold-time.";
  }

```

```

leaf minimum-advertisement-interval {
  type decimal64 {
    fraction-digits 2;
  }
  default 30;
  description
    "Minimum time which must elapse between subsequent UPDATE
    messages relating to a common set of NLRI being transmitted
    to a peer. This timer is referred to as
    MinRouteAdvertisementIntervalTimer by RFC 4721 and serves to
    reduce the number of UPDATE messages transmitted when a
    particular set of NLRI exhibit instability.";
  reference
    "RFC 4271 - A Border Gateway Protocol 4, Sec 9.2.1.1";
}
}

```

```

grouping bgp-neighbor-transport_config {
  description
    "Configuration parameters relating to the transport protocol
    used by the BGP session to the peer";

  leaf tcp-mss {
    type uint16;
    description
      "Sets the max segment size for BGP TCP sessions.";
  }

  leaf mtu-discovery {
    type boolean;
  }
}

```

```

  default false;
  description
    "Turns path mtu discovery for BGP TCP sessions on (true)
    or off (false)";
}

leaf passive-mode {
  type boolean;
  default false;
  description
    "Wait for peers to issue requests to open a BGP session,

```

```

        rather than initiating sessions from the local router.";
    }

    leaf local-address {
        type union {
            type inet:ip-address;
            type string;
        }
        //TODO: the string should be converted to a leafref type
        //to point to an interface when YANG 1.1 is available with
        //leafrefs in union types.
        description
            "Set the local IP (either IPv4 or IPv6) address to use
            for the session when sending BGP update messages. This
            may be expressed as either an IP address or reference
            to the name of an interface.";
    }
}

grouping bgp-neighbor-error-handling_config {
    description
        "Configuration parameters relating to enhanced error handling
        behaviours for BGP";

    leaf treat-as-withdraw {
        type boolean;
        default "false";
        description
            "Specify whether erroneous UPDATE messages for which the
            NLRI can be extracted are treated as though the NLRI is
            withdrawn - avoiding session reset";
        reference "draft-ietf-idr-error-handling-16";
    }
}

grouping bgp-neighbor-logging-options_config {
    description

```

```

    "Configuration parameters specifying the logging behaviour for
    BGP sessions to the peer";

```

```

    leaf log-neighbor-state-changes {

```

```

    type boolean;
    default "true";
    description
        "Configure logging of peer state changes. Default is
        to enable logging of peer state changes.";
}
}

grouping bgp-neighbor-multihop_config {
    description
        "Configuration parameters specifying the multihop behaviour for
        BGP sessions to the peer";

    leaf enabled {
        type boolean;
        default "false";
        description
            "When enabled the referenced group or neighbors are permitted
            to be indirectly connected - including cases where the TTL
            can be decremented between the BGP peers";
    }

    leaf multihop-ttl {
        type uint8;
        description
            "Time-to-live value to use when packets are sent to the
            referenced group or neighbors and ebgp-multihop is enabled";
    }
}

grouping bgp-neighbor-route-reflector_config {
    description
        "Configuration parameters determining whether the behaviour of
        the local system when acting as a route-reflector";

    leaf route-reflector-cluster-id {
        type bgp-types:rr-cluster-id-type;
        description
            "route-reflector cluster id to use when local router is
            configured as a route reflector. Commonly set at the group
            level, but allows a different cluster
            id to be set for each neighbor.";
    }
}

```

```
leaf route-reflector-client {
  type boolean;
  default "false";
  description
    "Configure the neighbor as a route reflector client.";
}
}

grouping bgp-neighbor-as-path-options_config {
  description
    "Configuration parameters allowing manipulation of the AS_PATH
    attribute";

  leaf allow-own-as {
    type uint8;
    default 0;
    description
      "Specify the number of occurrences of the local BGP speaker's
      AS that can occur within the AS_PATH before it is rejected.";
  }

  leaf replace-peer-as {
    type boolean;
    default "false";
    description
      "Replace occurrences of the peer's AS in the AS_PATH
      with the local autonomous system number";
  }
}

grouping bgp-neighbor-add-paths_config {
  description
    "Configuration parameters specifying whether the local system
    will send or receive multiple paths using ADD_PATHS";

  leaf receive {
    type boolean;
    default false;
    description
      "Enable ability to receive multiple path advertisements
      for an NLRI from the neighbor or group";
  }

  leaf send-max {
    type uint8;
    description
      "The maximum number of paths to advertise to neighbors";
  }
}
```

for a single NLRI";

```
    }
  }

  grouping bgp-neighbor-peer-group_config {
    description
      "Configuration parameters indicating whether the specified peer
      is to be considered as part of a peer-group - and therefore
      inherit its configuration";

    leaf peer-group {
      type leafref {
        // we are at /bgp/neighbors/neighbor/
        path "/bgp/peer-groups/peer-group/peer-group-name";
        require-instance true;
      }
      description
        "The peer-group with which this neighbor is associated";
    }
  }

  grouping bgp-graceful-restart {
    description
      "Configures BGP graceful restart, which is a negotiated
      option that indicates that a BGP speaker is able to retain
      forwarding state when a BGP session restarts";

    reference "RFC 4724: Graceful Restart Mechanism for BGP";
    container graceful-restart {
      description
        "Parameters relating the graceful restart mechanism for BGP";
      container config {
        description
          "Configuration parameters relating to graceful-restart";
        uses bgp-neighbor-graceful-restart_config;
      }
      container state {
        config false;
        description
          "State information associated with graceful-restart";
        uses bgp-neighbor-graceful-restart_config;
      }
    }
  }
}
```

```
}
}
}
```

```
grouping bgp-neighbor-graceful-restart_config {
  description
    "Configuration parameters relating to BGP graceful restart.";
```

Shaikh, et al.

Expires December 16, 2015

[Page 17]

Internet-Draft

BGP Model

June 2015

```
leaf enabled {
  type boolean;
  description
    "Enable or disable the graceful-restart capability.";
}

leaf restart-time {
  type uint16 {
    range 0..4096;
  }
  description
    "Estimated time (in seconds) for the local BGP speaker to
    restart a session. This value is advertise in the graceful
    restart BGP capability. This is a 12-bit value, referred to
    as Restart Time in RFC4724. Per RFC4724, the suggested
    default value is <= the hold-time value.";
}

leaf stale-routes-time {
  type decimal64 {
    fraction-digits 2;
  }
  description
    "An upper-bound on the time thate stale routes will be
    retained by a router after a session is restarted. If an
    End-of-RIB (EOR) marker is received prior to this timer
    expiring stale-routes will be flushed upon its receipt - if
    no EOR is received, then when this timer expires stale paths
    will be purged. This timer is referred to as the
    Selection_Deferral_Timer in RFC4724";
}

leaf helper-only {
```

```

type boolean;
description
    "Enable graceful-restart in helper mode only. When this
    leaf is set, the local system does not retain forwarding
    its own state during a restart, but supports procedures
    for the receiving speaker, as defined in RFC4724.";
}
}

// *****
// *          configuration context containers          *
// *****

grouping bgp-global-base {
description

```

```

    "Global configuration parameters for the BGP router";

container config {
description
    "Configuration parameters relating to the global BGP router";
uses bgp-global_config;
}
container state {
config false;
description
    "State information relating to the global BGP router";
uses bgp-global_config;
uses bgp-op:bgp-global_state;
}

uses bgp-mp:bgp-route-selection-options;

container default-route-distance {
description
    "Administrative distance (or preference) assigned to
    routes received from different sources
    (external, internal, and local).";

container config {
description
    "Configuration parameters relating to the default route

```

```

        distance";
    uses bgp-default-route-distance_config;
}
container state {
    config false;
    description
        "State information relating to the default route distance";
    uses bgp-default-route-distance_config;
}
}

container confederation {
    description
        "Parameters indicating whether the local system acts as part
        of a BGP confederation";

    container config {
        description
            "Configuration parameters relating to BGP confederations";
        uses bgp-confederation_config;
    }
    container state {

```

```

        config false;
        description
            "State information relating to the BGP confederations";
        uses bgp-confederation_config;
    }
}

uses bgp-mp:bgp-use-multiple-paths;

uses bgp-graceful-restart;

container afi-safis {
    description
        "Address family specific configuration";
    uses bgp-mp:bgp-common-afi-safi-list;
}
}

grouping bgp-neighbors {

```

```

description
  "BGP neighbors configured on the local system";
list neighbor {
  key "neighbor-address";
  description
    "List of BGP neighbors configured on the local system,
    uniquely identified by peer IPv[46] address";

  leaf neighbor-address {
    type leafref {
      path "../config/neighbor-address";
    }
    description
      "Reference to the address of the BGP neighbor used as
      a key in the neighbor list";
  }

  uses bgp-neighbor-group;
}
}

```

```

grouping bgp-peer-group {
  description
    "BGP peer-groups configured on the local system";
  list peer-group {
    key "peer-group-name";
    description
      "List of BGP peer-groups configured on the local system -
      uniquely identified by peer-group name";
  }
}

```

```

leaf peer-group-name {
  type leafref {
    path "../config/peer-group-name";
  }
  description
    "Reference to the name of the BGP peer-group used as a
    key in the peer-group list";
}

uses bgp-neighbor-group;
}
}

```

```

grouping bgp-neighbor-group {
  description
    "Parameters related to a BGP neighbor or group";

  container config {
    description
      "Configuration parameters relating to the BGP neighbor or
      group";
    uses bgp-neighbor_config;
  }
  container state {
    config false;
    description
      "State information relating to the BGP neighbor or group";
    uses bgp-neighbor_config;
  }

  container timers {
    description
      "Timers related to a BGP neighbor or group";
    container config {
      description
        "Configuration parameters relating to timers used for the
        BGP neighbor or group";
      uses bgp-neighbor-timers_config;
    }
    container state {
      config false;
      description
        "State information relating to the timers used for the BGP
        neighbor or group";
      uses bgp-neighbor-timers_config;
    }
  }
}

```

```

container transport {
  description
    "Transport session parameters for the BGP neighbor or group";
  container config {
    description

```

```

        "Configuration parameters relating to the transport
        session(s) used for the BGP neighbor or group";
    uses bgp-neighbor-transport_config;
}
container state {
    config false;
    description
        "State information relating to the transport session(s)
        used for the BGP neighbor or group";
    uses bgp-neighbor-transport_config;
}
}

container error-handling {
    description
        "Error handling parameters used for the BGP neighbor or
        group";
    container config {
        description
            "Configuration parameters enabling or modifying the
            behavior or enhanced error handling mechanisms for the BGP
            neighbor or group";
        uses bgp-neighbor-error-handling_config;
    }
    container state {
        config false;
        description
            "State information relating to enhanced error handling
            mechanisms for the BGP neighbor or group";
        uses bgp-neighbor-error-handling_config;
    }
}

container logging-options {
    description
        "Logging options for events related to the BGP neighbor or
        group";
    container config {
        description
            "Configuration parameters enabling or modifying logging
            for events relating to the BGP neighbor or group";
        uses bgp-neighbor-logging-options_config;
    }
}

```

```

container state {
    config false;
    description
        "State information relating to logging for the BGP neighbor
        or group";
    uses bgp-neighbor-logging-options_config;
}
}

container ebgp-multihop {
    description
        "eBGP multi-hop parameters for the BGP neighbor or group";
    container config {
        description
            "Configuration parameters relating to eBGP multihop for the
            BGP neighbor or group";
        uses bgp-neighbor-multihop_config;
    }
    container state {
        config false;
        description
            "State information for eBGP multihop, for the BGP neighbor
            or group";
        uses bgp-neighbor-multihop_config;
    }
}

container route-reflector {
    description
        "Route reflector parameters for the BGP neighbor or group";
    container config {
        description
            "Configuraton parameters relating to route reflection
            for the BGP neighbor or group";
        uses bgp-neighbor-route-reflector_config;
    }
    container state {
        config false;
        description
            "State information relating to route reflection for the
            BGP neighbor or group";
        uses bgp-neighbor-route-reflector_config;
    }
}

container as-path-options {
    description
        "AS_PATH manipulation parameters for the BGP neighbor or

```

Internet-Draft

BGP Model

June 2015

```
    group";
  container config {
    description
      "Configuration parameters relating to AS_PATH manipulation
      for the BGP peer or group";
    uses bgp-neighbor-as-path-options_config;
  }
  container state {
    config false;
    description
      "State information relating to the AS_PATH manipulation
      mechanisms for the BGP peer or group";
    uses bgp-neighbor-as-path-options_config;
  }
}

container add-paths {
  description
    "Parameters relating to the advertisement and receipt of
    multiple paths for a single NLRI (add-paths)";
  container config {
    description
      "Configuration parameters relating to ADD_PATHS";
    uses bgp-neighbor-add-paths_config;
  }
  container state {
    config false;
    description
      "State information associated with ADD_PATHS";
    uses bgp-neighbor-add-paths_config;
  }
}

container afi-safis {
  description
    "Per-address-family configuration parameters associated with
    the neighbor or group";
  uses bgp-mp:bgp-common-afi-safi-list;
}

uses bgp-graceful-restart;
```

```
    uses rpol:apply-policy-group;
}

grouping bgp-neighbor-neighbor-address_config {
  description
    "Configuration options relating to the BGP neighbor address";
```

```
  leaf neighbor-address {
    type inet:ip-address;
    description
      "Address of the BGP peer, either in IPv4 or IPv6";
  }
}

grouping bgp-peer-group-peer-group-name_config {
  description
    "Configuration options relating to the BGP peer-group name";

  leaf peer-group-name {
    type string;
    description
      "Name of the BGP peer-group";
  }
}

// add peer-group pointer only for the neighbor list
augment /bgp/neighbors/neighbor/config {
  description
    "Augmentation to allow association of a neighbor with a
    peer-group";
  uses bgp-neighbor-peer-group_config;
}

augment /bgp/neighbors/neighbor/state {
  description
    "Augmentation to reflect the association of a neighbor with a
    peer-group";
  uses bgp-neighbor-peer-group_config;
}

augment /bgp/peer-groups/peer-group {
  description
```

```

    "Augmentation to add multipath configuration to a peer-group";
    uses bgp-mp:bgp-use-multiple-paths;
}

augment /bgp/neighbors/neighbor {
  description
    "Augmentation to add the multipath configuration to a
    neighbor";
  uses bgp-mp:bgp-use-multiple-paths-neighbor;
}

augment /bgp/peer-groups/peer-group/afi-safis/afi-safi {
  description

```

```

    "Augmentation to add multipath configuration to a peer-group
    on a per-AFI-SAFI basis";
    uses bgp-mp:bgp-use-multiple-paths;
}

augment /bgp/neighbors/neighbor/afi-safis/afi-safi {
  description
    "Augmentation to add multipath configuration to a neighbor
    on a per-AFI-SAFI basis";
  uses bgp-mp:bgp-use-multiple-paths-neighbor;
}

augment /bgp/global/afi-safis/afi-safi {
  description
    "Augmentation to add global instance specific AFI-SAFI
    configuration information";
  uses bgp-mp:bgp-global-afi-safi;
  uses bgp-mp:bgp-use-multiple-paths;
}

augment /bgp/peer-groups/peer-group/afi-safis/afi-safi {
  description
    "Augmentation that adds peer-group instance specific
    AFI-SAFI configuration information";
  uses bgp-mp:bgp-group-afi-safi;
}

augment /bgp/neighbors/neighbor/config {

```

```

description
  "Augmentation adding the neighbor address to the
  neighbor configuration container";
uses bgp-neighbor-neighbor-address_config;
}

augment /bgp/neighbors/neighbor/state {
  description
    "Augmentation adding the neighbor address to the
    neighbor state container";
  uses bgp-neighbor-neighbor-address_config;
}

augment /bgp/peer-groups/peer-group/config {
  description
    "Augmentation adding the peer-group name to the
    peer-group configuration container";
  uses bgp-peer-group-peer-group-name_config;
}

```

```

augment /bgp/peer-groups/peer-group/state {
  description
    "Augmentation adding the peer-group name to the
    peer-group state container";
  uses bgp-peer-group-peer-group-name_config;
}

// *****
// *           Augmentations to add state *
// * (rjs: cleaner to have these in the base module to avoid *
// *   needing to specify which module - e.g. augment of *
// *   /bgp:bgp/bgp:neighbors/bgp:neighbor...) *
// *****
augment /bgp/neighbors/neighbor/state {
  description
    "Augmentation to add operational state related to a particular
    BGP neighbor";
  uses bgp-op:bgp-neighbor_state;
}

augment /bgp/neighbors/bgp:neighbor/state {

```

```

description
  "Augmentation to add operational state related to a particular
  BGP neighbor";

container messages {
  description
    "Counters for BGP messages sent and received from the
    neighbor";
  container sent {
    description
      "Counters relating to BGP messages sent to the neighbor";
    uses bgp-op:bgp-neighbor-message-counters-sent_state;
  }

  container received {
    description
      "Counters for BGP messages received from the neighbor";
    uses bgp-op:bgp-neighbor-message-counters-received_state;
  }
}

container queues {
  description
    "Counters related to queued messages associated with the
    BGP neighbor";
  uses bgp-op:bgp-neighbor-queue-counters_state;
}

```

```

}

augment /bgp:bgp/bgp:neighbors/neighbor/timers/state {
  description
    "Augmentation to add the operational state of timers associated
    with the BGP neighbor";
  uses bgp-op:bgp-neighbor-timers_state;
}

augment /bgp/neighbors/neighbor/transport/state {
  description
    "Augmentation to add the operational state of the transport
    session associated with the BGP neighbor";
  uses bgp-op:bgp-neighbor-transport_state;
}

```

```

}

augment /bgp/neighbors/neighbor/error-handling/state {
  description
    "Augmentation to add the operational state of the error
    handling associated with the BGP neighbor";
  uses bgp-op:bgp-neighbor-error-handling_state;
}

augment /bgp/neighbors/neighbor/graceful-restart/state {
  description
    "Augmentation to add the operational state of graceful-restart
    associated with a BGP neighbor";
  uses bgp-op:bgp-afi-safi-graceful-restart_state;
}

augment /bgp/peer-groups/peer-group/state {
  description
    "Augmentation to add the operational state and counters
    relating to a BGP peer-group";
  uses bgp-op:bgp-peer-group_state;
}

augment /bgp/global/afi-safis/afi-safi/state {
  description
    "Augmentation to add operational state and counters
    on a per-AFI-SAFI basis to the global BGP router";
  uses bgp-op:bgp-global-afi-safi_state;
}

augment /bgp/neighbors/neighbor/afi-safis/afi-safi/state {
  description
    "Augmentation to add per-AFI-SAFI operational state
    and counters to the BGP neighbor";

```

```

  uses bgp-op:bgp-neighbor-afi-safi_state;
}

augment "/bgp/neighbors/neighbor/afi-safis/afi-safi/" +
  "graceful-restart/state" {
  description
    "Augmentation to add per-AFI-SAFI operational state for BGP

```

```

    graceful-restart";
    uses bgp-op:bgp-neighbor-afi-safi-graceful-restart_state;
}

// *****
// *           module structure containers           *
// *****

container bgp {
    presence "Container for BGP protocol hierarchy";
    description
        "Top-level configuration and state for the BGP router";

    container global {
        description
            "Global configuration for the BGP router";
        uses bgp-global-base;
        uses rpol:apply-policy-group;
    }

    container neighbors {
        description
            "Configuration for BGP neighbors";
        uses bgp-neighbors;
    }

    container peer-groups {
        description
            "Configuration for BGP peer-groups";
        uses bgp-peer-group;
    }
}
}
<CODE ENDS>

```

[5.2.](#) BGP base types

```

<CODE BEGINS> file bgp-types.yang
module bgp-types {
    yang-version "1";

```

```
namespace "http://openconfig.net/yang/bgp-types";

prefix "bgp-types";

import ietf-inet-types { prefix inet; }

// meta
organization
  "OpenConfig working group";

contact
  "OpenConfig working group
  netopenconfig@googlegroups.com";

description
  "This module contains general data definitions for use in BGP
  policy. It can be imported by modules that make use of BGP
  attributes";

revision "2015-05-15" {
  description "Initial revision";
  reference "TBD";
}

identity bgp-capability {
  description "Base identity for a BGP capability";
}

identity MPBGP {
  base "bgp-capability";
  description
    "Multi-protocol extensions to BGP";
  reference "RFC2858";
}

identity ROUTE-REFRESH {
  base "bgp-capability";
  description
    "The BGP route-refresh functionality";
  reference "RFC2918";
}

identity ASN32 {
  base "bgp-capability";
  description
    "4-byte (32-bit) AS number functionality";
  reference "RFC6793";
}
```

Internet-Draft

BGP Model

June 2015

```
}

identity GRACEFUL-RESTART {
  base "bgp-capability";
  description
    "Graceful restart functionality";
  reference "RFC4724";
}

identity ADD-PATHS {
  base "bgp-capability";
  description
    "BGP add-paths";
  reference "draft-ietf-idr-add-paths";
}

identity afi-safi-type {
  description
    "Base identity type for AFI,SAFI tuples for BGP-4";
  reference "RFC4760 - multiprotocol extensions for BGP-4";
}

identity ipv4-unicast {
  base afi-safi-type;
  description
    "IPv4 unicast (AFI,SAFI = 1,1)";
  reference "RFC4760";
}

identity ipv6-unicast {
  base afi-safi-type;
  description
    "IPv6 unicast (AFI,SAFI = 2,1)";
  reference "RFC4760";
}

identity ipv4-labelled-unicast {
  base afi-safi-type;
  description
    "Labelled IPv4 unicast (AFI,SAFI = 1,4)";
  reference "RFC3107";
}
```

```
identity ipv6-labelled-unicast {
  base afi-safi-type;
  description
    "Labelled IPv6 unicast (AFI,SAFI = 2,4)";
  reference "RFC3107";
}
```

```
}

identity l3vpn-ipv4-unicast {
  base afi-safi-type;
  description
    "Unicast IPv4 MPLS L3VPN (AFI,SAFI = 1,128)";
  reference "RFC4364";
}

identity l3vpn-ipv6-unicast {
  base afi-safi-type;
  description
    "Unicast IPv6 MPLS L3VPN (AFI,SAFI = 2,128)";
  reference "RFC4659";
}

identity l3vpn-ipv4-multicast {
  base afi-safi-type;
  description
    "Multicast IPv4 MPLS L3VPN (AFI,SAFI = 1,129)";
  reference "RFC6514";
}

identity l3vpn-ipv6-multicast {
  base afi-safi-type;
  description
    "Multicast IPv6 MPLS L3VPN (AFI,SAFI = 2,129)";
  reference "RFC6514";
}

identity l2vpn-vpls {
  base afi-safi-type;
  description
    "BGP-signalled VPLS (AFI,SAFI = 25,65)";
  reference "RFC4761";
}
```

```
identity l2vpn-evpn {
  base afi-safi-type;
  description
    "BGP MPLS Based Ethernet VPN (AFI,SAFI = 25,70)";
}
```

```
identity bgp-well-known-std-community {
  description
    "Reserved communities within the standard community space
    defined by RFC1997. These communities must fall within the
    range 0x00000000 to 0xFFFFFFFF";
```

```
  reference "RFC1997";
}
```

```
identity NO_EXPORT {
  base bgp-well-known-std-community;
  description
    "Do not export NLRI received carrying this community outside
    the bounds of this autonomous system, or this confederation if
    the local autonomous system is a confederation member AS. This
    community has a value of 0xFFFFFFFF01.";
  reference "RFC1997";
}
```

```
identity NO_ADVERTISE {
  base bgp-well-known-std-community;
  description
    "All NLRI received carrying this community must not be
    advertised to other BGP peers. This community has a value of
    0xFFFFFFFF02.";
  reference "RFC1997";
}
```

```
identity NO_EXPORT_SUBCONFED {
  base bgp-well-known-std-community;
  description
    "All NLRI received carrying this community must not be
    advertised to external BGP peers - including over confederation
    sub-AS boundaries. This community has a value of 0xFFFFFFFF03.";
  reference "RFC1997";
```

```

}

identity NOPEER {
  base bgp-well-known-std-community;
  description
    "An autonomous system receiving NLRI tagged with this community
    is advised not to readvertise the NLRI to external bi-lateral
    peer autonomous systems. An AS may also filter received NLRI
    from bilateral peer sessions when they are tagged with this
    community value";
  reference "RFC3765";
}

identity INTERNET {
  base bgp-well-known-std-community;
  description
    "A community used by some implementations with the value 0:0
    which represents all possible community values.";
}

```

```

typedef bgp-session-direction {
  type enumeration {
    enum INBOUND {
      description
        "Refers to all NLRI received from the BGP peer";
    }
    enum OUTBOUND {
      description
        "Refers to all NLRI advertised to the BGP peer";
    }
  }
  description
    "Type to describe the direction of NLRI transmission";
}

typedef bgp-well-known-community-type {
  type identityref {
    base bgp-well-known-std-community;
  }
  description
    "Type definition for well-known IETF community attribute
    values";
}

```

```
reference
  "IANA Border Gateway Protocol (BGP) Well Known Communities";
}
```

```
typedef bgp-std-community-type {
  // TODO: further refine restrictions and allowed patterns
  // 4-octet value:
  // <as number> 2 octets
  // <community value> 2 octets
  type union {
    type uint32 {
      // per RFC 1997, 0x00000000 - 0x0000FFFF and 0xFFFF0000 -
      // 0xFFFFFFFF are reserved
      range "65536..4294901759"; // 0x00010000..0xFFFFEFFF
    }
    type string {
      pattern '([0-9]+:[0-9]+)';
    }
  }
  description
    "Type definition for standard community attributes";
  reference "RFC 1997 - BGP Communities Attribute";
}
```

```
typedef bgp-ext-community-type {
```

```
  // TODO: needs more work to make this more precise given the
  // variability of extended community attribute specifications
  // 8-octet value:
  // <type> 2 octets
  // <value> 6 octets
  type string {
    pattern '([0-9\.]+(:[0-9]+)?:[0-9]+)';
  }
  description
    "Type definition for extended community attributes";
  reference "RFC 4360 - BGP Extended Communities Attribute";
}
```

```
typedef bgp-community-regexp-type {
  // TODO: needs more work to decide what format these regexps can
```

```

// take.
type string;
description
    "Type definition for communities specified as regular
    expression patterns";
}

typedef bgp-origin-attr-type {
    type enumeration {
        enum IGP {
            description "Origin of the NLRI is internal";
        }
        enum EGP {
            description "Origin of the NLRI is EGP";
        }
        enum INCOMPLETE {
            description "Origin of the NLRI is neither IGP or EGP";
        }
    }
    description
        "Type definition for standard BGP origin attribute";
    reference "RFC 4271 - A Border Gateway Protocol 4 (BGP-4),
        Sec 4.3";
}

typedef peer-type {
    type enumeration {
        enum INTERNAL {
            description "internal (iBGP) peer";
        }
        enum EXTERNAL {
            description "external (eBGP) peer";
        }
    }
}

```

```

}
description
    "labels a peer or peer group as explicitly internal or
    external";
}

typedef remove-private-as-option {

```

```
type enumeration {
    enum ALL {
        description "remove all private ASes in the path";
    }
    enum REPLACE {
        description "replace private ASes with local AS";
    }
}
description
    "set of options for configuring how private AS path numbers
    are removed from advertisements";
}
```

```
typedef percentage {
    type uint8 {
        range "0..100";
    }
    description
        "Integer indicating a percentage value";
}
```

```
typedef rr-cluster-id-type {
    type union {
        type uint32;
        type inet:ipv4-address;
    }
    description
        "union type for route reflector cluster ids:
        option 1: 4-byte number
        option 2: IP address";
}
```

```
typedef community-type {
    type enumeration {
        enum STANDARD {
            description "send only standard communities";
        }
        enum EXTENDED {
            description "send only extended communities";
        }
    }
}
```

```
enum BOTH {
```

```

        description "send both standard and extended communities";
    }
    enum NONE {
        description "do not send any community attribute";
    }
}
description
    "type describing variations of community attributes:
    STANDARD: standard BGP community [rfc1997]
    EXTENDED: extended BGP community [rfc4360]
    BOTH: both standard and extended community";
}

}
<CODE ENDS>

```

[5.3.](#) BGP policy items

```

<CODE BEGINS> file bgp-policy.yang
module bgp-policy {

    yang-version "1";

    // namespace
    namespace "http://openconfig.net/yang/bgp-policy";

    prefix "bgp-pol";

    // import some basic types
    import ietf-inet-types { prefix inet; }
    import routing-policy {prefix rpol; }
    import policy-types { prefix pt; }
    import bgp-types { prefix bgp-types; }

    // meta
    organization
        "OpenConfig working group";

    contact
        "OpenConfig working group
        netopenconfig@googlegroups.com";

    description

```

```
"This module contains data definitions for BGP routing policy.
It augments the base routing-policy module with BGP-specific
options for conditions and actions.";

revision "2015-05-15" {
  description
    "Updated model to augment base routing-policy module";
  reference "TBD";
}

// extension statements

// feature statements

// identity statements

// typedef statements

typedef bgp-as-path-prepend-repeat {
  type uint8;
  description
    "Option for the BGP as-prepend policy action. Prepends the
    local AS number repeated n times";
}

typedef bgp-set-community-option-type {
  type enumeration {
    enum ADD {
      description
        "add the specified communities to the existing
        community attribute";
    }
    enum REMOVE {
      description
        "remove the specified communities from the
        existing community attribute";
    }
    enum REPLACE {
      description
        "replace the existing community attribute with
        the specified communities. If an empty set is
        specified, this removes the community attribute
        from the route.";
    }
  }
}
description
```

"Type definition for options when setting the community attribute in a policy action";

```
}

typedef bgp-next-hop-type {
  type union {
    type inet:ip-address;
    type enumeration {
      enum SELF {
        description "special designation for local router's own
          address, i.e., next-hop-self";
      }
    }
  }
  description
    "type definition for specifying next-hop in policy actions";
}

typedef bgp-set-med-type {
  type union {
    type uint32;
    type string {
      pattern "[+-][0-9]+";
    }
    type enumeration {
      enum IGP {
        description "set the MED value to the IGP cost toward the
          next hop for the route";
      }
    }
  }
  description
    "Type definition for specifying how the BGP MED can
    be set in BGP policy actions. The three choices are to set
    the MED directly, increment/decrement using +/- notation,
    and setting it to the IGP cost (predefined value).";
}

// grouping statements

grouping bgp-match-conditions {
```

```
description
  "Condition statement definitions for checking membership in a
  defined set";

container match-community-set {
  presence
    "The presence of this container indicates that the routes
    should match the referenced community-set";
```

```
description
  "Match a referenced community-set according to the logic
  defined in the match-set-options leaf";

leaf community-set {
  type leafref {
    path "/rpol:routing-policy/rpol:defined-sets/" +
      "bgp-pol:bgp-defined-sets/bgp-pol:community-sets/" +
      "bgp-pol:community-set/bgp-pol:community-set-name";
    require-instance true;
  }
  description
    "References a defined community set";
}
uses rpol:match-set-options-group;
}

container match-ext-community-set {
  presence
    "The presence of this container indicates that the routes
    should match the referenced extended community set";

  description
    "Match a referenced extended community-set according to the
    logic defined in the match-set-options leaf";

  leaf ext-community-set {
    type leafref {
      path "/rpol:routing-policy/rpol:defined-sets/" +
        "bgp-pol:bgp-defined-sets/bgp-pol:ext-community-sets/" +
        "bgp-pol:ext-community-set/" +
        "bgp-pol:ext-community-set-name";
```

```

        require-instance true;
    }
    description "References a defined extended community set";
}
uses rpol:match-set-options-group;
}

```

```

container match-as-path-set {
    presence
        "The presence of this container indicates that the route
        should match the referenced as-path set";

    description
        "Match a referenced as-path set according to the logic
        defined in the match-set-options leaf";
}

```

```

leaf as-path-set {
    type leafref {
        path "/rpol:routing-policy/rpol:defined-sets/" +
            "bgp-pol:bgp-defined-sets/bgp-pol:as-path-sets/" +
            "bgp-pol:as-path-set/bgp-pol:as-path-set-name";
        require-instance true;
    }
    description "References a defined AS path set";
}
uses rpol:match-set-options-group;
}
}

grouping bgp-attribute-conditions {
    description
        "Condition statement definitions for comparing a BGP route
        attribute to a specified value";

    leaf med-eq {
        type uint32;
        description
            "Condition to check if the received MED value is equal to
            the specified value";
    }
}

```

```

leaf origin-eq {
  type bgp-types:bgp-origin-attr-type;
  description
    "Condition to check if the route origin is equal to the
    specified value";
}

leaf-list next-hop-in {
  type inet:ip-address;
  description
    "List of next hop addresses to check for in the route
    update";
}

leaf local-pref-eq {
  type uint32;
  // TODO: add support for other comparisons if needed
  description
    "Condition to check if the local pref attribute is equal to
    the specified value";
}

container community-count {

```

```

  presence "node is present in the config data to indicate a
  community-count condition";

  description
    "Value and comparison operations for conditions based on the
    number of communities in the route update";

  uses pt:attribute-compare-operators;
}

container as-path-length {

  presence "node is present in the config data to indicate a
  as-path-length condition";

  description
    "Value and comparison operations for conditions based on the

```

```

        length of the AS path in the route update";

    uses pt:attribute-compare-operators;
}

leaf route-type {
    // TODO: verify extent of vendor support for this comparison
    type enumeration {
        enum INTERNAL {
            description "route type is internal";
        }
        enum EXTERNAL {
            description "route type is external";
        }
    }
    description
        "Condition to check the route type in the route update";
}

// augment statements

augment "/rpol:routing-policy/rpol:defined-sets" {
    description "adds BGP defined sets container to routing policy
    model";

    container bgp-defined-sets {
        description
            "BGP-related set definitions for policy match conditions";
    }
}

```

```

    container community-sets {
        description
            "Enclosing container for community sets";

        list community-set {
            key community-set-name;
            description
                "Definitions for community sets";

            leaf community-set-name {
                type string;
            }
        }
    }
}

```

```

        mandatory true;
        description
            "name / label of the community set -- this is used to
            reference the set in match conditions";
    }

    leaf-list community-member {
        type union {
            type bgp-types:bgp-std-community-type;
            type bgp-types:bgp-community-regexp-type;
            type bgp-types:bgp-well-known-community-type;
        }
        description
            "members of the community set";
    }
}

container ext-community-sets {
    description
        "Enclosing container for extended community sets";

    list ext-community-set {
        key ext-community-set-name;
        description
            "Definitions for extended community sets";

        leaf ext-community-set-name {
            type string;
            description
                "name / label of the extended community set -- this is
                used to reference the set in match conditions";
        }

        leaf-list ext-community-member {
            type union {
                type bgp-types:bgp-ext-community-type;

```

```

        // TODO: is regexp support needed for extended
        // communities?
        type bgp-types:bgp-community-regexp-type;
    }

```

```

        description
            "members of the extended community set";
    }
}

container as-path-sets {
    description
        "Enclosing container for AS path sets";

    list as-path-set {
        key as-path-set-name;
        description
            "Definitions for AS path sets";

        leaf as-path-set-name {
            type string;
            description
                "name of the AS path set -- this is used to reference
                the set in match conditions";
        }

        leaf-list as-path-set-member {
            // TODO: need to refine typedef for AS path expressions
            type string;
            description
                "AS path expression -- list of ASes in the set";
        }
    }
}

augment "/rpol:routing-policy/rpol:policy-definitions/" +
    "rpol:policy-definition/rpol:statements/rpol:statement/" +
    "rpol:conditions" {
    description "BGP policy conditions added to routing policy
    module";

    container bgp-conditions {
        description "Policy conditions for matching
        BGP-specific defined sets or comparing BGP-specific
        attributes";
    }
}

```

```
    uses bgp-match-conditions;
    uses bgp-attribute-conditions;
  }
}

augment "/rpol:routing-policy/rpol:policy-definitions/" +
  "rpol:policy-definition/rpol:statements/rpol:statement/" +
  "rpol:actions" {
  description "BGP policy actions added to routing policy
  module";

  container bgp-actions {
    description
      "Definitions for policy action statements that
      change BGP-specific attributes of the route";

    container set-as-path-prepend {

      presence "node is present in the config data to use the AS
      prepend action";
      description
        "action to prepend local AS number to the AS-path a
        specified number of times";

      leaf repeat-n {
        type uint8;
        description "number of times to prepend the local AS
        number";
      }
    }
  }

  container set-community {
    presence "node is present in the config data when
    set-community action is used";
    description
      "action to set the community attributes of the route, along
      with options to modify how the community is modified";

    choice set-community-method {
      description
        "Option to set communities using an inline list or
        reference to an existing defined set.";

      case inline {
        leaf-list communities {
          type union {
            type bgp-types:bgp-std-community-type;
          }
        }
      }
    }
  }
}
```

```
type bgp-types:bgp-well-known-community-type;
```

```
    }
    description
      "Set the community values for the update inline with
      a list.";
  }
}
case reference {
  leaf community-set-ref {
    type leafref {
      path "/rpol:routing-policy/rpol:defined-sets/" +
        "bgp-pol:bgp-defined-sets/" +
        "bgp-pol:community-sets/bgp-pol:community-set/" +
        "bgp-pol:community-set-name";
      require-instance true;
    }
    description
      "References a defined community set by name";
  }
}
leaf options {
  type bgp-set-community-option-type;
  description
    "Options for modifying the community attribute with
    the specified values. These options apply to both
    methods of setting the community attribute.";
}
}

container set-ext-community {

  presence "node is present in the config data when
  set-community action is used";
  description
    "Action to set the extended community attributes of the
    route, along with options to modify how the community is
    modified";

  choice set-ext-community-method {
    description
```

"Option to set communities using an inline list or reference to an existing defined set.";

```
case inline {
  leaf-list communities {
    type union {
      type bgp-types:bgp-ext-community-type;
      type bgp-types:bgp-well-known-community-type;
    }
  }
}
```

```
    }
    description
      "Set the community values for the update inline with
      a list.";
  }
}
case reference {
  leaf ext-community-set-ref {
    type leafref {
      path "/rpol:routing-policy/rpol:defined-sets/" +
        "bgp-pol:bgp-defined-sets/" +
        "bgp-pol:ext-community-sets/" +
        "bgp-pol:ext-community-set/" +
        "bgp-pol:ext-community-set-name";
      require-instance true;
    }
    description
      "References a defined extended community set by
      name";
  }
}
leaf options {
  type bgp-set-community-option-type;
  description
    "options for modifying the extended community
    attribute with the specified values. These options
    apply to both methods of setting the community
    attribute.";
}
}
leaf set-route-origin {
```

```

    type bgp-types:bgp-origin-attr-type;
    description "set the origin attribute to the specified
value";
}

leaf set-local-pref {
    type uint32;
    description "set the local pref attribute on the route
update";
}

leaf set-next-hop {
    type bgp-next-hop-type;
    description "set the next-hop attribute in the route update";
}

```

```

    leaf set-med {
        type bgp-set-med-type;
        description "set the med metric attribute in the route
update";
    }
}

// rpc statements

// notification statements
}
<CODE ENDS>

```

[5.4.](#) BGP multiprotocol items

```

<CODE BEGINS> file bgp-multiprotocol.yang
module bgp-multiprotocol {

    yang-version "1";

    // namespace
    namespace "http://openconfig.net/yang/bgp-multiprotocol";

    prefix "bgp-mp";

```

```

// import some basic inet types
import routing-policy { prefix rpol; }
import bgp-types { prefix bgp-types; }
import bgp-operational { prefix bgp-op; }

// meta
organization
  "OpenConfig working group";

contact
  "OpenConfig working group
  netopenconfig@googlegroups.com";

description
  "This module is part of a YANG model for BGP protocol
  configuration, focusing on configuration of multiprotocol
  BGP, in particular various relevant address families (AFI) and
  sub-address families (SAFI).

  Identities (rather than enumerated types) are used to identify
  each AFI / SAFI type to make it easier for users to extend to

```

pre-standard or custom AFI/SAFI types. This module is only intended to capture the most";

```

revision "2015-05-15" {
  description
    "Refactored multiprotocol module";
  reference "TBD";
}

grouping ipv4-unicast-group {
  description
    "Group for IPv4 Unicast configuration options";

  container ipv4-unicast {
    when "../afi-safi-name = 'bgp-mp:ipv4-unicast'" {
      description
        "Include this container for IPv4 Unicast specific
        configuration";
    }
  }
}

```

```

    }

    description "IPv4 unicast configuration options";

    // include common IPv[46] unicast options
    uses ipv4-ipv6-unicast-common;

    // placeholder for IPv4 unicast specific configuration
}
}

grouping ipv6-unicast-group {
    description
        "Group for IPv6 Unicast configuration options";

    container ipv6-unicast {
        when "../afi-safi-name = 'bgp-mp:ipv6-unicast'" {
            description
                "Include this container for IPv6 Unicast specific
                configuration";
        }

        description "IPv6 unicast configuration options";

        // include common IPv[46] unicast options
        uses ipv4-ipv6-unicast-common;

        // placeholder for IPv6 unicast specific configuration
        // options

```

```

    }
}

grouping ipv4-labelled-unicast-group {
    description
        "Group for IPv4 Labelled Unicast configuration options";

    container ipv4-labelled-unicast {
        when "../afi-safi-name = 'bgp-mp:ipv4-labelled-unicast'" {
            description
                "Include this container for IPv4 Labelled Unicast specific
                configuration";
        }

```

```

    }

    description "IPv4 Labelled Unicast configuration options";

    uses all-afi-safi-common;

    // placeholder for IPv4 Labelled Unicast specific config
    // options
}
}

grouping ipv6-labelled-unicast-group {
    description
        "Group for IPv6 Labelled Unicast configuration options";

    container ipv6-labelled-unicast {
        when "../afi-safi-name = 'bgp-mp:ipv6-labelled-unicast'" {
            description
                "Include this container for IPv6 Labelled Unicast specific
                configuration";
        }

        description "IPv6 Labelled Unicast configuration options";

        uses all-afi-safi-common;

        // placeholder for IPv6 Labelled Unicast specific config
        // options.
    }
}

grouping l3vpn-ipv4-unicast-group {
    description
        "Group for IPv4 Unicast L3VPN configuration options";

    container l3vpn-ipv4-unicast {

```

```

    when "../afi-safi-name = 'bgp-mp:l3vpn-ipv4-unicast'" {
        description
            "Include this container for IPv4 Unicast L3VPN specific
            configuration";
    }

```

```

description "Unicast IPv4 L3VPN configuration options";

// include common L3VPN configuration options
uses l3vpn-ipv4-ipv6-unicast-common;

// placeholder for IPv4 Unicast L3VPN specific config options.
}
}

grouping l3vpn-ipv6-unicast-group {
description
  "Group for IPv6 Unicast L3VPN configuration options";

container l3vpn-ipv6-unicast {
when "../afi-safi-name = 'bgp-mp:l3vpn-ipv6-unicast'" {
description
  "Include this container for unicast IPv6 L3VPN specific
  configuration";
}

description "Unicast IPv6 L3VPN configuration options";

// include common L3VPN configuration options
uses l3vpn-ipv4-ipv6-unicast-common;

// placeholder for IPv6 Unicast L3VPN specific configuration
// options
}
}

grouping l3vpn-ipv4-multicast-group {
description
  "Group for IPv4 L3VPN multicast configuration options";

container l3vpn-ipv4-multicast {
when "../afi-safi-name = 'bgp-mp:l3vpn-ipv4-multicast'" {
description
  "Include this container for multicast IPv6 L3VPN specific
  configuration";
}

description "Multicast IPv4 L3VPN configuration options";
}
}

```

```

    // include common L3VPN multicast options
    uses l3vpn-ipv4-ipv6-multicast-common;

    // placeholder for IPv4 Multicast L3VPN specific configuration
    // options
}
}

grouping l3vpn-ipv6-multicast-group {
    description
        "Group for IPv6 L3VPN multicast configuration options";

    container l3vpn-ipv6-multicast {
        when "../afi-safi-name = 'bgp-mp:l3vpn-ipv6-multicast'" {
            description
                "Include this container for multicast IPv6 L3VPN specific
                configuration";
        }

        description "Multicast IPv6 L3VPN configuration options";

        // include common L3VPN multicast options
        uses l3vpn-ipv4-ipv6-multicast-common;

        // placeholder for IPv6 Multicast L3VPN specific configuration
        // options
    }
}

grouping l2vpn-vpls-group {
    description
        "Group for BGP-signalled VPLS configuration options";

    container l2vpn-vpls {
        when "../afi-safi-name = 'bgp-mp:l2vpn-vpls'" {
            description
                "Include this container for BGP-signalled VPLS specific
                configuration";
        }

        description "BGP-signalled VPLS configuration options";

        // include common L2VPN options
        uses l2vpn-common;

        // placeholder for BGP-signalled VPLS specific configuration
        // options
    }
}

```

Internet-Draft

BGP Model

June 2015

```
}

grouping l2vpn-evpn-group {
  description
    "Group for BGP EVPN configuration options";

  container l2vpn-evpn {
    when "../afi-safi-name = 'bgp-mp:l2vpn-evpn'" {
      description
        "Include this container for BGP EVPN specific
        configuration";
    }

    description "BGP EVPN configuration options";

    // include common L2VPN options
    uses l2vpn-common;

    // placeholder for BGP EVPN specific configuration options
  }
}

grouping bgp-route-selection-options_config {
  description
    "Set of configuration options that govern best
    path selection.";

  leaf always-compare-med {
    type boolean;
    default "false";
    description
      "Compare multi-exit discriminator (MED) value from
      different ASes when selecting the best route. The
      default behavior is to only compare MEDs for paths
      received from the same AS.";
  }

  leaf ignore-as-path-length {
    type boolean;
    default "false";
  }
}
```

```
description
  "Ignore the AS path length when selecting the best path.
  The default is to use the AS path length and prefer paths
  with shorter length.";
}
```

```
leaf external-compare-router-id {
  type boolean;
  default "true";
  description
    "When comparing similar routes received from external
    BGP peers, use the router-id as a criterion to select
    the active path.";
}

leaf advertise-inactive-routes {
  type boolean;
  default "false";
  description
    "Advertise inactive routes to external peers. The
    default is to only advertise active routes.";
}

leaf enable-aigp {
  type boolean;
  default false;
  description
    "Flag to enable sending / receiving accumulated IGP
    attribute in routing updates";
}

leaf ignore-next-hop-igp-metric {
  type boolean;
  default "false";
  description
    "Ignore the IGP metric to the next-hop when calculating
    BGP best-path. The default is to select the route for
    which the metric to the next-hop is lowest";
}
}
```

```

grouping bgp-use-multiple-paths-ebgp-as-options_config {
  description
    "Configuration parameters specific to eBGP multipath applicable
    to all contexts";

  leaf allow-multiple-as {
    type boolean;
    default "false";
    description
      "Allow multipath to use paths from different neighbouring
      ASes. The default is to only consider multiple paths from
      the same neighbouring AS.";
  }
}

```

```

}

grouping bgp-use-multiple-paths-ebgp_config {
  description
    "Configuration parameters relating to multipath for eBGP";

  uses bgp-use-multiple-paths-ebgp-as-options_config;

  leaf maximum-paths {
    type uint32;
    default 1;
    description
      "Maximum number of parallel paths to consider when using
      BGP multipath. The default is use a single path.";
  }
}

grouping bgp-use-multiple-paths-ibgp_config {
  description
    "Configuration parameters relating to multipath for iBGP";

  leaf maximum-paths {
    type uint32;
    default 1;
    description
      "Maximum number of parallel paths to consider when using
      iBGP multipath. The default is to use a single path";
  }
}

```

```

}

grouping bgp-use-multiple-paths {
  description
    "Configuration parameters relating to multipath for BGP - both
    iBGP and eBGP";

  container use-multiple-paths {
    description
      "Parameters related to the use of multiple paths for the
      same NLRI";

    container config {
      description
        "Configuration parameters relating to multipath";
      uses bgp-use-multiple-paths_config;
    }
    container state {
      description
        "State parameters relating to multipath";
    }
  }
}

```

```

    uses bgp-use-multiple-paths_config;
  }

  container ebgp {
    description
      "Multipath parameters for eBGP";
    container config {
      description
        "Configuration parameters relating to eBGP multipath";
      uses bgp-use-multiple-paths-ebgp_config;
    }
    container state {
      config false;
      description
        "State information relating to eBGP multipath";
      uses bgp-use-multiple-paths-ebgp_config;
    }
  }
}

container ibgp {
  description

```

```

    "Multipath parameters for iBGP";
  container config {
    description
      "Configuration parameters relating to iBGP multipath";
    uses bgp-use-multiple-paths-ibgp_config;
  }
  container state {
    config false;
    description
      "State information relating to iBGP multipath";
    uses bgp-use-multiple-paths-ibgp_config;
  }
}
}
}
}

```

```

grouping bgp-use-multiple-paths-neighbor {
  description
    "Per-neighbor configuration for multipath for BGP";

  container use-multiple-paths {
    description
      "Parameters related to the use of multiple-paths for the same
      NLRI when they are received only from this neighbor";

    container config {
      description

```

```

    "Configuration parameters relating to multipath";
    uses bgp-use-multiple-paths_config;
  }
  container state {
    description
      "State parameters relating to multipath";
    uses bgp-use-multiple-paths_config;
  }

  container ebgp {
    description
      "Multipath configuration for eBGP";
    container config {
      description

```

```

        "Configuration parameters relating to eBGP multipath";
        uses bgp-use-multiple-paths-ebgp-as-options_config;
    }
    container state {
        config false;
        description
            "State information relating to eBGP multipath";
            uses bgp-use-multiple-paths-ebgp-as-options_config;
        }
    }
}

```

```

grouping bgp-use-multiple-paths_config {
    description
        "Generic configuration options relating to use of multiple
        paths for a referenced AFI-SAFI, group or neighbor";

```

```

    leaf enabled {
        type boolean;
        default false;
        description
            "Whether the use of multiple paths for the same NLRI is
            enabled for the neighbor. This value is overridden by
            any more specific configuration value.";
    }
}

```

```

grouping bgp-afi-safi-graceful-restart_config {
    description
        "BGP graceful restart parameters that apply on a per-AFI-SAFI
        basis";

```

```

    leaf enabled {

```

```

        type boolean;
        default false;
        description
            "This leaf indicates whether graceful-restart is enabled for
            this AFI-SAFI";
    }
}

```

```

grouping bgp-afi-safi_config {
  description
    "Configuration parameters used for all BGP AFI-SAFIs";

  leaf afi-safi-name {
    type identityref {
      base bgp-types:afi-safi-type;
    }
    description "AFI,SAFI";
  }

  leaf enabled {
    type boolean;
    default false;
    description
      "This leaf indicates whether the IPv4 Unicast AFI,SAFI is
      enabled for the neighbour or group";
  }
}

grouping all-afi-safi-common-prefix-limit_config {
  description
    "Configuration parameters relating to prefix-limits for an
    AFI-SAFI";

  leaf max-prefixes {
    type uint32;
    description
      "Maximum number of prefixes that will be accepted
      from the neighbour";
  }

  leaf shutdown-threshold-pct {
    type bgp-types:percentage;
    description
      "Threshold on number of prefixes that can be received
      from a neighbour before generation of warning messages
      or log entries. Expressed as a percentage of
      max-prefixes";
  }
}

```

```

leaf restart-timer {
  type decimal64 {
    fraction-digits 2;
  }
  units "seconds";
  description
    "Time interval in seconds after which the BGP session
    is re-established after being torn down due to exceeding
    the max-prefix limit.";
}
}

grouping ipv4-ipv6-unicast-common_config {
  description
    "Common configuration parameters for IPv4 and IPv6 Unicast
    address families";

  leaf send-default-route {
    type boolean;
    default "false";
    description
      "If set to true, send the default-route to the neighbour(s)";
  }
}

grouping all-afi-safi-common {
  description
    "Grouping for configuration common to all AFI,SAFI";

  container prefix-limit {
    description
      "Configure the maximum number of prefixes that will be
      accepted from a peer";

    container config {
      description
        "Configuration parameters relating to the prefix
        limit for the AFI-SAFI";
      uses all-afi-safi-common-prefix-limit_config;
    }
    container state {
      config false;
      description
        "State information relating to the prefix-limit for the
        AFI-SAFI";
      uses all-afi-safi-common-prefix-limit_config;
    }
  }
}
}

```

Internet-Draft

BGP Model

June 2015

```
}

grouping ipv4-ipv6-unicast-common {
  description
    "Common configuration that is applicable for IPv4 and IPv6
    unicast";

  // include common afi-safi options.
  uses all-afi-safi-common;

  // configuration options that are specific to IPv[46] unicast
  container config {
    description
      "Configuration parameters for common IPv4 and IPv6 unicast
      AFI-SAFI options";
    uses ipv4-ipv6-unicast-common_config;
  }
  container state {
    config false;
    description
      "State information for common IPv4 and IPv6 unicast
      parameters";
    uses ipv4-ipv6-unicast-common_config;
  }
}

grouping l3vpn-ipv4-ipv6-unicast-common {
  description
    "Common configuration applied across L3VPN for IPv4
    and IPv6";

  // placeholder -- specific configuration options that are generic
  // across IPv[46] unicast address families.
  uses all-afi-safi-common;
}

grouping l3vpn-ipv4-ipv6-multicast-common {
  description
    "Common configuration applied across L3VPN for IPv4
    and IPv6";

  // placeholder -- specific configuration options that are
  // generic across IPv[46] multicast address families.
```

```
    uses all-afi-safi-common;
}
```

```
grouping l2vpn-common {
    description
```

```
    "Common configuration applied across L2VPN address
    families";

    // placeholder -- specific configuration options that are
    // generic across L2VPN address families
    uses all-afi-safi-common;
}

grouping bgp-route-selection-options {
    description
        "Parameters relating to the BGP route selection process";

    container route-selection-options {
        description
            "Parameters relating to options for route selection";
        container config {
            description
                "Configuration parameters relating to route selection
                options";
            uses bgp-route-selection-options_config;
        }
        container state {
            config false;
            description
                "State information for the route selection options";
            uses bgp-route-selection-options_config;
        }
    }
}

// ***** STRUCTURE GROUPINGS *****

grouping bgp-global-afi-safi {
    description
        "Parameters and route selection options for MP-BGP
        specific to the Global AFI-SAFI";
```

```

    uses bgp-route-selection-options;
}

grouping bgp-group-afi-safi {
    description
        "Parameters and route selection options for MP-BGP
        specific to peer groups";
    uses bgp-route-selection-options;
}

grouping bgp-common-afi-safi-list {
    description

```

"List of address-families associated with the BGP instance,
a peer-group or neighbor";

```

list afi-safi {
    key "afi-safi-name";

    description
        "AFI,SAFI configuration available for the
        neighbour or group";

    leaf afi-safi-name {
        type leafref {
            path "../config/afi-safi-name";
        }
        description
            "Reference to the AFI-SAFI name used as a key
            for the AFI-SAFI list";
    }

    container graceful-restart {
        description
            "Parameters relating to BGP graceful-restart";
        container config {
            description
                "Configuration options for BGP graceful-restart";
            uses bgp-afi-safi-graceful-restart_config;
        }
        container state {

```

```

        config false;
        description
            "State information for BGP graceful-restart";
        uses bgp-afi-safi-graceful-restart_config;
    }
}

container config {
    description
        "Configuration parameters for the AFI-SAFI";
    uses bgp-afi-safi_config;
}
container state {
    config false;
    description
        "State information relating to the AFI-SAFI";
    uses bgp-afi-safi_config;
    uses bgp-op:bgp-afi-safi_state;
}

```

```

// import and export policy included for the afi/safi
uses rpol:apply-policy-group;

uses ipv4-unicast-group;
uses ipv6-unicast-group;
uses ipv4-labelled-unicast-group;
uses ipv6-labelled-unicast-group;
uses l3vpn-ipv4-unicast-group;
uses l3vpn-ipv6-unicast-group;
uses l3vpn-ipv4-multicast-group;
uses l3vpn-ipv6-multicast-group;
uses l2vpn-vpls-group;
uses l2vpn-evpn-group;
}
}
}
<CODE ENDS>

```

[5.5.](#) BGP operational data items

```
<CODE BEGINS> file bgp-operational.yang
```

```

module bgp-operational {

  yang-version "1";

  // namespace
  // TODO: change to an ietf or other more generic namespace
  namespace "http://openconfig.net/yang/bgp-operational";

  prefix "bgp-op";

  // import some basic inet types
  import ietf-inet-types { prefix inet; }
  import ietf-yang-types { prefix yang; }
  import bgp-types { prefix bgp-types; }

  // meta

  organization
    "OpenConfig working group";

  contact
    "OpenConfig working group
    netopenconfig@googlegroups.com";

  description
    "This module is part of a YANG model for BGP protocol

```

```

  configuration, focusing on operational data (i.e., state
  variables) related to BGP operations";

```

```

revision "2015-05-15" {
  description
    "Initial revision";
  reference "TBD";
}

```

```

// extension statements

```

```

// feature statements

```

```

// identity statements

```

```

// typedef statements

// grouping statements

grouping bgp-counters-message-types_common {
  description
    "Grouping of BGP message types, included for re-use
    across counters";

  leaf UPDATE {
    type uint64;
    description
      "Number of BGP UPDATE messages announcing, withdrawing
      or modifying paths exchanged.";
  }

  leaf NOTIFICATION {
    type uint64;
    description
      "Number of BGP NOTIFICATION messages indicating an
      error condition has occurred exchanged.";
  }
}

grouping bgp-context-pfx-path-counters_common {
  description
    "Grouping containing common counters relating to prefixes and
    paths";

  leaf total-paths {
    type uint32;

```

```

  description
    "Total number of BGP paths within the context";
}

leaf total-prefixes {
  type uint32;
  description
    "";

```

```

    }
}

grouping bgp-global_state {
  description
    "Grouping containing operational parameters relating to the
    global BGP instance";
  uses bgp-context-pfx-path-counters_common;
}

grouping bgp-global-afi-safi_state {
  description
    "Grouping containing operational parameters relating to each
    AFI-SAFI within the BGP global instance";
  uses bgp-context-pfx-path-counters_common;
}

grouping bgp-peer-group_state {
  description
    "Grouping containing operational parameters relating to a BGP
    peer group";
  uses bgp-context-pfx-path-counters_common;
}

grouping bgp-neighbor_state {
  description
    "Grouping containing operational state variables relating to a
    BGP neighbor";

  leaf session-state {
    type enumeration {
      enum IDLE {
        description
          "neighbor is down, and in the Idle state of the
          FSM";
      }
      enum CONNECT {
        description
          "neighbor is down, and the session is waiting for
          the underlying transport session to be established";
      }
    }
  }
}

```

}

```

        enum ACTIVE {
            description
                "neighbor is down, and the local system is awaiting
                a connction from the remote peer";
        }
        enum OPENSENT {
            description
                "neighbor is in the process of being established.
                The local system has sent an OPEN message";
        }
        enum OPENCONFIRM {
            description
                "neighbor is in the process of being established.
                The local system is awaiting a NOTIFICATION or
                KEEPALIVE message";
        }
        enum ESTABLISHED {
            description
                "neighbor is up - the BGP session with the peer is
                established";
        }
    }
    description
        "Operational state of the BGP peer";
}

leaf-list supported-capabilities {
    type identityref {
        base bgp-types:bgp-capability;
    }
    description
        "BGP capabilities negotiated as supported with the peer";
}
}

grouping bgp-neighbor-afi-safi_state {
    description
        "Operational state on a per-AFI-SAFI basis for a BGP
        neighbor";

    leaf active {
        type boolean;
        description
            "This value indicates whether a particular AFI-SAFI has
            been succesfully negotiated with the peer. An AFI-SAFI
            may be enabled in the current running configuration, but a
            session restart may be required in order to negotiate the new

```

```
        capability.";
    }

    uses bgp-neighbor-prefix-counters_state;
}

grouping bgp-neighbor-prefix-counters_state {
    description
        "Counters for BGP neighbor sessions";

    container prefixes {
        description "Prefix counters for the BGP session";
        leaf received {
            type uint32;
            description
                "The number of prefixes received from the neighbor";
        }

        leaf sent {
            type uint32;
            description
                "The number of prefixes advertised to the neighbor";
        }

        leaf installed {
            type uint32;
            description
                "The number of advertised prefixes installed in the
                Loc-RIB";
        }
    }
}

grouping bgp-neighbor-message-counters-sent_state {
    description
        "Counters relating to messages sent to a BGP neighbor";
    uses bgp-counters-message-types_common;
}

grouping bgp-neighbor-message-counters-received_state {
    description
        "Counters relating to the mesages received from a BGP
        neighbor";
    uses bgp-counters-message-types_common;
}
```

```
grouping bgp-neighbor-queue-counters_state {
  description
```

```
    "Counters relating to the message queues associated with the
    BGP peer";
  leaf input {
    type uint32;
    description
      "The number of messages received from the peer currently
      queued";
  }

  leaf output {
    type uint32;
    description
      "The number of messages queued to be sent to the peer";
  }
}

grouping bgp-neighbor-transport_state {
  description
    "Operational state parameters relating to the transport session
    used for the BGP session";

  leaf local-port {
    type inet:port-number;
    description
      "Local TCP port being used for the TCP session supporting
      the BGP session";
  }

  leaf remote-address {
    type inet:ip-address;
    description
      "Remote port being used by the peer for the TCP session
      supporting the BGP session";
  }

  leaf remote-port {
    type inet:port-number;
    description
      "Remote address to which the BGP session has been
```

```
        established";
    }
}

grouping bgp-neighbor-error-handling_state {
    description
        "Operational state parameters relating to enhanced error
        error handling for BGP";
}
```

```
leaf erroneous-update-messages {
    type uint32;
    description
        "The number of BGP UPDATE messages for which the
        treat-as-withdraw mechanism has been applied based
        on erroneous message contents";
}

grouping bgp-neighbor-timers_state {
    description
        "Operational state parameters relating to BGP timers associated
        with the BGP session";

    leaf uptime {
        type yang:timeticks;
        description
            "This timer determines the amount of time since the
            BGP last transitioned in or out of the Established
            state";
    }

    leaf negotiated-hold-time {
        type decimal64 {
            fraction-digits 2;
        }
        description
            "The negotiated hold-time for the BGP session";
    }
}

grouping bgp-afi-safi_state {
```

```

description
  "Operational state information relevant to all address
  families that may be carried by the BGP session";

// placeholder - options in this container are
// valid in both the global and per-neighbor
// paths

}

grouping bgp-afi-safi-graceful-restart_state {
  description
    "Operational state information relevant to graceful restart
    for BGP";

  leaf peer-restart-time {

```

```

  type uint16 {
    range 0..4096;
  }
  description
    "The period of time (advertised by the peer) that
    the peer expects a restart of a BGP session to
    take";
}

leaf peer-restarting {
  type boolean;
  description
    "This flag indicates whether the remote neighbor is currently
    in the process of restarting, and hence received routes are
    currently stale";
}

leaf local-restarting {
  type boolean;
  description
    "This flag indicates whether the local neighbor is currently
    restarting. The flag is unset after all NLRI have been
    advertised to the peer, and the End-of-RIB (EOR) marker has
    been unset";
}

```

```

leaf mode {
  type enumeration {
    enum HELPER-ONLY {
      description
        "The local router is operating in helper-only mode, and
        hence will not retain forwarding state during a local
        session restart, but will do so during a restart of the
        remote peer";
    }
    enum BILATERAL {
      description
        "The local router is operating in both helper mode, and
        hence retains forwarding state during a remote restart,
        and also maintains forwarding state during local session
        restart";
    }
    enum REMOTE-HELPER {
      description
        "The local system is able to retain routes during restart
        but the remote system is only able to act as a helper";
    }
  }
}

```

```

  description
    "Ths leaf indicates the mode of operation of BGP graceful
    restart with the peer";
}
}

grouping bgp-neighbor-afi-safi-graceful-restart_state {
  description
    "Operational state variables relating to the graceful-restart
    mechanism on a per-AFI-SAFI basis";

  leaf received {
    type boolean;
    description
      "This leaf indicates whether the neighbor advertised the
      ability to support graceful-restart for this AFI-SAFI";
  }
}

```

```
leaf advertised {
  type boolean;
  description
    "This leaf indicates whether the ability to support
    graceful-restart has been advertised to the peer";
}
}

}

<CODE ENDS>
```

6. References

6.1. Normative references

- [RFC6020] Bjorklund, M., "YANG - A Data Modeling Language for the Network Configuration Protocol (NETCONF)", [RFC 6020](#), October 2010.
- [RFC6241] Enns, R., Bjorklund, M., Schoenwaelder, J., and A. Bierman, "Network Configuration Protocol (NETCONF)", [RFC 6241](#), June 2011.
- [RFC4271] Rekhter, Y., Li, T., and S. Hares, "A Border Gateway Protocol 4 (BGP-4)", [RFC 4271](#), January 2006.

Shaikh, et al.

Expires December 16, 2015

[Page 71]

Internet-Draft

BGP Model

June 2015

- [RFC1997] Chandrasekeran, R., Traina, P., and T. Li, "BGP Communities Attribute", [RFC 1997](#), August 1996.
- [RFC4456] Bates, T., Chen, E., and R. Chandra, "BGP Route Reflection: An Alternative to Full Mesh Internal BGP (IBGP)", [RFC 4456](#), April 2006.
- [RFC3065] Traina, P., McPherson, D., and J. Scudder, "Autonomous System Confederations for BGP", [RFC 3065](#), February 2001.
- [RFC2439] Villamizar, C., Chandra, R., and R. Govindan, "BGP Route

Flap Damping", [RFC 2439](#), November 1998.

- [RFC4724] Sangli, S., Chen, E., Fernando, R., Scudder, J., and Y. Rekhter, "Graceful Restart Mechanism for BGP", [RFC 4724](#), January 2007.
- [RFC6811] Mohapatra, P., Scudder, J., Ward, D., Bush, R., and R. Austein, "BGP Prefix Origin Validation", [RFC 6811](#), January 2013.
- [RFC4760] Bates, T., Chandra, R., Katz, D., and Y. Rekhter, "Multiprotocol Extensions for BGP-4", [RFC 4760](#), January 2007.
- [RFC6991] Schoenwaelder, J., "Common YANG Data Types", [RFC 6991](#), July 2013.
- [RFC3688] Mealling, M., "The IETF XML Registry", [BCP 81](#), [RFC 3688](#), January 2004.

[6.2.](#) Informative references

- [I-D.openconfig-netmod-opstate]
Shakir, R., Shaikh, A., and M. Hines, "Consistent Modeling of Operational State Data in YANG", [draft-openconfig-netmod-opstate-00](#) (work in progress), March 2015.
- [I-D.shaikh-rtgwg-policy-model]
Shaikh, A., Shakir, R., D'Souza, K., and C. Chase, "Routing Policy Configuration Model for Service Provider Networks", [draft-shaikh-rtgwg-policy-model-00](#) (work in progress), January 2015.

[Appendix A.](#) Acknowledgements

The authors are grateful for valuable contributions to this document and the associated models from: Ebben Aires, Pavan Beeram, Chris

Chase, Ed Crabbe, Luyuan Fang, Bill Fenner, Akshay Gattani, Josh George, Vijay Gill, Jeff Haas, Dhanendra Jain, Ina Minei, Carl Moberg, Ashok Narayanan, Einar Nilsen-Nygaard, Adam Simpson, Puneet Sood, Jason Sterne, Jim Uttaro, and Gunter Vandevælde.

[Appendix B](#). Change summary

[B.1](#). Changes between revisions -01 and -02

The -02 revision generally does not affect the structure of the model, but there are a number of changes that improve clarity, or simplify mappings to implementations.

- o Reorganized modules to move BGP-specific types, including policy-related types, to the `bgp-types` module.
- o Added ability to configure route selection options at the global level. Removed route selection options from per-neighbor AFI-SAFI since it is not widely implemented.
- o Removed a number of presence containers (e.g., in AFI-SAFI, `graceful-restart`, and `multipath`). Presence has been replaced with an explicit 'enabled' leaf to simplify semantics of inheritance and override in other parts of the BGP hierarchy.
- o Fixed inconsistencies with `use-multiple-paths` config. Added 'enabled' leaves with default false.
- o Updated top level list key to be a leafref in most lists for consistency with the operational state modeling approach outlined in [[I-D.openconfig-netmod-opstate](#)].
- o Some minor renaming / restructuring of routing policy `defined-sets` and `apply-policy` container.
- o Added ability to increment/decrement MED value in BGP policy statement actions.
- o Changed `local-address` leaf to be a union which can specify either an IP address, or be a reference to an interface.
- o Changed `ebgp-multihop` to add 'enabled' leaf and TTL behavior.

- o Changed BGP well-known communities from an enumeration to an identity. Also made consistent with IANA-defined standard well-known communities.
- o Remove enumeration values from BGP origin type given the disagreement in [RFC 4271](#) and [RFC 4273](#).
- o Added an additional match-options enumerated type for sets that only support ANY | INVERT, but not ALL behavior.
- o Modified prefix-sets to use inet:ip-prefix type and removed range checking on masklength-range (also added 'exact' specifier for masklength range).
- o Removed send-update-delay timer leaf. Desired behavior is reflected by minimum-advertisement-interval, i.e., MRAI.
- o Changed allow-own-as leaf to allow specification of a number of occurrences -- some implementations only support 0 or 1, i.e., equivalent of a boolean but several others support multiple occurrences.

[B.2.](#) Changes between revisions -00 and -01

The -01 revision reflects a number of changes, many based on feedback from implementors of the model on various routing platforms.

- o Refactored model to explicitly provide 'config' and 'state' containers at each leaf node to enable consistent and predictable access to operational state data corresponding to configuration data. This is based on the model design in [\[I-D.openconfig-netmod-opstate\]](#).
- o Refactored multiprotocol module with explicit set of supported AFI-SAFI combinations (using YANG identities) in a flattened list. Focus was on common config with more AFI-SAFI specific configuration forthcoming in future revisions.
- o Refactored BGP policy module to work with a new general routing policy model [\[I-D.shaikh-rtgwg-policy-model\]](#) by augmenting it with BGP-specific policy options (conditions, actions, and defined sets).
- o Added enclosing containers to lists (e.g., neighbors, peer-groups, and AFI-SAFI)

Internet-Draft

BGP Model

June 2015

- o Removed neighbor configuration from the peer-group hierarchy. Neighbor configuration now has a peer-group leaf which references the peer group to which the neighbor belongs.
- o Several new configuration items added to base bgp module, including adding some configuration items to the global hierarchy level.

Authors' Addresses

Anees Shaikh (editor)
Google
1600 Amphitheatre Pkwy
Mountain View, CA 94043
US

Email: aashaikh@google.com

Rob Shakir (editor)
BT
pp. C3L, BT Centre
81, Newgate Street
London EC1A 7AJ
UK

Email: rob.shakir@bt.com
URI: <http://www.bt.com/>

Keyur Patel (editor)
Cisco
170 W. Tasman Drive
San Jose, CA 95134
USA

Email: keyupate@cisco.com

Susan Hares (editor)

Huawei
7453 Hickory Hill
Saline, MI 48176
USA

Email: shares@ndzh.com

Shaikh, et al.

Expires December 16, 2015

[Page 75]

Internet-Draft

BGP Model

June 2015

Kevin D'Souza
AT&T
200 S. Laurel Ave
Middletown, NJ
US

Email: kd6913@att.com

Deepak Bansal
Microsoft
205 108th Ave. NE, Suite 400
Bellevue, WA
US

Email: dbansal@microsoft.com

Alexander Clemm
Cisco
170 W. Tasman Drive
San Jose, CA 95134
USA

Email: alex@cisco.com

Aleksandr Zhdankin
Cisco
170 W. Tasman Drive
San Jose, CA 95134
USA

Email: azhdanki@cisco.com

Mahesh Jethanandani
Ciena
1741 Technology Drive
San Jose, CA 95110
USA

Email: mjethanandani@gmail.com

Shaikh, et al.

Expires December 16, 2015

[Page 76]

Internet-Draft

BGP Model

June 2015

Xyfeng Liu
Ericsson
1595 Spring Hill Road, Suite 500
Vienna, VA 22182
USA

Email: xufeng.liu@ericsson.com

