

Network Working Group
Internet-Draft
Intended status: Experimental
Expires: October 3, 2008

S. Harhalakis
TEI of Thessaloniki
April 2008

Timezone Information in HTTP
draft-sharhalakis-httpz-04.txt

Status of this Memo

By submitting this Internet-Draft, each author represents that any applicable patent or other IPR claims of which he or she is aware have been or will be disclosed, and any of which he or she becomes aware will be disclosed, in accordance with [Section 6 of BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF), its areas, and its working groups. Note that other groups may also distribute working documents as Internet-Drafts.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

The list of current Internet-Drafts can be accessed at <http://www.ietf.org/ietf/1id-abstracts.txt>.

The list of Internet-Draft Shadow Directories can be accessed at <http://www.ietf.org/shadow.html>.

This Internet-Draft will expire on October 3, 2008.

Abstract

This document defines a HTTP header for clients to provide timezone information to web servers. An ABNF description of the corresponding header is provided.

Discussion

Discussion about this document takes place in [http-wg mailing list \(ietf-http-wg@w3.org\)](mailto:http-wg@ietf.org). Please CC v13@v13.gr too.

Table of Contents

1.	Introduction	4
1.1.	Purpose	4
1.2.	Requirements	4
1.3.	Terminology	4
1.4.	Considerations	5
2.	Definition	7
2.1.	Client support	7
2.2.	Server support	7
2.3.	Proxy considerations	8
3.	Security Considerations	9
3.1.	Client side	9
3.2.	Server side	9
4.	IANA Considerations	10
5.	Acknowledgements	11
6.	References	12
6.1.	Normative	12
6.2.	Informative	12
Appendix A.	Examples	13
	Author's Address	14
	Intellectual Property and Copyright Statements	15

1. Introduction

1.1. Purpose

Many web based applications could benefit from knowing the timezone of their visiting clients. Most of the dynamic content provider applications depend on user accounts to display time and date in the client's native timezone. Even this is not always adequate since people may travel across timezone boundaries and they currently need to update their web accounts to reflect their actual timezone information. Furthermore, this is also the case for all HTTP-like or HTTP based protocols that make use of timestamps.

This document addresses this need by describing a header to be used by HTTP [[RFC2616](#)] so that interested clients may provide their current timezone information to web servers and thus to web based applications.

1.2. Requirements

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [[RFC2119](#)].

An implementation is not compliant if it fails to satisfy one or more of the MUST or REQUIRED level requirements. An implementation that satisfies all the MUST or REQUIRED level and all the SHOULD level requirements is said to be "unconditionally compliant"; one that satisfies all the MUST level requirements but not all the SHOULD level requirements is said to be "conditionally compliant".

1.3. Terminology

This document uses the following terms:

HTTP client

Every client of the HTTP protocol. Commonly referred to as a web browser.

Timezone string

A timezone string as described in this document.

HTTP header

An HTTP header as described in [[RFC2616](#)].

The HTTP header specification of this document is presented in the augmented Backus-Naur Form that is described in [[RFC2616](#)].

1.4. Considerations

Because of the variety of systems on the Internet and the non-technical nature of timezone, there is no simple method for a client to provide timezone information to HTTP servers. During the writing of this document the following were considered:

- o Simplicity is a must. The specification needs to be as simple as possible or allow for partial handling in a simple manner.
- o There is a variety of timezone styles. Some countries don't experience Daylight Saving Time (DST). Other countries have very unstable DST.
- o Politics affect DST. This makes it a moving target.
- o DST settings may change from year to year.
- o Complete past and future timezone information cannot be described using a simple string.
- o End user systems may have an invalid timezone configured.
- o There are systems without timezone information.
- o Not all systems have a time source.

This document tries to provide adequate data for applications that can take advantage of the Timezone information to fulfill their needs. There are different levels of requirements that applications may have and HTTP clients may be able to satisfy. Thus this document introduces a way for HTTP clients to provide:

- o The current client time.
- o The current time offset.
- o The current year's timezone information.
- o Complete timezone information.

depending on their abilities.

Simple server side applications may just use the current time offset and hope that it is correctly set. More advanced applications (like calendars) need to know when a DST change will occur to correctly represent future or past times. Even more advanced applications may need to know the exact client timezone which can only be described

using a reference to a timezone database entry. Finally, applications may choose to use the client's current time as reference time and optionally ignore client timezone information.

Paragraph 4.4 of [[RFC3339](#)] "Unqualified Local Time" considers systems with invalid timezone information as inappropriate for Internet communications.

2. Definition

2.1. Client support

HTTP clients MAY provide local timezone information to visiting web sites. This information is sent using the client-timezone HTTP header:

```
client-timezone = "Timezone" ":" tzdescr

tzdescr          = rfctime [ ";" posixtz [ ";" tznames ] ]

rfctime          = <local time>

posixtz          = <a POSIX 1003.1 timezone string>

tznames          = tzname *( "," tzname )

tzname           = <a timezone string from a timezone database>
```

Where:

rfctime A local time string as specified in [[RFC3339](#)]. It includes the current time offset.

posixtz A POSIX 1003.1 timezone string as specified in [[POSIXTZ](#)].

tzname A timezone name. Many systems use a timezone name from a timezone database. This is one such string. More than one such strings may be provided. All of them MUST identify the same timezone.

HTTP clients SHOULD provide all three parts of the header unless they aren't able to do so or they are configured not to send timezone information.

Clients that don't have a clock source MUST use zeroes for all digits of the datetime string except from the offset. "Z" MUST be used when the offset is also unavailable.

2.2. Server support

Compliant servers MAY validate the format of the provided information. Timezone strings that are not in a valid format MAY not be accepted. Validation checks MUST NOT be performed on the content of the Timezone string by servers. Only the format of the string may be checked. This way outdated servers will not filter out proper

information.

2.3. Proxy considerations

HTTP proxy servers MUST NOT alter this information.

Server side scripts that produce customized results based on the timezone information MUST return an appropriate "Vary" header as specified in paragraph 14.44 of [[RFC2616](#)].

3. Security Considerations

3.1. Client side

Timezone information may consist personal information regarding the location of a person. HTTP clients **MUST NOT** provide this information without letting the user prevent it. Clients must either ask users or provide an option for enabling/disabling this feature. The later is **RECOMMENDED**.

In most cases, Timezone information will not disclose more personal information than an IP address. HTTP clients **MAY** default in enabling this to improve user experience.

3.2. Server side

Web based applications **MUST** treat this information as user input that may be invalid or malicious.

4. IANA Considerations

This specification requires registration of a Message Header Field for HTTP [[RFC3864](#)].

Header field: Timezone

Applicable protocol: HTTP

Status: Experimental

Author/change controller:

IETF (iesg@ietf.org)

Internet Engineering Task Force

Specification document:

[this document]

5. Acknowledgements

Timezone information in HTTP was also proposed by David Robinson in an email at HTTP Working Group back in 1995 but the replies he got were negative. It was believed that timezone information should be handled by CGI scripts and not by the Hypertext Transfer Protocol. The discussion can be found at http-wg mailing list archives: <<http://www.hpl.hp.com/personal/ange/archives/archives-95/http-wg-archive/0521.html>>.

This document was properly formed thanks to the remarks of Julian Reschke.

6. References

6.1. Normative

- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), March 1997.
- [RFC2616] Fielding, R., Gettys, J., Mogul, J., Frystyk, H., Masinter, L., Leach, P., and T. Berners-Lee, "Hypertext Transfer Protocol -- HTTP/1.1", [RFC 2616](#), June 1999.
- [RFC3339] Klyne, G., Ed. and C. Newman, "Date and Time on the Internet: Timestamps", [RFC 3339](#), July 2002.
- [RFC3864] Klyne, G., Nottingham, M., and J. Mogul, "Registration Procedures for Message Header Fields", [BCP 90](#), [RFC 3864](#), September 2004.
- [POSIXTZ] IEEE, The Open Group, "IEEE Std 1003.1", 2004.

6.2. Informative

- [I-D.rfc-editor-rfc2223bis]
Reynolds, J. and R. Braden, "Instructions to Request for Comments (RFC) Authors", [draft-rfc-editor-rfc2223bis-08](#) (work in progress), July 2004.

[Appendix A](#). Examples

A complete timezone information header:

Current time is 12:00, Jul 30, 1977. time offset is +2 hours. The full timezone string is EET2EEST3,M3.2.0/02:00,M11.1.0/02:00. The timezone database identifier string is Europe/Athens.

```
Timezone: 1977-07-30T12:00+0200;  
         EET2EEST3,M3.2.0/02:00,M11.1.0/02:00;  
         Europe/Athens
```

A partial one:

GMT/UTC timezone is noted as Z(ulu).

```
Timezone: 2007-06-12T23:48Z
```

A header from a clock-less client without current offset information:

```
Timezone: 0000-00-00T00:00Z;  
         EET2EEST3,M3.2.0/02:00,M11.1.0/02:00;  
         Europe/Athens
```


Author's Address

Stefanos Harhalakis
Technological Educational Institute of Thessaloniki
Department of Information Technology
Thessaloniki, Greece
GR

Email: v13@v13.gr, v13@it.teithe.gr

Full Copyright Statement

Copyright (C) The IETF Trust (2008).

This document is subject to the rights, licenses and restrictions contained in [BCP 78](#), and except as set forth therein, the authors retain all their rights.

This document and the information contained herein are provided on an "AS IS" basis and THE CONTRIBUTOR, THE ORGANIZATION HE/SHE REPRESENTS OR IS SPONSORED BY (IF ANY), THE INTERNET SOCIETY, THE IETF TRUST AND THE INTERNET ENGINEERING TASK FORCE DISCLAIM ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY WARRANTY THAT THE USE OF THE INFORMATION HEREIN WILL NOT INFRINGE ANY RIGHTS OR ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

Intellectual Property

The IETF takes no position regarding the validity or scope of any Intellectual Property Rights or other rights that might be claimed to pertain to the implementation or use of the technology described in this document or the extent to which any license under such rights might or might not be available; nor does it represent that it has made any independent effort to identify any such rights. Information on the procedures with respect to rights in RFC documents can be found in [BCP 78](#) and [BCP 79](#).

Copies of IPR disclosures made to the IETF Secretariat and any assurances of licenses to be made available, or the result of an attempt made to obtain a general license or permission for the use of such proprietary rights by implementers or users of this specification can be obtained from the IETF on-line IPR repository at <http://www.ietf.org/ipr>.

The IETF invites any interested party to bring to its attention any copyrights, patents or patent applications, or other proprietary rights that may cover technology that may be required to implement this standard. Please address the information to the IETF at ietf-ipr@ietf.org.

Acknowledgment

This document was produced using xml2rfc v1.33 (of <http://xml.resource.org/>) from a source in [RFC-2629](#) XML format.

