

Network Working Group  
Internet-Draft  
Expires: January 14, 2013

M. Shore  
No Mountain Software  
C. Pignataro  
Cisco Systems, Inc.  
July 13, 2012

An Acceptable Use Policy for New ICMP Types and Codes  
draft-shore-icmp-aup-01

## Abstract

Some recent proposals to add new Internet Control Message Protocol (ICMP) types and/or codes have highlighted a need to describe policies for when adding new features to ICMP is desirable and when it is not. In this document we provide a basic description of ICMP's role in the IP stack and some guidelines for the future.

## Status of this Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <http://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on January 14, 2013.

## Copyright Notice

Copyright (c) 2012 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as

Internet-Draft

ICMP AUP

July 2012

described in the Simplified BSD License.

## Table of Contents

<a href="#">1.</a>	Introduction . . . . .	<a href="#">3</a>
<a href="#">2.</a>	Acceptable use policy . . . . .	<a href="#">4</a>
<a href="#">2.1.</a>	Classification of existing message types . . . . .	<a href="#">4</a>
<a href="#">3.</a>	ICMP's role in the internet . . . . .	<a href="#">8</a>
<a href="#">4.</a>	Management vs control . . . . .	<a href="#">9</a>
<a href="#">5.</a>	Security considerations . . . . .	<a href="#">11</a>
<a href="#">6.</a>	IANA considerations . . . . .	<a href="#">12</a>
<a href="#">7.</a>	Acknowledgments . . . . .	<a href="#">13</a>
<a href="#">8.</a>	Informative references . . . . .	<a href="#">14</a>
	Authors' Addresses . . . . .	<a href="#">15</a>

---

Internet-Draft

ICMP AUP

July 2012

## 1. Introduction

There have been some recent proposals to add new message types and codes to ICMP [[RFC792](#)]. Not all of these proposal are consistent with the design and intent of ICMP, and so we attempt to lay out a description of when (and when not) to move functionality into ICMP.

This document is the result of discussions within the IETF Operations area "ICMP Society," and concerns expressed by the OPS area leadership.

## [2.](#) Acceptable use policy

In this document we describe a proposed acceptable use policy for new ICMP message types and codes, and provide some background behind the proposed policy.

In summary, we propose that any future message types added to ICMP should be limited to two broad categories:

1. to inform a datagram's originator that a forwarding plane anomaly has been encountered downstream. The datagram originator must be able to determine whether or not the datagram was discarded by examining the ICMP message
2. to discover on-link routers and hosts

### [2.1.](#) Classification of existing message types

This section provides a rough breakdown of existing message types according to the taxonomy described in [Section 2](#).

IPv4 forwarding plane anomaly reporting

- 3: Destination unreachable
- 4: Source quench (deprecated)

- 5: Redirect
- 6: Alternate host address
- 11 Time exceeded
- 12 Parameter problem
- 31: Datagram conversion error
- 32: Mobile host redirect
- 41: ICMP messages utilized by experimental mobility protocols,  
such as Seamoby
- IPv4 router or host discovery

- 0: Echo reply
- 8: Echo
- 9: Router advertisement
- 10: Router solicitation
- 13: Timestamp
- 14: Timestamp reply
- 15: Information request
- 16: Information reply
- 17: Address mask request
- 18: Address mask reply
- 30: Traceroute

- 33: IPv6 Where-Are-You
  - 34: IPv6 I-Am-Here
  - 35: Mobile registration request
  - 36: Mobile registration reply
  - 37: Domain name request
  - 38: Domain name reply
  - 39: SKIP
  - 40: Photuris
  - 41: ICMP messages utilized by experimental mobility protocols,  
such as Seamoby
- IPv6 forwarding plane anomaly reporting

- 1: Destination unreachable
  - 2: Packet too big
  - 3: Time exceeded
  - 4: Parameter problem
  - 137: Redirect message
  - 150: ICMP messages utilized by experimental mobility protocols,  
such as Seamoby
- IPv6 router or host discovery

- 128: Echo request
- 129: Echo reply
- 130: Multicast listener query
- 131: Multicast listener report
- 132: Multicast listener done
- 133: Router solicitation
- 134: Router advertisement
- 135: Neighbor solicitation
- 136: Neighbor advertisement
- 138: Router renumbering
- 139: ICMP node information query
- 140: ICMP node information response
- 141: Inverse neighbor discovery solicitation message
- 142: Inverse neighbor discovery advertisement message

- 143: Version 2 multicast listener report
- 144: Home agent address discovery request message
- 145: Home agent address discovery reply message
- 146: Mobile prefix solicitation

- 147: Mobile prefix advertisement
- 148: Certification path solicitation message
- 149: Certification path advertisement message
- 150: ICMP messages utilized by experimental mobility protocols,  
such as Seamoby
- 151: Multicast router advertisement
- 152: Multicast router solicitation
- 153: Multicast router termination
- 154: FMIPv6 messages
- 155: RPL control message

### [3.](#) ICMP's role in the internet



ICMP was originally intended to be a mechanism for routers to report error conditions back to hosts [[RFC792](#)]. The word "control" in the protocol name did not describe ICMP's function (i.e. it did not "control" the internet), but rather that it was used to communicate about the control functions in the internet. For example, even though ICMP included a redirect message type, it was and is not used as a routing protocol.

Most likely because of the presence of the word "control" in the protocol name, ICMP is often understood to be a control protocol, borrowing some terminology from circuit networks and the PSTN. That is probably not correct - it might be more correct to describe it as being closer to a management plane protocol, given the data plane/ control plane/ management plane taxonomy often used in describing telephony protocols. However, layering in IP networks is not very clean and there's often some intermingling of function that can tend to lead to confusion about where to place new functions.

In following sections we provide some background on the differences between control and management traffic.

#### 4. Management vs control

In this section we attempt to draw a distinction between management and control planes, acknowledging in advance that this may serve to muddle the differences even further. Ultimately the difference may not matter that much for the purpose of creating a policy for adding new types to ICMP, but because that terminology has become ubiquitous, even in IETF discussions, and because it has come up in prior discussions of ICMP policies, it seems worthwhile to take a few paragraphs to describe what they are and what they are not.

The terms "management plane" and "control plane" came into use to describe one aspect of layering in telecommunications networks. It is particularly important, in the context of this discussion, to understand that "control plane" in telecomm networks almost always refers to 'signaling,' or call control and network control information. This includes "call" establishment and teardown, route establishment and teardown, requesting QoS or other parameters, and so on.

"Management," on the other hand, tends to fall under the rubric "OAM," or "Operations, Administration, and Management." typical functions include fault management and performance monitoring (Service Level Agreement [SLA] compliance), discovery, etc.

The correct answer to the question of where ICMP fits into the management/control/data taxonomy is that it doesn't, at least not neatly. While some of the message types are unambiguously management message (ICMP type 3, or "unreachable" messages), others are less clearly identifiable. For example, the "redirect" (ICMP type 5) message can be construed to contain control (in this case, routing) information, even though it is in some very real sense an error message.

At this time,

- o there are many, many other protocols that can be (and are) used for control traffic, whether they're routing protocols, telephony signaling protocols, QoS protocols, middlebox protocols, AAA protocols, etc.
- o the transport characteristics needed by control traffic can be incompatible with the ICMP protocol standard -- for example, they may require reliable delivery, very large payloads, or have security requirements that cannot be met.

and because of this we propose that any future message types added to ICMP must conform to the policy proposed in [Section 2](#). ICMP should

not be used as a routing or network management protocol.

## [5.](#) Security considerations

This document attempts to describe a high-level policy for adding ICMP types and codes. While special attention must be paid to the security implications of any particular new ICMP type or code, specific security considerations are outside the scope of this paper.

## [6.](#) IANA considerations

There are no actions required by IANA.

## [7.](#) Acknowledgments

This document was originally proposed by, and received substantial review and suggestions from, Ron Bonica.

## 8. Informative references

- [RFC792] Postel, J., "INTERNET CONTROL MESSAGE PROTOCOL", [RFC 792](#), September 1981.

Shore & Pignataro

Expires January 14, 2013

[Page 14]

---

Internet-Draft

ICMP AUP

July 2012

Authors' Addresses

Melinda Shore  
No Mountain Software



PO Box 16271  
Two Rivers, AK 99716  
US

Phone: +1 907 322 9522  
Email: melinda.shore@nomountain.net

Carlos Pignataro  
Cisco Systems, Inc.  
7200-12 Kit Creek Road  
Research Triangle Park, NC 27709  
US

Email: cpignata@cisc.com