

**A YANG Module for uCPE management.
draft-shytyi-opsawg-vysm-00**

Abstract

This document provides a YANG data model for uCPE management (VYSM) and definition of the uCPE equipment. The YANG Service Model serves as a base framework for managing an universal Customer-Premises Equipment (uCPE) subsystem. The model can be used by a Network Service Orchestrator.

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <https://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on March 24, 2020.

Copyright Notice

Copyright (c) 2019 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<https://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

Table of Contents

1. Introduction	2
2. Terminology	2
3. Universal CPE	2
4. YANG Service Model for uCPE management	4
5. uCPE YANG Service Model tree diagram overview	5
6. Specification of the VNF YANG Service Model	6
7. XML example	10
8. Security Considerations	13
9. IANA Considerations	13
10. Acknowledgements	13
11. Normative References	13
Author's Address	14

[1. Introduction](#)

Network Function Virtualization is a technology that allows to virtualize the network services running on dedicated hardware. This technology became a base for universal Customer-Premises Equipment (uCPE). This document defines the uCPE as hardware with x86 capabilities that has a hypervisor. In other words, uCPE is a host that may run multiple Virtual Machines with guest OSs, where each Guest OS may represent a Physical Network Function. This document presents the YANG Service Model (VYSM) to manage from an Orchestrator the infrastructure inside the uCPE.

[2. Terminology](#)

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [RFC 2119](#) [[RFC2119](#)].

Link - is an entity that enables link layer communication of nodes.

Port - node connector to the link.

NE - Network Element.

NSYM - Network Service Yang Module.

VYSM - VNF YANG Service Model.

[3. Universal CPE](#)


Firstly, this document defines the platform that is controlled with VYSM - universal CPE (uCPE). The uCPE as hardware with x86 capabilities that is generally running Linux distribution with

Shytyi

Expires March 24, 2020

[Page 2]

additinal virtualisation layer. Virtualization layer provides virtual compute, virtual storage and virtual network resources. Each VNF running in the uCPE requires the amount of virtual resources (for example: 4 vCPUs, 4GB RAM, 40GB storege, 4 vPorts). VNFs MAY be interconnected between each other and physical ports via Virtual Networks. Topology construction and VM lifecycle management is allowed via high level interface (Configuration can be done in the same transaction). The figure below presents the uCPE architecture.



The next elements can be managed in the uCPE:

- o Virtual Network Funcitons:
 - * Number of assigned vCPUs.
 - * Size of allocated RAM.
 - * VNF day0 config (bootstrap).
 - * vLinks that are attached to the VNF.
- o Virtual Switches:
 - * vLinks that are attached to the vSW.
- o Virtual Links(vLinks).
- o Physical Ports of the uCPE.

The VNF in the uCPE could be a vRouter or vFirewall or an SD-WAN that is not a default part of virtual network resources of the uCPE. We can have multiple VNFs instantiated in the uCPE. With support of links and switches, VNFs may participate a service chains. Example of service chains:

Shytyi

Expires March 24, 2020

[Page 3]

- o vSW(WAN)-l1-vRouter(vcPE)-l2-vSW(Service)-l3-vFirewall-l4-vSW(LAN).
- o vSW(WAN)-l1-SDWAN-l2-vSW(Service)-l3-vFirewall-l4-vSW(LAN).

4. YANG Service Model for uCPE management

Secondly, this document defines and classifies the VYSM as Network Service YANG Module(NSYM) layer component [RFC 8199](#) [[RFC8199](#)]. Thus it inherits the characteristics of the NSYM Layer. VYSM is a modeled representation of the specific service requirements. It provides abstraction of services configuration and operations that MAY be implemented in Network Elements (NEs). Thus VYSM does not describe all configuration to be performed on the devices, but provides the configuration that is required for the "Network Service to Network Element(s)" decomposition process [RFC 8199](#) [[RFC8199](#)]. Example of the decomposition is presented in the figure below.

The Network Service YANG module exposes the configuration commands via the Northbound interfaces of the orchestrator. Therefore the set of the commands modeled in the VYSM can be inputed via Northbound interfaces(for example CLI). In the example the command "vm VNF1" is passed via Northbound interface to the orchestrator. It defines the virtual machine name. Further the same configuration MAY be transformed to the one or multiple Network Element payloads (for example xml for NETCONF) that carry an equivalent of commands such as "nf nf-name VNF1"

Shytyi

Expires March 24, 2020

[Page 4]

```

+---+---+---+---+---+---+
|   |
| config t   |
|      vm VNF1 |
+---+---+---+---+---+---+
# 
#
+++++-----+-----+-----+-----+-----+-----+-----+-----+-----+
:
:
+---+-----+-----+-----+-----+-----+-----+-----+-----+-----+
| Network Service YANG Module | 
+---+-----+-----+-----+-----+-----+-----+-----+-----+-----+
# 
#####
#                                     orchestrator
#           #
'-----'-----'-----'
'Module1  ' ' Module 2  ' ' Module3  ' <= Network Element
'-----'-----'-----'           YANG Modules
#           #           #
#           #           #####           #
#####           #####           #           #
#           #           #           #           #
#####
#           #           #
Network # element 1     Network # element 2     Network # element3
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+
| domains domain VNF1| |tenants tenant name VNF1| |nf nf-name VNF1|
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+

```

5. uCPE YANG Service Model tree diagram overview

This section provides an overview of the Service YANG Model (VSYM) that MAY be made with "pyang" utility. The figure below presents the tree diagram of VYSM.

Shytyi

Expires March 24, 2020

[Page 5]

```

module: ietf-ucpe
  +-rw ucpe* [name]
    +-rw name          string
    +-rw links* [link]
      | +-rw link      string
    +-rw phyInterfaces* [interface]
      | +-rw interface  string
      | +-rw ports* [port]
      |   +-rw port     string
      |   +-rw link?    -> ../../links/link
    +-rw switches* [switch]
      | +-rw switch    string
      | +-rw ports* [port]
      |   +-rw port     string
      |   +-rw name?    string
      |   +-rw link?    -> ../../links/link
    +-rw vms* [vm]
      +-rw vm           string
      +-rw ports* [port]
        | +-rw port     string
        | +-rw name?    string
        | +-rw link?    -> ../../links/link
      +-rw ram?         uint64
      +-rw cpu?         uint64
      +-rw storages* [id]
        | +-rw id       string
        | +-rw location? string
      +-rw day0-config
        +-rw location?   string
        +-rw day0-var-path? string
        +-rw variable* [name]
          +-rw name     string
          +-rw value?   string

```

6. Specification of the VNF YANG Service Model

This section presents the specification of the VYSM.

```

<CODE BEGINS> file "ietf-ucpe@2019-09-16.yang"
module ietf-ucpe {
  namespace "urn:ietf:params:xml:ns:yang:ietf-ucpe";
  prefix ietf-ucpe;
  organization
  "SFR";
  contact
  "Dmytro Shytyi"

```

Shytyi

Expires March 24, 2020

[Page 6]

```
        EMail:ietf.dmytro@shytyi.net";
description
  "This YANG Service Model for uCPE management .";
revision 2018-07-01 {
  description
  "Initial revision.";
  reference
"draft-shytyi-netmod-vysm-01";
}
revision 2019-09-16{
  description
  "Added Oday config for VNFs.
  Yang model modified according
  to the received comments.";
  reference
"draft-shytyi-opsawg-vysm-00";
}

list ucpe{
  key name;
  leaf name {
    type string;
    description "ID of uCPE where
      a service is instantiated";
  }
list links{
  key link;
  leaf link{
    type string;
    description "Name of the virtual link from the pool
      of the links";
  }
  description "Pool of the virtual links that connect VMs and
    Interfaces";
}
list phyInterfaces{
  key interface;
  leaf interface{
    type string;
    description "Name of physical interface";
  }
list ports{
  key port;
  leaf port{
    type string;
    description "Name of the connector";
  }
  leaf link{
```

Shytyi

Expires March 24, 2020

[Page 7]

```
        type leafref{
            path "../../links/link";
        }
        description "Link that is connected to
        the port via connector";
    }
    description "Set of the connectors the
    physical interface has";
}
description "Set of physical interfaces";
}

list switches{
    key switch;
    leaf switch{
        type string;
        description "Name of the forwarding domain";
    }
    list ports{
        key port;
        leaf port{
            type string;
            description "Name of the connector";
        }
        leaf name{
            type string;
            description "Name of the
            subconnector";
        }
        leaf link{
            type leafref{
                path "../../links/link";
            }
            description "Link that is connected to the
            switch via port";
        }
        description "Set of the connectors the
        forwarding domain has";
    }
    description "Set of the forwarding domains";
}

list vms{
    key vm;
    leaf vm{
        type string;
        description "ID of the Virtual Machine";
    }
}
```

Shytyi

Expires March 24, 2020

[Page 8]

```
list ports{
    key port;
    leaf port{
        type string;
        description "Name of the connector";
    }
    leaf name{
        type string;
        description "Name of
        the subconnector";
    }
    leaf link{
        type leafref{
            path "../../links/link";
        }
        description "Link that connects the
        VM with a switch or Interface
        via connector";
    }
    description "Set of Virtual Machine connectors";
}

leaf ram{
    type uint64;
    description "Size of RAM to allocate for
    the Guest OS";
}
leaf cpu{
    type uint64;
    description "Number of vCPUs to
    allocate for the Guest OS";
}
list storages{
    key id;
    leaf id{
        type string;
        description "Number of
        vDisk attached to the VM";
    }
    leaf location{
        type string;
        description "External location where
        the image (ex.qcow2) is saved.";
    }
    description "Virtual storage/vDisk
    attached to the Virtual Machine";
}
container day0-config{
```

Shytyi

Expires March 24, 2020

[Page 9]

```
leaf location{
    type string;
    description "0day configuration location";
}
leaf day0-var-path{
    type string;
    description "path of the file
    that contains the 0day variables";
}
list variable{
    key name;
    leaf name{
        type string;
        description "variable name";
    }
    leaf value{
        type string;
        description "variable value";
    }
    description "list of variables";
}
description "0day configuration:init config";

}
description "Set of the Virtual Machines configured
on the universal Customer-Premises Equipment";
}
description "This is an uCPE management service";
}
<CODE ENDS>
```


[7. XML example](#)

The XML example below presents the configuration of the next service in the uCPE, where: vSW(LAN), vSW(WAN), vSW(Service) - virtual switches; l1,l2,l3,l4 - virtual links; VMs represent PNFs (Physical Network Functions) that could be bootstrapped with 0day config/ license.

Shytyi

Expires March 24, 2020

[Page 10]



```
<ucpe xmlns="urn:ietf:params:xml:ns:yang:ietf-ucpe">
  <name>ucpe1</name>
  <links>
    <link>l1</link>
  </links>
  <links>
    <link>l2</link>
  </links>
  <links>
    <link>l3</link>
  </links>
  <links>
    <link>l4</link>
  </links>
  <switches>
    <switch>lan</switch>
    <ports>
      <port>10</port>
      <name>l2p10</name>
      <link>l2</link>
    </ports>
  </switches>
  <switches>
    <switch>service</switch>
    <ports>
      <port>10</port>
      <name>l3p10</name>
      <link>l3</link>
    </ports>
    <ports>
      <port>11</port>
      <name>l4p10</name>
      <link>l4</link>
    </ports>
  </switches>
  <switches>
    <switch>wan</switch>
    <ports>
      <port>10</port>
```

Shytyi

Expires March 24, 2020

[Page 11]

```
    <link>l1</link>
  </ports>
</switches>
<vms>
  <vm>VNF-vCPE</vm>
  <ports>
    <port>1</port>
    <name>l1p1</name>
    <link>l1</link>
  </ports>
  <ports>
    <port>2</port>
    <name>l4p2</name>
    <link>l4</link>
  </ports>
  <ram>2048</ram>
  <cpu>2</cpu>
  <storages>
    <id>1</id>
    <location>http://192.168.2.1/vCPE-x86.qcow2</location>
  </storages>
  <day0-config>
    <location>https://192.168.2.1/vCPE-day0.iso</location>
    <day0-var-path>/config.rom</day0-var-path>
    <variable>
      <name>hostname</name>
      <value>IETF-vCPE</value>
    </variable>
    <variable>
      <name>ipaddress</name>
      <value>192.168.1.2 255.255.255.0</value>
    </variable>
  </day0-config>
</vms>
<vms>
  <vm>VNF-vFirewall</vm>
  <ports>
    <port>1</port>
    <name>l3p1</name>
    <link>l3</link>
  </ports>
  <ports>
    <port>2</port>
    <name>l2p2</name>
    <link>l2</link>
  </ports>
  <ram>2048</ram>
  <cpu>2</cpu>
```

Shytyi

Expires March 24, 2020

[Page 12]

```
<storages>
  <id>1</id>
  <location>http://192.168.2.1/vFirewall-x86.qcow2</location>
</storages>
<day0-config>
  <location>https://192.168.2.1/vFirewall-day0.iso</location>
  <day0-var-path>/config.rom</day0-var-path>
  <variable>
    <name>hostname</name>
    <value>vFirewall</value>
  </variable>
  <variable>
    <name>ipaddress</name>
    <value>192.168.1.3 255.255.255.0</value>
  </variable>
</day0-config>
</vms>
</ucpe>
```

8. Security Considerations

At this time, no security considerations are addressed by this memo.

9. IANA Considerations

No request to IANA at this time.

10. Acknowledgements

The authors would like to thank:

- o Mahesh Jethanandani.
- o Robert Varga.
- o Bill Wu

for their valuable comments.

11. Normative References

- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), DOI 10.17487/RFC2119, March 1997,
<<https://www.rfc-editor.org/info/rfc2119>>.

Shytyi

Expires March 24, 2020

[Page 13]

[RFC8199] Bogdanovic, D., Claise, B., and C. Moberg, "YANG Module Classification", [RFC 8199](#), DOI 10.17487/RFC8199, July 2017, <<https://www.rfc-editor.org/info/rfc8199>>.

Author's Address

Dmytro Shytyi
SFR
Paris area , Ile-de-France
France

Email: ietf.dmytro@shytyi.net
URI: <https://dmytro.shytyi.net>

Shytyi

Expires March 24, 2020

[Page 14]