

Copyright Notice

Copyright (c) 2023 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to BCP 78 and the IETF Trust's Legal Provisions Relating to IETF Documents (<https://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Revised BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Revised BSD License.

Table of Contents

- [1. Introduction](#)
- [2. Terminology](#)
- [3. Overview of Extensions to PCEP](#)
 - [3.1. LSP-EXTENDED-FLAG TLV](#)
 - [3.2. PATH-RECOMPUTATION TLV](#)
- [4. Operation](#)
 - [4.1. Strict path enforcement](#)
 - [4.2. Path recomputation](#)
- [5. Security Considerations](#)
- [6. IANA Considerations](#)
 - [6.1. LSP-EXTENDED-FLAG TLV](#)
 - [6.2. PATH-RECOMPUTATION TLV](#)
- [7. References](#)
 - [7.1. Normative References](#)
 - [7.2. Informative References](#)
- [Authors' Addresses](#)

1. Introduction

Usage of Segment-routing and PCEP in connection-oriented transport services require path persistency and hop-by-hop behavior for PCE computed paths.

Circuit-Style Policy introduced in [[I-D.schmutzer-spring-cs-sr-policy](#)] requires PCEP extensions, which are covered in this document.

This document:

- *Introduces possibility to request strict path from the PCE by extending LSP-EXTENDED-FLAG TLV

*Adding new TLV to encode information about disabling path recomputation for specific path to the PCE, to be carried inside the LSPA object, which is defined in [[RFC5440](#)].

*Clarifies usage of existing O-flag from RP object in Segment-routing

PCEP extensions described in this document are applicable to RSVP-TE and SR-TE.

2. Terminology

The following terminologies are used in this document:

ERO: Explicit Route Object

IGP: Interior Gateway Protocol

LSP: Label Switched Path.

LSPA: Label Switched Path Attributes.

OTN: Optical Transport Network.

PCC: Path Computation Client

PCE: Path Computation Element

PCEP: Path Computation Element Protocol.

SDH: Synchronous Digital Hierarchy

SID: Segment Identifier

SONET: Synchronous Optical Network

SR: Segment Routing.

SR-TE: Segment Routing Traffic Engineering.

3. Overview of Extensions to PCEP

3.1. LSP-EXTENDED-FLAG TLV

O-flag is proposed in the LSP-EXTENDED-FLAG TLV, which was introduced in 5.1.2 of [[I-D.ietf-pce-lsp-extended-flags](#)] and extended with E-flag in [[I-D.peng-pce-entropy-label-position](#)]. TLV format will be added after assigning O flag bit position by IANA.


Type (16 bits): the value is TBD1 by IANA.

Length (16 bits): multiple of 4 octets.

0 (Strict-Path): If set to 1, this indicates to the PCE that a path exclusively made of strict hops is required. Strict hop definition is described in Section 4.1

3.2. PATH-RECOMPUTATION TLV

This document defines new TLV for the LSPA Object for encoding information whether path recomputation is allowed for delegated LSP. The TLV is optional. If the TLV is included in LSPA object, the PCE MUST NOT recompute path in cases specified by flags in the TLV.



Type (16 bits): the value is TBD2 by IANA.

Length (16 bits): 4 octets

Reserved: MUST be set to zero by the sender and MUST be ignored by the receiver.

Flags: This document defines the following flag bits. The other bits MUST be set to zero by the sender and MUST be ignored by the receiver.

*P (Permanent): If set to 1, the PCE MUST NOT recompute path even if current path is not satisfying path computation constraints. Otherwise, if this flag is cleared, then the PCE MAY recompute path if original path is invalidated.

*F (Force): If set to 1, the PCE MUST NOT update path. If flag is cleared, the PCE MAY update path based on explicit request from operator.

4. Operation

4.1. Strict path enforcement

PCC MAY set the 0 flag in LSP-EXTENDED-FLAG TLV in PCRpt message to the PCE to indicate that a path exclusively made of strict hops is required.

0 flag cleared or LSP-EXTENDED-FLAG TLV not included indicates that a loose path is acceptable.

In PCUpdate or PCInitiate messages, PCE MAY set 0 bit if strict path is provided.

The flag is applicable only for stateful messages. Existing 0 flag in RP object MAY be used to indicate similar behavior in PCReq and PCRep messages as described in as described in Section 7.4.1 of [[RFC5440](#)].

If 0 flag is set to 1 for both stateful and stateless messages for SR paths introduced in [[RFC8664](#)], PCE MUST use only SIDs, which will use explicitly specified adjacencies for packet forwarding. For example Adjacency SIDs MAY be used, but Prefix SIDs MUST NOT be used (even if there is only one adjacency). the PCE MUST use Adjacency SIDs only.

4.2. Path recomputation

PCC MAY set flags in PATH-RECOMPUTATION TLV to control path computation behavior on PCE side. If TLV is not included, then the PCE MAY use local policy to trigger path-computation or LSP path update.

The presence of the TLV is blocking path recomputation based on various triggers like topology update, any periodic update or changed state of other LSPs in the network. LSP path MAY be modified if forwarded packets will still use same path - for example if same path can be encoded using Adjacency and Prefix SIDs, then PCE MAY switch between various representations of same path.

If P flag is cleared, the PCE MAY recompute if current path is not considered valid, for example after topology update resulting in path not satisfying LSP's path constraints, but it MUST NOT recompute path if current path is not optimal.

If P flag is set, the PCE MUST NOT recompute path during LSP lifetime even if path is invalidated. Only exception is explicit request from operator to recompute path

If F flag is cleared, path update triggered manually by operator or any northbound interface of PCE MAY be done. If flag is set the PCE CAN update path only to tear down LSP by sending PCUpdate message with empty ERO.

TLV MAY be included in PCInitiate and PCUpdate messages to indicate, which triggers will be disabled on the PCE. PCC should reflect flag values in PCRpt messages to forward requirement to other PCEs in the network.

5. Security Considerations

No additional security measure is required.

6. IANA Considerations

6.1. LSP-EXTENDED-FLAG TLV

[[I-D.ietf-pce-lsp-extended-flags](#)] defines the LSP-EXTENDED-FLAG TLV. IANA is requested to make the following assignment from the "LSP-EXTENDED-FLAG TLV Flag Field" registry:

Bit	Description	Reference
TBD1	Strict-Path Flag (0)	This document

Table 1

6.2. PATH-RECOMPUTATION TLV

IANA is requested to make the assignment of a new value for the existing "PCEP TLV Type Indicators" registry as follows:

TLV Type	TLV Name	Reference
TBD2	PATH-RECOMPUTATION TLV	This document

Table 2

7. References

7.1. Normative References

[[I-D.ietf-pce-lsp-extended-flags](#)]

Xiong, Q., "LSP Object Flag Extension of Stateful PCE", Work in Progress, Internet-Draft, draft-ietf-pce-lsp-extended-flags-09, 23 October 2022, <<https://www.ietf.org/archive/id/draft-ietf-pce-lsp-extended-flags-09.txt>>.

[[I-D.peng-pce-entropy-label-position](#)] Xiong, Q., Peng, S., and F. Qin, "PCEP Extension for SR-MPLS Entropy Label Position", Work in Progress, Internet-Draft, draft-peng-pce-entropy-label-position-08, 29 August 2022, <<https://www.ietf.org/archive/id/draft-peng-pce-entropy-label-position-08.txt>>.

[[RFC2119](#)] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, DOI 10.17487/

RFC2119, March 1997, <<https://www.rfc-editor.org/info/rfc2119>>.

[RFC5440] Vasseur, JP., Ed. and JL. Le Roux, Ed., "Path Computation Element (PCE) Communication Protocol (PCEP)", RFC 5440, DOI 10.17487/RFC5440, March 2009, <<https://www.rfc-editor.org/info/rfc5440>>.

[RFC8174] Leiba, B., "Ambiguity of Uppercase vs Lowercase in RFC 2119 Key Words", BCP 14, RFC 8174, DOI 10.17487/RFC8174, May 2017, <<https://www.rfc-editor.org/info/rfc8174>>.

[RFC8231] Crabbe, E., Minei, I., Medved, J., and R. Varga, "Path Computation Element Communication Protocol (PCEP) Extensions for Stateful PCE", RFC 8231, DOI 10.17487/RFC8231, September 2017, <<https://www.rfc-editor.org/info/rfc8231>>.

[RFC8664] Sivabalan, S., Filsfils, C., Tantsura, J., Henderickx, W., and J. Hardwick, "Path Computation Element Communication Protocol (PCEP) Extensions for Segment Routing", RFC 8664, DOI 10.17487/RFC8664, December 2019, <<https://www.rfc-editor.org/info/rfc8664>>.

7.2. Informative References

[I-D.schmutzer-spring-cs-sr-policy] Schmutzer, C., Filsfils, C., Ali, Z., and F. Clad, "Circuit Style Segment Routing Policies", Work in Progress, Internet-Draft, draft-schmutzer-spring-cs-sr-policy-00, 24 July 2022, <<https://www.ietf.org/archive/id/draft-schmutzer-spring-cs-sr-policy-00.txt>>.

[SDH] International Telecommunication Union, "Network node interface for the synchronous digital hierarchy (SDH)", ITU-T Recommendation G.707, October 2020.

[SONET] American National Standards Institute, "Synchronous Optical Network (SONET) Basic Description including Multiplex Structure, Rates, and Formats", ANSI T1.105, January 1995.

Authors' Addresses

Samuel Sidor
Cisco Systems, Inc.
Eurovea Central 3.
Pribinova 10
811 09 Bratislava
Slovakia

Email: ssidor@cisco.com

Zafar Ali
Cisco Systems, Inc.

Email: zali@cisco.com

Praveen Maheshwari
Airtel India

Email: Praveen.Maheshwari@airtel.com

Reza Rokui
Ciena

Email: rrokui@ciena.com

Andrew Stone
Nokia

Email: andrew.stone@nokia.com

Luay Jalil
Verizon

Email: luay.jalil@verizon.com

Shuping Peng
Huawei Technologies

Email: pengshuping@huawei.com

Tarek Saad
Juniper Networks

Email: tsaad@juniper.net

Daniel Voyer
Bell Canada

Email: daniel.voyer@bell.ca