

Network Working Group
Internet-Draft
Intended status: Standards Track
Expires: February 2, 2007

V. Singh
H. Schulzrinne
Columbia U.
H. Tschofenig
Siemens
August 2006

Dynamic Feature Extensions to the Presence Information Data Format
Location Object (PIDF-LO)
draft-singh-geopriv-pidf-lo-dynamic-00.txt

Status of this Memo

By submitting this Internet-Draft, each author represents that any applicable patent or other IPR claims of which he or she is aware have been or will be disclosed, and any of which he or she becomes aware will be disclosed, in accordance with [Section 6 of BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF), its areas, and its working groups. Note that other groups may also distribute working documents as Internet-Drafts.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

The list of current Internet-Drafts can be accessed at <http://www.ietf.org/ietf/lid-abstracts.txt>.

The list of Internet-Draft Shadow Directories can be accessed at <http://www.ietf.org/shadow.html>.

This Internet-Draft will expire on February 2, 2007.

Copyright Notice

Copyright (C) The Internet Society (2006).

Abstract

The Geopriv Location Object introduced by the Presence Information Data Format Location Object (PIDF-LO), [RFC 4119](#), defines a basic XML format for carrying geographical information of a presentity. This document extends the <location> element specified in [RFC 4119](#) to carry temporal feature elements useful for tracking moving objects.

It defines four elements, namely speed, bearing, acceleration, and elevation. The document also specifies mechanism to carry multiple moving object's status elements and proposes mechanism to indicate the type of the PIDF-LO content.

Table of Contents

1.	Introduction	3
2.	Terminology	4
3.	Protocol Behavior	4
3.1.	Indicating Use of Dynamic Feature PIDF-LO	5
3.2.	Units of Measure	5
4.	Transferring Multiple Location Objects	5
5.	XML Schema	6
6.	Example	7
7.	Security Considerations	10
8.	IANA Considerations	10
9.	Acknowledgements	10
10.	References	10
10.1.	Normative References	10
10.2.	Informative References	11
Appendix A.	Alternatives Considered	11
	Authors' Addresses	13
	Intellectual Property and Copyright Statements	14

1. Introduction

The existing Geopriv location object [5] gives presence information which is geographical location of the presentity. This corresponds to a physical location at a given instance of time. A large number of applications, specifically in the transportation industry, fleet management applications, goods delivery and postal companies require to track not only the geographical location but also the rate of change of location of the entities.

Some of the use case scenarios for such an extension are tracking the location of vehicles, monitoring if vehicles are deviating from their planned routes or pre-specified speed-limits, reporting the direction of movement of ships and airplanes at different instances of time, tracking kidnapped/trapped victims for emergency services and tracking of culprits by the police. The applications may be for safety and security of personals and vehicles, productivity management of mobile crews, monitoring to ensure schedules, monitoring to ensure no deviation from scheduled paths.

This document defines location vector by extending the the <location> introduced by the Presence Information Data Format Location Object (PIDF-LO), [RFC 4119](#), to carry temporal feature elements. It defines four elements, namely 'speed', 'bearing', 'acceleration', and 'elevation'. The description of these elements is taken from GML [1] and repeated for completeness reasons:

speed:

This element points to a measure of the rate of motion. It contains a 'uom' (Units Of Measure) attribute, which is a reference to a reference system for the amount, often a ratio or interval scale. The 'uom' attribute uses a URI to refer to a unit of measure definition. The GML document defines a set of convenience measure types described in ISO 19103. This is further explained in [section 3.2](#).

bearing:

The <bearing> element is of type `gml:DirectionPropertyType` and can contain a `gml:DirectionVector`, `gml:CompassPoint`, `DirectionKeyword`, or a `DirectionString` element. `gml:Directorvectors` are specified by providing components of a vector or two angles. A compass point is specified by a simple enumeration string type (e.g., "N", "NNE", "NE", ... "W"). Two elements to contain text-based descriptions of direction are provided. If the direction is specified using a term from a list, `gml:KeyWord` may be used, and the list indicated using the value of the `codeSpace` attribute. If

the direction is described in prose, `gml:DirectionString` may be used, allowing the value to be included inline or by reference.

acceleration:

This element specifies the rate (usually rapid) at which something happens. Similarly to the <speed> and the <elevation> element the <acceleration> element contains a 'uom' (Units Of Measure) attribute, which is a reference to a reference system for the amount.

elevation: The height of a thing above a reference level; altitude. Similarly to the <speed> and the <elevation> element the <acceleration> element contains a 'uom' (Units Of Measure) attribute, which is a reference to a reference system for the amount. The ability to use the 'elevation' element together with geospatial location offers a more compact way of expressing composite location information per [RFC 3825](#) [6] location information using a civic floor number.

This document therefore allows the existing location formats allowed by the GML `feature.xsd` schema to be extended with dynamic characteristics. The supported shapes are described in detail in [7]. This document enhances this functionality and offers support for moving objects.

[2.](#) Terminology

In this document, the key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" are to be interpreted as described in [RFC 2119](#) [2].

This document uses the terminology from [3].

[3.](#) Protocol Behavior

The document describes the protocol requirements for dynamic feature extensions, so that it can be transmitted by the location server and understood correctly by the clients. The clients should be able to indicate to the server that they can handle the dynamic feature elements. The server should also indicate to the clients that the type of location object is PIDF-LO + dynamic feature extensions. Also, the unit of measurements should be communicated by server and understood by the clients.

Singh, et al.

Expires February 2, 2007

[Page 4]

Internet-Draft

Dynamic Feature Extensions to PIDF-LO

August 2006

[3.1.](#) Indicating Use of Dynamic Feature PIDF-LO

The watcher can indicate its capability using the SIP Accept header. This document proposes to add a 'supported' parameter for the application/pidf+xml media type. It enumerates the non default namespaces supported by the UAS. An example is given below:

```
Accept: application/pidf+xml;  
supported="urn:ietf:params:xml:ns:temporal1"
```

Alternatively, a token can be defined and used, an example is given:

```
Accept: application/pidf+xml; supported="geopriv-temporal-features"
```

The server can specify the type of content using Content-Type header. The specific PIDF-LO type can be obtained by looking inside the XML content.

```
Content-Type: application/pidf+xml;
```

[3.2.](#) Units of Measure

GML permits a range of units of measure for all parameters. This document restricts this set to the following units: #m/s, #km/h and #mph

Editor's Note: Need to find the URN for kph, m/s, km/h need to be added here. Editor's Note: Need to find the URN for floor, if it exists. It is only valid for the elevation element.

Only the above-listed units of measurements MUST be used for the uom attribute.

4. Transferring Multiple Location Objects

Multiple location vector objects may be required to be transported simultaneously. This can be achieved using <timed-presence> defined in [RFC 4481](#) [4].

Typically, the watcher applications can reconstruct the path as well as dynamic behavior (speed, acceleration etc.) along the path by storing the received location vector objects. However, a new watcher may be interested in past location-vectors or may choose to receive notifications at a slower rate without losing valuable information. In other words, it can request to receive multiple location vector objects together. For example, it may want to get one NOTIFY every 15 minutes with multiple location objects aggregated.

The structure of the document which can be used for tracking moving objects using timed-status extension is shown below. An example is given in [section 6](#).

```
<tuple>
  <status>
    <gp:geopriv>
      .....
    </gp:geopriv>
  </status>
  <timestamp>.....</timestamp>

  <timed-status from="some time" until="some time">
```

```

        <gp:geopriv>
        .....
        </gp:geopriv>

        <gp:geopriv>
        .....
        </gp:geopriv>

    </timed-status>

</tuple>

<tuple>
.....
</tuple>

```

5. XML Schema

This section defines the XML schema consisting of four elements that are conveyed inside the <location-info> element defined by [RFC 4119 \[5\]](#). The data types are taken from GML.

```

<?xml version="1.0" encoding="UTF-8"?>
  <schema xmlns="http://www.w3.org/2001/XMLSchema"
    targetNamespace="urn:ietf:params:xml:ns:temporal1"
    xmlns:xml="http://www.w3.org/XML/1998/namespace"
    xmlns:temporal="urn:ietf:params:xml:ns:temporal1"
    xmlns:gml="http://www.opengis.net/gml"

    elementFormDefault="qualified"

```

```
attributeFormDefault="unqualified">
<import namespace="http://www.opengis.net/gml" schemaLocation=
"http://schemas.opengis.net/gml/3.1.1/base/dynamicFeature.xsd"/>

<element name="speed" type="gml:MeasureType" />
<element name="bearing" type="gml:DirectionPropertyType"/>
<element name="acceleration" type="gml:MeasureType"/>
<element name="elevation" type="gml:MeasureType"/>

</schema>
```

Figure 2: XML Schema

6. Example

The following example shows a PIDF-LO indicating geospatial location information using the `gml:Point` structure. Outside the `<gml:location/>` element the additional fields related to temporal characteristics are included.


```

<presence xmlns="urn:ietf:params:xml:ns:pidf"
  xmlns:gp="urn:ietf:params:xml:ns:pidf:geopriv10"
  xmlns:gml="urn:opengis:specification:gml:schema-xsd:feature:v3.0"
  xmlns:temp="urn:ietf:params:xml:ns:temporal1"
  entity="pres:geotarget@example.com">
  <tuple id="sg89ae">
    <status>
      <gp:geopriv>
        <gp:location-info>
          <gml:location>
            <gml:Point srsName="urn:ogc:def:crs:EPSG::4326">
              <gml:pos>-34.407 150.883</gml:pos>
            </gml:Point>
          </gml:location>
          <temp:speed uom="#kph">12</temp:speed>
          <temp:bearing>
            <temp:CompassPoint>SE</temp:CompassPoint>
          </temp:bearing>
        </gp:location-info>
        <gp:usage-rules>
          <gp:retransmission-allowed>no</gp:retransmission-allowed>
          <gp:retention-expiry>2003-06-23T04:57:29Z
          </gp:retention-expiry>
        </gp:usage-rules>
      </gp:geopriv>
    </status>
    <timestamp>2003-06-22T20:57:29Z</timestamp>
  </tuple>
</presence>

```

Figure 3: Example of a PIDF-LO with Speed Information

The following example shows multiple PIDF-LO using <timed-status>.

```

<?xml version="1.0" encoding="UTF-8"?>
<presence xmlns="urn:ietf:params:xml:ns:pidf"
  xmlns:gp="urn:ietf:params:xml:ns:pidf:geopriv10"
  xmlns:gml="urn:opengis:specification:gml:schema-xsd:feature:v3.0"
  xmlns:temp="urn:ietf:params:xml:ns:temporal1"
  entity="pres:geotarget@example.com">
  <tuple id="sg89ae">
    <status>
      <gp:geopriv>
        <gp:location-info>
          <gml:location>
            <gml:Point>

```

```
        <gml:pos>140. -35.</gml:pos>
      </gml:Point>
    </gml:location>
    <gml:speed uom="#kph">12.</gml:speed>
  </gp:location-info>
  <gp:usage-rules>
    <gp:retransmission-allowed>no</gp:retransmission-allowed>
    <gp:retention-expiry>2003-06-23T04:57:29Z
  </gp:retention-expiry>
  </gp:usage-rules>
</gp:geopriv>
</status>
<timestamp>2003-06-22T20:57:29Z</timestamp>

<timed-statusfrom="2005-08-15T10:20:00.000-05:00"
  until="2005-08-22T19:30:00.000-05:00">>
  <gp:geopriv>
    <gp:location-info>
      <gml:location>
        <gml:Point>
          <gml:pos>110. -35.</gml:pos>
        </gml:Point>
      </gml:location>
      <gml:speed uom="#kph">10</gml:speed>
    </gp:location-info>
    <gp:usage-rules>
      <gp:retransmission-allowed>yes</gp:retransmission-allowed>
      <gp:retention-expiry>2003-06-23T04:55:29Z
    </gp:retention-expiry>
    </gp:usage-rules>
  </gp:geopriv>
  <gp:geopriv>
    <gp:location-info>
      <gml:location>
        <gml:Point>
          <gml:pos>114. -35.</gml:pos>
        </gml:Point>
      </gml:location>
      <gml:speed uom="#kph">18.</gml:speed>
    </gp:location-info>
    <gp:usage-rules>
      <gp:retransmission-allowed>yes</gp:retransmission-allowed>
      <gp:retention-expiry>2003-06-23T04:53:29Z
    </gp:retention-expiry>
    </gp:usage-rules>
  </gp:geopriv>
```

</timed-status>

Singh, et al.

Expires February 2, 2007

[Page 9]

Internet-Draft

Dynamic Feature Extensions to PIDF-LO

August 2006

</tuple>
</presence>

Figure 4: Example showing multiple Location Vectors transmitted simultaneously.

7. Security Considerations

This document defines additional location elements carried by PIDF-LO (see [5]). The security considerations of [RFC 4119](#) [5] are applicable to this document.

8. IANA Considerations

A future version of this document will provide IANA considerations.

9. Acknowledgements

Add your name here.

10. References

10.1. Normative References

- [1] "Geographic information - Geography Markup Language (GML), OpenGIS 03-105r1, available at: http://portal.opengeospatial.org/files/?artifact_id=4700", April 2004.
- [2] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [RFC 2119](#), [BCP 14](#), March 1997.
- [3] Cuellar, J., Morris, J., Mulligan, D., Peterson, J., and J. Polk, "Geopriv Requirements", [RFC 3693](#), February 2004.

- [4] Schulzrinne, H., "Timed Presence Extensions to the Presence Information Data Format (PIDF) to Indicate Status Information for Past and Future Time Intervals", [RFC 4481](#), July 2006.
- [5] Peterson, J., "A Presence-based GEOPRIV Location Object Format", [RFC 4119](#), December 2005.

[10.2.](#) Informative References

- [6] Polk, J., Schnizlein, J., and M. Linsner, "Dynamic Host Configuration Protocol Option for Coordinate-based Location Configuration Information", [RFC 3825](#), July 2004.
- [7] Thomson, M., "Geodetic Shapes for the Representation of Uncertainty in PIDF-LO", [draft-thomson-geopriv-geo-shape-02](#) (work in progress), May 2006.
- [8] Mahy, R., "A Document Format for Filtering and Reporting Location Notifications in the Presence Information Document Format Location Object (PIDF-LO)", [draft-ietf-geopriv-loc-filters-00](#) (work in progress), March 2006.
- [9] Polk, J. and B. Rosen, "Session Initiation Protocol Location Conveyance", [draft-ietf-sip-location-conveyance-04](#) (work in progress), August 2006.
- [10] Schulzrinne, H., "Common Policy: A Document Format for Expressing Privacy Preferences", [draft-ietf-geopriv-common-policy-11](#) (work in progress), August 2006.
- [11] Schulzrinne, H., "A Document Format for Expressing Privacy Preferences for Location Information", [draft-ietf-geopriv-policy-08](#) (work in progress), February 2006.

[Appendix A.](#) Alternatives Considered

During the work on this document we encountered alternative approaches. These approaches make use of the MovingObjectStatus or its parent element track of dynamicFeature.xsd. MovingObjectStatus contains child elements where no use cases are currently known, e.g., validTime and contains elements that are already defined with PIDF-LO, such as <location>. Since it might not be known whether a Location Recipient understands the location extension defined in this document a PIDF-LO with a <location> element inside the <MovingObjectStatus> will likely create problems. Including the <location> element twice, once as defined with [RFC 4119](#) (PIDF-LO) and again in <MovingObjectStatus>, is unnecessary. The <track> element allows multiple <MovingObjectStatus> to be used. Figure 5 shows such an instance document carrying the <track> element.

```
<?xml version="1.0" encoding="UTF-8"?>
```

```
<presence xmlns="urn:ietf:params:xml:ns:pidf"
  xmlns:gp="urn:ietf:params:xml:ns:pidf:geopriv10"
  xmlns:gml="http://www.opengis.net/gml"
  entity="pres:geotarget@example.com">
  <tuple id="sg89ae">
    <status>
      <gp:geopriv>
        <gp:location-info>
          <gml:track>
            <gml:MovingObjectStatus>
              <gml:validTime>
                <gml:TimeInstant>
                  <gml:timePosition>2005-11-28T13:00:00
                </gml:timePosition>
                </gml:TimeInstant>
              </gml:validTime>
              <gml:location>
                <gml:Point>
                  <gml:pos>140. -35.</gml:pos>
                </gml:Point>
              </gml:location>
              <gml:speed uom="#kph">12</gml:speed>
              <gml:bearing>
                <gml:CompassPoint>SE</gml:CompassPoint>
              </gml:bearing>
            </gml:MovingObjectStatus>
          </gml:track>
        </gp:location-info>
      </gp:geopriv>
    </status>
  </tuple>
</presence>
```

```

    </gml:MovingObjectStatus>
  <gml:MovingObjectStatus>
    <gml:validTime>
      <gml:TimeInstant>
        <gml:timePosition>2005-11-28T14:00:00
        </gml:timePosition>
      </gml:TimeInstant>
    </gml:validTime>
    <gml:location>
      <gml:Point>
        <gml:pos>140.1 -34.9</gml:pos>
      </gml:Point>
    </gml:location>
    <gml:speed uom="#kph">23.</gml:speed>
    <gml:bearing>
      <gml:CompassPoint>ESE</gml:CompassPoint>
    </gml:bearing>
  </gml:MovingObjectStatus>
</gml:track>
</gp:location-info>
<gp:usage-rules>
  <gp:retransmission-allowed>no</gp:retransmission-allowed>
  <gp:retention-expiry>2003-06-23T04:57:29Z

```

```

    </gp:retention-expiry>
  </gp:usage-rules>
</gp:geopriv>
</status>
  <timestamp>2003-06-22T20:57:29Z</timestamp>
</tuple>
</presence>

```

Figure 5: Example of a PIDF-LO with a track Element

The authors decided to pick the simplest version.

Authors' Addresses

Singh Vishal
 Columbia University
 Department of Computer Science

450 Computer Science Building
New York, NY 10027
US

Email: vs2140@cs.columbia.edu
URI: <http://www.cs.columbia.edu/~vs2140>

Henning Schulzrinne
Columbia University
Department of Computer Science
450 Computer Science Building
New York, NY 10027
US

Phone: +1 212 939 7004
Email: hgs+ecrit@cs.columbia.edu
URI: <http://www.cs.columbia.edu/~hgs>

Hannes Tschofenig
Siemens
Otto-Hahn-Ring 6
Munich, Bavaria 81739
Germany

Phone: +49 89 636 40390
Email: Hannes.Tschofenig@siemens.com
URI: <http://www.tschofenig.com>

Full Copyright Statement

Copyright (C) The Internet Society (2006).

This document is subject to the rights, licenses and restrictions contained in [BCP 78](#), and except as set forth therein, the authors retain all their rights.

This document and the information contained herein are provided on an "AS IS" basis and THE CONTRIBUTOR, THE ORGANIZATION HE/SHE REPRESENTS OR IS SPONSORED BY (IF ANY), THE INTERNET SOCIETY AND THE INTERNET

ENGINEERING TASK FORCE DISCLAIM ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY WARRANTY THAT THE USE OF THE INFORMATION HEREIN WILL NOT INFRINGE ANY RIGHTS OR ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

Intellectual Property

The IETF takes no position regarding the validity or scope of any Intellectual Property Rights or other rights that might be claimed to pertain to the implementation or use of the technology described in this document or the extent to which any license under such rights might or might not be available; nor does it represent that it has made any independent effort to identify any such rights. Information on the procedures with respect to rights in RFC documents can be found in [BCP 78](#) and [BCP 79](#).

Copies of IPR disclosures made to the IETF Secretariat and any assurances of licenses to be made available, or the result of an attempt made to obtain a general license or permission for the use of such proprietary rights by implementers or users of this specification can be obtained from the IETF on-line IPR repository at <http://www.ietf.org/ipr>.

The IETF invites any interested party to bring to its attention any copyrights, patents or patent applications, or other proprietary rights that may cover technology that may be required to implement this standard. Please address the information to the IETF at ietf-ipr@ietf.org.

Acknowledgment

Funding for the RFC Editor function is provided by the IETF Administrative Support Activity (IASA).