

Network Working Group	H. Schulzrinne	<a href="#">TOC</a>
Internet-Draft	V. Singh	
Intended status: Standards Track	Columbia University	
Expires: February 18, 2010	H. Tschofenig	
	Nokia Siemens Networks	
	M. Thomson	
	Andrew Corporation	
	August 17, 2009	

## **Dynamic Extensions to the Presence Information Data Format Location**

### **Object (PIDF-LO)**

**[draft-singh-geopriv-pidf-lo-dynamic-07](#)**

#### **Status of this Memo**

This Internet-Draft is submitted to IETF in full conformance with the provisions of BCP 78 and BCP 79.

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF), its areas, and its working groups. Note that other groups may also distribute working documents as Internet-Drafts.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

The list of current Internet-Drafts can be accessed at <http://www.ietf.org/ietf/1id-abstracts.txt>.

The list of Internet-Draft Shadow Directories can be accessed at <http://www.ietf.org/shadow.html>.

This Internet-Draft will expire on February 18, 2010.

#### **Copyright Notice**

Copyright (c) 2009 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to BCP 78 and the IETF Trust's Legal Provisions Relating to IETF Documents in effect on the date of publication of this document (<http://trustee.ietf.org/license-info>). Please review these documents carefully, as they describe your rights and restrictions with respect to this document.

## **Abstract**

The Geopriv Location Object introduced by the Presence Information Data Format - Location Object (PIDF-LO), RFC 4119, defines a basic XML format for carrying geographical information of a presentity. This document defines PIDF-LO extensions that are intended to convey information about moving objects. Elements are defined that enable expression of spatial orientation, speed, heading, and acceleration of the presentity.

---

## **Table of Contents**

- [1. Introduction](#)
- [2. Terminology](#)
- [3. Dynamic Elements](#)
  - [3.1. Angular Measures and Coordinate Reference Systems](#)
- [4. Dynamic Feature XML Schema](#)
- [5. Security Considerations](#)
- [6. IANA Considerations](#)
  - [6.1. Dynamic Feature Extensions Namespace Registration](#)
  - [6.2. Dynamic Feature Extensions Schema Registration](#)
- [7. Acknowledgements](#)
- [8. References](#)
  - [8.1. Normative References](#)
  - [8.2. Informative References](#)
- [Appendix A. Earth Centered, Earth Fixed Direction Vectors](#)
- [§ Authors' Addresses](#)

---

## **1. Introduction**

[TOC](#)

The Presence Information Data Format - Location Object (PIDF-LO) (see RFC 4119 [\[RFC4119\]](#) ([Peterson, J., "A Presence-based GEOPRIV Location Object Format," December 2005.](#))) provides geographical location of a presentity. This corresponds to a physical location at a given instance of time. With the extensions defined in [\[RFC5491\]](#) ([Winterbottom, J., Thomson, M., and H. Tschofenig, "GEOPRIV Presence Information Data Format Location Object \(PIDF-LO\) Usage Clarification, Considerations, and Recommendations," March 2009.](#)) more guidelines to implementers are being provided with respect to the expression location information in PIDF-LO.

The addition of rate of change information to the PIDF-LO enables a range of use cases. These use cases either directly use dynamic information, or use that information for smoother tracking of a position over time. For example, an application that continuously

tracks a presentity could use velocity information to extrapolate positions in between times location information is measured. A shipping company could directly use speed to monitor delivery truck speed to ensure speed limits are observed.

---

## 2. Terminology

[TOC](#)

In this document, the key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" are to be interpreted as described in RFC 2119 [[RFC2119](#) ([Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels," March 1997.](#).)].

---

## 3. Dynamic Elements

[TOC](#)

This document defines a new element, <Dynamic>, for the conveyance of dynamic information.

Dynamic information MAY be included without any other location information being present. When dynamic information is associated with information about the instantaneous position of the presentity, the <Dynamic> element MUST be included in the same <location-info> element as the corresponding geodetic (or civic) location information.

Dynamic information can be safely ignored by a recipient that does not support this specification.

The <Dynamic> element contains the following components:

### **orientation:**

The <orientation> element describes the spatial orientation of the presentity; the direction that the object is pointing. For a device, this orientation might depend on the type of device. See [Section 3.1 \(Angular Measures and Coordinate Reference Systems\)](#) for details.

### **speed:**

Speed is the time rate of change in position of a presentity without regard for direction; the scalar component of velocity. The value for the <speed> element is a measure that is defined in meters per second.

### **heading:**

Heading is directional component of velocity. See [Section 3.1 \(Angular Measures and Coordinate Reference Systems\)](#)

for details.

**acceleration:**

Acceleration is the time rate of change of velocity. This element contains the scalar component of velocity, measured in meters per second per second.

Each element can be omitted if no information is available. In the following example the presentity is approximately oriented to the North at a slightly elevated angle. The presentity is travelling 24 meters per second to the West:

```
<?xml version="1.0" encoding="UTF-8"?>
<presence
    xmlns="urn:ietf:params:xml:ns:pidf"
    xmlns:dm="urn:ietf:params:xml:ns:pidf:data-model"
    xmlns:gp="urn:ietf:params:xml:ns:pidf:geopriv10"
    xmlns:dyn="urn:ietf:params:xml:ns:pidf:dynamic"
    xmlns:gml="http://www.opengis.net/gml"
    entity="pres:alice@example.com">
    <dm:device id="abc123">
        <gp:geopriv>
            <gp:location-info>
                <dyn:Dynamic>
                    <dyn:orientation>-3 12</dyn:orientation>
                    <dyn:speed>24</dyn:speed>
                    <dyn:heading>278</dyn:heading>
                </dyn:Dynamic>
            </gp:location-info>
            <gp:usage-rules/>
            <method>gps</method>
        </gp:geopriv>
        <timestamp>2009-06-22T20:57:29Z</timestamp>
        <dm:deviceID>mac:1234567890ab</dm:deviceID>
    </dm:device>
</presence>
```

Another example shows a PIDF-LO document of the presentity alice@example.com on a bike traveling 12 meters per second and with an acceleration of 2 meters per second. Her position is indicated as a circle. The values for speed and acceleration might be used by a receiver to adjust the uncertainty over time.

```

<?xml version="1.0" encoding="UTF-8"?>
<presence
    xmlns="urn:ietf:params:xml:ns:pidf"
    xmlns:dm="urn:ietf:params:xml:ns:pidf:data-model"
    xmlns:gp="urn:ietf:params:xml:ns:pidf:geopriv10"
    xmlns:dyn="urn:ietf:params:xml:ns:pidf:dynamic"
    xmlns:gml="http://www.opengis.net/gml"
    xmlns:gs="http://www.opengis.net/pidflo/1.0"
    entity="pres:alice@example.com">
    <dm:device id="abc123">
        <gp:geopriv>
            <gp:location-info>
                <gs:Circle srsName="urn:ogc:def:crs:EPSG::4326">
                    <gml:pos>42.5463 -73.2512</gml:pos>
                    <gs:radius uom="urn:ogc:def:uom:EPSG::9001">
                        100
                    </gs:radius>
                </gs:Circle>
                <dyn:Dynamic>
                    <dyn:speed>12</dyn:speed>
                    <dyn:acceleration>2</dyn:acceleration>
                </dyn:Dynamic>
            </gp:location-info>
            <gp:usage-rules/>
            <method>gps</method>
        </gp:geopriv>
        <timestampl>2009-06-22T20:57:29Z</timestampl>
        <dm:deviceID>mac:1234567890ab</dm:deviceID>
    </dm:device>
</presence>

```

---

### 3.1. Angular Measures and Coordinate Reference Systems

[TOC](#)

[\[RFC5491\] \(Winterbottom, J., Thomson, M., and H. Tschofenig, "GEOPRIV Presence Information Data Format Location Object \(PIDF-LO\) Usage Clarification, Considerations, and Recommendations," March 2009.\)](#)

constrains the coordinate reference system (CRS) used in PIDF-LO to World Geodetic System 1984 (WGS 84) using either the two-dimensional (latitude, longitude) CRS identified by "urn:ogc:def:crs:EPSG::4326" or the two-dimensional (latitude, longitude, altitude) CRS identified by "urn:ogc:def:crs:EPSG::4979". Dynamic locations similarly assume that either of these coordinate reference systems are used.

The <orientation> and <heading> establish a direction. Both measures contain one or two angular values that are expressed relative to the

current position of the presentity (see [Appendix A \(Earth Centered, Earth Fixed Direction Vectors\)](#)). Angular measures are expressed in degrees and values MAY be negative. If two measures are present, the values MUST be separated by whitespace.

The first measure specifies the horizontal direction from the current position of the presentity to a point that it either pointing towards or travelling towards. Horizontal angles are measured from Northing to Easting. Horizontal angles start from zero when pointing to or travelling towards the North and increase towards the East.

The second measure, if present, specifies the vertical component of this angle. This angle is the elevation from the local horizontal plane. If the second angle value is omitted, the vertical component is unknown and the speed measure MAY be assumed to only contain the horizontal component of speed.

---

[TOC](#)

#### 4. Dynamic Feature XML Schema

```
<?xml version="1.0"?>
<xs:schema
    targetNamespace="urn:ietf:params:xml:ns:pidf:dynamic"
    xmlns:dyn="urn:ietf:params:xml:ns:pidf:dynamic"
    xmlns:xs="http://www.w3.org/2001/XMLSchema"
    elementFormDefault="qualified"
    attributeFormDefault="unqualified">

    <xs:element name="Dynamic" type="dyn:dynamicType"/>

    <xs:complexType name="dynamicType">
        <xs:complexContent>
            <xs:restriction base="xs:anyType">
                <xs:sequence>
                    <xs:element name="orientation" minOccurs="0"
                        type="dyn:directionType"/>
                    <xs:element name="speed" minOccurs="0"
                        type="xs:double"/>
                    <xs:element name="heading" minOccurs="0"
                        type="dyn:directionType"/>
                    <xs:element name="acceleration" minOccurs="0"
                        type="xs:double"/>
                    <xs:any namespace="#other" processContents="lax"
                        minOccurs="0" maxOccurs="unbounded"/>
                </xs:sequence>
                <xs:anyAttribute namespace="#other" processContents="lax"/>
            </xs:restriction>
        </xs:complexContent>
    </xs:complexType>

    <xs:simpleType name="directionType">
        <xs:restriction base="dyn:doubleListType">
            <xs:minLength value="1"/>
            <xs:maxLength value="2"/>
        </xs:restriction>
    </xs:simpleType>

    <xs:simpleType name="doubleListType">
        <xs:list itemType="xs:double"/>
    </xs:simpleType>

</xs:schema>
```

## 5. Security Considerations

This document defines additional location elements carried by PIDF-LO. No additional security considerations beyond those described in [RFC 4119 \(Peterson, J., "A Presence-based GEOPRIV Location Object Format," December 2005.\)](#) [RFC4119] are applicable to this document.

---

## 6. IANA Considerations

[TOC](#)

This section registers a new XML namespace (as described in [\[RFC3688\] \(Mealling, M., "The IETF XML Registry," January 2004.\)](#)) and a new XML schema.

---

### 6.1. Dynamic Feature Extensions Namespace Registration

[TOC](#)

**URI:** urn:ietf:params:xml:ns:pidf:dynamic"

**Registrant Contact:** IETF Geopriv Working Group, Hannes Tschofenig (hannes.tschofenig@gmx.net).

**XML:**

```
BEGIN
<?xml version="1.0"?>
<!DOCTYPE html PUBLIC "-//W3C//DTD XHTML Basic 1.0//EN"
  "http://www.w3.org/TR/xhtml-basic/xhtml-basic10.dtd">
<html xmlns="http://www.w3.org/1999/xhtml">
<head>
  <title>Dynamic Feature Extensions Namespace</title>
</head>
<body>
  <h1>Namespace for Dynamic Feature Extensions to PIDF-LO</h1>
  <h2>urn:ietf:params:xml:ns:pidf:dynamic</h2>
<p>See <a href="[URL of published RFC]">RFCXXXX
  [NOTE TO IANA/RFC-EDITOR:
    Please replace XXXX with the RFC number of this
    specification.]</a>.</p>
</body>
</html>
END
```

---

## 6.2. Dynamic Feature Extensions Schema Registration

[TOC](#)

**URI:** urn:ietf:params:xml:schema:pidf:dynamic

**Registrant Contact:** IETF Geopriv Working Group, Hannes Tschofenig  
(hannes.tschofenig@gmx.net)

**XML:** The XML schema to be registered is contained in [Section 4](#)  
([Dynamic Feature XML Schema](#)). Its first line is

```
<?xml version="1.0"?>
```

and its last line is

```
</xs:schema>
```

---

## 7. Acknowledgements

[TOC](#)

We would like to thank Klaus Darilion, Cullen Jennings, Rohan Mahy, Carl Reed, and Brian Rosen for their comments.

---

---

## 8. References

[TOC](#)

---

### 8.1. Normative References

[TOC](#)

[RFC2119]	<a href="#">Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels,"</a> BCP 14, RFC 2119, March 1997 ( <a href="#">TXT</a> , <a href="#">HTML</a> , <a href="#">XML</a> ).
[RFC3688]	Mealling, M., " <a href="#">The IETF XML Registry</a> ," BCP 81, RFC 3688, January 2004 ( <a href="#">TXT</a> ).
[RFC4119]	Peterson, J., " <a href="#">A Presence-based GEOPRIV Location Object Format</a> ," RFC 4119, December 2005 ( <a href="#">TXT</a> ).

## 8.2. Informative References

[TOC](#)

[GeoShape]	Thomson, M. and C. Reed, "GML 3.1.1 PIDF-LO Shape Application Schema for use by the Internet Engineering Task Force (IETF)," Candidate OpenGIS Implementation Specification 06-142, Version: 0.0.9, December 2006.
[RFC5491]	Winterbottom, J., Thomson, M., and H. Tschofenig, " <a href="#">GEOPRIV Presence Information Data Format Location Object (PIDF-LO) Usage Clarification, Considerations, and Recommendations</a> ," RFC 5491, March 2009 ( <a href="#">TXT</a> ).

---

## Appendix A. Earth Centered, Earth Fixed Direction Vectors

[TOC](#)

The absolute orientation or heading of a presentity depends on its latitude and longitude. The following vectors can be used to determine the absolute direction in the WGS 84 Earth Centered, Earth Fixed (X, Y, Z) coordinate space.

The direction of North as a unit vector in ECEF coordinates is:

```
North = [ -1 * sin(latitude) * cos(longitude),  
          -1 * sin(latitude) * sin(longitude),  
          cos(latitude) ]
```

The direction of "up" (the upward normal of the horizontal plane) as a unit vector in ECEF coordinates is:

```
Up = [ cos(latitude) * cos(longitude),  
        cos(latitude) * sin(longitude),  
        sin(latitude) ]
```

---

## Authors' Addresses

[TOC](#)

	Henning Schulzrinne
	Columbia University
	Department of Computer Science
	450 Computer Science Building, New York, NY 10027
	US
Phone:	+1 212 939 7004
Email:	<a href="mailto:hgs@cs.columbia.edu">hgs@cs.columbia.edu</a>
URI:	<a href="http://www.cs.columbia.edu/">http://www.cs.columbia.edu/</a>
	Vishal Singh

Columbia University
Department of Computer Science
450 Computer Science Building, New York, NY 10027
US
Email: <a href="mailto:vs2140@cs.columbia.edu">vs2140@cs.columbia.edu</a>
URI: <a href="http://www.cs.columbia.edu/~vs2140">http://www.cs.columbia.edu/~vs2140</a>
Hannes Tschofenig
Nokia Siemens Networks
Linnoitustie 6
Esboo 02600
Finland
Phone: +358 (50) 4871445
Email: <a href="mailto:Hannes.Tschofenig@gmx.net">Hannes.Tschofenig@gmx.net</a>
URI: <a href="http://www.tschofenig.priv.at/">http://www.tschofenig.priv.at/</a>
Martin Thomson
Andrew Corporation
Wollongong
NSW Australia
Email: <a href="mailto:martin.thomson@andrew.com">martin.thomson@andrew.com</a>