

Network Working Group	H. Schulzrinne	
Internet-Draft	V. Singh	
Intended status: Standards Track	Columbia University	
Expires: September 27, 2010	H. Tschofenig	
	Nokia Siemens Networks	
	M. Thomson	
	Andrew Corporation	
	March 26, 2010	

[TOC](#)

Dynamic Extensions to the Presence Information Data Format Location Object (PIDF-LO)
draft-singh-geopriv-pidf-lo-dynamic-09

Abstract

The Geopriv Location Object introduced by the Presence Information Data Format - Location Object (PIDF-LO), RFC 4119, defines a basic XML format for carrying geographical information of a presentity. This document defines PIDF-LO extensions to convey information about moving objects. Elements are defined that enable expression of spatial orientation, speed, and heading of the presentity.

Status of this Memo

This Internet-Draft is submitted to IETF in full conformance with the provisions of BCP 78 and BCP 79.

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF), its areas, and its working groups. Note that other groups may also distribute working documents as Internet-Drafts.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

The list of current Internet-Drafts can be accessed at <http://www.ietf.org/ietf/1id-abstracts.txt>.

The list of Internet-Draft Shadow Directories can be accessed at <http://www.ietf.org/shadow.html>.

This Internet-Draft will expire on September 27, 2010.

Copyright Notice

Copyright (c) 2010 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to BCP 78 and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the BSD License.

Table of Contents

- [1.](#) Introduction
- [2.](#) Terminology
- [3.](#) Dynamic Elements
 - [3.1.](#) Angular Measures and Coordinate Reference Systems
- [4.](#) Dynamic Feature XML Schema
- [5.](#) Security Considerations
- [6.](#) IANA Considerations
 - [6.1.](#) Dynamic Feature Extensions Namespace Registration
 - [6.2.](#) Dynamic Feature Extensions Schema Registration
- [7.](#) Acknowledgements
- [8.](#) References
 - [8.1.](#) Normative References
 - [8.2.](#) Informative References
- [Appendix A.](#) Earth Centered, Earth Fixed Direction Vectors
- [§](#) Authors' Addresses

1. Introduction

[TOC](#)

The Presence Information Data Format - Location Object (PIDF-LO) (see RFC 4119 [\[RFC4119\]](#) (Peterson, J., "A Presence-based GEOPRIV Location Object Format," December 2005.)) provides geographical location of a presentity. This corresponds to a physical location at a given instance of time. With the extensions defined in [\[RFC5491\]](#) (Winterbottom, J., Thomson, M., and H. Tschofenig, "GEOPRIV Presence Information Data Format Location Object (PIDF-LO) Usage Clarification, Considerations, and Recommendations," March 2009.) more guidelines to implementers are being provided with respect to the expression location information in PIDF-LO.

The addition of rate of change information to the PIDF-LO enables a range of use cases. These use cases either directly use dynamic information, or use that information for smoother tracking of a position over time. For example, an application that continuously tracks a presentity could use velocity information to extrapolate positions in between times location information is measured. A shipping company could directly use speed to monitor delivery truck speed to ensure speed limits are observed.

2. Terminology

[TOC](#)

In this document, the key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" are to be interpreted as described in RFC 2119 [\[RFC2119\]](#) (Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels," March 1997.).

This document uses the term "presentity", as defined in in RFC 2778 [\[RFC2778\]](#) (Day, M., Rosenberg, J., and H. Sugano, "A Model for Presence and Instant Messaging," February 2000.), through the document to refer to the device subject to location determination. The similarity with presence concepts and the abstract location privacy architecture, as described in RFC 4079 [\[RFC4079\]](#) (Peterson, J., "A Presence Architecture for the Distribution of GEOPRIV Location Objects," July 2005.), lead to re-use of the Presence Information Data Format (PIDF), see RFC 3863 [\[RFC3863\]](#) (Sugano, H., Fujimoto, S., Klyne, G., Bateman, A., Carr, W., and J. Peterson, "Presence Information Data Format (PIDF)," August 2004.), and its enhancement for location information with RFC 4119 [\[RFC4119\]](#) (Peterson, J., "A Presence-based GEOPRIV Location Object Format," December 2005.). Note that this document does not differentiate between human and non-human objects and hence both are in scope.

3. Dynamic Elements

[TOC](#)

This document defines a new element, <Dynamic>, for the conveyance of dynamic information.

Dynamic information MAY be included without any other location information being present. When dynamic information is associated with information about the instantaneous position of the presentity, the <Dynamic> element MUST be included in the same <location-info> element as the corresponding geodetic (or civic) location information. Dynamic information can be safely ignored by a recipient that does not support this specification.

The <Dynamic> element contains the following components:

orientation:

The <orientation> element describes the spatial orientation of the presentity; the direction that the object is pointing. For a device, this orientation might depend on the type of device. See [Section 3.1 \(Angular Measures and Coordinate Reference Systems\)](#) for details.

speed:

Speed is the time rate of change in position of a presentity without regard for direction; the scalar component of velocity. The value for the <speed> element is a measure that is defined in meters per second.

heading:

Heading is directional component of velocity. See [Section 3.1 \(Angular Measures and Coordinate Reference Systems\)](#) for details.

Each element can be omitted if no information is available. In the following example the presentity is approximately oriented to the North at a slightly elevated angle. The presentity is travelling 24 meters per second to the West:

```

<?xml version="1.0" encoding="UTF-8"?>
<presence
  xmlns="urn:ietf:params:xml:ns:pidf"
  xmlns:dm="urn:ietf:params:xml:ns:pidf:data-model"
  xmlns:gp="urn:ietf:params:xml:ns:pidf:geopriv10"
  xmlns:dyn="urn:ietf:params:xml:ns:pidf:dynamic"
  xmlns:gml="http://www.opengis.net/gml"
  entity="pres:alice@example.com">
  <dm:device id="abc123">
    <gp:geopriv>
      <gp:location-info>
        <dyn:Dynamic>
          <dyn:orientation>-3 12</dyn:orientation>
          <dyn:speed>24</dyn:speed>
          <dyn:heading>278</dyn:heading>
        </dyn:Dynamic>
      </gp:location-info>
      <gp:usage-rules/>
      <method>gps</method>
    </gp:geopriv>
    <timestamp>2009-06-22T20:57:29Z</timestamp>
    <dm:deviceId>mac:1234567890ab</dm:deviceId>
  </dm:device>
</presence>

```

Another example shows a PIDF-LO document of the present entity `alice@example.com` on a bike traveling 12 meters per second. Her position is indicated as a circle. The values for speed may be used by a receiver to adjust the uncertainty over time.

```

<?xml version="1.0" encoding="UTF-8"?>
<presence
  xmlns="urn:ietf:params:xml:ns:pidf"
  xmlns:dm="urn:ietf:params:xml:ns:pidf:data-model"
  xmlns:gp="urn:ietf:params:xml:ns:pidf:geopriv10"
  xmlns:dyn="urn:ietf:params:xml:ns:pidf:dynamic"
  xmlns:gml="http://www.opengis.net/gml"
  xmlns:gs="http://www.opengis.net/pidflo/1.0"
  entity="pres:alice@example.com">
  <dm:device id="abc123">
    <gp:geopriv>
      <gp:location-info>
        <gs:Circle srsName="urn:ogc:def:crs:EPSG::4326">
          <gml:pos>42.5463 -73.2512</gml:pos>
          <gs:radius uom="urn:ogc:def:uom:EPSG::9001">
            100
          </gs:radius>
        </gs:Circle>
        <dyn:Dynamic>
          <dyn:speed>12</dyn:speed>
        </dyn:Dynamic>
      </gp:location-info>
      <gp:usage-rules/>
      <method>gps</method>
    </gp:geopriv>
    <timestamp>2009-06-22T20:57:29Z</timestamp>
    <dm:deviceID>mac:1234567890ab</dm:deviceID>
  </dm:device>
</presence>

```

3.1. Angular Measures and Coordinate Reference Systems

[TOC](#)

[\[RFC5491\]](#) (Winterbottom, J., Thomson, M., and H. Tschofenig, "GEOPRIV Presence Information Data Format Location Object (PIDF-LO) Usage Clarification, Considerations, and Recommendations," March 2009.)

constrains the coordinate reference system (CRS) used in PIDF-LO to World Geodetic System 1984 (WGS 84) using either the two-dimensional (latitude, longitude) CRS identified by "urn:ogc:def:crs:EPSG::4326" or the three-dimensional (latitude, longitude, altitude) CRS identified by "urn:ogc:def:crs:EPSG::4979". Dynamic locations similarly assume that either of these coordinate reference systems are used.

The <orientation> and <heading> elements both describe a direction. The <orientation> element describes the "direction of facing"; the <heading> element describes the "direction of travel". Both measures

contain one or two angular values that are expressed relative to the current position of the presentity (see [Appendix A \(Earth Centered, Earth Fixed Direction Vectors\)](#)). Angular measures are expressed in degrees and values can be negative. If two measures are present, the values MUST be separated by whitespace.

The first measure specifies the horizontal direction from the current position of the presentity to a point that it is pointing towards (for <orientation>) or travelling towards (for <heading>). Horizontal angles are measured from Northing to Easting. Horizontal angles start from zero when pointing to or travelling towards the North and increase towards the East.

The second measure, if present, specifies the vertical component of this angle. This angle is the elevation from the local horizontal plane. If the second angle value is omitted, the vertical component is unknown. If only one angle is present, <orientation> describes only the horizontal component. For <heading>, the associated <speed> measure contains only the horizontal component of speed.

4. Dynamic Feature XML Schema

```
<?xml version="1.0"?>
<xs:schema
  targetNamespace="urn:ietf:params:xml:ns:pidf:dynamic"
  xmlns:dyn="urn:ietf:params:xml:ns:pidf:dynamic"
  xmlns:xs="http://www.w3.org/2001/XMLSchema"
  elementFormDefault="qualified"
  attributeFormDefault="unqualified">

  <xs:element name="Dynamic" type="dyn:dynamicType"/>

  <xs:complexType name="dynamicType">
    <xs:complexContent>
      <xs:restriction base="xs:anyType">
        <xs:sequence>
          <xs:element name="orientation" minOccurs="0"
            type="dyn:directionType"/>
          <xs:element name="speed" minOccurs="0"
            type="xs:double"/>
          <xs:element name="heading" minOccurs="0"
            type="dyn:directionType"/>
          <xs:any namespace="##other" processContents="lax"
            minOccurs="0" maxOccurs="unbounded"/>
        </xs:sequence>
        <xs:anyAttribute namespace="##other" processContents="lax"/>
      </xs:restriction>
    </xs:complexContent>
  </xs:complexType>

  <xs:simpleType name="directionType">
    <xs:restriction base="dyn:doubleListType">
      <xs:minLength value="1"/>
      <xs:maxLength value="2"/>
    </xs:restriction>
  </xs:simpleType>

  <xs:simpleType name="doubleListType">
    <xs:list itemType="xs:double"/>
  </xs:simpleType>

</xs:schema>
```


5. Security Considerations

This document defines additional location elements carried by PIDF-LO. These additional elements provide greater reason to observe the privacy and security considerations described in [RFC 4119 \(Peterson, J., "A Presence-based GEOPRIV Location Object Format," December 2005.\)](#) [RFC4119]. No further privacy or security measures are necessary. RFC 4119 points back to RFC 3694 [\[RFC3694\] \(Danley, M., Mulligan, D., Morris, J., and J. Peterson, "Threat Analysis of the Geopriv Protocol," February 2004.\)](#) and RFC 3693 [\[RFC3693\] \(Cuellar, J., Morris, J., Mulligan, D., Peterson, J., and J. Polk, "Geopriv Requirements," February 2004.\)](#) to describe the threat model and the security requirements imposed on the GEOPRIV architecture for sharing location information as result of the threat model. It is important to note that these two documents often refer to threats related to the current location information of a presentity, while this document introduces dynamic information that may be used by attackers to anticipate the future location of a presentity. While already a series of location snapshots is likely to offer information for guessing the future location of a presentity it has to be said that including more information in a PIDF-LO does increase the severity of an information leak. Those who deploy location based services are in general strongly advised to provide their users with ways to control the distribution of location information to those who have been authorized to see it.

6. IANA Considerations

[TOC](#)

This section registers a new XML namespace (as described in [\[RFC3688\] \(Mealling, M., "The IETF XML Registry," January 2004.\)](#)) and a new XML schema.

6.1. Dynamic Feature Extensions Namespace Registration

[TOC](#)

URI:

urn:ietf:params:xml:ns:pidf:dynamic"

Registrant Contact: IETF Geopriv Working Group, Hannes Tschofenig
(hannes.tschofenig@gmx.net).

XML:

```
BEGIN
<?xml version="1.0"?>
<!DOCTYPE html PUBLIC "-//W3C//DTD XHTML Basic 1.0//EN"
  "http://www.w3.org/TR/xhtml1-basic/xhtml1-basic10.dtd">
<html xmlns="http://www.w3.org/1999/xhtml">
<head>
  <title>Dynamic Feature Extensions Namespace</title>
</head>
<body>
  <h1>Namespace for Dynamic Feature Extensions to PIDF-L0</h1>
  <h2>urn:ietf:params:xml:ns:pidf:dynamic</h2>
  <p>See <a href="[URL of published RFC]">RFCXXXX
    [NOTE TO IANA/RFC-EDITOR:
      Please replace XXXX with the RFC number of this
      specification.]</a>.</p>
</body>
</html>
END
```

6.2. Dynamic Feature Extensions Schema Registration

[TOC](#)

URI: urn:ietf:params:xml:ns:pidf:dynamic

Registrant Contact: IETF Geopriv Working Group, Hannes Tschofenig
(hannes.tschofenig@gmx.net)

XML: The XML schema to be registered is contained in [Section 4](#)
([Dynamic Feature XML Schema](#)). Its first line is

```
<?xml version="1.0"?>
```

and its last line is

```
</xs:schema>
```

7. Acknowledgements

[TOC](#)

We would like to thank Klaus Darilion, Cullen Jennings, Rohan Mahy, Carl Reed, and Brian Rosen for their comments. Furthermore, we would like to thank Alexey Melnikov, Adrian Farrel, Tim Polk, Dan Romascanu for his IESG review comments, Avshalom Hourì for his Gen Art review, Hilarie Orman for her SECDIR review, and Joel Jaeggli for his Operations Directorate review.

8. References

[TOC](#)

8.1. Normative References

[TOC](#)

[RFC2119]	Bradner, S. , " Key words for use in RFCs to Indicate Requirement Levels ," BCP 14, RFC 2119, March 1997 (TXT , HTML , XML).
[RFC3688]	Mealling, M., " The IETF XML Registry ," BCP 81, RFC 3688, January 2004 (TXT).
[RFC4119]	Peterson, J., " A Presence-based GEOPRIV Location Object Format ," RFC 4119, December 2005 (TXT).

8.2. Informative References

[TOC](#)

[GeoShape]	Thomson, M. and C. Reed, "GML 3.1.1 PIDF-LO Shape Application Schema for use by the Internet Engineering Task Force (IETF)," Candidate OpenGIS Implementation Specification 06-142, Version: 0.0.9, December 2006.
[RFC2778]	Day, M. , Rosenberg, J. , and H. Sugano , " A Model for Presence and Instant Messaging ," RFC 2778, February 2000 (TXT).
[RFC3693]	Cuellar, J., Morris, J., Mulligan, D., Peterson, J., and J. Polk, " Geopriv Requirements ," RFC 3693, February 2004 (TXT).
[RFC3694]	Danley, M., Mulligan, D., Morris, J., and J. Peterson, " Threat Analysis of the Geopriv Protocol ," RFC 3694, February 2004 (TXT).
[RFC3863]	Sugano, H., Fujimoto, S., Klyne, G., Bateman, A., Carr, W., and J. Peterson, " Presence Information Data Format (PIDF) ," RFC 3863, August 2004 (TXT).
[RFC4079]	

	Peterson, J., " A Presence Architecture for the Distribution of GEOPRIV Location Objects ," RFC 4079, July 2005 (TXT).
[RFC5491]	Winterbottom, J., Thomson, M., and H. Tschofenig, " GEOPRIV Presence Information Data Format Location Object (PIDF-LO) Usage Clarification, Considerations, and Recommendations ," RFC 5491, March 2009 (TXT).

Appendix A. Earth Centered, Earth Fixed Direction Vectors

[TOC](#)

The absolute orientation or heading of a presentity depends on its latitude and longitude. The following vectors can be used to determine the absolute direction in the WGS 84 Earth Centered, Earth Fixed (X, Y, Z) coordinate space.

The direction of North as a unit vector in ECEF coordinates is:

$$\text{North} = \begin{bmatrix} -1 * \sin(\text{latitude}) * \cos(\text{longitude}), \\ -1 * \sin(\text{latitude}) * \sin(\text{longitude}), \\ \cos(\text{latitude}) \end{bmatrix}$$

The direction of "up" (the upward normal of the horizontal plane) as a unit vector in ECEF coordinates is:

$$\text{Up} = \begin{bmatrix} \cos(\text{latitude}) * \cos(\text{longitude}), \\ \cos(\text{latitude}) * \sin(\text{longitude}), \\ \sin(\text{latitude}) \end{bmatrix}$$

Authors' Addresses

[TOC](#)

	Henning Schulzrinne
	Columbia University
	Department of Computer Science
	450 Computer Science Building, New York, NY 10027
	US
Phone:	+1 212 939 7004
Email:	hgs@cs.columbia.edu
URI:	http://www.cs.columbia.edu/
	Vishal Singh
	Columbia University
	Department of Computer Science
	450 Computer Science Building, New York, NY 10027
	US

Email:	vs2140@cs.columbia.edu
URI:	http://www.cs.columbia.edu/~vs2140
	Hannes Tschofenig
	Nokia Siemens Networks
	Linnoitustie 6
	Espoo 02600
	Finland
Phone:	+358 (50) 4871445
Email:	Hannes.Tschofenig@gmx.net
URI:	http://www.tschofenig.priv.at/
	Martin Thomson
	Andrew Corporation
	Wollongong
	NSW Australia
Email:	martin.thomson@andrew.com