

Audio/Video Transport Working Group
Internet-Draft
Intended status: Standards Track
Expires: April 22, 2016

V. Singh, Ed.
callstats.io
C. Perkins
University of Glasgow
A. Clark
Telchemy
R. Huang
Huawei
October 20, 2015

RTP Control Protocol (RTCP) Extended Report (XR) Block for Independent
Reporting of Burst/Gap Discard Metric
draft-singh-xrblock-independent-burst-gap-discard-01

Abstract

This document defines an RTP Control Protocol (RTCP) Extended Report (XR) block that allows the reporting of burst and gap discard metrics independently of the burst and gap loss metrics for use in a range of RTP applications.

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <http://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on April 22, 2016.

Copyright Notice

Copyright (c) 2015 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents

Internet-Draft

RTCP XR Burst/Gap Discard

October 2015

carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

Table of Contents

1.	Introduction	2
1.1.	Burst-Gap Discard Metrics Block	2
1.2.	RTCP and RTCP Extended Reports	3
1.3.	Performance Metrics Framework	3
1.4.	Applicability	4
2.	Terminology	4
3.	Burst/Gap Discard Metrics Block	5
3.1.	Report Block Structure	5
3.2.	Definition of Fields in Burst/Gap Discard Metrics Block	5
3.3.	Derived Metrics Based on the Reported Metrics	7
4.	Considerations for Voice-over-IP Applications	8
5.	SDP Signaling	8
5.1.	SDP rtcp-xr Attribute Extension	8
5.2.	Offer/Answer Usage	9
6.	IANA Considerations	9
6.1.	New RTCP XR Block Type Value	9
6.2.	New RTCP XR SDP Parameter	9
6.3.	Contact Information for Registrations	9
7.	Security Considerations	9
8.	Contributors	9
9.	Acknowledgments	10
10.	References	10
10.1.	Normative References	10
10.2.	Informative References	10
Appendix A.	Metrics Represented Using the Template from RFC 6390	12

[1.](#) Introduction

[1.1.](#) Burst-Gap Discard Metrics Block

This document defines a new block type that extends the metrics defined in [[RFC7003](#)], the metrics in this report block can be used in a range of RTP applications. The new block type reports the proportion of packets discarded by the jitter buffer at the receiver in a burst and number of packets discarded depends on the dejitter

buffer algorithm implemented by the endpoint.

The new report block defined in this document is different from the one defined in [\[RFC7003\]](#). The metrics in [\[RFC7003\]](#) depends on the metrics in the burstgap loss metric defined in [\[RFC6958\]](#).

Consequently, an endpoint using [\[RFC7003\]](#) MUST report it along with [\[RFC6958\]](#) for it to be useful. The combined usage is useful when an endpoint observes correlated packet losses and discard. However, when the burst of packet losses and discards do not occur simultaneously, the application may prefer a concise report block that just reports the burstgap of discarded packets. The report block in this document provides the complete information and does not require additional report blocks. That is, this block reports: the total number of packets discarded, the total burst duration, and the total number of bursts, all of these metrics are missing in [\[RFC7003\]](#).

This block provides information on transient network issues. Burst/gap metrics are typically used in cumulative reports; however, they may also be used in interval reports (see the Interval Metric flag in [Section 3.2](#)). The variation in the number of packet discard in a burst affects the user experience. Based on the metrics reported in the block, the sending endpoint may change the packetisation interval, vary the bitrate, etc. The report may additionally be used for diagnostics [\[RFC6792\]](#). The metric belongs to the class of transport-related end-system metrics defined in [\[RFC6792\]](#).

The definitions of "burst", "gap", "loss", and "discard" are consistent with the definitions in [\[RFC3611\]](#). To accommodate the range of jitter buffer algorithms and packet discard logic that may be used by implementors, the method used to distinguish between bursts and gaps shall use an equivalent method to that defined in [Section 4.7.2 of \[RFC3611\]](#). Note that reporting the specific jitter buffer algorithms and/or packet discard logic is out of the scope of this document.

[1.2](#). RTCP and RTCP Extended Reports

The use of RTCP for reporting is defined in [\[RFC3550\]](#). [\[RFC3611\]](#) defined an extensible structure for reporting using an RTCP Extended Report (XR). This document defines a new Extended Report block for

use with [\[RFC3550\]](#) and [\[RFC3611\]](#).

[1.3.](#) Performance Metrics Framework

The Performance Metrics Framework [\[RFC6390\]](#) provides guidance on the definition and specification of performance metrics. The RTP Monitoring Framework [\[RFC6792\]](#) provides guidelines for reporting block format using RTCP XR. The metrics block described in this document is in accordance with the guidelines in [\[RFC6390\]](#) and [\[RFC6792\]](#).

[1.4.](#) Applicability

These metrics are applicable to a range of RTP applications that contain de-jitter buffers [\[RFC5481\]](#) at the receiving end to smooth variation in packet-arrival time and don't use stream repair means, e.g., Forward Error Correction (FEC) [\[I-D.ietf-payload-flexible-fec-scheme\]](#) and/or retransmission [\[RFC4588\]](#).

[2.](#) Terminology

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [RFC 2119](#) [\[RFC2119\]](#).

In addition, the following terms are defined:

Received, Lost, and Discarded

A packet shall be regarded as "lost" if it fails to arrive within an implementation-specific time window. A packet that arrives within this time window but is too early to be played out, too late to be played out, or thrown away before playout due to packet duplication or redundancy shall be regarded as discarded. A packet shall not be regarded as discarded if it arrives within this time window but is dropped during decoding by some higher-layer decoder, e.g., due to a decoding error. A packet shall be classified as one of received (or OK), discarded, or lost. The metric "cumulative number of packets lost" defined in [\[RFC3550\]](#)

reports a count of packets lost from the media stream (single synchronization source (SSRC) within a single RTP session). Similarly, the metric "number of packets discarded" defined in [[RFC7002](#)] reports a count of packets discarded from the media stream (single SSRC within a single RTP session) arriving at the receiver. Another metric, defined in [[RFC5725](#)], is available to report on packets that are not recovered by any repair techniques that may be in use. Note that the term "discard" defined here builds on the "discard" definition in [[RFC3611](#)] but extends the concept to take into account packet duplication and reports different types of discard counts [[RFC7002](#)].

Bursts and Gaps

The terms "burst" and "gap" are used in a manner consistent with that of RTCP XR [[RFC3611](#)]. RTCP XR views an RTP stream as being divided into bursts, which are periods during which the discard rate is high enough to cause noticeable quality degradation (generally over 5 percent discard rate), and gaps, which are

periods during which discarded packets are infrequent and hence quality is generally acceptable.

[3.](#) Burst/Gap Discard Metrics Block

Metrics in this block report on burst/gap discard in the stream arriving at the RTP system. Measurements of these metrics are made at the receiving end of the RTP stream. Instances of this metrics block use the synchronization source (SSRC) to refer to the separate auxiliary Measurement Information Block [[RFC6776](#)], which describes measurement periods in use (see [[RFC6776](#)], [Section 4.2](#)).

This metrics block relies on the measurement period in the Measurement Information Block indicating the span of the report. Senders MUST send this block in the same compound RTCP packet as the Measurement Information Block. Receivers MUST verify that the measurement period is received in the same compound RTCP packet as this metrics block. If not, this metrics block MUST be discarded.

[3.1.](#) Report Block Structure

The structure of the Burst/Gap Discard Metrics Block is as follows.




Figure 1: Report Block Structure

3.2. Definition of Fields in Burst/Gap Discard Metrics Block

Block Type (BT): 8 bits

A Burst/Gap Discard Metrics Block is identified by the constant IBGD.

[Note to RFC Editor: Please replace IBGD with the IANA provided RTCP XR block type for this block.]

Interval Metric flag (I): 2 bits

This field is used to indicate whether the burst/gap discard metrics are Sampled, Interval, or Cumulative metrics [[RFC6792](#)]:

I=10: Interval Duration - the reported value applies to the most recent measurement interval duration between successive metrics reports.

I=11: Cumulative Duration - the reported value applies to the accumulation period characteristic of cumulative measurements.

I=01: Sampled Value - the reported value is a sampled instantaneous value.

In this document, burst/gap discard metrics can only be measured over definite intervals and cannot be sampled. Also, the value I=00 is reserved for future use. Senders MUST NOT use the values I=00 or I=01. If a block is received with I=00 or I=01, the receiver MUST discard the block.

Reserved (resv): 6 bits

These bits are reserved. They MUST be set to zero by senders and ignored by receivers (see [\[RFC6709\], Section 4.2](#)).

Block Length: 16 bits

The length of this report block in 32-bit words, minus one. For the Burst/Gap Discard Metrics Block, the block length is equal to 5. The block MUST be discarded if the block length is set to a different value.

SSRC of Source: 32 bits

As defined in [Section 4.1 of \[RFC3611\]](#).

Threshold: 8 bits

The Threshold is equivalent to Gmin in [\[RFC3611\]](#), i.e., the number of successive packets that must not be discarded prior to and following a discard packet in order for this discarded packet to be regarded as part of a gap. Note that the Threshold is set in accordance with the Gmin calculation defined in [Section 4.7.2 of \[RFC3611\]](#).

Sum of Burst Durations (ms): 24 bits

The total duration of bursts of discarded packets in the period of the report (Interval or Cumulative).

The measured value is an unsigned value. If the measured value exceeds 0xFFFFFD, the value 0xFFFFFE MUST be reported to indicate an over-range measurement. If the measurement is unavailable, the

value 0xFFFFFFFF MUST be reported.

Packets Discarded in Bursts: 24 bits

The total number of packets discarded during discard bursts, as defined in [Section 3.2 of \[RFC7002\]](#).

Number of Bursts: 16 bits

The number of discard bursts in the period of the report (Interval or Cumulative).

The measured value is an unsigned value. If the measured value exceeds 0xFFFFD, the value 0xFFFFE MUST be reported to indicate an over-range measurement. If the measurement is unavailable, the value 0xFFFF MUST be reported.

Total Packets Expected in Bursts: 24 bits

The total number of packets expected during discarded bursts (that is, the sum of received packets and lost packets). The metric is defined in [\[RFC7003\]](#).

Discard Count: 32 bits

Number of packets discarded over the period (Interval or Cumulative) covered by this report, as defined in [Section 3.2 of \[RFC7002\]](#).

[3.3](#). Derived Metrics Based on the Reported Metrics

The metrics described here are intended to be used in conjunction with information from the Measurement Information Block [\[RFC6776\]](#).

These metrics provide the following information relevant to statistical parameters (depending on cumulative or interval measures), for example:

- o The average discarded burst size, which can be calculated by

dividing the metric "Packets Discarded in Bursts" with the "Number of Bursts".

- o The average burst duration, which can be calculated by dividing the metric "Sum of Burst Durations (ms)" with the "Number of bursts".

4. Considerations for Voice-over-IP Applications

This metrics block is applicable to a broad range of RTP applications. Where the metric is used with a Voice-over-IP (VoIP) application and the stream repair means is not available, the following considerations apply.

RTCP XR views a call as being divided into bursts, which are periods during which the discard rate is high enough to cause noticeable call quality degradation (generally over 5 percent discard rate) and gaps, which are periods during which discarded packets are infrequent and hence call quality is generally acceptable.

If voice activity detection is used, the burst and gap duration shall be determined as if silence packets had been sent, i.e., a period of silence in excess of Gmin packets will terminate a burst condition.

The recommended value for the threshold Gmin in [\[RFC3611\]](#) results in a burst being a period of time during which the call quality is degraded to a similar extent to a typical pulse code modulation (PCM) severely errored second.

5. SDP Signaling

[\[RFC3611\]](#) defines the use of SDP (Session Description Protocol) [\[RFC4566\]](#) for signaling the use of XR blocks. XR blocks MAY be used without prior signaling.

5.1. SDP rtcp-xr Attribute Extension

This section augments the SDP [\[RFC4566\]](#) attribute "rtcp-xr" defined in [\[RFC3611\]](#) by providing an additional value of "xr-format" to signal the use of the report block defined in this document. The ABNF [\[RFC5234\]](#) syntax is as follows.

```
xr-format =/ xr-ind-bgd-block
```

```
xr-ind-bgd-block = "ind-burst-gap-discard"
```

[5.2.](#) Offer/Answer Usage

When SDP is used in Offer/Answer context, the SDP Offer/Answer usage defined in [\[RFC3611\]](#) for unilateral "rtcp-xr" attribute parameters applies. For detailed usage in Offer/Answer for unilateral parameters, refer to [Section 5.2 of \[RFC3611\]](#).

[6.](#) IANA Considerations

New block types for RTCP XR are subject to IANA registration. For general guidelines on IANA considerations for RTCP XR, refer to [\[RFC3611\]](#).

[6.1.](#) New RTCP XR Block Type Value

This document assigns the block type value IBGD in the IANA "RTP Control Protocol Extended Reports (RTCP XR) Block Type Registry" to the "Burst/Gap Discard Metrics Block".

[Note to RFC Editor: Please replace IBGD with the IANA provided RTCP XR block type for this block.]

[6.2.](#) New RTCP XR SDP Parameter

This document also registers a new parameter "ind-burst-gap-discard" in the "RTP Control Protocol Extended Reports (RTCP XR) Session Description Protocol (SDP) Parameters Registry".

[6.3.](#) Contact Information for Registrations

The contact information for the registrations is:

RAI Area Directors <rai-ads@tools.ietf.org>

[7.](#) Security Considerations

It is believed that this RTCP XR block introduces no new security considerations beyond those described in [\[RFC3611\]](#). This block does not provide per-packet statistics, so the risk to confidentiality documented in [Section 7](#), paragraph 3 of [\[RFC3611\]](#) does not apply.

[8.](#) Contributors

Qin Wu, Rachel Huang, and Alan Clark wrote [RFC7003](#), which this document extends.

9. Acknowledgments

The authors acknowledge the reviews and feedback provided by various people.

10. References

10.1. Normative References

- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), March 1997.
- [RFC3550] Schulzrinne, H., Casner, S., Frederick, R., and V. Jacobson, "RTP: A Transport Protocol for Real-Time Applications", STD 64, [RFC 3550](#), July 2003.
- [RFC3611] Friedman, T., Caceres, R., and A. Clark, "RTP Control Protocol Extended Reports (RTCP XR)", [RFC 3611](#), November 2003.
- [RFC4566] Handley, M., Jacobson, V., and C. Perkins, "SDP: Session Description Protocol", [RFC 4566](#), July 2006.
- [RFC5234] Crocker, D., Ed. and P. Overell, "Augmented BNF for Syntax Specifications: ABNF", STD 68, [RFC 5234](#), DOI 10.17487/[RFC5234](#), January 2008, <<http://www.rfc-editor.org/info/rfc5234>>.
- [RFC5725] Begen, A., Hsu, D., and M. Lague, "Post-Repair Loss RLE Report Block Type for RTP Control Protocol (RTCP) Extended Reports (XRs)", [RFC 5725](#), February 2010.
- [RFC6776] Clark, A. and Q. Wu, "Measurement Identity and Information Reporting Using a Source Description (SDS) Item and an RTCP Extended Report (XR) Block", [RFC 6776](#), October 2012.

10.2. Informative References

[I-D.ietf-payload-flexible-fec-scheme]

Singh, V., Begen, A., Zanaty, M., and G. Mandyam, "RTP Payload Format for Flexible Forward Error Correction (FEC)", [draft-ietf-payload-flexible-fec-scheme-01](#) (work in progress), October 2015.

- [RFC4588] Rey, J., Leon, D., Miyazaki, A., Varsa, V., and R. Hakenberg, "RTP Retransmission Payload Format", [RFC 4588](#), July 2006.

Singh, et al.

Expires April 22, 2016

[Page 10]

Internet-Draft

RTCP XR Burst/Gap Discard

October 2015

- [RFC5481] Morton, A. and B. Claise, "Packet Delay Variation Applicability Statement", [RFC 5481](#), DOI 10.17487/RFC5481, March 2009, <<http://www.rfc-editor.org/info/rfc5481>>.
- [RFC6390] Clark, A. and B. Claise, "Guidelines for Considering New Performance Metric Development", [BCP 170](#), [RFC 6390](#), October 2011.
- [RFC6709] Carpenter, B., Aboba, B., Ed., and S. Cheshire, "Design Considerations for Protocol Extensions", [RFC 6709](#), DOI 10.17487/RFC6709, September 2012, <<http://www.rfc-editor.org/info/rfc6709>>.
- [RFC6792] Wu, Q., Ed., Hunt, G., and P. Arden, "Guidelines for Use of the RTP Monitoring Framework", [RFC 6792](#), DOI 10.17487/[RFC6792](#), November 2012, <<http://www.rfc-editor.org/info/rfc6792>>.
- [RFC6958] Clark, A., Zhang, S., Zhao, J., and Q. Wu, "RTP Control Protocol (RTCP) Extended Report (XR) Block for Burst/Gap Loss Metric Reporting", [RFC 6958](#), May 2013.
- [RFC7002] Clark, A., Zorn, G., and Q. Wu, "RTP Control Protocol (RTCP) Extended Report (XR) Block for Discard Count Metric Reporting", [RFC 7002](#), September 2013.
- [RFC7003] Clark, A., Huang, R., and Q. Wu, "RTP Control Protocol (RTCP) Extended Report (XR) Block for Burst/Gap Discard Metric Reporting", [RFC 7003](#), September 2013.

[Appendix A](#). Metrics Represented Using the Template from [RFC 6390](#)

a. Threshold Metric

- * Defined in Appendix A.a of [[RFC7003](#)].

b. Sum of burst durations (ms)

- * Metric Name: Sum of Burst Durations with Discarded RTP Packets.
- * Metric Description: The total duration of bursts of discarded RTP packets in the period of the report.
- * Method of Measurement or Calculation: See [Section 3.1](#), Sum of Burst Durations definition.
- * Units of Measurement: See [Section 3.1](#), Sum of Burst Durations definition.
- * Measurement Point(s) with Potential Measurement Domain: See [Section 3](#), 1st paragraph.
- * Measurement Timing: See [Section 3](#), 2nd paragraph for measurement timing and [Section 3.1](#) for Interval Metric flag.

- * Use and Applications: See [Section 1.4](#).
- * Reporting Model: See [RFC 3611](#).
- c. Packets Discarded in Bursts Metric
 - * Defined in Appenix A.b of [[RFC7003](#)].
- d. Number of bursts
 - * Metric Name: Number of discard bursts in RTP.
 - * Metric Description: The total number of bursts with discarded RTP packets in the period of the report.
 - * Method of Measurement or Calculation: See [Section 3.1](#), Number of discard bursts definition.
 - * Units of Measurement: See [Section 3.1](#) for the Number of bursts definition.

- * Measurement Point(s) with Potential Measurement Domain: See [Section 3](#), 1st paragraph.
- * Measurement Timing: See [Section 3](#), 2nd paragraph for measurement timing and [Section 3.1](#) for Interval Metric flag.
- * Use and Applications: See [Section 1.4](#).
- * Reporting Model: See [RFC 3611](#).
- e. Total Packets Expected in Bursts Metric
 - * Defined in Appenix A.c of [[RFC7003](#)].
- f. Discard Count
 - * Defined in Appenix A.a of [[RFC7002](#)].

Authors' Addresses

Varun Singh (editor)
Nemu Dialogue Systems Oy
Runeberginkatu 4c A 4
Helsinki 00100
Finland

E-Mail: varun@callstats.io
URI: <http://www.callstats.io/>

Colin Perkins
University of Glasgow
School of Computing Science
Glasgow G12 8QQ
United Kingdom

E-Mail: csp@csperkins.org

Alan Clark
Telchemy Incorporated
2905 Premiere Parkway, Suite 280
Duluth, GA 30097
USA

E-Mail: alan.d.clark@telchemy.com

Singh, et al.

Expires April 22, 2016

[Page 13]

Internet-Draft

RTCP XR Burst/Gap Discard

October 2015

Rachel Huang
Huawei Technologies Co., Ltd.
101 Software Avenue, Yuhua District
Nanjing, Jiangsu 210012
China

E-Mail: Rachel@huawei.com

