Network Working Group

Internet-Draft
Intended status: Informational

Expires: March 16, 2014

R. Sinnema E. Wilde EMC Corporation September 12, 2013

eXtensible Access Control Markup Language (XACML) XML Media Type draft-sinnema-xacml-media-type-06

Abstract

This specification registers an XML-based media type for the eXtensible Access Control Markup Language (XACML).

Note to Readers

This draft should be discussed on the apps-discuss mailing list [1].

Online access to all versions and files is available on github [2].

Status of this Memo

This Internet-Draft is submitted in full conformance with the provisions of \underline{BCP} 78 and \underline{BCP} 79.

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at http://datatracker.ietf.org/drafts/current/.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on March 16, 2014.

Copyright Notice

Copyright (c) 2013 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to <u>BCP 78</u> and the IETF Trust's Legal Provisions Relating to IETF Documents

(http://trustee.jetf.org/license-info) in effect on the date of the date of the left of the lef

(http://trustee.ietf.org/license-info) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must

include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

Table of Contents

<u>1</u> .	Inti	roduct	clon																				3
<u>2</u> .	IAN	A Cons	siden	rat:	ions	· .																	3
2.	<u>1</u> .	XACMI	_ Med	dia	Тур	е	app	01:	ica	ati	Lor	1/>	kad	cm]	L+>	km]	L						3
<u>3</u> .	Seci	urity	Cons	side	erat	io	ns																6
<u>4</u> .	Chai	nge Lo	og .																				<u>6</u>
4.	<u>1</u> .	From	-05	to	-06	ò.																	<u>6</u>
<u>4</u> .	<u>2</u> .	From	-04	to	- 05	5.																	7
<u>4</u> .	<u>.3</u> .	From	-03	to	- 04	↓.																	7
<u>4</u> .	<u>.4</u> .	From	-02	to	-03	3.																	7
<u>4</u> .	<u>5</u> .	From	-01	to	-02	2.																	7
<u>4</u> .	<u>6</u> .	From	-00	to	-01	L.																	7
<u>4</u> .	<u>. 7</u> .	Vers	ions	pr	ior	to	I.	-D	- (90													7
$\underline{5}$. Normative References																					7		
$\underline{\text{Appendix } A}. \text{Acknowledgements}$																						9	
Auth	nors	' Addı	resse	es																			9

1. Introduction

The eXtensible Access Control Markup Language (XACML) [XACML-3] defines an architecture and a language for access control (authorization). The language consists of requests, responses, and policies. Clients sends a request to a server to query whether a given action should be allowed. The server evaluates the request against the available policies and returns a reponse. The policies implement the organization's access control requirements.

2. IANA Considerations

This specification registers an XML-based media type for the eXtensible Access Control Markup Language (XACML) that will be registered with the Internet Assigned Numbers Authority (IANA) following the "Media Type Specifications and Registration Procedures" [RFC6838]. The XACML media type represents an XACML request, response, or policy in the XML-based format defined by the core XACML specification [XACML-3].

2.1. XACML Media Type application/xacml+xml

This specification requests the registration of an XML-based media type for the eXtensible Access Control Markup Language (XACML).

2.1.1. Media Type Name

application

2.1.2. Subtype Name

xacml+xml

2.1.3. Required Parameters

none

2.1.4. Optional Parameters

charset: The charset parameter is the same as the charset parameter of application/xml [RFC3023], including the same default (see section 3.2).

version: The version parameter indicates the version of the XACML specification. It can be used for content negotiation when dealing with clients and servers that support multiple XACML versions. Its range is the range of published XACML versions. As of this writing

that is: 1.0 [XACML-1], 1.1 [XACML-1.1], 2.0 [XACML-2], and 3.0 [XACML-3]. These and future version identifiers must follow the OASIS patterns for versions [OASIS-Version]. If this parameter is not specified by the client, the server is free to return any version it deems fit. If a client cannot or does not want to deal with that, it should explicitly specify a version.

2.1.5. Encoding Considerations

Same as for application/xml [RFC3023].

2.1.6. Security Considerations

Per their specification, application/xacml+xml typed objects do not contain executable content. However, these objects are XML-based, and thus they have all of the general security considerations presented in section 10 of RFC 3023 [RFC3023].

XACML [XACML-3] contains information whose integrity and authenticity is important - identity provider and service provider public keys and endpoint addresses, for example. Sections "9.2.1 Authentication" and "9.2.4 Policy Integrity" in XACML [XACML-3] describe requirements and considerations for such authentication and integrity protection.

To counter potential issues, the publisher may sign application/ xacml+xml typed objects. Any such signature should be verified by the recipient of the data - both as a valid signature, and as being the signature of the publisher. The XACML v3.0 XML Digital Signature Profile [XACML-3-DSig] describes how to use XML-based digital signatures with XACML.

Additionally, various of the possible publication protocols, for example HTTPS, offer means for ensuring the authenticity of the publishing party and for protecting the policy in transit.

2.1.7. Interoperability Considerations

Different versions of XACML use different XML namespace URIS:

- o 1.0 & 1.1 use the urn:oasis:names:tc:xacml:1.0:policy XML namespace URI for policies, and the urn:oasis:names:tc:xacml:1.0:context XML namespace URI for requests and responses
- o 2.0 uses the urn:oasis:names:tc:xacml:2.0:policy XML namespace URI for policies, and the urn:oasis:names:tc:xacml:2.0:context XML namespace URI for requests and responses

o 3.0 uses the urn:oasis:names:tc:xacml:3.0:core:schema:wd-17 XML namespace URI for policies, requests, and responses

Signed XACML has a wrapping SAML 2.0 assertion [SAML-2], which uses the urn:oasis:names:tc:SAML:2.0:assertion namespace URI. Interoperability with SAML is defined by the SAML 2.0 Profile of XACML [XACML-3-SAML] for all versions of XACML.

2.1.8. Applications which use this media type

Potentially any application implementing or using XACML, as well as those applications implementing or using specifications based on XACML. In particular, applications using the REST Profile [XACML-REST] can benefit from this media type.

2.1.9. Magic number(s)

In general, the same as for application/xml [RFC3023]. In particular, the XML document element of the returned object will be one of xacml:Policy, xacml:PolicySet, context:Request, or context:Response. The xacml and context namespace prefixes bind to the respective namespaces URIs for the various versions of XACML as follows:

- 0 1.0 & 1.1: The xacml prefix maps to
 urn:oasis:names:tc:xacml:1.0:policy, the context prefix maps to
 urn:oasis:names:tc:xacml:1.0:context
- o 2.0: The xacml prefix maps to urn:oasis:names:tc:xacml:2.0:policy, the context prefix maps to urn:oasis:names:tc:xacml:2.0:context
- o 3.0: Both the xacml and context prefixes map to the namespace URI urn:oasis:names:tc:xacml:3.0:core:schema:wd-17

For signed XACML [XACML-3-DSig], the XML document element is saml: Assertion, where the saml prefix maps to the SAML 2.0 namespace URI urn:oasis:names:tc:SAML:2.0:assertion [SAML-2]

2.1.10. File extension(s)

none

2.1.11. Macintosh File Type Code(s)

none

2.1.12. Person & email address to contact for further information

This registration is made on behalf of the OASIS eXtensible Access Control Markup Language Technical Committee (XACMLTC). Please refer to the XACMLTC website for current information on committee chairperson(s) and their contact addresses:

http://www.oasis-open.org/committees/xacml/. Committee members
should submit comments and potential errata to the
xacml@lists.oasis-open.org list. Others should submit them by
filling out the web form located at http://www.oasis-open.org/committees/comments/form.php?wg_abbrev=xacml.

Additionally, the XACML developer community email distribution list, xacml-dev@lists.oasis-open.org, may be employed to discuss usage of the application/xacml+xml MIME media type. The xacml-dev mailing list is publicly archived here:

http://www.oasis-open.org/archives/xacml-dev/. To post to the xacml-dev mailing list, one must subscribe to it. To subscribe, visit the OASIS mailing list page at http://www.oasis-open.org/mlmanage/.

2.1.13. Intended Usage

Common

2.1.14. Author/Change Controller

The XACML specification sets are a work product of the OASIS eXtensible Access Control Markup Language Technical Committee (XACMLTC). OASIS and the XACMLTC have change control over the XACML specification sets.

3. Security Considerations

The security considerations for this specifications are described in <u>Section 2.1.6</u> of the media type registration.

4. Change Log

Note to RFC Editor: Please remove this section before publication.

4.1. From -05 to -06

o Minor changes in wording.

4.2. From -04 to -05

o Incorporating feedback from Oscar Koeroo (ISE review report).

4.3. From -03 to -04

- o Creating a proper "IANA Considerations" section.
- o Creating a proper "Security Considerations" section.

4.4. From -02 to -03

o Switched category from "std" to "info".

4.5. From -01 to -02

- o Added new introduction text.
- o Improved definition of version numbers and their handling.

4.6. From -00 to -01

- o Added new introduction text.
- o Changed reference from $\underline{\mathsf{RFC}}$ 4288 to $\underline{\mathsf{RFC}}$ 6838 (updated RFC for media type registrations).

4.7. Versions prior to I-D -00

Prior to being published as a I-D document, this document was published and revised as an OASIS document with the following versions:

- o 2012-02-29 (WD01): Initial revision with one media type.
- o 2012-04-23 (WD02): Added JSON media type.
- o 2012-04-24 (WD03): Fixed layout, typos, and references. Better defined the allowable range of values for the version parameter.

5. Normative References

[OASIS-Version]

Organization for the Advancement of Structured Information Standards, "OASIS Naming Directives 1.3", December 2012, < http://docs.oasis-open.org/specGuidelines/ndr/ namingDirectives.html#Version>.

- [RFC3023] Murata, M., St. Laurent, S., and D. Kohn, "XML Media Types", RFC 3023, January 2001.
- [RFC6838] Freed, N., Klensin, J., and T. Hansen, "Media Type Specifications and Registration Procedures", <u>BCP 13</u>, <u>RFC 6838</u>, January 2013.
- [SAML-2] Organization for the Advancement of Structured Information Standards, "Security Assertion Markup Language (SAML) Version 2.0. OASIS Standard", March 2005, http://docs.oasis-open.org/security/saml/v2.0/saml-core-2.0-os.pdf>.
- [XACML-1] Organization for the Advancement of Structured Information Standards, "eXtensible Access Control Markup Language (XACML) Version 1.0. OASIS Standard", February 2003, https://www.oasis-open.org/committees/download.php/2406/oasis-xacml-1.0.pdf>.

[XACML-1.1]

Organization for the Advancement of Structured Information Standards, "eXtensible Access Control Markup Language (XACML) Version 1.1. OASIS Committee Specification", August 2003, http://www.oasis-open.org/committees/xacml/repository/cs-xacml-specification-1.1.pdf>.

- [XACML-2] Organization for the Advancement of Structured Information Standards, "eXtensible Access Control Markup Language (XACML) Version 2.0. OASIS Standard", February 2005, https://docs.oasis-open.org/xacml/2.0/ access_control-xacml-2.0-core-spec-os.pdf>.
- [XACML-3] Organization for the Advancement of Structured Information Standards, "eXtensible Access Control Markup Language (XACML) Version 3.0. OASIS Standard", January 2013, http://docs.oasis-open.org/xacml/3.0/xacml-3.0-core-spec-os-en.pdf>.

[XACML-3-DSig]

Organization for the Advancement of Structured Information Standards, "XACML v3.0 XML Digital Signature Profile Version 1.0. OASIS Committee Specification 01", August 2010, http://docs.oasis-open.org/xacml/3.0/xacml-3.0-dsig-v1-spec-cs-01-en.pdf>.

[XACML-3-SAML]

Organization for the Advancement of Structured Information Standards, "SAML 2.0 Profile of XACML, Version 2.0. OASIS

Committee Specification 01", August 2010, <http://docs.oasis-open.org/xacml/3.0/xacml-profile-saml2.0-v2-spec-cs-01-en.pdf>.

[XACML-REST]

Organization for the Advancement of Structured Information Standards, "REST Profile of XACML v3.0 Version 1.0. OASIS Committee Specification Draft 01", November 2012, http://docs.oasis-open.org/xacml/xacml-rest/v1.0/ xacml-rest-v1.0.pdf>.

- [1] <https://www.ietf.org/mailman/listinfo/apps-discuss>
- [2] <https://github.com/dret/I-D/tree/master/xacml-media-type>

Appendix A. Acknowledgements

The following individuals have participated in the creation of this specification and are gratefully acknowledged: Oscar Koeroo (Nikhef), Erik Rissanen (Axiomatics), and Jonathan Robie (EMC).

Authors' Addresses

Remon Sinnema EMC Corporation

Email: remon.sinnema@emc.com

URI: http://securesoftwaredev.com/

Erik Wilde EMC Corporation 6801 Koll Center Parkway Pleasanton, CA 94566 U.S.A.

Phone: +1-925-6006244 Email: erik.wilde@emc.com

URI: http://dret.net/netdret/