

INTERNET-DRAFT
Intended Status: Informational
Expires: December 8, 2018

P. Spinosa
(ICT consultant)
E. Francesconi
ITTIG/CNR
C. Lupo
(ICT consultant)
June 6, 2018

**A Uniform Resource Name (URN) Namespace
for Sources of Law (LEX)
draft-spinosa-urn-lex-13.txt**

Status of this Memo

This Internet-Draft is submitted to IETF in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF), its areas, and its working groups. Note that other groups may also distribute working documents as Internet-Drafts.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

The list of current Internet-Drafts can be accessed at <http://www.ietf.org/1id-abstracts.html>

The list of Internet-Draft Shadow Directories can be accessed at <http://www.ietf.org/shadow.html>

This Internet-Draft will expire on December 8, 2018.

Copyright Notice

Copyright (c) 2017 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document.

Abstract

This document describes a Uniform Resource Name (URN) Namespace Identification (NID) convention as prescribed by the Internet Engineering Task Force (IETF) for identifying, naming, assigning, and managing persistent resources in the legal domain.

Table of Contents

1	Introduction	5
1.1	The Purpose of Namespace "lex"	5
1.2	Entities Supporting this Standard	5
1.3	The Context	5
1.4	General Characteristics of the System	8
1.5	Linking a LEX Name to a Document	9
1.6	Use of LEX Names in References	10
1.7	Definitions	10
1.8	Terminology	11
1.9	Syntax Used in this Document	11
2	Registration Template	11
3	Specifications of Registration Template	15
3.1	Identifier structure	15
3.2	Conformance with URN Syntax	16
3.3	Validation Mechanism	16
3.4	Scope	16
4	General Syntax and Features of the LEX Identifier	16
4.1	Allowed and Not Allowed Characters	16
4.2	Reserved Characters	17
4.3	Case Sensitivity	17
4.4	National Characters and Diacritic Signs	17
4.5	Abbreviations	18
4.6	Date Format	18
5	Specific Syntax and Features of the LEX Identifier	18
5.1	Spaces, Connectives and Punctuation Marks	19
5.2	Acronyms	19
5.3	Ordinal Numbers	19
6	Creation of the Source of Law LEX Identifier	19
6.1	Basic Principles	19
6.2	Model of Sources of Law Representation	20
6.3	The Structure of the Local Name	20
6.4	Structure of the Document Identifier at Work Level	21
6.5	Aliases	22
6.6	Structure of the Document Identifier at Expression Level	23
6.7	Structure of the Document Identifier at Manifestation Level	24
6.8	Sources of Law References	26
7	The Procedure of Uniform Names Assignment	27
7.1	Specifying the <jurisdiction> Element of the LEX Identifier	27
7.2	Jurisdictional Registrar for Names Assignment	27
7.3	Identifier Uniqueness	28
7.4	Identifier Persistence Considerations	28
8	Principles of the Resolution Service	29
8.1	The General Architecture of the System	29
8.2	Catalogues for Resolution	30

P. Spinosa

Expires December 8, 2018

[Page 3]

8.3	Suggested Resolver Behaviour	31
9	Namespace Considerations	31
10	Community Considerations	32
11	IANA Considerations	32
11.1	NID Registration	32
11.2	Jurisdiction-code Registration	33
12	References	34
12.1	Normative References	34
12.2	Informative References	35
13	Acknowledgements	35
14	Author's Addresses	36
Attachment A -- Summary of the Syntax of the Uniform Names of the "lex" Namespace		37
Attachment B -- Specific Syntax of the Identifier at Work Level .		41
B1	The <authority> Element	41
B1.1	Indication of the Authority	41
B1.2	Multiple Issuers	41
B1.3	Indication of the Issuer	41
B1.4	Indication of the Body	41
B1.5	Indication of the Function	42
B1.6	Conventions for the Authority	42
B2	The <measure> Element	42
B2.1	Criteria for the Indication of the Type of Measure	42
B2.2	Further Specification to the Type of Measure	43
B2.3	Aliases for Sources of Law with Different Normative References	43
B2.4	Relations between Measure and Authority in the Aliases .	43
B3	The <details> Element	44
B3.1	Indication of the Details	44
B3.2	Multiple Dates	44
B3.3	Unnumbered Measures	45
B3.4	Multiple Numbers	45
B4	The <annex> Element	46
B4.1	Formal Annexes	46
B4.2	Annexes of Annexes	46
Attachment C -- Specific Syntax of the <version> Element of the Expression		47
C1	The <version> Element	47
C1.1	Different Versions of a Legislative Document	47
C1.2	Identification of the Version	47
Attachment D -- Http LEX Identifier		50
D1	Http URI	50
D2	The Http LEX Identifier Structure	51
D3	The Http LEX Identifier at Work Level	52
D4	The Http LEX Identifier at Expression Level	52
D5	The Http LEX Identifier at Manifestation Level	53

P. Spinosa

Expires December 8, 2018

[Page 4]

1 Introduction

1.1 The Purpose of Namespace "lex"

The purpose of the "lex" namespace is to assign an unequivocal identifier, in standard format, to documents that are sources of law. To the extent of this namespace, "sources of law" include any legal document within the domain of legislation, case law and administrative acts or regulations; moreover potential "sources of law" (acts under the process of law formation, as bills) are included as well. Therefore "legal doctrine" is explicitly not covered.

The identifier is conceived so that its recommended construction depends only on the characteristics (details) of the document itself and is, therefore, independent from the document's on-line availability, its physical location, and access mode. The identifier itself is assigned by the jurisdiction that owns the identified document. Even a document that is not available online at all may still have a URN LEX that identifies it.

This identifier will be used as a way to represent the references (and more generally, any type of relation) among the various sources of law. In an on-line environment with resources distributed among different Web publishers, uniform resource names allow simplified global interconnection of legal documents by means of automated hypertext linking. LEX URNs are therefore particularly useful when they can be mapped into or associated with locators such as HTTP URLs.

1.2 Entities Supporting this Standard

The following entities support this proposal at the time of publication:

- ITTIG/CNR (Institute of Legal Information Theory and Techniques of the Italian National Research Council) - Italy;
- National Centre for ICT in Public Administration - Italy;
- PRODASEN - IT Department of the Federal Senate - Brazil;
- LII (Legal Information Institute), Cornell Law School - USA

1.3 The Context

In the last few years a number of initiatives have arisen in the field of legal document management.

Since 2001 the Italian Government, through the National Center for Information Technology in the Public Administration, the Ministry of Justice and ITTIG-CNR (the Institute of Legal Information Theory and

Techniques of the Italian National Research Council) promoted the NormeInRete project. It was aimed at introducing standards for sources of law description and identification using XML and URN techniques.

Other national initiatives in Europe introduced standards for the description of legal sources [[FRAN](#)]: for example the Metalex project, promoted by the University of Amsterdam and adopted by the Dutch Tax and Customs Administration, the Belgian Public Centers for Welfare and others; LexDania project in Denmark supported by the Danish Ministry of Justice; CHLexML in Switzerland developed by COPIUR, the Coordination Office for the Electronic Publication of Legal Data Federal Office of Justice; eLaw in Austria mainly coordinated by the Austrian Parliament.

Such initiatives, based in synergies between government, national research institutes, and universities, have defined national XML standards for legal document management, as well as schemes for legal document identification.

Outside Europe, similar initiatives have faced similar problems. For example, the Brazilian Senate carried out a feasibility study to provide unique and transparent identifiers to sources of law on the basis of the IFLA-FRBR model.

Similarly, the Akoma Ntoso (Architecture for Knowledge-Oriented Management of African Normative Texts using Open Standards and Ontologies) project provides a set of guidelines for e-Parliament services in a Pan-African context by proposing an XML document schema providing sophisticated description possibilities for several Parliamentary document types (including bills, acts and parliamentary records, etc.).

Finally, the Tasmanian Government provided advanced legislative information services through the EnAct project. It gave searchable consolidated Tasmanian legislation by automating much of the legislative drafting and consolidation process, as well as using SGML document representation. Numerous less-visible efforts in the United States and elsewhere have struggled with similar issues.

Several of these identifiers are based on a URN schema. The first national standard was defined in Italy within the NormeInRete project; to this the Brazilian Lexml standard followed. Denmark, Hungary, Slovenia and Switzerland expressed their interest in URN identifier for legislation as well. All these standards have a common internal structure, regarding both the hierarchy and the elements content.

In today's information society the processes of political, social and economic integration of European Union member states as well as the

P. Spinosa

Expires December 8, 2018

[Page 6]

increasing integration of the world-wide legal and economic processes are causing a growing interest in exchanging legal information knowledge at national and trans-national levels.

The growing desire for improved quality and accessibility of legal information amplifies the need for interoperability among legal information systems across national boundaries. A common open standard used to identify sources of law at international level is an essential prerequisite for interoperability.

Interest groups within several countries have already expressed their intention to adopt a shared solution based on a URN technique.

The need for a unequivocal identifier of sources of law in different EU Member States, based on open standards and able to provide advanced modalities of document hyper-linking, has been expressed in several conferences by representatives of the Publications Office of the European Union (OP), with the aim of promoting interoperability among national and European institution information systems. Similar concerns have been raised by international groups concerned with free access to legal information, and the Permanent Bureau of the Hague Conference on Private International Law is considering a resolution that would encourage member states to "adopt neutral methods of citation of their legal materials, including methods that are medium-neutral, provider-neutral and internationally consistent". In a similar direction the CEN Metalex initiative is moving, at European level, towards the definition of a standard interchange format for sources of law, including recommendations for defining naming conventions to them.

The need of unequivocal identifiers for sources of law is of particular interest also in the domain of case law. Such need is extremely felt within both common law systems, where cases are the main law sources, and civil law systems, for the importance of providing an integrated access to cases and legislation, as well as to track the relationships between them. This domain is characterized by a high degree of fragmentation in case law information systems, which usually lack interoperability.

Recently in the European Union, the community institutions have stressed the need for citizens, businesses, lawyers, prosecutors and judges to become more aware not only of (directly applicable) EU law, but also of the various national legal systems. The growing importance of national judiciaries for the application of Community law was stressed in the resolution of the European Parliament of 9 July 2008 on the role of the national judge in the European judicial system.

Similarly the European e-Justice action plans 2009-2013 and 2014-2018 of the Council of the European Union underlined the importance of cross-border access to national case law, as well as the need for its standardisation, in view of an integrated access in a decentralized

P. Spinosa

Expires December 8, 2018

[Page 7]

architecture. In this view the Working Party on Legal Data Processing (e-Law) of the Council of the European Union formed a task group to study the possibilities for improving cross-border access to national case law. Taking notice of the report of the Working Party's task group the Council of the EU decided in 2009 to elaborate on a uniform, European system for the identification of case law (ECLI: European Case-Law Identifier) and uniform Dublin Core-based set of metadata.

More recently the Council of the European Union invited the Member States to introduce in the legal information systems the European Legislation Identifier (ELI), an http-based Semantic Web oriented identification system for European Union and Member States legislation.

LEX identifier is conceived to be general enough, so to provide guidance at the core of the standard and sufficient flexibility to cover a wide variety of needs for identifying all the legal documents of different nature, namely legislative, case-law and administrative acts. Moreover, it can be effectively used within a federative environment where different publishers (public and private) can provide their own items of an act (that is there is more than one manifestation of the same act).

However specifications and syntax rules of LEX identifier can be used also for http-based naming convention (Appendix D) to cope with different requirements in legal information management, for example the need of having an identifier compliant with the Linked Open Data principles.

This document supplements the required name syntax with a suggested naming convention that interprets all these recommendations into an original solution for sources of law identification.

1.4 General Characteristics of the System

Registrants wish now to promote interoperability among legal information systems by the definition of a namespace convention and structure that will create and manage identifiers for legal documents. The identifiers will be:

- globally unique
- transparent
- bidirectional
- persistent
- location-independent, and
- language-neutral.

These qualities will facilitate legal document management as well as provide a mechanism of stable cross-collections and cross-country references.

P. Spinosa

Expires December 8, 2018

[Page 8]

Transparency means that given an act and its relevant metadata (issuing authority, type of measure, etc.) it is possible to create the related urn identifier. Moreover this identifier is able to unequivocally identify the related act. These two properties makes the identification system bidirectional (from an act to its URN and from a URN to the related act).

Language-neutrality is an especially important feature that will promote adoption of the standard by organizations that must adhere to official-language requirements. The proposed standard will provide useful guidance to both public and private groups that create, promulgate, and publish legal documents. Registrants wish to minimize the potential for creating conflicting proprietary schemes, while preserving sufficient flexibility to allow for diverse document types and to respect the need for local control of collections by an equally diverse assortment of administrative entities.

As usual, the problem is to provide the right amount guidance at the core of the standard while providing sufficient flexibility to cover a wide variety of needs. The proposed LEX standard does this by splitting the identifier into parts. The first part uses a predetermined standard ("country/jurisdiction name standard") to specify the country (or more generally the jurisdiction) of origin for the legal document being identified; the remainder ("local name") is intended for local use in identifying documents issued in that country or jurisdiction. This second part depends only on sources of law identification system operating in that nation and it is mainly composed by a formalized information related to the enacting authority, the type of measure, the details and possibly the annex.

The identification system based on uniform names SHOULD include:

- a schema for assigning names capable of representing unambiguously any addressed source of law, namely legislation, case law and administrative acts, issued by any authority (intergovernmental, supranational, national, regional and local) at any time (past, present and future);
- a resolution mechanism - in a distributed environment - that ties a uniform name to the on-line location of the corresponding resources.

This document only considers the first of these requirements. It also contains a few references to the architecture of the resolution service and to the corresponding software.

1.5 Linking a LEX Name to a Document

The LEX name is linked to the document through meta-information which may be specified:

- internally to the document itself through a specific element within

P. Spinosa

Expires December 8, 2018

[Page 9]

- an XML schema or by an HTML META tag;
- externally by means of an RDF triple, a specific attribute in a database, etc.

One of these modalities is necessary for enabling automated construction and updating of catalogues (distributed and centralized) and the implementation of resolvers that associate the uniform name of a document with its physical location(s). The standard assumes no particular relationship between the originator of the document, its publisher, and the implementer of catalogues or resolution services. They may be the same entity, or not.

1.6 Use of LEX Names in References

LEX names will be used on a large scale in references as a HREF attribute value of the hypertext link to the referred document.

This link can be created in two ways:

- by manually inserting, in the referring document, the link with the uniform name: this is a burdensome procedure especially for documents that are already on-line;
- by automatically constructing (either permanently or temporarily) the link with the uniform name, through reference parsers of a text: this is a more time-saving procedure even if subject to a certain percentage of errors, since references are not always accurate or complete. This solution could nevertheless be acceptable for already published documents.

In any case, whatever the method adopted is, new documents produced in XML format compliant with the relative DTD/XMLSchema, SHOULD express references through the uniform name of the document referred to.

1.7 Definitions

According to this document, the following terms are used in the following meaning:

- Source of Law:
is a general concept, and is used to refer to legislation, case law, regulations and administrative acts. In its broadest sense, the source of law is anything that can be conceived of as the originator of 'erga omnes' legal rules. In this document "source of law" refers also to acts during their formation cycle as bills that might or might not become sources of law;
- Jurisdictional Registrar:
is an organization which shares and defines in any country or jurisdiction the assignment of the main components of the resource identifier through which its uniqueness is guaranteed. This task includes the definition of possible jurisdiction unit and the primary elements (issuing authority and type of legal measure) of uniform name, according to the characteristics of its own state or

P. Spinosa

Expires December 8, 2018

[Page 10]

institution organization.

1.8 Terminology

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [[RFC2119](#)].

1.9 Syntax Used in this Document

This document uses the syntax common to many Internet RFCs, which is based on the ABNF (Augmented Backus-Naur Form) [[RFC5234](#)] meta-language.

2 Registration Template

Namespace Identifier:

"lex" requested according to [[RFC8141](#)].

Version:

1.0

Date:

2018-06-06

Registrant:

Institute of Legal Information Theory and Techniques (ITTIG)
Italian National Research Council (CNR)
Via de' Barucci, 20
50127 Florence
Italy
e-mail: lex@ittig.cnr.it
phone: +39 055 43995

contact: Enrico Francesconi
e-mail: enrico.francesconi@ittig.cnr.it

Purpose:

The purpose of the "lex" namespace is to assign an unequivocal identifier, in standard format, to documents that are sources of law.

In the last few years a number of institutional initiatives

have arisen in the field of legal document management. They were aimed at introducing standards for sources of law description and identification using XML and URI techniques, respectively (for more details see [Section 1.3](#)) LEX identifier is conceived to be general enough, so to provide guidance at the core of the standard and sufficient flexibility to cover a wide variety of needs for identifying all the legal documents of different nature, namely legislative, case-law and administrative acts. Moreover, it can be effectively used within a federative environment where different publishers (public and private) can provide their own items of an act (that is there is more than one manifestation of the same act).

The LEX identifier is conceived to be: globally unique, transparent, bidirectional, persistent, location-independent, and language-neutral. It is organized into parts. The first part uses a predetermined standard to specify the country (or more generally the jurisdiction) of origin for the legal document being identified; the remainder is intended for local use in identifying documents issued in that country or jurisdiction. This second part depends only on sources of law identification system operating in that nation. For more details on the nature of the LEX characteristics and the general internal organization, see [Section 1.4](#).

The LEX name is linked to the document through specific meta-information, internally (with a tag) or externally (with a attribute) (for details on this see [Section 1.5](#))

LEX names will be used on a large scale in references either in (X)HTML document or, more generally, in XML documents format compliant with the relative DTD/XMLSchema (see [Section 1.6](#) for more information).

Syntax:

The identifier has a hierarchical structure as follows:

"urn:lex:" NSS

where <NSS> is the Namespace Specific String composed as follows:

NSS = jurisdiction ":" local-name

where:

<jurisdiction> is the part providing the identification of the

jurisdiction, generally corresponding to the country, where the source of law is issued. It is also possible to represent international organizations (either states or public administrations or private entities);

<local-name> is the uniform name of the source of law in the country or jurisdiction where it is issued; its internal structure is common to the already adopted schemas. It is able to represent all the aspects of an intellectual production, as it is a legal document, from its initial idea, through its evolution during the time, to its realisation by different means (paper, digital, etc.).

LEX specifications gives information on the internal structure of both <jurisdiction> and <local-name>, including specifications about case sensitivity, the use of national characters and diacritics, as well as spaces, connectives, punctuation marks, abbreviations, acronyms, date formats and ordinal numbers. For more details on the internal structure and syntax of the LEX identifier, see [Section 3](#), 4 and 5.

The use of r- and q- components, recently introduced by [\[RFC8141\]](#), with LEX URNs is not defined in this document. However they provide new and interesting perspectives when using URNs in a complex sector as sources of law, characterized by different versions, languages, publishers, and so on. In particular, by using the r-component at the resolver level, and therefore at the whole NSS level, you can select from the same work only expressions written in a given language, or manifestations published by a particular institutional site, etc. Using the q-component at the act metadata level, you can select versions that are valid at a particular date, or modified by a specific act, etc.

Assignment:

The Jurisdictional Registrar (or those it delegates) of each adhering country or organization is responsible of the definition or acceptance of the uniform name's primary elements (issuing authority and type of legal measure).

Any country or jurisdiction, aiming to adopt this schema, identifies a Jurisdictional Registrar, an organization which shares and defines the structure of the optional part of the name, according to the organization of the state or institution. The process of assigning the <local-name> will be managed by each specific country or jurisdiction under the related <jurisdiction> element (details on this can be found in

[Section 7.2](#)).

Identifiers in the "lex" namespace are defined through a <jurisdiction> element assigned to the sources of law of a specific country or organization, and a <local-name> assigned by the issuing authority. The goal of the LEX schema is to maintain uniqueness and persistence of all resources identified by the assigned URNs. The elements values for the LEX identifier within a jurisdiction are defined by the Jurisdictional Registrar, this ensures that the constructed URNs are unique (see [Section 7.3](#) for details on uniqueness).

The persistence of identifiers depends on the durability of the institutions that assign and administer them (see [Section 7.3](#) for details on persistence)

Security and Privacy:

This document introduces no additional security considerations beyond those associated with the use and resolution of URNs in general.

Interoperability:

As open standard naming convention to identify sources of law at international level, LEX is meant to guarantee interoperability among legal information systems across national boundaries.

The characteristics of the LEX naming convention facilitate legal document management as well as provide a mechanism of stable cross-collections and cross-country references, thus allowing the distribution of the legal information towards a federated architecture.

Resolution:

The resolution service associates a LEX identifier with a specific document address on the net. The related system will have a distributed architecture based on two fundamental components: a chain of information in DNS (Domain Name System) and a series of resolution services from URNs to URLs, each competent within a specific domain of the namespace (see [Section 8.1](#) for more details).

To cope with possible incomplete or inaccurate uniform names, the implementation of a catalogue, based on a relational-database, able to associate a URN to related URLs, is

suggested, as it will lead to a higher flexibility in the resolution process. A resolver can provide names normalization, completion of inaccurate or incomplete names, and finally their resolution in network locations (see [Section 8.2](#) and 8.3 for characteristics and behaviour of a catalogue for resolution).

Documentation:

The syntax, semantics and usage details of LEX URNs are given in [this RFC].

Additional Information:

See [[FRAN](#)] and [[SPIN](#)].

Revision Information:

None

[3](#) Specifications of Registration Template

[3.1](#) Identifier structure

The <jurisdiction> element is composed of two specific fields:

```
jurisdiction = jurisdiction-code *(";" jurisdiction-unit)
```

where:

<jurisdiction-code> is usually the identification code of the country where the source of law is issued.

To facilitate the transparency of the name, the <jurisdiction-code> follows usually the rules of identification of other Internet applications, based on Domain Name.

Where applicable, the ccTLD, or the TLD, or the Domain Name of the country or multinational or international organisation is used. Examples reported in this document are hypothetical and assumed that the corresponding Domain Name is used for the <jurisdiction-code>.

However, a special register for the <jurisdiction-code> is required, the rules of which are defined in [section 11.2](#).

<jurisdiction-unit> are the possible administrative hierarchical sub-structures defined by each country or organisation within their specific legal system. This additional information can be used in case two or more levels of legislative or judicial production exist (e.g., federal, state and municipality level) and the same bodies may

be present in each jurisdiction. Therefore acts of the same type issued by similar authorities in different areas differ for the jurisdiction-unit specification. An example can be the following: "br:governo:decreto" (decree of federal government), "br;sao.paulo:governo:decreto" (decree of SU+000000E3o Paulo state) and "br;sao.paulo;campinas:governo: decreto" (decree of Campinas municipality).

Examples (hypothetical) of sources of law identifiers are:

urn:lex:it:stato:legge:2003-09-21;456 (Italian act)
urn:lex:fr:etat:loi:2004-12-06;321 (French act)
urn:lex:es:estado:ley:2002-07-12;123 (Spanish act)
urn:lex:ch;glarus:regiere:erlass:2007-10-15;963 (Glarus Swiss Canton decree)
urn:lex:eu:commission:directive:2010-03-09;2010-19-EU (EU Commission Directive)
urn:lex:us:federal.supreme.court:decision:1963-03-18;372.us.335 (US FSC decision)
urn:lex:be:conseil.etat:decision:2008-07-09;185.273 (Decision of the Belgian Council of State)

[3.2](#) Conformance with URN Syntax

The "lex" NID syntax conforms to [\[RFC8141\]](#). However, a series of characters are reserved to identify elements or sub-elements, or for future extensions of the identifier.

[3.3](#) Validation Mechanism

The Jurisdictional Registrar (or those it delegates) of each adhering country or organization is responsible of the definition or acceptance of the uniform name's primary elements (issuing authority and type of legal measure).

[3.4](#) Scope

Global interest.

[4](#) General Syntax and Features of the LEX Identifier

This section lists the general features applicable to all jurisdictions.

[4.1](#) Allowed and Not Allowed Characters

These characters are defined in accordance with the [\[RFC8141\]](#) "Uniform Resource Names (URNs)". For various reasons, later

explained, in the "lex" <NSS> only a sub-set of characters is allowed. All other characters are either eliminated or converted.

For the full syntax of the uniform names in the "lex" space, please see Attachment A.

4.2 Reserved Characters

These characters MUST always and uniquely be used for the assigned purpose.

The first category includes those characters bearing a specific meaning in the general creation of the URI (Uniform Resource Identifier)[[RFC3986](#)] as "%", "?", "#", etc.

The following characters instead are reserved in the specific "lex" namespace:

- "@" separator of the expression, that contains information on version and language;
- "\$" separator of the manifestation, that contains information on format, editor, etc.;
- ":" separator of the main elements of the name at any entity;
- ";" separator of level. It identifies the introduction of an element at a hierarchically lower level, or the introduction of a specification;
- "+" separator of the repetitions of an entire main element (e.g., multiple authorities);
- "," separator of the repetitions of individual components in the main elements, each bearing the same level of specificity (e.g., multiple numbers);
- "~" separator of the partition identifier in references (e.g., paragraph of an article);
- "*" and "!" are reserved for future expansions.

To keep backward compatibility with existing applications in some jurisdictions, the "lex" NID syntax does not include the use of the character "/" in this version.

4.3 Case Sensitivity

Names belonging to the "lex" namespace are case-insensitive. It is RECOMMENDED that they be created in lower case, but names that differ only in case MUST be considered to be equivalent. (e.g., "Ministry" will be recorded as "ministry").

4.4 National Characters and Diacritic Signs

In order to exploit DNS as a routing tool towards the proper

resolution system, to keep editing and communication more simple and to avoid character percent-encoding, it is strongly RECOMMENDED that national characters and diacritic signs are turned into base ASCII characters (e.g., the Italian term "sanitU+000000E0" converted into "sanita", the French term "ministU+000000E8re" converted into "ministere"), in case by transliteration (e.g. "MU+000000FCnchen" converted into "muenchen").

If this conversion is not acceptable by a specific jurisdiction, UTF-8 %-encoding [[STD63](#)] may be used. In this case it should be noted that the generated URN (as some of its parts) can not be used directly for routing through DNS, and therefore the jurisdiction must adopt one of the following strategies:

- to convert non-ASCII characters within the DNS into the IDN encoding, using the [[RFC5894](#)] punycode translation (ex: mU+000000FCnchen in xn--mnchen-3ya), and to develop an interface software that converts the URN before the navigation in DNS, or
- to create a routing service relying to a software, out of DNS, addressing a proper resolution service.

Summarizing, the preference order is the following:

- Conversion into base ASCII (RECOMMENDED solution);
- Conversion to punycode only for navigation in DNS, via software interface;
- Creation of a routing service relying on a software, out of DNS, addressing a proper resolution service.

The first solution allows native DNS routing, while the other two require a software development for the interface or the routing. However it is up to the specific jurisdiction to choose the preferred solution.

[4.5](#) Abbreviations

Abbreviations are often used in law for indicating institutions (e.g. Min.), structures (e.g. Dept.), or legal measures (e.g. Reg.) but not in a uniform way, therefore their expansion is highly RECOMMENDED. (e.g., "Min." is reported as "ministry")

[4.6](#) Date Format

Dates are expressed by numbers in the [[ISO8601](#)] format:

yyyy-mm-dd

(e.g., "September 2, 99" will be written as "1999-09-02")

[5](#) Specific Syntax and Features of the LEX Identifier

In this section there are other features related to a specific jurisdiction and the implementation of which is recommended.

5.1 Spaces, Connectives and Punctuation Marks

All the language connectives (e.g., articles, prepositions, etc.), the punctuation marks and all the special characters (as apostrophes, dashes, etc.), when explicitly present, are eliminated (no transformation occurs in cases of languages with declensions or agglutinating languages). The words left are connected each other by a dot (".") which substitutes the "space".

(e.g., "Ministry of Finances, Budget and of Economic Planning" becomes "ministry.finances.budget.economic.planning"; "Ministerstvo Finansov" becomes "ministerstvo.finansov")

5.2 Acronyms

The use of acronyms might be confusing and encourage ambiguity in uniform names (the same acronym may indicate two different institutions or structures), therefore their expansion is highly RECOMMENDED.

(e.g., "FAO" is expanded as "food.agriculture.organization")

5.3 Ordinal Numbers

To even the representation, it is highly RECOMMENDED that any ordinal number included in a component of a document name (e.g., in the description of an institution body) is indicated in Western Arabic numerals, regardless to the original expression: whether in Roman numerals, or with an adjective, or in Arabic numeral with apex, etc. (IV, third, 1U+000000B0, 2[^], etc.).

(e.g., "Department IV" becomes "department.4")

6 Creation of the Source of Law LEX Identifier

6.1 Basic Principles

The uniform name must identify one and only one document (more precisely a "bibliographic entity") and is created in such a way that it is:

- self-explanatory ;
- identifiable through simple and clear rules;
- compatible with the practice commonly used for references;
- able to be created from references in the text, automatically (by parser) or manually;
- representative of both the formal and the substantive aspects of the document.

6.2 Model of Sources of Law Representation

According to FRBR (Functional Requirements for Bibliographic Records) model developed by IFLA (International Federation of Library Associations and Institutions), in a source of law, as in any intellectual production, 4 fundamental entities (or aspects) can be specified.

The first 2 entities reflect its contents:

- work: identifies a distinct intellectual creation; in our case, it identifies a source of law both in its being (as it has been issued or proposed) and in its becoming (as it is modified over time);
- expression: identifies a specific intellectual realisation of a work; in our case it identifies every different (original or up-to-date) version of the source of law over time and/or language in which the text is expressed;

while the other 2 entities relate to its form:

- manifestation: identifies a concrete realisation of an expression; in our case it identifies realizations in different media (printing, digital, etc.), encoding formats (XML, PDF, etc.), or other publishing characteristics;
- item: identifies a specific copy of a manifestation; in our case it identifies individual physical copies as they are found in particular physical locations.

In this document the FRBR model has been interpreted for the specific characteristics of the legal domain. In particular, a part from the language which does produce a specific expression, the discriminative criterion between expression and manifestation is based on the difference of the juridical effects that a variation can provide with respect to the involved actors (citizens, parties, institutions). In this scenario the main characteristic of the expression of an act is represented by its validity over the time, during which it provides the same juridical effects. These effects change for amendments or annulments of other legislative or jurisprudential acts. Therefore notes, summarizations, comments, anonymizations and other editorial activities over the same text do not produce different expressions, but different manifestations.

6.3 The Structure of the Local Name

The <local-name> within the "lex" namespace MUST contain all the necessary pieces of information enabling the unequivocal identification of a legal document.

In the legal domain, at the "work" level, they are essentially four: the enacting authority, the type of measure, the details and the annex, if any.

It is often necessary to differentiate various expressions, that is:

P. Spinosa

Expires December 8, 2018

[Page 20]

- the original version and all the amended versions of the same document;
- the versions of the text expressed in the different official languages of the state or organization.

Finally the uniform name allows a distinction among diverse manifestations, which may be produced in multiple locations using different means and formats.

In every case, the basic identifier of the source of law (work) remains the same, but information is added regarding the specific version under consideration (expression); similarly a suffix is added to the expression for representing the characteristics of the publication (manifestation).

The information which forms a source of law uniform name at each level (work, expression, manifestation) is expressed in the official language of the related jurisdiction; in case of more official languages (as in Switzerland) or more involved jurisdictions (as in international treaties), more language-dependent names (aliases) are created.

Therefore, the more general structure of the local name appears as follows:

local-name = work ["@" expression] ["\$" manifestation]

However, consistent with legislative practice, the uniform name of the main original provision (work) becomes the identifier of an entire class of documents which includes: the original main document, the annexes, and all their versions, languages and formats subsequently generated.

6.4 Structure of the Document Identifier at Work Level

The structure of the document identifier is made of the four fundamental elements mentioned above, clearly distinguished one from the other in accordance with an order identifying increasingly narrow domains and competences:

work = authority ":" measure ":" details *(":" annex)

where:

<authority> is the issuing or proposing authority of the measure (e.g., State, Ministry, Municipality, Court, etc.);

<measure> is the type of the measure, both public nature (e.g., constitution, act, treaty, regulation, decree, decision, etc.) as well as private one (e.g., license, agreement, etc);

<details> are the terms associated to the measure, typically the date (usually the signature date) and the number included in the heading of the act;

<annex> is the identifier of the annex, if any (e.g., Annex 1).

In case of annexes, both the main document and its annexes have their own uniform name so that they can individually be referenced; the identifier of the annex adds a suffix to that of the main document. In similar way the identifier of an annex of an annex adds an ending to that of the annex which it is attached to.

The main elements of the work name are generally divided into several elementary components, and, for each, specific rules of representation are established (criteria, modalities, syntax and order).

For the details regarding each element, please see the Attachment B.

Examples (hypothetical) of <work> identifiers are:

```
urn:lex:it:stato:legge:2006-05-14;22
urn:lex:uk:ministry.justice:decree:1999-10-07;45
urn:lex:ch:glarus:regiere:erlass:2007-10-15;963
urn:lex:es:tribunal.supremo:decision:2001-09-28;68
urn:lex:fr:assemblee.nationale:proposition.loi:13.legislature;1762
urn:lex:br:estado:constituicao:1988-10-05;lex-1
urn:lex:fsf.org:free.software.foundation:general.public.license:2007-06-29;lex-1
urn:lex:nl:hoge.raad:besluit:2008-04-01;bc8581
```

It is worth to note that the type of measure is important to identify case law, as well as legislation, especially within the legal systems where cases, by tradition, are identified only through the year of release and a number. Since the aim of the "urn:lex" schema is to identify specific materials, the type of measure or the full date are able to provide discrimination between materials belonging to a specific case.

Here below is an example where the type of measure or the full date are essential for identify specific materials of a case:

- 4/59 Judgement of the EEC Court of Justice 04/04/1960, Mannesmann AG and others / ECSC High Authority
urn:lex:eec.lex.arpa:court.justice:judgement:1960-04-04;4-59
- 4/59 Order of the EEC Court of Justice 18/05/1960, Mannesmann AG and others / ECSC High Authority
urn:lex:eec.lex.arpa:court.justice:order:1960-05-18;4-59

[6.5](#) Aliases

International treaties involve more jurisdictions (the signing ones) so they are represented through more identifiers, each of them related to an involved jurisdiction. For example, a bilateral France and Germany treaty is identified through two URNs (aliases) belonging to either "fr" or "de" jurisdiction (e.g., "urn:lex:fr:etat:traite:..." and "urn:lex:de:staat:vertrag:...") since it pertains to both the French and the German jurisdiction.

In the states or organisations that have more than one official language, a document has more identifiers, each of them expressed in a different official language, basically a set of equivalent aliases. This system permits manual or automated construction of the uniform name of the referred source of law in the same language used in the document itself.

(e.g., "urn:lex:eu:council:directive:2004-12-07;31",
"urn:lex:eu:consiglio:direttiva:2004-12-07;31", etc.)

Moreover, a document can be assigned more than one uniform name in order to facilitate its linking to other documents. This option can be used for documents that, although unique, are commonly referenced from different perspectives. For example, the form of a document's promulgation and its specific content (e.g., a Regulation promulgated through a Decree of the President of the Republic).

6.6 Structure of the Document Identifier at Expression Level

There may be several expressions of a legal text, connected to specific versions or languages.

Each version is characterized by the period of time during which that text is to be considered as the valid text (in force or effective). The lifetime of a version ends with the issuing of the subsequent version.

New versions of a text may be brought into existence by:

- changes in the text (amendments) due to the issuing of other legal acts and to the subsequent production of updated or consolidated texts;
- correction of publication errors (rectification or errata corrige);
- entry into or departure from a particular time span, depending on the specific date in which different partitions of a text come into force.

Each of such versions may be expressed in more than one language, with each language-version having its own specific identifier.

The identifier of a source of law expression adds such information to the work identifier, using the following main structure:

expression = version [":" language]

where:

<version> is the identifier of the version of the (original or amended) source of law. In general it is expressed by the promulgation date of the amending act; anyway other specific information can be used for particular documents. If necessary, the original version is specified by the string "original" (for the details regarding this element, please see the Attachment C);

<language> is the identification code of the language in which the document is expressed, according to [BCP47] (it=Italian, fr=French, de=German, etc.). The granularity level of the language (for example the specification of the German language as used in Switzerland rather than the standard German) is left to each specific jurisdiction. The information is not necessary when the text is expressed in the unique official language of the country or jurisdiction.

Examples (hypothetical) of document identifiers for expressions are:

urn:lex:ch:etat:loi:2006-05-14;22@originel:fr (original version in French)

urn:lex:ch:staat:gesetz:2006-05-14;22@original:de (original version in German)

urn:lex:ch:etat:loi:2006-05-14;22@2008-03-12:fr (amended version in French)

urn:lex:ch:staat:gesetz:2006-05-14;22@2008-03-12:de (amended version in German)

urn:lex:be:conseil.etat:decision:2008-07-09;185.273@originel:fr (original version in French of a Belgian decision)

6.7 Structure of the Document Identifier at Manifestation Level

To identify a specific manifestation, the uniform name of the expression is followed by a suitable suffix describing the:

- digital format (e.g., XML, HTML, PDF, etc.) expressed according to the MIME Content-Type standard [RFC2045], where the "/" character is to be substituted by the "-" sign;
- editorial staff who produced it, expressed according to its Internet domain name. Since publishers' domain names may vary over time, manifestations already assigned by a publisher remain unchanged even if the identified object is no longer accessible. In this case, in order to make its materials accessible, the publisher will have to create for each of them a new manifestation with the new domain name;
- possible components of the expressions contained in the manifestation. Such components are expressed by language-dependent labels representing the whole document (in English "all") or the

- main part of the document (in English "body") or the caption label of the component itself (e.g. Table 1, Figure 2, etc.);
- other features of the document (e.g., anonymized decision text).

The <manifestation> suffix will thus read:

```
manifestation = format ":" editor
                [(": component [":" feature]) /
                (":" "all" ":" feature)]
```

Note that the value "all" can be expressed by language-dependent equivalents. To indicate possible features or peculiarities, each main element of the manifestation MAY be followed by further specifications, for example as regards <format> the version, for <editor> the archive name and the electronic publisher, etc.

(examples (hypothetical):

the original version the Italian act 3 April 2000, n. 56 might have the following manifestations with their relative uniform names:

- PDF format (vers. 1.7) of the whole act edited by the Italian Parliament:
"urn:lex:it:stato:legge:2000-04-03;56\$application-pdf;1.7:parlamento.it"
- XML format (version 2.2 DTD NIR) of the text of the act and PDF format (version 1.7) of the "Figura 1" (figure 1) contained in the body, edited by the Italian Senate:
"urn:lex:it:stato:legge:2000-04-03;56\$text-xml;dtd-nir-2.2:senato.it:testo"
"urn:lex:it:stato:legge:2000-04-03;56\$application-pdf;1.7:senato.it:figura.1"

the Spanish URN of the html format of the whole Judgement of the European Court of Justice n. 33/08 of 11/06/2009, in Spanish version, published in the Jurifast data base in anonymized form:

"urn:lex:eu:tribunal.justicia:sentencia:2009-06-11;33-08@original:es\$text-html:juradmin.eu;jurifast:todo:anonimo")

Furthermore, it is useful to be able to assign a uniform name to a manifestation (or to a part of it) in case non-textual objects are involved. These may be multimedia objects that are non-textual in their own right (e.g. geographic maps, photographs, etc.), or texts recorded in non-textual formats, such as image scans of documents.

In these ways, a LEX name permits:

- exploitation of all the advantages of an unequivocal identifier that is independent of physical location;
- a means to provide choice among different existing manifestations (e.g. XML or PDF formats, resolution degree of an image etc.) of

the same expression.

6.8 Sources of Law References

References to sources of law often refer to specific partitions of the act (article, paragraph, etc.) and not to the entire document.

From a legal point of view, a partition is always a more or less wide text block, that represents a logical subdivision of an act.

As regards the digital representation, in a structured format (as XML) perfectly fitting the document logical structure, a partition is represented by an element (a block of text) with its own ID; this ID aims to identify the related element and to locate it. In this case, therefore, it is possible either extracting or pointing to a partition.

In a mark-up not fitting the logical structure of the text (as HTML), generally only the starting point of the partition, rather than the whole block of text or element, is identified through a label (a <a name> tag). In this case therefore it is not possible to extract a partition but only to point to it.

In both cases, having a partition identifier is useful; therefore, for allowing browsers to point to a specific partition, it is necessary that such partition is endowed with an unequivocal label or ID within the including document and its value is the same independently from the document format.

For enabling the construction of the partition identifier between different collections of documents, specific construction rules for IDs or labels SHOULD be defined and shared, within each country or jurisdiction, for any document type (e.g., for legislation, the paragraph 2 of the article 3 might have as label or ID the value "art3;par2", similarly for case-law, paragraph 22 of the judgement in Case 46/76 Bauhuis v Netherlands, might have as label or ID the value "par22").

Furthermore, it is useful to foresee the compatibility with applications able to manage this information (e.g., returning the proper element); these procedures are particularly useful in the case of rather long acts, such as codes, constitutions, regulations, etc. For this purpose it is necessary that the partition identifier is transmitted to the servers (resolution and application) and therefore it cannot be separated by the typical "#" character of URI fragment, which is not transmitted to the server.

According to these requirements, the syntax of a reference is:

URN-reference = URN-document ["~" partition-id]

(e.g., to refer to the paragraph 3 of the article 15 of the French

Act of 15 may 2004, n. 106, the reference is written
"urn:lex:fr:etat:loi:2004-05-15;106~art15;par3").

Using a different separator ("~") from the document name, the partition ID is not withheld by the browser but it is transmitted to the resolution process. This enables the resolver to retrieve (for example, out of a database), if it is possible, only the referred partition, otherwise to return the whole act.

Anyway, to make it effective in a browser pointing to the indicated partition, the resolver SHOULD transform the partition ID of each returned URL in a URI fragment; this is obtained appending to the URL the "#" character followed by the partition ID (in the example above, the returned URL will be <URL-document>#art15;par3). Doing this, knowing the granularity of the act markup, the resolver could exploit the hierarchical structure of the ID, eliminating sub-partitions not addressed. If only the article was identified in the act, in the previous example it could return <URL-document>#art15 only.

Anyway it is possible to use the general syntax (with "#"); in this case only the URN document component of the reference is transmitted to the resolver, therefore the whole document will be always retrieved.

7 The Procedure of Uniform Names Assignment

7.1 Specifying the <jurisdiction> Element of the LEX Identifier

Under the "lex" namespace, each country or international organization is assigned with a jurisdiction code, which characterizes the URNs of the source of law of that country or jurisdiction. This code is assigned according to ccTLD (as well as TLDN or DN for the organizations) representation and it is the value of the <jurisdiction-code> element, which preserves cross-country uniqueness of the identifiers.

7.2 Jurisdictional Registrar for Names Assignment

Any country or jurisdiction, who intends to adopt this schema, identifies a Jurisdictional Registrar, an organization which shares and defines the structure of the optional part (<jurisdiction-unit>) of the name, according to the organization of the state or institution. For example, in a federal state a <jurisdiction-unit> corresponding to the name of each member state (e.g. "br;sao.paolo", "br;minas.gerais", etc.) may be defined.

The process of assigning the <local-name> will be managed by each specific country or jurisdiction under the related <jurisdiction> element.

In any country the Jurisdictional Registrar shares and defines the assignment of the primary elements (issuing authority and type of legal measure) of the local names considering the characteristics of its own state or institution organization.

Such a Registrar MUST establish, according to the guidelines indicated in the current document, a uniform procedure within the country or organization to define <local-name> elements, to take decisions upon normalizations and finally to solve and avoid possible name collisions as well as to maintain authoritative registries of various kinds (e.g., for authorities, types of measures, etc.). In particular, accurate point-in-time representations of the structure and naming of government entities are important to semantically-aware applications in this domain.

Moreover, the Registrar shares and defines the rules to construct partition IDs for each document type.

Finally, the Registrar will develop and publish the rules and the guidelines for the <local-name> construction as well as the predefined values and codes. The Registrar should also promote the urn:lex identifier for the sources of law of its jurisdiction.

Such a set of rules will have to be followed by all institutional bodies adherent to the project as well as by private publishers and each of them will be responsible for assigning names to their domains.

7.3 Identifier Uniqueness

Identifiers in the "lex" namespace are defined through a <jurisdiction> element assigned to the sources of law of a specific country or organization, and a <local-name> assigned by the issuing authority. The main elements (authority and type of measure) of the <local-name> are defined by the Jurisdictional Registrar, so that it is ensured that the constructed URNs are unique. The Jurisdictional Registrar SHOULD provide clear documentation of rules by which names are to be constructed, and SHOULD update and make accessible its registries.

Any issuing authority is responsible to define formal parameters to guarantee local name uniqueness by attributing, if necessary, a conventional internal number, which, combined with the other <local-name> components (authority, measure and date), builds an unequivocal identifier. Uniqueness is achieved by checking against the catalogue of previously assigned names.

7.4 Identifier Persistence Considerations

The persistence of identifiers depends on the durability of the institutions that assign and administer them. The goal of the LEX

schema is to maintain uniqueness and persistence of all resources identified by the assigned URNs.

In particular, ITTIG-CNR, as proposer, is responsible of maintaining the uniqueness of the <jurisdiction> element; given that the <jurisdiction> is assigned on the basis of the long-held ccTLD representation of the country (or the TLDN or DN of the organization) and that the country or organization associated code is expected to continue indefinitely, the URN also persists indefinitely.

The rules for the construction of the name are conceived to delegate the responsibility of their uniqueness to a set of authorities which is identified within each country or organization.

Therefore, each authority is responsible for assigning URNs which have a very long life expectancy and can be expected to remain unique for the foreseeable future. Practical and political considerations, as well as diverse local forms of government organization, will result in different methods of assigning responsibility for different levels of the name.

Where this cannot be accomplished by the implementation of an authoritative hierarchy, it can and SHOULD be done by creating consensus around a series of published rules for the creation and administration of names by institutions and bodies that operate by means of collaboration rather than compulsion.

Issuing authorities that operate in more localized scopes, ranging from the national down to the very local, MUST equally take responsibility for the persistence of identifiers within their scope.

8 Principles of the Resolution Service

8.1 The General Architecture of the System

The task of the resolution service is that of associating a LEX identifier with a specific document address on the network. By contrast with systems that can be constructed around rigorous and enforceable engineering premises, such as DNS, the "lex" namespace resolver will be expected to cope with a wide variety of "dirty" inputs, particularly those created by the automated extraction of references from incomplete or inaccurate texts. In this document, the result is a particular emphasis on a flexible and robust resolver design.

The system has a distributed architecture based on two fundamental components: a chain of information in DNS (Domain Name System) and a series of resolution services from URNs to URLs, each competent

within a specific domain of the namespace.

Through the NAPTR records of the DNS (described in [[RFC3403](#)]), the client identifies the characteristics (protocol, port, site) of the service (e.g. according to [[RFC2169](#)]) capable of associating the relative URLs with the URN in question, thereby allowing access to the document.

A resolution service can delegate the resolution and management of hierarchically-dependent portions of the name.

Delegation of this responsibility will not be unreasonably withheld provided that the processes for their resolution and management are robust and are followed.

For the "lex" namespace, ITTIG-CNR will maintain the root zone "lex.urn.arpa" (see [[RFC3405](#)]) and, in correspondence with the adhesion of a new country (e.g., "br") or organization, will update the DNS information with a new record to delegate the relative resolution. This may be obtained by a regular expression that matches the initial part of the URN (e.g., "urn:lex:br") and redirects towards the proper zone (e.g., "lex.senado.gov.br").

Likewise the institution responsible for the jurisdiction uniform names (e.g., "urn:lex:br") has the task of managing the relative root in the DNS system (e.g., "lex.senado.gov.br" zone) and routing the resolution towards its resolvers on the basis of parts of the uniform names. In similar way it can delegate the resolution of country/organization sub-levels (e.g., "urn:lex:br;sao.paulo") towards the relative zone (e.g., "lex.sao-paulo.gov.br").

Such DNS routing chain does not work for all the URN components containing %-encoded characters. Therefore in these cases a proper software implementing punycode conversion or routing service has to be developed.

The resolution service is made up of two elements: a knowledge base (consisting in a catalogue or a set of transformation rules) and a software to query the knowledge base itself.

[8.2](#) Catalogues for Resolution

Incompleteness and inaccuracy are rather frequent in legal citations, and incomplete or inaccurate uniform names of the referred document are thus likely to be built from textual references (this is even more frequent if they are created automatically through a specific parser). For this reason, the implementation of a catalogue, based on a relational-database, is suggested, as it will lead to a higher flexibility in the resolution process.

In addition the catalogue must manage the aliases, the various

versions and languages of the same source of law as well as the related manifestations.

It is suggested that each enacting authority implements its own catalogue, assigning a corresponding unambiguous uniform name to each resource.

8.3 Suggested Resolver Behaviour

First of all the resolver should separate the part corresponding to the partition ID, through the "~" separator, from the document name.

So, the resolution process SHOULD implement a normalization of the uniform name to be resolved. This may involve transforming some components to the canonical form (e.g., filling out the acronyms, expanding the abbreviations, unifying the institution names, standardizing the type of measures, etc.). For this function authorities and types of measure registers are useful.

The resolver SHOULD then query the catalogue searching for the URN which corresponds exactly to the given one (normalized if necessary). Since the names coming from the references may be inaccurate or incomplete, an iterative, heuristic approach (based on partial matches) is indicated. It is worth remarking that incomplete references (not including all the elements to create the canonical uniform name) are normal and natural; for a human reader, the reference would be "completed" by contextual understanding of the reference in the document in which it occurs.

In this phase, the resolver should use the partition ID information to retrieve, if it is possible, only the referred partition, otherwise to return of the entire document.

Lacking more specific indications, the resolver SHOULD select the best (most recent) version of the requested source of law, and provide all the manifestations with their related items. A more specific indication in the uniform name to be resolved will, of course, result in a more selective retrieval, based on any suggested expression and/or manifestations components (e.g. date, language, format, etc.).

Finally, the resolver SHOULD append to URLs the "#" character followed by partition ID, transforming it in a URI fragment for browser pointing.

9 Namespace Considerations

In collaboration with the legislative XML community, registrants

carried out a preliminary study of the URI alternatives to satisfy the key requirements.

The options analysed were: a private URI scheme, URL, PURL and URN. URN was considered the most appropriate URI given the requirements analysis.

Advantages we would emphasize are:

- greater flexibility in building the identifier;
- the capacity to represent name components that are not strictly hierarchical;
- the potential for clear division of the identifier into macro parts, main elements and components, using different separators;
- ease of managing optional parts of a name.

10 Community Considerations

The use of the "lex" namespace facilitates the interoperability of information systems used in the Public Administration at the national and international level. Moreover it allows the distribution of the legal information towards a federated architecture. In such an architecture, documents are directly managed by the issuing authorities, with resulting benefits in information authenticity, quality and currency. A shared identification mechanism resources guarantees that a distributed system will be as efficient and effective as a comparable centralized system.

Creators of Internet content that references legal materials - including publishers operating well outside the traditional arenas of legal publishing - benefit by the registration of the namespace because facilitates the linking of legal documents, whether by manual or automated means, and reduces the cost of maintaining documents that contain such references.

Any citizen or organisation with Internet web browser capability will be entitled to access the namespace and its associated application, registers, and resolution services, to facilitate document access.

It is envisaged to promote the urn:lex identification system for sources of law through all the various dissemination channels such as conferences, a project dedicated website, references from other projects, etc.

11 IANA Considerations

11.1 NID Registration

This document includes a URN NID registration for "lex" for entry in the IANA registry of URN NIDs (see [[RFC8141](#)]), as well as the registration of the following NAPTRs record:

in the URN.ARPA domain:

```
lex IN NAPTR 100 10 "" "" "" <urn-lex.zone.org>.
```

in the URN.URI.ARPA domain:

```
lex IN NAPTR 100 10 "" "" "" <urn-lex.zone.org>.
```

where <urn-lex.zone.org> indicates the server of the organization that is responsible for the "lex" area under urn.arpa and urn.uri.arpa, and will be specified at implementation time.

11.2 Jurisdiction-code Registration

It is requested to create a new registry for <jurisdiction-code>, with the following format:

- <jurisdiction-code>: the identifier code of jurisdiction, assigned to the country or organisation;
- <jurisdiction>: the official denomination of the jurisdiction, country or organisation;
- <registrant>: all information about the organization that requested the registration of the code. Such organization will be responsible for its DNS zone and for the attribution of sub-zone delegations, and so on. It is desirable that each jurisdiction creates a register of all delegated levels so that the organization responsible of each sub-zone can easily be identified;
- <reference>: a reference to the defining document (if any).

The table is initially empty. Possible example entries are:

```
"br"; "Brazil"; "Prodasen, Federal Senate, <address>, <contact>";  
[reference]  
"eu"; "European Union"; "DG Digit, European Commission, <address>,  
<contact>"; [reference]  
"un.org"; "United Nations"; "DPI, United Nations, <address>,  
<contact>"; [reference]
```

In the current experimental LEX registration phase, ITTIG-CNR will take care to create and maintain the registry for <jurisdiction-code>. As the criteria of the LEX names assignment will be consolidated, after the experimental phase such registry will be maintained by IANA.

The adopted registration policy is compliant with the "Expert Review" as specified in [[RFC8126](#)]. Designated Expert(s) will assign jurisdiction codes based on the following principles:

- if a request comes from a jurisdiction that corresponds to a country and the jurisdiction code is the same as a top level ccTLD, which is not yet registered, then the top level ccTLD should be used as the jurisdiction code;
- if a request comes from a jurisdiction that corresponds to a multi-national (e.g., European Union) or international (e.g., United

Nations, Free Software Foundation) organizations the Top Level Domain Name (e.g., "eu") or the Domain Name (e.g., "un.org", "wto.int") of the organization should be used as the jurisdiction code;

- in case when such multi-national or international organization does not have a registered domain, Designated Expert(s) should assign something like <name>.lex.arpa, where <name> is the English acronym of the organization name. For example, the jurisdiction code of the European Economic Community is "eec.lex.arpa".

Jurisdiction codes can't be renamed, because allowing for renames would violate rules that URN assignments are persistent.

Jurisdiction codes can never be deleted. They can only be marked as "obsolete", i.e. closed for new assignments within the jurisdiction. Requests to obsolete a jurisdiction code are also processed by Designated Expert.

Designated Expert(s) can unilaterally initiate allocation or obsolescence of a jurisdiction code.

Request for new jurisdiction code assignment must include Organization or Country requesting it and Contact information (email) of who requested the assignment.

12 References

12.1 Normative References

- [BCP47] A. Phillips, M. Davis, "Tags for Identifying Languages", [BCP 47](#), [RFC 5646](#), September 2009
- [STD63] F. Yergeau, "UTF-8, a transformation format of ISO 10646", STD 63, [RFC 3629](#), November 2003.
- [RFC2045] N. Freed, N. Borenstein, "Multipurpose Internet Mail Extensions (MIME) Part One: Format of Internet Message Bodies", [RFC 2045](#), November 1996.
- [RFC2119] S. Bradner, "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), March 1997.
- [RFC2169] R. Daniel, "A Trivial Convention for using HTTP in URN", [RFC 2169](#), June 1997
- [RFC3403] M. Mealling, Dynamic Delegation Discovery System (DDDS), Part Three: The Domain Name System (DNS) Database, [RFC 3403](#), October 2002.

- [RFC3405] M. Mealling, Dynamic Delegation Discovery System (DDDS), Part Five: URI.ARPA Assignment Procedures, [RFC 3405](#), October 2002.
- [RFC3986] Berners-Lee, T., Fielding, R., and L. Masinter, "Uniform Resource Identifiers (URI): Generic Syntax", STD 66, [RFC 3986](#), January 2005.
- [RFC5234] D. Crocker Ed., P. Overell, "Augmented BNF for Syntax Specifications: ABNF", STD 68, [RFC 5234](#), January 2008
- [RFC5894] J. Klensin, "Internationalized Domain Names for Applications (IDNA): Background, Explanation, and Rationale", [RFC 5894](#), August 2010
- [RFC8126] M. Cotton, B. Leiba, T. Narten, "Guidelines for Writing an IANA Considerations Section in RFCs", [RFC 8126](#), June 2017
- [RFC8141] P. Saint-Andre, J.C. Klensin, "Uniform Resource Names (URNs)", [RFC 8141](#), April 2017
- [RFC8288] M. Nottingham, "Web Linking", [RFC 8288](#), October 2017
- [ISO8601] ISO 8601, "Data elements and interchange formats", ISO 8601:2004

[12.2](#) Informative References

- [FRAN] E. Francesconi, "Technologies for European Integration. Standards-based Interoperability of Legal Information Systems", ISBN 978-88-8398-050-3, European Press Academic Publishing, 2007.
- [SPIN] P.L. Spinosa, "The Assignment of Uniform Names to Italian Legal Documents", URN-NIR 1.4, June, 2010, ITTIG Technical Report n. 8/2010.

[13](#) Acknowledgements

The authors of this document wish to thank all the supporters for giving suggestions and comments.

They are also grateful to the Legislative XML community for the interesting discussions on this topic and to the Working Group "Identification of the legal resources through URNs" of Italian NormeInRete project for the provided guidance [[SPIN](#)].

The authors owe a debt of gratitude to Tom Bruce, director of the Legal Information Institute of the Cornell University Law School, for

his contribution in revising this document and sharing fruitful discussions which greatly improved the final draft. The authors wish to specially thank Marc van Opijnen (Dutch Ministry of Security and Justice) for his valuable comments on LEX specifications which contributed to improve the final result, as well as for the common work aimed to harmonize ECLI and LEX standards. Thanks also to Joao Alberto de Oliveira Lima, legislative system analyst of the Brazilian Federal Senate, and to Attila Torcsvari, information management consultant, for their detailed comments on the first drafts of this document, which provided significant hints to the final version of the standard, and to Robert Richards of the Legal Information Institute (Cornell University Law School), promoter and maintainer of the Legal Informatics Research social network, as well as to the members of this network, for their valuable comments on this proposal.

Finally, many thanks go to Loriana Serrotti who significantly contributed to the first drafting of this document.

14 Author's Addresses

PierLuigi Spinosa
(ICT consultant)
Via Zanardelli, 15
50136 Firenze
Italy
Telephone: +39 339 5614056
e-mail: pierluigi.spinosa@gmail.com

Enrico Francesconi
Istituto di Teoria e Tecniche dell'Informazione Giuridica (ITTIG)
Consiglio Nazionale delle Ricerche (CNR)
Via de' Barucci, 20
50127 Firenze
Italy
Telephone: +39 055 43995
e-mail: enrico.francesconi@ittig.cnr.it

Caterina Lupo
(ICT consultant)
Via San Fabiano, 25
00165 Roma
Italy
Telephone: +39 3382632348
e-mail: caterina.lupo@gmail.com

Attachment A -- Summary of the Syntax of the Uniform Names of the "lex" Namespace

```
;-----  
; Structure of a Uniform Resource Name (URN) of the "lex" namespace  
; NID-lex = namespace  
; NSS-lex = specific name  
;-----  
URN-lex = "urn:" NID-lex ":" NSS-lex  
  
NID-lex = "lex"  
  
;-----  
; Structure of a "lex" specific name  
;-----  
NSS-lex = jurisdiction ":" local-name  
  
;-----  
; Structure of the <jurisdiction> element  
;-----  
jurisdiction = jurisdiction-code *("; " jurisdiction-unit)  
  
jurisdiction-code = 2*alf-dot  
  
jurisdiction-unit = alf-dot  
  
;-----  
; Structure of the <local-name> element  
;-----  
local-name = work ["@" expression] ["$" manifestation]  
  
;-----  
; Structure of the <work> element  
;-----  
work = authority ":" measure ":" details *(": " annex)  
  
;-----  
; Structure of the <authority> element  
;-----  
authority = issuer *("+ " issuer)  
  
issuer = (institution *("; " body-function)) / office  
  
institution = alf-dot  
  
body-function = alf-dot
```


office = alf-dot

; Structure of the <measure> element

measure = measure-type *(";" specification)

measure-type = alf-dot

specification = alf-dot

; Structure of the <details> element

details = (dates / period) ";" numbers

dates = date *(", " date)

period = alf-dot

numbers = (document-id *(", " document-id)) / number-lex

document-id = alf-dot-oth

number-lex = "lex-" 1*DIGIT

; Structure of the <annex> element

annex = annex-id *(";" specification)

annex-id = alf-dot

; Structure of the <expression> element

expression = version [":" language]

; Structure of the <version> element

version = (amendment-date / specification)
 *(";" (event-date / event))

amendment-date = date

event-date = date

event = alf-dot

```
;-----  
; Structure of the <language> element  
;-----  
language = 2*3alfa
```

```
;-----  
; Structure of the <manifestation> element  
;-----  
manifestation = format *(";" specification)  
                  ":" editor *(";" specification)  
                  [ ":" component [ ":" feature ] ] /  
                  ( ":" "all" ":" feature ) ]
```

component = part *(";" specification)

feature = attribute *(";" specification)

format = alf-dot-hyp

editor = alf-dot-hyp

part = alf-dot-hyp

attribute = alf-dot-hyp

```
;-----  
; Structure of the date  
;-----  
date = year "-" month "-" day
```

year = 4DIGIT

month = 2DIGIT

day = 2DIGIT

```
;-----  
; Allowed, reserved and future characters  
;-----  
; allowed = alfadot / other / reserved  
; reserved = ":" / "@" / "$" / "+" / ";" / "," / "~"  
; future = "*" / "!"
```

alf-dot = alfanum *alfadot

alf-dot-hyp = alfanum *(alfadot / "-")

alf-dot-oth = alfanum *(alfadot / other)

alfadot = alfanum / "."

alfa = lowercase / uppercase

alfanum = alfa / DIGIT / encoded

lowercase = %x61-7A ; lower-case ASCII letters (a-z)

uppercase = %x41-5A ; upper-case ASCII letters (A-Z)

DIGIT = %x30-39 ; decimal digits (0-9)

encoded = "%" 2HEXDIG

HEXDIG = DIGIT / %x41-46 / %x61-66 ; hex digits (0-9,A-F,a-f)

other = "-" / "_" / "'" / "=" / "(" / ")"

Attachment B -- Specific Syntax of the Identifier at Work Level

B1 The <authority> Element

B1.1 Indication of the Authority

The <authority> element of a uniform name may indicate, in the various cases:

- the actual authority issuing the legal provision. More specifically, the authority adopting the provision or enacting it;
- the institution where the provision is registered, known and referenced to, even if produced by others (e.g., the bills identified through the reference to the Chamber where they are presented);
- the institution regulated (and referred to in citations) by the legal provision even when this is issued by another authority (e.g., the statute of a Body);
- the entity that proposed the legal material not yet included in the institutional process (e.g. a proposed bill written by a political party).

B1.2 Multiple Issuers

Some sources of law are enacted by a number of issuing parties (e.g., inter-ministerial decrees, agreements, etc.). In this case, the <authority> element contains all the issuing parties (properly separated), as follows:

authority = issuer *("+" issuer)

(e.g., "ministry.justice+ministry.finances")

B1.3 Indication of the Issuer

Each issuing authority is essentially represented by either an institutional office (e.g., Prime Minister) or an institution (e.g., Ministry); in the last case, the authority is indicated in accordance with the institution's hierarchical structure, from the more general to more specific (Council, Department, etc.), ending with the relative office (President, Director, etc.).

Therefore, the structure of the issuer is as follows:

issuer = (institution *(";" body-function)) / office

(e.g., "ministry.finances;department.revenues;manager")

B1.4 Indication of the Body

Depending on the kind of measure, the body within the issuing authority is unambiguously determined (e.g., the Council for Regional Acts) and normally it is not indicated in the references. Just like in practice, the indication of the enacting authority is limited to the minimum in relation to the type of measure. (e.g., "region.tuscany:act" and not "region.tuscany;council:act")

B1.5 Indication of the Function

Generally, the function is indicated, sometimes instead of the body itself:

- in case of political, representative or elective offices (e.g., "university.oxford;rector:decree" instead of "university.oxford;rectorship:decree");
- when it refers to a top officer in the institution (e.g., general manager, general secretary, etc.) which is not always possible to associate a specific internal institutional structure to (e.g., "national.council.research;general.manager").

It is not indicated when it clearly corresponds to the person in charge of an institution (typically, a general director); in this case, only the structure and not the person in charge is indicated (e.g., "ministry.justice;department.penitentiary.administration").

The function **MUST** be indicated when:

- it is not the same of the director or the person in charge of the structure (for example, in case of an undersecretary, a deputy director, etc.);
- the type of measure may be both monocratic or collegial: the indication of the office eliminates the ambiguity.

B1.6 Conventions for the Authority

Acts and measures bearing the same relevance as an act, issued or enacted since the foundation of the State, have conventionally indicated "state" (expressed in each country official language) as authority; the same convention is used for constitutions, codes (civil, criminal, civil procedure, criminal procedure, etc) and international treaties.

B2 The <measure> Element

B2.1 Criteria for the Indication of the Type of Measure

In uniform names the issuing authority of a document is mandatory. This makes unnecessary to indicate any further qualification of the measure (e.g., ministerial decree, directorial ordinance, etc.), even if it is widely used.

When the authority-measure combination clearly identifies a specific document, the type of measure is not defined through attributes referring to the enacting authority.
(e.g., "region.tuscany:act" and not "region.tuscany:regional.act")

B2.2 Further Specification to the Type of Measure

In the <measure> element, it is usually sufficient to indicate the type of a measure. As usual, references to sources of law, rather than through the formal details (date and number), may be made through some of their characteristics such as the subject-matter covered (e.g., accounting regulations), nicknames referring to the promoter (e.g., Bassanini Act) or to the topic of the act (e.g., Bankruptcy Law), etc..

In these cases, the type of measure MAY be followed by further specifications useful in referencing even if the details are lacking:

measure = measure-type *(";" specification)

(e.g., "regulations;accounting" or "act;bankruptcy")

B2.3 Aliases for Sources of Law with Different Normative References

There are legislative measures that, although unique, are usually cited in different ways, for example through the legislative act introducing them into the legal order (President's decree, legislative decree, etc.) or through their legislative category (regulations, consolidation, etc.).

In order to ensure, in all the cases, the validity of the references, an alias that takes into account the measure category is associated to the uniform name, representing the legislative form.

(e.g., "state:decree.legislative:1992-07-24;358" and "state:consolidation;public.contracts:1992-07-24;358").

B2.4 Relations between Measure and Authority in the Aliases

The sources of law including different normative references are usually introduced in legislation through the adoption or the issuing of an act, which they are either included or attached to. It is, therefore, necessary to create an alias linking the two aspects of the same document. Specifically, the different measures can be:

- adopted/issued by an authority different from the one regulated by the provision (e.g., the statute of a Body); in this case, the correlation is established between two uniform names each featuring a completely different <authority> element
(e.g., "italian.society.authors.publishers:statute" and "ministry.cultural.activities+ministry.finances.budget.economic.planning:decree");

- issued by the institution itself either because it has issuing authority or by virtue of a proxy (e.g., a provision that refers to the functioning of the Body itself); in this case, the two aliases share the first part of the authority; (e.g., "municipality.firenze:statute" and "municipality.firenze;council:deliberation");
- issued by the same Body to regulate a particular sector of its own competence; in this case the <authority> element is the same (e.g., "ministry.justice:regulation;use.information.tools.telematic.process" and "ministry.justice:decree").

B3 The <details> Element

B3.1 Indication of the Details

The details of a source of law usually include the date of the enactment and the identification number (inclusion in the body of laws, register, protocol, etc.).

Some measures can have multiple dates; there are also cases in which the number of the measure does not exist (unnumbered measures) or a measure has multiple numbers (e.g., unified cases). For these reasons, the set up of both elements (date and number) includes multiple values.

Some institutions (e.g., the Parliaments) usually identify documents through their period of reference (e.g., the legislature number) rather than through a date, which would be much less meaningful and never used in references (e.g., Senate bill S.2544 of the XIV legislature). In these cases, the component <period> is used in substitution of the component <dates>.

Usually details of a measure are not reported according to a specific sequence; in accordance with the global structure of the uniform name, which goes from the general to the specific, the sequence date-number has the following form:

details = (dates / period) ";" numbers

(e.g., "2000-12-06;126", "14.legislature;s.2544")

B3.2 Multiple Dates

Some sources of law, even if unique, are identified by more than one date; in this case, in the field <dates> all the given dates are to be reported and indicated as follows:

dates = date *(", " date)

(e.g., the measure of the Data Protection Authority of December 30, 1999- January 13, 2000, No. 1/P/2000 has the following uniform name: "personal.data.protection.authority:measure:1999-12-30,2000-01-13;1-p-2000").

B3.3 Unnumbered Measures

Measures not officially numbered in the publications may have a non-unequivocal identifier, because several measures of the same type can exist, issued on the same day by the same authority.

To ensure that the uniform name is unambiguous, the <numbers> field MUST, in any case, contain a discriminating element, which can be any identifier used internally, and not published, by the authority (e.g., protocol).

If the authority does not have its own identifier, one identifier MUST be created for the name system. In order to easily differentiate it, such number is preceded by the string "lex-":

number-lex = "lex-" 1*DIGIT

(e.g., "ministry.finances:decree:1999-12-20;lex-3")

It is responsibility of the authority issuing a document to assign a discriminating specification to it; in case of multiple authorities, only one of them is responsible for the assignment of the number to the document (e.g., the proponent).

The unnumbered measures published on an official publication (e.g., the Official Gazette), instead of by a progressive number are recognized by the univocal identifying label printed on the paper. Such an identifier, even if unofficial but assigned to a document in an official publication, is to be preferred because it has the clear advantage to be public and therefore easier to be found.

B3.4 Multiple Numbers

Some legal documents (e.g., bills), even if unique, are identified by a set of numbers (e.g., the unification of cases or bills).

In this case, in the <numbers> field, all the identifiers are reported, according to the following structure:

numbers = document-id *(", " document-id)

(e.g., "2000-06-12;c-10-97,c-11-97,c-12-97")

The characters which are not allowed (e.g., "/") or reserved (e.g., ":"), including the comma, cannot exist inside the <document-id>, and therefore MUST be turned into "-".

This conversion may imply that the uniform name of the document is no more unique (e.g., removal 123-BIS and return 123/BIS of the bill 123

both are identified as "123-bis"); in this case, it is necessary to add a specific distinctive ending (e.g., "123-bis-removal" and "123-bis-return").

B4 The <annex> Element

B4.1 Formal Annexes

Although annexes are an integral part of the legal document, they may be referred to and undergo amendments separately from the act to which they are annexed. It is, therefore, necessary that both the main document as well as each formal individual annex is univocally identified.

Formal annexes may be registered as separate parts or together with a legal provision; they may also be autonomous in nature or not. In any case, they MUST be given a uniform name, which includes the uniform name of the source of law to which they are attached, and a suffix which identifies the annex itself.

The suffix of formal annexes includes the official heading of the annex and, possibly, further specifications (e.g., the title) which will facilitate the retrieval of the annex in case the identifier is missing:

annex = annex-id *(";" specification)

(e.g., "region.sicily;council:deliberation:1998-02-12;14:annex.a;borders.park")

The characters which are not allowed (e.g. "/") or which are reserved (e.g. ":") must not be featured in the <annex-id> and therefore MUST be turned into ".".

B4.2 Annexes of Annexes

When there are annexes to an annex, their corresponding identifiers are created by adding to the identifier of the original annex those of the annexes that are connected with it (that is, attached to it).

(e.g., Table 1 attached to Attachment A of the preceding legal act has the following uniform name:

"region.sicily;council:deliberation:1998-02-12;14:annex.a;borders.park:table.1;municipality.territories").

Attachment C -- Specific Syntax of the <version> Element of the Expression

C1 The <version> Element

C1.1 Different Versions of a Legislative Document

The creation of an updated text of a document may have one of the following forms:

- "multi-version": when specific mark-ups which identify the modified parts of a document (added, substituted or deleted parts) and their related periods of effectiveness are indicated inside one single object (e.g., an xml file). Such a document will be able, in a dynamic way, to appear in different forms according to the requested date of effectiveness.

In this document type, usually a set of metadata contains the lifecycle of the document (from the original to the last modification), including the validity time interval of each version and of each related text portion;

- "single-version": when, on the contrary, a new and distinct object is created for each amendment to the text at a given time. Each object is, therefore, characterized by its own period of validity. In any case all the versions SHOULD be linked one another and immediately navigable.

In a "multi-version" document each time interval should have a link to the related in-force document version obtained by displaying in a different way the very same document.

In a "single-version" document, the metadata should contain links to the all the previous modifications and a link only to the following version, if any.

[RFC8288] can be used as reference to establish links between different document versions, either in the "multi-version" or in the "single-version" document. According to [[RFC8288](#)] the following relations are useful:

- current (or last or last-version): in-force version
- self: this version
- next: next version
- previous: previous version
- first: original version

It is RECOMMENDED that these relations are inserted in the header of each version (if "single-version") or associated to each entry containing a single URN (if "multi-version").

C1.2 Identification of the Version

In order to identify the different time versions of the same act, to the uniform name of the original document has to be added a specific suffix.

Such a suffix identifies each version of a legal provision and includes, first and foremost, one of the following elements:

- the issuing date of the last amending measure taken into account;
- the date in which the communication of the rectification or of the errata corrige, is published;
- a specification which must identify the reason concerning the amendment (e.g., the specific phase of the legislative process), for the cases in which the date is not usually used (e.g., bills).

Anyway it is possible to add further specifications that will distinguish each of the different versions of the text to guarantee identifier unequivocalness. For example with regard to changes of the in-force or effectiveness of any partition or portion of the text itself (e.g., when the amendments introduced by an act are applied at different times) or different events occurring in the same date.

version = (amendment-date / specification)
*(";" (event-date / event))

where:

- <amendment-date> contains the issuing date of the last considered amendment or of the last communication of amendment. In case the original text introduces differentiated periods in which an act is effective and the information system produces one version for each of them, such element contains the string "original";
- <specification> any information useful to identify unambiguously and univocally the version;
- <event-date> contains the date in which a version is put into force, is effective or is published;
- <event> is a name assigned to the event producing a further version (e.g., amendment, decision, etc.).

The issuing date of an amending act was chosen as identifier of a version because it can be obtained from the heading (formal data).

(e.g., the name "state:royal.decreet:1941-01-30;12@1998-02-19" identifies the updated text of the "Royal Decree of 30/1/1941, No. 12" with the amendments introduced by the "Law Decree of 19/2/1998, No. 51", without any indication of its actual entry into force. The same uniform name with the additional ending ";1999-01-01" indicates the in-force or effective version starting in a different date (from 1/1/99).

For a full compatibility, every updating of a text or of the effectiveness of a "multi-version" document implies the creation of a

new uniform name, even if the object remains only one, containing the identifier of the virtually generated version, exactly as in the case of a "single-version" document. A specific meta-data will associate every uniform name with the period of time during which such a name together with its corresponding text is to be considered valid.

(e.g., the multi-version document containing the "R.D. of 01/30/1941, no. 12", updated by the amendments introduced by the "D.Lgs. of 02/19/1998, no. 51", contains the name of the original "state:royal.decreree:1941-01-30;12" as well as the name of the updated version "state:royal.decreree:1941-01-30;12@1998-02-19").

Please note that in case of attachments or annexes, the creation of a new version (even in the case of only one component) would imply the creation of a new uniform name for all the connected objects in order to guarantee their alignment (i.e., the main document, the attachments and annexes).

Attachment D -- Http LEX Identifier

D1 Http URI

Http URIs have been recently promoted as stable and location-independent identifiers [[RFC3986](#)]. According to this syntax, at all levels, resource IDs belong to the http scheme and are normally resolved using mechanisms widely available in browsers and web servers.

Such kind of identifiers have been recently suggested also within the set of principles and technologies, known as "Linked Data" as a basic infrastructure of the semantic web to enable data sharing and reuse on a massive scale.

Such principles, introduced by Tim Berners-Lee in his Web architecture note "Linked Data" (<http://www.w3.org/DesignIssues/LinkedData.html>), are synthetically:

- Use URIs as names for things;
- Use HTTP URIs, so that people can look up those names;
- When someone looks up a URI, provide useful information, using the standards (RDF, SPARQL);
- Include links to other URIs, so that they can discover more things.

The second principle is the one more affecting a discussion about the scheme to be used for legal resources identification; in particular to the aim of guaranteeing the access to the resources, http identifiers are suggested. This property is addressed as "dereferenceability", meaning a resource retrieval mechanism using any of the Internet protocols, e.g. HTTP, so that HTTP clients, for instance, can look up the URI using the HTTP protocol and retrieve a description of the resource that is identified by the URI. Such property is available for http identifiers either with or without a resolver allowing a 1-to-1 association with the "best copy" of the resource; in the legal domain it is related to the unique act manifestation of a specific publisher and format.

The same property holds for URN identifiers, as long as a resolver is properly set-up, allowing 1-to-N association with more manifestations of a resource (act).

Therefore an http identifier, stable and independent from the resource location, can be effectively used when a single publisher provides a specific item of this resource (1-to-1 mapping between an identifier and manifestation of an act). The independence from the resource location is managed by a "303 Redirect" status code (see

<http://linkeddatabook.com/editions/1.0/#htoc11>) which may require a resolver able to access the physical location of the resource (e.g., through submitting a query to a database). A URN identifier, stable and independent from the resource location, can be effectively used within a federative environment where different publishers can provide different items of the same act (1-to-N mapping between an identifier and different manifestations of an act).

In order to comply with the Linked Data principles and to build http identifiers using the LEX namespace specifications, the LEX schema and metadata set can be serialized according to an http URI syntax. It is worthwhile to mention that URN focuses on acts identification, while Linked Data principles focus on identifying a resource on the Web.

In the following sections the http serialization of the urn LEX schema is reported.

D2 The Http LEX Identifier Structure

The http hierarchical structure of the LEX identifier is the following:

```
"http://" host-name "/lex/" jurisdiction "/" local-name
```

where:

- <host-name> represents the name of the organization server publishing the resource;
- "lex" is the equivalent of the URN namespace ID and provides the reference to the naming convention adopted;
- <jurisdiction> and <local-name> share meaning and syntax of the corresponding components in the LEX specifications.

The <jurisdiction> element follows the syntax rules of the corresponding element in the URN specification, therefore it has the following structure:

```
jurisdiction = jurisdiction-code *(";" jurisdiction-unit)
```

The character ";" still separates the identification code of the country or jurisdiction where the source of law is issued (<jurisdiction-code>) from any possible administrative hierarchical sub-structures defined by each country or organisation according to its own legal system.

The <local-name> follows the FRBR model as implemented by the LEX specifications, therefore its http structure is the following:

local-name = work "/"@/" expression "\$/" manifestation

The content of URN:LEX identifier elements is directly transferred to the corresponding elements of its http version, except for characters outside the ASCII set: such characters have to be converted into a valid ASCII format using the typical URL percent encoding rules.

D3 The Http LEX Identifier at Work Level

According to the corresponding level of the URN version, the http LEX identifier structure at work level is the following:

work = authority "/" measure "/" details *("/" annex)

The elements <authority>, <measure> and <annex> follow the same syntax rules of the corresponding elements in the URN specification.

Examples of http identifiers at <work> level, corresponding to the urn examples in [Section 6.4](#), are the following:

```
http://<host-name>/lex/it/stato/legge/2006-05-14;22
http://<host-name>/lex/uk/ministry.justice/decreree/1999-10-07;45
http://<host-name>/lex/ch;glarus/regiere/erlass/2007-10-15;963
http://<host-name>/lex/es/tribunal.supremo/decision/2001-09-28;68
http://<host-name>/lex/fr/assemblee.nationale/proposition.loi/
    13.legislature;1762
http://<host-name>/lex/br/estado/constituicao/1988-10-05;lex-1
http://<host-name>/lex/fsf.org/free.software.foundation/
    general.public.license/2007-06-29;lex-1
http://<host-name>/lex/nl/hoge.raad/besluit/2008-04-01;bc8581
```

D4 The Http LEX Identifier at Expression Level

According to the corresponding level of the URN version, the http LEX structure at expression level is the following:

expression = version ["/" language]

The elements <version> and <annex> follow the same syntax rules of the corresponding elements in the URN specification.

Examples of http identifiers at expression level, corresponding to the urn examples in [Section 6.6](#), are the following:

```
http://<host-name>/lex/ch/etat/loi/2006-05-14;22/@/origine1/fr
    (original version in French)
http://<host-name>/lex/ch/staat/gesetz/2006-05-14;22/@/original/de
    (original version in German)
```


<http://<host-name>/lex/ch/etat/loi/2006-05-14;22/@/2008-03-12/fr>
(amended version in French)
<http://<host-name>/lex/ch/staat/gesetz/2006-05-14;22/@/2008-03-12/de>
(amended version in German)
<http://<host-name>/lex/be/conseil.etat/decision/2008-07-09;185.273/@/origine1/fr>
(original version in French of a Belgian decision)

D5 The Http LEX Identifier at Manifestation Level

Information provided in the URN version at manifestation level is differently accommodated in the corresponding level of the http LEX identifier.

The `<editor>` element, reported at manifestation level in the urn LEX version, is an information already contained in the `<host-name>` of the http LEX identifier, therefore it is omitted in the `<manifestation>` elements.

Similarly the `<feature>` element is omitted since it loses its meaning which would derived from the comparison between different manifestations.

The `<format>` element is reported as unique extension of the data format in which the manifestation is drafted. The value is compliant with the registered file extensions, thus it can be "pdf" for PDF, "doc" for MS Word, "xml" for XML documents, "tif" for tiff image format, etc.

Therefore the http LEX structure at manifestation level is the following:

```
manifestation = [ component *(";" specification)] "." format
```

The element `<component>` follows the same syntax rules of the corresponding element in the URN specification.

Examples of http identifiers at manifestation level, corresponding to the urn examples in [Section 6.7](#) are the following:

[http://www.senato.it/lex/it/stato/legge/2000-04-03;56/\\$/testo.xml](http://www.senato.it/lex/it/stato/legge/2000-04-03;56/$/testo.xml)
(body of the Italian law 3 April 2000, n. 56, published by the Italian Senate in xml format)
[http://www.senato.it/lex/it/stato/legge/2000-04-03;56/\\$/figura.1.pdf](http://www.senato.it/lex/it/stato/legge/2000-04-03;56/$/figura.1.pdf)
(Figure 1 in PDF format of the Italian law 3 April 2000, n. 56, published by the Italian Senate)
[http://www.juradmin.eu/jurifast/lex/eu/tibunal.justicia/sentencia/2009-06-11;33-08/@/original/es/\\$/todo.html](http://www.juradmin.eu/jurifast/lex/eu/tibunal.justicia/sentencia/2009-06-11;33-08/@/original/es/$/todo.html)
(the Spanish http LEX identifier of the html format of the whole

Judgement of the European Court of Justice n. 33/08 of 11/06/2009,
in Spanish version, published by the Juriadmin site in the
Jurifast data base)

<http://eur-lex.europa.eu/lex/eu/commission/directive/>

2010-03-09;2010-19-EU/\$/body.xml

(body of the EU Directive n. 2010-19-EU, dated 2010-03-09, in its
XML format published by Eur-Lex)