Internet Engineering Task Force

Internet-Draft

Intended status: Standards Track

Expires: September 15, 2016

H. Stenn Network Time Foundation March 14, 2016

Network Time Protocol I-Do Extension Field draft-stenn-ntp-i-do-00

Abstract

The first implementation of NTPv4 was released in 2003. NTPv4 is defined by RFC 5905 [RFC5905]. It contains a public-key security protocol, autokey, which is defined by RFC 5906 [RFC5906]. Until very recently, autokey has been the only defined "user" of NTP packet Extension Fields. New proposals for extension fields are being written and there is currently no convenient way to learn if a remote instance of NTP supports any extension fields or not. This proposal contains a method to tell a remote instance of NTP what we support, and ask what they support.

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of \underline{BCP} 78 and \underline{BCP} 79.

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at http://datatracker.ietf.org/drafts/current/.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on September 15, 2016.

Copyright Notice

Copyright (c) 2016 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to <u>BCP 78</u> and the IETF Trust's Legal Provisions Relating to IETF Documents (http://trustee.ietf.org/license-info) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect

to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

Table of Contents

<u>1</u> .	Introduction										2
1	<u>.1</u> . Requirements Language										2
<u>2</u> .	The I-Do Extension Field										2
<u>3</u> .	Acknowledgements										4
<u>4</u> .	IANA Considerations										4
<u>5</u> .	Security Considerations .										4
<u>6</u> .	Normative References										5
Auth	nor's Address										5

1. Introduction

The first implementation of NTPv4 was released in 2003. NTPv4 is defined by RFC 5905 [RFC5905]. It contains a public-key security protocol, autokey, which is defined by RFC 5906 [RFC5906]. Until very recently, autokey has been the only defined "user" of NTP packet Extension Fields. New proposals for extension fields are being written and there is currently no convenient way to learn if a remote instance of NTP supports any extension fields or not. This proposal contains a method to tell a remote instance of NTP what we support, and ask what they support.

1.1. Requirements Language

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in RFC 2119 [RFC2119].

2. The I-Do Extension Field

If an incoming packet contains an unrecognized extension field, one of two things will happen. Either that extension field will be ignored, or the entire packet will be dropped. If an extension field is present there ordinarily SHOULD be a MAC following the extension field. Some extension fields are unable to be "signed" by a MAC, regardless of whether or not that MAC is a traditional MAC or an extension field MAC.

0										1										2										3		
0	1	2	3	4	5	6	7	8	9	0	1	2	3	4	5	6	7	8	9	0	1	2	3	4	5	6	7	8	9	0	1	
+-								+								+															+	-
	Field Type												Field Length																			
+-																+															+	-
	I-Do 1																															
+-																+															+	-
						I	- Do	1 c	V													P	ad	di	ng							
+-																															+	-

NTP Extension Field: REFID Suggestion

Field Type: TBD (Recommendation for IANA: 0x0007 (I-Do, MAC required), 0x2007 (I-Do, MAC OPTIONAL), 0x4007 (I-Do Response, MAC required), 0x6007 I-Do Response, MAC OPTIONAL))

Field Length: as needed

Payload: An enumeration of the suppported base Field Types, followed by any padding, 0x0000, needed to fill the payload to the desired 32-bit boundary.

Example: A system that wants to advertise support for Autokey and I-Do, sending to a system that wants to advertise support for I-Do, NTS, and MAC-As-Extension-Field

0										1										2										3	
0	1	2	3	4	5	6	7	8	9	0	1	2	3	4	5	6	7	8	9	0	1	2	3	4	5	6	7	8	9	0	1
+								+								+															+
Field Type (0x2007)										Field Length (0x0008)																					
+	. - .															+															+
	0×0007										0×0002											1									
+																+															+

NTP Extension Field: I-Do

0 1		2	3									
0 1 2 3 4 5 6 7 8 9 0 1	2 3 4 5 6 7	8 9 0 1 2 3 4	5 6 7 8 9 0 1									
+			+									
Field Type (0x6007)	F	ield Length (0x000a)									
+			+									
0x0003	I	0x0004										
+			+									
0×0007	1	0×0000										
+	+		+									

NTP Extension Field: I-Do Response

The sender of any I-Do extension field MUST send an extension field with a Field Type of 0x0007 (I-Do, MAC required) or 0x2007 (I-Do, MAC OPTIONAL) and SHOULD include a paylod with any 0x0000 padding values after enumerating the supported base Extension Field Types. The responding system MUST reply with an extension field with a Field Type of 0x4007 (I-Do Response, MAC required) or 0x6007 (I-Do Response, MAC OPTIONAL), and SHOULD include a paylod with any 0x0000 padding values after enumerating the supported base Extension Field Types.

The following information is included here until it is specified in a better location. If the Field Type does not have bit 0x2000 set, there MUST be a MAC included later in the packet for this field to be accepted. If the Field Type has bit 0x2000 set, the presence of a MAC later in the packet is OPTIONAL.

Any system that receives an I-Do extension field as either an "offer" or a "response" SHOULD scan the entire payload looking for nonzero values that specify the capabilities of the remote association.

Any system that receives an I-Do "offer", 0x0007 or 0x2007, SHOULD reply with an I-Do "response", 0x4007 or 0x6007.

Any system that sends an I-Do "offer" or "response" may send as few or as many of its supported Field Types as it chooses. At any subsequent time, either side may re-negotiate the list of supported field types it is prepared to accept from the other system by sending a new I-Do extension field.

The most-recently received I-Do list replaces any previous I-Do list.

3. Acknowledgements

The author wishes to acknowledge the contributions of Joey Saccadonuts.

4. IANA Considerations

This memo requests IANA to allocate NTP Extension Field Types 0x0007 (I-Do), 0x2007 (I-Do, MAC OPTIONAL), 0x4007 (I-Do Response), and 0x6007 (I-Do Response, MAC OPTIONAL) for this proposal.

5. Security Considerations

Additional information TBD

6. Normative References

- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate
 Requirement Levels", BCP 14, RFC 2119,
 DOI 10.17487/RFC2119, March 1997,
 http://www.rfc-editor.org/info/rfc2119.
- [RFC5905] Mills, D., Martin, J., Ed., Burbank, J., and W. Kasch,
 "Network Time Protocol Version 4: Protocol and Algorithms
 Specification", RFC 5905, DOI 10.17487/RFC5905, June 2010,
 http://www.rfc-editor.org/info/rfc5905>.
- [RFC5906] Haberman, B., Ed. and D. Mills, "Network Time Protocol
 Version 4: Autokey Specification", RFC 5906,
 DOI 10.17487/RFC5906, June 2010,
 http://www.rfc-editor.org/info/rfc5906>.

Author's Address

Harlan Stenn
Network Time Foundation
P.O. Box 918
Talent, OR 97540
US

Email: stenn@nwtime.org