

Internet Engineering Task Force
Internet-Draft
Expires: November 18, 2005

S. Kumar
Samsung India Software Operations
L. Morand
France Telecom R&D
A. Yegin
Samsung Advanced Institute of
Technology
S. Madanapalli
Samsung India Software Operations
May 17, 2005

DHCPv4 option for PANA Authentication Agents
draft-suraj-dhcpv4-paa-option-00.txt

Status of this Memo

By submitting this Internet-Draft, each author represents that any applicable patent or other IPR claims of which he or she is aware have been or will be disclosed, and any of which he or she becomes aware will be disclosed, in accordance with [Section 6 of BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF), its areas, and its working groups. Note that other groups may also distribute working documents as Internet-Drafts.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

The list of current Internet-Drafts can be accessed at
<http://www.ietf.org/ietf/lid-abstracts.txt>.

The list of Internet-Draft Shadow Directories can be accessed at
<http://www.ietf.org/shadow.html>.

This Internet-Draft will expire on November 18, 2005.

Copyright Notice

Copyright (C) The Internet Society (2005).

Abstract

This document defines a new Dynamic Host Configuration Protocol version 4 (DHCPv4) option that contains a list of domain names or

Internet-Draft

DHCPv4 PAA Option

May 2005

IPv4 addresses that can be mapped to one or more of PANA Authentication Agents (PAA). This is one of the many methods that a PANA Client (PaC) can use to locate PANA Authentication Agents (PAA).

Table of Contents

| | | |
|---------------------|--|--------------------|
| 1. | Introduction | 3 |
| 2. | Terminology | 4 |
| 3. | Requirements | 5 |
| 4. | DHCPv4 specification dependency | 6 |
| 5. | PANA Authentication Agent DHCPv4 Option | 7 |
| 5.1 | PANA Authentication Agent Domain Name List | 7 |
| 5.2 | PANA Authentication Agent IPv4 Address List | 8 |
| 6. | Client Operation | 10 |
| 7. | DHCPv4 Server Operation | 11 |
| 8. | Security Considerations | 12 |
| 9. | IANA Considerations | 13 |
| 10. | Future Work | 14 |
| 11. | Normative References | 14 |
| | Authors' Addresses | 14 |
| | Intellectual Property and Copyright Statements | 16 |

[1.](#) Introduction

The Protocol for carrying Authentication for Network Access (PANA) [\[1\]](#) defines a new Extensible Authentication Protocol (EAP) lower layer that uses IP between the protocol end points.

The PANA protocol is run between a PANA Client (PaC) and a PANA Authentication Agent (PAA) in order to perform authentication and authorization for the network access service.

This document specifies a new DHCPv4 option [\[2\]](#) that allows PANA client (PaC) to discover PANA Authentication Agents (PAA). This is one of the many methods for locating PAAs: manual configuration is an example of another one.

[2.](#) Terminology

This document uses the PANA terminology defined in [\[1\]](#).

This document uses the DHCP terminology defined in [\[2\]](#) and [\[3\]](#).

[3.](#) Requirements

The keywords MUST, MUST NOT, REQUIRED, SHALL, SHALL NOT, SHOULD, SHOULD NOT, RECOMMENDED, MAY, and OPTIONAL, when they appear in this document, are to be interpreted as described in [\[4\]](#).

[4.](#) DHCPv4 specification dependency

This document describes a new DHCPv4 option for obtaining a list of domain names or IPv4 addresses to locate a PANA Authentication Agent. This document should be read in conjunction with the DHCPv4 specifications [\[2\]](#) and [\[3\]](#).

Definitions for terms and acronyms not specifically defined in this document are defined in [\[2\]](#) and [\[3\]](#).

[5.](#) PANA Authentication Agent DHCPv4 Option

This document defines a DHCPv4 option that carries either a 32-bit (binary) IPv4 address list or, preferably, a domain name list to be used by the PANA client to locate a PANA authentication Agent.

The option has two encodings, specified by the encoding byte ('enc') that follows the code byte. If the encoding byte has the value 0, it

is followed by a list of domain names, as described below ([Section 5.1](#)). If the encoding byte has the value 1, it is followed by one or more IPv4 addresses ([Section 5.2](#)). All implementations MUST support both encodings. The 'option-length' field indicates the total number of octets in the option following the 'option-length' field, including the encoding byte.

[5.1](#) PANA Authentication Agent Domain Name List

If the 'enc' byte has a value of 0, the encoding byte is followed by a sequence of labels, encoded according to [Section 3.1 of RFC 1035](#) [5], quoted below:

Domain names in messages are expressed in terms of a sequence of labels. Each label is represented as a one octet length field followed by that number of octets. Since every domain name ends with the null label of the root, a domain name is terminated by a length byte of zero. The high order two bits of every length octet must be zero, and the remaining six bits of the length field limit the label to 63 octets or less. To simplify implementations, the total length of a domain name (i.e., label octets and label length octets) is restricted to 255 octets or less.

[RFC 1035](#) encoding was chosen to accommodate future internationalized domain name mechanisms.

The option MAY contain multiple domain names, but these SHOULD refer to different NAPTR records, rather than different A records. Domain names MUST be listed in order of preference.

Use of multiple domain names is not meant to replace NAPTR and SRV records, but rather to allow a single DHCPv4 server to indicate multiple PANA Authentication Agents available in the same access network.

Clients MUST support compression according to the encoding in [Section 4.1.4](#) of [5].

If the length of the domain list exceeds the maximum permissible

within a single option (254 octets), then the domain list MUST be

represented in the DHCP message as specified in [6].

The DHCPv4 option for this encoding has the format shown in Fig. 1.




Figure 1: DHCPv4 option for PAA Domain Name List

option-code: OPTION_PANA_AGENT(TBD)

option-length: Number of octets following the 'option-length' field, including the encoding byte, in octets; variable.

enc: Encoding byte set to 0

PAA Domain Name List: The domain names of the PANA Authentication Agents for the client to use. The domain names are encoded according to [Section 3.1 of RFC 1035](#) [5].

5.2 PANA Authentication Agent IPv4 Address List

If the 'enc' byte has a value of 1, the encoding byte is followed by a list of IPv4 addresses indicating one or more PANA Authentication Agents available to the PANA client. PAAs MUST be listed in order of preference.

The DHCPv4 option for this encoding has the format shown in Fig. 2.




Figure 2: DHCPv4 option for PAA IPv4 Address List

option-code: OPTION_PANA_AGENT(TBD)

option-length: Number of octets following the 'option-length' field, including the encoding byte in octets; Must be a multiple of 4 plus one.

enc: Encoding byte set to 1

PAA IP Address: IPv4 address of a PAA for the PaC to use. The PAAs are listed in the order of preference for use by the PaC.

[6.](#) Client Operation

The client requests PAA DHCPv4 Option in a Parameter Request List as described in [\[2\]](#) and [\[3\]](#).

If the PAA DHCPv4 option provided in response by the DHCPv4 server contains multiple domain names, the client MUST try the records in the order listed. The client only resolves the subsequent domain names if attempts to contact the first one failed or denote a domain administratively prohibited by client policy.

If the PAA DHCPv4 option provided in response by the DHCPv4 server contains multiple IP addresses, the client MUST try the records in the order listed.

[7.](#) DHCPv4 Server Operation

If a DHCPv4 server is configured with both PAA domain name list and PAA IP address list, the DHCPv4 server should responds to the request with the domain name list to be used by the PANA client.

A DHCP server MUST NOT mix the two list types (domain names and IPv4 address) in the same DHCPv4 message, even if it sends two different instances of the same option.

[8.](#) Security Considerations

The security considerations in [\[1\]](#) and [\[2\]](#) apply. If an adversary manages to modify the response from a DHCP server or insert its own response, a PANA Client could be led to contact a rogue PANA Agent, possibly one that then intercepts call requests or denies service.

[9.](#) IANA Considerations

IANA assignment for the following DHCPv4 option code is needed.

| Option Name | Value |
|------------------|-------|
| ----- | |
| OPTION_PAA_AGENT | TBD |

[10.](#) Future Work

Defining similar options for DHCPv6 [\[7\]](#).

[11.](#) Normative References

- [1] Forsberg, D., Ohba, Y., Patil, B., Tschofenig, H., and A. Yegin, "Protocol for Carrying Authentication for Network Access (PANA), [draft-ietf-pana-pana-08](#) (work in progress)", Novemeber 2005.

- [2] Droms, R., "Dynamic Host Configuration Protocol", [RFC 2131](#), March 1997.
- [3] Alexander, S. and R. Droms, "DHCP Options and BOOTP Vendor Extensions", [RFC 2132](#), March 1997.
- [4] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), March 1997.
- [5] Mockapetris, P., "Domain names - implementation and specification", STD 13, [RFC 1035](#), November 1987.
- [6] Lemon, T. and S. Cheshire, "Encoding Long Options in the Dynamic Host Configuration Protocol (DHCPv4)", [RFC 3396](#), November 2002.
- [7] Droms, R., Bound, J., Volz, B., Lemon, T., Perkins, C., and M. Carney, "Dynamic Host Configuration Protocol for IPv6 (DHCPv6)", [RFC 3315](#), July 2003.

Authors' Addresses

Suraj Kumar
Samsung India Software Operations
No. 3/1 Millers Road
Bangalore
India

Phone: +91 80 51197777
Email: suraj.kumar@samsung.com

Lionel Morand
France Telecom R&D
38-40 rue du general Leclerc
Issy-les-Moulineaux, F-92130

France

Phone: +33 1 4529 6257

Email: lionel.morand@francetelecom.com

Alper E. Yegin

Samsung Advanced Institute of Technology

75 West Plumeria Drive

San Jose, CA 95134

USA

Phone: +1 408 544 5656

Email: alper.yegin@samsung.com

Syam Madanapalli

Samsung India Software Operations

No. 3/1 Millers Road

Bangalore

India

Phone: +91 80 51197777

Email: syam@samsung.com

Intellectual Property Statement

The IETF takes no position regarding the validity or scope of any Intellectual Property Rights or other rights that might be claimed to pertain to the implementation or use of the technology described in this document or the extent to which any license under such rights might or might not be available; nor does it represent that it has made any independent effort to identify any such rights. Information on the procedures with respect to rights in RFC documents can be found in [BCP 78](#) and [BCP 79](#).

Copies of IPR disclosures made to the IETF Secretariat and any assurances of licenses to be made available, or the result of an attempt made to obtain a general license or permission for the use of such proprietary rights by implementers or users of this specification can be obtained from the IETF on-line IPR repository at <http://www.ietf.org/ipr>.

The IETF invites any interested party to bring to its attention any copyrights, patents or patent applications, or other proprietary rights that may cover technology that may be required to implement this standard. Please address the information to the IETF at ietf-ipr@ietf.org.

Disclaimer of Validity

This document and the information contained herein are provided on an "AS IS" basis and THE CONTRIBUTOR, THE ORGANIZATION HE/SHE REPRESENTS OR IS SPONSORED BY (IF ANY), THE INTERNET SOCIETY AND THE INTERNET ENGINEERING TASK FORCE DISCLAIM ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY WARRANTY THAT THE USE OF THE INFORMATION HEREIN WILL NOT INFRINGE ANY RIGHTS OR ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

Copyright Statement

Copyright (C) The Internet Society (2005). This document is subject to the rights, licenses and restrictions contained in [BCP 78](#), and except as set forth therein, the authors retain all their rights.

Acknowledgment

Funding for the RFC Editor function is currently provided by the Internet Society.

