

Network Working Group  
Internet-Draft  
Intended status: Standards Track  
Expires: January 5, 2016

A. Takacs  
F. Fondelli  
B. Tremblay  
Ericsson  
Z. Ali  
Cisco Systems  
July 6, 2015

**RSVP-TE Recovery Extension for data plane initiated reversion,  
and protection timer signaling  
draft-takacs-ccamp-revertive-ps-11**

Abstract

RSVP-TE recovery extensions are specified in [[RFC4872](#)] and [[RFC4873](#)]. Currently recovery signaling does not support the request for revertive protection and recovery timers values. This document extends the PROTECTION Object format allowing sub-TLVs, and defines two sub-TLVs to carry wait-to-restore and hold-off intervals.

## Requirements Language

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in

## Status of this Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <http://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on January 2016.

## Copyright Notice

Copyright (c) 2014 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.



## Table of Contents

<a href="#">1.</a>	Introduction . . . . .	<a href="#">4</a>
<a href="#">2.</a>	Updated PROTECTION Object format and sub-TLVs . . . . .	<a href="#">6</a>
<a href="#">3.</a>	Error handling . . . . .	<a href="#">9</a>
<a href="#">4.</a>	IANA Considerations . . . . .	<a href="#">10</a>
<a href="#">5.</a>	Security Considerations . . . . .	<a href="#">11</a>
<a href="#">6.</a>	References . . . . .	<a href="#">12</a>
	Authors' Addresses . . . . .	<a href="#">13</a>

## 1. Introduction

Generalized MPLS (GMPLS) extends MPLS to include support for different switching technologies [RFC3471]. These switching technologies provide several protection schemes [RFC4426][RFC4427] (e.g. 1+1, 1:N, M:N). Many characteristics of those protection schemes are common regardless of the switching technology (e.g. TDM, LSC, etc). GMPLS RSVP-TE signaling has been extended to support the various protection schemes and establish Label Switched Paths (LSPs) configuring its specific protection characteristics [RFC4426][RFC4872].

Currently RSVP-TE extensions do not address the values of protection switching timers. It also does not provide information on the protection switching operation mode (i.e., revertive or non-revertive) and sub-network connection (SNC) protection options.

The Hold-off time (HOFF) is defined as the time between the reporting of signal fail or degrade, and the initialization of the recovery switching operation [RFC4427]. This timer is useful to limit the number of switch actions when multiple layers of recovery are being used, or in case of 1+1 unidirectional protection scheme [G.808.1] to prevent too early switching due to the differential delay between the short and long path.

The Wait-to-Restore time (WTR) is defined as a period of time that must elapse after a recovered fault before an LSP can be used again to transport the normal traffic and/or to select the normal traffic from the LSP [RFC4427]. The WTR time is fundamental in revertive mode of operation, to prevent frequent operation of the protection switch due to an intermittent defect [G.808.1].

Reversion refers to the process of moving normal traffic back to the original working LSP after the failure is cleared and the path is repaired [RFC4426][RFC4427][RFC4872]. In transport networks reversion is desirable since the protection path may not be optimal from a routing and resource consumption point of view, additionally, moving traffic back to the working LSP allows the protection resources to be used to protect other LSPs.


WTR, HOFF timers and SNC protection options must be accurately configured at both ends of the LSP. Operators may need to tune WTR and HOFF timers on a per LSP basis to ensure best protection switching performance (e.g., account for differential delays between

worker and protection paths). Currently these values are either pre-configured to a default value (and so may be suboptimal for some of the LSPs) or need to be manually set/tuned after the connections have been established. Since these parameters are important for recovery in transport networks, it is desirable that GMPLS RSVP-TE protection signaling carries the necessary information.

This document extends the PROTECTION Object format allowing sub-TLVs, and defines three sub-TLVs to carry WTR, HOFF timer values and SNC protection options.


## 2. Updated PROTECTION Object format and sub-TLVs

In [RFC4872] and [RFC4873] the PROTECTION object is specified to support end-to-end and segment recovery. In order to ease addition of protection attributes the PROTECTION Object is extended to carry sub-TLVs. The new format updates the PROTECTION Object format of C-Type TBD (suggested value 3). The updated format is depicted below. IANA is requested to maintain the TLV space for the PROTECTION Object.




This document specifies three new sub-TLVs.


WTR - Wait-to-Restore time sub-TLV specifies the WTR time. If the WTR field is 0 the protection switching operation mode is non-revertive, otherwise revertive operation with the signalled timer (in milliseconds) is requested. The value 0xffffffff is reserved, and refers to a locally pre-configured WTR value.



HOFF - Hold-off time sub-TLV specifies the HOFF time. The values are in milliseconds. The value 0xffffffff is reserved, and refers to a locally pre-configured HOFF value.



SNC protection options sub-TLV specifies attributes of the SNC protection.



Mode field (3 bits): The mode values are defined as follows:

SNC Protection Mode -----	Value -----
Reserved	0x0
SNC/N (Sub Network Connection protection with Non-intrusive monitoring)	0x1
SNC/I (Sub Network Connection protection with Inherent monitoring)	0x2
SNC/S (Sub Network Connection protection with Sub-layer monitoring)	0x3

TCM-ID: Tandem Connection Monitoring Identifier used. This is applicable when SNC mode is set to SNC/S.

Reserved field (29 bits): This field is reserved for future use. It MUST be set to 0 when sent and MUST be ignored when received.

In the case of end-to-end protection the PROTECTION Object is



inserted at the top level in the Path message, the WTR and HOFF

options sub-TLVs correspond to the end-to-end protection. In the case when a segment of the LSP is to be protected and the WTR and HOFF timers for the protection segment are to be set by signaling, explicit segment recovery control has to be used, i.e., the PROTECTION Object with the desired timers set must be inserted in the appropriate Secondary Explicit Route Object (SERO).

### **3. Error handling**

In the case a specific configuration of the timers is not supported the corresponding error should be generated and sent in the PathErr message: "Routing Problem/Unsupported WTR value" or "Routing Problem/Unsupported HOFF value".

## **4. IANA Considerations**

### **4.1. New TLV space for the PROTECTION object**

A new TLV space needs to be opened and maintained for the PROTECTION Object in the "Class Names, Class Numbers, and Class Types " Registry.

### **4.3. New RSVP error sub-code**

For Error Code = 24 "Routing Problem" (see [[RFC3209](#)]) the following sub-codes are defined.

Sub-code	Value
-----	-----
Unsupported WTR value	To be assigned by IANA
Unsupported HOFF value	To be assigned by IANA

## **5. Security Considerations**

This document introduces no new security issues. The considerations in [[RFC4872](#)] and [[RFC4873](#)] apply.

## **6. References**

- [G.808.1] "Generic protection switching -- Linear trail and subnetwork protection", ITU-T Recommendation G.808.1, March 2006.
- [IEEE-PBBTE]  
"IEEE 802.1Qay Draft Standard for Provider Backbone Bridging Traffic Engineering", work in progress.
- [RFC3471] "Generalized Multi-Protocol Label Switching (GMPLS) Signaling Functional Description", [RFC 3471](#), January 2003.
- [RFC4426] "Generalized Multi-Protocol Label Switching (GMPLS) Recovery Functional Specification", [RFC 4426](#), March 2006.
- [RFC4427] "Recovery (Protection and Restoration) Terminology for Generalized Multi-Protocol Label Switching (GMPLS)", [RFC 4427](#), March 2006.
- [RFC4872] "RSVP-TE Extensions in Support of End-to-End Generalized Multi-Protocol Label Switching (GMPLS) Recovery", [RFC 4872](#), May 2007.
- [RFC4873] "GMPLS Segment Recovery", [RFC 4873](#), May 2007.



Authors' Addresses

Attila Takacs  
Ericsson  
Laborc u. 1.  
Budapest, 1037  
Hungary

Email: attila.takacs@ericsson.com

Francesco Fondelli  
Ericsson  
Via Negrone  
Genova, 16153  
Italy

Email: francesco.fondelli.ericsson.com

Benoit Tremblay  
Ericsson  
8400 Decarie.  
Montreal, Quebec H4P 2N2  
Canada

Email: benoit.c.tremblay@ericsson.com

Zafar Ali  
Cisco Systems  
Email: zali@cisco.com



