

OSPF Working Group  
Internet-Draft  
Intended status: Standards Track  
Expires: September 9, 2016

J. Tantsura  
U. Chunduri  
Ericsson  
March 8, 2016

**Signaling MSD (Maximum SID Depth) using OSPF**  
**draft-tantsura-ospf-segment-routing-msd-00**

Abstract

This document proposes a way to expose Maximum SID Depth (MSD) supported by a node at node and/or link level by an OSPF Router. In a Segment Routing (SR) enabled network a centralized controller that programs SR tunnels at the head-end node needs to know the MSD information at node level and/or link level to push the label stack of an appropriate depth. Here the term OSPF means both OSPFv2 and OSPFv3.

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <http://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on September 9, 2016.

Copyright Notice

Copyright (c) 2016 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in [Section 4.e](#) of

the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

## Table of Contents

<a href="#">1.</a>	Introduction . . . . .	<a href="#">2</a>
<a href="#">1.1.</a>	Conventions used in this document . . . . .	<a href="#">3</a>
<a href="#">1.1.1.</a>	Terminology . . . . .	<a href="#">3</a>
<a href="#">1.2.</a>	Requirements Language . . . . .	<a href="#">3</a>
<a href="#">2.</a>	Terminology . . . . .	<a href="#">3</a>
<a href="#">3.</a>	Node MSD TLV . . . . .	<a href="#">3</a>
<a href="#">4.</a>	LINK MSD sub-TLV . . . . .	<a href="#">4</a>
<a href="#">5.</a>	Acknowledgements . . . . .	<a href="#">4</a>
<a href="#">6.</a>	IANA Considerations . . . . .	<a href="#">4</a>
<a href="#">7.</a>	Security Considerations . . . . .	<a href="#">4</a>
<a href="#">8.</a>	References . . . . .	<a href="#">5</a>
<a href="#">8.1.</a>	Normative References . . . . .	<a href="#">5</a>
<a href="#">8.2.</a>	Informative References . . . . .	<a href="#">5</a>
	Authors' Addresses . . . . .	<a href="#">6</a>

## [1.](#) Introduction

When Segment Routing tunnels are computed by a centralized controller, it is crucial that the controller knows the MSD "Maximum SID Depth" of the node or link SR tunnel exits over, so it doesn't download a path with SID (label stack) of a depth more than the node or link used is capable of imposing. This document describes how to use OSPF to expose the MSD of the node or link to a centralized controller.

PCEP SR extensions [[I-D.ietf-pce-segment-routing](#)] has defined MSD, to signal in SR PCE Capability TLV, METRIC Object. However, If PCEP is not supported by a node (head-end of the SR tunnel) and controller does not participate in IGP routing it has no way to learn the MSD of the node or link configured. BGP-LS [[I-D.ietf-idr-ls-distribution](#)] defines a way to expose topology and associated different attributes, capabilities of the nodes in that topology to a centralized controller and MSD has been defined in [[I-D.tantsura-bgp-ls-segment-routing-msd](#)]. For this information to be advertised by BGP for the all nodes and links of the network, where this is provisioned, OSPF module should have this information in the LSDB.

[[I-D.ietf-ospf-mpls-etc](#)] defines, RLSDC which indicates how many labels a node can read to take a decision to insert an Entropy Label (EL) and is different than how many labels a node can push as defined by MSD in this draft.



### **1.1. Conventions used in this document**

#### **1.1.1. Terminology**

BGP-LS: Distribution of Link-State and TE Information using Border Gateway Protocol

OSPF: Open Shortest Path First

MSD: Maximum SID Depth

PCC: Path Computation Client

PCE: Path Computation Element

PCEP: Path Computation Element Protocol

SID: Segment Identifier

SR: Segment routing

### **1.2. Requirements Language**

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [RFC 2119](#) [[RFC2119](#)].

## **2. Terminology**

This memo makes use of the terms defined in [[RFC4970](#)].

## **3. Node MSD TLV**

A new TLV within the body of the OSPF RI Opaque LSA, called Node MSD TLV is defined to carry the provisioned SID depth of the router originating the RI LSA. Node MSD is the lowest MSD supported by the node.

The Type (2 bytes) of this TLV is TBD.

Length is 2 bytes, and

the Value field contains MSD of the router originating the RI LSA. Node MSD is a number in the range of 0-254. 0 represents lack of the ability to push MSD of any depth; any other value represents that of the node. This value SHOULD represent the lowest value supported by node.



This TLV is applicable to OSPFv2 and to OSPFv3 [[RFC5838](#)] and is optional. The scope of the advertisement is specific to the deployment.

#### **4. LINK MSD sub-TLV**

A new sub-TLV called Link MSD sub-TLV is defined to carry the provisioned SID depth of the interface associated with the link.

The Type (2 bytes) of this TLV is TBD.

Length is 2 bytes, and

the Value field contains Link MSD of the router originating the corresponding LSA as specified for OSPFv2 and OSPFv3. Link MSD is a number in the range of 0-254. 0 represents lack of the ability to push MSD of any depth; any other value represents that of the particular link MSD value.

For OSPFv2, the Link level MSD value is advertised as an optional Sub-TLV of OSPFv2 Extended Link TLV as defined in [[RFC7684](#)].

For OSPFv3, the Link level MSD value is advertised as an optional Sub-TLV of the Router-Link TLV as defined in [[I-D.ietf-ospf-ospfv3-lsa-extend](#)].

#### **5. Acknowledgements**

TBD

#### **6. IANA Considerations**

This document includes a request to IANA to allocate TLV type codes for the new TLV proposed in [Section 3](#) of this document from OSPF Router Information (RI) TLVs Registry as defined by [[RFC4970](#)]. Also for link MSD, we request IANA to allocate new sub-TLV codes as proposed in [Section 4](#) from OSPFv2 Extended Link Opaque LSAs Extended Link TLV registry and from Router-Link TLV defined in OSPFv3 Extended-LSA Sub-TLV registry.

#### **7. Security Considerations**

This document describes a mechanism for advertising Segment Routing SID depth supported at node and link level information through OSPF LSAs and does not introduce any new security issues.



## 8. References

### 8.1. Normative References

- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), DOI 10.17487/RFC2119, March 1997, <<http://www.rfc-editor.org/info/rfc2119>>.
- [RFC4970] Lindem, A., Ed., Shen, N., Vasseur, JP., Aggarwal, R., and S. Shaffer, "Extensions to OSPF for Advertising Optional Router Capabilities", [RFC 4970](#), DOI 10.17487/RFC4970, July 2007, <<http://www.rfc-editor.org/info/rfc4970>>.

### 8.2. Informative References

- [I-D.ietf-idr-ls-distribution]  
Gredler, H., Medved, J., Previdi, S., Farrel, A., and S. Ray, "North-Bound Distribution of Link-State and TE Information using BGP", [draft-ietf-idr-ls-distribution-13](#) (work in progress), October 2015.
- [I-D.ietf-ospf-mpls-elc]  
Xu, X., Kini, S., Sivabalan, S., Filsfils, C., and S. Litkowski, "Signaling Entropy Label Capability Using OSPF", [draft-ietf-ospf-mpls-elc-01](#) (work in progress), November 2015.
- [I-D.ietf-ospf-ospfv3-lsa-extend]  
Lindem, A., Mirtorabi, S., Roy, A., and F. Baker, "OSPFv3 LSA Extendibility", [draft-ietf-ospf-ospfv3-lsa-extend-09](#) (work in progress), November 2015.
- [I-D.ietf-pce-segment-routing]  
Sivabalan, S., Medved, J., Filsfils, C., Crabbe, E., Lopez, V., Tantsura, J., Henderickx, W., and J. Hardwick, "PCEP Extensions for Segment Routing", [draft-ietf-pce-segment-routing-06](#) (work in progress), August 2015.
- [I-D.tantsura-bgp-ls-segment-routing-msd]  
Tantsura, J., Mirsky, G., Sivabalan, S., and U. Chunduri, "Signaling Maximum SID Depth using Border Gateway Protocol Link-State", [draft-tantsura-bgp-ls-segment-routing-msd-02](#) (work in progress), January 2016.





- [RFC5838] Lindem, A., Ed., Mirtorabi, S., Roy, A., Barnes, M., and R. Aggarwal, "Support of Address Families in OSPFv3", [RFC 5838](http://www.rfc-editor.org/info/rfc5838), DOI 10.17487/RFC5838, April 2010, <<http://www.rfc-editor.org/info/rfc5838>>.
- [RFC7684] Psenak, P., Gredler, H., Shakir, R., Henderickx, W., Tantsura, J., and A. Lindem, "OSPFv2 Prefix/Link Attribute Advertisement", [RFC 7684](http://www.rfc-editor.org/info/rfc7684), DOI 10.17487/RFC7684, November 2015, <<http://www.rfc-editor.org/info/rfc7684>>.

#### Authors' Addresses

Jeff Tantsura  
Ericsson

Email: [jeff.tantsura@ericsson.com](mailto:jeff.tantsura@ericsson.com)

Uma Chunduri  
Ericsson

Email: [uma.chunduri@ericsson.com](mailto:uma.chunduri@ericsson.com)

