

NETCONF Working Group Q.
Wu
Internet-Draft Q.
Ma
Intended status: Standards Track
Huawei
Expires: May 2, 2021 L.
Geng P.
Liu
China
Mobile
October 29,
2020

**Telemetry Data Export capability
draft-[tao-netconf-data-export-capabilities-02](#)**

Abstract

This document proposes a YANG module for telemetry data export capability which augments system Capabilities model and provides additional telemetry data export attributes associated with system capability for transport dependent capability negotiation.

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <https://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on May 2, 2021.

Copyright Notice

Copyright (c) 2020 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<https://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must

include Simplified BSD License text as described in [Section 4](#).e of

Wu, et al.
1]

Expires May 2, 2021

[Page

the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

Table of Contents

[1](#) [1.1](#) [2](#) [3](#) [4](#) [9](#) [10](#) [11](#) [12](#) [13](#) [15](#)

[1](#). Introduction

[1.1](#). Terminology

[2](#). Data Export capability

[2.1](#). Tree Diagram

[3](#). YANG Module

[4](#). IANA Considerations

[4.1](#). Updates to the IETF XML Registry

[4.2](#). Updates to the YANG Module Names Registry

[5](#). Security Considerations

[6](#). Contributors

[7](#). References

[7.1](#). Normative References

[7.2](#). Informative References

[Appendix A](#). Usage Example of interaction between telemetry data export capabilities and Adaptive Subscription . . .

Authors' Addresses

1. Introduction

Notification capability model defined in [I-D.netconf-notification-capabilities] allows a client to discover a set of capabilities supported by the server (e.g., basic system capability and YANG-Push related capabilities) both at implementation-time and run-time. These "capabilities" permit the client to adjust its behavior to take advantage of the features exposed by the device.

However pre-configuration for some transport specific parameters (e.g., transport protocol, encoding format, encryption by the client is still inevitable, which may cause unexpected failure and additional message exchange between client and server.

This document proposes a YANG module for telemetry data export capability which augments System Capabilities model and provide additional data export attributes for transport dependent capability negotiation.

1.1. Terminology

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "NOT RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in

[BCP](#)

[14](#) [[RFC2119](#)] [[RFC8174](#)] when, and only when, they appear in all capitals, as shown here.

2. Data Export capability

The YANG module `ietf-notification-capabilities` defined in [I-D.netconf-notification-capabilities] specify the following server capabilities related to YANG Push:

- o A set of capabilities related to the amount of notifications the server can send out
- o Specification of which data nodes support on-change notifications.
- o Capability values can be specified on server level, datastore level or on specific data nodes (and their contained sub-tree) of a specific datastore. Capability values on a smaller, more specific part of the server's data always override more generic values.
- o On-change capability is not specified on a server level as different datastores usually have different on-change capabilities. On a datastore level on-change capability for configuration and state data can be specified separately.

These server capabilities are transport independent and session level

capabilities and can be provided either at implementation time or reported at run time.

This document augments system Capabilities model and provides additional data export attributes associated with system capabilities:

- o Specification of transport protocol the client can use to establish transport connection;
- o Specification of encoding selection(e.g., XML or JSON, to binary) of Data Modeled with YANG;
- o Specification of secure transport mechanisms that are needed by the client to communicate with the server;
- o Specification of the type of data compression algorithm (e.g., lossless data compression) the client can use for file compression and decompression
- o Specification of the notification message encapsulation type, either one notification per message or multiple notifications per message.

- o Specification of the update trigger type such as adaptive interval trigger, timer event based trigger, count threshold trigger, redundant suppression.

2.1. Tree Diagram

The following tree diagram [[RFC8340](#)] provides an overview of the data model.

```
module: ietf-data-export-capabilities
  augment /sysc:system-capabilities:
    +--ro data-export-capabilities
      +--ro transport-protocol?          identityref
      +--ro encoding-format?            identityref
      +--ro security-protocol?          identityref
      +--ro compression-mode?           identityref
    augment /sysc:system-capabilities/inc:subscription-capabilities:
      +--ro data-export-capabilities
      +--ro message-bundling-support?    boolean
    augment /sysc:system-capabilities/sysc:datastore-capabilities/
  sysc:per-node-capabilities:
    +--ro data-export-capabilities
      +--ro adaptive-interval-support    boolean
      +--ro timer-event-support?         boolean
      +--ro counter-threshold-support?   boolean
      +--ro suppress-redundant?          boolean
```

3. YANG Module

```
<CODE BEGINS> file "ietf-data-export-capabilities.yang"
module ietf-data-export-capabilities {
  yang-version 1.1;
  namespace "urn:ietf:params:xml:ns:yang:ietf-data-export-
capabilities";
  prefix dec;

  import ietf-system-capabilities {
    prefix sysc;
  }
  import ietf-notification-capabilities {
    prefix inc;
  }

  organization
    "IETF NETCONF (Network Configuration) Working Group";
  contact
    "WG Web: <https://tools.ietf.org/wg/netconf/>
    WG List: <mailto:netconf@ietf.org>
    Editor: Qin Wu
           <mailto:bill.wu@huawei.com>;
```



```
description
  "This module defines an extension to System Capability and YANG
Push Notification Capabilities model and provides additional data
export attributes for transport dependent capability negotiation.
```

Copyright (c) 2019 IETF Trust and the persons identified as authors of the code. All rights reserved.

Redistribution and use in source and binary forms, with or without modification, is permitted pursuant to, and subject to the license terms contained in, the Simplified BSD License set forth in [Section 4.c](#) of the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>).

This version of this YANG module is part of RFC XXXX; see the RFC itself for full legal notices.";

```
revision 2020-07-03 {
  description
    "Initial revision.";
  reference
    "RFC XXXX: Telemetry Data Export capability";
}

identity transport-protocol {
  description
    "Base identity for transport protocol type.";
}

identity tcp {
  base transport-protocol;
  description
    "Identity for tcp transport protocol.";
}

identity udp {
  base transport-protocol;
  description
    "Identity for udp transport protocol.";
}

identity grpc {
  base transport-protocol;
  description
    "Identity for grpc transport protocol.";
}
```



```
identity security-protocol {
  description
    "Base identity for security protocol type.";
}

identity tls {
  base security-protocol;
  description
    "Identity for tls security protocol.";
}

identity ssh {
  base security-protocol;
  description
    "Identity for ssh transport protocol.";
}

identity encoding-format {
  description
    "Base identity for encoding format type.";
}

identity xml {
  base encoding-format;
  description
    "Identity for xml encoding format.";
}

identity json {
  base encoding-format;
  description
    "Identity for json encoding format.";
}

identity gpb {
  base encoding-format;
  description
    "Identity for gpb encoding format.";
}

identity cbor {
  base encoding-format;
  description
    "Identity for cbor encoding format.";
}

identity compression-mode {
  description
```



```
    "Base identity for compression mode.";
}

identity gzip {
    base security-protocol;
    description
        "Identity for gzip compression mode.";
}

identity deflate {
    base security-protocol;
    description
        "Identity for deflate compression mode.";
}

identity subscription-mode {
    description
        "Base identity for subscription mode.";
}

identity periodic {
    base subscription-mode;
    description
        "Identity for periodic subscription mode.";
}

identity on-change {
    base subscription-mode;
    description
        "Identity for on change subscription mode.";
}

identity event {
    base subscription-mode;
    description
        "Identity for event based subscription mode.";
}

typedef centiseconds {
    type uint32;
    description
        "A period of time, measured in units of 0.01 seconds.";
}

augment "/sysc:system-capabilities" {
    description
        "Add system level capability.";
    container data-export-capabilities {
```



```
    description
      "Capabilities related to telemetry data export capability
negotiation.";
    leaf transport-protocol {
      type identityref {
        base transport-protocol;
      }
      description
        "Type of transport protocol.";
    }
    leaf encoding-format {
      type identityref {
        base encoding-format;
      }
      description
        "Type of encoding format.";
    }
    leaf security-protocol {
      type identityref {
        base security-protocol;
      }
      description
        "Type of secure transport.";
    }
    leaf compression-mode {
      type identityref {
        base compression-mode;
      }
      description
        "Type of compression mode.";
    }
  }
}
augment "/sysc:system-capabilities/inc:subscription-capabilities" {
  description
    "Add subscription level capability.";
  container data-export-capabilities {
    description
      "Capabilities related to telemetry data export capability
negotiation.";
    leaf message-bundling-support {
      type boolean;
      default "false";
      description
        "Enables message bundling support.";
    }
  }
}
augment "/sysc:system-capabilities/sysc:datastore-capabilities/
sysc:per-node-capabilities" {
  description
```



```
    "Add datastore and node level capability.";
  container data-export-capabilities {
    description
      "Capabilities related to telemetry data export capability
negotiation.";
    leaf adaptive-interval-support {
      type boolean;
      default "false";
      description
        "Set to true if one event stream supports multiple period
intervals and
allows period interval switching. Set to false if the event
stream doesn't
support period interval switching.";
    }
    leaf timer-event-support {
      type boolean;
      default "false";
      description
        "Set to true if timer event is supported, i.e.,, schedule a
specific event
periodically with specified start time, duration, repeat
option, repeat
interval.";
    }
    leaf counter-threshold-support {
      type boolean;
      default "false";
      description
        "Set to true if the subscription mode is event based
subscription mode and counter based trigger is support
(i.e., named counter crosses a specified threshold).
Set to false if event based subscription mode is not
supported.";
    }
    leaf suppress-redundant {
      type boolean;
      default "false";
      description
        "Suppress duplicated data objects to be sent during each
update interval.";
    }
  }
}
}
}
<CODE ENDS>
```

4. IANA Considerations

4.1. Updates to the IETF XML Registry

This document registers a URI in the "IETF XML Registry" [[RFC3688](#)].

Following the format in [[RFC3688](#)], the following registration has been made:

Wu, et al.
9]

Expires May 2, 2021

[Page

URI:
urn:ietf:params:xml:ns:yang:ietf-data-export-capabilities
Registrant Contact:
The IESG.
XML:
N/A; the requested URI is an XML namespace.

4.2. Updates to the YANG Module Names Registry

This document registers one YANG module in the "YANG Module Names" registry [[RFC6020](#)]. Following the format in [[RFC6020](#)], the following registration has been made:

```
name:
  ietf-data-export-capabilities
namespace:
  urn:ietf:params:xml:ns:yang:ietf-data-export-capabilities
prefix:
  dec
reference:
  RFC XXXX (RFC Ed.: replace XXX with actual RFC number and
remove  this note.)
```

5. Security Considerations

The YANG module specified in this document defines a schema for data that is designed to be accessed via network management protocols such as NETCONF [[RFC6241](#)] or RESTCONF [[RFC8040](#)]. The lowest NETCONF layer is the secure transport layer, and the mandatory-to-implement secure transport is Secure Shell (SSH) [[RFC6242](#)]. The lowest RESTCONF layer is HTTPS, and the mandatory-to-implement secure transport is TLS [[RFC8446](#)].

The NETCONF Configuration Access Control Model (NACM) [[RFC8341](#)] provides the means to restrict access for particular NETCONF or RESTCONF users to a preconfigured subset of all available NETCONF or RESTCONF protocol operations and content.

There are a number of data nodes defined in this YANG module that are writable/creatable/deletable (i.e., config true, which is the default). These data nodes may be considered sensitive in some network environments. Write operations (e.g., edit-config) to these data nodes without proper protection can have a negative effect on network operations. These are the subtrees and data nodes and their sensitivity/vulnerability:

o /sysctl:system-capabilities/dec:transport-protocol

Wu, et al.
10]

Expires May 2, 2021

[Page

- o /sysc:system-capabilities/dec:encoding-format
- o /sysc:system-capabilities/dec:secure-transport
- o /sysc:system-capabilities/dec:compression-mode
- o /sysc:system-capabilities/inc:subscription-capabilities/
dec:message-bundling-support
- o /sysc:system-capabilities/inc:subscription-capabilities/
dec:subscription-mode
- o /sysc:system-capabilities/sysc:datastore-capabilities/sysc:per-
node-capabilities/dec:sampling-interval

6. Contributors

The authors would like to thank Ran Tao for his major contributions to the initial modeling and use cases.

7. References

7.1. Normative References

- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), DOI 10.17487/RFC2119, March 1997, <<https://www.rfc-editor.org/info/rfc2119>>.
- [RFC6241] Enns, R., Ed., Bjorklund, M., Ed., Schoenwaelder, J., Ed., and A. Bierman, Ed., "Network Configuration Protocol (NETCONF)", [RFC 6241](#), DOI 10.17487/RFC6241, June 2011, <<https://www.rfc-editor.org/info/rfc6241>>.
- [RFC6242] Wasserman, M., "Using the NETCONF Protocol over Secure Shell (SSH)", [RFC 6242](#), DOI 10.17487/RFC6242, June 2011, <<https://www.rfc-editor.org/info/rfc6242>>.
- [RFC7950] Bjorklund, M., Ed., "The YANG 1.1 Data Modeling Language", [RFC 7950](#), DOI 10.17487/RFC7950, August 2016, <<https://www.rfc-editor.org/info/rfc7950>>.
- [RFC8040] Bierman, A., Bjorklund, M., and K. Watsen, "RESTCONF Protocol", [RFC 8040](#), DOI 10.17487/RFC8040, January 2017, <<https://www.rfc-editor.org/info/rfc8040>>.

- [RFC8126] Cotton, M., Leiba, B., and T. Narten, "Guidelines for Writing an IANA Considerations Section in RFCs", [BCP 26](#), [RFC 8126](#), DOI 10.17487/RFC8126, June 2017, <<https://www.rfc-editor.org/info/rfc8126>>.
- [RFC8174] Leiba, B., "Ambiguity of Uppercase vs Lowercase in [RFC 2119](#) Key Words", [BCP 14](#), [RFC 8174](#), DOI 10.17487/RFC8174, May 2017, <<https://www.rfc-editor.org/info/rfc8174>>.
- [RFC8341] Bierman, A. and M. Bjorklund, "Network Configuration Access Control Model", STD 91, [RFC 8341](#), DOI 10.17487/RFC8341, March 2018, <<https://www.rfc-editor.org/info/rfc8341>>.
- [RFC8342] Bjorklund, M., Schoenwaelder, J., Shafer, P., Watsen, K., and R. Wilton, "Network Management Datastore Architecture (NMDA)", [RFC 8342](#), DOI 10.17487/RFC8342, March 2018, <<https://www.rfc-editor.org/info/rfc8342>>.
- [RFC8407] Bierman, A., "Guidelines for Authors and Reviewers of Documents Containing YANG Data Models", [BCP 216](#), [RFC 8407](#), DOI 10.17487/RFC8407, October 2018, <<https://www.rfc-editor.org/info/rfc8407>>.
- [RFC8446] Rescorla, E., "The Transport Layer Security (TLS) Protocol Version 1.3", [RFC 8446](#), DOI 10.17487/RFC8446, August 2018, <<https://www.rfc-editor.org/info/rfc8446>>.

7.2. Informative References

- [RFC3688] Mealling, M., "The IETF XML Registry", [BCP 81](#), [RFC 3688](#), DOI 10.17487/RFC3688, January 2004, <<https://www.rfc-editor.org/info/rfc3688>>.
- [RFC6020] Bjorklund, M., Ed., "YANG - A Data Modeling Language for the Network Configuration Protocol (NETCONF)", [RFC 6020](#), DOI 10.17487/RFC6020, October 2010, <<https://www.rfc-editor.org/info/rfc6020>>.
- [RFC8340] Bjorklund, M. and L. Berger, Ed., "YANG Tree Diagrams", [BCP 215](#), [RFC 8340](#), DOI 10.17487/RFC8340, March 2018, <<https://www.rfc-editor.org/info/rfc8340>>.

Appendix A. Usage Example of interaction between telemetry data export capabilities and Adaptive Subscription

The following instance-data example describes the notification capabilities of a hypothetical "acme-router". The router implements the running, and operational datastores. Every change can be reported on-change from running, but only config=true nodes and some config=false data from operational. Interface statistics are reported only when both adaptive-interval-support and count-threshold-support are set to true.

<CODE BEGINS> file "acme-router-notification-capabilities.xml"
 ===== NOTE: '\' line wrapping per BCP YYY (RFC YYYY) =====

```
<?xml version="1.0" encoding="UTF-8"?>
<instance-data-set xmlns=\
  "urn:ietf:params:xml:ns:yang:ietf-yang-instance-data">
  <name>acme-router-notification-capabilities</name>
  <content-schema>
    <module>ietf-system-capabilities@2020-03-23</module>
    <module>ietf-notification-capabilities@2020-03-23</module>
    <module>ietf-data-export-capabilities@2020-03-23</module>
  </content-schema>
  <!-- revision date, contact, etc. -->
  <description>Defines the notification capabilities of an acme-router.
    The router only has running, and operational datastores.
    Every change can be reported on-change from running, but
    only config=true nodes and some config=false data from operational.
    Statistics are not reported based on timer based trigger and
counter
    threshold based trigger.
  </description>
  <content-data>
    <system-capabilities \
      xmlns="urn:ietf:params:xml:ns:yang:ietf-system-capabilities" \
      xmlns:inc=\
        "urn:ietf:params:xml:ns:yang:ietf-notification-capabilities" \
      xmlns:ds="urn:ietf:params:xml:ns:yang:ietf-datastores">
    <datastore-capabilities>
      <datastore>ds:operational</datastore>
    <per-node-capabilities>
      <node-selector>\
        /if:interfaces/if:interface/if:statistics\
      </node-selector>
    <inc:subscription-capabilities>
      <inc:minimum-dampening-period>5
        </inc:minimum-dampening-period>
      <inc:on-change-supported>\
        state-changes\

```



```

        </inc:on-change-supported>
    </inc:subscription-capabilities>
</per-node-capabilities>
<per-node-capabilities>
    <node-selector>\
        /if:interfaces/if:interface/if:statistics/if:out-octets\
    </node-selector>
    <dec:data-export-capabilities>
        <dec:adaptive-interval-support>false</dec:adaptive-
interval-support>
        <dec:threshold-event-support>false</dec:threshold-event-
support>
    </dec:data-export-capabilities>
</per-node-capabilities>
</per-node-capabilities>
<per-node-capabilities>
    <node-selector>\
        /if:interfaces/if:interface/if:statistics/if:in-errors\
    </node-selector>
    <dec:data-export-capabilities>
        <dec:adaptive-interval-support>true</dec:adaptive-interval-
support>
        <dec:threshold-event-support>true</dec:threshold-event-
support>
    </dec:data-export-capabilities>
</per-node-capabilities>
</datastore-capabilities>
</system-capabilities>
</content-data>
</instance-data-set>

```

The client configure adaptive subscription parameters on the server. The adaptive subscription configuration parameters require the server to scan all interface of specific type every 5 seconds up to 30 seconds if the value of interface in-errors is greater than 1000; If the interface in-errors value is less than 1000, switch to 60 seconds period value, and then scan all client every 60 seconds up to 360 seconds. 30 seconds and 360 seconds can be seen as time window. The time window length is 6 period values. Irrespective of period value set for adaptive subscription, 6 event records during the time window should be generated for the same subscription and send to the receivers.


```
<rpc message-id="101"
  xmlns="urn:ietf:params:xml:ns:netconf:base:1.0">
  <edit-config>
    <target>
      <running/>
    </target>
    <config xmlns:xc="urn:ietf:params:xml:ns:netconf:base:1.0">
      <top xmlns="http://example.com/schema/1.2/config">
        <yp:datastore
          xmlns:ds="urn:ietf:params:xml:ns:yang:ietf-datastores">
          ds:running
        </yp:datastore>
        <yp:datastore-xpath-filter
          xmlns:ex="https://example.com/sample-data/1.0">
          /if:ietf-interfaces
        </yp:datastore-xpath-filter>
        <as:adaptive-subscriptions
          xmlns:as="urn:ietf:params:xml:ns:yang:ietf-adaptive-
subscription">
          <as:data-path>/if:interfaces/if:interface/if:statistics</
as:data-path>
          <as:target>in-errors</as:target>
          <as:adaptive-period>
            <as:condition-expression>in-errors < 1000</as:condition-
expressioni>
            <as:watermark>1000</as:watermark>
            <as:period>5</as:period>
            <as:count>12</as:count>
          </as:adaptive-period>
          <as:adaptive-period>
            <as:condition-expression>in-errors < 1000</as:condition-
expressioni>
            <as:watermark>1000</as:watermark>
            <as:period>60</as:period>
            <as:count>12</as:count>
          </as:adaptive-period>
        </as:adaptive-subscriptions>
      </top>
    </config>
  </edit-config>
</rpc>
```

Authors' Addresses

Qin Wu
Huawei
101 Software Avenue, Yuhua District
Nanjing, Jiangsu 210012
China

Email: bill.wu@huawei.com

Internet-Draft
2020

Data Export Capability

October

Qiufang Ma
Huawei
101 Software Avenue, Yuhua District
Nanjing, Jiangsu 210012
China

Email: maqiufang1@huawei.com

Liang Geng
China Mobile
32 Xuanwumen West St, Xicheng District
Beijing 10053

Email: gengliang@chinamobile.com

Peng Liu
China Mobile
32 Xuanwumen West St, Xicheng District
Beijing 10053

Email: liupengyjy@chinamobile.com

