

NETCONF Working Group  
Internet-Draft  
Intended status: Standards Track  
Expires: 28 August 2022

Q. Wu  
Q. Ma  
Huawei  
P. Liu  
China Mobile  
W. Wang  
China Telecom  
24 February 2022

Data Export Notification Capability  
draft-tao-netconf-data-export-capabilities-07

## Abstract

This document proposes a YANG module for data export notification capabilities which augments "ietf-system-capabilities" YANG module defined in [RFC9196] and provides additional data export attributes associated with system capabilities for transport specific Notification. This YANG module can be used by the client to learn capability information from the server at runtime or at implementation time, by making use of the YANG instance data file format.

## Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <https://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on 28 August 2022.

## Copyright Notice

Copyright (c) 2022 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<https://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Revised BSD License text as described in Section 4.e of the [Trust Legal Provisions](#) and are provided without warranty as described in the Revised BSD License.

## Table of Contents

<a href="#">1.</a>	Introduction . . . . .	<a href="#">2</a>
<a href="#">1.1.</a>	Terminology . . . . .	<a href="#">3</a>
<a href="#">2.</a>	Data Export Capability . . . . .	<a href="#">3</a>
<a href="#">2.1.</a>	Tree Diagram . . . . .	<a href="#">4</a>
<a href="#">3.</a>	YANG Module . . . . .	<a href="#">4</a>
<a href="#">4.</a>	IANA Considerations . . . . .	<a href="#">8</a>
<a href="#">4.1.</a>	Updates to the IETF XML Registry . . . . .	<a href="#">8</a>
<a href="#">4.2.</a>	Updates to the YANG Module Names Registry . . . . .	<a href="#">8</a>
<a href="#">5.</a>	Security Considerations . . . . .	<a href="#">8</a>
<a href="#">6.</a>	Contributors . . . . .	<a href="#">9</a>
<a href="#">7.</a>	References . . . . .	<a href="#">9</a>
<a href="#">7.1.</a>	Normative References . . . . .	<a href="#">9</a>
<a href="#">7.2.</a>	Informative References . . . . .	<a href="#">10</a>
<a href="#">Appendix A.</a>	Usage Example of interaction with UDP Notif and HTTP Notif for Configured Subscription . . . . .	<a href="#">11</a>
<a href="#">Appendix B.</a>	Changes between Revisions . . . . .	<a href="#">13</a>
	Authors' Addresses . . . . .	<a href="#">14</a>

## [1.](#) Introduction

Notification capabilities model defined in [\[RFC9196\]](#) allows a client to discover a set of capabilities supported by the server (e.g., basic system capabilities and YANG-Push related capabilities) both at implementation time and at runtime. These capabilities allow the client to adjust its behavior to take advantage of the features exposed by the server.

However the client and the server may still support various different transport specific parameters (e.g., transport protocol, encoding format, encryption). As described in [section 3.1 of \[RFC8641\]](#), a simple negotiation (i.e., inserting hints into error responses to a failed RPC request) between subscribers and publishers for

subscription parameters increases the likelihood of success for subsequent RPC requests, but not guaranteed, which may cause unexpected failure or additional message exchange between client and server.

This document defines a corresponding solution that is built on top of [\[RFC9196\]](#). Supplementing that work are YANG data model augmentations for transport specific notification. The module can be used by the client to discover capability information from the server at runtime or at implementation time, by making use of the YANG instance data file format.

## [1.1.](#) Terminology

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "NOT RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [BCP 14](#) [\[RFC2119\]](#) [\[RFC8174\]](#) when, and only when, they appear in all capitals, as shown here.

## [2.](#) Data Export Capability

The YANG module "ietf-notification-capabilities" defined in [\[RFC9196\]](#) specifies the following server capabilities related to YANG Push:

- \* Supported (reporting) periods for "periodic" subscriptions
- \* Maximum number of objects that can be sent in an update
- \* The set of datastores or data nodes for which "periodic" or "on-change" notification is supported
- \* Supported dampening periods for "on-change" subscriptions

These server capabilities are transport independent, session level capabilities. They can be provided either at the implementation time or reported at runtime.

This document augments System Capabilities model and provides additional data export attributes associated with system capabilities:

- \* Specification of transport protocols the client can use to establish a transport connection;
- \* Specification of the encoding selection used (e.g., XML or JSON, Binary) for Data modeled with YANG;
- \* Specification of secure transport mechanisms that are needed by the client to communicate with the server;

- \* Specification of the notification message encapsulation type, either one notification per message or multiple notifications per message [I-D. ietf-netconf-notification-messages].

### [2.1.](#) Tree Diagram

The following tree diagram [[RFC8340](#)] provides an overview of the data model.

```

module: ietf-data-export-capabilities
  augment /sysc:system-capabilities:
    +--ro data-export-capabilities
      +--ro data-export-capability* []
        +--ro transport-protocol?      identityref
        +--ro encoding-format*         identityref
        +--ro security-protocol?       identityref
        +--ro message-bundling-support? empty

```

### [3.](#) YANG Module

```

<CODE BEGINS> file "ietf-data-export-capabilities.yang"
module ietf-data-export-capabilities {
  yang-version 1.1;
  namespace "urn:ietf:params:xml:ns:yang:ietf-data-export-capabilities";
  prefix dec;

  import ietf-system-capabilities {
    prefix sysc;
  }
}

```

```

import ietf-notification-capabilities {
  prefix inc;
}
organization
  "IETF NETCONF (Network Configuration) Working Group";
contact
  "WG Web:    <https://tools.ietf.org/wg/netconf/>
  WG List:    <mailto:netconf@ietf.org>
  Editor:     Qin Wu <mailto:bill.wu@huawei.com>
  Editor:     Qiufang Ma <mailto:maqiufang1@huawei.com>
  Editor:     Peng Liu <mailto:liupengyjy@chinamobile.com>
  Editor:     Wei Wang <mailto:wangw36@chinatelecom.cn>";
description
  "This module defines an extension to System Capability and YANG Push
  Notification Capabilities model and provides additional data export
  attributes for transport specific notification.

  Copyright (c) 2019 IETF Trust and the persons identified as
  authors of the code. All rights reserved.

```

Wu, et al.

Expires 28 August 2022

[Page 4]

---

Internet-Draft

Data Export Capability

February 2022

Redistribution and use in source and binary forms, with or without modification, is permitted pursuant to, and subject to the license terms contained in, the Simplified BSD License set forth in [Section 4.c](#) of the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>).

This version of this YANG module is part of RFC XXXX; see the RFC itself for full legal notices.";

```

revision 2020-07-03 {
  description
    "Initial revision.";
  reference
    "RFC XXXX: Data Export Notification Capability";
}

identity transport-protocol {
  description
    "Base identity for transport protocol type.";
}

```

```

identity tcp {
    base transport-protocol;
    description
        "Identity for tcp as transport protocol.";
}

identity udp-notif {
    base transport-protocol;
    description
        "Identity for udp notif as transport protocol.";
    reference
        "draft-ietf-netconf-udp-notif:UDP-based Transport
        for Configured Subscriptions";
}

identity http-notif {
    base transport-protocol;
    description
        "Identity for http notif as transport protocol.";
    reference
        "draft-ietf-netconf-https-notif: An HTTPS-based
        Transport for Configured Subscriptions";
}

identity grpc {
    base transport-protocol;

```

```

    description
        "Identity for grpc as transport protocol.";
}

identity security-protocol {
    description
        "Base identity for security protocol type.";
}

identity tls {
    base security-protocol;
    description
        "Identity for tls security protocol.";
}

```

```

identity dtls {
    base security-protocol;
    description
        "Identity for dtls security protocol.";
}

identity ssh {
    base security-protocol;
    description
        "Identity for ssh transport protocol.";
}

identity encoding-format {
    description
        "Base identity for encoding format type.";
}

identity xml {
    base encoding-format;
    description
        "Identity for xml encoding format.";
}

identity json {
    base encoding-format;
    description
        "Identity for json encoding format.";
}

identity binary {
    base encoding-format;
    description
        "Identity for binary encoding format.";
}

```

```

}

identity cbor {
    base binary;
    description
        "Identity for cbor encoding format.";
}

```

```

augment "/sysc:system-capabilities" {
  description
    "Add system level capability.";
  container data-export-capabilities {
    description
      "Capabilities related to data export notification capabilities negot
    list data-export-capability {
      description
        "Capability list related to data export notification capabilities
      leaf transport-protocol {
        type identityref {
          base transport-protocol;
        }
        description
          "Type of transport protocol.";
      }
      leaf-list encoding-format {
        type identityref {
          base encoding-format;
        }
        description
          "Type of encoding format.";
      }
      leaf security-protocol {
        type identityref {
          base security-protocol;
        }
        description
          "Type of secure transport.";
      }
      leaf message-bundling-support {
        type empty;
        description
          "Enables message bundling support.";
      }
    }
  }
}
}
}
}
<CODE ENDS>

```



#### [4.1.](#) Updates to the IETF XML Registry

This document registers a URI in the "IETF XML Registry" [[RFC3688](#)]. Following the format in [[RFC3688](#)], the following registration has been made:

URI:  
urn:ietf:params:xml:ns:yang:ietf-data-export-capabilities  
Registrant Contact:  
The IESG.  
XML:  
N/A; the requested URI is an XML namespace.

#### [4.2.](#) Updates to the YANG Module Names Registry

This document registers one YANG module in the "YANG Module Names" registry [[RFC6020](#)]. Following the format in [[RFC6020](#)], the following registration has been made:

name:  
ietf-data-export-capabilities  
namespace:  
urn:ietf:params:xml:ns:yang:ietf-data-export-capabilities  
prefix:  
dec  
reference:  
RFC XXXX (RFC Ed.: replace XXX with actual RFC number and remove this note.)

### [5.](#) Security Considerations

The YANG module specified in this document defines a schema for data that is designed to be accessed via network management protocols such as NETCONF [[RFC6241](#)] or RESTCONF [[RFC8040](#)]. The lowest NETCONF layer is the secure transport layer, and the mandatory-to-implement secure transport is Secure Shell (SSH) [[RFC6242](#)]. The lowest RESTCONF layer is HTTPS, and the mandatory-to-implement secure transport is TLS [[RFC8446](#)].

The NETCONF Configuration Access Control Model (NACM) [[RFC8341](#)] provides the means to restrict access for particular NETCONF or RESTCONF users to a preconfigured subset of all available NETCONF or RESTCONF protocol operations and content.

All protocol-accessible data nodes are read-only and cannot be modified. The data in these modules is not security sensitive. Access control may be configured, to avoid exposing the read-only data.

When this data is in file format, data should be protected against modification or unauthorized access using normal file handling mechanisms.

## 6. Contributors

Ran Tao  
Huawei  
101 Software Avenue, Yuhua District  
Nanjing, Jiangsu 210012  
China  
Email: taoran20@huawei.com

Liang Geng  
China Mobile  
32 Xuanwumen West St, Xicheng District  
Beijing 10053  
  
Email: gengliang@chinamobile.com

Thomas Graf  
Swisscom  
Binzring 17  
Zuerich 8045  
Switzerland

Email: thomas.graf@swisscom.com

## 7. References

### 7.1. Normative References

- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), DOI 10.17487/RFC2119, March 1997, <<https://www.rfc-editor.org/info/rfc2119>>.
- [RFC6241] Enns, R., Ed., Bjorklund, M., Ed., Schoenwaelder, J., Ed., and A. Bierman, Ed., "Network Configuration Protocol (NETCONF)", [RFC 6241](#), DOI 10.17487/RFC6241, June 2011, <<https://www.rfc-editor.org/info/rfc6241>>.

Internet-Draft

Data Export Capability

February 2022

- [RFC6242] Wasserman, M., "Using the NETCONF Protocol over Secure Shell (SSH)", [RFC 6242](#), DOI 10.17487/RFC6242, June 2011, <<https://www.rfc-editor.org/info/rfc6242>>.
- [RFC7950] Bjorklund, M., Ed., "The YANG 1.1 Data Modeling Language", [RFC 7950](#), DOI 10.17487/RFC7950, August 2016, <<https://www.rfc-editor.org/info/rfc7950>>.
- [RFC8040] Bierman, A., Bjorklund, M., and K. Watsen, "RESTCONF Protocol", [RFC 8040](#), DOI 10.17487/RFC8040, January 2017, <<https://www.rfc-editor.org/info/rfc8040>>.
- [RFC8126] Cotton, M., Leiba, B., and T. Narten, "Guidelines for Writing an IANA Considerations Section in RFCs", [BCP 26](#), [RFC 8126](#), DOI 10.17487/RFC8126, June 2017, <<https://www.rfc-editor.org/info/rfc8126>>.
- [RFC8174] Leiba, B., "Ambiguity of Uppercase vs Lowercase in [RFC 2119](#) Key Words", [BCP 14](#), [RFC 8174](#), DOI 10.17487/RFC8174, May 2017, <<https://www.rfc-editor.org/info/rfc8174>>.
- [RFC8341] Bierman, A. and M. Bjorklund, "Network Configuration Access Control Model", STD 91, [RFC 8341](#), DOI 10.17487/RFC8341, March 2018, <<https://www.rfc-editor.org/info/rfc8341>>.
- [RFC8342] Bjorklund, M., Schoenwaelder, J., Shafer, P., Watsen, K., and R. Wilton, "Network Management Datastore Architecture (NMDA)", [RFC 8342](#), DOI 10.17487/RFC8342, March 2018, <<https://www.rfc-editor.org/info/rfc8342>>.
- [RFC8407] Bierman, A., "Guidelines for Authors and Reviewers of Documents Containing YANG Data Models", [BCP 216](#), [RFC 8407](#), DOI 10.17487/RFC8407, October 2018, <<https://www.rfc-editor.org/info/rfc8407>>.
- [RFC8446] Rescorla, E., "The Transport Layer Security (TLS) Protocol Version 1.3", [RFC 8446](#), DOI 10.17487/RFC8446, August 2018, <<https://www.rfc-editor.org/info/rfc8446>>.

- [RFC9196] Lengyel, B., Clemm, A., and B. Claise, "YANG Modules Describing Capabilities for Systems and Datastore Update Notifications", [RFC 9196](#), DOI 10.17487/RFC9196, February 2022, <<https://www.rfc-editor.org/info/rfc9196>>.

## [7.2.](#) Informative References

Wu, et al.

Expires 28 August 2022

[Page 10]

---

Internet-Draft

Data Export Capability

February 2022

[I-D.ietf-netconf-https-notif]

Jethanandani, M. and K. Watsen, "An HTTPS-based Transport for YANG Notifications", Work in Progress, Internet-Draft, [draft-ietf-netconf-https-notif-09](#), 24 October 2021, <<https://www.ietf.org/archive/id/draft-ietf-netconf-https-notif-09.txt>>.

[I-D.ietf-netconf-notification-messages]

Voit, E., Jenkins, T., Birkholz, H., Bierman, A., and A. Clemm, "Notification Message Headers and Bundles", Work in Progress, Internet-Draft, [draft-ietf-netconf-notification-messages-08](#), 17 November 2019, <<https://www.ietf.org/archive/id/draft-ietf-netconf-notification-messages-08.txt>>.

[I-D.ietf-netconf-udp-notif]

Zheng, G., Zhou, T., Graf, T., Francois, P., Feng, A. H., and P. Lucente, "UDP-based Transport for Configured Subscriptions", Work in Progress, Internet-Draft, [draft-ietf-netconf-udp-notif-04](#), 21 October 2021, <<https://www.ietf.org/archive/id/draft-ietf-netconf-udp-notif-04.txt>>.

- [RFC3688] Mealling, M., "The IETF XML Registry", [BCP 81](#), [RFC 3688](#), DOI 10.17487/RFC3688, January 2004, <<https://www.rfc-editor.org/info/rfc3688>>.

- [RFC6020] Bjorklund, M., Ed., "YANG - A Data Modeling Language for the Network Configuration Protocol (NETCONF)", [RFC 6020](#), DOI 10.17487/RFC6020, October 2010, <<https://www.rfc-editor.org/info/rfc6020>>.

[RFC8340] Bjorklund, M. and L. Berger, Ed., "YANG Tree Diagrams", [BCP 215](#), [RFC 8340](#), DOI 10.17487/RFC8340, March 2018, <<https://www.rfc-editor.org/info/rfc8340>>.

## [Appendix A](#). Usage Example of interaction with UDP Notif and HTTP Notif for Configured Subscription

The following instance-data example describes the Data Export Notification capabilities of a hypothetical "acme-router".

Wu, et al.

Expires 28 August 2022

[Page 11]

---

Internet-Draft

Data Export Capability

February 2022

```
<?xml version="1.0" encoding="UTF-8"?>
<instance-data-set xmlns=
"urn:ietf:params:xml:ns:yang:ietf-yang-instance-data">
  <name>acme-router-notification-capabilities</name>
  <content-schema>
    <module>ietf-system-capabilities@2020-03-23</module>
    <module>ietf-notification-capabilities@2020-03-23</module>
    <module>ietf-data-export-capabilities@2020-03-23</module>
  </content-schema>
  <!-- revision date, contact, etc. -->
  <description>Server Capability Discovery</description>
  <content-data>
    <system-capabilities
      xmlns="urn:ietf:params:xml:ns:yang:ietf-system-capabilities"
      xmlns:inc="urn:ietf:params:xml:ns:yang:ietf-notification-capabilities"
      xmlns:ds="urn:ietf:params:xml:ns:yang:ietf-datastores">
      <data-export-capabilities>
        <data-export-capability>
          <transport-protocol>http-notif</transport-protocol>
          <encoding-format>json</encoding-format>
          <encoding-format>xml</encoding-format>
        </data-export-capability>
        <data-export-capability>
          <transport-protocol>udp-notif</transport-protocol>
          <encoding-format>binary</encoding-format>
```

```

        </data-export-capability>
    </data-export-capabilities>
</system-capabilities>
</content-data>
</instance-data-set>

```

In addition, the client could also query data export capability from the server. For example, the client sends <get> request message to the the server to query data export capability from the server.

```

<rpc message-id="101" xmlns="urn:ietf:params:xml:ns:netconf:base:1.0">
  <get>
    <filter type="subtree">
      <system-capabilities xmlns="urn:ietf:params:xml:ns:yang:ietf-system-capabi
        <data-export-capabilities/>
      </system-capabilities>
    </filter>
  </get>
</rpc>

```

The server returns server data export capability using <rpc-reply> as follows:

```

<rpc-reply message-id="101" xmlns="urn:ietf:params:xml:ns:netconf:base:1.0">
  <data>
    <system-capabilities
      xmlns="urn:ietf:params:xml:ns:yang:ietf-system-capabilities"
      xmlns:dec="urn:ietf:params:xml:ns:yang:ietf-data-export-capabilities">
      <data-export-capabilities>
        <data-export-capability>
          <transport-protocol>http-notif</transport-protocol>
          <encoding-format>json</encoding-format>
        </data-export-capability>
        <data-export-capability>
          <transport-protocol>udp-notif</transport-protocol>
          <encoding-format>binary</encoding-format>
        </data-export-capability>
      </data-export-capabilities>
    </system-capabilities>
  </data>
</rpc-reply>

```

## [Appendix B](#). Changes between Revisions

### v06-v07

- \* Delete the per-node related capability parameters from the Appendix.

### v05-v06

- \* Revise abstract and introduction sessions so that the scope of this draft is not limited to telemetry but other notification.
- \* Revise the description of module ietf-system-capabilities to align with the latest version of [draft-ietf-netconf-notification-capabilities](#).
- \* Remove compression-mode, timer-event-support and suppress-redundant parameters in the model.
- \* Move per-node related capability parameters to appendix section.
- \* Add a container to wrap data export capabilities to cleanly separate different groups of capabilities.

### v04 - v05

- \* Change per-node-capabilities related parameters into empty type.

- \* Revise abstract and introduction section to only focus on capability fetching mechanism from the client to the server.
- \* Update Usage Example of interaction with HTTP-Notif and UDP-Notif for Configured Subscription.

### v03 - v04

- \* Add interface namespace in the Adaptive Subscription usage example.

- \* subtrees and data nodes changes in the security section.
- \* Two compression mode related identities change.
- \* Move message-bundling-support parameter to system capabilities level.
- \* Add an example to discuss report receiver capability from the client per yang instance file format.
- \* Change encoding format from leaf to leaf-list and support multiple encoding formats for the same transport specific notif.

v02 - v03

- \* Change 'data-export-capabilities' into list type to support multiple transport protocol, encoding on the server.
- \* Add Usage Example of interaction with UDP based Transport for Configured Subscription.
- \* Add Thomas Graf as a contributor;
- \* Update motivation in the introduction to clarify why this work is needed.
- \* Support udp notif and http notif as two optional transport in the YANG data model.

#### Authors' Addresses

Qin Wu  
 Huawei  
 101 Software Avenue, Yuhua District  
 Nanjing  
 Jiangsu, 210012  
 China

Wu, et al.

Expires 28 August 2022

[Page 14]

Internet-Draft

Data Export Capability

February 2022

Email: [bill.wu@huawei.com](mailto:bill.wu@huawei.com)

Qiufang Ma



Huawei  
101 Software Avenue, Yuhua District  
Nanjing  
Jiangsu, 210012  
China  
Email: maqiufang1@huawei.com

Peng Liu  
China Mobile  
Beiqijia Town, Changping District  
Beijing  
Email: liupengyjy@chinamobile.com

Wei Wang  
China Telecom  
32 Xuanwumen West St, Xicheng District  
Beijing  
Email: wangw36@chinatelecom.cn