

Network Working Group  
Internet-Draft  
Obsoletes: [rfc5320](#), [rfc5558](#), [rfc5720](#),  
[rfc6179](#), [rfc6706](#) (if  
approved)  
Intended status: Standards Track  
Expires: February 6, 2016

F. Templin, Ed.  
Boeing Research & Technology  
August 5, 2015

**Asymmetric Extended Route Optimization (AERO)**  
**draft-templin-aerolink-61.txt**

**Abstract**

This document specifies the operation of IP over tunnel virtual links using Asymmetric Extended Route Optimization (AERO). Nodes attached to AERO links can exchange packets via trusted intermediate routers that provide forwarding services to reach off-link destinations and redirection services for route optimization. AERO provides an IPv6 link-local address format known as the AERO address that supports operation of the IPv6 Neighbor Discovery (ND) protocol and links IPv6 ND to IP forwarding. Admission control, provisioning and mobility are supported by the Dynamic Host Configuration Protocol for IPv6 (DHCPv6), and route optimization is naturally supported through dynamic neighbor cache updates. Although DHCPv6 and IPv6 ND messaging are used in the control plane, both IPv4 and IPv6 are supported in the data plane. AERO is a widely-applicable tunneling solution using standard control messaging exchanges as described in this document.

**Status of This Memo**

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <http://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on February 6, 2016.

## Copyright Notice

Copyright (c) 2015 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

## Table of Contents

<a href="#">1.</a>	Introduction . . . . .	<a href="#">3</a>
<a href="#">2.</a>	Terminology . . . . .	<a href="#">4</a>
<a href="#">3.</a>	Asymmetric Extended Route Optimization (AERO) . . . . .	<a href="#">6</a>
<a href="#">3.1.</a>	AERO Link Reference Model . . . . .	<a href="#">6</a>
<a href="#">3.2.</a>	AERO Link Node Types . . . . .	<a href="#">8</a>
<a href="#">3.3.</a>	AERO Addresses . . . . .	<a href="#">9</a>
<a href="#">3.4.</a>	AERO Interface Characteristics . . . . .	<a href="#">10</a>
<a href="#">3.5.</a>	AERO Link Registration . . . . .	<a href="#">11</a>
<a href="#">3.6.</a>	AERO Interface Initialization . . . . .	<a href="#">12</a>
<a href="#">3.6.1.</a>	AERO Relay Behavior . . . . .	<a href="#">12</a>
<a href="#">3.6.2.</a>	AERO Server Behavior . . . . .	<a href="#">12</a>
<a href="#">3.6.3.</a>	AERO Client Behavior . . . . .	<a href="#">13</a>
<a href="#">3.6.4.</a>	AERO Forwarding Agent Behavior . . . . .	<a href="#">13</a>
<a href="#">3.7.</a>	AERO Link Routing System . . . . .	<a href="#">13</a>
<a href="#">3.8.</a>	AERO Interface Neighbor Cache Maintenance . . . . .	<a href="#">15</a>
<a href="#">3.9.</a>	AERO Interface Sending Algorithm . . . . .	<a href="#">16</a>
<a href="#">3.10.</a>	AERO Interface Encapsulation and Re-encapsulation . . . . .	<a href="#">18</a>
<a href="#">3.11.</a>	AERO Interface Decapsulation . . . . .	<a href="#">19</a>
<a href="#">3.12.</a>	AERO Interface Data Origin Authentication . . . . .	<a href="#">19</a>
<a href="#">3.13.</a>	AERO Interface MTU and Fragmentation . . . . .	<a href="#">20</a>
<a href="#">3.13.1.</a>	All Elements in Same Administrative Domain . . . . .	<a href="#">20</a>
<a href="#">3.13.2.</a>	Some Elements in Different Administrative Domain . . . . .	<a href="#">21</a>
<a href="#">3.13.3.</a>	Accommodating Large Control Messages . . . . .	<a href="#">23</a>
<a href="#">3.13.4.</a>	Integrity . . . . .	<a href="#">24</a>
<a href="#">3.14.</a>	AERO Interface Error Handling . . . . .	<a href="#">25</a>
<a href="#">3.15.</a>	AERO Router Discovery, Prefix Delegation and Address Configuration . . . . .	<a href="#">29</a>
<a href="#">3.15.1.</a>	AERO DHCPv6 Service Model . . . . .	<a href="#">29</a>
<a href="#">3.15.2.</a>	AERO Client Behavior . . . . .	<a href="#">30</a>
<a href="#">3.15.3.</a>	AERO Server Behavior . . . . .	<a href="#">33</a>
<a href="#">3.15.4.</a>	Deleting Link Registrations . . . . .	<a href="#">36</a>

Templin

Expires February 6, 2016

[Page 2]

<a href="#">3.16.</a>	<a href="#">AERO Forwarding Agent Behavior . . . . .</a>	<a href="#">37</a>
<a href="#">3.17.</a>	<a href="#">AERO Intradomain Route Optimization . . . . .</a>	<a href="#">37</a>
<a href="#">3.17.1.</a>	<a href="#">Reference Operational Scenario . . . . .</a>	<a href="#">38</a>
<a href="#">3.17.2.</a>	<a href="#">Concept of Operations . . . . .</a>	<a href="#">39</a>
<a href="#">3.17.3.</a>	<a href="#">Message Format . . . . .</a>	<a href="#">40</a>
<a href="#">3.17.4.</a>	<a href="#">Sending Predirects . . . . .</a>	<a href="#">40</a>
<a href="#">3.17.5.</a>	<a href="#">Re-encapsulating and Relaying Predirects . . . . .</a>	<a href="#">42</a>
<a href="#">3.17.6.</a>	<a href="#">Processing Predirects and Sending Redirects . . . . .</a>	<a href="#">42</a>
<a href="#">3.17.7.</a>	<a href="#">Re-encapsulating and Relaying Redirects . . . . .</a>	<a href="#">44</a>
<a href="#">3.17.8.</a>	<a href="#">Processing Redirects . . . . .</a>	<a href="#">45</a>
<a href="#">3.17.9.</a>	<a href="#">Server-Oriented Redirection . . . . .</a>	<a href="#">45</a>
<a href="#">3.18.</a>	<a href="#">Neighbor Unreachability Detection (NUD) . . . . .</a>	<a href="#">46</a>
<a href="#">3.19.</a>	<a href="#">Mobility Management . . . . .</a>	<a href="#">47</a>
<a href="#">3.19.1.</a>	<a href="#">Announcing Link-Layer Address Changes . . . . .</a>	<a href="#">47</a>
<a href="#">3.19.2.</a>	<a href="#">Bringing New Links Into Service . . . . .</a>	<a href="#">48</a>
<a href="#">3.19.3.</a>	<a href="#">Removing Existing Links from Service . . . . .</a>	<a href="#">49</a>
<a href="#">3.19.4.</a>	<a href="#">Moving to a New Server . . . . .</a>	<a href="#">49</a>
<a href="#">3.20.</a>	<a href="#">Proxy AERO . . . . .</a>	<a href="#">50</a>
<a href="#">3.21.</a>	<a href="#">Extending AERO Links Through Security Gateways . . . . .</a>	<a href="#">52</a>
<a href="#">3.22.</a>	<a href="#">Extending IPv6 AERO Links to the Internet . . . . .</a>	<a href="#">54</a>
<a href="#">3.23.</a>	<a href="#">Encapsulation Protocol Version Considerations . . . . .</a>	<a href="#">57</a>
<a href="#">3.24.</a>	<a href="#">Multicast Considerations . . . . .</a>	<a href="#">58</a>
<a href="#">3.25.</a>	<a href="#">Operation on AERO Links Without DHCPv6 Services . . . . .</a>	<a href="#">58</a>
<a href="#">3.26.</a>	<a href="#">Operation on Server-less AERO Links . . . . .</a>	<a href="#">58</a>
<a href="#">3.27.</a>	<a href="#">Manually-Configured AERO Tunnels . . . . .</a>	<a href="#">58</a>
<a href="#">3.28.</a>	<a href="#">Intradomain Routing . . . . .</a>	<a href="#">59</a>
<a href="#">4.</a>	<a href="#">Implementation Status . . . . .</a>	<a href="#">59</a>
<a href="#">5.</a>	<a href="#">Next Steps . . . . .</a>	<a href="#">59</a>
<a href="#">6.</a>	<a href="#">IANA Considerations . . . . .</a>	<a href="#">59</a>
<a href="#">7.</a>	<a href="#">Security Considerations . . . . .</a>	<a href="#">59</a>
<a href="#">8.</a>	<a href="#">Acknowledgements . . . . .</a>	<a href="#">60</a>
<a href="#">9.</a>	<a href="#">References . . . . .</a>	<a href="#">61</a>
<a href="#">9.1.</a>	<a href="#">Normative References . . . . .</a>	<a href="#">61</a>
<a href="#">9.2.</a>	<a href="#">Informative References . . . . .</a>	<a href="#">63</a>
	<a href="#">Author's Address . . . . .</a>	<a href="#">69</a>

## [1. Introduction](#)

This document specifies the operation of IP over tunnel virtual links using Asymmetric Extended Route Optimization (AERO). The AERO link can be used for tunneling to neighboring nodes over either IPv6 or IPv4 networks, i.e., AERO views the IPv6 and IPv4 networks as equivalent links for tunneling. Nodes attached to AERO links can exchange packets via trusted intermediate routers that provide forwarding services to reach off-link destinations and redirection services for route optimization that addresses the requirements outlined in [[RFC5522](#)].



AERO provides an IPv6 link-local address format known as the AERO address that supports operation of the IPv6 Neighbor Discovery (ND) [[RFC4861](#)] protocol and links IPv6 ND to IP forwarding. Admission control, provisioning and mobility are supported by the Dynamic Host Configuration Protocol for IPv6 (DHCPv6) [[RFC3315](#)], and route optimization is naturally supported through dynamic neighbor cache updates. Although DHCPv6 and IPv6 ND messaging are used in the control plane, both IPv4 and IPv6 can be used in the data plane. AERO is a widely-applicable tunneling solution using standard control messaging exchanges as described in this document. The remainder of this document presents the AERO specification.

## 2. Terminology

The terminology in the normative references applies; the following terms are defined within the scope of this document:

### AERO link

a Non-Broadcast, Multiple Access (NBMA) tunnel virtual overlay configured over a node's attached IPv6 and/or IPv4 networks. All nodes on the AERO link appear as single-hop neighbors from the perspective of the virtual overlay.

### AERO interface

a node's attachment to an AERO link. Nodes typically have a single AERO interface; support for multiple AERO interfaces is also possible but out of scope for this document.

### AERO address

an IPv6 link-local address constructed as specified in [Section 3.3](#) and assigned to a Client's AERO interface.

### AERO node

a node that is connected to an AERO link and that participates in IPv6 ND and DHCPv6 messaging over the link.

### AERO Client ("Client")

a node that issues DHCPv6 messages using the special IPv6 link-local address 'fe80::ffff:ffff:ffff:ffff' to receive IP Prefix Delegations (PD) from one or more AERO Servers. Following PD, the Client assigns an AERO address to the AERO interface which it uses in IPv6 ND messaging to coordinate with other AERO nodes.

### AERO Server ("Server")

a node that configures an AERO interface to provide default forwarding and DHCPv6 services for AERO Clients. The Server assigns an administratively provisioned IPv6 link-local unicast



address to support the operation of DHCPv6 and the IPv6 ND protocol. An AERO Server can also act as an AERO Relay.

AERO Relay ("Relay")

a node that configures an AERO interface to relay IP packets between nodes on the same AERO link and/or forward IP packets between the AERO link and the native Internetwork. The Relay assigns an administratively provisioned IPv6 link-local unicast address to the AERO interface the same as for a Server. An AERO Relay can also act as an AERO Server.

AERO Forwarding Agent ("Forwarding Agent")

a node that performs data plane forwarding services as a companion to an AERO Server.

ingress tunnel endpoint (ITE)

an AERO interface endpoint that injects tunneled packets into an AERO link.

egress tunnel endpoint (ETE)

an AERO interface endpoint that receives tunneled packets from an AERO link.

underlying network

a connected IPv6 or IPv4 network routing region over which the tunnel virtual overlay is configured. A typical example is an enterprise network.

underlying interface

an AERO node's interface point of attachment to an underlying network.

link-layer address

an IP address assigned to an AERO node's underlying interface. When UDP encapsulation is used, the UDP port number is also considered as part of the link-layer address. Link-layer addresses are used as the encapsulation header source and destination addresses.

network layer address

the source or destination address of the encapsulated IP packet.

end user network (EUN)

an internal virtual or external edge IP network that an AERO Client connects to the rest of the network via the AERO interface.

AERO Service Prefix (ASP)





an IP prefix associated with the AERO link and from which AERO Client Prefixes (ACPs) are derived (for example, the IPv6 ACP 2001:db8:1:2::/64 is derived from the IPv6 ASP 2001:db8::/32).

AERO Client Prefix (ACP)

a more-specific IP prefix taken from an ASP and delegated to a Client.

Throughout the document, the simple terms "Client", "Server" and "Relay" refer to "AERO Client", "AERO Server" and "AERO Relay", respectively. Capitalization is used to distinguish these terms from DHCPv6 client/server/relay [[RFC3315](#)].

The terminology of [[RFC4861](#)] (including the names of node variables and protocol constants) applies to this document. Also throughout the document, the term "IP" is used to generically refer to either Internet Protocol version (i.e., IPv4 or IPv6).

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [[RFC2119](#)]. Lower case uses of these words are not to be interpreted as carrying [RFC2119](#) significance.

### **[3.](#) Asymmetric Extended Route Optimization (AERO)**

The following sections specify the operation of IP over Asymmetric Extended Route Optimization (AERO) links:

#### **[3.1.](#) AERO Link Reference Model**






Figure 1: AERO Link Reference Model

Figure 1 presents the AERO link reference model. In this model:

- o Relay R1 acts as a default router for its associated Servers S1 and S2, and connects the AERO link to the rest of the IP Internetwork
- o Servers S1 and S2 associate with Relay R1 and also act as default routers for their associated Clients C1 and C2.
- o Clients C1 and C2 associate with Servers S1 and S2, respectively and also act as default routers for their associated EUNs
- o Hosts H1 and H2 attach to the EUNs served by Clients C1 and C2, respectively



Each node maintains a neighbor cache and IP forwarding table. (For example, AERO Relay R1 in the diagram has neighbor cache entries for Servers S1 and S2 and IP forwarding table entries for the ACPs delegated to Clients C1 and C2.) In common operational practice, there may be many additional Relays, Servers and Clients. (Although not shown in the figure, AERO Forwarding Agents may also be provided for data plane forwarding offload services.)

### **3.2. AERO Link Node Types**

AERO Relays provide default forwarding services to AERO Servers. Relays forward packets between Servers connected to the same AERO link and also forward packets between the AERO link and the native IP Internetwork. Relays present the AERO link to the native Internetwork as a set of one or more AERO Service Prefixes (ASPs) and serve as a gateway between the AERO link and the Internetwork. AERO Relays maintain an AERO interface neighbor cache entry for each AERO Server, and maintain an IP forwarding table entry for each AERO Client Prefix (ACP). AERO Relays can also be configured to act as AERO Servers.

AERO Servers provide default forwarding services to AERO Clients. Each Server also peers with each Relay in a dynamic routing protocol instance to advertise its list of associated ACPs. Servers configure a DHCPv6 server function to facilitate Prefix Delegation (PD) exchanges with Clients. Each delegated prefix becomes an ACP taken from an ASP. Servers forward packets between AERO interface neighbors only, i.e., and not between the AERO link and the native IP Internetwork. AERO Servers maintain an AERO interface neighbor cache entry for each AERO Relay. They also maintain both a neighbor cache entry and an IP forwarding table entry for each of their associated Clients. AERO Servers can also be configured to act as AERO Relays.

AERO Clients act as requesting routers to receive ACPs through DHCPv6 PD exchanges with AERO Servers over the AERO link and sub-delegate portions of their ACPs to EUN interfaces. (Each Client MAY associate with a single Server or with multiple Servers, e.g., for fault tolerance, load balancing, etc.) Each IPv6 Client receives at least a /64 IPv6 ACP, and may receive even shorter prefixes. Similarly, each IPv4 Client receives at least a /32 IPv4 ACP (i.e., a singleton IPv4 address), and may receive even shorter prefixes. AERO Clients maintain an AERO interface neighbor cache entry for each of their associated Servers as well as for each of their correspondent Clients.

AERO Clients typically configure a TUN/TAP interface [[TUNTAP](#)] as a point-to-point linkage between the IP layer and the AERO interface. The IP layer therefore sees only the TUN/TAP interface, while the



AERO interface provides an intermediate conduit between the TUN/TAP interface and the underlying interfaces. AERO Clients that act as hosts assign one or more IP addresses from their ACPs to the TUN/TAP interface, i.e., and not to the AERO interface.

AERO Forwarding Agents provide data plane forwarding services as companions to AERO Servers. Note that while Servers are required to perform both control and data plane operations on their own behalf, they may optionally enlist the services of special-purpose Forwarding Agents to offload data plane traffic.

### **3.3. AERO Addresses**

An AERO address is an IPv6 link-local address with an embedded ACP and assigned to a Client's AERO interface. The AERO address is formed as follows:

```
fe80::[ACP]
```

For IPv6, the AERO address begins with the prefix `fe80::/64` and includes in its interface identifier the base prefix taken from the Client's IPv6 ACP. The base prefix is determined by masking the ACP with the prefix length. For example, if the AERO Client receives the IPv6 ACP:

```
2001:db8:1000:2000::/56
```

it constructs its AERO address as:

```
fe80::2001:db8:1000:2000
```

For IPv4, the AERO address is formed from the lower 64 bits of an IPv4-mapped IPv6 address [[RFC4291](#)] that includes the base prefix taken from the Client's IPv4 ACP. For example, if the AERO Client receives the IPv4 ACP:

```
192.0.2.32/28
```

it constructs its AERO address as:

```
fe80::FFFF:192.0.2.32
```

The AERO address remains stable as the Client moves between topological locations, i.e., even if its link-layer addresses change.

NOTE: In some cases, prospective neighbors may not have advanced knowledge of the Client's ACP length and may therefore send initial IPv6 ND messages with an AERO destination address that matches the





ACP but does not correspond to the base prefix. In that case, the Client **MUST** accept the address as equivalent to the base address, but then use the base address as the source address of any IPv6 ND message replies. For example, if the Client receives the IPv6 ACP 2001:db8:1000:2000::/56 then subsequently receives an IPv6 ND message with destination address fe80::2001:db8:1000:2001, it accepts the message but uses fe80::2001:db8:1000:2000 as the source address of any IPv6 ND replies.

### 3.4. AERO Interface Characteristics

AERO interfaces use encapsulation (see [Section 3.10](#)) to exchange packets with neighbors attached to the AERO link. AERO interfaces maintain a neighbor cache, and AERO Clients and Servers use unicast IPv6 ND messaging. AERO interfaces use unicast Neighbor Solicitation (NS), Neighbor Advertisement (NA), Router Solicitation (RS) and Router Advertisement (RA) messages the same as for any IPv6 link. AERO interfaces use two redirection message types -- the first known as a Redirect message and the second being the standard Redirect message (see [Section 3.17](#)). AERO links further use link-local-only addressing; hence, AERO nodes ignore any Prefix Information Options (PIOs) they may receive in RA messages over an AERO interface.

AERO interface ND messages include one or more Source/Target Link-Layer Address Options (S/TLLAOs) formatted as shown in Figure 2:




Figure 2: AERO Source/Target Link-Layer Address Option (S/TLLA0) Format



In this format, Link ID is an integer value between 0 and 255 corresponding to an underlying interface of the target node, NDSCPs encodes an integer value between 1 and 64 indicating the number of Differentiated Services Code Point (DSCP) octets that follow. Each DSCP octet is a 6-bit integer DSCP value followed by a 2-bit Preference ("Prf") value. Each DSCP value encodes an integer between 0 and 63 associated with this Link ID, where the value 0 means "default" and other values are interpreted as specified in [\[RFC2474\]](#). The 'Prf' qualifier for each DSCP value is set to the value 0 ("deprecated"), 1 ("low"), 2 ("medium"), or 3 ("high") to indicate a preference level for packet forwarding purposes. UDP Port Number and IP Address are set to the addresses used by the target node when it sends encapsulated packets over the underlying interface. When the encapsulation IP address family is IPv4, IP Address is formed as an IPv4-mapped IPv6 address [\[RFC4291\]](#).

AERO interfaces may be configured over multiple underlying interfaces. For example, common mobile handheld devices have both wireless local area network ("WLAN") and cellular wireless links. These links are typically used "one at a time" with low-cost WLAN preferred and highly-available cellular wireless as a standby. In a more complex example, aircraft frequently have many wireless data link types (e.g. satellite-based, terrestrial, air-to-air directional, etc.) with diverse performance and cost properties.

If a Client's multiple underlying interfaces are used "one at a time" (i.e., all other interfaces are in standby mode while one interface is active), then Redirect, Predirect and unsolicited NA messages include only a single TLLAO with Link ID set to a constant value.

If the Client has multiple active underlying interfaces, then from the perspective of IPv6 ND it would appear to have a single link-local address with multiple link-layer addresses. In that case, Redirect, Predirect and unsolicited NA messages MAY include multiple TLLAOs -- each with a different Link ID that corresponds to a specific underlying interface of the Client.

### **[3.5.](#) AERO Link Registration**

When an administrative authority first deploys a set of AERO Relays and Servers that comprise an AERO link, they also assign a unique domain name for the link, e.g., "linkupnetworks.example.com". Next, if administrative policy permits Clients within the domain to serve as correspondent nodes for Internet mobile nodes, the administrative authority adds a Fully Qualified Domain Name (FQDN) for each of the AERO link's ASPs to the Domain Name System (DNS) [\[RFC1035\]](#). The FQDN is based on the suffix "aero.linkupnetworks.net" with a prefix formed from the wildcard-terminated reverse mapping of the ASP



[[RFC3596](#)][RFC4592], and resolves to a DNS PTR resource record. For example, for the ASP '2001:db8:1::/48' within the domain name "linkupnetworks.example.com", the DNS database contains:

```
'*.1.0.0.0.8.b.d.0.1.0.0.2.aero.linkupnetworks.net. PTR
linkupnetworks.example.com'
```

This DNS registration advertises the AERO link's ASPs to prospective correspondent nodes.

### **3.6. AERO Interface Initialization**

#### **3.6.1. AERO Relay Behavior**

When a Relay enables an AERO interface, it first assigns an administratively provisioned link-local address fe80::ID to the interface. Each fe80::ID address MUST be unique among all AERO nodes on the link, and MUST NOT collide with any potential AERO addresses nor the special addresses fe80:: and fe80::ffff:ffff:ffff:ffff. (The fe80::ID addresses are typically taken from the available range fe80::/96, e.g., as fe80::1, fe80::2, fe80::3, etc.) The Relay then engages in a dynamic routing protocol session with all Servers on the link (see: [Section 3.7](#)), and advertises its assigned ASP prefixes into the native IP Internetwork.

Each Relay subsequently maintains an IP forwarding table entry for each Client-Server association, and maintains a neighbor cache entry for each Server on the link. Relays exchange NS/NA messages with AERO link neighbors the same as for any AERO node, however they typically do not perform explicit Neighbor Unreachability Detection (NUD) (see: [Section 3.18](#)) since the dynamic routing protocol already provides reachability confirmation.

#### **3.6.2. AERO Server Behavior**

When a Server enables an AERO interface, it assigns an administratively provisioned link-local address fe80::ID the same as for Relays. The Server further configures a DHCPv6 server function to facilitate DHCPv6 PD exchanges with AERO Clients. The Server maintains a neighbor cache entry for each Relay on the link, and manages per-Client neighbor cache entries and IP forwarding table entries based on control message exchanges. Each Server also engages in a dynamic routing protocol with each Relay on the link (see: [Section 3.7](#)).

When the Server receives an NS/RS message from a Client on the AERO interface it returns an NA/RA message but does not update the neighbor cache. The Server further provides a simple conduit between



AERO interface neighbors. Therefore, packets enter the Server's AERO interface from the link layer and are forwarded back out the link layer without ever leaving the AERO interface and therefore without ever disturbing the network layer.

### **3.6.3. AERO Client Behavior**

When a Client enables an AERO interface, it uses the special address `fe80::ffff:ffff:ffff:ffff` to obtain an ACP from an AERO Server via DHCPv6 PD. Next, it assigns the corresponding AERO address to the AERO interface and creates a neighbor cache entry for the Server, i.e., the PD exchange bootstraps autoconfiguration of a unique link-local address. The Client maintains a neighbor cache entry for each of its Servers and each of its active correspondent Clients. When the Client receives Redirect/Predirect messages on the AERO interface it updates or creates neighbor cache entries, including link-layer address information. Unsolicited NA messages update the cached link-layer addresses for correspondent Clients (e.g., following a link-layer address change due to node mobility) but do not create new neighbor cache entries. NS/NA messages used for NUD update timers in existing neighbor cache entries but do not update link-layer addresses nor create new neighbor cache entries.

Finally, the Client need not maintain any IP forwarding table entries for its Servers or correspondent Clients. Instead, it can set a single "route-to-interface" default route in the IP forwarding table, and all forwarding decisions can be made within the AERO interface based on neighbor cache entries. (On systems in which adding a default route would violate security policy, the default route could instead be installed via a "synthesized RA", e.g., as discussed in [Section 3.15.2.](#))

### **3.6.4. AERO Forwarding Agent Behavior**

When a Forwarding Agent enables an AERO interface, it assigns the same link-local address(es) as the companion AERO Server. The Forwarding Agent thereafter provides data plane forwarding services based solely on the forwarding information assigned to it by the companion AERO Server.

## **3.7. AERO Link Routing System**

Relays require full topology knowledge of all ACP/Server associations for the ASPs they service, while individual Servers at a minimum only need to know the ACPs for their current set of associated Clients. This is accomplished through the use of an internal instance of the Border Gateway Protocol (BGP) [[RFC4271](#)] coordinated between Servers and Relays. This internal BGP instance does not interact with the





public Internet BGP instance; therefore, the AERO link is presented to the IP Internetwork as a small set of ASPs as opposed to the full set of individual ACPs.

In a reference BGP arrangement, each AERO Server is configured as an Autonomous System Border Router (ASBR) for a stub Autonomous System (AS) using an AS Number (ASN) that is unique within the BGP instance, and each Server further peers with each Relay but does not peer with other Servers. Similarly, Relays do not peer with each other, since they will reliably receive all updates from all Servers and will therefore have a consistent view of the AERO link ACP delegations.

Each Server maintains a working set of associated ACPs, and dynamically announces new ACPs and withdraws departed ACPs in its BGP updates to Relays. Clients are expected to remain associated with their current Servers for extended timeframes, however Servers SHOULD selectively suppress BGP updates for impatient Clients that repeatedly associate and disassociate with them in order to dampen routing churn.

Each Relay configures a black-hole route for each ASP associated with the AERO link. By black-holing the ASPs, the Relay will maintain active forwarding table entries only for the ACPs that are currently active, and all other ACPs will correctly result in destination unreachable failures due to the black hole route.

Scaling properties of the AERO routing system are limited by the number of BGP routes that can be carried by Relays. Assuming  $O(10^6)$  as a reasonable maximum number of BGP routes, this means that  $O(10^6)$  Clients can be serviced by a single set of Relays. A means of increasing scaling would be to assign a different set of Relays for each set of ASPs. In that case, each Server still peers with each Relay, but the Server institutes route filters so that each set of Relays only receives BGP updates for the ACPs they aggregate. For example, if the ASP for the AERO link is `2001:db8::/32`, a first set of Relays could service the ASP segment `2001:db8::/40`, a second set of Relays could service `2001:db8:0100::/40`, a third set could service `2001:db8:0200::/40`, etc.

Assuming up to  $O(10^3)$  sets of Relays, the system can then accommodate  $O(10^9)$  Clients with no additional overhead for Servers and Relays. In this way, each set of Relays services a specific set of ASPs that they advertise to the native routing system outside of the AERO link, and each Server configures ASP-specific routes that list the correct set of Relays as next hops. This arrangement also allows for natural incremental deployment, and can support small scale initial deployments followed by dynamic deployment of



additional Clients, Servers and Relays without disturbing the already-deployed base.

### **3.8. AERO Interface Neighbor Cache Maintenance**

Each AERO interface maintains a conceptual neighbor cache that includes an entry for each neighbor it communicates with on the AERO link, the same as for any IPv6 interface [[RFC4861](#)]. AERO interface neighbor cache entries are said to be one of "permanent", "static" or "dynamic".

Permanent neighbor cache entries are created through explicit administrative action; they have no timeout values and remain in place until explicitly deleted. AERO Relays maintain a permanent neighbor cache entry for each Server on the link, and AERO Servers maintain a permanent neighbor cache entry for each Relay. Each entry maintains the mapping between the neighbor's fe80::ID network-layer address and corresponding link-layer address.

Static neighbor cache entries are created through DHCPv6 PD exchanges and remain in place for durations bounded by prefix lifetimes. AERO Servers maintain static neighbor cache entries for the ACPs of each of their associated Clients, and AERO Clients maintain a static neighbor cache entry for each of their associated Servers. When an AERO Server sends a DHCPv6 Reply message response to a Client's DHCPv6 Solicit/Request, Rebind or Renew message, it creates or updates a static neighbor cache entry based on the AERO address corresponding to the Client's ACP as the network-layer address, the prefix lifetime as the neighbor cache entry lifetime, the Client's encapsulation IP address and UDP port number as the link-layer address and the prefix length as the length to apply to the AERO address. When an AERO Client receives a DHCPv6 Reply message from a Server, it creates or updates a static neighbor cache entry based on the Reply message link-local source address as the network-layer address, the prefix lifetime as the neighbor cache entry lifetime, and the encapsulation IP source address and UDP source port number as the link-layer address.

Dynamic neighbor cache entries are created or updated based on receipt of an IPv6 ND message, and are garbage-collected if not used within a bounded timescale. AERO Clients maintain dynamic neighbor cache entries for each of their active correspondent Client ACPs with lifetimes based on IPv6 ND messaging constants. When an AERO Client receives a valid Redirect message it creates or updates a dynamic neighbor cache entry for the Redirect target network-layer and link-layer addresses plus prefix length. The node then sets an "AcceptTime" variable in the neighbor cache entry to ACCEPT\_TIME seconds and uses this value to determine whether packets received



from the correspondent can be accepted. When an AERO Client receives a valid Redirect message it creates or updates a dynamic neighbor cache entry for the Redirect target network-layer and link-layer addresses plus prefix length. The Client then sets a "ForwardTime" variable in the neighbor cache entry to FORWARD\_TIME seconds and uses this value to determine whether packets can be sent directly to the correspondent. The Client also sets a "MaxRetry" variable to MAX\_RETRY to limit the number of keepalives sent when a correspondent may have gone unreachable.

For dynamic neighbor cache entries, when an AERO Client receives a valid NS message it (re)sets AcceptTime for the neighbor to ACCEPT\_TIME. When an AERO Client receives a valid solicited NA message, it (re)sets ForwardTime for the neighbor to FORWARD\_TIME and sets MaxRetry to MAX\_RETRY. When an AERO Client receives a valid unsolicited NA message, it updates the correspondent's link-layer addresses but DOES NOT reset AcceptTime, ForwardTime or MaxRetry.

It is RECOMMENDED that FORWARD\_TIME be set to the default constant value 30 seconds to match the default REACHABLE\_TIME value specified for IPv6 ND [[RFC4861](#)].

It is RECOMMENDED that ACCEPT\_TIME be set to the default constant value 40 seconds to allow a 10 second window so that the AERO redirection procedure can converge before AcceptTime decrements below FORWARD\_TIME.

It is RECOMMENDED that MAX\_RETRY be set to 3 the same as described for IPv6 ND address resolution in [Section 7.3.3 of \[RFC4861\]](#).

Different values for FORWARD\_TIME, ACCEPT\_TIME, and MAX\_RETRY MAY be administratively set, if necessary, to better match the AERO link's performance characteristics; however, if different values are chosen, all nodes on the link MUST consistently configure the same values. Most importantly, ACCEPT\_TIME SHOULD be set to a value that is sufficiently longer than FORWARD\_TIME to allow the AERO redirection procedure to converge.

### **[3.9.](#) AERO Interface Sending Algorithm**

IP packets enter a node's AERO interface either from the network layer (i.e., from a local application or the IP forwarding system), or from the link layer (i.e., from the AERO tunnel virtual link). Packets that enter the AERO interface from the network layer are encapsulated and admitted into the AERO link, i.e., they are tunnelled to an AERO interface neighbor. Packets that enter the AERO interface from the link layer are either re-admitted into the AERO link or delivered to the network layer where they are subject to



either local delivery or IP forwarding. Since each AERO node may have only partial information about neighbors on the link, AERO interfaces may forward packets with link-local destination addresses at a layer below the network layer. This means that AERO nodes act as both IP routers and sub-IP layer forwarding agents. AERO interface sending considerations for Clients, Servers and Relays are given below.

When an IP packet enters a Client's AERO interface from the network layer, if the destination is covered by an ASP the Client searches for a dynamic neighbor cache entry with a non-zero ForwardTime and an AERO address that matches the packet's destination address. (The destination address may be either an address covered by the neighbor's ACP or the (link-local) AERO address itself.) If there is a match, the Client uses a link-layer address in the entry as the link-layer address for encapsulation then admits the packet into the AERO link. If there is no match, the Client instead uses the link-layer address of a neighboring Server as the link-layer address for encapsulation.

When an IP packet enters a Server's AERO interface from the link layer, if the destination is covered by an ASP the Server searches for a neighbor cache entry with an AERO address that matches the packet's destination address. (The destination address may be either an address covered by the neighbor's ACP or the AERO address itself.) If there is a match, the Server uses a link-layer address in the entry as the link-layer address for encapsulation and re-admits the packet into the AERO link. If there is no match, the Server instead uses the link-layer address in a permanent neighbor cache entry for a Relay as the link-layer address for encapsulation.

When an IP packet enters a Relay's AERO interface from the network layer, the Relay searches its IP forwarding table for an entry that is covered by an ASP and also matches the destination. If there is a match, the Relay uses the link-layer address in a permanent neighbor cache entry for a Server as the link-layer address for encapsulation and admits the packet into the AERO link. When an IP packet enters a Relay's AERO interface from the link-layer, if the destination is not a link-local address and does not match an ASP the Relay removes the packet from the AERO interface and uses IP forwarding to forward the packet to the Internetwork. If the destination address is a link-local address or a non-link-local address that matches an ASP, and there is a more-specific ACP entry in the IP forwarding table, the Relay uses the link-layer address in the corresponding neighbor cache entry as the link-layer address for encapsulation and re-admits the packet into the AERO link. When an IP packet enters a Relay's AERO interface from either the network layer or link-layer, and the packet's destination address matches an ASP but there is no more-





specific ACP entry, the Relay drops the packet and returns an ICMP Destination Unreachable message (see: [Section 3.14](#)).

When an AERO Server receives a packet from a Relay via the AERO interface, the Server MUST NOT forward the packet back to the same or a different Relay.

When an AERO Relay receives a packet from a Server via the AERO interface, the Relay MUST NOT forward the packet back to the same Server.

When an AERO node re-admits a packet into the AERO link without involving the network layer, the node MUST NOT decrement the network layer TTL/Hop-count.

When an AERO node forwards a data packet to the primary link-layer address of a Server, it may receive Redirect messages with an SLLAO that include the link-layer address of an AERO Forwarding Agent. The AERO node SHOULD record the link-layer address in the neighbor cache entry for the neighbor and send subsequent data packets via this address instead of the Server's primary address (see: [Section 3.16](#)).

### **[3.10](#). AERO Interface Encapsulation and Re-encapsulation**

AERO interfaces encapsulate IP packets according to whether they are entering the AERO interface from the network layer or if they are being re-admitted into the same AERO link they arrived on. This latter form of encapsulation is known as "re-encapsulation".

The AERO interface encapsulates packets per the Generic UDP Encapsulation (GUE) encapsulation procedures in [\[I-D.ietf-nvo3-gue\]](#) [\[I-D.herbert-gue-fragmentation\]](#). During encapsulation, the AERO interface copies the "TTL/Hop Limit", "Type of Service/Traffic Class" [\[RFC2983\]](#), "Flow Label" [\[RFC6438\]](#) (for IPv6) and "Congestion Experienced" [\[RFC3168\]](#) values in the packet's IP header into the corresponding fields in the encapsulation IP header. For packets undergoing re-encapsulation, the AERO interface instead copies the "TTL/Hop Limit", "Type of Service/Traffic Class", "Flow Label" and "Congestion Experienced" values in the original encapsulation IP header into the corresponding fields in the new encapsulation IP header, i.e., the values are transferred between encapsulation headers and \*not\* copied from the encapsulated packet's network-layer header.

The AERO interface next sets the UDP source port to a constant value that it will use in each successive packet it sends, and sets the UDP length field to the length of the encapsulated packet plus 8 bytes for the UDP header itself, plus the length of the GUE header. For



packets sent via a Server, the AERO interface sets the UDP destination port to 8060, i.e., the IANA-registered port number for AERO. For packets sent to a correspondent Client, the AERO interface sets the UDP destination port to the port value stored in the neighbor cache entry for this correspondent. The AERO interface also sets the UDP checksum field per the procedures specified in [\[I-D.ietf-nvo3-gue\]](#).

The AERO interface next sets the IP protocol number in the encapsulation header to 17 (i.e., the IP protocol number for UDP). When IPv4 is used as the encapsulation protocol, the AERO interface sets the DF bit as discussed in [Section 3.13](#).

### **[3.11.](#) AERO Interface Decapsulation**

AERO interfaces decapsulate packets destined either to the node itself or to a destination reached via an interface other than the AERO interface the packet was received on. Decapsulation is per the procedures specified in [\[I-D.ietf-nvo3-gue\]](#).

### **[3.12.](#) AERO Interface Data Origin Authentication**

AERO nodes employ simple data origin authentication procedures for encapsulated packets they receive from other nodes on the AERO link. In particular:

- o AERO Relays and Servers accept encapsulated packets with a link-layer source address that matches a permanent neighbor cache entry.
- o AERO Servers accept authentic encapsulated DHCPv6 messages from Clients, and create or update a static neighbor cache entry for the source based on the specific message type.
- o AERO Servers accept encapsulated packets if there is a neighbor cache entry with an AERO address that matches the packet's network-layer source address and with a link-layer address that matches the packet's link-layer source address.
- o AERO Clients accept encapsulated packets if there is a static neighbor cache entry with a link-layer source address that matches the packet's link-layer source address.
- o AERO Clients and Servers accept encapsulated packets if there is a dynamic neighbor cache entry with an AERO address that matches the packet's network-layer source address, with a link-layer address that matches the packet's link-layer source address, and with a non-zero AcceptTime.



Note that this simple data origin authentication is effective in environments in which link-layer addresses cannot be spoofed. In other environments, each AERO message must include a signature that the recipient can use to authenticate the message origin.

### **3.13. AERO Interface MTU and Fragmentation**

The AERO interface is the node's point of attachment to the AERO link. AERO links over IP networks have a maximum link MTU of 64KB minus the encapsulation overhead (i.e., 64KB-ENCAPS), since the maximum packet size in the base IP specifications is 64KB [RFC0791][RFC2460]. While IPv6 jumbograms can be up to 4GB [RFC2675], they are considered optional for IPv6 nodes [RFC6434] and therefore out of scope for this document.

AERO interfaces are considered to have an indefinite MTU, i.e., instead of clamping the MTU to a finite size. The MTU for each destination AERO interface is therefore constrained by the minimum of 64KB, the MTU of the underlying interface used for tunneling, and the path MTU within the tunnel (minus ENCAPS in each case).

IPv6 specifies a minimum link MTU of 1280 bytes [RFC2460]. This is the minimum packet size the AERO interface MUST admit without returning an ICMP Packet Too Big (PTB) message. Although IPv4 specifies a smaller minimum link MTU of 68 bytes [RFC0791], AERO interfaces also observe a 1280 byte minimum for IPv4.

The vast majority of links in the Internet configure an MTU of at least 1500 bytes. Original source hosts have therefore become conditioned to expect that IP packets up to 1500 bytes in length will either be delivered to the final destination or a suitable PTB message returned. However, PTB messages may be lost in the network [RFC2923] resulting in failure of the IP Path MTU Discovery (PMTUD) mechanisms [RFC1191][RFC1981], or crafted for malicious purposes such as denial of service. For these reasons, the source AERO interface (i.e., the tunnel ingress) sends encapsulated packets to the destination AERO interface (i.e., the tunnel egress) subject to whether standard PMTUD can be leveraged within the specific deployment model. The two cases for consideration are as follows:

#### **3.13.1. All Elements in Same Administrative Domain**

When the original source, ingress and egress are all within the same well-managed administrative domain, the ingress admits a packet into the tunnel if it is not too large to traverse the tunnel in one piece or if the path MTU within the tunnel is not yet known. Otherwise, the ingress drops the packet and sends a PTB message back to the original source. Additionally, the ingress SHOULD translate any PTB



messages it receives from a router on the path to the egress and cache the MTU value as a maximum size for large packet admission.

These procedures apply when the MTU for this egress is no smaller than (1280+ENCAPS) bytes. Otherwise, the ingress can either shut down the tunnel or begin fragmenting packets that are no larger than 1280 bytes but larger than the MTU minus ENCAPS using tunnel fragmentation as specified in [Section 3.13.2](#). This exactly parallels the standard behavior specified in [\[RFC2473\]](#) except that, when the original packet is an IPv4 packet with DF=0, the ingress uses IPv4 fragmentation to fragment the original packet when necessary before encapsulation as specified in [Section 3.13.2](#).

### **[3.13.2](#). Some Elements in Different Administrative Domain**

When the original source, ingress and egress are not all within the same well-managed administrative domain, the ingress admits all packets up to 1500 bytes in length even if some fragmentation is necessary, and admits larger packets without fragmentation in case they are able to traverse the tunnel in one piece. In that case, the ingress SHOULD process any PTB messages it receives with an MTU size larger than 1500 bytes as a packet size limitation the same as described in [Section 3.13.1](#).

Several factors must be considered when fragmentation is needed. For AERO links over IPv4, the IP ID field is only 16 bits in length, meaning that fragmentation at high data rates could result in data corruption due to reassembly misassociations [\[RFC6864\]](#)[\[RFC4963\]](#) (see: [Section 3.13.4](#)). For AERO links over both IPv4 and IPv6, studies have also shown that IP fragments are dropped unconditionally over some network paths [\[I-D.taylor-v6ops-fragdrop\]](#). For these reasons, when fragmentation is needed the ingress inserts a GUE fragment header [\[I-D.herbert-gue-fragmentation\]](#) and applies tunnel fragmentation as described in [Section 3.1.7 of \[RFC2764\]](#). Since the fragment header reduces the room available for packet data, but the original source has no way to control its insertion, the ingress MUST include the fragment header length in the ENCAPS length even for packets in which the header does not appear.

The ingress therefore sends encapsulated packets to the egress according to the following algorithm:

- o For IP packets that are no larger than (1280-ENCAPS) bytes, the ingress encapsulates the packet and admits it into the tunnel without fragmentation. For IPv4 AERO links, the ingress sets the Don't Fragment (DF) bit to 0 so that these packets will be delivered to the egress even if there is a restricting link in the path, i.e., unless lost due to congestion or routing errors.





- o For IP packets that are larger than (1280-ENCAPS) bytes but no larger than 1500 bytes, the ingress encapsulates the packet and inserts a GUE fragment header. Next, the ingress fragments the packet into two non-overlapping fragments where the first fragment (including ENCAPS) is no larger than 1024 bytes and the second is no larger than the first. Each fragment consists of identical IP/UDP/GUE encapsulation headers followed by the fragment of the encapsulated packet itself. The ingress then admits both fragments into the tunnel, and for IPv4 sets the DF bit to 0 in the IP encapsulation header. These fragmented encapsulated packets will be delivered to the egress, which reassembles them into a whole packet. The egress therefore **MUST** be capable of reassembling packets up to 1500+ENCAPS bytes in length; hence, it is **RECOMMENDED** that the egress be capable of reassembling at least 2KB.
- o For IPv4 packets that are larger than 1500 bytes and with the DF bit set to 0, the ingress uses ordinary IPv4 fragmentation to break the unencapsulated packet into a minimum number of non-overlapping fragments where the first fragment is no larger than 1024-ENCAPS and all other fragments are no larger than the first fragment. The ingress then encapsulates each fragment (and for IPv4 sets the DF bit to 0) then admits them into the tunnel. These fragments will be delivered to the final destination via the egress.
- o For all other IP packets, if the packet is too large to enter the underlying interface following encapsulation, the ingress drops the packet and returns a network-layer (L3) PTB message to the original source with MTU set to the larger of 1500 bytes or the underlying interface MTU minus ENCAPS. Otherwise, the ingress encapsulates the packet and admits it into the tunnel without fragmentation (and for IPv4 sets the DF bit to 1) and translates any link-layer (L2) PTB messages it may receive from the network with an MTU size larger than 1500 bytes into corresponding L3 PTB messages to send to the original source as specified in [Section 3.14](#). Since both L2 and L3 PTB messages may either be lost or contain insufficient information, however, it is **RECOMMENDED** that original sources that send unfragmentable IP packets larger than 1500 bytes use Packetization Layer Path MTU Discovery (PLPMTUD) [[RFC4821](#)].

While sending packets according to the above algorithm, the ingress **MAY** also send 1500 byte or larger probe packets to determine whether they can reach the egress without fragmentation. If the probes succeed, the ingress can discontinue fragmentation and (for IPv4) set DF to 1. Since the path MTU within the tunnel may fluctuate due to routing changes, the ingress **SHOULD** continue to send additional



probes subject to rate limiting and SHOULD process any L2 PTB messages as an indication that the path MTU may have decreased. If the path MTU within the tunnel becomes insufficient, the source MUST resume fragmentation.

To construct a probe, the ingress can prepare an NS message with a Nonce option plus trailing NULL padding octets added to the probe length without including the length of the padding in the IPv6 Payload Length field, but with the length included in the encapsulating IP header. The ingress then encapsulates the padded NS message in the encapsulation headers (and for IPv4 sets DF to 1) then sends the message to the egress. If the egress returns a solicited NA message with a matching Nonce option, the ingress deems the probe successful. (Note that other means of probing such as sending a self-addressed data packet that will be looped back if received by the egress are also permissible.)

When probing is used, it is essential that probes follow the same paths used to convey actual data packets to avoid path variations due to Equal Cost MultiPath (ECMP) and Link Aggregation Gateway (LAG) equipment in the path. In order to ensure that probes follow the same paths as data packets, the ingress sets both the Differentiated Service Code Point (DSCP) [[RFC2983](#)] and (for IPv6) Flow Label [[RFC6438](#)] fields to a constant value during encapsulation instead of copying these values from the original packet. In that case, it is RECOMMENDED that the ingress set these fields to the value 0.

Note that an exception to the above rules occurs when the original source and ingress are both within the same well-managed administrative domain. In that case, if the underlying interface used by the ingress for tunneling configures an MTU smaller than (1500+HLEN) bytes, the ingress MAY drop packets that are larger than 1280 bytes and larger than the underlying interface MTU following encapsulation, and return a PTB message to the original source.

### **[3.13.3.](#) Accommodating Large Control Messages**

Control messages (i.e., IPv6 ND, DHCPv6, etc.) MUST be accommodated even if some fragmentation is necessary. These packets are therefore accommodated through a modification of the second rule in the above algorithm as follows:

- o For control messages that are larger than (1280-ENCAPS) bytes, the ingress encapsulates the packet and inserts a GUE fragment header. Next, the ingress uses GUE fragmentation [[I-D.herbert-gue-fragmentation](#)] to break the packet into a minimum number of non-overlapping fragments where the first fragment (including ENCAPS) is no larger than 1024 bytes and the remaining



fragments are no larger than the first. The ingress then encapsulates each fragment (and for IPv4 sets the DF bit to 0) then admits them into the tunnel.

Control messages that exceed the 2KB minimum reassembly size rarely occur in the modern era, however the egress SHOULD be able to reassemble them if they do. This means that the egress SHOULD include a configuration knob allowing the operator to set a larger reassembly buffer size if large control messages become more common in the future.

The ingress MAY send large control messages without fragmentation if there is assurance that large packets can traverse the tunnel without fragmentation.

The ingress MAY send 1500 byte or larger probe packets as specified in the previous section to determine a size for which fragmentation can be avoided.

#### **3.13.4. Integrity**

When fragmentation is needed, there must be assurance that reassembly can be safely conducted without incurring data corruption. Sources of corruption can include implementation errors, memory errors and misassociations of fragments from a first datagram with fragments of another datagram. The first two conditions (implementation and memory errors) are mitigated by modern systems and implementations that have demonstrated integrity through decades of operational practice. The third condition (reassembly misassociations) must be accounted for by AERO.

The fragmentation procedure described in the above algorithms can reuse standard IPv6 fragmentation and reassembly code. Since the GUE fragment header includes a 32-bit ID field, there would need to be  $2^{32}$  packets alive in the network before a second packet with a duplicate ID enters the system with the (remote) possibility for a reassembly misassociation. For 1280 byte packets, and for a maximum network lifetime value of 60 seconds[RFC2460], this means that the ingress would need to produce  $\sim(7 * 10^{12})$  bits/sec in order for a duplication event to be possible. This exceeds the bandwidth of data link technologies of the modern era, but not necessarily so going forward into the future. Although wireless data links commonly used by AERO Clients support vastly lower data rates, the aggregate data rates between AERO Servers and Relays may be substantial. However, high speed data links in the network core are expected to configure larger MTUs, e.g., 4KB, 8KB or even larger such that unfragmented packets can be used. Hence, no integrity check is included to cover fragmentation and reassembly procedures.



When the ingress sends an IPv4-encapsulated packet with the DF bit set to 0 in the above algorithms, there is a chance that the packet may be fragmented by an IPv4 router somewhere within the tunnel. Since the largest such packet is only 1280 bytes, however, it is very likely that the packet will traverse the tunnel without incurring a restricting link. Even when a link within the tunnel configures an MTU smaller than 1280 bytes, it is very likely that it does so due to limited performance characteristics [[RFC3819](#)]. This means that the tunnel would not be able to convey fragmented IPv4-encapsulated packets fast enough to produce reassembly misassociations, as discussed above. However, AERO must also account for the possibility of tunnel paths that include "poorly managed" IPv4 link MTUs due to misconfigurations.

Since the IPv4 header includes only a 16-bit ID field, there would only need to be  $2^{16}$  packets alive in the network before a second packet with a duplicate ID enters the system. For 1280 byte packets, and for a maximum network lifetime value of 120 seconds[RFC0791], this means that the ingress would only need to produce  $\sim(5 * 10^6)$  bits/sec in order for a duplication event to be possible - a value that is well within range for many modern wired and wireless data link technologies.

Therefore, if there is strong operational assurance that no IPv4 links capable of supporting data rates of 5Mbps or more configure an MTU smaller than 1280 the ingress MAY omit an integrity check for the IPv4 fragmentation and reassembly procedures; otherwise, the ingress SHOULD include an integrity check. When an upper layer encapsulation (e.g., IPsec) already includes an integrity check, the ingress need not include an additional check. Otherwise, the ingress calculates the UDP checksum over the encapsulated packet and writes the value into the UDP encapsulation header, i.e., instead of writing the value 0. The egress will then verify the UDP checksum and discard the packet if the checksum is incorrect.

### **[3.14.](#) AERO Interface Error Handling**

When an AERO node admits encapsulated packets into the AERO interface, it may receive link-layer (L2) or network-layer (L3) error indications.

An L2 error indication is an ICMP error message generated by a router on the path to the neighbor or by the neighbor itself. The message includes an IP header with the address of the node that generated the error as the source address and with the link-layer address of the AERO node as the destination address.





The IP header is followed by an ICMP header that includes an error Type, Code and Checksum. For ICMPv6 [RFC4443], the error Types include "Destination Unreachable", "Packet Too Big (PTB)", "Time Exceeded" and "Parameter Problem". For ICMPv4 [RFC0792], the error Types include "Destination Unreachable", "Fragmentation Needed" (a Destination Unreachable Code that is analogous to the ICMPv6 PTB), "Time Exceeded" and "Parameter Problem".

The ICMP header is followed by the leading portion of the packet that generated the error, also known as the "packet-in-error". For ICMPv6, [RFC4443] specifies that the packet-in-error includes: "As much of invoking packet as possible without the ICMPv6 packet exceeding the minimum IPv6 MTU" (i.e., no more than 1280 bytes). For ICMPv4, [RFC0792] specifies that the packet-in-error includes: "Internet Header + 64 bits of Original Data Datagram", however [RFC1812] Section 4.3.2.3 updates this specification by stating: "the ICMP datagram SHOULD contain as much of the original datagram as possible without the length of the ICMP datagram exceeding 576 bytes".

The L2 error message format is shown in Figure 3:




Figure 3: AERO Interface L2 Error Message Format



The AERO node rules for processing these L2 error messages is as follows:

- o When an AERO node receives an L2 Parameter Problem message, it processes the message the same as described as for ordinary ICMP errors in the normative references [[RFC0792](#)][RFC4443].
- o When an AERO node receives persistent L2 IPv4 Time Exceeded messages, the IP ID field may be wrapping before earlier fragments have been processed. In that case, the node SHOULD begin including IPv4 integrity checks (see: [Section 3.13.4](#)).
- o When an AERO Client receives persistent L2 Destination Unreachable messages in response to tunneled packets that it sends to one of its dynamic neighbor correspondents, the Client SHOULD test the path to the correspondent using Neighbor Unreachability Detection (NUD) (see [Section 3.18](#)). If NUD fails, the Client SHOULD set ForwardTime for the corresponding dynamic neighbor cache entry to 0 and allow future packets destined to the correspondent to flow through a Server.
- o When an AERO Client receives persistent L2 Destination Unreachable messages in response to tunneled packets that it sends to one of its static neighbor Servers, the Client SHOULD test the path to the Server using NUD. If NUD fails, the Client SHOULD delete the neighbor cache entry and attempt to associate with a new Server.
- o When an AERO Server receives persistent L2 Destination Unreachable messages in response to tunneled packets that it sends to one of its static neighbor Clients, the Server SHOULD test the path to the Client using NUD. If NUD fails, the Server SHOULD cancel the DHCPv6 PD for the Client's ACP, withdraw its route for the ACP from the AERO routing system and delete the neighbor cache entry (see [Section 3.18](#) and [Section 3.19](#)).
- o When an AERO Relay or Server receives an L2 Destination Unreachable message in response to a tunneled packet that it sends to one of its permanent neighbors, it discards the message since the routing system is likely in a temporary transitional state that will soon re-converge.
- o When an AERO node receives an L2 PTB message, it translates the message into an L3 PTB message if possible (\*) and forwards the message toward the original source as described below.

To translate an L2 PTB message to an L3 PTB message, the AERO node first caches the MTU field value of the L2 ICMP header. The node next discards the L2 IP and ICMP headers, and also discards the



encapsulation headers of the original L3 packet. Next the node encapsulates the included segment of the original L3 packet in an L3 IP and ICMP header, and sets the ICMP header Type and Code values to appropriate values for the L3 IP protocol. In the process, the node writes the maximum of 1500 bytes and (L2 MTU - ENCAPS) into the MTU field of the L3 ICMP header.

The node next writes the IP source address of the original L3 packet as the destination address of the L3 PTB message and determines the next hop to the destination. If the next hop is reached via the AERO interface, the node uses the IPv6 address ":::" or the IPv4 address "0.0.0.0" as the IP source address of the L3 PTB message. Otherwise, the node uses one of its non link-local addresses as the source address of the L3 PTB message. The node finally calculates the ICMP checksum over the L3 PTB message and writes the Checksum in the corresponding field of the L3 ICMP header. The L3 PTB message therefore is formatted as follows:

```

+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+
~
|          L3 IP Header of          |
|          error message            |
~
+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+
|          L3 ICMP Header           |
+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+ ---
~                                     ~   p
|          IP header of             |   k
|          original L3 packet       |   t
~                                     ~
+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+   i
~                                     ~   n
|          Upper layer headers and  |
|          leading portion of body  |   e
|          of the original L3 packet |   r
~                                     ~   r
+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+ ---

```

Figure 4: AERO Interface L3 Error Message Format

After the node has prepared the L3 PTB message, it either forwards the message via a link outside of the AERO interface without encapsulation, or encapsulates and forwards the message to the next hop via the AERO interface.

When an AERO Relay receives an L3 packet for which the destination address is covered by an ASP, if there is no more-specific routing information for the destination the Relay drops the packet and



returns an L3 Destination Unreachable message. The Relay first writes the IP source address of the original L3 packet as the destination address of the L3 Destination Unreachable message and determines the next hop to the destination. If the next hop is reached via the AERO interface, the Relay uses the IPv6 address "::" or the IPv4 address "0.0.0.0" as the IP source address of the L3 Destination Unreachable message and forwards the message to the next hop within the AERO interface. Otherwise, the Relay uses one of its non link-local addresses as the source address of the L3 Destination Unreachable message and forwards the message via a link outside the AERO interface.

When an AERO node receives any L3 error message via the AERO interface, it examines the destination address in the L3 IP header of the message. If the next hop toward the destination address of the error message is via the AERO interface, the node re-encapsulates and forwards the message to the next hop within the AERO interface. Otherwise, if the source address in the L3 IP header of the message is the IPv6 address "::" or the IPv4 address "0.0.0.0", the node writes one of its non link-local addresses as the source address of the L3 message and recalculates the IP and/or ICMP checksums. The node finally forwards the message via a link outside of the AERO interface.

(\*) Note that in some instances the packet-in-error field of an L2 PTB message may not include enough information for translation to an L3 PTB message. In that case, the AERO interface simply discards the L2 PTB message. It can therefore be said that translation of L2 PTB messages to L3 PTB messages can provide a useful optimization when possible, but is not critical for sources that correctly use PLPMTUD.

### **3.15. AERO Router Discovery, Prefix Delegation and Address Configuration**

#### **3.15.1. AERO DHCPv6 Service Model**

Each AERO Server configures a DHCPv6 server function to facilitate PD requests from Clients. Each Server is provisioned with a database of ACP-to-Client ID mappings for all Clients enrolled in the AERO system, as well as any information necessary to authenticate each Client. The Client database is maintained by a central administrative authority for the AERO link and securely distributed to all Servers, e.g., via the Lightweight Directory Access Protocol (LDAP) [[RFC4511](#)] or a similar distributed database service.

Therefore, no Server-to-Server DHCPv6 PD delegation state synchronization is necessary, and Clients can optionally hold separate delegations for the same ACP from multiple Servers. In this





way, Clients can associate with multiple Servers, and can receive new delegations from new Servers before deprecating delegations received from existing Servers.

AERO Clients and Servers exchange Client link-layer address information using an option format similar to the Client Link Layer Address Option (CLLAO) defined in [[RFC6939](#)]. Due to practical limitations of CLLAO, however, AERO interfaces instead use Vendor-Specific Information Options as described in the following sections.

### **3.15.2. AERO Client Behavior**

AERO Clients discover the link-layer addresses of AERO Servers via static configuration, or through an automated means such as DNS name resolution. In the absence of other information, the Client resolves the FQDN "linkupnetworks.[domainname]" where "linkupnetworks" is a constant text string and "[domainname]" is the connection-specific DNS suffix for the Client's underlying network connection (e.g., "example.com"). After discovering the link-layer addresses, the Client associates with one or more of the corresponding Servers.

To associate with a Server, the Client acts as a requesting router to request an ACP through a two-message (i.e., Solicit/Reply) or four-message (i.e., Solicit/Advertise/Request/Reply) DHCPv6 PD exchange [[RFC3315](#)][RFC3633]. The Client's Solicit/Request message includes fe80::ffff:ffff:ffff:ffff as the IPv6 source address, 'All\_DHCP\_Relay\_Agents\_and\_Servers' as the IPv6 destination address and the link-layer address of the Server as the link-layer destination address. The Solicit/Request message also includes a Rapid Commit option, a Client Identifier option with a DHCP Unique Identifier (DUID) and an Identity Association for Prefix Delegation (IA\_PD) option. If the Client is pre-provisioned with an ACP associated with the AERO service, it MAY also include the ACP in the IA\_PD to indicate its preference to the DHCPv6 server.

The Client also SHOULD include an AERO Link-registration Request (ALREQ) option to register one or more links with the Server. The Server will include an AERO Link-registration Reply (ALREP) option in the corresponding DHCPv6 Reply message as specified in [Section 3.15.3](#). (The Client MAY omit the ALREQ option, in which case the Server will still include an ALREP option in its Reply with "Link ID" set to 0, "DSCP" set to 0, and "Prf" set to 3.)

The format for the ALREQ option is shown in Figure 5:



```

      0          1          2          3
    0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1
+-+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+
|      OPTION_VENDOR_OPTS      |      option-len (1)      |
+-+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+
|                               enterprise-number = 45282   |
+-+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+
| opt-code = OPTION_ALREQ (0) |      option-len (2)      |
+-+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+
|      Link ID   | DSCP #1 |Prf| DSCP #2 |Prf|      ...
+-+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+

```

Figure 5: AERO Link-registration Request (ALREQ) Option

In the above format, the Client sets 'option-code' to `OPTION_VENDOR_OPTS`, sets 'option-len (1)' to the length of the option following this field, sets 'enterprise-number' to 45282 (see: "IANA Considerations"), sets opt-code to the value 0 ("`OPTION_ALREQ`") and sets 'option-len (2)' to the length of the remainder of the option. The Client includes appropriate 'Link ID', 'DSCP' and 'Prf' values for the underlying interface over which the DHCPv6 PD Solicit/Request message will be issued the same as specified for an S/TLLAO [Section 3.4](#). The Client MAY include multiple (DSCP, Prf) values with this Link ID, with the number of values indicated by option-len (2). The Server will register each value with the Link ID in the Client's neighbor cache entry. The Client finally includes any necessary authentication options to identify itself to the DHCPv6 server, and sends the encapsulated DHCPv6 PD Solicit/Request message via the underlying interface corresponding to Link ID. (Note that this implies that the Client must perform additional Rebind/Reply DHCPv6 exchanges with the server following the initial PD exchange using different underlying interfaces and their corresponding Link IDs if it wishes to register additional link-layer addresses and their associated DSCPs.)

When the Client receives its ACP via a DHCPv6 Reply from the AERO Server, it creates a static neighbor cache entry with the Server's link-local address as the network-layer address and the Server's encapsulation address as the link-layer address. The Client then considers the link-layer address of the Server as the primary default encapsulation address for forwarding packets for which no more-specific forwarding information is available. The Client further caches any ASPs included in the ALREP option as ASPs to apply to the AERO link.

Next, the Client autoconfigures an AERO address from the delegated ACP, assigns the AERO address to the AERO interface and sub-delegates the ACP to its attached EUNs and/or the Client's own internal virtual



interfaces. The Client also assigns a default IP route to the AERO interface as a route-to-interface, i.e., with no explicit next-hop. The Client can then determine the correct next hops for packets submitted to the AERO interface by inspecting the neighbor cache.

The Client subsequently renews its ACP delegation through each of its Servers by performing DHCPv6 Renew/Reply exchanges with the link-layer address of a Server as the link-layer destination address and the same options that were used in the initial PD request. Note that if the Client does not issue a DHCPv6 Renew before the delegation expires (e.g., if the Client has been out of touch with the Server for a considerable amount of time) it must re-initiate the DHCPv6 PD procedure.

Since the Client's AERO address is obtained from the unique ACP delegation it receives, there is no need for Duplicate Address Detection (DAD) on AERO links. Other nodes maliciously attempting to hijack an authorized Client's AERO address will be denied access to the network by the DHCPv6 server due to an unacceptable link-layer address and/or security parameters (see: Security Considerations).

When a Client attempts to perform a DHCPv6 PD exchange with a Server that is too busy to service the request, the Client may receive a "NoPrefixAvail" status code in the Server's Reply per [\[RFC3633\]](#). In that case, the Client SHOULD discontinue DHCPv6 PD attempts through this Server and try another Server.

#### **[3.15.2.1](#). Autoconfiguration for Constrained Platforms**

On some platforms (e.g., popular cell phone operating systems), the act of assigning a default IPv6 route and/or assigning an address to an interface may not be permitted from a user application due to security policy. Typically, those platforms include a TUN/TAP interface that acts as a point-to-point conduit between user applications and the AERO interface. In that case, the Client can instead generate a "synthesized RA" message. The message conforms to [\[RFC4861\]](#) and is prepared as follows:

- o the IPv6 source address is the Client's AERO address
- o the IPv6 destination address is all-nodes multicast
- o the Router Lifetime is set to a time that is no longer than the ACP DHCPv6 lifetime
- o the message does not include a Source Link Layer Address Option (SLLAO)



- o the message includes a Prefix Information Option (PIO) with a /64 prefix taken from the ACP as the prefix for autoconfiguration

The Client then sends the synthesized RA message via the TUN/TAP interface, where the operating system kernel will interpret it as though it were generated by an actual router. The operating system will then install a default route and use Stateless Address AutoConfiguration (SLAAC) to configure an IPv6 address on the TUN/TAP interface. Methods for similarly installing an IPv4 default route and IPv4 address on the TUN/TAP interface are based on synthesized DHCPv4 messages [[RFC2131](#)].

#### **[3.15.2.2.](#) Client DHCPv6 Message Source Address**

In the initial DHCPv6 PD message exchanges, AERO Clients use the special IPv6 source address 'fe80::ffff:ffff:ffff:ffff' since their AERO addresses are not yet configured. After AERO address autoconfiguration, however, AERO Clients can either continue to use 'fe80::ffff:ffff:ffff:ffff' as the source address for further DHCPv6 messaging or begin using their AERO address as the source address.

#### **[3.15.3.](#) AERO Server Behavior**

AERO Servers configure a DHCPv6 server function on their AERO links. AERO Servers arrange to add their encapsulation layer IP addresses (i.e., their link-layer addresses) to the DNS resource records for the FQDN "linkupnetworks.[domainname]" before entering service.

When an AERO Server receives a prospective Client's DHCPv6 PD Solicit/Request on its AERO interface, and the Server is too busy to service the message, it returns a Reply with status code "NoPrefixAvail" per [[RFC3633](#)]. Otherwise, the Server authenticates the message.

If authentication succeeds, the Server determines the correct ACP to delegate to the Client by searching the Client database. In environments where spoofing is not considered a threat, the Server MAY use the Client's DUID as the identification value. Otherwise, the Server SHOULD use a signed certificate provided by the Client.

When the Server delegates the ACP, it also creates an IP forwarding table entry so that the AERO routing system will propagate the ACP to all Relays that aggregate the corresponding ASP (see: [Section 3.7](#)). Next, the Server prepares a DHCPv6 Reply message to send to the Client while using fe80::ID as the IPv6 source address, the link-local address taken from the Client's Solicit/Request as the IPv6 destination address, the Server's link-layer address as the source link-layer address, and the Client's link-layer address as the





destination link-layer address. The server also includes an IA\_PD option with the delegated ACP. Since the Client may experience a fault that prevents it from issuing a DHCPv6 Release before departing from the network, Servers should set a short prefix lifetime (e.g., 40 seconds) so that stale prefix delegation state can be flushed out of the network.

The Server also includes an ALREP option that includes the UDP Port Number and IP Address values it observed when it received the ALREQ in the Client's original DHCPv6 message (if present) followed by the ASP(s) for the AERO link. The ALREP option is formatted as shown in Figure 6:




Figure 6: AERO Link-registration Reply (ALREP) Option

In the ALREP, the Server sets 'option-code' to OPTION\_VENDOR\_OPTS, sets 'option-length (1)' to the length of the option, sets



'enterprise-number' to 45282 (see: "IANA Considerations"), sets opt-code to OPTION\_ALREP (1), and sets 'option-len (2)' to the length of the remainder of the option. Next, the Server sets 'Link ID' to the same value that appeared in the ALREQ, sets Reserved to 0 and sets 'UDP Port Number' and 'IP address' to the Client's link-layer address. The Server next includes one or more ASP with the IP prefix as it would appear in the interface identifier portion of the corresponding AERO address (see: [Section 3.3](#)), except that the low-order 8 bits of the ASP field encode the prefix length instead of the low-order 8 bits of the prefix. The longest prefix that can therefore appear as an ASP is /56 for IPv6 or /24 for IPv4. (Note that if the Client did not include an ALREQ option in its DHCPv6 message, the Server MUST still include an ALREP option in the corresponding reply with 'Link ID' set to 0.)

When the Server admits the DHCPv6 Reply message into the AERO interface, it creates a static neighbor cache entry for the Client's AERO address with lifetime set to no more than the delegation lifetime and the Client's link-layer address as the link-layer address for the Link ID specified in the ALREQ. The Server then uses the Client link-layer address information in the ALREQ option as the link-layer address for encapsulation based on the (DSCP, Prf) information.

After the initial DHCPv6 PD exchange, the AERO Server maintains the neighbor cache entry for the Client until the delegation lifetime expires. If the Client issues a Renew/Reply exchange, the Server extends the lifetime. If the Client issues a Release/Reply, or if the Client does not issue a Renew/Reply before the lifetime expires, the Server deletes the neighbor cache entry for the Client and withdraws the IP route from the AERO routing system.

#### **3.15.3.1. Lightweight DHCPv6 Relay Agent (LDRA)**

AERO Clients and Servers are always on the same link (i.e., the AERO link) from the perspective of DHCPv6. However, in some implementations the DHCPv6 server and AERO interface driver may be located in separate modules. In that case, the Server's AERO interface driver module acts as a Lightweight DHCPv6 Relay Agent (LDRA) [[RFC6221](#)] to relay DHCPv6 messages to and from the DHCPv6 server module.

When the LDRA receives a DHCPv6 message from a client, it prepares an ALREP option the same as described above then wraps the option in a Relay-Supplied DHCP Option option (RSOO) [[RFC6422](#)]. The LDRA then incorporates the option into the Relay-Forward message and forwards the message to the DHCPv6 server.



When the DHCPv6 server receives the Relay-Forward message, it caches the ALREP option and authenticates the encapsulated DHCPv6 message. The DHCPv6 server subsequently ignores the ALREQ option itself, since the relay has already included the ALREP option.

When the DHCPv6 server prepares a Reply message, it then includes the ALREP option in the body of the message along with any other options, then wraps the message in a Relay-Reply message. The DHCPv6 server then delivers the Relay-Reply message to the LDRA, which discards the Relay-Reply wrapper and delivers the DHCPv6 message to the Client.

#### 3.15.4. Deleting Link Registrations

After an AERO Client registers its Link IDs and their associated (DSCP,Prf) values with the AERO Server, the Client may wish to delete one or more Link registrations, e.g., if an underlying link becomes unavailable. To do so, the Client prepares a DHCPv6 Rebind message that includes an AERO Link-registration Delete (ALDEL) option and sends the Rebind message to the Server over any available underlying link. The ALDEL option is formatted as shown in Figure 7:

```

      0              1              2              3
      0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+
|      OPTION_VENDOR_OPTS      |      option-len (1)      |
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+
|                               enterprise-number = 45282   |
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+
| opt-code = OPTION_ALDEL (2) |      option-len (2)      |
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+
| Link ID #1 | Link ID #2 | Link ID #3 |      ...      |
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+

```

Figure 7: AERO Link-registration Delete (ALDEL) Option

In the ALDEL, the Client sets 'option-code' to `OPTION_VENDOR_OPTS`, sets 'option-length (1)' to the length of the option, sets 'enterprise-number' to 45282 (see: "IANA Considerations"), sets optcode to `OPTION_ALDEL (2)`, and sets 'option-len (2)' to the length of the remainder of the option. Next, the Server includes each 'Link ID' value that it wishes to delete.

If the Client wishes to discontinue use of a Server and thereby delete all of its Link ID associations, it must use a DHCPv6 Release/Reply exchange to delete the entire neighbor cache entry, i.e., instead of using a DHCPv6 Rebind/Reply exchange with one or more ALDEL options.



### **3.16. AERO Forwarding Agent Behavior**

AERO Servers MAY associate with one or more companion AERO Forwarding Agents as platforms for offloading high-speed data plane traffic. When an AERO Server receives a Client's DHCPv6 Solicit/Request/Renew/Rebind/Release message, it services the message then forwards the corresponding Reply message to the Forwarding Agent. When the Forwarding Agent receives the Reply message, it creates, updates or deletes a neighbor cache entry with the Client's AERO address and link-layer information included in the Reply message. The Forwarding Agent then forwards the Reply message back to the AERO Server, which forwards the message to the Client. In this way, Forwarding Agent state is managed in conjunction with Server state, with the Client responsible for reliability. If the Client subsequently disappears without issuing a Release, the Server is responsible for purging stale state by sending synthesized Reply messages to the Forwarding Agent.

When an AERO Server receives a data packet on an AERO interface with a network layer destination address for which it has distributed forwarding information to a Forwarding Agent, the Server returns a Redirect message to the source neighbor (subject to rate limiting) then forwards the data packet as usual. The Redirect message includes a TLLAO with the link-layer address of the Forwarding Engine.

When the source neighbor receives the Redirect message, it SHOULD record the link-layer address in the TLLAO as the encapsulation addresses to use for sending subsequent data packets. However, the source MUST continue to use the primary link-layer address of the Server as the encapsulation address for sending control messages.

### **3.17. AERO Intradomain Route Optimization**

When a source Client forwards packets to a prospective correspondent Client within the same AERO link domain (i.e., one for which the packet's destination address is covered by an ASP), the source Client initiates an intra-domain AERO route optimization procedure. It is important to note that this procedure is initiated by the Client; if the procedure were initiated by the Server, the Server would have no way of knowing whether the Client was actually able to contact the correspondent over the route-optimized path.

The procedure is based on an exchange of IPv6 ND messages using a chain of AERO Servers and Relays as a trust basis. This procedure is in contrast to the Return Routability procedure required for route optimization to a correspondent Client located in the Internet as





described in [Section 3.22](#). The following sections specify the AERO intradomain route optimization procedure.

### 3.17.1. Reference Operational Scenario

Figure 8 depicts the AERO intradomain route optimization reference operational scenario, using IPv6 addressing as the example (while not shown, a corresponding example for IPv4 addressing can be easily constructed). The figure shows an AERO Relay ('R1'), two AERO Servers ('S1', 'S2'), two AERO Clients ('C1', 'C2') and two ordinary IPv6 hosts ('H1', 'H2'):




Figure 8: AERO Reference Operational Scenario

In Figure 8, Relay ('R1') assigns the address fe80::1 to its AERO interface with link-layer address L2(R1), Server ('S1') assigns the address fe80::2 with link-layer address L2(S1), and Server ('S2') assigns the address fe80::3 with link-layer address L2(S2). Servers ('S1') and ('S2') next arrange to add their link-layer addresses to a published list of valid Servers for the AERO link.

AERO Client ('C1') receives the ACP 2001:db8:0::/48 in a DHCPv6 PD exchange via AERO Server ('S1') then assigns the address fe80::2001:db8:0:0 to its AERO interface with link-layer address L2(C1). Client ('C1') configures a default route and neighbor cache entry via the AERO interface with next-hop address fe80::2 and link-layer address L2(S1), then sub-delegates the ACP to its attached



EUNs. IPv6 host ('H1') connects to the EUN, and configures the address 2001:db8:0::1.

AERO Client ('C2') receives the ACP 2001:db8:1::/48 in a DHCPv6 PD exchange via AERO Server ('S2') then assigns the address fe80::2001:db8:1:0 to its AERO interface with link-layer address L2(C2). Client ('C2') configures a default route and neighbor cache entry via the AERO interface with next-hop address fe80::3 and link-layer address L2(S2), then sub-delegates the ACP to its attached EUNs. IPv6 host ('H1') connects to the EUN, and configures the address 2001:db8:1::1.

### **3.17.2. Concept of Operations**

Again, with reference to Figure 8, when source host ('H1') sends a packet to destination host ('H2'), the packet is first forwarded over the source host's attached EUN to Client ('C1'). Client ('C1') then forwards the packet via its AERO interface to Server ('S1') and also sends a Redirect message toward Client ('C2') via Server ('S1'). Server ('S1') then re-encapsulates and forwards both the packet and the Redirect message out the same AERO interface toward Client ('C2') via Relay ('R1').

When Relay ('R1') receives the packet and Redirect message, it consults its forwarding table to discover Server ('S2') as the next hop toward Client ('C2'). Relay ('R1') then forwards both the packet and the Redirect message to Server ('S2'), which then forwards them to Client ('C2').

After Client ('C2') receives the Redirect message, it processes the message and returns a Redirect message toward Client ('C1') via Server ('S2'). During the process, Client ('C2') also creates or updates a dynamic neighbor cache entry for Client ('C1').

When Server ('S2') receives the Redirect message, it re-encapsulates the message and forwards it on to Relay ('R1'), which forwards the message on to Server ('S1') which forwards the message on to Client ('C1'). After Client ('C1') receives the Redirect message, it processes the message and creates or updates a dynamic neighbor cache entry for Client ('C2').

Following the above Redirect/Redirect message exchange, forwarding of packets from Client ('C1') to Client ('C2') without involving any intermediate nodes is enabled. The mechanisms that support this exchange are specified in the following sections.



### 3.17.3. Message Format

AERO Redirect/Predirect messages use the same format as for ICMPv6 Redirect messages depicted in [Section 4.5 of \[RFC4861\]](#), but also include a new "Prefix Length" field taken from the low-order 8 bits of the Redirect message Reserved field. For IPv6, valid values for the Prefix Length field are 0 through 64; for IPv4, valid values are 0 through 32. The Redirect/Predirect messages are formatted as shown in Figure 9:




Figure 9: AERO Redirect/Predirect Message Format

### 3.17.4. Sending Predirects

When a Client forwards a packet with a source address from one of its ACPs toward a destination address covered by an ASP (i.e., toward another AERO Client connected to the same AERO link), the source Client MAY send a Predirect message forward toward the destination Client via the Server.

In the reference operational scenario, when Client ('C1') forwards a packet toward Client ('C2'), it MAY also send a Predirect message



forward toward Client ('C2'), subject to rate limiting (see [Section 8.2 of \[RFC4861\]](#)). Client ('C1') prepares the Predirect message as follows:

- o the link-layer source address is set to 'L2(C1)' (i.e., the link-layer address of Client ('C1')).
- o the link-layer destination address is set to 'L2(S1)' (i.e., the link-layer address of Server ('S1')).
- o the network-layer source address is set to fe80::2001:db8:0:0 (i.e., the AERO address of Client ('C1')).
- o the network-layer destination address is set to fe80::2001:db8:1:0 (i.e., the AERO address of Client ('C2')).
- o the Type is set to 137.
- o the Code is set to 1 to indicate "Predirect".
- o the Prefix Length is set to the length of the prefix to be assigned to the Target Address.
- o the Target Address is set to fe80::2001:db8:0:0 (i.e., the AERO address of Client ('C1')).
- o the Destination Address is set to the source address of the originating packet that triggered the Predirection event. (If the originating packet is an IPv4 packet, the address is constructed in IPv4-compatible IPv6 address format).
- o the message includes one or more TLLAOs with Link ID and DSCPs set to appropriate values for Client ('C1')'s underlying interfaces, and with UDP Port Number and IP Address set to 0'.
- o the message SHOULD include a Timestamp option and a Nonce option.
- o the message includes a Redirected Header Option (RHO) that contains the originating packet truncated if necessary to ensure that at least the network-layer header is included but the size of the message does not exceed 1280 bytes.

Note that the act of sending Predirect messages is cited as "MAY", since Client ('C1') may have advanced knowledge that the direct path to Client ('C2') would be unusable or otherwise undesirable. If the direct path later becomes unusable after the initial route optimization, Client ('C1') simply allows packets to again flow through Server ('S1').





### **3.17.5. Re-encapsulating and Relaying Predirects**

When Server ('S1') receives a Predirect message from Client ('C1'), it first verifies that the TLLAOs in the Predirect are a proper subset of the Link IDs in Client ('C1')'s neighbor cache entry. If the Client's TLLAOs are not acceptable, Server ('S1') discards the message. Otherwise, Server ('S1') validates the message according to the ICMPv6 Redirect message validation rules in [Section 8.1 of \[RFC4861\]](#), except that the Predirect has Code=1. Server ('S1') also verifies that Client ('C1') is authorized to use the Prefix Length in the Predirect when applied to the AERO address in the network-layer source address by searching for the AERO address in the neighbor cache. If validation fails, Server ('S1') discards the Predirect; otherwise, it copies the correct UDP Port numbers and IP Addresses for Client ('C1')'s links into the (previously empty) TLLAOs.

Server ('S1') then examines the network-layer destination address of the Predirect to determine the next hop toward Client ('C2') by searching for the AERO address in the neighbor cache. Since Client ('C2') is not one of its neighbors, Server ('S1') re-encapsulates the Predirect and relays it via Relay ('R1') by changing the link-layer source address of the message to 'L2(S1)' and changing the link-layer destination address to 'L2(R1)'. Server ('S1') finally forwards the re-encapsulated message to Relay ('R1') without decrementing the network-layer TTL/Hop Limit field.

When Relay ('R1') receives the Predirect message from Server ('S1') it determines that Server ('S2') is the next hop toward Client ('C2') by consulting its forwarding table. Relay ('R1') then re-encapsulates the Predirect while changing the link-layer source address to 'L2(R1)' and changing the link-layer destination address to 'L2(S2)'. Relay ('R1') then relays the Predirect via Server ('S2').

When Server ('S2') receives the Predirect message from Relay ('R1') it determines that Client ('C2') is a neighbor by consulting its neighbor cache. Server ('S2') then re-encapsulates the Predirect while changing the link-layer source address to 'L2(S2)' and changing the link-layer destination address to 'L2(C2)'. Server ('S2') then forwards the message to Client ('C2').

### **3.17.6. Processing Predirects and Sending Redirects**

When Client ('C2') receives the Predirect message, it accepts the Predirect only if the message has a link-layer source address of one of its Servers (e.g., L2(S2)). Client ('C2') further accepts the message only if it is willing to serve as a redirection target. Next, Client ('C2') validates the message according to the ICMPv6



Redirect message validation rules in [Section 8.1 of \[RFC4861\]](#), except that it accepts the message even though Code=1 and even though the network-layer source address is not that of its current first-hop router.

In the reference operational scenario, when Client ('C2') receives a valid Redirect message, it either creates or updates a dynamic neighbor cache entry that stores the Target Address of the message as the network-layer address of Client ('C1'), stores the link-layer addresses found in the TLLAOs as the link-layer addresses of Client ('C1') and stores the Prefix Length as the length to be applied to the network-layer address for forwarding purposes. Client ('C2') then sets AcceptTime for the neighbor cache entry to ACCEPT\_TIME.

After processing the message, Client ('C2') prepares a Redirect message response as follows:

- o the link-layer source address is set to 'L2(C2)' (i.e., the link-layer address of Client ('C2')).
- o the link-layer destination address is set to 'L2(S2)' (i.e., the link-layer address of Server ('S2')).
- o the network-layer source address is set to fe80::2001:db8:1:0 (i.e., the AERO address of Client ('C2')).
- o the network-layer destination address is set to fe80::2001:db8:0:0 (i.e., the AERO address of Client ('C1')).
- o the Type is set to 137.
- o the Code is set to 0 to indicate "Redirect".
- o the Prefix Length is set to the length of the prefix to be applied to the Target Address.
- o the Target Address is set to fe80::2001:db8:1:0 (i.e., the AERO address of Client ('C2')).
- o the Destination Address is set to the destination address of the originating packet that triggered the Redirection event. (If the originating packet is an IPv4 packet, the address is constructed in IPv4-compatible IPv6 address format).
- o the message includes one or more TLLAOs with Link ID and DSCPs set to appropriate values for Client ('C2')'s underlying interfaces, and with UDP Port Number and IP Address set to '0'.



- o the message SHOULD include a Timestamp option and MUST echo the Nonce option received in the Redirect (i.e., if a Nonce option is included).
- o the message includes as much of the RHO copied from the corresponding AERO Redirect message as possible such that at least the network-layer header is included but the size of the message does not exceed 1280 bytes.

After Client ('C2') prepares the Redirect message, it sends the message to Server ('S2').

### **3.17.7. Re-encapsulating and Relaying Redirects**

When Server ('S2') receives a Redirect message from Client ('C2'), it first verifies that the TLLAOs in the Redirect are a proper subset of the Link IDs in Client ('C2')'s neighbor cache entry. If the Client's TLLAOs are not acceptable, Server ('S2') discards the message. Otherwise, Server ('S2') validates the message according to the ICMPv6 Redirect message validation rules in [Section 8.1 of \[RFC4861\]](#). Server ('S2') also verifies that Client ('C2') is authorized to use the Prefix Length in the Redirect when applied to the AERO address in the network-layer source address by searching for the AERO address in the neighbor cache. If validation fails, Server ('S2') discards the Redirect; otherwise, it copies the correct UDP Port numbers and IP Addresses for Client ('C2')'s links into the (previously empty) TLLAOs.

Server ('S2') then examines the network-layer destination address of the Redirect to determine the next hop toward Client ('C2') by searching for the AERO address in the neighbor cache. Since Client ('C2') is not a neighbor, Server ('S2') re-encapsulates the Redirect and relays it via Relay ('R1') by changing the link-layer source address of the message to 'L2(S2)' and changing the link-layer destination address to 'L2(R1)'. Server ('S2') finally forwards the re-encapsulated message to Relay ('R1') without decrementing the network-layer TTL/Hop Limit field.

When Relay ('R1') receives the Redirect message from Server ('S2') it determines that Server ('S1') is the next hop toward Client ('C1') by consulting its forwarding table. Relay ('R1') then re-encapsulates the Redirect while changing the link-layer source address to 'L2(R1)' and changing the link-layer destination address to 'L2(S1)'. Relay ('R1') then relays the Redirect via Server ('S1').

When Server ('S1') receives the Redirect message from Relay ('R1') it determines that Client ('C1') is a neighbor by consulting its



neighbor cache. Server ('S1') then re-encapsulates the Redirect while changing the link-layer source address to 'L2(S1)' and changing the link-layer destination address to 'L2(C1)'. Server ('S1') then forwards the message to Client ('C1').

#### **3.17.8. Processing Redirects**

When Client ('C1') receives the Redirect message, it accepts the message only if it has a link-layer source address of one of its Servers (e.g., 'L2(S1)'). Next, Client ('C1') validates the message according to the ICMPv6 Redirect message validation rules in [Section 8.1 of \[RFC4861\]](#), except that it accepts the message even though the network-layer source address is not that of its current first-hop router. Following validation, Client ('C1') then processes the message as follows.

In the reference operational scenario, when Client ('C1') receives the Redirect message, it either creates or updates a dynamic neighbor cache entry that stores the Target Address of the message as the network-layer address of Client ('C2'), stores the link-layer addresses found in the TLLAOs as the link-layer addresses of Client ('C2') and stores the Prefix Length as the length to be applied to the network-layer address for forwarding purposes. Client ('C1') then sets ForwardTime for the neighbor cache entry to FORWARD\_TIME.

Now, Client ('C1') has a neighbor cache entry with a valid ForwardTime value, while Client ('C2') has a neighbor cache entry with a valid AcceptTime value. Thereafter, Client ('C1') may forward ordinary network-layer data packets directly to Client ('C2') without involving any intermediate nodes, and Client ('C2') can verify that the packets came from an acceptable source. (In order for Client ('C2') to forward packets to Client ('C1'), a corresponding Redirect/Redirect message exchange is required in the reverse direction; hence, the mechanism is asymmetric.)

#### **3.17.9. Server-Oriented Redirection**

In some environments, the Server nearest the target Client may need to serve as the redirection target, e.g., if direct Client-to-Client communications are not possible. In that case, the Server prepares the Redirect message the same as if it were the destination Client (see: [Section 3.17.6](#)), except that it writes its own link-layer address in the TLLAO option. The Server must then maintain a dynamic neighbor cache entry for the redirected source Client.





### **3.18. Neighbor Unreachability Detection (NUD)**

AERO nodes perform Neighbor Unreachability Detection (NUD) by sending unicast NS messages to elicit solicited NA messages from neighbors the same as described in [\[RFC4861\]](#). NUD is performed either reactively in response to persistent L2 errors (see [Section 3.14](#)) or proactively to refresh existing neighbor cache entries.

When an AERO node sends an NS/NA message, it MUST use its link-local address as the IPv6 source address and the link-local address of the neighbor as the IPv6 destination address. When an AERO node receives an NS message or a solicited NA message, it accepts the message if it has a neighbor cache entry for the neighbor; otherwise, it ignores the message.

When a source Client is redirected to a target Client it SHOULD proactively test the direct path by sending an initial NS message to elicit a solicited NA response. While testing the path, the source Client can optionally continue sending packets via the Server, maintain a small queue of packets until target reachability is confirmed, or (optimistically) allow packets to flow directly to the target. The source Client SHOULD thereafter continue to proactively test the direct path to the target Client (see [Section 7.3 of \[RFC4861\]](#)) periodically in order to keep dynamic neighbor cache entries alive.

In particular, while the source Client is actively sending packets to the target Client it SHOULD also send NS messages separated by RETRANS\_TIMER milliseconds in order to receive solicited NA messages. If the source Client is unable to elicit a solicited NA response from the target Client after MAX\_RETRY attempts, it SHOULD set ForwardTime to 0 and resume sending packets via one of its Servers. Otherwise, the source Client considers the path usable and SHOULD thereafter process any link-layer errors as a hint that the direct path to the target Client has either failed or has become intermittent.

When a target Client receives an NS message from a source Client, it resets AcceptTime to ACCEPT\_TIME if a neighbor cache entry exists; otherwise, it discards the NS message. If ForwardTime is non-zero, the target Client then sends a solicited NA message to the link-layer address of the source Client; otherwise, it sends the solicited NA message to the link-layer address of one of its Servers.

When a source Client receives a solicited NA message from a target Client, it resets ForwardTime to FORWARD\_TIME if a neighbor cache entry exists; otherwise, it discards the NA message.



When ForwardTime for a dynamic neighbor cache entry expires, the source Client resumes sending any subsequent packets via a Server and may (eventually) attempt to re-initiate the AERO redirection process. When AcceptTime for a dynamic neighbor cache entry expires, the target Client discards any subsequent packets received directly from the source Client. When both ForwardTime and AcceptTime for a dynamic neighbor cache entry expire, the Client deletes the neighbor cache entry.

### **3.19. Mobility Management**

#### **3.19.1. Announcing Link-Layer Address Changes**

When a Client needs to change its link-layer address, e.g., due to a mobility event, it performs an immediate DHCPv6 Rebind/Reply exchange via each of its Servers using the new link-layer address as the source address and with an ALREQ that includes the correct Link ID and DSCP values. If authentication succeeds, the Server then update its neighbor cache and sends a DHCPv6 Reply. Note that if the Client does not issue a DHCPv6 Rebind before the prefix delegation lifetime expires (e.g., if the Client has been out of touch with the Server for a considerable amount of time), the Server's Reply will report NoBinding and the Client must re-initiate the DHCPv6 PD procedure.

Next, the Client sends unsolicited NA messages to each of its correspondent Client neighbors using the same procedures as specified in [Section 7.2.6 of \[RFC4861\]](#), except that it sends the messages as unicast to each neighbor via a Server instead of multicast. In this process, the Client should send no more than MAX\_NEIGHBOR\_ADVERTISEMENT messages separated by no less than RETRANS\_TIMER seconds to each neighbor.

With reference to Figure 8, when Client ('C2') needs to change its link-layer address it sends unicast unsolicited NA messages to Client ('C1') via Server ('S2') as follows:

- o the link-layer source address is set to 'L2(C2)' (i.e., the link-layer address of Client ('C2')).
- o the link-layer destination address is set to 'L2(S2)' (i.e., the link-layer address of Server ('S2')).
- o the network-layer source address is set to fe80::2001:db8:1:0 (i.e., the AERO address of Client ('C2')).
- o the network-layer destination address is set to fe80::2001:db8:0:0 (i.e., the AERO address of Client ('C1')).



- o the Type is set to 136.
- o the Code is set to 0.
- o the Solicited flag is set to 0.
- o the Override flag is set to 1.
- o the Target Address is set to fe80::2001:db8:1:0 (i.e., the AERO address of Client ('C2')).
- o the message includes one or more TLLAOs with Link ID and DSCPs set to appropriate values for Client ('C2')'s underlying interfaces, and with UDP Port Number and IP Address set to '0'.
- o the message SHOULD include a Timestamp option.

When Server ('S1') receives the NA message, it relays the message in the same way as described for relaying Redirect messages in [Section 3.17.7](#). In particular, Server ('S1') copies the correct UDP port numbers and IP addresses into the TLLAOs, changes the link-layer source address to its own address, changes the link-layer destination address to the address of Relay ('R1'), then forwards the NA message via the relaying chain the same as for a Redirect.

When Client ('C1') receives the NA message, it accepts the message only if it already has a neighbor cache entry for Client ('C2') then updates the link-layer addresses for Client ('C2') based on the addresses in the TLLAOs. Next, Client ('C1') SHOULD initiate the NUD procedures specified in [Section 3.18](#) to provide Client ('C2') with an indication that the link-layer source address has been updated, and to refresh ('C2')'s AcceptTime and ('C1')'s ForwardTime timers.

If Client ('C2') receives an NS message from Client ('C1') indicating that an unsolicited NA has updated its neighbor cache, Client ('C2') need not send additional unsolicited NAs. If Client ('C2')'s unsolicited NA messages are somehow lost, however, Client ('C1') will soon learn of the mobility event via NUD.

### **[3.19.2.](#) Bringing New Links Into Service**

When a Client needs to bring a new underlying interface into service (e.g., when it activates a new data link), it performs an immediate Rebind/Reply exchange via each of its Servers using the new link-layer address as the source address and with an ALREQ that includes the new Link ID and DSCP values. If authentication succeeds, the Server then updates its neighbor cache and sends a DHCPv6 Reply. The Client MAY then send unsolicited NA messages to each of its



correspondent Clients to inform them of the new link-layer address as described in [Section 3.19.1](#).

### **[3.19.3.](#) Removing Existing Links from Service**

When a Client needs to remove an existing underlying interface from service (e.g., when it de-activates an existing data link), it performs an immediate Rebind/Reply exchange via each of its Servers over any available link with an ALDEL that includes the deprecated Link ID. If authentication succeeds, the Server then updates its neighbor cache and sends a DHCPv6 Reply. The Client SHOULD then send unsolicited NA messages to each of its correspondent Clients to inform them of the deprecated link-layer address as described in [Section 3.19.1](#).

### **[3.19.4.](#) Moving to a New Server**

When a Client associates with a new Server, it performs the Client procedures specified in [Section 3.15.2](#).

When a Client disassociates with an existing Server, it sends a DHCPv6 Release message via a new Server to the unicast link-local network layer address of the old Server. The new Server then writes its own link-layer address in the DHCPv6 Release message IP source address and forwards the message to the old Server.

When the old Server receives the DHCPv6 Release, it first authenticates the message. The Server then resets the Client's neighbor cache entry lifetime to 5 seconds, rewrites the link-layer address in the neighbor cache entry to the address of the new Server, then returns a DHCPv6 Reply message to the Client via the old Server. When the lifetime expires, the old Server withdraws the IP route from the AERO routing system and deletes the neighbor cache entry for the Client. The Client can then use the Reply message to verify that the termination signal has been processed, and can delete both the default route and the neighbor cache entry for the old Server. (Note that since Release/Reply messages may be lost in the network the Client MUST retry until it gets Reply indicating that the Release was successful.)

Clients SHOULD NOT move rapidly between Servers in order to avoid causing excessive oscillations in the AERO routing system. Such oscillations could result in intermittent reachability for the Client itself, while causing little harm to the network. Examples of when a Client might wish to change to a different Server include a Server that has gone unreachable, topological movements of significant distance, etc.





### **3.20. Proxy AERO**

Proxy Mobile IPv6 (PMIPv6) [[RFC5213](#)][RFC5844][[RFC5949](#)] presents a localized mobility management scheme for use within an access network domain. It is typically used in WiFi and cellular wireless access networks, and allows Mobile Nodes (MNs) to receive and retain an IP address that remains stable within the access network domain without needing to implement any special mobility protocols. In the PMIPv6 architecture, access network devices known as Mobility Access Gateways (MAGs) provide MNs with an access link abstraction and receive prefixes for the MNs from a Local Mobility Anchor (LMA).

In a proxy AERO domain, a proxy AERO Client (acting as a MAG) can similarly provide proxy services for MNs that do not participate in AERO messaging. The proxy Client presents an access link abstraction to MNs, and performs DHCPv6 PD exchanges over the AERO interface with an AERO Server (acting as an LMA) to receive ACPs for address provisioning of new MNs that come onto an access link. This scheme assumes that proxy Clients act as fixed (non-mobile) infrastructure elements under the same administrative trust basis as for Relays and Servers.

When an MN comes onto an access link within a proxy AERO domain for the first time, the proxy Client authenticates the MN and obtains a unique identifier that it can use as a DHCPv6 DUID then issues a DHCPv6 PD Solicit/Request to its Server. When the Server delegates an ACP, the proxy Client creates an AERO address for the MN and assigns the ACP to the MN's access link. The proxy Client then configures itself as a default router for the MN and provides address autoconfiguration services (e.g., SLAAC, DHCPv6, DHCPv4, etc.) for provisioning MN addresses from the ACP over the access link. Since the proxy Client may serve many such MNs simultaneously, it may receive multiple ACP prefix delegations and configure multiple AERO addresses, i.e., one for each MN.

When two MNs are associated with the same proxy Client, the Client can forward traffic between the MNs without involving a Server since it configures the AERO addresses of both MNs and therefore also has the necessary routing information. When two MNs are associated with different proxy Clients, the source MN's Client can initiate standard AERO route optimization to discover a direct path to the target MN's Client through the exchange of Predirect/Redirect messages.

When an MN in a proxy AERO domain leaves an access link provided by an old proxy Client, the MN issues an access link-specific "leave" message that informs the old Client of the link-layer address of a new Client on the planned new access link. This is known as a "predictive handover". When an MN comes onto an access link provided



by a new proxy Client, the MN issues an access link-specific "join" message that informs the new Client of the link-layer address of the old Client on the actual old access link. This is known as a "reactive handover".

Upon receiving a predictive handover indication, the old proxy Client sends a DHCPv6 PD Solicit/Request message directly to the new Client and queues any arriving data packets addressed to the departed MN. The Solicit/Request message includes the MN's ID as the DUID, the ACP in an IA\_PD option, the old Client's address as the link-layer source address and the new Client's address as the link-layer destination address. When the new Client receives the Solicit/Request message, it changes the link-layer source address to its own address, changes the link-layer destination address to the address of its Server, and forwards the message to the Server. At the same time, the new Client creates access link state for the ACP in anticipation of the MN's arrival (while queuing any data packets until the MN arrives), creates a neighbor cache entry for the old Client with AcceptTime set to ACCEPT\_TIME, then sends a Redirect message back to the old Client. When the old Client receives the Redirect message, it creates a neighbor cache entry for the new Client with ForwardTime set to FORWARD\_TIME, then forwards any queued data packets to the new Client. At the same time, the old Client sends a DHCPv6 PD Release message to its Server. Finally, the old Client sends unsolicited NA messages to any of the ACP's correspondents with a TLLAO containing the link-layer address of the new Client. This follows the procedure specified in [Section 3.19.1](#), except that it is the old Client and not the Server that supplies the link-layer address.

Upon receiving a reactive handover indication, the new proxy Client creates access link state for the MN's ACP, sends a DHCPv6 PD Solicit/Request message to its Server, and sends a DHCPv6 PD Release message directly to the old Client. The Release message includes the MN's ID as the DUID, the ACP in an IA\_PD option, the new Client's address as the link-layer source address and the old Client's address as the link-layer destination address. When the old Client receives the Release message, it changes the link-layer source address to its own address, changes the link-layer destination address to the address of its Server, and forwards the message to the Server. At the same time, the old Client sends a Redirect message back to the new Client and queues any arriving data packets addressed to the departed MN. When the new Client receives the Redirect, it creates a neighbor cache entry for the old Client with AcceptTime set to ACCEPT\_TIME, then sends a Redirect message back to the old Client. When the old Client receives the Redirect message, it creates a neighbor cache entry for the new Client with ForwardTime set to FORWARD\_TIME, then forwards any queued data packets to the new



Client. Finally, the old Client sends unsolicited NA messages to correspondents the same as for the predictive case.

When a Server processes a DHCPv6 Solicit/Request message, it creates a neighbor cache entry for this ACP if none currently exists. If a neighbor cache entry already exists, however, the Server changes the link-layer address to the address of the new proxy Client (this satisfies the case of both the old Client and new Client using the same Server).

When a Server processes a DHCPv6 Release message, it resets the neighbor cache entry lifetime for this ACP to 5 seconds if the cached link-layer address matches the old proxy Client's address. Otherwise, the Server ignores the Release message (this satisfies the case of both the old Client and new Client using the same Server).

When a correspondent Client receives an unsolicited NA message, it changes the link-layer address for the ACP's neighbor cache entry to the address of the new proxy Client. The correspondent Client then issues a Predirect/Redirect exchange to establish a new neighbor cache entry in the new Client.

From an architectural perspective, in addition to the use of DHCPv6 PD and IPv6 ND signaling the AERO approach differs from PMIPv6 in its use of the NBMA virtual link model instead of point-to-point tunnels. This provides a more agile interface for Client/Server and Client/Client coordinations, and also facilitates simple route optimization. The AERO routing system is also arranged in such a fashion that Clients get the same service from any Server they happen to associate with. This provides a natural fault tolerance and load balancing capability such as desired for distributed mobility management.

### **3.21. Extending AERO Links Through Security Gateways**

When an enterprise mobile device moves from a campus LAN connection to a public Internet link, it must re-enter the enterprise via a security gateway that has both a physical interface connection to the Internet and a physical interface connection to the enterprise internetwork. This most often entails the establishment of a Virtual Private Network (VPN) link over the public Internet from the mobile device to the security gateway. During this process, the mobile device supplies the security gateway with its public Internet address as the link-layer address for the VPN. The mobile device then acts as an AERO Client to negotiate with the security gateway to obtain its ACP.

In order to satisfy this need, the security gateway also operates as an AERO Server with support for AERO Client proxying. In particular,



when a mobile device (i.e., the Client) connects via the security gateway (i.e., the Server), the Server provides the Client with an ACP in a DHCPv6 PD exchange the same as if it were attached to an enterprise campus access link. The Server then replaces the Client's link-layer source address with the Server's enterprise-facing link-layer address in all AERO messages the Client sends toward neighbors on the AERO link. The AERO messages are then delivered to other devices on the AERO link as if they were originated by the security gateway instead of by the AERO Client. In the reverse direction, the AERO messages sourced by devices within the enterprise network can be forwarded to the security gateway, which then replaces the link-layer destination address with the Client's link-layer address and replaces the link-layer source address with its own (Internet-facing) link-layer address.

After receiving the ACP, the Client can send IP packets that use an address taken from the ACP as the network layer source address, the Client's link-layer address as the link-layer source address, and the Server's Internet-facing link-layer address as the link-layer destination address. The Server will then rewrite the link-layer source address with the Server's own enterprise-facing link-layer address and rewrite the link-layer destination address with the target AERO node's link-layer address, and the packets will enter the enterprise network as though they were sourced from a device located within the enterprise. In the reverse direction, when a packet sourced by a node within the enterprise network uses a destination address from the Client's ACP, the packet will be delivered to the security gateway which then rewrites the link-layer destination address to the Client's link-layer address and rewrites the link-layer source address to the Server's Internet-facing link-layer address. The Server then delivers the packet across the VPN to the AERO Client. In this way, the AERO virtual link is essentially extended *\*through\** the security gateway to the point at which the VPN link and AERO link are effectively grafted together by the link-layer address rewriting performed by the security gateway. All AERO messaging services (including route optimization and mobility signaling) are therefore extended to the Client.

In order to support this virtual link grafting, the security gateway (acting as an AERO Server) must keep static neighbor cache entries for all of its associated Clients located on the public Internet. The neighbor cache entry is keyed by the AERO Client's AERO address the same as if the Client were located within the enterprise internetwork. The neighbor cache is then managed in all ways as though the Client were an ordinary AERO Client. This includes the AERO IPv6 ND messaging signaling for Route Optimization and Neighbor Unreachability Detection.





Note that the main difference between a security gateway acting as an AERO Server and an enterprise-internal AERO Server is that the security gateway has at least one enterprise-internal physical interface and at least one public Internet physical interface. Conversely, the enterprise-internal AERO Server has only enterprise-internal physical interfaces. For this reason security gateway proxying is needed to ensure that the public Internet link-layer addressing space is kept separate from the enterprise-internal link-layer addressing space. This is afforded through a natural extension of the security association caching already performed for each VPN client by the security gateway.

### **3.22. Extending IPv6 AERO Links to the Internet**

When an IPv6 host ('H1') with an address from an ACP owned by AERO Client ('C1') sends packets to a correspondent IPv6 host ('H2'), the packets eventually arrive at the IPv6 router that owns ('H2')s prefix. This IPv6 router may or may not be an AERO Client ('C2') either within the same home network as ('C1') or in a different home network.

If Client ('C1') is currently located outside the boundaries of its home network, it will connect back into the home network via a security gateway acting as an AERO Server. The packets sent by ('H1') via ('C1') will then be forwarded through the security gateway then through the home network and finally to ('C2') where they will be delivered to ('H2'). This could lead to sub-optimal performance when ('C2') could instead be reached via a more direct route without involving the security gateway.

Consider the case when host ('H1') has the IPv6 address 2001:db8:1::1, and Client ('C1') has the ACP 2001:db8:1::/64 with underlying IPv6 Internet address of 2001:db8:1000::1. Also, host ('H2') has the IPv6 address 2001:db8:2::1, and Client ('C2') has the ACP 2001:db8:2::/64 with underlying IPv6 address of 2001:db8:2000::1. Client ('C1') can determine whether 'C2' is indeed also an AERO Client willing to serve as a route optimization correspondent by resolving the AAAA records for the DNS FQDN that matches ('H2')s prefix, i.e.:

```
'0.0.0.0.2.0.0.0.8.b.d.0.1.0.0.2.aero.linkupnetworks.net'
```

If ('C2') is indeed a candidate correspondent, the FQDN lookup will return a PTR resource record that contains the domain name for the AERO link that manages ('C2')s ASP. Client ('C1') can then attempt route optimization using an approach similar to the Return Routability procedure specified for Mobile IPv6 (MIPv6) [[RFC6275](#)]. In order to support this process, both Clients MUST intercept and



decapsulate packets that have a subnet router anycast address corresponding to any of the /64 prefixes covered by their respective ACPs.

To initiate the process, Client ('C1') creates a specially-crafted encapsulated AERO Predirect message that will be routed through its home network then through ('C2')s home network and finally to ('C2') itself. Client ('C1') prepares the initial message in the exchange as follows:

- o The encapsulating IPv6 header source address is set to 2001:db8:1:: (i.e., the IPv6 subnet router anycast address for ('C1')s ACP)
- o The encapsulating IPv6 header destination address is set to 2001:db8:2:: (i.e., the IPv6 subnet router anycast address for ('C2')s ACP)
- o The encapsulating IPv6 header is followed by a UDP header with source and destination port set to 8060
- o The encapsulated IPv6 header source address is set to fe80::2001:db8:1:0 (i.e., the AERO address for ('C1'))
- o The encapsulated IPv6 header destination address is set to fe80::2001:db8:2:0 (i.e., the AERO address for ('C2'))
- o The encapsulated AERO Predirect message includes all of the securing information that would occur in a MIPv6 "Home Test Init" message (format TBD)

Client ('C1') then further encapsulates the message in the encapsulating headers necessary to convey the packet to the security gateway (e.g., through IPsec encapsulation) so that the message now appears "double-encapsulated". ('C1') then sends the message to the security gateway, which re-encapsulates and forwards it over the home network from where it will eventually reach ('C2').

At the same time, ('C1') creates and sends a second encapsulated AERO Predirect message that will be routed through the IPv6 Internet without involving the security gateway. Client ('C1') prepares the message as follows:

- o The encapsulating IPv6 header source address is set to 2001:db8:1000:1 (i.e., the Internet IPv6 address of ('C1'))



- o The encapsulating IPv6 header destination address is set to 2001:db8:2:: (i.e., the IPv6 subnet router anycast address for ('C2')s ACP)
- o The encapsulating IPv6 header is followed by a UDP header with source and destination port set to 8060
- o The encapsulated IPv6 header source address is set to fe80::2001:db8:1:0 (i.e., the AERO address for ('C1'))
- o The encapsulated IPv6 header destination address is set to fe80::2001:db8:2:0 (i.e., the AERO address for ('C2'))
- o The encapsulated AERO Redirect message includes all of the securing information that would occur in a MIPv6 "Care-of Test Init" message (format TBD)

('C2') will receive both Redirect messages through its home network then return a corresponding Redirect for each of the Redirect messages with the source and destination addresses in the inner and outer headers reversed. The first message includes all of the securing information that would occur in a MIPv6 "Home Test" message, while the second message includes all of the securing information that would occur in a MIPv6 "Care-of Test" message (formats TBD).

When ('C1') receives the Redirect messages, it performs the necessary security procedures per the MIPv6 specification. It then prepares an encapsulated NS message that includes the same source and destination addresses as for the "Care-of Test Init" Redirect message, and includes all of the securing information that would occur in a MIPv6 "Binding Update" message (format TBD) and sends the message to ('C2').

When ('C2') receives the NS message, if the securing information is correct it creates or updates a neighbor cache entry for ('C1') with fe80::2001:db8:1:0 as the network-layer address, 2001:db8:1000::1 as the link-layer address and with AcceptTime set to ACCEPT\_TIME. ('C2') then sends an encapsulated NA message back to ('C1') that includes the same source and destination addresses as for the "Care-of Test" Redirect message, and includes all of the securing information that would occur in a MIPv6 "Binding Acknowledgement" message (format TBD) and sends the message to ('C1').

When ('C1') receives the NA message, it creates or updates a neighbor cache entry for ('C2') with fe80::2001:db8:2:0 as the network-layer address and 2001:db8:2:: as the link-layer address and with ForwardTime set to FORWARD\_TIME, thus completing the route optimization in the forward direction.



('C1') subsequently forwards encapsulated packets with outer source address 2001:db8:1000::1, with outer destination address 2001:db8:2::, with inner source address taken from the 2001:db8:1::, and with inner destination address taken from 2001:db8:2:: due to the fact that it has a securely-established neighbor cache entry with non-zero ForwardTime. ('C2') subsequently accepts any such encapsulated packets due to the fact that it has a securely-established neighbor cache entry with non-zero AcceptTime.

In order to keep neighbor cache entries alive, ('C1') periodically sends additional NS messages to ('C2') and receives any NA responses. If ('C1') moves to a different point of attachment after the initial route optimization, it sends a new secured NS message to ('C2') as above to update ('C2')s neighbor cache.

If ('C2') has packets to send to ('C1'), it performs a corresponding route optimization in the opposite direction following the same procedures described above. In the process, the already-established unidirectional neighbor cache entries within ('C1') and ('C2') are updated to include the now-bidirectional information. In particular, the AcceptTime and ForwardTime variables for both neighbor cache entries are updated to non-zero values, and the link-layer address for ('C1')s neighbor cache entry for ('C2') is reset to 2001:db8:2000::1.

Note that two AERO Clients can use full security protocol messaging instead of Return Routability, e.g., if strong authentication and/or confidentiality are desired. In that case, security protocol key exchanges such as specified for MOBIKE [[RFC4555](#)] would be used to establish security associations and neighbor cache entries between the AERO clients. Thereafter, AERO NS/NA messaging can be used to maintain neighbor cache entries, test reachability, and to announce mobility events. If reachability testing fails, e.g., if both Clients move at roughly the same time, the Clients can tear down the security association and neighbor cache entries and again allow packets to flow through their home network.

### **3.23. Encapsulation Protocol Version Considerations**

A source Client may connect only to an IPvX underlying network, while the target Client connects only to an IPvY underlying network. In that case, the target and source Clients have no means for reaching each other directly (since they connect to underlying networks of different IP protocol versions) and so must ignore any redirection messages and continue to send packets via the Server.





### **3.24. Multicast Considerations**

When the underlying network does not support multicast, AERO nodes map IPv6 link-scoped multicast addresses (including 'All\_DHCP\_Relay\_Agents\_and\_Servers') to the link-layer address of a Server.

When the underlying network supports multicast, AERO nodes use the multicast address mapping specification found in [[RFC2529](#)] for IPv4 underlying networks and use a direct multicast mapping for IPv6 underlying networks. (In the latter case, "direct multicast mapping" means that if the IPv6 multicast destination address of the encapsulated packet is "M", then the IPv6 multicast destination address of the encapsulating header is also "M".)

### **3.25. Operation on AERO Links Without DHCPv6 Services**

When Servers on the AERO link do not provide DHCPv6 services, operation can still be accommodated through administrative configuration of ACPs on AERO Clients. In that case, administrative configurations of AERO interface neighbor cache entries on both the Server and Client are also necessary. However, this may interfere with the ability for Clients to dynamically change to new Servers, and can expose the AERO link to misconfigurations unless the administrative configurations are carefully coordinated.

### **3.26. Operation on Server-less AERO Links**

In some AERO link scenarios, there may be no Servers on the link and/or no need for Clients to use a Server as an intermediary trust anchor. In that case, each Client acts as a Server unto itself to establish neighbor cache entries by performing direct Client-to-Client IPv6 ND message exchanges, and some other form of trust basis must be applied so that each Client can verify that the prospective neighbor is authorized to use its claimed ACP.

When there is no Server on the link, Clients must arrange to receive ACPs and publish them via a secure alternate prefix delegation authority through some means outside the scope of this document.

### **3.27. Manually-Configured AERO Tunnels**

In addition to the dynamic neighbor discovery procedures for AERO link neighbors described above, AERO encapsulation can be applied to manually-configured tunnels. In that case, the tunnel endpoints use an administratively-assigned link-local address and exchange NS/NA messages the same as for dynamically-established tunnels.



### **3.28. Intradomain Routing**

After a tunnel neighbor relationship has been established, neighbors can use a traditional dynamic routing protocol over the tunnel to exchange routing information without having to inject the routes into the AERO routing system.

## **4. Implementation Status**

User-level and kernel-level AERO implementations have been developed and are undergoing internal testing within Boeing.

## **5. Next Steps**

A new Generic UDP Encapsulation (GUE) format has been specified in [[I-D.herbert-gue-fragmentation](#)] [[I-D.ietf-nvo3-gue](#)]. The GUE encapsulation format will eventually supplant the native AERO UDP encapsulation format.

Future versions of the spec will explore the subject of DSCP marking in more detail.

## **6. IANA Considerations**

The IANA has assigned a 4-octet Private Enterprise Number "45282" for AERO in the "enterprise-numbers" registry.

The IANA has assigned the UDP port number "8060" for an earlier experimental version of AERO [[RFC6706](#)]. This document obsoletes [[RFC6706](#)] and claims the UDP port number "8060" for all future use.

No further IANA actions are required.

## **7. Security Considerations**

AERO link security considerations are the same as for standard IPv6 Neighbor Discovery [[RFC4861](#)] except that AERO improves on some aspects. In particular, AERO uses a trust basis between Clients and Servers, where the Clients only engage in the AERO mechanism when it is facilitated by a trust anchor. Unless there is some other means of authenticating the Client's identity (e.g., link-layer security), AERO nodes SHOULD also use DHCPv6 securing services (e.g., DHCPv6 authentication, Secure DHCPv6 [[I-D.ietf-dhc-sedhcpv6](#)], etc.) for Client authentication and network admission control. In particular, Clients SHOULD include authenticating information on each Solicit/Request/Rebind/Release message they send, but omit authenticating information on Renew messages. Renew messages are exempt due to the fact that the Renew must already be checked for



having a correct link-layer address and does not update any link-layer addresses. Therefore, asking the Server to also authenticate the Renew message would be unnecessary and could result in excessive processing overhead.

AERO Redirect, Predirect and unsolicited NA messages SHOULD include a Timestamp option (see [Section 5.3 of \[RFC3971\]](#)) that other AERO nodes can use to verify the message time of origin. AERO Predirect, NS and RS messages SHOULD include a Nonce option (see [Section 5.3 of \[RFC3971\]](#)) that recipients echo back in corresponding responses.

AERO links must be protected against link-layer address spoofing attacks in which an attacker on the link pretends to be a trusted neighbor. Links that provide link-layer securing mechanisms (e.g., IEEE 802.1X WLANs) and links that provide physical security (e.g., enterprise network wired LANs) provide a first line of defense that is often sufficient. In other instances, additional securing mechanisms such as Secure Neighbor Discovery (SeND) [\[RFC3971\]](#), IPsec [\[RFC4301\]](#) or TLS [\[RFC5246\]](#) may be necessary.

AERO Clients MUST ensure that their connectivity is not used by unauthorized nodes on their EUNs to gain access to a protected network, i.e., AERO Clients that act as routers MUST NOT provide routing services for unauthorized nodes. (This concern is no different than for ordinary hosts that receive an IP address delegation but then "share" the address with unauthorized nodes via a NAT function.)

On some AERO links, establishment and maintenance of a direct path between neighbors requires secured coordination such as through the Internet Key Exchange (IKEv2) protocol [\[RFC5996\]](#) to establish a security association.

An AERO Client's link-layer address could be rewritten by a link-layer switching element on the path from the Client to the Server and not detected by the DHCPv6 security mechanism. However, such a condition would only be a matter of concern on unmanaged/unsecured links where the link-layer switching elements themselves present a man-in-the-middle attack threat. For this reason, IP security MUST be used when AERO is employed over unmanaged/unsecured links.

## **[8. Acknowledgements](#)**

Discussions both on IETF lists and in private exchanges helped shape some of the concepts in this work. Individuals who contributed insights include Mikael Abrahamsson, Mark Andrews, Fred Baker, Stewart Bryant, Brian Carpenter, Wojciech Dec, Ralph Droms, Adrian Farrel, Sri Gundavelli, Brian Haberman, Joel Halpern, Tom Herbert,



Sascha Hlusiak, Lee Howard, Andre Kostur, Ted Lemon, Andy Malis, Satoru Matsushima, Tomek Mrugalski, Alexandru Petrescu, Behcet Saikaya, Joe Touch, Bernie Volz, Ryuji Wakikawa and Lloyd Wood. Members of the IESG also provided valuable input during their review process that greatly improved the document. Special thanks go to Stewart Bryant, Joel Halpern and Brian Haberman for their shepherding guidance.

This work has further been encouraged and supported by Boeing colleagues including Dave Bernhardt, Cam Brodie, Balaguruna Chidambaram, Bruce Cornish, Claudiu Danilov, Wen Fang, Anthony Gregory, Jeff Holland, Ed King, Gen MacLean, Rob Muszkiewicz, Sean O'Sullivan, Kent Shuey, Brian Skeen, Mike Slane, Brendan Williams, Julie Wulff, Yueli Yang, and other members of the BR&T and BIT mobile networking teams.

Earlier works on NBMA tunneling approaches are found in [\[RFC2529\]](#) [\[RFC5214\]](#) [\[RFC5569\]](#).

Many of the constructs presented in this second edition of AERO are based on the author's earlier works, including:

- o The Internet Routing Overlay Network (IRON) [\[RFC6179\]](#) [\[I-D.templin-ironbis\]](#)
- o Virtual Enterprise Traversal (VET) [\[RFC5558\]](#) [\[I-D.templin-intarea-vet\]](#)
- o The Subnetwork Encapsulation and Adaptation Layer (SEAL) [\[RFC5320\]](#) [\[I-D.templin-intarea-seal\]](#)
- o AERO, First Edition [\[RFC6706\]](#)

Note that these works cite numerous earlier efforts that are not also cited here due to space limitations. The authors of those earlier works are acknowledged for their insights.

## **9. References**

### **9.1. Normative References**

- [\[RFC0768\]](#) Postel, J., "User Datagram Protocol", STD 6, [RFC 768](#), DOI 10.17487/RFC0768, August 1980, <http://www.rfc-editor.org/info/rfc768>.
- [\[RFC0791\]](#) Postel, J., "Internet Protocol", STD 5, [RFC 791](#), DOI 10.17487/RFC0791, September 1981, <http://www.rfc-editor.org/info/rfc791>.





- [RFC0792] Postel, J., "Internet Control Message Protocol", STD 5, [RFC 792](#), DOI 10.17487/RFC0792, September 1981, <<http://www.rfc-editor.org/info/rfc792>>.
- [RFC2003] Perkins, C., "IP Encapsulation within IP", [RFC 2003](#), DOI 10.17487/RFC2003, October 1996, <<http://www.rfc-editor.org/info/rfc2003>>.
- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), DOI 10.17487/RFC2119, March 1997, <<http://www.rfc-editor.org/info/rfc2119>>.
- [RFC2460] Deering, S. and R. Hinden, "Internet Protocol, Version 6 (IPv6) Specification", [RFC 2460](#), DOI 10.17487/RFC2460, December 1998, <<http://www.rfc-editor.org/info/rfc2460>>.
- [RFC2473] Conta, A. and S. Deering, "Generic Packet Tunneling in IPv6 Specification", [RFC 2473](#), DOI 10.17487/RFC2473, December 1998, <<http://www.rfc-editor.org/info/rfc2473>>.
- [RFC2474] Nichols, K., Blake, S., Baker, F., and D. Black, "Definition of the Differentiated Services Field (DS Field) in the IPv4 and IPv6 Headers", [RFC 2474](#), DOI 10.17487/RFC2474, December 1998, <<http://www.rfc-editor.org/info/rfc2474>>.
- [RFC3315] Droms, R., Ed., Bound, J., Volz, B., Lemon, T., Perkins, C., and M. Carney, "Dynamic Host Configuration Protocol for IPv6 (DHCPv6)", [RFC 3315](#), DOI 10.17487/RFC3315, July 2003, <<http://www.rfc-editor.org/info/rfc3315>>.
- [RFC3633] Troan, O. and R. Droms, "IPv6 Prefix Options for Dynamic Host Configuration Protocol (DHCP) version 6", [RFC 3633](#), DOI 10.17487/RFC3633, December 2003, <<http://www.rfc-editor.org/info/rfc3633>>.
- [RFC3971] Arkko, J., Ed., Kempf, J., Zill, B., and P. Nikander, "SEcure Neighbor Discovery (SEND)", [RFC 3971](#), DOI 10.17487/RFC3971, March 2005, <<http://www.rfc-editor.org/info/rfc3971>>.
- [RFC4213] Nordmark, E. and R. Gilligan, "Basic Transition Mechanisms for IPv6 Hosts and Routers", [RFC 4213](#), DOI 10.17487/RFC4213, October 2005, <<http://www.rfc-editor.org/info/rfc4213>>.



- [RFC4861] Narten, T., Nordmark, E., Simpson, W., and H. Soliman, "Neighbor Discovery for IP version 6 (IPv6)", [RFC 4861](#), DOI 10.17487/RFC4861, September 2007, <<http://www.rfc-editor.org/info/rfc4861>>.
- [RFC4862] Thomson, S., Narten, T., and T. Jinmei, "IPv6 Stateless Address Autoconfiguration", [RFC 4862](#), DOI 10.17487/RFC4862, September 2007, <<http://www.rfc-editor.org/info/rfc4862>>.
- [RFC6434] Jankiewicz, E., Loughney, J., and T. Narten, "IPv6 Node Requirements", [RFC 6434](#), DOI 10.17487/RFC6434, December 2011, <<http://www.rfc-editor.org/info/rfc6434>>.

## 9.2. Informative References

- [I-D.herbert-gue-fragmentation]  
Herbert, T. and F. Templin, "Fragmentation option for Generic UDP Encapsulation", [draft-herbert-gue-fragmentation-00](#) (work in progress), March 2015.
- [I-D.ietf-dhc-sedhcpv6]  
Jiang, S., Shen, S., Zhang, D., and T. Jinmei, "Secure DHCPv6", [draft-ietf-dhc-sedhcpv6-08](#) (work in progress), June 2015.
- [I-D.ietf-nvo3-gue]  
Herbert, T., Yong, L., and O. Zia, "Generic UDP Encapsulation", [draft-ietf-nvo3-gue-01](#) (work in progress), June 2015.
- [I-D.templin-intarea-seal]  
Templin, F., "The Subnetwork Encapsulation and Adaptation Layer (SEAL)", [draft-templin-intarea-seal-68](#) (work in progress), January 2014.
- [I-D.templin-intarea-vet]  
Templin, F., "Virtual Enterprise Traversal (VET)", [draft-templin-intarea-vet-40](#) (work in progress), May 2013.
- [I-D.templin-ironbis]  
Templin, F., "The Interior Routing Overlay Network (IRON)", [draft-templin-ironbis-16](#) (work in progress), March 2014.



[I-D.vandeveldde-idr-remote-next-hop]

Velde, G., Patel, K., Rao, D., Raszuk, R., and R. Bush,  
"BGP Remote-Next-Hop", [draft-vandeveldde-idr-remote-next-hop-09](#) (work in progress), March 2015.

[RFC0879] Postel, J., "The TCP Maximum Segment Size and Related Topics", [RFC 879](#), DOI 10.17487/RFC0879, November 1983, <<http://www.rfc-editor.org/info/rfc879>>.

[RFC1035] Mockapetris, P., "Domain names - implementation and specification", STD 13, [RFC 1035](#), DOI 10.17487/RFC1035, November 1987, <<http://www.rfc-editor.org/info/rfc1035>>.

[RFC1191] Mogul, J. and S. Deering, "Path MTU discovery", [RFC 1191](#), DOI 10.17487/RFC1191, November 1990, <<http://www.rfc-editor.org/info/rfc1191>>.

[RFC1812] Baker, F., Ed., "Requirements for IP Version 4 Routers", [RFC 1812](#), DOI 10.17487/RFC1812, June 1995, <<http://www.rfc-editor.org/info/rfc1812>>.

[RFC1930] Hawkinson, J. and T. Bates, "Guidelines for creation, selection, and registration of an Autonomous System (AS)", [BCP 6](#), [RFC 1930](#), DOI 10.17487/RFC1930, March 1996, <<http://www.rfc-editor.org/info/rfc1930>>.

[RFC1981] McCann, J., Deering, S., and J. Mogul, "Path MTU Discovery for IP version 6", [RFC 1981](#), DOI 10.17487/RFC1981, August 1996, <<http://www.rfc-editor.org/info/rfc1981>>.

[RFC2131] Droms, R., "Dynamic Host Configuration Protocol", [RFC 2131](#), DOI 10.17487/RFC2131, March 1997, <<http://www.rfc-editor.org/info/rfc2131>>.

[RFC2529] Carpenter, B. and C. Jung, "Transmission of IPv6 over IPv4 Domains without Explicit Tunnels", [RFC 2529](#), DOI 10.17487/RFC2529, March 1999, <<http://www.rfc-editor.org/info/rfc2529>>.

[RFC2675] Borman, D., Deering, S., and R. Hinden, "IPv6 Jumbograms", [RFC 2675](#), DOI 10.17487/RFC2675, August 1999, <<http://www.rfc-editor.org/info/rfc2675>>.

[RFC2764] Gleeson, B., Lin, A., Heinanen, J., Armitage, G., and A. Malis, "A Framework for IP Based Virtual Private Networks", [RFC 2764](#), DOI 10.17487/RFC2764, February 2000, <<http://www.rfc-editor.org/info/rfc2764>>.



- [RFC2784] Farinacci, D., Li, T., Hanks, S., Meyer, D., and P. Traina, "Generic Routing Encapsulation (GRE)", [RFC 2784](#), DOI 10.17487/RFC2784, March 2000, <<http://www.rfc-editor.org/info/rfc2784>>.
- [RFC2923] Lahey, K., "TCP Problems with Path MTU Discovery", [RFC 2923](#), DOI 10.17487/RFC2923, September 2000, <<http://www.rfc-editor.org/info/rfc2923>>.
- [RFC2983] Black, D., "Differentiated Services and Tunnels", [RFC 2983](#), DOI 10.17487/RFC2983, October 2000, <<http://www.rfc-editor.org/info/rfc2983>>.
- [RFC3168] Ramakrishnan, K., Floyd, S., and D. Black, "The Addition of Explicit Congestion Notification (ECN) to IP", [RFC 3168](#), DOI 10.17487/RFC3168, September 2001, <<http://www.rfc-editor.org/info/rfc3168>>.
- [RFC3596] Thomson, S., Huitema, C., Ksinant, V., and M. Souissi, "DNS Extensions to Support IP Version 6", [RFC 3596](#), DOI 10.17487/RFC3596, October 2003, <<http://www.rfc-editor.org/info/rfc3596>>.
- [RFC3819] Karn, P., Ed., Bormann, C., Fairhurst, G., Grossman, D., Ludwig, R., Mahdavi, J., Montenegro, G., Touch, J., and L. Wood, "Advice for Internet Subnetwork Designers", [BCP 89](#), [RFC 3819](#), DOI 10.17487/RFC3819, July 2004, <<http://www.rfc-editor.org/info/rfc3819>>.
- [RFC4271] Rekhter, Y., Ed., Li, T., Ed., and S. Hares, Ed., "A Border Gateway Protocol 4 (BGP-4)", [RFC 4271](#), DOI 10.17487/RFC4271, January 2006, <<http://www.rfc-editor.org/info/rfc4271>>.
- [RFC4291] Hinden, R. and S. Deering, "IP Version 6 Addressing Architecture", [RFC 4291](#), DOI 10.17487/RFC4291, February 2006, <<http://www.rfc-editor.org/info/rfc4291>>.
- [RFC4301] Kent, S. and K. Seo, "Security Architecture for the Internet Protocol", [RFC 4301](#), DOI 10.17487/RFC4301, December 2005, <<http://www.rfc-editor.org/info/rfc4301>>.
- [RFC4443] Conta, A., Deering, S., and M. Gupta, Ed., "Internet Control Message Protocol (ICMPv6) for the Internet Protocol Version 6 (IPv6) Specification", [RFC 4443](#), DOI 10.17487/RFC4443, March 2006, <<http://www.rfc-editor.org/info/rfc4443>>.





- [RFC4511] Serfersheim, J., Ed., "Lightweight Directory Access Protocol (LDAP): The Protocol", [RFC 4511](#), DOI 10.17487/RFC4511, June 2006, <<http://www.rfc-editor.org/info/rfc4511>>.
- [RFC4555] Eronen, P., "IKEv2 Mobility and Multihoming Protocol (MOBIKE)", [RFC 4555](#), DOI 10.17487/RFC4555, June 2006, <<http://www.rfc-editor.org/info/rfc4555>>.
- [RFC4592] Lewis, E., "The Role of Wildcards in the Domain Name System", [RFC 4592](#), DOI 10.17487/RFC4592, July 2006, <<http://www.rfc-editor.org/info/rfc4592>>.
- [RFC4821] Mathis, M. and J. Heffner, "Packetization Layer Path MTU Discovery", [RFC 4821](#), DOI 10.17487/RFC4821, March 2007, <<http://www.rfc-editor.org/info/rfc4821>>.
- [RFC4963] Heffner, J., Mathis, M., and B. Chandler, "IPv4 Reassembly Errors at High Data Rates", [RFC 4963](#), DOI 10.17487/RFC4963, July 2007, <<http://www.rfc-editor.org/info/rfc4963>>.
- [RFC4994] Zeng, S., Volz, B., Kinnear, K., and J. Brzozowski, "DHCPv6 Relay Agent Echo Request Option", [RFC 4994](#), DOI 10.17487/RFC4994, September 2007, <<http://www.rfc-editor.org/info/rfc4994>>.
- [RFC5213] Gundavelli, S., Ed., Leung, K., Devarapalli, V., Chowdhury, K., and B. Patil, "Proxy Mobile IPv6", [RFC 5213](#), DOI 10.17487/RFC5213, August 2008, <<http://www.rfc-editor.org/info/rfc5213>>.
- [RFC5214] Templin, F., Gleeson, T., and D. Thaler, "Intra-Site Automatic Tunnel Addressing Protocol (ISATAP)", [RFC 5214](#), DOI 10.17487/RFC5214, March 2008, <<http://www.rfc-editor.org/info/rfc5214>>.
- [RFC5246] Dierks, T. and E. Rescorla, "The Transport Layer Security (TLS) Protocol Version 1.2", [RFC 5246](#), DOI 10.17487/RFC5246, August 2008, <<http://www.rfc-editor.org/info/rfc5246>>.
- [RFC5320] Templin, F., Ed., "The Subnetwork Encapsulation and Adaptation Layer (SEAL)", [RFC 5320](#), DOI 10.17487/RFC5320, February 2010, <<http://www.rfc-editor.org/info/rfc5320>>.



- [RFC5494] Arkko, J. and C. Pignataro, "IANA Allocation Guidelines for the Address Resolution Protocol (ARP)", [RFC 5494](#), DOI 10.17487/RFC5494, April 2009, <<http://www.rfc-editor.org/info/rfc5494>>.
- [RFC5522] Eddy, W., Ivancic, W., and T. Davis, "Network Mobility Route Optimization Requirements for Operational Use in Aeronautics and Space Exploration Mobile Networks", [RFC 5522](#), DOI 10.17487/RFC5522, October 2009, <<http://www.rfc-editor.org/info/rfc5522>>.
- [RFC5558] Templin, F., Ed., "Virtual Enterprise Traversal (VET)", [RFC 5558](#), DOI 10.17487/RFC5558, February 2010, <<http://www.rfc-editor.org/info/rfc5558>>.
- [RFC5569] Despres, R., "IPv6 Rapid Deployment on IPv4 Infrastructures (6rd)", [RFC 5569](#), DOI 10.17487/RFC5569, January 2010, <<http://www.rfc-editor.org/info/rfc5569>>.
- [RFC5720] Templin, F., "Routing and Addressing in Networks with Global Enterprise Recursion (RANGER)", [RFC 5720](#), DOI 10.17487/RFC5720, February 2010, <<http://www.rfc-editor.org/info/rfc5720>>.
- [RFC5844] Wakikawa, R. and S. Gundavelli, "IPv4 Support for Proxy Mobile IPv6", [RFC 5844](#), DOI 10.17487/RFC5844, May 2010, <<http://www.rfc-editor.org/info/rfc5844>>.
- [RFC5949] Yokota, H., Chowdhury, K., Koodli, R., Patil, B., and F. Xia, "Fast Handovers for Proxy Mobile IPv6", [RFC 5949](#), DOI 10.17487/RFC5949, September 2010, <<http://www.rfc-editor.org/info/rfc5949>>.
- [RFC5996] Kaufman, C., Hoffman, P., Nir, Y., and P. Eronen, "Internet Key Exchange Protocol Version 2 (IKEv2)", [RFC 5996](#), DOI 10.17487/RFC5996, September 2010, <<http://www.rfc-editor.org/info/rfc5996>>.
- [RFC6146] Bagnulo, M., Matthews, P., and I. van Beijnum, "Stateful NAT64: Network Address and Protocol Translation from IPv6 Clients to IPv4 Servers", [RFC 6146](#), DOI 10.17487/RFC6146, April 2011, <<http://www.rfc-editor.org/info/rfc6146>>.
- [RFC6179] Templin, F., Ed., "The Internet Routing Overlay Network (IRON)", [RFC 6179](#), DOI 10.17487/RFC6179, March 2011, <<http://www.rfc-editor.org/info/rfc6179>>.



- [RFC6204] Singh, H., Beebe, W., Donley, C., Stark, B., and O. Troan, Ed., "Basic Requirements for IPv6 Customer Edge Routers", [RFC 6204](#), DOI 10.17487/RFC6204, April 2011, <<http://www.rfc-editor.org/info/rfc6204>>.
- [RFC6221] Miles, D., Ed., Ooghe, S., Dec, W., Krishnan, S., and A. Kavanagh, "Lightweight DHCPv6 Relay Agent", [RFC 6221](#), DOI 10.17487/RFC6221, May 2011, <<http://www.rfc-editor.org/info/rfc6221>>.
- [RFC6241] Enns, R., Ed., Bjorklund, M., Ed., Schoenwaelder, J., Ed., and A. Bierman, Ed., "Network Configuration Protocol (NETCONF)", [RFC 6241](#), DOI 10.17487/RFC6241, June 2011, <<http://www.rfc-editor.org/info/rfc6241>>.
- [RFC6275] Perkins, C., Ed., Johnson, D., and J. Arkko, "Mobility Support in IPv6", [RFC 6275](#), DOI 10.17487/RFC6275, July 2011, <<http://www.rfc-editor.org/info/rfc6275>>.
- [RFC6355] Narten, T. and J. Johnson, "Definition of the UUID-Based DHCPv6 Unique Identifier (DUID-UUID)", [RFC 6355](#), DOI 10.17487/RFC6355, August 2011, <<http://www.rfc-editor.org/info/rfc6355>>.
- [RFC6422] Lemon, T. and Q. Wu, "Relay-Supplied DHCP Options", [RFC 6422](#), DOI 10.17487/RFC6422, December 2011, <<http://www.rfc-editor.org/info/rfc6422>>.
- [RFC6438] Carpenter, B. and S. Amante, "Using the IPv6 Flow Label for Equal Cost Multipath Routing and Link Aggregation in Tunnels", [RFC 6438](#), DOI 10.17487/RFC6438, November 2011, <<http://www.rfc-editor.org/info/rfc6438>>.
- [RFC6691] Borman, D., "TCP Options and Maximum Segment Size (MSS)", [RFC 6691](#), DOI 10.17487/RFC6691, July 2012, <<http://www.rfc-editor.org/info/rfc6691>>.
- [RFC6706] Templin, F., Ed., "Asymmetric Extended Route Optimization (AERO)", [RFC 6706](#), DOI 10.17487/RFC6706, August 2012, <<http://www.rfc-editor.org/info/rfc6706>>.
- [RFC6864] Touch, J., "Updated Specification of the IPv4 ID Field", [RFC 6864](#), DOI 10.17487/RFC6864, February 2013, <<http://www.rfc-editor.org/info/rfc6864>>.



- [RFC6935] Eubanks, M., Chimento, P., and M. Westerlund, "IPv6 and UDP Checksums for Tunneled Packets", [RFC 6935](#), DOI 10.17487/RFC6935, April 2013, <<http://www.rfc-editor.org/info/rfc6935>>.
- [RFC6936] Fairhurst, G. and M. Westerlund, "Applicability Statement for the Use of IPv6 UDP Datagrams with Zero Checksums", [RFC 6936](#), DOI 10.17487/RFC6936, April 2013, <<http://www.rfc-editor.org/info/rfc6936>>.
- [RFC6939] Halwasia, G., Bhandari, S., and W. Dec, "Client Link-Layer Address Option in DHCPv6", [RFC 6939](#), DOI 10.17487/RFC6939, May 2013, <<http://www.rfc-editor.org/info/rfc6939>>.
- [RFC6980] Gont, F., "Security Implications of IPv6 Fragmentation with IPv6 Neighbor Discovery", [RFC 6980](#), DOI 10.17487/RFC6980, August 2013, <<http://www.rfc-editor.org/info/rfc6980>>.
- [RFC7078] Matsumoto, A., Fujisaki, T., and T. Chown, "Distributing Address Selection Policy Using DHCPv6", [RFC 7078](#), DOI 10.17487/RFC7078, January 2014, <<http://www.rfc-editor.org/info/rfc7078>>.
- [TUNTAP] Wikipedia, W., "<http://en.wikipedia.org/wiki/TUN/TAP>", October 2014.

#### Author's Address

Fred L. Templin (editor)  
Boeing Research & Technology  
P.O. Box 3707  
Seattle, WA 98124  
USA

Email: [fltemplin@acm.org](mailto:fltemplin@acm.org)



