

6lo  
Internet-Draft  
Updates: [4944](#) (if approved)  
Intended status: Standards Track  
Expires: December 30, 2016

P. Thubert, Ed.  
Cisco  
Z. Brodard  
Ecole Polytechnique  
H. Jiang  
G. Texier  
Telecom Bretagne  
June 28, 2016

**A 6LoRH for BitStrings**  
**draft-thubert-6lo-bier-dispatch-00**

Abstract

This specification extends the 6LoWPAN Routing Header to signal BitStrings such as utilized in Bit Index Explicit Replication and its Traffic Engineering variant.

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <http://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on December 30, 2016.

Copyright Notice

Copyright (c) 2016 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in [Section 4.e](#) of

the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

## Table of Contents

<a href="#">1.</a>	<a href="#">Introduction</a>	<a href="#">2</a>
<a href="#">2.</a>	<a href="#">Terminology</a>	<a href="#">3</a>
<a href="#">3.</a>	<a href="#">Applicability</a>	<a href="#">3</a>
<a href="#">4.</a>	<a href="#">The BIER-6LoRH encoding</a>	<a href="#">4</a>
<a href="#">4.1.</a>	<a href="#">The Bit-by-bit BitStrings</a>	<a href="#">4</a>
<a href="#">4.2.</a>	<a href="#">Bloom Filters</a>	<a href="#">5</a>
<a href="#">4.3.</a>	<a href="#">Types of BIER-6LoRH header</a>	<a href="#">5</a>
<a href="#">5.</a>	<a href="#">Implementation Status</a>	<a href="#">6</a>
<a href="#">6.</a>	<a href="#">Security Considerations</a>	<a href="#">6</a>
<a href="#">7.</a>	<a href="#">IANA Considerations</a>	<a href="#">7</a>
<a href="#">8.</a>	<a href="#">Acknowledgments</a>	<a href="#">7</a>
<a href="#">9.</a>	<a href="#">References</a>	<a href="#">7</a>
<a href="#">9.1.</a>	<a href="#">Normative References</a>	<a href="#">7</a>
<a href="#">9.2.</a>	<a href="#">Informative References</a>	<a href="#">8</a>
	<a href="#">Authors' Addresses</a>	<a href="#">8</a>

## [1.](#) Introduction

The type of information that needs to be present in a packet inside the LLN but not outside of the LLN varies with the routing operation, but there is overall a need for an extensible compression technique that would simplify the IP-in-IP encapsulation, when needed, and optimally compress existing routing artifacts found in LLNs.

The 6LoWPAN Routing Header [[I-D.ietf-roll-routing-dispatch](#)] (6LoRH) specification is such a technique, that extends the 6lo adaptation layer framework [[RFC4944](#)], [[RFC6282](#)] so as to carry routing information for Route-over use cases. The original specification includes the formats necessary for RPL such as the Source Route Header (SRH) and is intended to be extended for additional routing artifacts.

The Bit Index Explicit Replication (BIER), as introduced in the BIER Architecture [[I-D.ietf-bier-architecture](#)], can be used as an alternate artifact to route multicast as well as unicast traffic. The Traffic Engineering for Bit Index Explicit Replication [[I-D.eckert-bier-te-arch](#)] (BIER-TE) adds support for traffic engineering by explicit hop-by-hop forwarding and loose hop forwarding of packets along a unicast route.

This specification provides additional formats for the 6LoRH compression to carry BitStrings such as used for Bit Index Explicit



Replication and its Traffic Engineering variant (BIER and BIER-TE, respectively).

## 2. Terminology

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "NOT RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [\[RFC2119\]](#).

The Terminology used in this document is consistent with and incorporates that described in Terms Used in Routing for Low-Power and Lossy Networks (LLNs). [\[RFC7102\]](#).

Other terms in use in LLNs are found in Terminology for Constrained-Node Networks [\[RFC7228\]](#).

The term "byte" is used in its now customary sense as a synonym for "octet".

"RPL", "RPL Packet Information" (RPI) and "RPL Instance" are defined in the RPL: IPv6 Routing Protocol for Low-Power and Lossy Networks [\[RFC6550\]](#) specification.

The terms Bit-Forwarding Egress Routers (BFR), BFR-id and BitString are defined in [\[I-D.ietf-bier-architecture\]](#). A BitString indicates a continuous sequence of bits indexed by an offset in the sequence. The leftmost bit is bit 0 and corresponds to the value 0x80 of the leftmost octet in the BitString.

## 3. Applicability

BIER and other bit-indexed methods that would leverage BitStrings will generally require additional information in the packet to complement the BitString. For instance, BIER has the concept of a BFR-id and an Entropy value in the BIER header. Since those additional fields depend on the bit-indexed method, they are expected to be transported separately from the BitString. This specification concentrates on the BitString alone.

The DetNet Data Plane Protocol and Solution Alternatives [\[I-D.dt-detnet-dp-alt\]](#) document details how BIER-TE can be leveraged to activate the Deterministic Networking Replication and Elimination functions in a manner that is abstract to the data plane forwarding information. An adjacency, which is represented by a bit in the BIER header, can be mapped in the data plane to an Ethernet hop, a Label Switched Path, or it may correspond to a loose or a strict IPv6 Source Routed Path.



In the context of LLNs, the 6TiSCH Architecture [[I-D.ietf-6tisch-architecture](#)] introduces the concept of a Track that is a directional traffic-engineered path between a source and a destination. A Track is indicated in a packet by a Source or Destination IPv6 Address and a RPL Local Instance. The RPL Instance is carried in an IPv6 packet as part of the RPL Packet Information (RPI), and a bit in the RPI indicates whether the Instance is Local to the Source or the Destination Address. The RPI can be compressed as a RPI 6LoRH header (RPI-6LoRH) as described in [[I-D.ietf-roll-routing-dispatch](#)].

The 6TiSCH requirements for DetNet [[I-D.thubert-6tisch-4detnet](#)] indicate that a 6TiSCH Track may leverage replication and elimination as defined in DetNet. This specification enables this behavior as follows: if a BIER-6LoRH is positioned right after a RPI-6LoRH, then the BitString in the BIER-6LoRH applies to the context of the Track indicated by the source or destination address of the packet and the local Instance ID associated to the source or destination of the packet.

#### 4. The BIER-6LoRH encoding

The BIER 6LoRH (BIER-6LoRH) is a Critical 6LoWPAN Routing Header that provides a variable-size container for a BitString such as, a but not limited to, a BIER BitString.

The capability to parse the BIER BitString is necessary to forward the packet so the Type cannot be ignored.




Figure 1: The BIER-6LoRH

This specification provides a 5-bit Control field that can be used to encode information that is specific to the BitString. The type and size of the BitString are encoded in the 6LoRHType.

##### 4.1. The Bit-by-bit BitStrings

In the bit-by-bit case, each bit is mapped in an unequivocal fashion with a single addressable resource in the network. This may rapidly lead to large BitStrings, and BIER allows to divide a network into groups that partition the network so that a given BitString is



locally significant to one group only. This specification uses the 5-bits Control field to encode the group.

When groups are used, it may be that a packet is sent to different groups at the same time. In that case, multiple BIER-6LoRH headers can be prepended to a same packet, each one for a different group. As the packet flows along the multicast distribution tree, a BIER-6LoRH header that has no more destination in a given branch may be removed to make the packet shorter.

#### **4.2. Bloom Filters**

A Bloom Filter can be seen as a compression technique for the BitString. A Bloom Filter may generate false positives, which, in the case of BIER, result in undue forwarding of a packet down a path where no listener exists.

As an example, the Constrained-Cast [[I-D.bergmann-bier-ccast](#)] specification employs Bloom Filters as a compact representation of a match or non-match for elements in a set that may be larger than the number of bits in the BitString.

In the case of a Bloom Filter, a number of Hash functions must be run to obtain a multi-bit signature of an encoded element. This specification uses the 5-bits Control field to signal an Identifier of the set of Hash functions being used to generate a certain BitString, so as to enable the migration from a set of Hash functions to the next.

#### **4.3. Types of BIER-6LoRH header**

The Type of a BIER-6LoRH header indicates the size of words used to build the BitString and whether the BitString is operated as an uncompressed bit-by-bit mapping, or as a Bloom filter.





Type	Encoding	Control field	BitString Size
15	bit-by-bit	Group ID	8 bits
16	bit-by-bit	Group ID	16 bits
17	bit-by-bit	Group ID	32 bits
18	bit-by-bit	Group ID	64 bits
19	bit-by-bit	Group ID	128 bits
20	Bloom filter	Hash function Set ID	8 bits
21	Bloom filter	Hash function Set ID	16 bits
22	Bloom filter	Hash function Set ID	32 bits
23	Bloom filter	Hash function Set ID	64 bits
24	Bloom filter	Hash function Set ID	128 bits

Figure 2: The BIER-6LoRH Types

In order to address a potentially large number of devices, the BitString may grow very large. Yet, the maximum frame size for a given MAC layer may limit the number of bits that can be dedicated to routing. With this specification, a number of BIER-6LoRH headers of a same type (bit-by-bit or Bloom filter) may be placed contiguously in the packet. This results in a larger BitString that is the concatenation of the BitStrings in the individual headers in the order they are appearing in the packet.

## 5. Implementation Status

A research implementation was developed at Cisco's Paris Innovation Lab (PIRL) by Zacharie Brodard.

The implementation is based on openWSN (<https://openwsn.atlassian.net/wiki/pages/viewpage.action?pageId=688187>), and was tested on OpenMote hardware (<http://www.openmote.com/>).

The implementation covers 6LoRH Types 15 to 18 for 6TiSCH Tracks, and does not attempt to support Bloom Filters.

## 6. Security Considerations

The security considerations of [[I-D.ietf-roll-routing-dispatch](#)] apply.



## 7. IANA Considerations

This document extends the IANA registry created by [I-D.ietf-roll-routing-dispatch] for the 6LoWPAN Routing Header Type, and adds the following values:

15..24 : BIER-6LoRH [RFCthis]

## 8. Acknowledgments

## 9. References

### 9.1. Normative References

- [I-D.ietf-roll-routing-dispatch]  
Thubert, P., Bormann, C., Toutain, L., and R. Cragie,  
"6LoWPAN Routing Header", [draft-ietf-roll-routing-dispatch-00](#) (work in progress), March 2016.
- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), DOI 10.17487/RFC2119, March 1997, <<http://www.rfc-editor.org/info/rfc2119>>.
- [RFC4944] Montenegro, G., Kushalnagar, N., Hui, J., and D. Culler, "Transmission of IPv6 Packets over IEEE 802.15.4 Networks", [RFC 4944](#), DOI 10.17487/RFC4944, September 2007, <<http://www.rfc-editor.org/info/rfc4944>>.
- [RFC6550] Winter, T., Ed., Thubert, P., Ed., Brandt, A., Hui, J., Kelsey, R., Levis, P., Pister, K., Struik, R., Vasseur, JP., and R. Alexander, "RPL: IPv6 Routing Protocol for Low-Power and Lossy Networks", [RFC 6550](#), DOI 10.17487/RFC6550, March 2012, <<http://www.rfc-editor.org/info/rfc6550>>.
- [RFC7102] Vasseur, JP., "Terms Used in Routing for Low-Power and Lossy Networks", [RFC 7102](#), DOI 10.17487/RFC7102, January 2014, <<http://www.rfc-editor.org/info/rfc7102>>.
- [RFC7228] Bormann, C., Ersue, M., and A. Keranen, "Terminology for Constrained-Node Networks", [RFC 7228](#), DOI 10.17487/RFC7228, May 2014, <<http://www.rfc-editor.org/info/rfc7228>>.



## 9.2. Informative References

- [I-D.bergmann-bier-ccast]  
Bergmann, O., Bormann, C., Gerdes, S., and H. Chen,  
"Constrained-Cast: Source-Routed Multicast for RPL",  
[draft-bergmann-bier-ccast-01](#) (work in progress), April  
2016.
- [I-D.dt-detnet-dp-alt]  
Korhonen, J., Farkas, J., Mirsky, G., Thubert, P.,  
Zhuangyan, Z., and L. Berger, "DetNet Data Plane Protocol  
and Solution Alternatives", [draft-dt-detnet-dp-alt-00](#)  
(work in progress), March 2016.
- [I-D.eckert-bier-te-arch]  
Eckert, T., Cauchie, G., Braun, W., and M. Menth, "Traffic  
Engineering for Bit Index Explicit Replication BIER-TE",  
[draft-eckert-bier-te-arch-03](#) (work in progress), March  
2016.
- [I-D.ietf-6tisch-architecture]  
Thubert, P., "An Architecture for IPv6 over the TSCH mode  
of IEEE 802.15.4", [draft-ietf-6tisch-architecture-10](#) (work  
in progress), June 2016.
- [I-D.ietf-bier-architecture]  
Wijnands, I., Rosen, E., Dolganow, A., Przygienda, T., and  
S. Aldrin, "Multicast using Bit Index Explicit  
Replication", [draft-ietf-bier-architecture-03](#) (work in  
progress), January 2016.
- [I-D.thubert-6tisch-4detnet]  
Thubert, P., "6TiSCH requirements for DetNet", [draft-  
thubert-6tisch-4detnet-01](#) (work in progress), June 2015.
- [RFC6282] Hui, J., Ed. and P. Thubert, "Compression Format for IPv6  
Datagrams over IEEE 802.15.4-Based Networks", [RFC 6282](#),  
DOI 10.17487/RFC6282, September 2011,  
<<http://www.rfc-editor.org/info/rfc6282>>.

Authors' Addresses



Pascal Thubert (editor)  
Cisco Systems  
Village d'Entreprises Green Side  
400, Avenue de Roumanille  
Batiment T3  
Biot - Sophia Antipolis 06410  
FRANCE

Phone: +33 4 97 23 26 34  
Email: pthubert@cisco.com

Zacharie Brodard  
Ecole Polytechnique  
Route de Saclay  
Palaiseau 91128  
FRANCE

Phone: +33 6 73 73 35 09  
Email: zacharie.brodard@polytechnique.edu

Hao Jiang  
Telecom Bretagne  
2, rue de la Chataigneraie  
Cesson-Sevigne 35510  
FRANCE

Phone: +33 7 53 70 97 34  
Email: hao.jiang@telecom-bretagne.eu

Geraldine Texier  
Telecom Bretagne  
2, rue de la Chataigneraie  
Cesson-Sevigne 35510  
FRANCE

Phone: +33 2 99 12 70 38  
Email: geraldine.texier@telecom-bretagne.eu



