

DMM  
Internet-Draft  
Intended status: Informational  
Expires: April 19, 2014

P. Thubert, Ed.  
Cisco  
R. Wakikawa  
Softbank Mobile  
V. Devarapalli  
WiChorus  
October 18, 2013

Global HA to HA protocol  
[draft-thubert-dmm-global-haha-00](#)

## Abstract

This HAHA protocol extends MIPv6 [[RFC6275](#)] and NEMO [[RFC3963](#)] to remove their link layer dependencies on the Home Link and distribute the HAs at IP layer. Global HAHA considers the distribution at the scale of the Internet, and introduces the MIP proxy for Local Mobility Management and Route Optimization in the Infrastructure.

## Status of this Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <http://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on April 19, 2014.

## Copyright Notice

Copyright (c) 2013 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the [Trust Legal Provisions](#) and are provided without warranty as described in the Simplified BSD License.

## Table of Contents

Thubert, Wakikawa & DevarExpires April 19, 2014

[Page 1]

---

Internet-Draft	Global-HAHA	October 2013
<a href="#">1.</a>	Introduction . . . . .	<a href="#">2</a>
<a href="#">2.</a>	Motivations . . . . .	<a href="#">3</a>
<a href="#">2.1.</a>	Requirements . . . . .	<a href="#">3</a>
<a href="#">2.2.</a>	Layer 3 operations . . . . .	<a href="#">4</a>
<a href="#">2.3.</a>	Route Optimization . . . . .	<a href="#">5</a>
<a href="#">2.4.</a>	Single point of failure . . . . .	<a href="#">7</a>

3.	Rationale for the proposed solution . . . . .	7
4.	A proxy for Mobile IP . . . . .	7
5.	Overview . . . . .	8
5.1.	Initial routing . . . . .	9
5.1.1.	External routing . . . . .	9
5.1.2.	Internal routing . . . . .	10
5.2.	Binding . . . . .	11
5.2.1.	Direct primary binding . . . . .	12
5.2.2.	local proxy binding . . . . .	12
5.2.3.	Foreign proxy binding . . . . .	13
5.3.	Route Optimizations . . . . .	13
5.3.1.	Leaking MNP routes in the HAHA network . . . . .	14
5.3.2.	On-demand proxy routes . . . . .	15
6.	Terminology and concepts . . . . .	16
7.	Distributed Home Network . . . . .	18
8.	Message Formats . . . . .	18
9.	Mobile Router Operation . . . . .	19
9.1.	Locating Home . . . . .	19
9.2.	Proxy MIP client . . . . .	19
10.	Home Agent Operation . . . . .	19
10.1.	Locating the other HAs that serve the same Home . . . . .	19
10.2.	Locating the HA that owns the binding for a HoA . . . . .	19
11.	Acknowledgements . . . . .	19
12.	IANA considerations . . . . .	19
13.	Security Considerations . . . . .	19
14.	References . . . . .	20
14.1.	informative reference . . . . .	20
14.2.	normative reference . . . . .	20
	Authors' Addresses . . . . .	20

## 1. Introduction

This draft was initially submitted as [draft-thubert-nemo-global-haha](#) in 2004, but the object of the work is now being considered at DMM, so the draft is republished there to provide an historical reference. Over the ten years since the draft was originally published, IPv6 mobility evolved in particular with the introduction of Proxy Mobile IPv6 (PMIP) [[RFC5213](#)] and the Locator/ID Separation Protocol (LISP) [[RFC6830](#)]. It can be noted that the MIP proxy introduced in this document is a Route Optimization function, entirely different from a PMIP proxy function.

The MIP proxy in global HAHA is probably still relevant since it allows the separation of the interaction with 1) the client, 2) the HAs and 3) other MIP proxies, which can be individually based on traditional protocols such as Mobile IPv6 [[RFC6275](#)] and NEMO [[RFC3963](#)], or more recent approaches such as PMIP and LISP.

Mobile IPv6 [[RFC6275](#)] and NEMO Basic Support [[RFC3963](#)] documents. As such, the reader is expected to understand the concept of a Home Link and the Neighbor Discovery related operations that take place over that link.

Home Agent global distribution is useful when a Mobile Router moves geographically large area such as airplane, vehicle, etc... The overhead of the basic NEMO protocol is redundant route caused by the bi-directional tunnel between a Home Agent and a Mobile Router. If a Mobile Router moves far away from a Home Agent, the overhead can not be ignored.

Thus, it is reasonable to consider that a Mobile Router dynamically switches to the topologically closest Home Agent (Home Link). This distribution is also effective for load-balancing. The Home Agent is expected to serve thousands of Mobile Routers on its Home Link and tunnels all packets for the Mobile Routers by itself.

But with NEMO basic support and MIPv6, Home is locally anchored to the Home Link at Layer 2, so Home can not be distributed geographically. In particular for NEMO, what's needed is a route to a mobile prefix via a tunnel end point that is the CareOf address of the Mobile Router. The Home Address is but a practical artifact that is mostly needed as a correlator for the registration.

This draft proposes a model that enables the HA to HA communication at Layer 3, allowing to get rid of the Home Link in configurations where it's not needed.

This draft also introduces the concept of proxy Home Agent, enabling a Mobile Router to binding locally as it is roaming far from any of its own Home Agents.

Finally, the draft presents how the Home Agents and the proxy Home Agents can use the concept of route projection to improve the data path between Mobile Routers.

## [2.](#) Motivations

### [2.1.](#) Requirements

This draft addresses two generic requirements expressed in the Nemo requirements [[RFC4886](#)]:

Local Mobility and Global Mobility: Multihoming is mentioned as desirable. The global mobility type is not expected to be limited for any consideration other than administrative and security policies.

Scalability: NEMO support signaling and processing is expected to scale to a potentially large number of mobile networks. Thus draft extends the scalability of the NEMO basic protocol.

Thubert, Wakikawa & DevarExpires April 19, 2014

[Page 3]

There is a requirement from airplane companies which want to be at Home in the various airports that their planes visit. In fact, this is expressed in an abstract fashion by the case (1,n,1) of the NEMO multihoming issues [[RFC4980](#)] draft: "Single MR, Multiple HAs, Single NEMO-Prefix".

There is also a general direction that indicates that NEMO could be extended as a solution for VPN. To get there, we must ensure that NEMO is upscaled to the classical capabilities of VPN, including the global distribution of Points Of Presence. It is a classical feature for VPNs to allow the roaming users to connect to the closest point of presence into their company VPN. The same feature can not be provided with MIPv6 or NEMO, because the Home depends on a link that has a unique physical location.

## 2.2. Layer 3 operations

Mobile IPv6 [[RFC6275](#)] standarizes an interface between a Mobile Node and its Home Agent and its correspondents, as well as an interface between Home Agents. One angle of the MIPv6 operation is that the protocols hides the MN mobility by making as if the Mobile Node was always connected to a Home Link. The connectivity is maintained by Home Agents that are permanently and physically attached to that Home Link.

So the model for MIPv6 is Home Link centric and it is no surprise that it extends IPv6 Neighbor Discovery [[RFC4861](#)] for its operations, in particular for HAs to discover each others, and to discover when one of them has a binding for a Mobile Node, and which one. An immediate consequence of being Link centric is that Home can not be distributed at Layer 3, locally within a site or over the Internet.

the NEMO Basic Support [[RFC3963](#)] inherits the concept of Home Link and MIPv6 operations on that link, making NEMO partially a link layer operation. On the other hand, the NEMO Basic Support also operates as a routing protocol at L3, for example when it injects routes in the explicit prefix mode. So NEMO operations are somewhat half L2 and half L3.


What we are getting at with the HAHA protocol is placing NEMO fully at L3. This mostly means the replacement of all ND based exchanges by some equivalent, but at Layer 3, over the Internet Protocol. This also means the abstraction of the concept of Home Address into a globally unique router ID, as opposed to an address from a Home Link. So even if this paper trivially applies to Mobile IPv6, we place our descriptions in the context of NEMO, and use MRs where MIPv6 MNs

## 2.3. Route Optimization

MIPv6 comes with a Route Optimization scheme that enables a direct MR-CN conversation, bypassing the Home Agent. With the basic support, NEMO does not have such a support yet. In any case, RO comes at an additional cost in terms of protocol, which varies with the degree of expected trust.

Without Route optimization, all the packets MR-CN flow via the Home

Agent; this increases both the cost and the latency. The resulting path can be illustrated like this:



The routing overhead becomes costly when:

The distance  $||MR, CN||$  is much smaller than the sum of the distances  $||MR, HA|| + ||HA, CN||$ .

AND

$||MR, HA|| + ||HA, CN||$  is costly. If the 3 points are very close, the overhead is relatively important, but small in absolute terms.

In the picture above, say that a European phone (MR) is roaming in New Jersey but Homed in Brittany. And say that the phone owner places a call in New York city to CN1. Without RO, the voice packets flow back and forth over the peering lines between Brittany and the US, and the routing overhead causes an additional latency that decreases the perceived quality of the phone call.

On the other hand, calling CN2 would result in a small, acceptable overhead, considering that the distance  $||HA, CN2||$  is very small with regards to  $||MR, HA||$  or  $||MR, CN2||$ . Now, when the MR moves back to Brittany and places a new call to CN2, going via the HA might double the distance, but the whole thing being local, it is

The geographical distribution of Home generalizes this latter situation. If we can get rid of the concept of a Home Link that anchors the HA in a single location, then we can distribute HAs geographically, and, hopefully, one is close to our MR when it's roaming.

So if a MR can locate and bind with a closeby HA, then  $||MR, HA||$  is contained and the overhead is globally limited. In a same fashion, when a CN sends a packet to the MR, it finds a HA closeby and the overhead  $||HA, CN||$  is contained as well.

CN1 <-----+ +-----> CN2



all relies on HAHA communication over the PHYSICAL Home Link; so making that link virtual implies a single Home Agent. In turn this makes the HA a single point of failure, and disables the scalability that the DHAAD mechanism provides to MIPv6.

### 3. Rationale for the proposed solution

For the time being, the precise flows are not elaborated. One idea is that a protocol such as IS-IS or OSPFv3 could help a lot, mostly in the registration phase. Another is that HAs should be proactively preassigned to receive a given set of registration, in order to allow a certain degree of aggregation within sites and in between site. Finally, the concept of proxy is introduced to limit the number of primary sites (to 1?) and as a key element for an upcoming NEMO route optimization scheme, where routes can be exchanged in a trusted fashion between proxies.


### 4. A proxy for Mobile IP

The draft references extensively a MIP proxy HA function. The word proxy, here, is taken in a classical sense, like, for instance, a web proxy: a MIP proxy Home Agent acts as a HA for the MN and as a MN for the HA, the CN, and other proxies. In particular, the MIP proxy terminates the MR-HA tunnel and the associated encryption, extracts the packets, and reencapsulates them to the destination. This differs from a proxy-MIP function, which performs the Mobile Node operation on behalf of a non MIP-enabled node, in order to manage its mobility transparently.

Internet-Draft

Global-HAHA

October 2013







It is out of the scope of this document to discuss how the subnetting was decided and configured. It is also out of the scope of this document to describe the operations within a site where more than one HA is deployed. It is expected that in each primary site, HAs discover each other, mesh using tunnels, and form an area that owns the partition of Home that was assigned to that site.

### 5.1.1. External routing

Sites are expected to be connected locally to the internet, via the network of one or more service provider. Each site has a default route to the internet via that connection.

Internet-Draft

Global-HAHA

October 2013

```

-----
      . . . /
      ..... ..; .
-----
|      |      ..      / .....      |
| ::/0 -> ....      ;      ... <- ::/0
|      |
| =====HAHA=TUNNEL=====
|      |      .....      ;      .....      |
|      |      .<- Home::/16 / Home::/16 ->..      |
|      |
-----
      ...      ;      ...
      .....      /      ..
      .      ; .....      .....
      /      .....

```

In return, each site advertises a Home aggregation to the internet. The Home aggregation has a very short prefix which should be partitioned amongst a number of Service Providers and subnetted to serve as Distributed Home Networks for their customers. One could visualize this aggregation as a subway for Mobile Nodes.

[illegible]

```

| _____ | .      ;      ... | _____ |
|           | .      /      ... |           |
|           | ... ;.... .....
|           | /      .....

```

Thus, a site attracts the DHAAD requests from any MR that happens to be roaming close to the site, regardless of the MR primary site. So MRs bind to the closest site from their physical location. In a same fashion, CNs send all packets to LFNs via the closest Home site. But packets back flow directly from the site where the MR is bound.

#### 5.1.2. Internal routing

In each site, border HAs are elected to mesh with peers in other sites. Sites are interconnected over a mesh tunnels and private links. Routing between sites obeys the traditional rules of the Internet, using for instance an Exterior Gateway Protocol (like BGP) between different service providers, and an IGP within a Distributed Home Network.

Between sites of a given Distributed Home Network, it might be

Internet-Draft Global-HAHA October 2013  
preferable to form a fully meshed backbone, in order to limit the cost of routing and optimize the paths.

```

.....
-----
| site1 | ..... ; .... | Site2 |
|-----|
| Home:Site2::/48 ->      <- Home:Site1::/48 |
|-----HAHA-tunnel-----|
| @ @ @ | / . | @ @ |
| @ @ | <- Home::/16 ; Home::/16 -> | @ @ @ |
|-----|
|           | /      ...
|           | ... ..; .....
|           | /.....

```

It can be expected that, in order to scale, satellite sites would be deployed to take the proxy bindings but would not participate to the HAHA protocol that happens between the primary sites - at least when a proactive version of HAHA is being used.

```

.....
-----
| Sat1 | ..... ; .... | Site1 |
|-----|
| Home::/16 ->      <- Home:Site1:Sat1:/64 |
|-----proxyHAHA-tunnel-----|
| #### | / . | @ @ @ |
| #### | <- Home::/16 ; Home::/16 -> | @ @ |
|-----|
|           | /      ...
|           | ... ..; .....

```

/.....

In a satellite site, HAs are only proxy, never primary. Each proxy HA has at least one assigned parent HA, which belongs to a primary site. A tunnel is established between the proxy HA and the parent HA. The parent advertises the Home Aggregation to the proxy over that tunnel, as it does over the internet. In return, the proxy advertises its own prefixes, and redistributes the Home Aggregation over the internet. Finally, the parent redistributes the route to the proxy's network into its area, via itself, as an external route.

## 5.2. Binding

At that point, the primary sites are ready to accept bindings, either directly from Mobile Routers or via proxy HAs. This is the runtime phase for HAHA.

Internet-Draft

Global-HAHA

October 2013

A MR that is located close to its primary site will register there for its primary binding. In that case, the binding is direct. Otherwise, the MR will use a proxy in order to bind locally, and the proxy will perform the primary binding on behalf of the MR. If the proxy is parented at the primary site, the binding is local; otherwise, it is called a foreign binding.

### 5.2.1. Direct primary binding

When the primary HA accepts a direct binding from a MR, then it must let the other primaries know that it owns the binding for that Home Address, in a fashion that is discussed in [Section 10.2](#).

```
.....
...../.    ...  -----
...          ;    .. |                               Site1 |
..          / Home::/16 ->. | @--@--@ |
...          ;    .. | / |
....        /    MR ==MRHA=== @ <- Home:site1:MNP::/64 |
....          ;    |    .. | \ |
...        /    -----    ... | @--@ |
...          ;    MNP    | |
... / ..          ...  -----
```

The primary HA installs all (implicit and explicit) routes to the MR MNPs over the MRHA tunnel. It must also inject any required route, such as explicit prefix routes, into the primary area, as external routes via itself. All these routes are summarized at the area border and the other areas are not affected by the routing change.

### 5.2.2. local proxy binding

When a MR binds to a satellite site, a HA acts as a proxy and binds in turn with a primary site, on behalf of that MR, to create the primary binding. The proxy binding can only succeed if the primary


binding does. If the primary accepts the binding, then it returns a positive Binding Ack, with the list of the prefixes that are routed via the Mobile Router.



Then the proxy HA installs the routes that it got from the the positive Binding Acknowledgement over the proxy MRHA tunnel, and Acknowledges the proxy BU. Once a primary binding has succeeded, the proxy might establish secondary bindings with other sites.

### 5.2.3. Foreign proxy binding

When a MR binds to a foreign site, whether the site is primary or satellite, a HA from the site acts as a proxy as if the site was a satellite from the primary.



### 5.3. Route Optimizations


When the MR binds in a foreign location, the transport between an arbitrary correspondent and the MR within the HAHA network might be far from optimized.

As a result of the primary binding, a proxyHAHA tunnel is established between the proxy and the primary HA. That tunnel is itself encapsulated in the HAHA tunnels when packets flow over the internet.

Internet-Draft

Global-HAHA

October 2013



Also, packets from an arbitrary correspondent reach the site that is closest to the correspondent, then forwarded to the primary site for the destination. Within the primary site, they are encapsulated towards the proxy and sent across the HAHA network again. Finally they reach the proxy that decapsulates the packets and encapsulates them back.

In order to improve this, various possibilities are offered:


#### [5.3.1.](#) Leaking MNP routes in the HAHA network

The proxy can establish a secondary binding with its parent. In return, the parent redistributes an external route to the MNP via itself, and leaks that route inside the whole HAHA network.

Internet-Draft

Global-HAHA

October 2013




This bypasses the primary home agent for packet forwarding. Note that the packets still flow within the HAHA network between the ingress site close to the correspondent and the egress (satellite) site.

Note also that when the proxy HA binds to either its parent or the primary HA, it uses an address from within the HABA network (its HABA Address), as CareOf.

### 5.3.2. On-demand proxy routes

The proxy can establish a secondary binding with the correspondent's proxy provided there's such a node. It might be envisioned to adapt NHRP [[RFC2735](#)] for IPv6 in order to discover the remote tunnel end point.



An example of application is when two proxies from a same Home establish a cross binding. In fact, the Mobile Routers are unaware of the Route Optimization that takes place. This feature might be desirable when the privacy of the location is an issue for the service provider.

As part of the secondary binding to the ingress proxy, the egress proxy passes all the MNPs for the MR. This can be done using HAHA signalling, as explicit prefix routes. It is expected that the proxies belong to a chain of trust that links the primary and the satellite sites together. This, the ingress proxy trusts the egress proxy both for the binding and for the explicit prefixes.

The routes are literally projected from a proxy to the other while unseen by node in between; this is why this model is called Route Projection, by opposition with the traditional model of route injection which impacts the nodes on the way and is problematic with mobility.

Note that in that case, the binding uses the proxy's external address as careof. The packets are thus routed straight between the proxies, outside of the HAHA network.

## 6. Terminology and concepts

Most of the mobility related terms used in this document are defined in the Mobility Related Terminology document [[RFC3753](#)] and in the Mobile IPv6 specification [[RFC6275](#)].

Additionally, some terms were created or extended for NEMO. These specific terms are defined in the NEMO Terminology document [[RFC4885](#)].

This draft introduces the following definitions:

**Distributed Home Network:** In distributed home network, a global Home is advertised by several sites that are geographically distributed and meshed using tunnels in a VPN fashion. Mobile Nodes locate the closest site using DHAAD and bind there. More in [Section 7...](#)

**Partitioned Home Network:** A Partitioned Home is a specific deployment of a Distributed Home Network where each location owns a subnet of Home. The local Home Agents accept registration for the local partition. The local HAs also act as NEMO proxy HAs for the rest of Home.

**Primary Home Agent:** A Home Agent that can serve a Binding Update from a Mobile Router. The Mobile Router is always associated with a (set of) primary Home Agent (s) to register its binding.

**Proxy Home Agent:** This is a form of proxy, for the NEMO protocol. A proxy HA acts as a HA for MRs to register, but needs to register to a primary HA in order to accept the binding.

**Primary site:** A site is primary for a MR if at least one local HA on that site can accept a registration for that MR. When Home is not partitioned and sites overlap, primary HAs for a same subnet have to be aware of each other in order to find if a binding already exists in one of the sites and in which Home Agent.

**satellite site:** A site that is not primary for any binding. It is dependent on a parent primary site for HAHA operations. satellite sites are deployed around central primary sites, and one final goal for HAHA is to dynamically draw routes between satellite sites in order to shortcut the backbone of primary HAs.

**Secondary site:** A site is secondary for a MR if it is primary for other MRs but not that one. HAs in a secondary site can act as proxies for that MR, and the site is its own parent.

**Primary Binding:** A Binding is primary if it happens with a primary Home Agent, whether the client is a MR or a proxy HA.

**Secondary Binding:** A Binding is secondary if it happens between a proxy and a non primary Home Agent. It is used to improve the path between sites towards the HA where a MR is registered.


**Proxy Binding:** A Binding is proxy if it happens between a MR and a proxy HA, whether the proxy is a pure proxy HA or a secondary HA acting as proxy for that MR. The proxy HA relays the proxy binding to a primary HA in a primary binding. It may maintain a set of secondary bindings, depending on the deployment.

**Direct Binding:** A Binding that does not pass via a proxy, straight between the MR and its Home Agent.



## 7. Distributed Home Network

This section describes a detailed example how multiple Home Agents are configured in different routing domains. You are encouraged to read the nemo basic Home Network Models [\[RFC4887\]](#) draft before going through this section.



In distributed home network, a global Home is advertised by several sites that are geographically distributed and meshed using tunnels in a VPN fashion. Mobile Nodes locate the closest site using DHAAD against the global Home Network and bind there. Some form of inter-site synchronization (e.g. a routing protocol), which Mobile IPv6 and Nemo Basic Support do not provide, must take place in order to allow packets to be routed between the incoming site to the Mobile Node. The HAHA (Home Agent to Home Agent) protocol is being designed for that purpose.

In one model, called the Partitioned Home Network each site is responsible for a subnet of Home. When a Mobile Node roams far from its natural (primary) site, it registers to a Home Agent on a remote site, that takes the registration and notifies at least the natural site of the foreign registration.

One specific advantage of not relying on a Home Link for HAHA communication is that for a large configuration, the Home Agents can be organized hierarchically and distributed geographically, as a set of local clusters linked together to form a global Home Network.

## 8. Message Formats

Thubert, Wakikawa &amp; DevarExpires April 19, 2014

[Page 18]

drafts suggest to use the messages and formats detailed in the HAHA specification [I-D.wakikawa-mip6-nemo-haha-spec].

## 9. Mobile Router Operation

### 9.1. Locating Home

### 9.2. Proxy MIP client

## 10. Home Agent Operation

### 10.1. Locating the other HAs that serve the same Home

### 10.2. Locating the HA that owns the binding for a HoA

At the time of processing a binding update, a Home Agent (be it primary or simply proxy for the binding Home Address) needs to discover if the binding already exists with a primary Home Agent. There are at least 3 approaches that might be deployed for that purpose:

Reactive: This method is also referred to as 'on-demand'. In case of a binding cache miss, a primary Home Agent floods a Binding Information Request message to all the other primary Home Agents for the home address that is sought for. The reactive approach can be used between a satellite site and its parent site even when the primary HAs use an other method in the backbone.

Proactive: The binding information is shared proactively between the primary Home Agents for the existing bindings. All primary HAs know at any point of time which Home Addresses are bound and with which primary Home Agent. This approach is preferred for stable configurations, for instance if NEMO is used as a tool to simplify the configuration and reconfiguration of mostly stable networks.

Predictive: Ranges of Home Addresses and prefixes are preassigned to the Home Agents, following a rule that is shared or commonly computed by all HAs. A partitioned Home Network is an example of that, but this is mostly useful within a site between local Home Agents.

## 11. Acknowledgements

The authors wish to thank:

## 12. IANA considerations

This document does not require any IANA action.

## 13. Security Considerations

Thubert, Wakikawa & DevarExpires April 19, 2014

[Page 19]

---

Internet-Draft

Global-HAHA

October 2013

This document explores how to use the haha protocol but does not standardize any new operation that would be harmful.

## 14. References

### 14.1. informative reference

[RFC3753] Manner, J. and M. Kojo, "Mobility Related Terminology", [RFC 3753](#), June 2004.

[RFC4885] Ernst, T. and H-Y. Lach, "Network Mobility Support Terminology", [RFC 4885](#), July 2007.

[RFC4886] Ernst, T., "Network Mobility Support Goals and Requirements", [RFC 4886](#), July 2007.

[RFC4887] Thubert, P., Wakikawa, R. and V. Devarapalli, "Network

- Mobility Home Network Models", [RFC 4887](#), July 2007.
- [[RFC4980](#)] Ng, C., Ernst, T., Paik, E. and M. Bagnulo, "Analysis of Multihoming in Network Mobility Support", [RFC 4980](#), October 2007.

#### 14.2. normative reference

- [[RFC2735](#)] Fox, B.A. and B. Petri, "NHRP Support for Virtual Private Networks", [RFC 2735](#), December 1999.
- [[RFC3963](#)] Devarapalli, V., Wakikawa, R., Petrescu, A. and P. Thubert, "Network Mobility (NEMO) Basic Support Protocol", [RFC 3963](#), January 2005.
- [[RFC4861](#)] Narten, T., Nordmark, E., Simpson, W. and H. Soliman, "Neighbor Discovery for IP version 6 (IPv6)", [RFC 4861](#), September 2007.
- [[RFC5213](#)] Gundavelli, S., Leung, K., Devarapalli, V., Chowdhury, K. and B. Patil, "Proxy Mobile IPv6", [RFC 5213](#), August 2008.
- [[RFC6275](#)] Perkins, C., Johnson, D. and J. Arkko, "Mobility Support in IPv6", [RFC 6275](#), July 2011.
- [[RFC6830](#)] Farinacci, D., Fuller, V., Meyer, D. and D. Lewis, "The Locator/ID Separation Protocol (LISP)", [RFC 6830](#), January 2013.

Authors' Addresses

Thubert, Wakikawa & DevarExpires April 19, 2014

[Page 20]

---

Internet-Draft

Global-HAHA

October 2013

Pascal Thubert, editor  
Cisco Systems, Inc  
Building D  
45 Allee des Ormes - BP1200  
MOUGINS - Sophia Antipolis, 06254  
FRANCE

Phone: +33 497 23 26 34  
Email: pthubert@cisco.com  
Ryuji Wakikawa  
Softbank Mobile  
1-9-1, Higashi-Shimbashi, Minato-Ku  
Tokyo, 06254105-7322  
Japan

Email: ryuji.wakikawa@gmail.com  
Vijay Devarapalli  
WiChorus  
3590 North First St  
San Jose, CA, 95134  
USA

Email: vijay@wichorus.com

