TSGWG J. Touch
Internet Draft USC/ISI

Intended status: Best Current Practice

Expires: September 2017

# Resolving Multiple Time Scales in the Internet draft-touch-time-00.txt

Status of this Memo

This Internet-Draft is submitted in full conformance with the provisions of  $\underline{\mathsf{BCP}}$  78 and  $\underline{\mathsf{BCP}}$  79. This document may not be modified, and derivative works of it may not be created, and it may not be published except as an Internet-Draft.

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF), its areas, and its working groups. Note that other groups may also distribute working documents as Internet-Drafts.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

The list of current Internet-Drafts can be accessed at <a href="http://www.ietf.org/ietf/lid-abstracts.txt">http://www.ietf.org/ietf/lid-abstracts.txt</a>

The list of Internet-Draft Shadow Directories can be accessed at <a href="http://www.ietf.org/shadow.html">http://www.ietf.org/shadow.html</a>

This Internet-Draft will expire on September 27, 2017.

# Copyright Notice

Copyright (c) 2017 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to <u>BCP 78</u> and the IETF Trust's Legal Provisions Relating to IETF Documents (<a href="http://trustee.ietf.org/license-info">http://trustee.ietf.org/license-info</a>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document.

March 27, 2017

#### Abstract

Internet systems use a variety of time scales, which can complicate time comparisons and calculations. This document explains these various ways of indicating time and explains how they can be used together safely. This document is intended as a companion to Internet time as discussed in RFC 3339.

## Table of Contents

<u>1</u> .	Introduction $\underline{2}$
<u>2</u> .	Conventions used in this document $\underline{3}$
<u>3</u> .	Terminology <u>3</u>
<u>4</u> .	Background <u>4</u>
	$\underline{4.1}$ . Time uses and properties $\underline{5}$
	<u>4.2</u> . Time scales <u>5</u>
	$\underline{4.3}$ . Comparison of properties
<u>5</u> .	Computing time
	<u>5.1</u> . Conversion <u>8</u>
	<u>5.1.1</u> . Continuous and uniform <u>8</u>
	<u>5.1.2</u> . Uniform but not continuous <u>9</u>
	<u>5.1.3</u> . Not uniform <u>9</u>
	<u>5.1.4</u> . Ordering <u>10</u>
	<u>5.2</u> . Calculating intervals <u>11</u>
<u>6</u> .	Advice
	<u>6.1</u> . Selection advice <u>12</u>
	<u>6.2</u> . Hazards <u>12</u>
<u>7</u> .	Security Considerations $\underline{13}$
<u>8</u> .	
<u>9</u> .	References <u>13</u>
	<u>9.1</u> . Normative References <u>13</u>
	<u>9.2</u> . Informative References <u>13</u>
<u>10</u>	. Acknowledgments <u>15</u>

# 1. Introduction

A popular proverb reads, "a person with one clock always knows what time it is; a person with two clocks is never sure." Unfortunately, Internet systems rely on a variety of time references that often need to be reconciled. This document attempts to explain this issue and provide advice on how to avoid temporal ambiguity.

The Internet has a standard for expressing time [RFC3339]. This document explains the complexities of using any single such time scale and describes how to safely apply any one time scale and to accommodate concurrent use of different time scales.

## 2. Conventions used in this document

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in RFC 2119 [RFC2119].

In this document, these words will appear with that interpretation only when in ALL CAPS. Lowercase uses of these words are not to be interpreted as carrying significance described in RFC 2119.

# Terminology

- o Instant: a specific moment in time.
- o Time scale: a method of indicating intervals and dates, defined by a unit of time and an epoch.
- o Interval: the elapsed time between instants.
- o Date: an instant indicated in a time scale as an interval from an epoch; dates are accurate only for non-negative intervals.
- o Unit of time: an interval for indicating dates in a time scale.
- o Epoch: a reference point for indicating dates in a time scale.
- o Clock: a mechanism indicating the current date in a time scale.
- o Solar day: a unit of time defined as the interval of one rotation of the earth as measured between the repeated position of the sun in the sky as viewed from a fixed location, typically indicated as a mean over a year (one orbit of the earth around the sun). A given solar day can vary by as much as 30 seconds vs. the mean.
- o Tropical year: a unit of time defined by the interval of one rotation of the earth around the sun as measured using the position of the sun in the sky in the same way as a solar day.
- o Second: the unit of time, which has multiple definitions whose values differ:
  - o Exactly 1/(24 \* 60 \* 60) of a solar day.
  - o Exactly 1/(31,556,925.9747) of a tropical year.
  - o A basic SI unit, measured from specific radiation of a cesium 133 atom at rest, at mean sea level, at a temperature of OK.

- o Leap seconds or days: a unit of time added or subtracted from a date or clock to allow time scales with different interval units to have the same value at the same instant.
- o Offset: an interval added or subtracted from a date or clock to convert between time scales with different epochs and leap seconds.
- o Local time: a variation of a time scale intended to approximate that time scale at a given geographic location relative to that time scale at a reference geographic location, indicated as an offset.
- o Time zone: an offset defined within a geographic region, used to compute local time.

# 4. Background

There are a variety of types of time scales in widespread use for scientific, civil, and computational purposes. Scientific time is based on the International System (SI) standard definition of a second based on atomic clocks, and its goal is to provide a uniform standard for the passage of time. Civil time is based on the rotation of the earth, and its goal is to ensure that a single geographic location has the same reference to the sun at the same time each day, including variations that support localized time to approximate that effect for other locations around the earth. Computational time is an approximation of civil time that is intended to be inexpensive for computers to maintain without external information.

Each of these time scales has different properties. Scientific time is intended to be continuous and uniform, so that one second of elapsed time always has the effect of moving a scientific clock forward one second. Civil time can be non-continuous, such as when leap seconds or leap days are added to compensate for the difference between elapsed time and the rotation of the earth relative to the sun. Computational time can be non-uniform, such as when Unix system clocks are sped up to synchronize with civil time in a way intended to avoid discontinuity.

Each of these types of time scales also has different primary uses. Scientific time ensures uniform comparison of elapsed time and event ordering. Civil time is used by people and their governments. Computational time is used by computers to approximate other time systems. Time represented in each of these systems can be converted to other representations, given sufficient additional information.

Time is used throughout the Internet, to govern protocols (e.g., timers in TCP [RFC793]), to improve efficiency (e.g., TCP RTT estimation using timestamps [RFC7323]), as well as to indicate a correlation with civilian time (e.g., NTP [RFC5905] and calendars [RFC5545]). Each of these types of uses has distinct requirements on the kind of time used.

## **4.1**. Time uses and properties

Protocols use time for three primary purposes:

- o Ordering: to determine the relative sequence of events across systems, such as with Lamport clocks [La78].
- o Determining intervals: to determine actions to occur in a protocol in the absence of user requests and received messages (e.g., timers in TCP [RFC793]), to interact with physical systems (e.g., generating symbols at a given rate on a link), or to determine performance.
- o Interacting with people: to exchange dates with the real world, as when indicating the civil date of an email transmission [RFC3339], web page [IS098], or managing calendars [RFC5545].

Each of these uses mandates a key property. Ordering requires that a time reference is monotonic and increasing, such that the time reference values change between any two events whose order needs to be established. Accurate interval calculation requires that a time reference also be continuous and uniform, such that the calculated differences between any two dates separated by the same interval yield the same value. Interacting with people requires the use of a time reference they already use, so that expressed dates have known meaning.

These properties are not all supported by the variety of time references in widespread use. Some insert leap seconds and leap days, introducing discontinuities. Some vary their basic interval unit (e.g., to accommodate astronomical variances), which undermines their uniformity. These issues affect the choice of time reference and conversion between time references.

## 4.2. Time scales

The following is a description of the time scales in widespread use:

- o TAI (International Atomic Time) [BI06]: a time scale based on the weighted average of SI seconds as measured by a set of atomic clocks operated by national laboratories throughout the world.
- o UT (Universal Time) [Mc09]: a time scale based on the solar day using zero degrees longitude as the earth location and a specific astronomical location (originally the sun, but now more distant objects). UT has several variants:
  - o UTO: uncorrected solar date (rarely used).
  - o UT1: UT0 corrected for earth axis variation (widely used)
  - o UT1R: UT1 corrected for tidal variations (rarely used).
  - o UT2: UT1 corrected for seasonal variations (rarely used).
- o UTC (Coordinated Universal Time) [ITU02]: an approximation of UT1 based on TAI corrected with leap seconds.
- o DUT1 [ $\underline{\text{IERS}}$ ]: the number of leap seconds between the current TAI date and the UTC epoch.
- o GPS [<u>Ha01</u>]: the US Global Positioning System, defined as TAI + 19 SI seconds.
- o GLONASS [R198]: Russia's satellite clock system, defined as UTC.
- o BeiDou-2 (prev. COMPASS) [NAE12]: China's satellite clock system
- o Galileo [Ga17]: the European Union's satellite clock system
- o NTP [RFC5905]: the Network Time Protocol, used in the Internet to synchronize local clocks, in which dates are indicated by UTC values.
- o Unix [OGO8]: the POSIX/IEEE standard for Unix-based operating system software, in which dates are indicated as the number of seconds that have elapsed since UTC 1970-1-1 00:00:00, increased by exactly 86,400 seconds per day (note that 'day' is not defined).

## 4.3. Comparison of properties

Time scales can be compared using the following properties, in addition to their epoch and the interval used as their unit of time:

- o delta to TAI (d-TAI): how closely do dates in this time scale match TAI, excepting known offsets (to account for different epochs or leap seconds).
- o Continuous (Cont): are dates in this time scale continuous, i.e., so that intervals can be calculated directly from the difference in dates.
- o Uniform (Unif): are dates in this time scale uniform, i.e., so that all intervals of the same size represent the same amount of time.

The table in Figure 1 describes the time scales considered herein. All time scales use fixed epoch values except GLONASS, which reports dates relative to the current UTC. UT1 can drift in comparison to TAI by up to 0.9s, at which point a leap second is added. The satellite systems (GPS, BaiDou-2, GLONASS, and Galileo) attempt to track TAI, each with particular variances as design goals. NTP varies from TAI because of network latency variations, except where smearing is used [Go17]. Unix clocks typically use quartz oscillators as clocks, which can drift from TAI by 1-2s/week unless continuously corrected, e.g., by NTP over the network.

Time scale Epoch Unit d-TAI Cont Unif \_\_\_\_\_ 1977-01-01 TAI SI Yes Yes UT1 1582-10-15 solar 0.9s Yes No UTC 1582-10-15 SI \_ No Yes GPS 1980-01-06 SI 25ns\* Yes Yes 100ns\* BaiDou-2 2006-01-01 SI Yes Yes GLONASS UTC SI 1ms\* No Yes Galilelo 1999-08-22 SI 50ns\* Yes Yes NTP(1) 1582-10-15 SI 100ms No Yes NTP(2) 1582-10-15 SI 1.1s Yes No Unix 1970-01-01 solar ~100s Yes No

Figure 1 Time scale properties

- (1) As specified [RFC5905]
- (2) Some servers, notably Google's, 'smear' leap seconds [GO17]
- \* TAI comparisons from [Sa11]

TAI was designed to be both continuous and uniform. UT1 was designed to be both uniform and track the solar day. The difference is addressed in different ways in other time scales, which are largely derived from these two.

## 5. Computing time

The concurrent use of multiple time scales results in the need to coordinate clocks and convert dates, and can complicate ordering. Conversions require more context than just the time units and epochs. It is also useful to be able to calculate the interval between two dates within a single time scale. Each of these calculations can require context, some of which cannot be statically encoded. Ordering depends on monotonically increasing clocks, which some time scales do not support.

#### 5.1. Conversion

Dates in different time scales can be converted precisely as long as both time scales are uniform. When both time scales are also continuous, conversion is simple and relies only on the specification of the time scales. If either time scale is discontinuous, an additional table of discontinuities is required.

When either time scale is non-uniform, precise conversion is not defined unless the non-uniformity is also precisely indicated. The following subsections address each of these cases.

#### **5.1.1.** Continuous and uniform

For continuous and uniform time scales sharing the same unit of time, the difference in epoch is sufficient to convert one scale to the other, e.g.:

TS2\_date = TS1\_date - TS1\_epoch + TS2\_epoch

This conversion assumes both epochs are indicated in the same time scale (or can be converted to such - if not, no conversion is possible). For example, GPS reports the TAI date as an interval from January 6, 1980, whereas TAI reports the date as an interval from January 1, 1977, and both epochs are indicated in solar time. The difference between those two epochs is exactly 95,040,019 SI seconds, which is the total of 1,100 days of 86,400 SI seconds each and an additional 19 SI seconds, needed to align the epochs indicated as solar dates. As a result, dates indicated in year/month/day/second format need only have their seconds values adjusted as follows:

GPS\_date = TAI\_date + 19s

If time scales do not share the same unit of time, the conversion needs to account for the difference in the intervals from epoch. For

example, a solar day is composed of 'solar seconds', but approximately 86,400.002 SI seconds. Conversion now requires that the epochs and units are expressed in a common time scale, and can be computed as follows:

TS2\_date = (TS1\_date - TS1\_epoch)/TS1\_unit \* TS2\_unit + TS2\_epoch

Converting a common time frame to local time further requires knowing the location of each date and consulting a time zone database, which is also available online [tzdb] [RFC7808]. In this way, UTC can be converted to its local equivalent using a similar lookup operation (where TZDB is the time zone database):

UTC\_localdate = UTC\_date + TZDB[UTC\_date, local\_location]

#### 5.1.2. Uniform but not continuous

Changes in the rotation of the earth and its orbit around the sun cause variations in the difference between the unit of a second as defined by solar day, tropical year, and SI methods. These differences are corrected by introducing "leap seconds", which are added (or removed) on specific dates [IERS]. E.g., UTC adds or removes leap seconds (known as DUT1) to TAI on specific dates to help it approximate UT1.

Leap second dates can be approximated using a known calculation, but the exact date is determined administratively (rather than by calculation). Those dates are announced several months in advance and can be obtained online <a href="[tzdb]">[tzdb]</a>[RFC6557]</a>[RFC7808]. As a consequence, conversion accounting for leap seconds requires a lookup operation (where "leapDB" is a database that indicates the number of leap seconds added since the epoch):

UTC\_date = TAI\_date + leapDB[TAI\_date]

Between dates when leap second dates, precise differences in solar vs. SI time scales can be computed below 1s by accounting for the ratio between a solar second and an SI second, but this is rarely considered.

## 5.1.3. Not uniform

Some time scales are not uniform, i.e., the duration of an interval is indicated in units that vary and so are not easily directly comparable. Solar days vary by as much as 50 SI seconds because of the eccentricity of the earth's orbit and wobble around its axis of rotation. Because a solar day is defined as a fixed number of

(solar) seconds, one solar second varies by as much as 0.06%. This variability is not simple to compute, but can be averaged out over long periods, but only in hindsight. Similarly, the earth's orbit around the sun varies and is slowing over time, resulting in an increasing stretching of a solar second.

Some time scales replace discrete leap seconds with a leap smear, stretching the interval of one second over 10-20 hours before the corresponding leap second date [Go17]. This allows a time scale to avoid discontinuities and non-conventional interval values (e.g., minutes with 59 or 61 seconds). Smearing causes non-uniformity of intervals that span the smear, especially because there is no current standard for the smear interval or algorithm.

Additionally, some time scales have no precise conversion, e.g., GPS is coordinated to within 25ns of TAI, but there is no information on the exact difference. This occurs because GPS uses its own set of atomic clocks rather than using the TAI directly, and the same is true for other satellite systems. Other time scales are imprecise by definition, as with Unix time, which is based on clocks that vary widely by instance and with changes in temperature.

#### **5.1.4.** Ordering

Events in a distributed system often require ordering to ensure consistent views of their aggregate state [La78]. It can be important to know whether a bank deposit occurs before a withdrawal or if a license application has been submitted before a deadline.

Time scales that are continuous enable easy ordering of dates, e.g., all dates comparisons correctly either indicate concurrence (when dates match) or a specific order. Time scales that are discontinuous can give false results, such as during a leap second. Consider the UTC date encodings indicated in Figure 2.

In	stant	TAI date	UTC encoding (61s minute)
Α		2016-01-01T00:00:34.0	2016-12-31T23:59:59.0
В		2016-01-01T00:00:34.5	2016-12-31T23:59:59.5
С		2016-01-01T00:00:35.0	2016-12-31T23:59:60.0
D		2016-01-01T00:00:35.5	2016-12-31T23:59:60.5
Ε		2016-01-01T00:00:36.0	2016-01-01T00:00:00.0

Figure 2 Leap seconds with long minutes

In both cases, two SI seconds progress between instants A and E. However, the last minute before midnight on December 31, 2016 has a

minute that lasts 61 seconds (0..61), rather than 60. Ordering of these instants is unambiguous in this example.

Consider instead a system that cannot represent minutes with more than 60 seconds. In such systems, the clock is either stalled or delayed during a leap second insertion, resulting in repeated values (Figure 3). Here, the order of instants B, C, and D cannot be established accurately from the dates. Additionally, intervals that span this "reset" are inaccurately calculated from date differences unless explicitly corrected.

Instant	TAI date	UTC encoding (60s minute)
Α	2016-01-01T00:00:34.0	2016-12-31T23:59:59.0
В	2016-01-01T00:00:34.5	2016-12-31T23:59:59.5
С	2016-01-01T00:00:35.0	2016-12-31T23:59:59.0
D	2016-01-01T00:00:35.5	2016-12-31T23:59:59.5
E	2016-01-01T00:00:36.0	2016-01-01T00:00:00.0

Figure 3 Leap seconds with repeating dates

Ordering can be restored using leap smear, as shown in Figure 4, but at the expense of complicating the computation of intervals that span the smear.

Instant	TAI date	UTC encoding (60s minute)
Α	2016-01-01T00:00:34.0	2016-12-31T23:59:59.0
В	2016-01-01T00:00:34.5	2016-12-31T23:59:59.25
С	2016-01-01T00:00:35.0	2016-12-31T23:59:59.5
D	2016-01-01T00:00:35.5	2016-12-31T23:59:59.75
E	2016-01-01T00:00:36.0	2016-01-01T00:00:00.0

Figure 4 Leap seconds with smear

## **5.2.** Calculating intervals

Intervals can be calculated directly between two dates of a uniform time scale directly as the difference between two dates A and B as follows (where "abs" is the absolute value function):

```
interval = abs(dateA - dateB)
```

A non-continuous time scale requires external information, e.g., the leap second dates that occur during the interval. Computing intervals in these time scales requires that the representation does not repeat or smear time. The interval is computed by converting

non-continuous time to continuous time by removing the effect of leap seconds and proceeding as with the continuous case, as follows:

```
interval = abs((dateA - leapDB(dateA)) - (dateB - leapDB(dateB)))
```

Non-uniform time scale intervals can sometimes be calculated, but this is rarely supported.

#### 6. Advice

No single time scale serves all purposes. Use of multiple time scales requires conversion, which often requires external information. Maintaining accurate clocks can also require external information (to insert leap seconds), as can the computation of intervals.

#### 6.1. Selection advice

A primary time scale SHOULD be chosen from among existing time scales, if possible. Creating a new time scale increases complexity and is unlikely to avoid the issues already present with existing time scales, e.g., being continuous, uniform, requiring conversion, or needing external information for conversion or interval computation.

A primary time scale SHOULD be chosen to minimize the need for repeated conversion and/or to minimize the complexity of computing intervals, depending on the expected frequency of these operations.

For example, if synchronizing clocks with other systems using NTP is the primary goal, implementers would probably select UTC [RFC5905]. If user presentation is primary, as for email or calendaring, implementers would probably select local time [RFC5545]. If interval computation is primary, implementers would probably select TAI.

As a consequence, in most cases, implementers SHOULD select either TAI or UTC, or a system that closely approximates these (e.g., GPS-like systems or NTP), and expect to maintain updated leap second information [RFC7808].

## 6.2. Hazards

Incorrect time scale selection can result in increased computational overhead and the need for increased storage. External information might be needed for conversion, or conversion or calculation may not be possible (as with smearing).

Implementers SHOULD NOT use time scales that smear, for two reasons. First, there is no current standard for leap smearing, so the same time scale implemented on different systems are likely to indicate incorrect relative dates (i.e., incorrectly indicating instance ordering). Second, leap smearing complicates interval measurements computed over the smear which can be difficult to compensate.

## Security Considerations

Time is used within security systems for a variety of reasons, including indicating the validity of certificates used for encryption and authentication [RFC5280]. Inaccurate dates, intervals, or ordering can affect the ability to use these protocols.

As a result, it can be important to secure the protocols used to coordinate time [RFC7384]. NTP, the most common such protocol, supports secure operation [RFC5905].

#### 8. IANA Considerations

This document has no IANA considerations. This section should be removed prior to publication as an RFC.

#### 9. References

#### 9.1. Normative References

[RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", <u>BCP 14</u>, <u>RFC 2119</u>, March 1997.

## 9.2. Informative References

- [BI06] Bureau International des Poids et Mesures (International Bureau of Weights and Measures), "The International System of Units (SI)," 8th Edition, 2006.
- [Ga17] Galileo system web pages, <a href="http://galileognss.eu/gst-galileo-system-time/">http://galileognss.eu/gst-galileo-system-time/</a>
- [Go17] Google's approach to NTP leap smearing, proposed in 2017. https://developers.google.com/time/smear
- [Ha01] Hoffman-Wellenhof, B., H. Lichtenegger, J. Collins. Global positioning system: theory and practice. New York, Springer-Verlag, 2001.

- [IERS] International Earth Rotation and Reference Systems Service
   (IERS). https://www.iers.org/
- [IS098] International Standards Organization, "Data elements and interchange formats - Information interchange -Representation of dates and times", ISO 8601, 1988.
- [ITU02] International Telecommunication Union, "Standard-frequency and time-signal emissions," ITU-R Recommendations and Reports, TF.460-6, 2002.
- [La78] Lamport, L., "Time, Clocks, and the Ordering of Events in a Distributed System," Communications of the ACM, V21 N7, Jul. 1978, pp. 558-565.
- [McO9] McCarthy, D., P. Seidelmann, "Time Applications," in Time
   From Earth Rotation to Atomic Physics, Wiley-VCH, 2009.
  doi: 10.1002/9783527627943.ch19
- [NAE12] National Academy of Engineering, "Global Navigation Satellite Systems," National Academies Press, ISBN 978-0-309-22275-4, 2012.
- [OG08] The Open Group, "Base Specifications, Issue 7, 2016 Edition," IEEE Std 1003.1 / POSIX.1-2008, 2008.
- [RFC3339] Klyne, G., C. Newman, "Date and Time on the Internet: Timestamps," RFC 3339, July 2002.
- [RFC5280] Cooper, D., S. Santesson, S. Farrell, S. Boeyen, R. Housley, W. Polk, "Internet X.509 Public Key Infrastructure Certificate and Certificate Revocation List (CRL) Profile," RFC 5280, May 2008.
- [RFC5545] Desruisseaux, B. (Ed.), "Internet Calendaring and Scheduling Core Object Specification (iCalendar)," RFC 5545, Sep. 2009.
- [RFC5905] Mills, D., J. Martin (Ed.), J. Burbank, W. Kasch, "Network Time Protocol Version 4: Protocol and Algorithms Specification," RFC 5905, June 2010.
- [RFC6557] Lear, E., P. Eggert, "Procedures for Maintaining the Time Zone Database," <u>RFC 6557</u>, <u>BCP 175</u>, Feb. 2012.

- [RFC7323] Borman, D., R. Braden, V. Jacobson, R. Scheffenegger (Ed.), "TCP Extensions for High Performance," RFC 7323, Sep. 2014.
- [RFC7384] Mizrahi, T., "Security Requirements of Time Protocols in Packet Switched Networks," RFC 7384, Oct. 2014.
- [RFC7808] Douglass, M., C. Daboo, "Time Zone Data Distribution Service," <u>RFC 7808</u>, Mar. 2016.
- Russian Institute of Space Device Engineering, "GLONASS [RI98] Interface Control Document", 1998.
- [Sa11] Sanz Subirana, J., J. Juan Zornoza, M. Hernandez-Pajares, "Time References in GNSS," Navipedia web pages, 2011. http://www.navipedia.net/index.php/Time\_References\_in\_GNSS
- [tzdb] Time zone database, <a href="https://www.iana.org/time-zones">https://www.iana.org/time-zones</a>

# 10. Acknowledgments

This work originated in response to a proposal for a new continuous time scale by Phillip Hallam-Baker, and benefitted from discussion on the IETF list, notably with Tony Finch, Nicholas Mailhot, and Michael Thornburgh.

This work is partly supported by USC/ISI's Postel Center.

This document was prepared using 2-Word-v2.0.template.dot.

# Authors' Addresses

Joe Touch USC/ISI 4676 Admiralty Way Marina del Rey, CA 90292 USA

Phone: +1 (310) 448-9151 Email: touch@isi.edu