UTA Internet-Draft Intended status: Informational Expires: September 6, 2018 H. Tschofenig Arm Limited T. Fossati Nokia March 05, 2018

TLS/DTLS 1.3 Profiles for the Internet of Things draft-tschofenig-uta-tls13-profile-00

Abstract

This document is a companion to $\frac{\text{RFC 7925}}{\text{profiles for Internet of Things devices.}}$

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of <u>BCP 78</u> and <u>BCP 79</u>.

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <u>http://datatracker.ietf.org/drafts/current/</u>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on September 6, 2018.

Copyright Notice

Copyright (c) 2018 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to <u>BCP 78</u> and the IETF Trust's Legal Provisions Relating to IETF Documents (<u>http://trustee.ietf.org/license-info</u>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License. This document may contain material from IETF Documents or IETF Contributions published or made publicly available before November 10, 2008. The person(s) controlling the copyright in some of this material may not have granted the IETF Trust the right to allow modifications of such material outside the IETF Standards Process. Without obtaining an adequate license from the person(s) controlling the copyright in such materials, this document may not be modified outside the IETF Standards Process, and derivative works of it may not be created outside the IETF Standards Process, except to format it for publication as an RFC or to translate it into languages other than English.

Table of Contents

<u>1</u> .	Introduction	<u>2</u>
<u>2</u> .	Conventions and Terminology	<u>3</u>
<u>3</u> .	Credential Types	<u>3</u>
<u>4</u> .	Error Handling	<u>3</u>
<u>5</u> .	Session Resumption	<u>4</u>
<u>6</u> .	Compression	<u>4</u>
<u>7</u> .	Perfect Forward Secrecy	<u>4</u>
<u>8</u> .	Кеер-Alive	<u>4</u>
<u>9</u> .	Timeouts	<u>4</u>
<u>10</u> .	Random Number Generation	<u>4</u>
<u>11</u> .	Server Name Indication (SNI)	<u>4</u>
<u>12</u> .	Maximum Fragment Length Negotiation	<u>4</u>
<u>13</u> .	Crypto Agility	<u>5</u>
<u>14</u> .	Key Length Recommendations	<u>5</u>
<u>15</u> .	0-RTT Data	<u>5</u>
<u>16</u> .	Security Considerations	<u>5</u>
<u>17</u> .	References	<u>5</u>
<u>1</u>	7.1. Normative References	<u>5</u>
<u>1</u>	7.2. Informative References	<u>6</u>
Appe	endix A. The Timestamp Option	<u>7</u>
Autl	hors' Addresses	7

1. Introduction

This document defines a profile of DTLS 1.3 [<u>I-D.ietf-tls-dtls13</u>] and TLS 1.3 [<u>I-D.ietf-tls-tls13</u>] that offers communication security services for IoT applications and is reasonably implementable on many constrained devices. Profile thereby means that available configuration options and protocol extensions are utilized to best support the IoT environment.

For IoT profiles using TLS/DTLS 1.2 please consult [RFC7925]. This document re-uses the communication pattern defined in RFC 7925 and

makes IoT-domain specific recommendations for version 1.3 (where necessary).

TLS 1.3 has been re-designed and several previously defined extensions are not applicable to the new version of TLS/DTLS anymore. This clean-up also simplifies this document. Furthermore, many outdated ciphersuites have been omitted from the TLS/DTLS 1.3 specification.

2. Conventions and Terminology

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "NOT RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in <u>RFC</u> 2119 [RFC2119].

<u>3</u>. Credential Types

In accordance with the recommendations in [<u>RFC7925</u>] a compliant implementation MUST implement TLS_AES_128_CCM_8_SHA256. It SHOULD implement TLS_CHACHA20_POLY1305_SHA256.

For use of a pre-shared secrets for authentication is now integrated into the main specification and does not rely on extensions, as it was the case with earlier versions. The support has also been aligned with the session resumption feature.

A compliant implementation supporting authentication based on certificates and raw public keys MUST support digital signatures with ecdsa_secp256r1_sha256. A compliant implementation MUST support the key exchange with secp256r1 (NIST P-256) and SHOULD support key exchange with X25519.

A plain PSK-based TLS/DTLS client or server MUST implement the following extensions: - supported_versions - cookie - server_name - pre_shared_key - psk_key_exchange_modes

For TLS/DTLS clients and servers implementing raw public keys and/or certificates the guidance for mandatory-to-implement extensions described in Section 9.2 of [<u>I-D.ietf-tls-tls13</u>] MUST be followed.

<u>4</u>. Error Handling

TLS 1.3 simplified the Alert protocol but the underlying challenge in an embedded context remains unchanged, namely what should an IoT device do when it encounters an error situation. The classical approach used in a desktop environment where the user is prompted is often not applicable with unattended devices. Hence, it is more important for a developer to find out from situation situation the device can recover from and what situations are hopeless.

5. Session Resumption

TLS 1.3 has built-in support for session resumption by utilizing PSKbased credentials established in an earlier exchange.

6. Compression

TLS 1.3 does not have support for compression.

7. Perfect Forward Secrecy

TLS 1.3 allows the use of PFS with all ciphersuites since the support for it is negotiated independently.

8. Keep-Alive

The discussion in <u>Section 10 of RFC 7925</u> is applicable.

9. Timeouts

The recommendation in <u>Section 11 of RFC 7925</u> is applicable. In particular this document RECOMMENDED to use an initial timer value of 9 seconds with exponential back off up to no less then 60 seconds.

<u>10</u>. Random Number Generation

The discussion in <u>Section 12 of RFC 7925</u> is applicable with one exception: the ClientHello and the ServerHello messages in TLS 1.3 do not contain gmt_unix_time component anymore.

<u>11</u>. Server Name Indication (SNI)

This specification mandates the implementation of the SNI extension.

<u>12</u>. Maximum Fragment Length Negotiation

The Maximum Fragment Length Negotiation (MFL) extension has been superseded by the Record Size Limit (RSL) extension [<u>I-D.ietf-tls-record-limit</u>]. Implementations in compliance with this specification MUST implement the RSL extension and SHOULD use it to indicate their RAM limitations.

<u>13</u>. Crypto Agility

The recommendations in <u>Section 19 of RFC 7925</u> are applicable.

<u>14</u>. Key Length Recommendations

The recommendations in <u>Section 20 of RFC 7925</u> are applicable.

15. 0-RTT Data

When clients and servers share a PSK, TLS/DTLS 1.3 allows clients to send data on the first flight ("early data"). This is a great performance improvement but requires application protocols to define its use with the 0-RTT data functionality.

For HTTP this functionality is described in [<u>I-D.ietf-httpbis-replay</u>]. This document specifies the application profile for CoAP.

For a given request, the level of tolerance to replay risk is specific to the resource it operates upon (and therefore only known to the origin server). In general, if processing a request does not have state-changing side effects, the consequences of replay are not significant. The server can choose whether it will process early data before the TLS handshake completes.

It is RECOMMENDED that origin servers allow resources to explicitly configure whether early data is appropriate in requests.

This specification defines a new CoAP option "timestamp", which allows the server to attach a timestamp to each CoAP message for the purpose of replay detection.

16. Security Considerations

This entire document is about security.

<u>17</u>. References

<u>17.1</u>. Normative References

[I-D.ietf-tls-dtls13]

Rescorla, E., Tschofenig, H., and N. Modadugu, "The Datagram Transport Layer Security (DTLS) Protocol Version 1.3", <u>draft-ietf-tls-dtls13-26</u> (work in progress), March 2018. [I-D.ietf-tls-record-limit] Thomson, M., "Record Size Limit Extension for Transport Layer Security (TLS)", draft-ietf-tls-record-limit-02 (work in progress), February 2018.

- [I-D.ietf-tls-tls13]
 Rescorla, E., "The Transport Layer Security (TLS) Protocol
 Version 1.3", draft-ietf-tls-tls13-26 (work in progress),
 March 2018.
- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", <u>BCP 14</u>, <u>RFC 2119</u>, DOI 10.17487/RFC2119, March 1997, <<u>https://www.rfc-</u> editor.org/info/rfc2119>.

<u>17.2</u>. Informative References

- [I-D.ietf-httpbis-replay] Thomson, M., Nottingham, M., and W. Tarreau, "Using Early Data in HTTP", <u>draft-ietf-httpbis-replay-02</u> (work in progress), November 2017.
- [RFC7925] Tschofenig, H., Ed. and T. Fossati, "Transport Layer Security (TLS) / Datagram Transport Layer Security (DTLS) Profiles for the Internet of Things", <u>RFC 7925</u>, DOI 10.17487/RFC7925, July 2016, <<u>https://www.rfc-</u> editor.org/info/rfc7925>.

<u>Appendix A</u>. The Timestamp Option

The Timestamp option encodes time in standard UNIX 32-bit format (seconds since the midnight starting Jan 1, 1970, UTC, ignoring leap seconds) according to the sender's internal clock.

+----+ | No. | C | U | N | R | Name | Format | Length | Default | E | +----+
TBD
|
|
Timestamp
|
opaque
4
|
(none)
|
x

> C=Critical, U=Unsafe, N=NoCacheKey, R=Repeatable, E=Encrypt and Integrity Protect (when using OSCORE)

> > Figure 1: Timestamp Option.

Authors' Addresses

Hannes Tschofenig Arm Limited

EMail: hannes.tschofenig@gmx.net

Thomas Fossati Nokia

EMail: thomas.fossati@nokia.com