

Network Working Group
Internet Draft
Updates: [1321](#), [2202](#) (once approved)
Intended Status: Informational
Expires: January 12, 2011

S. Turner
IECA
L. Chen
NIST
July 12, 2010

Updated Security Considerations for the
MD5 Message-Digest and the HMAC-MD5 Algorithms
draft-turner-md5-seccon-update-02.txt

Abstract

This document updates the security considerations for the MD5 message digest algorithm. It also updates the security considerations for HMAC-MD5.

Status of this Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#). This document may contain material from IETF Documents or IETF Contributions published or made publicly available before November 10, 2008.

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF), its areas, and its working groups. Note that other groups may also distribute working documents as Internet-Drafts.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

The list of current Internet-Drafts can be accessed at <http://www.ietf.org/ietf/1id-abstracts.txt>.

The list of Internet-Draft Shadow Directories can be accessed at <http://www.ietf.org/shadow.html>.

This Internet-Draft will expire on January 12, 2011.

Copyright Notice

Copyright (c) 2010 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

[1.](#) Introduction

MD5 [[MD5](#)] is a message digest algorithm that takes as input a message of arbitrary length and produces as output a 128-bit "fingerprint" or "message digest" of the input. The published attacks against MD5 show and that it is not prudent to use MD5 when collision resistance is required. This document replaces the security considerations in [RFC 1321](#) [[MD5](#)].

[HMAC] defined a mechanism for message authentication using cryptographic hash functions. Any message digest algorithm can be used, but the cryptographic strength of HMAC depends on the properties of the underlying hash function. [[HMAC-MD5](#)] defined test cases for HMAC-MD5. This document updates the security considerations in [[HMAC-MD5](#)].

[HASH-Attack] summarizes the use of hashes in many protocols and discusses how attacks against a message digest algorithm's one-way and collision-free properties affect and do not affect Internet protocols.

[2.](#) Security Considerations

MD5 was published in 1992 as an Informational RFC. Since that time, MD5 has been studied extensively. What follows are recent attacks against MD5's collisions, pre-image, and second pre-image resistance. Additionally, attacks against MD5 used in message authentication with a shared secret (i.e., HMAC-MD5) are discussed.

Some may find the guidance for key lengths and algorithm strengths in [[SP800-57](#)] and [[SP800-131](#)] useful.

[2.1.](#) Collision Resistance

Pseudo-collisions for the compress function of MD5 were first described in 1993 [[denBB01993](#)]. In 1996, [[DOB1995](#)] demonstrated a collision pair for the MD5 compression function with a chosen initial value. The first paper that demonstrated two collision pairs for

regular MD5 was published in 2004 [[WFLY2004](#)]. The detailed attack techniques for MD5 were published at EUROCRYPT 2005 [[WAYU2005](#)]. Since then, a lot of research results have been published to improve collision attacks on MD5. The attacks presented in [[KLIM2006](#)] can find MD5 collision in about one minute on a standard notebook PC (Intel Pentium, 1.6 GHz.). In [[STEV2007](#)], he claim that it takes 10 seconds or less on a 2.6Ghz Pentium4 to find collisions. In [[STEV2007](#)] [[SLdeW2007](#)] [[SSALMdeW2009](#)] [[SLdeW2009](#)], the collision attacks on MD5 were successfully applied to X.509 certificates.

Notice that the collision attack on MD5 can also be applied to password based challenge-and-response authentication protocols such as APOP protocol used in post office authentication as presented in [[LEUR2007](#)].

In fact, more delicate attacks on MD5 to improve the speed of finding collisions have published recently. However, the aforementioned results have provided sufficient reason to eliminate MD5 usage in applications where collision resistance is required such as digital signatures.

[2.2](#). Pre-image and Second Pre-image Resistance

Even though the best result can find a pre-image attack of MD5 faster than exhaustive search as presented in [[SAA02009](#)], the complexity $2^{123.4}$ is still pretty high.

[2.3](#). HMAC

The cryptanalysis of HMAC-MD5 usually conducted together with NMAC (Nested MAC) since they are closely related. NMAC uses two independent keys K_1 and K_2 such that $NMAC(K_1, K_2, M) = H(K_1, H(K_2, M))$, where K_1 and K_2 are used as secret IVs for hash functions $H(IV, M)$. If we re-write HMAC equation using two secret IVs such that $IV_2 = H(K \text{ Xor } \text{ipad})$ and $IV_1 = H(K \text{ Xor } \text{opad})$, then $HMAC(K, M) = NMAC(IV_1, IV_2, M)$. Here it is very important to notice that IV_1 and IV_2 are not independently selected.

The first analysis was explored on NMAC-MD5 using related keys in [COYI2006]. The partial key recovery attack cannot be extended to HMAC-MD5, since for HMAC, recovering partial secret IVs can hardly lead to recovering (partial) key K. Another paper presented at Crypto 2007 [FLN2007] extended results of [COYI2006] to a full key recovery attack on NMAC-MD5. Since it also uses related key attack, it does not seem applicable to HMAC-MD5.

A EUROCRYPT 2009 paper presented a distinguishing attack on HMAC-MD5 [WYWZZ2009] without using related keys. It can distinguish an

Turner & Chen

Expires January 12, 2011

[Page 3]

Internet-Draft MD5 and HMAC-MD5 Security Considerations

July 2010

instantiation of HMAC with MD5 from an instantiation with a random function with 2^{97} queries with probability 0.87. This is called distinguishing-H. Using the distinguishing attack, it can recover some bits of the intermediate status of the second block. However, as it is pointed in [WYWZZ2009], it cannot be used to recover the (partial) inner key $H(K \text{ Xor } \text{ipad})$. It is not obvious how the attack can be used to form a forgery attack either.

The attacks on HMAC-MD5 do not seem to indicate a practical vulnerability when used as a message authentication code. Considering that the distinguishing-H attack is different from distinguishing-R attack, which distinguishes an HMAC from a random function, the practical impact on HMAC usage as a PRF such as in a key derivation function is not well understood.

Therefore, it may not be urgent to remove HMAC-MD5 from the existing protocols. However, since MD5 must not be used for digital signatures, for a new protocol design, a ciphersuite with HMAC-MD5 should not be included. Options include HMAC-SHA256 [HMAC] [HMAC-SHA256] and [AES-CMAC] when AES is more readily available than a hash function.

[3.](#) IANA Considerations

None.

[4.](#) Acknowledgements

Obviously, we have to thank all the cryptographers who produced the results we refer to in this document. We'd also like to thank Martin Rex and Benne de Weger for their comments.

[5.](#) Normative References

- [AES-CMAC] Song, J., Poovendran, R., Lee., J., and T. Iwata, "The AES-CMAC Algorithm", [RFC 4493](#), June 2006.
- [COYI2006] S. Contini, Y.L. Yin. Forgery and partial key-recovery attacks on HMAC and NMAC using hash collisions. ASIACRYPT 2006. LNCS 4284, Springer, 2006.
- [denBB01993] den Boer, B. and A. Bosselaers, "Collisions for the compression function of MD5", Eurocrypt 1993.
- [DOB1995] Dobbertin, H., "Cryptanalysis of MD5 Compress", Eurocrypt 1996.

Turner & Chen

Expires January 12, 2011

[Page 4]

Internet-Draft MD5 and HMAC-MD5 Security Considerations

July 2010

- [FLN2007] Fouque, P.-A., Leurent, G., Nguyen, P.Q.: Full key-recovery attacks on HMAC/NMAC-MD4 and NMAC-MD5. CRYPTO 2007. LNCS, 4622, Springer, 2007.
- [HASH-Attack] Hoffman, P., and B. Schneier, "Attacks on Cryptographic Hashes in Internet Protocols", [RFC 4270](#), November 2005.
- [HMAC] Krawczyk, H., Bellare, M., and R. Canetti, "HMAC: Keyed-Hashing for Message Authentication", [RFC 2104](#), February 1997.
- [HMAC-MD5] Cheng, P., and R. Glenn, "Test Cases for HMAC-MD5 and HMAC-SHA-1", RC 2201, September 1997.
- [HMAC-SHA256] Nystrom, M., "Identifiers and Test Vectors for HMAC-SHA-224, HMAC-SHA-256, HMAC-SHA-384, and HMAC-SHA-512", [RFC 4231](#), December 2005.
- [KLIM2006] V. Klima. Tunnels in Hash Functions: MD5 Collisions within a Minute. Cryptology ePrint Archive, Report 2006/105 (2006), <http://eprint.iacr.org/2006/105>.
- [LEUR2007] G. Leurent, Message freedom in MD4 and MD5 collisions: Application to APOP. Proceedings of FSE 2007. Lecture Notes in Computer Science 4715. Springer 2007.

- [MD5] Rivest, R., "The MD5 Message-Digest Algorithm", [RFC 1321](#), April 1992.
- [SAA02009] Y. Sasaki and K. Aoki. Finding preimages in full MD5 faster than exhaustive search. Advances in Cryptology – EUROCRYPT 2009, LNCS 5479 of Lecture Notes in Computer Science, Springer, 2009.
- [SLdeW2007] Stevens, M., Lenstra, A., de Weger, B., Chosen-prefix Collisions for MD5 and Colliding X.509 Certificates for Different Identities. EuroCrypt 2007.
- [SLdeW2009] Stevens, M., Lenstra, A., de Weger, B., "Chosen-prefix Collisions for MD5 and Applications", Journal of Cryptology, 2009.
<http://deweger.xs4all.nl/papers/%5B42%5DStLedW-MD5-JCryp%5B2009%5D.pdf>.

Turner & Chen

Expires January 12, 2011

[Page 5]

Internet-Draft MD5 and HMAC-MD5 Security Considerations

July 2010

- [SSALM0deW2009] Stevens, M., Sotirov, A., Appelbaum, J., Lenstra, A., Molnar, D., Osvik, D., and B. de Weger. Short chosen-prefix collisions for MD5 and the creation of a rogue CA certificate, Crypto 2009.
- [SP800-57] National Institute of Standards and Technology (NIST), Special Publication 800-57: Recommendation for Key Management – Part 1 (Revised), March 2007.
- [SP800-131] National Institute of Standards and Technology (NIST), Special Publication 800-131: DRAFT Recommendation for the Transitioning of Cryptographic Algorithms and Key Sizes, June 2010.
- [STEV2007] Stevens, M., On Collisions for MD5.
<http://www.win.tue.nl/hashclash/On%20Collisions%20for%20MD5%20-%20M.M.J.%20Stevens.pdf>.
- [WAYU2005] X. Wang and H. Yu. How to Break MD5 and other Hash Functions. LNCS 3494. Advances in Cryptology – EUROCRYPT2005, Springer 2005.
- [WFLY2004] X. Wang, D. Feng, X. Lai, H. Yu, Collisions for

Hash Functions MD4, MD5, HAVAL-128 and RIPEMD,
2004, <http://eprint.iacr.org/2004/199.pdf>

[WYWZZ2009]

X. Wang, H. Yu, W. Wang, H. Zhang, and T. Zhan.
Cryptanalysis of HMAC/NMAC-MD5 and MD5-MAC. LNCS
5479. Advances in Cryptology - EUROCRYPT2009,
Springer 2009.

Turner & Chen

Expires January 12, 2011

[Page 6]

Internet-Draft MD5 and HMAC-MD5 Security Considerations

July 2010

Authors' Addresses

Sean Turner
IECA, Inc.
3057 Nutley Street, Suite 106
Fairfax, VA 22031
USA

EMail: turners@ieca.com

Lily Chen
National Institute of Standards and Technology
100 Bureau Drive, Mail Stop 8930
Gaithersburg, MD 20899-8930
USA

EMail: lily.chen@nist.gov

