

LIME Working Group
Internet-Draft
Intended status: Informational
Expires: January 18, 2018

Y. Tochio
Fujitsu
H. van Helvoort
Hai Gaoming BV
L. Xia
Huawei
July 17, 2017

Gap Analysis for Layer and Technology Independent OAM Management in the
Multi-Layer Environment
[draft-txh-lime-gap-analysis-04](#)

Abstract

This draft analyses the existing management plane OAM related works in different SDOs, against the key objectives of Layer Independent OAM Management (LIME), to find the gap between them. The results can be used as the guidance for further work. This gap analysis is not targeted at L0-L2 transport OAM in ITU-T, either technology specific or generic across those technologies. Rather, it is intended to leverage knowledge from that domain for the benefit of developing generic layer independent OAM management for L3-L7 (and L2.5 MPLS OAM).

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <http://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on December 7, 2016.

Copyright Notice

Copyright (c) 2016 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

Table of Contents

1.	Introduction	2
2.	Conventions used in this document	3
2.1.	Terminology	3
3.	Existing OAM Related Works	4
3.1.	Survey of ITU-T Work from L0-L2	5
3.1.1.	Generic L0-L2	5
3.1.2.	Technology Specific L0-L2	5
3.2.	Management Information Models	5
3.3.	IEEE CFM MIB	6
3.4.	MEF SOAM FM and PM MIB	6
3.5.	IETF Technology-specific MIB Series	7
3.6.	IEEE CFM YANG	7
3.7.	MEF CFM and SOAM YANG Data Model	7
3.8.	YANG Model for OAM Management and Technology-specific extensions	7
3.9.	Discussion	8
4.	Security Considerations	8
5.	IANA Considerations	8
6.	Acknowledgements	8
7.	Normative References	8
	Authors' Addresses	12

[1.](#) Introduction

Operations, Administration, and Maintenance (OAM) mechanisms are critical building blocks in network operations that are used for service assurance, fulfillment, or service diagnosis, troubleshooting, and repair. The current practice is maintenance and troubleshooting are achieved per technology and per layer. The operation process can be very cumbersome. At present, within the L0-L2 technology domains, considerable effort has been expended in ITU-T to establish a coherent approach to OAM, including generic layer independent principles.

Due to this fact, [[I-D.edprop-opsawg-multi-layer-oam-ps](#)] discusses a valuable direction in management plane by establishing a coherent approach to OAM information from L2.5-L7 using a centralized

management entity and have a unified and consistent OAM view of multi-layer networks. Operators can rely on consolidated OAM management to correlate different layer OAM information (e.g., fault, defects and network failure), and quickly identify the faulty element with its layer information in the network path. Note that current LIME work focuses on layer-independent and technology-independent configuration, reporting and presentation for OAM mechanisms in the context of IP, MPLS, BFD, pseudowires, and Transparent Interconnection of Lots of Links (TRILL) technology developed by IETF. The second important objective of LIME is to achieve a layer and technology independent OAM view of a network and allow management applications present to the user an abstract view of this network and its supporting layers that is strictly topological, free of any technology specific information. This means an abstract and generic OAM management model in the management plane should be utilized (with extensions as appropriate to L2.5-L7), from which OAM specific views can be established, and technology-specific OAM data models can be developed by mapping from the information model view. A generic OAM management model can provide a consistent configuration, reporting, and presentation for the OAM mechanisms. It also can mitigate the problem related to specific OAM technology dependency.

This draft analyses the existing management plane OAM related work in several SDOs, against the key objectives of LIME, to find the gap between them. The results can be used as the guidance for further work.

2. Conventions used in this document

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [RFC2119](#) [[RFC2119](#)].

2.1. Terminology

DM Data Model

EMS Element Management System

IM Information Model

NMS Network Management System

MP Maintenance Point [[802.1Q](#)]

MEG Maintenance Entity Group [[G.8013](#)] [[RFC6371](#)]

MEP MEG End Point [[G.8013](#)] [[RFC6371](#)]

MIP MEG Intermediate Point [[G.8013](#)] [[RFC6371](#)]

ME Maintenance Entity [[G.8013](#)] [[RFC6371](#)]

MD Maintenance Domain [[802.1Q](#)]

MPLS Multiprotocol Label Switching

NE Network Element

OAM Operations, Administration, and Maintenance [[RFC6291](#)]

LIME Layer Independent OAM Management

SFC Service Function Chaining

SFF Service Function Forwarder

SDO Standard Developing Organization

3. Existing OAM Related Works

3.1. Survey of ITU-T Work from L0-L2

3.1.1. Generic L0-L2

[G.800] and [G.805] specify the unified and generic functional architecture of transport networks. [G.806] specifies the generic processing of transport equipment functions, including handling of OAM, defect correlation, and alarm suppression, etc. [G.7710] specifies the generic management requirements for configuration, fault, and performance (i.e. the C, F, P of FCAPS). [G.7711] is on-going work in ITU-T to specify the generic management information model for L0-L2 transport networks.

3.1.2. Technology Specific L0-L2

[G.803], [G.872], [G.8010] and [G.8110.1] specify the functional architecture respectively for SDH, OTN, Ethernet, MPLS-TP transport networks. [G.783], [G.798], [G.8021] and [G.8121] specify respectively the processing of transport equipment functions for SDH, OTN, Ethernet, MPLS-TP, including handling of OAM, and defect correlation, and alarm suppression, etc. [G.784], [G.874], [G.8051] and [G.8151] specify respectively the management requirements for configuration, fault, and performance (i.e. the C, F, P of FCAPS). [G.774], [G.874.1], [G.8052] and [G.8152] specify respectively the management information model for SDH, OTN, Ethernet, MPLS-TP transport networks.

3.2. Management Information Models

ITU-T's Recommendation [G.8052] and [G.8152] provide the management protocol-neutral information models for managing network elements in the Ethernet transport network and MPLS-TP transport network as defined in Recommendations [G.8010] and [G.8110.1] respectively. The management information models are derived from the "functional models", which describe the data plane behavior and processing. Management information models manage the "atomic functions" defined in the data plane in transport networks. They contain the object classes for the Ethernet and MPLS-TP NE management. This includes the Termination Point (TP), Maintenance Entity Group (MEG) End Point (MEP), MEG Intermediate Point (MIP), Traffic Conditioning & Shaping (TCS), Loss Measurement (LM), Delay Measurement (DM), and the general Performance Monitoring (PM), Current Data (CD) and History Data (HD). [G.8052] has been published. [G.8152] is still in progress. There is already some degree of consolidation among the /L0 (OTN) [G.874.1], (SDH) [G.774]/, /L1 (OTN) [G.874.1], (SDH) [G.774]/ and

/L2 (Ethernet) [[G.8052](#)], (MPLS-TP) [[G.8152](#)]/ information models specified by these ITU-T recommendations. In fact, they have a common basis for information model and are not technology-specific models any more.

[MEF-7.1] specifies the EMS-NMS interface profile identifying the managed objects (i.e. logical UML objects) needed to support Metro Ethernet services. This specification provides the profile of management entities based on ITU-T [[Q.840.1](#)], and also provides a mapping to the TMF's MTNM 3.5 Ethernet model. Specifically this document adds management support for Service OAM. The Ethernet Service OAM object definitions include common OAM objects (e.g., EthMe, EthMeg, EthMep, etc.), Fault Management Objects (e.g., Continuity Check, Loopback, etc.), Performance Monitoring Objects (e.g., Loss Measurement, Delay Measurement, etc.).

[3.3.](#) IEEE CFM MIB

The IEEE8021-CFM-MIB MIB Module and IEEE8021-CFM-V2-MIB MIB module are CFM MIB modules for managing IEEE CFM in [[802.1Q](#)]. The former document defines all the MIB objects that used to read, create, modify, and delete OAM related information (i.e., CFM Stack Table, MD Table, MA Table, MEP Table, LinkTrace Reply Table, MEP DB Table, Notifications Table, etc). The latter document defines CFM V2 module for managing IEEE CFM. It contains objects that replace those deprecated in the IEEE8021-CFM-MIB module (i.e., CFM Stack Table, CFM Vlan Table, CFM Default MD Level Table, etc).

[3.4.](#) MEF SOAM FM and PM MIB

[MEF-31] defines the MIB modules for MEF Service OAM Fault Management (FM). This document includes two MIBs necessary to support the MEF SOAM FM functionality: the MEF-SOAM-TC-MIB that includes the Textual Conventions (TC) for the SOAM MIB family and the MEF-SOAM-FM-MIB that includes extensions to Connectivity Fault Management (CFM) as developed in [IEEE 802.1Q], including MIBs found in [IEEE 802.1Q] and [IEEE 802.1ap], and enhanced by ITU-T [Y.1731] to support the SOAM FM functions as presented in the [[MEF-30](#)] specification. It includes the SOAM FM MIB objects such as mefSoamNet, mefSoamMeg, mefSoamMep, mefSoamCc, mefSoamAis, mefSoamLb, etc.

[MEF-36] specifies the Performance Monitoring (PM) MIB necessary to manage SOAM implementations that satisfy the Service OAM requirements and framework specified by [[MEF-17](#)], the Service OAM Performance Monitoring requirements as specified by [[MEF-35](#)], and the Service OAM management objects as specified by [[MEF-7.1](#)] which are applicable to Performance Monitoring functions. Two non-MEF documents serve as the baseline documents for this work: ITU-T [[G.8013](#)] and IEEE [[802.1Q](#)].

The SOAM PM MIB is divided into a number of different object

Tochio, et al.

Expires January 9, 2018

[Page 6]

groupings: the PM MIB MEP Objects, PM MIB Loss Measurement Objects, PM MIB Delay Measurement Objects, and SOAM PM Notifications.

3.5. IETF Technology-specific MIB Series

IETF specifies a series MIB module for various technologies, which includes: [[RFC7331](#)] for BFD MIB, [[RFC4560](#)] for PING MIB, [MPLS-TP OAM ID MIB] for MPLS-TP MIB, etc.

All these documents are technology-specific and limited to L1, L2, L3. The OAM MIB definition above L3 (i.e., SFC service layer) is still missing in IETF.

3.6. IEEE CFM YANG

[P802.1Qcx] specifies Unified Modeling Language (UML)-based information model and a YANG data model that allows configuration and status reporting for bridges and bridge components for Connectivity Fault Management (CFM) as specified in [[802.1Q](#)].

3.7. MEF CFM and SOAM YANG Data Model

SOAM CFM YANG module [[MEF-38](#)] is an important work that defines the managed objects necessary to support SOAM CFM functionality by using the IETF YANG Module Language [[RFC6020](#)]. This YANG module contains the management data definitions for the management of Ethernet Services OAM for Connectivity Fault Management.

[MEF-39] provides the YANG module that supports the Ethernet Service OAM (SOAM) Performance Monitoring functions. This YANG module contains the management data definitions for the management of Ethernet Services OAM for Performance Monitoring and extends the Connectivity Fault Management (CFM) YANG modules.

[MEF-38] and [[MEF-39](#)] will be updated as [MEF-38.1] and [MEF-39.1].

3.7. YANG Model for OAM Management and Technology-specific extensions

[I-D.ietf-lime-yang-oam-model] is an IETF work that creates a YANG unified data models for connection oriented OAM protocols. It defines a YANG [[RFC6020](#)] data model for Layer independent OAM Management implementations that can be applied to various network technologies.

[I-D.ietf-trill-yang-oam] extends the Generic YANG model defined in [[I-D.ietf-lime-yang-oam-model](#)] for OAM with TRILL technology.

[I-D.ietf-bfd-yang] defines YANG data model for BFD without augmenting the Generic YANG model for connection-less OAM defined in [I-D.ietf-lime-yang-connectionless].

3.9. Discussion

Until now, all the OAM models and operations in the management plane for L3-L7 are technology dependent and limited to one specific layer. One point which should be noticed is that the information models specified for transport networks (L0/L1/L2, [G.874.1], [G.8052], [G.8152]) by the ITU-T have received some degree of consolidation, and are not technology dependent. [I-D. lam-lime-summary-l0-l2-layer-independent] provides the summary on this point.

Also, [I-D.ietf-bfd-yang] indicates the concern how it can augment to the Generic YANG model defined [I-D. ietf-lime-yang-connectionless].

It is noted that the YANG Data model for OAM Performance Management has not been developed and and some drafts for them are expired.

4. Security Considerations

TBD.

5. IANA Considerations

This drafts includes no request to IANA.

6. Acknowledgements

The authors would like to thank for Eve Varma, Maarten Visser for their valuable comments and thoughtful inputs to this draft regarding ITU-T OAM works in L0-L2.

7. Normative References

- [G.774] "Synchronous digital hierarchy (SDH) - Management information model for the network element view", ITU-T G.774, February 2001.
- [G.783] "Characteristics of synchronous digital hierarchy (SDH) equipment functional blocks", ITU-T G.783, March 2006.
- [G.784] "Management aspects of synchronous digital hierarchy (SDH) transport network elements", ITU-T G.784, March 2008.
- [G.798] "Characteristics of optical transport network hierarchy equipment functional blocks", ITU-T G.798, December 2012.
- [G.800] "Unified functional architecture of transport networks", ITU-T G.800, February 2012.

- [G.8010] "Architecture of Ethernet layer networks", ITU-T G.8010, February 2004.
- [G.8013] "OAM functions and mechanisms for Ethernet based networks", ITU-T G.8013/Y.1731, August 2015.
- [G.8021] "Characteristics of Ethernet transport network equipment functional blocks", ITU-T G.8021, January 2015.
- [G.803] "Architecture of transport networks based on the synchronous digital hierarchy (SDH)", ITU-T G.803, March 2000.
- [G.805] "Generic functional architecture of transport networks", ITU-T G.805, March 2000.
- [G.8051] "Management aspects of the Ethernet Transport (ET) capable network element", ITU-T G.8051, August 2015.
- [G.8052] "Protocol-neutral management information model for the Ethernet transport capable network element", ITU-T G.8052/Y.1346, November 2015.
- [G.806] "Characteristics of transport equipment - Description methodology and generic functionality", ITU-T G.806, February 2012.
- [G.8110.1] "Architecture of MPLS Transport Profile (MPLS-TP) layer network", ITU-T G.8110.1/Y.1370.1, December 2011.
- [G.8121] "Characteristics of MPLS-TP equipment functional blocks", ITU-T G.8121, April 2016.
- [G.8151] "Management aspects of the MPLS-TP network element", ITU-T G.8151, January 2015.
- [G.8152] "Protocol-neutral management information model for the MPLS-TP network element", ITU-T G.8152/Y.1375, December 2016.
- [G.7710] "Common equipment management function requirements", ITU-T G.7710, February 2012.
- [G.7711] "Generic protocol-neutral information model for transport resources", ITU-T G.7711, August 2015.
- [G.872] "Architecture of optical transport networks", ITU-T G.872, October 2012.

- [G.874] "Management aspects of optical transport network elements", ITU-T G.874, August 2013.
- [G.874.1] "Optical transport network: Protocol-neutral management information model for the network element view", ITU-T G.874.1, October 2012.
- [I-D.edprop-opsawg-multi-layer-oam-ps]
Taylor, T., "Problem Statement for Layer and Technology Independent OAM in a Multi-Layer Environment", ID [draft-edprop-opsawg-multi-layer-oam-ps](#)(Expired), September 2014.
- [I-D.ietf-lime-yang-oam-model]
Kumar, D., Wu, Q., and Wang, M. "Generic YANG Data Model for Connection Oriented Operations, Administration, and Maintenance (OAM)", [draft-ietf-lime-yang-connection-oriented-oam-model-07](#), July 2016.
- [I-D.ietf-bfd-yang]
Zheng, L., " Yang Data Model for Bidirectional Forwarding Detection(BFD) ", ID [draft-ietf-bfd-yang-06](#), June 2017.
- [I-D.ietf-trill-yang-oam]
Kumar, D., "YANG Data Model for TRILL Operations, Administration, and Maintenance (OAM)", [draft-ietf-trill-yang-oam-04](#), July 2016.
- [I-D. lam-lime-summary-l0-l2-layer-independent]
K. Lam., "Existing Support for Network Operations in Multilayer Transport Network based upon unified approach to OAM (Layer 0 - Layer 2)", ID [draft-lam-lime-summary-l0-l2-layer-independent-05](#)(Expired), October 2016.
- [I-D. ietf-lime-yang-connectionless]
Kumar, D., "Generic YANG Data Model for Connection Less, Operations, Administration, and Maintenance (OAM) protocols", [draft-ietf-lime-yang-connectionless-oam-07](#), June 2017
- [802.1Q] "Media Access Control (MAC) Bridges and Virtual Bridged Local Area Networks", IEEE Std 802.1Q-2014, November 2014.
- [P802.1Qcx]
"Standard for Local and metropolitan area networks --Bridges and Bridged Networks Amendment: YANG Data Model for Connectivity Fault Management", (in progress).

- [MEF-17] "Service OAM Requirements & Framework - Phase 1", MEF 17, April 2007.
- [MEF-30] "Service OAM Fault Management Implementation Agreement", MEF 30, January 2011.
- [MEF-31] "Service OAM Fault Management Definition of Managed Objects", MEF 31, January 2011.
- [MEF-35] "Service OAM Performance Monitoring Implementation Agreement", MEF 35, January 2012.
- [MEF-36] "Service OAM SNMP MIB for Performance Monitoring", MEF 36, January 2012.
- [MEF-38] "Service OAM Fault Management YANG Modules", MEF 38, April 2012.
- [MEF-39] "Service OAM Performance Monitoring YANG Module", MEF 39, April 2012.
- [MEF-7.1] "EMS-NMS Information Model - Phase 2", MEF Fourm MEF 7.1, 2009.
- [Q.840.1] "Requirements and Analysis for NMS-EMS Management Interface of Ethernet over Transport and Metro Ethernet Network", Draft Recommendation ITU-T Q.840.1, 2007.
- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", March 1997.
- [RFC4560] Quittek, J., "Definitions of Managed Objects for Remote Ping, Traceroute, and Lookup Operations", June 2006.
- [RFC6020] Bjorklund, M., "YANG - A Data Modeling Language for the Network Configuration Protocol (NETCONF)", [RFC 6020](#), October 2010.
- [RFC6291] Andersson, L., van Helvoort, H., Bonica, R., Romascanu, D., and S. Mansfield, "Guidelines for the use of the "OAM" Acronym in the IETF", [RFC 6291](#), June 2011.
- [RFC6371] Busi, I. and D. Allan, "Operations, Administration, and Maintenance Framework for MPLS-Based Transport Networks", [RFC 6371](#), September 2011.
- [RFC7331] Nadeau, T., Ali, Z., and N. Akiya, "Bidirectional Forwarding Detection (BFD) Management Information Base", [RFC 7331](#), August 2014.

Authors' Addresses

Yuji Tochio
Fujitsu

Email: tochio@jp.fujitsu.com

Huub van Helvoort
Hai Gaoming BV
The Netherlands

Email: huubatwork@gmail.com

Liang (Frank) Xia
Huawei
101 Software Avenue, Yuhua District
Nanjing, Jiangsu 210012
China

Email: Frank.xialiang@huawei.com