

Network Working Group
Internet-Draft
Intended status: Standards Track
Expires: November 9, 2017

S. Vallin
Stefan Vallin AB
M. Bjorklund
Cisco
May 8, 2017

YANG Alarm Module
draft-vallin-netmod-alarm-module-02

Abstract

This document defines a YANG module for alarm management. It includes functions for alarm list management, alarm shelving and notifications to inform management systems. There are also RPCs to manage the operator state of an alarm and administrative alarm procedures. The module carefully maps to relevant alarm standards.

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <http://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on November 9, 2017.

Copyright Notice

Copyright (c) 2017 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in [Section 4.e](#) of

the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

Table of Contents

1.	Requirements notation	3
2.	Introduction	3
2.1.	Terminology	3
3.	Objectives	4
4.	Background and Usability Requirements	5
5.	Alarm Concepts	8
5.1.	What is an Alarm?	9
5.2.	What is an Alarm Type?	9
5.3.	How are Resources Identified?	12
5.4.	How are Alarm Instances Identified?	12
5.5.	What is the Life-Cycle of an Alarm?	13
5.5.1.	Resource Alarm Life-Cycle	13
5.5.2.	Operator Alarm Life-cycle	14
5.5.3.	Administrative Alarm Life-Cycle	14
5.6.	Root Cause and Impacted Resources	15
5.7.	Alarm Shelving	15
6.	Alarm Data Model	15
6.1.	Alarm Control	17
6.1.1.	Alarm Shelving	18
6.2.	Alarm Inventory	18
6.3.	Alarm Summary	19
6.4.	The Alarm List	19
6.5.	The Shelved Alarms List	21
6.6.	RPCs	21
6.7.	Notifications	21
7.	Alarm YANG Module	21
8.	X.733 Alarm Mapping Data Model	46
9.	X.733 Alarm Mapping YANG Module	46
10.	Security Considerations	52
11.	Acknowledgements	52
12.	References	53
12.1.	Normative References	53
12.2.	Informative References	53
Appendix A.	Enterprise-specific Alarm-Types Example	54
Appendix B.	Alarm Inventory Example	55
Appendix C.	Alarm List Example	56
Appendix D.	Alarm Shelving Example	57
Appendix E.	X.733 Mapping Example	58
	Authors' Addresses	58

1. Requirements notation

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [[RFC2119](#)].

2. Introduction

This document defines a YANG [[RFC7950](#)] module for alarm management. The purpose is to define a standardised alarm interface for network devices that can be easily integrated into management applications. The model is also applicable as a northbound alarm interface in the management applications.

Alarm monitoring is a fundamental part of monitoring the network. Raw alarms from devices do not always tell the status of the network services or necessarily point to the root cause. However, being able to feed alarms to the network management system in a standardised format is a starting point for performing higher level network assurance tasks.

The telecommunication domain has standardised an alarm interface in ITU-T X.733 [[X.733](#)]. This continued in mobile networks within the 3GPP organisation [[ALARMIRP](#)]. Although SNMP is the dominant mechanism for monitoring devices, IETF did not early on standardise an alarm MIB. Instead, management systems interpreted the enterprise specific traps per MIB and device to build an alarm list. When finally The Alarm MIB [[RFC3877](#)] was published, it had to address the existence of enterprise traps and map these into alarms. This requirement led to a MIB that is not easy to use.

This document defines a standardised YANG module for alarm management. The design of the module is based on experience from using and implementing the above mentioned alarm standards.

2.1. Terminology

The following terms are defined in [[RFC7950](#)]:

- o action
- o client
- o data tree
- o RPC
- o server

The following terms are used within this document:

- o Alarm (the general concept): An alarm signifies an undesirable state in a resource that requires corrective action.
- o Alarm Instance: The alarm state for a specific resource and alarm type. For example (GigabitEthernet0/15, link-alarm). An entry in the alarm list.
- o Alarm Inventory: A list of all possible alarm types on a system.
- o Alarm Shelving: Blocking alarms according to specific criteria.
- o Alarm Type: An alarm type identifies a possible unique alarm state for a resource. Alarm types are names to identify the state like 'link-alarm', 'jitter-violation', 'high-disk-utilization'.
- o Management System: The alarm management application that consumes the alarms, i.e., acts as a client.
- o Resource: A fine-grained identification of the alarming resource, for example: an interface, a process.
- o System: The system that implements this YANG alarm module, i.e., acts as a server. This corresponds to a network device or a management application that provides a north-bound alarm interface.

3. Objectives

The objectives for the design of the Alarm Module are:

- o Simple to use. If a system supports this module, it shall be straight-forward to integrate this into a YANG based alarm manager.
- o View alarms as states on resources and not as discrete notifications.
- o Clear definition of "alarm" in order to exclude general events that should not be forwarded as alarm notifications.
- o Clear and precise identification of alarm types and alarm instances.
- o A management system should be able to pull all available alarm types from a system, i.e., read the alarm inventory from a system.

This makes it possible to prepare alarm operators with corresponding alarm instructions.

- o Address alarm usability requirements. While IETF has not really addressed alarm management, telecom standards has addressed it purely from a protocol perspective. The process industry has published several relevant standards addressing requirements for a useful alarm interface; [EEMUA], [ISA182]. This alarm module defines usability requirements as well as a YANG data model.
- o Mapping to X.733, which is a requirement for many alarm systems. Still, keep some of the X.733 concepts out of the core model in order to make the model small and easy to understand.

4. Background and Usability Requirements

Common alarm problems and the cause of the problems are summarised in Table 1. This summary is adopted to networking based on the ISA [ISA182] and EEMUA [EEMUA] standards.

Problem	Cause	How this module address the cause
Alarms are generated but they are ignored by the operator.	"Nuisance" alarms (chattering alarms and fleeting alarms), faulty hardware, redundant alarms, cascading alarms, incorrect alarm settings, alarms have not been rationalised, the alarms represent log information rather than true alarms.	Strict definition of alarms requiring corrective response. Alarm requirements in Table 2.
When alarms occur, operators do not know how to respond.	Insufficient alarm response procedures and not well defined alarm types.	The alarm inventory lists all alarm types and corrective actions. Alarm requirements in Table 2.
The alarm display is full of alarms, even when there is nothing wrong.	Nuisance alarms, stale alarms, alarms from equipment not in service.	The alarm definition and alarm shelving.
During a failure, operators are flooded with so many alarms that they do not know which ones are the most important.	Incorrect prioritization of alarms. Not using advanced alarm techniques (e.g. state-based alarming).	State-based alarm model, alarm rate requirements in Table 3 and Table 4

Table 1: Alarm Problems and Causes

Based upon the above problems EEMUA gives the following definition of a good alarm:

Characteristic	Explanation
Relevant	Not spurious or of low operational value.
Unique	Not duplicating another alarm.
Timely	Not long before any response is needed or too late to do anything.
Prioritised	Indicating the importance that the operator deals with the problem.
Understandable	Having a message which is clear and easy to understand.
Diagnostic	Identifying the problem that has occurred.
Advisory	Indicative of the action to be taken.
Focusing	Drawing attention to the most important issues.

Table 2: Definition of a Good Alarm

Vendors SHOULD rationalise all alarms according to above. Another crucial requirement is acceptable alarm rates. Vendors SHOULD make sure that they do not exceed the recommendations from EEMUA below:

Long Term Alarm Rate in Steady Operation	Acceptability
More than one per minute	Very likely to be unacceptable.
One per 2 minutes	Likely to be over-demanding.
One per 5 minutes	Manageable.
Less than one per 10 minutes	Very likely to be acceptable.

Table 3: Acceptable Alarm Rates, Steady State

Number of alarms displayed in 10 minutes following a major network problem	Acceptability
More than 100	Definitely excessive and very likely to lead to the operator to abandon the use of the alarm system.
20-100	Hard to cope with.
Under 10	Should be manageable - but may be difficult if several of the alarms require a complex operator response.

Table 4: Acceptable Alarm Rates, Burst

The numbers in Table 3 and Table 4 are the sum of all alarms for a network being managed from one alarm console. So every individual system or NMS contributes to these numbers.

Vendors SHOULD make sure that the following rules are used in designing the alarm interface:

1. Rationalize the alarms in the system to ensure that every alarm is necessary, has a purpose, and follows the cardinal rule - that it requires an operator response. Adheres to the rules of Table 2
2. Audit the quality of the alarms. Talk with the operators about how well the alarm information support them. Do they know what to do in the event of an alarm? Are they able to quickly diagnose the problem and determine the corrective action? Does the alarm text adhere to the requirements in Table 2?
3. Analyze and benchmark the performance of the system and compare it to the recommended metrics in Table 3 and Table 4. Start by identifying nuisance alarms, standing alarms at normal state and startup.

5. Alarm Concepts

This section defines the fundamental concepts behind the data model. This section is rooted in the works of Vallin et. al [[ALARMSEM](#)].

5.1. What is an Alarm?

There are two misconceptions regarding alarms and alarm interfaces that are important to sort out. The first problem is that alarms are mixed with events in general. Alarms MUST correspond to an undesirable state that needs corrective action. Many implementations of alarm interfaces do not adhere to this principle and just send events in general. In order to qualify as an alarm, there must exist a corrective action. If that is not true, it is an event that can go into logs.

The other misconception is that the term alarm refers to the notification itself. Rather, an alarm is a state of a resource in the system. The alarm notifications report state changes of the alarm, such as alarm raise and alarm clear.

Based upon the above, we will use the following alarm definition:

An alarm signifies an undesirable state in a resource that requires corrective action.

"One of the most important principles of alarm management is that an alarm requires an action. This means that if the operator does not need to respond to an alarm (because unacceptable consequences do not occur), then it is not an alarm. Following this cardinal rule will help eliminate many potential alarm management issues." [[ISA182](#)]

5.2. What is an Alarm Type?

One of the fundamental requirements stated in the previous section is that every alarm must have a corresponding corrective action. This means that every vendor should be able to prepare a list of available alarms and their corrective actions. We use the term 'alarm type' to refer to every possible alarm that could be active in the system.

Alarm types are also fundamental in order to provide a state-based alarm list. The alarm list correlates alarm state changes for the same alarm type and the same resource into one alarm.

Different alarm interfaces use different mechanisms to define alarm types, ranging from simple error numbers to more advanced mechanisms like the X.733 triplet of event type, probable cause and specific problem.

This document defines an alarm type with an alarm type id and an alarm type qualifier.

The alarm type id is modeled as a YANG identity. With YANG identities, new alarm types can be defined in a distributed fashion. YANG identities are hierarchical, which means that an hierarchy of alarm types can be defined.

The primary goal for the alarm module has been to provide a simple but extensible mechanism. YANG identities is a good mechanism for enumerated values that are easy to extend.

This means that every possible alarm type that can appear in a system exists as a well defined hierarchical identity along with a description. Tools can provide a list of possible alarms by parsing the YANG identities rather than reading user guides.

Standards and vendors should define their own alarm type identities based on this definition.

The use of YANG identities means that all possible alarms are identified at design time. This explicit declaration of alarm types makes it easier to allow for alarm qualification reviews and preparation of alarm actions and documentation.

There are occasions where the alarm types are not known at design time. For example, a system with digital inputs that allows users to connects detectors (e.g., smoke detector) to the inputs. In this case it is a configuration action that says that certain connectors are fire alarms for example. The drawback of this is that there is a big risk that alarm operators will receive alarm types as a surprise, they do not know how to resolve the problem since a defined alarm procedure does not necessarily exist.

In order to allow for dynamic addition of alarm types the alarm module also allows for further qualification of the identity based alarm type using a string.

A common misunderstanding is that individual alarm notifications are alarm types. This is not correct; e.g., "link-up" and "link-down" are two notifications reporting different states for the same alarm type, "link-alarm".

A vendor or standard can then define their own alarm-type hierarchy. The example below shows a hierarchy based on X.733 event types:


```
import ietf-alarms {
  prefix al;
}
identity vendor-alarms {
  base al:alarm-type;
}
identity communications-alarm {
  base vendor-alarms;
}
identity link-alarm {
  base communications-alarm;
}
```

Alarm types can be abstract. An abstract alarm type is used as a base for defining hierarchical alarm types. Concrete alarm types are used for alarm states and appear in the alarm inventory. There are two kinds of concrete alarm types:

1. The last subordinate identity in the 'alarm-type-id' hierarchy is concrete, for example: "alarm-identity.environmental-alarm.smoke". In this example "alarm-identity" and "environmental-alarm" are abstract YANG identities, whereas "smoke" is a concrete YANG identity.
2. The YANG identity hierarchy is abstract and the concrete alarm type is defined by the dynamic alarm qualifier string, for example: "alarm-identity.environmental-alarm.external-detector" with alarm-type-qualifier "smoke".

For example:


```
// Alternative 1: concrete alarm type identity
import ietf-alarms {
  prefix al;
}
identity environmental-alarm {
  base al:alarm-type;
  description "Abstract alarm type";
}
identity smoke {
  base environmental-alarm;
  description "Concrete alarm type";
}

// Alternative 2: concrete alarm type qualifier
import ietf-alarms {
  prefix al;
}
identity environmental-alarm {
  base al:alarm-type;
  description "Abstract alarm type";
}
identity external-detector {
  base environmental-alarm;
  description
    "Abstract alarm type, a run-time configuration
    procedure sets the type of alarm detected. This will
    be reported in the alarm-type-qualifier.";
}
```

5.3. How are Resources Identified?

It is of vital importance to be able to refer to the alarming resource. This reference must be as fine-grained as possible. If the alarming resource exists in the data tree then an instance-identifier MUST be used with the full path to the object.

This module also allows for alternate naming of the alarming resource if it is not available in the data tree.

5.4. How are Alarm Instances Identified?

A primary goal of this alarm module is to remove any ambiguity in how alarm notifications are mapped to an update of an alarm instance. X.733 and especially 3GPP was not really clear on this point. This YANG alarm module states that the tuple (resource, alarm type identifier, alarm type qualifier) corresponds to the same alarm instance. This means that alarm notifications for the same resource

and same alarm type are matched to update the same alarm instance. These three leafs are therefore used as the key in the alarm list:

```
list alarm {
  key "resource alarm-type-id alarm-type-qualifier";
  ...
}
```

5.5. What is the Life-Cycle of an Alarm?

The alarm model clearly separates the resource alarm life-cycle from the operator and administrative life-cycles of an alarm.

- o resource alarm life-cycle: the alarm instrumentation that controls alarm raise, clearance, and severity changes.
- o operator alarm life-cycle: operators acting upon alarms with actions like acknowledgment and closing. Closing an alarm implies that the operator considers the corrective action performed. Operators can also shelf alarms in order to avoid nuisance alarms.
- o administrative alarm life-cycle: deleting (purging) alarms and compressing the alarm status change list. This module exposes operations to manage the administrative life-cycle. The server may also perform these operations based on other policies, but how that is done is out of scope for this document.

5.5.1. Resource Alarm Life-Cycle

From a resource perspective, an alarm can have the following life-cycle: raise, change severity, change severity, clear, being raised again etc. All of these status changes can have different alarm texts generated by the instrumentation. Two important things to note:

1. Alarms are not deleted when they are cleared. Deleting alarms is an administrative process. The alarm module defines an rpc "purge" that deletes alarms.
2. Alarms are not cleared by operators, only the underlying instrumentation can clear an alarm. Operators can close alarms.

The YANG tree representation below illustrates the resource oriented life-cycle:


```

+--ro alarm* [resource alarm-type-id alarm-type-qualifier]
  ...
  +--ro is-cleared          boolean
  +--ro last-changed       yang:date-and-time
  +--ro perceived-severity severity
  +--ro alarm-text         alarm-text
  +--ro status-change* [time]
    +--ro time              yang:date-and-time
    +--ro perceived-severity severity
    +--ro alarm-text       alarm-text

```

For every status change from the resource perspective a row is added to the 'status-change' list. The last status values are also represented at leafs for the alarm. Note well that the alarm severity does not include 'cleared', alarm clearance is a flag.

An alarm can therefore look like this: ((GigabitEthernet0/25, link-alarm,""), false, T, major, "Interface GigabitEthernet0/25 down")

5.5.2. Operator Alarm Life-cycle

Operators can also act upon alarms using the set-operator-state action:

```

+--ro alarm* [resource alarm-type-id alarm-type-qualifier]
  ...
  +--ro operator-state-change* [time] {operator-actions}?
  | +--ro time          yang:date-and-time
  | +--ro operator      string
  | +--ro state         operator-state
  | +--ro text?        string
  +---x set-operator-state {operator-actions}?
    +---w input
    +---w state         operator-state
    +---w text?        string

```

The operator state for an alarm can be: 'none', 'ack', 'shelved', and 'closed'. Alarm deletion, 'rpc purge', can use this state as a criteria. A closed alarm is an alarm where the operator has performed any required corrective actions. Closed alarms are good candidates for being deleted.

5.5.3. Administrative Alarm Life-Cycle

Deleting alarms from the alarm list is considered an administrative action. This is supported by the "purge-alarms" rpc. The "purge-alarms" rpc takes a filter as input. The filter selects alarms based on the operator and resource life-cycle such as "all closed cleared

alarms older than a time specification". The server may also perform these operations based on other policies, but how that is done is out of scope for this document.

Alarms can be compressed. Compressing an alarm deletes all entries in the alarm's "status-change" list except for the last status change. A client can perform this using the "compress-alarms" rpc. The server may also perform these operations based on other policies, but how that is done is out of scope for this document.

5.6. Root Cause and Impacted Resources

The general principle of this alarm module is to limit the amount of alarms. The alarm has two leaf-lists to identify possible impacted resources and possible root-cause resources. The system should not send individual alarms for the possible root-cause resources and impacted resources. These serves as hints only. It is up to the client application to use this information to present the overall status.

5.7. Alarm Shelving

Alarm shelving is an important function in order for alarm management applications and operators to stop superfluous alarms. A shelved alarm implies that any alarms fulfilling this criteria are ignored. Shelved alarms appear in a dedicated shelved alarm list in order not to disturb the relevant alarms. Shelved alarms do not generate notifications.

6. Alarm Data Model

Alarm shelving and operator actions are YANG features so that a server can select not to support these.

The data model has the following overall structure:

```

+--rw alarms
  +--rw control
    | +--rw max-alarm-status-changes?  union
    | +--rw notify-status-changes?    boolean
    | +--rw alarm-shelving {alarm-shelving}?
    |   +--rw shelf* [shelf-name]
    |     +--rw shelf-name              string
    |     +--rw resource?              resource
    |     +--rw alarm-type-id?         alarm-type-id
    |     +--rw alarm-type-qualifier?  alarm-type-qualifier
    |     +--rw description?          string
  +--ro alarm-inventory

```



```

| +--ro alarm-type* [alarm-type-id alarm-type-qualifier]
|   +--ro alarm-type-id          alarm-type-id
|   +--ro alarm-type-qualifier   alarm-type-qualifier
|   +--ro resource*              string
|   +--ro has-clear               boolean
|   +--ro description             string
+--ro summary
| +--ro alarm-summary* [severity]
| | +--ro severity                severity
| | +--ro total?                  yang:gauge32
| | +--ro cleared?                yang:gauge32
| | +--ro cleared-not-closed?     yang:gauge32
| | | {operator-actions}?
| | +--ro cleared-closed?         yang:gauge32
| | | {operator-actions}?
| | +--ro not-cleared-closed?     yang:gauge32
| | | {operator-actions}?
| | +--ro not-cleared-not-closed? yang:gauge32
| | | {operator-actions}?
| +--ro shelves-active?  empty {alarm-shelving}?
+--ro alarm-list
| +--ro number-of-alarms?  yang:gauge32
| +--ro last-changed?      yang:date-and-time
| +--ro alarm* [resource alarm-type-id alarm-type-qualifier]
|   +--ro time-created      yang:date-and-time
|   +--ro resource          resource
|   +--ro alarm-type-id     alarm-type-id
|   +--ro alarm-type-qualifier alarm-type-qualifier
|   +--ro alt-resource*     resource
|   +--ro related-alarm*
|     [resource alarm-type-id alarm-type-qualifier]
|     +--ro resource
|     | -> /alarms/alarm-list/alarm/resource
|     +--ro alarm-type-id   leafref
|     +--ro alarm-type-qualifier leafref
|   +--ro impacted-resource* resource
|   +--ro root-cause-resource* resource
|   +--ro is-cleared        boolean
|   +--ro last-changed      yang:date-and-time
|   +--ro perceived-severity severity
|   +--ro alarm-text        alarm-text
|   +--ro status-change* [time] {alarm-history}?
|     +--ro time            yang:date-and-time
|     +--ro perceived-severity severity-with-clear
|     +--ro alarm-text      alarm-text
|   +--ro operator-state-change* [time] {operator-actions}?
|     +--ro time            yang:date-and-time
|     +--ro operator        string

```



```

|   | +--ro state      operator-state
|   | +--ro text?     string
|   +---x set-operator-state {operator-actions}?
|       +---w input
|           +---w state      operator-state
|           +---w text?     string
+--ro shelved-alarms {alarm-shelving}?
  +--ro number-of-shelved-alarms?  yang:gauge32
  +--ro alarm-shelf-last-changed?  yang:date-and-time
  +--ro shelved-alarm*
    [resource alarm-type-id alarm-type-qualifier]
    +--ro resource                resource
    +--ro alarm-type-id           alarm-type-id
    +--ro alarm-type-qualifier    alarm-type-qualifier
    +--ro alt-resource*           resource
    +--ro related-alarm*
      [resource alarm-type-id alarm-type-qualifier]
      | +--ro resource
      | | -> /alarms/alarm-list/alarm/resource
      | +--ro alarm-type-id       leafref
      | +--ro alarm-type-qualifier leafref
    +--ro impacted-resource*      resource
    +--ro root-cause-resource*    resource
    +--ro is-cleared              boolean
    +--ro last-changed            yang:date-and-time
    +--ro perceived-severity      severity
    +--ro alarm-text              alarm-text
    +--ro status-change* [time] {alarm-history}?
      | +--ro time                yang:date-and-time
      | +--ro perceived-severity  severity-with-clear
      | +--ro alarm-text          alarm-text
    +--ro operator-state-change* [time] {operator-actions}?
      +--ro time                yang:date-and-time
      +--ro operator            string
      +--ro state                operator-state
      +--ro text?               string

```

6.1. Alarm Control

The "/alarms/control/notify-status-changes" leaf controls if notifications are sent for all state changes, severity change and alarm text change, or just for new and cleared alarms.

Every alarm has a list of status changes, this is a circular list. The length of this list is controlled by "/alarms/control/max-alarm-status-changes".

6.1.1. Alarm Shelving

The shelving control tree is shown below:

```
+--rw alarm-shelving {alarm-shelving}?
  +--rw shelf* [shelf-name]
    +--rw shelf-name                string
    +--rw resource?                 resource
    +--rw alarm-type-id?            alarm-type-id
    +--rw alarm-type-qualifier?     alarm-type-qualifier
```

Shelved alarms are shown in a dedicated shelved alarm list. The instrumentation MUST move shelved alarms from the alarm list (/alarms/alarm-list) to the shelved alarm list (/alarms/shelved-alarms/). Shelved alarms do not generate any notifications. When the shelving criteria is removed or changed the alarm list MUST be updated to the correct actual state of the alarms.

A leaf (/alarms/summary/shelfs-active) in the alarm summary indicates if there are shelved alarms.

A system can select to not support the shelving feature.

6.2. Alarm Inventory

The alarm inventory represents all possible alarm types that may occur in the system. A management system may use this to build alarm procedures. The alarm inventory is relevant for several reasons:

The system might not instrument all alarm type identities.

The system has configured dynamic alarm types using the alarm qualifier. The inventory makes it possible for the management system to discover these.

Note that the mechanism whereby dynamic alarm types are added using the alarm type qualifier MUST populate this list.

The optional leaf-list "resource" in the alarm inventory enables the system to publish for which resources a given alarm type may appear.

The alarm inventory tree is shown below:


```
ro alarm-inventory
+--ro alarm-type* [alarm-type-id alarm-type-qualifier]
  +--ro alarm-type-id      alarm-type-id
  +--ro alarm-type-qualifier alarm-type-qualifier
  +--ro resource*         string
  +--ro has-clear         boolean
  +--ro description       string
```

6.3. Alarm Summary

The alarm summary list summarises alarms per severity; how many cleared, cleared and closed, and closed. It also gives an indication if there are shelved alarms.

6.4. The Alarm List

The alarm list (/alarms/alarm-list) is a function from (resource, alarm type, alarm type qualifier) to the current alarm state.


```

+--ro alarm-list
  +--ro number-of-alarms?  yang:gauge32
  +--ro last-changed?     yang:date-and-time
  +--ro alarm* [resource alarm-type-id alarm-type-qualifier]
    +--ro time-created      yang:date-and-time
    +--ro resource          resource
    +--ro alarm-type-id     alarm-type-id
    +--ro alarm-type-qualifier alarm-type-qualifier
    +--ro alt-resource*     resource
    +--ro related-alarm*
      | [resource alarm-type-id alarm-type-qualifier]
      | +--ro resource
      | | -> /alarms/alarm-list/alarm/resource
      | +--ro alarm-type-id     leafref
      | +--ro alarm-type-qualifier leafref
    +--ro impacted-resource* resource
    +--ro root-cause-resource* resource
    +--ro is-cleared         boolean
    +--ro last-changed      yang:date-and-time
    +--ro perceived-severity severity
    +--ro alarm-text        alarm-text
    +--ro status-change* [time] {alarm-history}?
      | +--ro time              yang:date-and-time
      | +--ro perceived-severity severity-with-clear
      | +--ro alarm-text        alarm-text
    +--ro operator-state-change* [time] {operator-actions}?
      | +--ro time              yang:date-and-time
      | +--ro operator          string
      | +--ro state              operator-state
      | +--ro text?             string
    +---x set-operator-state {operator-actions}?
      +---w input
        +---w state      operator-state
        +---w text?     string

```

Every alarm has three important states, the resource clearance state "is-cleared", the severity "perceived-severity" and the operator state available in the operator state change list.

In order to see the alarm history the resource state changes are available in the "status-change" list and the operator history is available in the "operator-state-change" list.

6.5. The Shelved Alarms List

The shelved alarm list has the same structure as the alarm list above. It shows all the alarms that matches the shelving criteria (/alarms/control/alarm-shelving).

6.6. RPCs

The alarm module supports rpcs/actions to manage the alarms:

"purge-alarms" (RPC): delete alarms according to specific criteria, for example all cleared alarms older then a specific date.

"compress" and "compress-alarms" rpcs: compress the status-change list for the alarms.

"set-operator-state" action: change the operator state for an alarm: for example acknowledge.

6.7. Notifications

The alarm module supports a general notification to report alarm state changes. It carries all relevant parameters for the alarm management application.

There is also a notification to report that an operator changed the operator state on an alarm, like acknowledge.

If the alarm inventory is changed, for example a new card type is inserted, a notification will tell the management application that new alarm types are available.

7. Alarm YANG Module

```
<CODE BEGINS> file "ietf-alarms@2017-05-08.yang"
module ietf-alarms {
  yang-version 1.1;
  namespace "urn:ietf:params:xml:ns:yang:ietf-alarms";
  prefix al;

  import ietf-yang-types {
    prefix yang;
  }

  organization
```


"IETF NETMOD (NETCONF Data Modeling Language) Working Group";

contact

"WG Web: <<http://tools.ietf.org/wg/netmod/>>

WG List: <<mailto:netmod@ietf.org>>

Editor: Stefan Vallin
<<mailto:stefan@wallan.se>>

Editor: Martin Bjorklund
<<mailto:mbj@tail-f.com>>";

description

"This module defines an interface for managing alarms. Main inputs to the module design are the 3GPP Alarm IRP, ITU-T X.733 and ANSI/ISA-18.2 alarm standards.

Main features of this module include:

- * Alarm list:
A list of all alarms. Cleared alarms stay in the list until explicitly removed.
- * Operator actions on alarms:
Acknowledging and closing alarms.
- * Administrative actions on alarms:
Purging alarms from the list according to specific criteria.
- * Alarm inventory:
A management application can read all alarm types implemented by the system.
- * Alarm shelving:
Shelving (blocking) alarms according to specific criteria.

This module uses a stateful view on alarms. An alarm is a state for a specific resource (note that an alarm is not a notification). An alarm type is a possible alarm state for a resource. For example, the tuple:

```
('link-alarm', 'GigabitEthernet0/25')
```

is an alarm of type 'link-alarm' on the resource 'GigabitEthernet0/25'.

Alarm types are identified using YANG identities and an optional string-based qualifier. The string-based qualifier allows for dynamic extension of the statically defined alarm types. Alarm types identify a possible alarm state and not the individual notifications. For example, the traditional 'link-down' and 'link-up' notifications are two notifications referring to the same alarm type 'link-alarm'.

With this design there is no ambiguity about how alarm and alarm clear correlation should be performed: notifications that report the same resource and alarm type are considered updates of the same alarm, such as clearing an active alarm or changing the severity of an alarm.

The instrumentation can update 'severity' and 'alarm-text' on an existing alarm. The above alarm example can therefore look like:

```
(('link-alarm', 'GigabitEthernet0/25'),  
  warning,  
  'interface down while interface admin state is up')
```

There is a clear separation between updates on the alarm from the underlying resource, like clear, and updates from an operator like acknowledge or closing an alarm:

```
(('link-alarm', 'GigabitEthernet0/25'),  
  warning,  
  'interface down while interface admin state is up',  
  cleared,  
  closed)
```

Administrative actions like removing closed alarms older than a given time is supported.";

```
revision 2017-05-08 {  
  description  
    "Initial revision."  
  reference  
    "RFC XXXX: YANG Alarm Module";  
}  
  
/*  
 * Features  
 */  
  
feature operator-actions {  
  description
```



```
    "This feature means that the systems supports operator states
      on alarms.";
  }

  feature alarm-shelving {
    description
      "This feature means that the system supports shelving
        (blocking) alarms.";
  }

  feature alarm-history {
    description
      "This feature means that the alarm list also maintains a
        history of state changes for each alarm.  For example, if an
        alarm toggles between cleared and active 10 times, a list for
        that alarm will show those state changes with time-stamps.";
  }
  /*
  * Identities
  */

  identity alarm-identity {
    description
      "Base identity for alarm types.  A unique identification of the
        alarm, not including the resource.  Different resources can
        share alarm types.  If the resource reports the same alarm
        type, it is to be considered to be the same alarm.  The alarm
        type is a simplification of the different X.733 and 3GPP alarm
        IRP alarm correlation mechanisms and it allows for
        hierarchical extensions.

        A string-based qualifier can be used in addition to the
        identity in order to have different alarm types based on
        information not known at design-time, such as values in
        textual SNMP Notification var-binds.

        Standards and vendors can define sub-identities to clearly
        identify specific alarm types.

        This identity is abstract and shall not be used for alarms.";
  }
  /*
  * Common types
  */

  typedef resource {
    type union {
```



```
    type instance-identifier {
      require-instance false;
    }
    type yang:object-identifier;
    type string;
  }
  description
    "This is an identification of the alarming resource, such as an
    interface. It should be as fine-grained as possible both to
    guide the operator and to guarantee uniqueness of the
    alarms. If a resource has both a config and a state tree
    normally this should identify the state tree,
    (e.g., /interfaces-state/interface/name).
    But if the instrumentation can detect a broken config, this
    should be identified as the resource.
    If the alarming resource is modelled in YANG, this
    type will be an instance-identifier. If the resource is an
    SNMP object, the type will be an object-identifier. If the
    resource is anything else, for example a distinguished name or
    a CIM path, this type will be a string."
}

typedef alarm-text {
  type string;
  description
    "The string used to inform operators about the alarm. This
    MUST contain enough information for an operator to be able
    to understand the problem and how to resolve it. If this
    string contains structure, this format should be clearly
    documented for programs to be able to parse that
    information."
}

typedef severity {
  type enumeration {
    enum indeterminate {
      value 2;
      description
        "Indicates that the severity level could not be
        determined. This level SHOULD be avoided."
    }
    enum minor {
      value 3;
      description
        "The 'minor' severity level indicates the existence of a
        non-service affecting fault condition and that corrective
        action should be taken in order to prevent a more serious
        (for example, service affecting) fault. Such a severity
```



```
        can be reported, for example, when the detected alarm
        condition is not currently degrading the capacity of the
        resource.";
    }
    enum warning {
        value 4;
        description
            "The 'warning' severity level indicates the detection of
            a potential or impending service affecting fault, before
            any significant effects have been felt. Action should be
            taken to further diagnose (if necessary) and correct the
            problem in order to prevent it from becoming a more
            serious service affecting fault.";
    }
    enum major {
        value 5;
        description
            "The 'major' severity level indicates that a service
            affecting condition has developed and an urgent
            corrective action is required. Such a severity can be
            reported, for example, when there is a severe
            degradation in the capability of the resource
            and its full capability must be restored.";
    }
    enum critical {
        value 6;
        description
            "The 'critical' severity level indicates that a service
            affecting condition has occurred and an immediate
            corrective action is required. Such a severity can be
            reported, for example, when a resource becomes totally
            out of service and its capability must be restored.";
    }
}
description
    "The severity level of the alarm. Note well that value 'clear'
    is not included. If an alarm is cleared or not is a separate
    boolean flag.";
reference
    "ITU Recommendation X.733: Information Technology
    - Open Systems Interconnection
    - System Management: Alarm Reporting Function";
}

typedef severity-with-clear {
    type union {
        type enumeration {
            enum cleared {
```



```
        value 1;
        description
            "The alarm is cleared by the instrumentation.";
    }
}
type severity;
}
description
    "The severity level of the alarm including clear.
    This is used *only* in notifications reporting state changes
    for an alarm.";
}

typedef operator-state {
    type enumeration {
        enum none {
            value 1;
            description
                "The alarm is not being taken care of.";
        }
        enum ack {
            value 2;
            description
                "The alarm is being taken care of. Corrective action not
                taken yet, or failed";
        }
        enum closed {
            value 3;
            description
                "Corrective action taken successfully.";
        }
        enum shelved {
            value 4;
            description
                "Alarm shelved. Alarms in alarms/shelved-alarms/
                MUST be assigned this operator state by the server as
                the last entry in the operator-state-change list.";
        }
        enum un-shelved {
            value 5;
            description
                "Alarm moved back to alarm-list from shelf.
                Alarms 'moved' from /alarms/shelved-alarms/
                to /alarms/alarm-list MUST be assigned this
                state by the server as the last entry in the
                operator-state-change list.";
        }
    }
}
```



```
    }
    description
      "Operator states on an alarm. The 'closed' state indicates
       that an operator considers the alarm being resolved. This
       is separate from the resource alarm clear flag.";
  }

/* Alarm type */

typedef alarm-type-id {
  type identityref {
    base alarm-identity;
  }
  description
    "Identifies an alarm type. The description of the alarm type
     id MUST indicate if the alarm type is abstract or not. An
     abstract alarm type is used as a base for other alarm type ids
     and will not be used as a value for an alarm or be present in
     the alarm inventory.";
}

typedef alarm-type-qualifier {
  type string;
  description
    "If an alarm type can not be fully specified at design time by
     alarm-type-id, this string qualifier is used in addition to
     fully define a unique alarm type.

     The definition of alarm qualifiers is considered being part
     of the instrumentation and out of scope for this module.
     An empty string is used when this is part of a key.";
}

/*
 * Groupings
 */

grouping common-alarm-parameters {
  description
    "Common parameters for an alarm.

     This grouping is used both in the alarm list and in the
     notification representing an alarm state change.";

  leaf resource {
    type resource;
    mandatory true;
    description
```



```
    "The alarming resource. See also 'alt-resource'.
    This could for example be a reference to the alarming
    interface";
}

leaf alarm-type-id {
  type alarm-type-id;
  mandatory true;
  description
    "This leaf and the leaf 'alarm-type-qualifier' together
    provides a unique identification of the alarm type.";
}

leaf alarm-type-qualifier {
  type alarm-type-qualifier;
  description
    "This leaf is used when the 'alarm-type-id' leaf cannot
    uniquely identify the alarm type. Normally, this is not
    the case, and this leaf is the empty string.";
}

leaf-list alt-resource {
  type resource;
  description
    "Used if the alarming resource is available over other
    interfaces. This field can contain SNMP OID's, CIM paths or
    3GPP Distinguished names for example.";
}

list related-alarm {
  key "resource alarm-type-id alarm-type-qualifier";

  description
    "References to related alarms. Note that the related alarm
    might have been removed from the alarm list.";

  leaf resource {
    type leafref {
      path "/alarms/alarm-list/alarm/resource";
      require-instance false;
    }
    description
      "The alarming resource for the related alarm.";
  }
  leaf alarm-type-id {
    type leafref {
      path "/alarms/alarm-list/alarm"
        + "[resource=current()/../resource]"
    }
  }
}
```



```
        + "/alarm-type-id";
        require-instance false;
    }
    description
        "The alarm type identifier for the related alarm.";
}
leaf alarm-type-qualifier {
    type leafref {
        path "/alarms/alarm-list/alarm"
            + "[resource=current()/../resource]"
            + "[alarm-type-id=current()/../alarm-type-id]"
            + "/alarm-type-qualifier";
        require-instance false;
    }
    description
        "The alarm qualifier for the related alarm.";
}
}
leaf-list impacted-resource {
    type resource;
    description
        "Resources that might be affected by this alarm. If the
        system creates an alarm on a resource and also has a mapping
        to other resources that might be impacted, these resources
        can be listed in this leaf-list. In this way the system can
        create one alarm instead of several. For example, if an
        interface has an alarm, the 'impacted-resource' can
        reference the aggregated port channels.";
}
leaf-list root-cause-resource {
    type resource;
    description
        "Resources that are candidates for causing the alarm. If the
        system has a mechanism to understand the candidate root
        causes of an alarm, this leaf-list can be used to list the
        root cause candidate resources. In this way the system can
        create one alarm instead of several. An example might be a
        logging system (alarm resource) that fails, the alarm can
        reference the file-system in the 'root-cause-resource'
        leaf-list. Note that the intended use is not to also send an
        an alarm with the root-cause-resource as alarming resource.
        The root-cause-resource leaf list is a hint and should not
        also generate an alarm for the same problem.";
}
}
}
grouping alarm-state-change-parameters {
    description
```


"Parameters for an alarm state change.

This grouping is used both in the alarm list's status-change list and in the notification representing an alarm state change.";

```
leaf time {
  type yang:date-and-time;
  mandatory true;
  description
    "The time the status of the alarm changed. The value
     represents the time the real alarm state change appeared
     in the resource and not when it was added to the
     alarm list. The /alarm-list/alarm/last-changed MUST be
     set to the same value.";
}
leaf perceived-severity {
  type severity-with-clear;
  mandatory true;
  description
    "The severity of the alarm as defined by X.733. Note
     that this may not be the original severity since the alarm
     may have changed severity.";
  reference
    "ITU Recommendation X.733: Information Technology
     - Open Systems Interconnection
     - System Management: Alarm Reporting Function";
}
leaf alarm-text {
  type alarm-text;
  mandatory true;
  description
    "A user friendly text describing the alarm state change.";
  reference
    "ITU Recommendation X.733: Information Technology
     - Open Systems Interconnection
     - System Management: Alarm Reporting Function";
}
}

grouping operator-parameters {
  description
    "This grouping defines parameters that can
     be changed by an operator";
  leaf time {
    type yang:date-and-time;
    mandatory true;
    description
```



```
        "Timestamp for operator action on alarm.";
    }
    leaf operator {
        type string;
        mandatory true;
        description
            "The name of the operator that has acted on this
            alarm.";
    }
    leaf state {
        type operator-state;
        mandatory true;
        description
            "The operator's view of the alarm state.";
    }
    leaf text {
        type string;
        description
            "Additional optional textual information provided by
            the operator.";
    }
}

grouping resource-alarm-parameters {
    description
        "Alarm parameters that originates from the resource view.";
    leaf is-cleared {
        type boolean;
        mandatory true;
        description
            "Indicates the current clearance state of the alarm. An
            alarm might toggle from active alarm to cleared alarm and
            back to active again.";
    }

    leaf last-changed {
        type yang:date-and-time;
        mandatory true;
        description
            "A timestamp when the alarm status was last changed. Status
            changes are changes to 'is-cleared', 'perceived-severity',
            and 'alarm-text'.";
    }

    leaf perceived-severity {
        type severity;
        mandatory true;
        description
```



```
    "The last severity of the alarm.

    If an alarm was raised with severity 'warning', but later
    changed to 'major', this leaf will show 'major'.";
}

leaf alarm-text {
  type alarm-text;
  mandatory true;
  description
    "The last reported alarm text. This text should contain
    information for an operator to be able to understand
    the problem and how to resolve it.";
}

list status-change {
  if-feature alarm-history;
  key time;
  min-elements 1;
  description
    "A list of status change events for this alarm.

    The entry with latest time-stamp in this list MUST
    correspond to the leafs 'is-cleared', 'perceived-severity'
    and 'alarm-text' for the alarm. The time-stamp for that
    entry MUST be equal to the 'last-changed' leaf.

    This list is ordered according to the timestamps of
    alarm state changes. The last item corresponds to the
    latest state change.

    The following state changes creates an entry in this
    list:
    - changed severity (warning, minor, major, critical)
    - clearance status, this also updates the 'is-cleared'
      leaf
    - alarm text update";

  uses alarm-state-change-parameters;
}

/*
 * The /alarms data tree
 */

container alarms {
```



```
description
  "The top container for this module";
container control {
  description
    "Configuration to control the alarm behaviour.";
  leaf max-alarm-status-changes {
    type union {
      type uint16;
      type enumeration {
        enum infinite {
          description
            "The status change entries are accumulated
            infinitely.";
        }
      }
    }
    default 32;
    description
      "The status-change entries are kept in a circular list
      per alarm. When this number is exceeded, the oldest
      status change entry is automatically removed. If the
      value is 'infinite', the status change entries are
      accumulated infinitely.";
  }
}

leaf notify-status-changes {
  type boolean;
  default false;
  description
    "This leaf controls whether notifications are sent on all
    alarm status updates, e.g., updated perceived-severity or
    alarm-text. By default the notifications are only sent
    when a new alarm is raised, re-raised after being cleared
    and when an alarm is cleared.";
}

container alarm-shelving {
  if-feature alarm-shelving;
  description
    "This list is used to shelve alarms. The server will move
    any alarms corresponding to the shelving criteria from the
    alarms/alarm-list/alarm list to the
    alarms/shelved-alarms/shelved-alarm list. It will also
    stop sending notifications for the shelved alarms. The
    conditions in the shelf criteria are logically ANDed.
    When the shelving criteria is deleted or changed, the
    non-matching alarms MUST appear in the
    alarms/alarm-list/alarm list according to the real state.
    This means that the instrumentation MUST maintain states
```



```
    for the shelved alarms. Alarms that match the criteria
    shall have an operator-state 'shelved.'";
list shelf {
  key shelf-name;
  leaf shelf-name {
    type string;
    description
      "An arbitrary name for the alarm shelf.";
  }
  description
    "Each entry defines the criteria for shelving alarms.
    Criterias are ANDed.";

  leaf resource {
    type resource;
    description
      "Shelve alarms for this resource.";
  }
  leaf alarm-type-id {
    type alarm-type-id;
    description
      "Shelve alarms for this alarm type identifier.";
  }
  leaf alarm-type-qualifier {
    type alarm-type-qualifier;
    description
      "Shelve alarms for this alarm type qualifier.";
  }
  leaf description {
    type string;
    description
      "An optional textual description of the shelf. This
      description should include the reason for shelving
      these alarms.";
  }
}
}
}

container alarm-inventory {
  config false;
  description
    "This list contains all possible alarm types for the system.
    If the system knows for wich resources a a specific alarm
    type can appear, this is also identified in the inventory.
    The list also tells if each alarm type has a corresponding
    clear state. The inventory shall only contain concrete
    alarm types.
```


The alarm inventory MUST be updated by the system when new alarms can appear. This can be the case when installing new software modules or inserting new card types. A notification 'alarm-inventory-changed' is sent when the inventory is changed.";

```
list alarm-type {
  key "alarm-type-id alarm-type-qualifier";
  description
    "An entry in this list defines a possible alarm.";
  leaf alarm-type-id {
    type alarm-type-id;
    mandatory true;
    description
      "The statically defined alarm type identifier for this
       possible alarm.";
  }
  leaf alarm-type-qualifier {
    type alarm-type-qualifier;
    description
      "The optionally dynamically defined alarm type identifier
       for this possible alarm.";
  }
  leaf-list resource {
    type string;
    description
      "Optionally, specifies for which resources the alarm type
       is valid. This string is for human consumption but
       SHOULD refer to paths in the model.";
  }
  leaf has-clear {
    type boolean;
    mandatory true;
    description
      "This leaf tells the operator if the alarm will be
       cleared when the correct corrective action has been
       taken. Implementations SHOULD strive for detecting the
       cleared state for all alarm types. If this leaf is
       true, the operator can monitor the alarm until it
       becomes cleared after the corrective action has been
       taken. If this leaf is false the operator needs to
       validate that the alarm is not longer active using other
       mechanisms. Alarms can lack a corresponding clear due
       to missing instrumentation or that there is no logical
       corresponding clear state.";
  }
  leaf description {
    type string;
```



```
        mandatory true;
        description
            "A description of the possible alarm. It SHOULD include
            information on possible underlying root causes and
            corrective actions.";
    }
}
}

container summary {
    config false;
    description
        "This container gives a summary of number of alarms
        and shelved alarms";
    list alarm-summary {
        key severity;
        description
            "A global summary of all alarms in the system.";
        leaf severity {
            type severity;
            description
                "Alarm summary for this severity level.";
        }
        leaf total {
            type yang:gauge32;
            description
                "Total number of alarms of this severity level.";
        }
        leaf cleared {
            type yang:gauge32;
            description
                "For this severity level, the number of alarms that are
                cleared.";
        }
        leaf cleared-not-closed {
            if-feature operator-actions;
            type yang:gauge32;
            description
                "For this severity level, the number of alarms that are
                cleared but not closed.";
        }
        leaf cleared-closed {
            if-feature operator-actions;
            type yang:gauge32;
            description
                "For this severity level, the number of alarms that are
                cleared and closed.";
        }
    }
}
```



```
leaf not-cleared-closed {
  if-feature operator-actions;
  type yang:gauge32;
  description
    "For this severity level, the number of alarms that are
    not cleared but closed.";
}
leaf not-cleared-not-closed {
  if-feature operator-actions;
  type yang:gauge32;
  description
    "For this severity level, the number of alarms that are
    not cleared and not closed.";
}
}
leaf shelves-active {
  if-feature alarm-shelving;
  type empty;
  description
    "This is a hint to the operator that there are active
    alarm shelves. This leaf MUST exist if the
    alarms/shelved-alarms/number-of-shelved-alarms is > 0.";
}
}
container alarm-list {
  config false;
  description
    "The alarms in the system.";
  leaf number-of-alarms {
    type yang:gauge32;
    description
      "This object shows the total number of
      alarms in the system, i.e., the total number
      of entries in the alarm list.";
  }
}
leaf last-changed {
  type yang:date-and-time;
  description
    "A timestamp when the alarm list was last
    changed. The value can be used by a manager to
    initiate an alarm resynchronization procedure.";
}
}
list alarm {
  key "resource alarm-type-id alarm-type-qualifier";
```


`description`

"The list of alarms. Each entry in the list holds one alarm for a given alarm type and resource.

An alarm can be updated from the underlying resource or by the user. The following leafs are maintained by the resource: `is-cleared`, `last-change`, `perceived-severity`, and `alarm-text`. An operator can change: `operator-state` and `operator-text`.

Entries appear in the alarm list the first time an alarm becomes active for a given alarm-type and resource. Entries do not get deleted when the alarm is cleared, this is a boolean state in the alarm.

Alarm entries are removed, purged, from the list by an explicit purge action. For example, delete all alarms that are cleared and in closed operator-state that are older than 24 hours. Systems may also remove alarms based on locally configured policies which is out of scope for this module.";

```
leaf time-created {
  type yang:date-and-time;
  mandatory true;
  description
    "The time-stamp when this alarm entry was created. This
    represents the first time the alarm appeared, it can
    also represent that the alarm re-appeared after a purge.
    Further state-changes of the same alarm does not change
    this leaf, these changes will update the 'last-changed'
    leaf.";
}

uses common-alarm-parameters;
uses resource-alarm-parameters;
list operator-state-change {
  if-feature operator-actions;
  key time;
  description
    "This list is used by operators to indicate
    the state of human intervention on an alarm.
    For example, if an operator has seen an alarm,
    the operator can add a new item to this list indicating
    that the alarm is acknowledged.";
  uses operator-parameters;
}

action set-operator-state {
  if-feature operator-actions;
```



```
description
  "This is a means for the operator to indicate
  the level of human intervention on an alarm.";
input {
  leaf state {
    type operator-state;
    mandatory true;
    description
      "Set this operator state.";
  }
  leaf text {
    type string;
    description
      "Additional optional textual information.";
  }
}
}
}

container shelved-alarms {
  if-feature alarm-shelving;
  config false;
  description
    "The shelved alarms. Alarms appear here if they match the
    criterias in /alarms/control/alarm-shelving. This list does
    not generate any notifications. The list represents alarms
    that are considered not relevant by the operator. Alarms in
    this list have an operator-state of 'shelved'. This can not
    be changed.";
  leaf number-of-shelved-alarms {
    type yang:gauge32;
    description
      "This object shows the total number of currently
      alarms, i.e., the total number of entries
      in the alarm list.";
  }

  leaf alarm-shelf-last-changed {
    type yang:date-and-time;
    description
      "A timestamp when the shelved alarm list was last
      changed. The value can be used by a manager to
      initiate an alarm resynchronization procedure.";
  }

  list shelved-alarm {
    key "resource alarm-type-id alarm-type-qualifier";
```



```
    description
      "The list of shelved alarms. Each entry in the list holds
      one alarm for a given alarm type and resource. An alarm
      can be updated from the underlying resource or by the
      user. These changes are reflected in different lists
      below the corresponding alarm.";

    uses common-alarm-parameters;
    uses resource-alarm-parameters;

    list operator-state-change {
      if-feature operator-actions;
      key time;
      description
        "This list is used by operators to indicate
        the state of human intervention on an alarm.
        For example, if an operator has seen an alarm,
        the operator can add a new item to this list indicating
        that the alarm is acknowledged.";
      uses operator-parameters;
    }
  }
}

/*
 * Operations
 */

rpc compress-alarms {
  if-feature alarm-history;
  description
    "This operation requests the server to compress entries in the
    alarm list by removing all but the latest state change for all
    alarms. Conditions in the input are logically ANDed. If no
    input condition is given, all alarms are compressed.";
  input {
    leaf resource {
      type leafref {
        path "/alarms/alarm-list/alarm/resource";
        require-instance false;
      }
      description
        "Compress the alarms with this resource.";
    }
    leaf alarm-type-id {
      type leafref {
        path "/alarms/alarm-list/alarm/alarm-type-id";
      }
    }
  }
}
```



```
    }
    description
      "Compress alarms with this alarm-type-id.";
  }
  leaf alarm-type-qualifier {
    type leafref {
      path "/alarms/alarm-list/alarm/alarm-type-qualifier";
    }
    description
      "Compress the alarms with this alarm-type-qualifier.";
  }
}
output {
  leaf compressed-alarms {
    type uint32;
    description
      "Number of compressed alarm entries.";
  }
}
}

grouping filter-input {
  description
    "Grouping to specify a filter construct on alarm information.";
  leaf alarm-status {
    type enumeration {
      enum any {
        description
          "Ignore alarm clearance status.";
      }
      enum cleared {
        description
          "Filter cleared alarms.";
      }
      enum not-cleared {
        description
          "Filter not cleared alarms.";
      }
    }
  }
  mandatory true;
  description
    "The clearance status of the alarm.";
}

container older-than {
  presence "Age specification";
  description
    "Matches the 'last-status-change' leaf in the alarm.";
}
```



```
choice age-spec {
  description
    "Filter using date and time age.";
  case seconds {
    leaf seconds {
      type uint16;
      description
        "Seconds part";
    }
  }
  case minutes {
    leaf minutes {
      type uint16;
      description
        "Minute part";
    }
  }
  case hours {
    leaf hours {
      type uint16;
      description
        "Hours part.";
    }
  }
  case days {
    leaf days {
      type uint16;
      description
        "Day part";
    }
  }
  case weeks {
    leaf weeks {
      type uint16;
      description
        "Week part";
    }
  }
}
}

container severity {
  presence "Severity filter";
  choice sev-spec {
    description
      "Filter based on severity level.";
    leaf below {
      type severity;
      description
```



```
        "Severity less than this leaf.";
    }
    leaf is {
        type severity;
        description
            "Severity level equal this leaf.";
    }
    leaf above {
        type severity;
        description
            "Severity level higher than this leaf.";
    }
}
description
    "Filter based on severity.";
}
container operator-state-filter {
    if-feature operator-actions;
    presence "Operator state filter";
    leaf state {
        type operator-state;
        description
            "Filter on operator state.";
    }
    leaf user {
        type string;
        description
            "Filter based on which operator.";
    }
}
description
    "Filter based on operator state.";
}
}

rpc purge-alarms {
    description
        "This operation requests the server to delete entries from the
        alarm list according to the supplied criteria. Typically it
        can be used to delete alarms that are in closed operator state
        and older than a specified time. The number of purged alarms
        is returned as an output parameter";
    input {
        uses filter-input;
    }
    output {
        leaf purged-alarms {
            type uint32;
            description
```



```
        "Number of purged alarms.";
    }
}

/*
 * Notifications
 */

notification alarm-notification {
    description
        "This notification is used to report a state change for an
        alarm. The same notification is used for reporting a newly
        raised alarm, a cleared alarm or changing the text and/or
        severity of an existing alarm.";

    uses common-alarm-parameters;
    uses alarm-state-change-parameters;
}

notification alarm-inventory-changed {
    description
        "This notification is used to report that the list of possible
        alarms has changed. This can happen when for example if a new
        software module is installed, or a new physical card is
        inserted";
}

notification operator-action {
    if-feature operator-actions;
    description
        "This notification is used to report that an operator
        acted upon an alarm.";

    leaf resource {
        type leafref {
            path "/alarms/alarm-list/alarm/resource";
            require-instance false;
        }
        description
            "The alarming resource.";
    }
    leaf alarm-type-id {
        type leafref {
            path "/alarms/alarm-list/alarm"
                + "[resource=current()/../resource]"
                + "/alarm-type-id";
            require-instance false;
        }
    }
}
```



```
    }
    description
      "The alarm type identifier for the alarm.";
  }
  leaf alarm-type-qualifier {
    type leafref {
      path "/alarms/alarm-list/alarm"
        + "[resource=current()/../resource]"
        + "[alarm-type-id=current()/../alarm-type-id]"
        + "/alarm-type-qualifier";
      require-instance false;
    }
    description
      "The alarm qualifier for the alarm.";
  }
  uses operator-parameters;
}
```

<CODE ENDS>

8. X.733 Alarm Mapping Data Model

Many alarm management systems are based on the X.733 alarm standard. This YANG module allows a mapping from alarm types to X.733 event-type and probable-cause.

The module augments the alarm inventory, the alarm list and the alarm notification with X.733 parameters.

The module also supports a feature whereby the alarm manager can configure the mapping. This might be needed when the default mapping provided by the system is in conflict with other systems or not considered good.

9. X.733 Alarm Mapping YANG Module

This YANG module references [[X.736](#)].

```
<CODE BEGINS> file "ietf-alarms-x733@2017-05-08.yang"
module ietf-alarms-x733 {
  yang-version 1.1;
  namespace "urn:ietf:params:xml:ns:yang:ietf-alarms-x733";
  prefix x733;

  import ietf-alarms {
    prefix al;
  }
}
```


organization

"IETF NETMOD (NETCONF Data Modeling Language) Working Group";

contact

"WG Web: <<http://tools.ietf.org/wg/netmod/>>

WG List: <<mailto:netmod@ietf.org>>

Editor: Stefan Vallin
<<mailto:stefan@wallan.se>>

Editor: Martin Bjorklund
<<mailto:mbj@tail-f.com>>";

description

"This module augments the ietf-alarms module with X.733 mapping information. The following structures are augmented with event type and probable cause:

- 1) alarm inventory: all possible alarms.
- 2) alarm: every alarm in the system.
- 3) alarm notification: notifications indicating alarm state changes.

The module also optionally allows the alarm management system to configure the mapping. The mapping does not include a corresponding specific problem value. The recommendation is to use alarm-type-qualifier which serves the same purpose.";

reference

"ITU Recommendation X.733: Information Technology
- Open Systems Interconnection
- System Management: Alarm Reporting Function";

revision 2017-05-08 {

description

"Initial revision.";

reference

"RFC XXXX: YANG Alarm Module";

}

/*

* Features

*/

feature configure-x733-mapping {

description

"The system supports configurable X733 mapping from alarm type to event type and probable cause.";

}


```
/*
 * Typedefs
 */

typedef event-type {
  type enumeration {
    enum other {
      value 1;
      description
        "None of the below.";
    }
    enum communications-alarm {
      value 2;
      description
        "An alarm of this type is principally associated with the
        procedures and/or processes required to convey
        information from one point to another.";
      reference
        "ITU Recommendation X.733: Information Technology
        - Open Systems Interconnection
        - System Management: Alarm Reporting Function";
    }
    enum quality-of-service-alarm {
      value 3;
      description
        "An alarm of this type is principally associated with a
        degradation in the quality of a service.";
      reference
        "ITU Recommendation X.733: Information Technology
        - Open Systems Interconnection
        - System Management: Alarm Reporting Function";
    }
    enum processing-error-alarm {
      value 4;
      description
        "An alarm of this type is principally associated with a
        software or processing fault.";
      reference
        "ITU Recommendation X.733: Information Technology
        - Open Systems Interconnection
        - System Management: Alarm Reporting Function";
    }
    enum equipment-alarm {
      value 5;
      description
        "An alarm of this type is principally associated with an
        equipment fault.";
      reference

```



```
        "ITU Recommendation X.733: Information Technology
          - Open Systems Interconnection
          - System Management: Alarm Reporting Function";
    }
enum environmental-alarm {
    value 6;
    description
        "An alarm of this type is principally associated with a
        condition relating to an enclosure in which the equipment
        resides.";
    reference
        "ITU Recommendation X.733: Information Technology
          - Open Systems Interconnection
          - System Management: Alarm Reporting Function";
}
enum integrity-violation {
    value 7;
    description
        "An indication that information may have been illegally
        modified, inserted or deleted.";
    reference
        "ITU Recommendation X.736: Information Technology
          - Open Systems Interconnection
          - System Management: Security Alarm Reporting Function";
}
enum operational-violation {
    value 8;
    description
        "An indication that the provision of the requested service
        was not possible due to the unavailability, malfunction or
        incorrect invocation of the service.";
    reference
        "ITU Recommendation X.736: Information Technology
          - Open Systems Interconnection
          - System Management: Security Alarm Reporting Function";
}
enum physical-violation {
    value 9;
    description
        "An indication that a physical resource has been violated
        in a way that suggests a security attack.";
    reference
        "ITU Recommendation X.736: Information Technology
          - Open Systems Interconnection
          - System Management: Security Alarm Reporting Function";
}
enum security-service-or-mechanism-violation {
    value 10;
```



```
    description
      "An indication that a security attack has been detected by
       a security service or mechanism.";
    reference
      "ITU Recommendation X.736: Information Technology
       - Open Systems Interconnection
       - System Management: Security Alarm Reporting Function";
  }
  enum time-domain-violation {
    value 11;
    description
      "An indication that an event has occurred at an unexpected
       or prohibited time.";
    reference
      "ITU Recommendation X.736: Information Technology
       - Open Systems Interconnection
       - System Management: Security Alarm Reporting Function";
  }
}
description
  "The event types as defined by X.733 and X.736. The use of the
   term 'event' is a bit confusing. In an alarm context these
   are top level alarm types.";
}

/*
 * Groupings
 */

grouping x733-alarm-parameters {
  description
    "Common X.733 parameters for alarms.";

  leaf event-type {
    type event-type;
    description
      "The X.733/X.736 event type for this alarm.";
  }
  leaf probable-cause {
    type uint32;
    description
      "The X.733 probable cause for this alarm.";
  }
}

grouping x733-alarm-definition-parameters {
  description
    "Common X.733 parameters for alarm definitions.";
```



```
leaf event-type {
  type event-type;
  description
    "The alarm type has this X.733/X.736 event type.";
}
leaf probable-cause {
  type uint32;
  description
    "The alarm type has this X.733 probable cause value.
    This module defines probable cause as an integer
    and not as an enumeration. The reason being that the
    primary use of probable cause is in the management
    application if it is based on the X.733 standard.
    However, most management applications have their own
    defined enum definitions and merging enums from
    different systems might create conflicts. By using
    a configurable uint32 the system can be configured
    to match the enum values in the manager.";
}
}
}
/*
 * Add X.733 parameters to the alarm definitions, alarms,
 * and notification.
 */
augment "/al:alarms/al:alarm-inventory/al:alarm-type" {
  description
    "Augment X.733 mapping information to the alarm inventory.";

  uses x733-alarm-definition-parameters;
}

augment "/al:alarms/al:control" {
  description
    "Add X.733 mapping capabilities. ";
  list x733-mapping {
    if-feature configure-x733-mapping;
    key "alarm-type-id alarm-type-qualifier-match";
    description
      "This list allows a management application to control the
      X.733 mapping for all alarm types in the system. Any entry
      in this list will allow the alarm manager to over-ride the
      default X.733 mapping in the system and the final mapping
      will be shown in the alarm-inventory";

    leaf alarm-type-id {
      type al:alarm-type-id;
    }
  }
}
```



```
        description
            "Map the alarm type with this alarm type identifier.";
    }
    leaf alarm-type-qualifier-match {
        type string;
        description
            "A W3C regular expression that is used when mapping an
            alarm type and alarm-type-qualifier to X.733 parameters.";
    }

    uses x733-alarm-definition-parameters;
}

augment "/al:alarms/al:alarm-list/al:alarm" {
    description
        "Augment X.733 information to the alarm.";

    uses x733-alarm-parameters;
}

augment "/al:alarms/al:shelved-alarms/al:shelved-alarm" {
    description
        "Augment X.733 information to the alarm.";

    uses x733-alarm-parameters;
}

augment "/al:alarm-notification" {
    description
        "Augment X.733 information to the alarm notification.";

    uses x733-alarm-parameters;
}
}

<CODE ENDS>
```

10. Security Considerations

None.

11. Acknowledgements

The author wishes to thank Viktor Leijon and Johan Nordlander for their valuable input on forming the alarm model.

12. References

12.1. Normative References

- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), DOI 10.17487/RFC2119, March 1997, <<http://www.rfc-editor.org/info/rfc2119>>.
- [RFC7950] Bjorklund, M., Ed., "The YANG 1.1 Data Modeling Language", [RFC 7950](#), DOI 10.17487/RFC7950, August 2016, <<http://www.rfc-editor.org/info/rfc7950>>.

12.2. Informative References

- [ALARMIRP] 3GPP, "Telecommunication management; Fault Management; Part 2: Alarm Integration Reference Point (IRP): Information Service (IS)", 3GPP TS 32.111-2 3.4.0, March 2005.
- [ALARMSEM] Wallin, S., Leijon, V., Nordlander, J., and N. Bystedt, "The semantics of alarm definitions: enabling systematic reasoning about alarms. International Journal of Network Management, Volume 22, Issue 3, John Wiley and Sons, Ltd, <http://dx.doi.org/10.1002/nem.800>", March 2012.
- [EEMUA] EEMUA Publication No. 191 Engineering Equipment and Materials Users Association, London, 2 edition., "Alarm Systems: A Guide to Design, Management and Procurement.", 2007.
- [ISA182] International Society of Automation, ISA, "ANSI/ISA-18.2-2009 Management of Alarm Systems for the Process Industries", 2009.
- [RFC3877] Chisholm, S. and D. Romascanu, "Alarm Management Information Base (MIB)", [RFC 3877](#), DOI 10.17487/RFC3877, September 2004, <<http://www.rfc-editor.org/info/rfc3877>>.
- [X.733] International Telecommunications Union, "Information Technology - Open Systems Interconnection - Systems Management: Alarm Reporting Function", ITU-T Recommendation X.733, 1992.

[X.736] International Telecommunications Union, "Information Technology - Open Systems Interconnection - Systems Management: Security alarm reporting function", ITU-T Recommendation X.736, 1992.

[Appendix A](#). Enterprise-specific Alarm-Types Example

This example shows how to define alarm-types in an enterprise specific module. In this case "xyz" has chosen to define top level identities according to X.733 event types.

```
module example-xyz-alarms {
  namespace "urn:example:xyz-alarms";
  prefix xyz-al;

  import ietf-alarms {
    prefix al;
  }

  identity xyz-alarms {
    base al:alarm-identity;
  }

  identity communications-alarm {
    base xyz-alarms;
  }
  identity quality-of-service-alarm {
    base xyz-alarms;
  }
  identity processing-error-alarm {
    base xyz-alarms;
  }
  identity equipment-alarm {
    base xyz-alarms;
  }
  identity environmental-alarm {
    base xyz-alarms;
  }

  // communications alarms
  identity link-alarm {
    base communications-alarm;
  }

  // QoS alarms
  identity high-jitter-alarm {
    base quality-of-service-alarm;
  }
}
```

[Appendix B](#). Alarm Inventory Example

This shows an alarm inventory, it shows one alarm type defined only with the identifier, and another dynamically configured. In the latter case a digital input has been connected to a smoke-detector, therefore the 'alarm-type-qualifier' is set to "smoke-detector" and the 'alarm-type-identity' to "environmental-alarm".


```

<alarms xmlns="urn:ietf:params:xml:ns:yang:ietf-alarms"
  xmlns:xyz-al="urn:example:xyz-alarms">
  <alarm-inventory>
    <alarm-type>
      <alarm-type-id>xyz-al:link-alarm</alarm-type-id>
      <alarm-type-qualifier/>
      <has-clear>true</has-clear>
      <description>
        Link failure, operational state down but admin state up
      </description>
    </alarm-type>
    <alarm-type>
      <alarm-type-id>xyz-al:environmental-alarm</alarm-type-id>
      <alarm-type-qualifier>smoke-alarm</alarm-type-qualifier>
      <has-clear>true</has-clear>
      <description>
        Connected smoke detector to digital input
      </description>
    </alarm-type>
  </alarm-inventory>
</alarms>

```

[Appendix C](#). Alarm List Example

In this example we show an alarm that has toggled [major, clear, major]. An operator has acknowledged the alarm.

```

<alarms xmlns="urn:ietf:params:xml:ns:yang:ietf-alarms"
  xmlns:xyz-al="urn:example:xyz-alarms"
  xmlns:dev="urn:example:device">
  <alarm-list>
    <number-of-alarms>1</number-of-alarms>
    <last-changed>2015-04-08T08:39:50.00Z</last-changed>

    <alarm>
      <resource>
        /dev:interfaces/dev:interface[name='FastEthernet1/0']
      </resource>
      <alarm-type-id>xyz-al:link-alarm</alarm-type-id>
      <alarm-type-qualifier></alarm-type-qualifier>

      <time-created>2015-04-08T08:39:50.00Z</time-created>
      <is-cleared>>false</is-cleared>
      <alt-resource>1.3.6.1.2.1.2.2.1.1.17</alt-resource>
      <last-changed>2015-04-08T08:39:40.00Z</last-changed>
      <perceived-severity>major</perceived-severity>
      <alarm-text>

```



```
    Link operationally down but administratively up
  </alarm-text>
  <status-change>
    <time>2015-04-08T08:39:40.00Z</time>
    <perceived-severity>major</perceived-severity>
    <alarm-text>
      Link operationally down but administratively up
    </alarm-text>
  </status-change>
  <status-change>
    <time>2015-04-08T08:30:00.00+00:00</time>
    <perceived-severity>cleared</perceived-severity>
    <alarm-text>
      Link operationally up and administratively up
    </alarm-text>
  </status-change>
  <status-change>
    <time>2015-04-08T08:20:10.00+00:00</time>
    <perceived-severity>major</perceived-severity>
    <alarm-text>
      Link operationally down but administratively up
    </alarm-text>
  </status-change>
  <operator-state-change>
    <time>2015-04-08T08:39:50.00Z</time>
    <state>ack</state>
    <operator>joe</operator>
    <text>Will investigate, ticket TR764999</text>
  </operator-state-change>
</alarm>
</alarm-list>
</alarms>
```

[Appendix D](#). Alarm Shelving Example

This example shows how to shelf alarms. We shelf alarms related to the smoke-detectors since they are being installed and tested. We also shelf all alarms from FastEthernet1/0.


```

<alarms xmlns="urn:ietf:params:xml:ns:yang:ietf-alarms"
  xmlns:xyz-al="urn:example:xyz-alarms"
  xmlns:dev="urn:example:device">
  <control>
    <alarm-shelving>
      <shelf>
        <shelf-name>FE10</shelf-name>
        <resource>
          /dev:interfaces/dev:interface[name='FastEthernet1/0']
        </resource>
      </shelf>
      <shelf>
        <shelf-name>detectortest</shelf-name>
        <alarm-type-id>xyz-al:environmental-alarm</alarm-type-id>
        <alarm-type-qualifier>smoke-alarm</alarm-type-qualifier>
      </shelf>
    </alarm-shelving>
  </control>
</alarms>

```

[Appendix E](#). X.733 Mapping Example

This example shows how to map a dynamic alarm type (alarm-type-identity=environmental-alarm, alarm-type-qualifier=smoke-alarm) to the corresponding X.733 event-type and probable cause parameters.

```

<alarms xmlns="urn:ietf:params:xml:ns:yang:ietf-alarms"
  xmlns:xyz-al="urn:example:xyz-alarms">
  <control>
    <x733-mapping
      xmlns="urn:ietf:params:xml:ns:yang:ietf-alarms-x733">
      <alarm-type-id>xyz-al:environmental-alarm</alarm-type-id>
      <alarm-type-qualifier-match>
        smoke-alarm
      </alarm-type-qualifier-match>
      <event-type>quality-of-service-alarm</event-type>
      <probable-cause>777</probable-cause>
    </x733-mapping>
  </control>
</alarms>

```

Authors' Addresses

Stefan Vallin
Stefan Vallin AB

Email: stefan@wallan.se

Martin Bjorklund
Cisco

Email: mbj@tail-f.com