

dnsop  
Internet-Draft  
Updates: [4034](#), [5155](#) (if approved)  
Intended status: Standards Track  
Expires: 27 May 2021

P. van Dijk  
PowerDNS  
23 November 2020

NSEC(3) TTLs and NSEC Aggressive Use  
draft-vandijk-dnsop-nsec-ttl-00

## Abstract

Due to a combination of unfortunate wording in earlier documents, aggressive use of NSEC(3) records may deny names far beyond the intended lifetime of a denial. This document changes the definition of the NSEC(3) TTL to correct that situation.

## Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <https://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on 27 May 2021.

## Copyright Notice

Copyright (c) 2020 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<https://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the [Trust Legal Provisions](#) and are provided without warranty as described in the Simplified BSD License.

Internet-Draft

nsec-ttl

November 2020

## Table of Contents

<a href="#">1.</a>	Introduction . . . . .	<a href="#">2</a>
<a href="#">2.</a>	Document work . . . . .	<a href="#">3</a>
<a href="#">3.</a>	Conventions and Definitions . . . . .	<a href="#">4</a>
<a href="#">4.</a>	NSEC(3) TTL changes . . . . .	<a href="#">4</a>
<a href="#">4.1.</a>	In <a href="#">RFC4034</a> . . . . .	<a href="#">4</a>
<a href="#">4.2.</a>	In <a href="#">RFC5155</a> . . . . .	<a href="#">4</a>
<a href="#">4.3.</a>	Zone operator guidance . . . . .	<a href="#">4</a>
<a href="#">5.</a>	Security Considerations . . . . .	<a href="#">5</a>
<a href="#">6.</a>	Implementation Status . . . . .	<a href="#">5</a>
<a href="#">7.</a>	IANA Considerations . . . . .	<a href="#">5</a>
<a href="#">8.</a>	Acknowledgements . . . . .	<a href="#">5</a>
<a href="#">9.</a>	Normative References . . . . .	<a href="#">5</a>
<a href="#">10.</a>	Informative References . . . . .	<a href="#">6</a>
<a href="#">Appendix A.</a>	Document history . . . . .	<a href="#">6</a>
	Author's Address . . . . .	<a href="#">6</a>

[1.](#) Introduction

[RFC editor: please remove this block before publication.]

Earlier notes on this:

- \* <https://indico.dns-oarc.net/event/29/sessions/98/#20181013>  
(<https://indico.dns-oarc.net/event/29/sessions/98/#20181013>)
- \* <https://lists.dns-oarc.net/pipermail/dns-operations/2018-April/thread.html#17420> (<https://lists.dns-oarc.net/pipermail/dns-operations/2018-April/thread.html#17420>)
- \* <https://lists.dns-oarc.net/pipermail/dns-operations/2018-March/017416.html> (<https://lists.dns-oarc.net/pipermail/dns-operations/2018-March/017416.html>)

]

[RFC2308] defines that the SOA TTL to be used in negative answers (NXDOMAIN, NoData NOERROR) is

| the minimum of the MINIMUM field of the SOA record and the TTL of  
| the SOA itself

Thus, if the TTL of the SOA in the zone is lower than the SOA MINIMUM value (the last number in a SOA record), the negative TTL for that zone is lower than the SOA MINIMUM value.

However, [\[RFC4034\] section 4](#) has this unfortunate text:

van Dijk

Expires 27 May 2021

[Page 2]

---

Internet-Draft

nsec-ttl

November 2020

| The NSEC RR SHOULD have the same TTL value as the SOA minimum TTL  
| field. This is in the spirit of negative caching ([\[RFC2308\]](#)).

This text, while referring to [RFC2308](#), can cause NSEC records to have much higher TTLs than the appropriate negative TTL for a zone. [\[RFC5155\]](#) contains equivalent text.

[RFC8198] [section 5.4](#) tries to correct this:

| [Section 5 of \[RFC2308\]](#) also states that a negative cache entry TTL  
| is taken from the minimum of the SOA.MINIMUM field and SOA's TTL.  
| This can be less than the TTL of an NSEC or NSEC3 record, since  
| their TTL is equal to the SOA.MINIMUM field (see [\[RFC4035\]](#),  
| [Section 2.3](#) and [\[RFC5155\], Section 3](#)).

| A resolver that supports aggressive use of NSEC and NSEC3 SHOULD  
| reduce the TTL of NSEC and NSEC3 records to match the SOA.MINIMUM  
| field in the authority section of a negative response, if  
| SOA.MINIMUM is smaller.

But the NSEC(3) RRs should, per [RFC4034](#), already be at the MINIMUM TTL, which means this advice would never actually change the TTL used for the NSEC(3) RRs.

As a concrete example, the ".com" SOA currently looks like this:

```
"com. 900 IN SOA a.gtld-servers.net. nstld.verisign-grs.com.  
1606158464 1800 900 604800 86400"
```

The SOA record has a 900 second TTL, and a 86400 MINIMUM TTL. Negative responses from this zone have a 900 second TTL, but the NSEC3 records in those negative responses have a 86400 TTL. If a resolver were to use those NSEC3s aggressively, they would be considered valid for a day, instead of the intended 15 minutes. (Note that, because .com uses opt-out NSEC3, such aggressive use would not in fact apply to this zone - it is merely used as a very

visible example here.)

## 2. Document work

This document lives on GitHub (<https://github.com/PowerDNS/draft-dnsop-nsec-ttl>); proposed text and editorial changes are very much welcomed there, but any functional changes should always first be discussed on the IETF DNSOP WG mailing list.

## 3. Conventions and Definitions

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "NOT RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [BCP 14](#) [[RFC2119](#)] [[RFC8174](#)] when, and only when, they appear in all capitals, as shown here.

## 4. NSEC(3) TTL changes

### 4.1. In [RFC4034](#)

Where [[RFC4034](#)] says:

```
| The NSEC RR SHOULD have the same TTL value as the SOA minimum TTL  
| field. This is in the spirit of negative caching ([RFC2308]).
```

This is updated to say:

```
| The NSEC RR MUST have the same TTL value as the minimum of the  
| MINIMUM field of the SOA record and the TTL of the SOA itself.  
| This matches the definition of the TTL for negative responses in  
| [RFC2308].
```

### 4.2. In [RFC5155](#)

Where [[RFC5155](#)] says:

```
| The NSEC3 RR SHOULD have the same TTL value as the SOA minimum TTL
```

| field. This is in the spirit of negative caching [[RFC2308](#)].

This is updated to say:

| The NSEC3 RR MUST have the same TTL value as the minimum of the  
| MINIMUM field of the SOA record and the TTL of the SOA itself.  
| This matches the definition of the TTL for negative responses in  
| [[RFC2308](#)].

#### [4.3.](#) Zone operator guidance

If signers & DNS servers for a zone cannot immediately be updated to conform to this document, zone operators are encouraged to consider setting their SOA record TTL and the SOA MINIMUM field to the same value. That way, the TTL used for aggressive NSEC use matches the SOA TTL for negative responses.

## [5.](#) Security Considerations

An attacker can prevent future records from appearing in a cache by seeding the cache with queries that cause NSEC(3) responses to be cached, for aggressive use purposes. This document reduces the impact of that attack in cases where the NSEC(3) TTL is higher than the zone operator intended.

## [6.](#) Implementation Status

[RFC Editor: please remove this section before publication]

Implemented in PowerDNS Authoritative Server 4.3.0  
<https://doc.powerdns.com/authoritative/dnssec/operational.html?highlight=ttl#some-notes-on-ttl-usage>  
(<https://doc.powerdns.com/authoritative/dnssec/operational.html?highlight=ttl#some-notes-on-ttl-usage>) .

## [7.](#) IANA Considerations

IANA is requested to add a reference to this document in the DNS Resource Record Types registry, for the NSEC and NSEC3 types.

## 8. Acknowledgements

Ralph Dolmans helpfully pointed out that fixing this in [RFC8198](#) is only possible for negative (NXDOMAIN/NoData NOERROR) responses, and not for wildcard responses.

Warren Kumari gracefully acknowledged that the current behaviour of [RFC8198](#), in context of the NSEC TTL defined in [RFC4034](#), is not the intended behaviour.

## 9. Normative References

- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), DOI 10.17487/RFC2119, March 1997, <<https://www.rfc-editor.org/info/rfc2119>>.
- [RFC2308] Andrews, M., "Negative Caching of DNS Queries (DNS NCACHE)", [RFC 2308](#), DOI 10.17487/RFC2308, March 1998, <<https://www.rfc-editor.org/info/rfc2308>>.
- [RFC4034] Arends, R., Austein, R., Larson, M., Massey, D., and S. Rose, "Resource Records for the DNS Security Extensions", [RFC 4034](#), DOI 10.17487/RFC4034, March 2005, <<https://www.rfc-editor.org/info/rfc4034>>.

- [RFC5155] Laurie, B., Sisson, G., Arends, R., and D. Blacka, "DNS Security (DNSSEC) Hashed Authenticated Denial of Existence", [RFC 5155](#), DOI 10.17487/RFC5155, March 2008, <<https://www.rfc-editor.org/info/rfc5155>>.
- [RFC8198] Fujiwara, K., Kato, A., and W. Kumari, "Aggressive Use of DNSSEC-Validated Cache", [RFC 8198](#), DOI 10.17487/RFC8198, July 2017, <<https://www.rfc-editor.org/info/rfc8198>>.

## 10. Informative References

- [RFC8174] Leiba, B., "Ambiguity of Uppercase vs Lowercase in [RFC 2119](#) Key Words", [BCP 14](#), [RFC 8174](#), DOI 10.17487/RFC8174, May 2017, <<https://www.rfc-editor.org/info/rfc8174>>.

[Appendix A](#). Document history

Author's Address

Peter van Dijk  
PowerDNS  
Den Haag  
Netherlands

Email: `peter.van.dijk@powerdns.com`