

Network Working Group	T.J. Chown
Internet-Draft	University of Southampton
Intended status: Informational	M. Eubanks
Expires: September 15, 2011	Iformata Communications
	R. Parekh
	G. Van de Velde
	S. Venaas
	cisco Systems
	March 14, 2011

Multicast Addresses for Documentation  
draft-venaas-mboned-mcaddrdoc-03.txt

## Abstract

This document discusses which multicast addresses should be used for documentation purposes and reserves multicast addresses for such use. Some multicast addresses are derived from AS numbers or unicast addresses. This document also explains how these can be used for documentation purposes.

## Status of this Memo

This Internet-Draft is submitted in full conformance with the provisions of BCP 78 and BCP 79. Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet- Drafts is at <http://datatracker.ietf.org/drafts/current/>. Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress." This Internet-Draft will expire on September 15, 2011.

## Copyright Notice

Copyright (c) 2011 IETF Trust and the persons identified as the document authors. All rights reserved. This document is subject to BCP 78 and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

## Table of Contents

- \*1. [Introduction](#)
- \*2. [IPv4 multicast documentation addresses](#)
  - \*2.1. [Administratively scoped IPv4 multicast addresses](#)
  - \*2.2. [GLOP multicast addresses](#)
  - \*2.3. [Unicast prefix based IPv4 multicast addresses](#)
- \*3. [IPv6 multicast documentation addresses](#)
  - \*3.1. [Unicast prefix based IPv6 multicast addresses](#)
  - \*3.2. [Embedded-RP IPv6 multicast addresses](#)
- \*4. [Security Considerations](#)
- \*5. [IANA Considerations](#)
- \*6. [Acknowledgments](#)
- \*7. [References](#)
- \*[Authors' Addresses](#)

## **1. Introduction**

It is often useful in documentation, IETF documents, etc., to provide examples containing IP multicast addresses. For documentation where examples of general purpose multicast addresses are needed, one should use multicast addresses that never will be assigned or in actual use. There is a risk that addresses used in examples may accidentally be used. It is then important that the same addresses are not used by other multicast applications or services. It may also be beneficial to filter out such addresses from multicast signalling and multicast data sent to such addresses.

For unicast there are both IPv4 and IPv6 addresses reserved for this purpose, see [\[RFC5737\]](#) and [\[RFC3849\]](#) respectively. This document reserves multicast addresses for this purpose.

There are also some multicast addresses that are derived from AS numbers or unicast addresses. For examples where such addresses are desired, one should derive them from the AS numbers and unicast addresses reserved for documentation purposes. This document also discusses the use of these.

## **2. IPv4 multicast documentation addresses**

The type of multicast addresses most commonly used today, are addresses used for so-called ASM (Any-Source Multicast). For ASM, the IPv4 multicast addresses allocated for documentation purposes are 233.252.0.0 - 233.252.0.255 (233.252.0.0/24).

Another type of multicast is SSM (Source-Specific Multicast). For SSM, the IPv4 multicast addresses allocated for documentation purposes are TBD. Note that for SSM examples, one will often also want to specify source addresses. In that case the unicast addresses should be addresses reserved for documentation purposes, see [\[RFC5737\]](#). Sometimes one wants to give examples where a specific type of address is desired. E.g. for text about multicast scoping, one might want the examples to use addresses that are to be used for administrative scoping. See below for guidance on how to construct specific types of example addresses.

### **2.1. Administratively scoped IPv4 multicast addresses**

Administratively scoped IPv4 multicast addresses [\[RFC2365\]](#) are reserved for scoped multicast. They can be used within a site or an organization. Apart from a small set of scope relative addresses, these addresses are not assigned. There are no specific scoped addresses available for documentation purposes. Except for examples detailing the use of scoped multicast, one should avoid using them.

### **2.2. GLOP multicast addresses**

GLOP [\[RFC3180\]](#) is a method for deriving IPv4 multicast group addresses from 16 bit AS numbers. For examples where GLOP addresses are desired, the addresses should be derived from the AS numbers reserved for documentation use. See [\[RFC5398\]](#).

### **2.3. Unicast prefix based IPv4 multicast addresses**

IPv4 multicast addresses can be derived from IPv4 unicast prefixes, see [\[RFC6034\]](#). For examples where this type of addresses are desired, the addresses should be derived from the unicast addresses reserved for documentation purposes, see [\[RFC5737\]](#).

## **3. IPv6 multicast documentation addresses**

The type of multicast addresses most commonly used today, are addresses used for so-called ASM (Any-Source Multicast). For ASM, the IPv6 multicast addresses allocated for documentation purposes are TBD. Another type of multicast is SSM (Source-Specific Multicast). For SSM, the IPv6 multicast addresses allocated for documentation purposes are TBD. Note that for SSM examples, one will often also want to specify source addresses. In that case the unicast addresses should be addresses reserved for documentation purposes, see [\[RFC5737\]](#).

Sometimes one wants to give examples where a specific type of address is desired. E.g. for text about multicast scoping, one might want the examples to use addresses that are to be used for administrative scoping. See below for guidance on how to construct specific types of example addresses.

### **3.1. Unicast prefix based IPv6 multicast addresses**

IPv6 multicast addresses can be derived from IPv6 unicast prefixes, see [\[RFC3306\]](#). For examples where this type of addresses is desired, the addresses should be derived from the unicast addresses reserved for documentation purposes, see [\[RFC3849\]](#).

### **3.2. Embedded-RP IPv6 multicast addresses**

There is a type of IPv6 multicast addresses called Embedded-RP addresses where the IPv6 address of a Rendezvous-Point is embedded inside the multicast address, see [\[RFC3956\]](#). For examples where this type of addresses is desired, the addresses should be derived from the unicast addresses reserved for documentation purposes, see [\[RFC3849\]](#).

## **4. Security Considerations**

The use of specific multicast addresses for documentation purposes has no impact on security.

## **5. IANA Considerations**

IANA is requested to assign multicast addresses for documentation purposes as follows:

- \*2 IPv4 SSM addresses in the Source-Specific Multicast Block 232/8.

- \*A set of IPv6 multicast addresses of "variable scope". The set should be a /96 prefix of the form FF0X:...

- \*A set of IPv6 SSM addresses in the Source-Specific Multicast Block FF3X:0000:/32. The set should be a /124 prefix.

## **6. Acknowledgments**

The authors thank Roberta Maglione for providing comments on this document.

## **7. References**

<a href="#">[RFC5737]</a>
---------------------------

	Arkko, J., Cotton, M. and L. Vegoda, " <a href="#">IPv4 Address Blocks Reserved for Documentation</a> ", RFC 5737, January 2010.
[RFC3849]	Huston, G., Lord, A. and P. Smith, " <a href="#">IPv6 Address Prefix Reserved for Documentation</a> ", RFC 3849, July 2004.
[RFC3180]	Meyer, D. and P. Lothberg, " <a href="#">GLOP Addressing in 233/8</a> ", BCP 53, RFC 3180, September 2001.
[RFC5398]	Huston, G., " <a href="#">Autonomous System (AS) Number Reservation for Documentation Use</a> ", RFC 5398, December 2008.
[RFC3306]	Haberman, B. and D. Thaler, " <a href="#">Unicast-Prefix-based IPv6 Multicast Addresses</a> ", RFC 3306, August 2002.
[RFC3956]	Savola, P. and B. Haberman, " <a href="#">Embedding the Rendezvous Point (RP) Address in an IPv6 Multicast Address</a> ", RFC 3956, November 2004.
[RFC3307]	Haberman, B., " <a href="#">Allocation Guidelines for IPv6 Multicast Addresses</a> ", RFC 3307, August 2002.
[RFC2365]	Meyer, D., " <a href="#">Administratively Scoped IP Multicast</a> ", BCP 23, RFC 2365, July 1998.
[RFC6034]	Thaler, D., " <a href="#">Unicast-Prefix-Based IPv4 Multicast Addresses</a> ", RFC 6034, October 2010.

### [Authors' Addresses](#)

Tim Chown Chown University of Southampton Highfield Southampton ,  
Hampshire SO17 1BJ United Kingdom EMail: [tjc@ecs.soton.ac.uk](mailto:tjc@ecs.soton.ac.uk)

Marshall Eubanks Eubanks Iformata Communications 130 W. Second  
Street Dayton, Ohio 45402 US Phone: +1 703 501 4376 EMail:  
[marshall.eubanks@iformata.com](mailto:marshall.eubanks@iformata.com) URI: <http://www.iformata.com/>

Rishabh Parekh Parekh cisco Systems Tasman Drive San Jose, CA 95134  
USA EMail: [riparekh@cisco.com](mailto:riparekh@cisco.com)

Gunter Van de Velde Van de Velde cisco Systems De Kleetlaan 6a  
Diegem, 1831 Belgium Phone: +32 476 476 022 EMail:  
[gvandeve@cisco.com](mailto:gvandeve@cisco.com)

Stig Venaas Venaas cisco Systems  
Tasman Drive San Jose, CA 95134 USA EMail: [stig@cisco.com](mailto:stig@cisco.com)