

6man Group
Internet-Draft
Intended status: Standards Track
Expires: August 29, 2015

E. Vyncke, Ed.
S. Previdi
Cisco Systems, Inc.
D. Lebrun
Universite Catholique de Louvain
February 25, 2015

IPv6 Segment Routing Security Considerations
draft-vyncke-6man-segment-routing-security-02

Abstract

Segment Routing (SR) allows a node to steer a packet through a controlled set of instructions, called segments, by prepending a SR header to the packet. A segment can represent any instruction, topological or service-based. SR allows to enforce a flow through any path (topological, or application/service based) while maintaining per-flow state only at the ingress node to the SR domain.

Segment Routing can be applied to the IPv6 data plane with the addition of a new type of Routing Extension Header. This document analyzes the security aspects of the Segment Routing Extension Header (SRH) and how it is used by SR capable nodes to deliver a secure service.

Requirements Language

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [RFC 2119](#) [[RFC2119](#)].

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <http://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on August 29, 2015.

Internet-Draft Pv6 Segment Routing Security Considerations February 2015

Copyright Notice

Copyright (c) 2015 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

Table of Contents

1.	Introduction	2
1.1.	Segment Routing Documents	3
2.	Threat model	3
2.1.	Source routing threats	4
2.2.	Applicability of RFC 5095 to SRH	4
2.3.	Service stealing threat	5
2.4.	Topology disclosure	5
2.5.	ICMP Generation	5
3.	Security fields in SRH	6
3.1.	Selecting a hash algorithm	7
3.2.	Performance impact of HMAC	7
3.3.	Pre-shared key management	8
4.	Deployment Models	9
4.1.	Nodes within the SR domain	9
4.2.	Nodes outside of the SR domain	9
4.3.	SR path exposure	10
4.4.	Impact of BCP-38	10
5.	IANA Considerations	10
6.	Manageability Considerations	11
7.	Security Considerations	11
8.	Acknowledgements	11
9.	References	11
9.1.	Normative References	11
9.2.	Informative References	11
	Authors' Addresses	13

1. Introduction

This document analyzes the security threat model, the security issues and proposed solutions related to the new routing header for segment routing with an IPv6 data plane.

Internet-Draft Pv6 Segment Routing Security Considerations February 2015

The Segment Routing Header (SRH) is simply another type of the routing header as described in [RFC 2460](#) [[RFC2460](#)] and is:

- o inserted by a SR edge router when entering the segment routing domain or by the originating host itself. The source host can even be outside the SR domain;
- o inspected and acted upon when reaching the destination address of the IP header per [RFC 2460](#) [[RFC2460](#)].

Per [RFC2460](#) [[RFC2460](#)], routers on the path that simply forward an IPv6 packet (i.e. the IPv6 destination address is none of theirs) will never inspect and process the content of SRH. Routers whose one interface IPv6 address equals the destination address field of the IPv6 packet MUST to parse the SRH and, if supported and if the local configuration allows it, MUST act accordingly to the SRH content.

According to [RFC2460](#) [[RFC2460](#)], the default behavior of a non SR-capable router upon receipt of an IPv6 packet with SRH destined to an address of its, is to:

- o ignore the SRH completely if the Segment Left field is 0 and proceed to process the next header in the IPv6 packet;
- o discard the IPv6 packet if Segment Left field is greater than 0, it MAY send a Parameter Problem ICMP message back to the Source Address.

1.1. Segment Routing Documents

Segment Routing terminology is defined in [[I-D.ietf-spring-segment-routing](#)] and in [[I-D.ietf-spring-problem-statement](#)]. Segment Routing use cases are described in [[I-D.filsfils-spring-segment-routing-use-cases](#)]. Segment Routing protocol extensions are defined in [[I-D.ietf-isis-segment-routing-extensions](#)], and

[\[I-D.ietf-ospf-ospfv3-segment-routing-extensions\]](#).

Segment Routing IPv6 use cases are described in [\[I-D.ietf-spring-ipv6-use-cases\]](#). And the IPv6 Segment Routing header is described in [\[I-D.previdi-6man-segment-routing-header\]](#).

2. Threat model

Internet-Draft Pv6 Segment Routing Security Considerations February 2015

2.1. Source routing threats

Using a SRH is similar to source routing, therefore it has some well-known security issues as described in [RFC4942](#) [\[RFC4942\]](#) [section 2.1.1](#) and [RFC5095](#) [\[RFC5095\]](#):

- o amplification attacks: where a packet could be forged in such a way to cause looping among a set of SR-enabled routers causing unnecessary traffic, hence a Denial of Service (DoS) against bandwidth;
- o reflection attack: where a hacker could force an intermediate node to appear as the immediate attacker, hence hiding the real attacker from naive forensic;
- o bypass attack: where an intermediate node could be used as a stepping stone (for example in a De-Militarized Zone) to attack another host (for example in the datacenter or any back-end server).

2.2. Applicability of [RFC 5095](#) to SRH

First of all, the reader must remember this specific part of [section 1 of RFC5095](#) [\[RFC5095\]](#), "A side effect is that this also eliminates benign RH0 use-cases; however, such applications may be facilitated by future Routing Header specifications.". In short, it is not forbidden to create new secure type of Routing Header; for example, [RFC 6554](#) (RPL) [\[RFC6554\]](#) also creates a new Routing Header type for a specific application confined in a single network.

In the segment routing architecture described in [\[I-D.ietf-spring-segment-routing\]](#) there are basically two kinds of nodes (routers and hosts):

- o nodes within the SR domain, which is within one single administrative domain, i.e., where all nodes are trusted anyway else the damage caused by those nodes could be worse than amplification attacks: traffic interception, man-in-the-middle attacks, more server DoS by dropping packets, and so on.
- o nodes outside of the SR domain, which is outside of the administrative segment routing domain hence they cannot be trusted because there is no physical security for those nodes, i.e., they can be replaced by hostile nodes or can be coerced in wrong behaviors.

The main use case for SR consists of the single administrative domain where only trusted nodes with SR enabled and configured participate

Internet-Draft Pv6 Segment Routing Security Considerations February 2015

in SR: this is the same model as in [RFC6554](#) [[RFC6554](#)]. All non-trusted nodes do not participate as either SR processing is not enabled by default or because they only process SRH from nodes within their domain.

Moreover, all SR nodes ignore SRH created by outsiders based on topology information (received on a peering or internal interface) or on presence and validity of the HMAC field. Therefore, if intermediate nodes ONLY act on valid and authorized SRH (such as within a single administrative domain), then there is no security threat similar to RH-0. Hence, the [RFC 5095](#) [[RFC5095](#)] attacks are not applicable.

[2.3.](#) Service stealing threat

Segment routing is used for added value services, there is also a need to prevent non-participating nodes to use those services; this is called 'service stealing prevention'.

[2.4.](#) Topology disclosure

The SRH may also contains IPv6 addresses of some intermediate SR-

nodes in the path towards the destination, this obviously reveals those addresses to the potentially hostile attackers if those attackers are able to intercept packets containing SRH. On the other hand, if the attacker can do a traceroute whose probes will be forwarded along the SR path, then there is little learned by intercepting the SRH itself. Also the clean-bit of SRH can help by removing the SRH before forwarding the packet to potentially a non-trusted part of the network.

[2.5.](#) ICMP Generation

Per [section 4.4 of RFC2460](#) [[RFC2460](#)], when destination nodes (i.e. where the destination address is one of theirs) receive a Routing Header with unsupported Routing Type, the required behavior is:

- o If Segments Left is zero, the node must ignore the Routing header and proceed to process the next header in the packet.
- o If Segments Left is non-zero, the node must discard the packet and send an ICMP Parameter Problem, Code 0, message to the packet's Source Address, pointing to the unrecognized Routing Type.

This required behavior could be used by an attacker to force the generation of ICMP message by any node. The attacker could send packets with SRH (with Segment Left set to 0) destined to a node not supporting SRH. Per [RFC2460](#) [[RFC2460](#)], the destination node could

generate an ICMP message, causing a local CPU utilization and if the source of the offending packet with SRH was spoofed could lead to a reflection attack without any amplification.

It must be noted that this is a required behavior for any unsupported Routing Type and not limited to SRH packets. So, it is not specific to SRH and the usual rate limiting for ICMP generation is required anyway for any IPv6 implementation and has been implemented and deployed for many years.

[3.](#) Security fields in SRH

This section summarizes the use of specific fields in the SRH; they are integral part of [[I-D.previdi-6man-segment-routing-header](#)] and they are again described here for reader's sake. They are based on a

key-hashed message authentication code (HMAC).

The security-related fields in SRH are:

- o HMAC Key-id, 8 bits wide;
- o HMAC, 256 bits wide (optional, exists only if HMAC Key-id is not 0).

The HMAC field is the output of the HMAC computation (per [RFC 2104](#) [[RFC2104](#)]) using a pre-shared key identified by HMAC Key-id and of the text which consists of the concatenation of:

- o the source IPv6 address;
- o First Segment field;
- o an octet whose bit-0 is the clean-up bit flag and others are 0;
- o HMAC Key-id;
- o all addresses in the Segment List.

The purpose of the HMAC field is to verify the validity, the integrity and the authorization of the SRH itself. If an outsider of the SR domain does not have access to a current pre-shared secret, then it cannot compute the right HMAC field and the first SR router on the path processing the SRH and configured to check the validity of the HMAC will simply reject the packet.

The HMAC field is located at the end of the SRH simply because only the router on the ingress of the SR domain needs to process it, then all other SR nodes can ignore it (based on local policy) because they

trust the upstream router. This is to speed up forwarding operations because SR routers which do not validate the SRH do not need to parse the SRH until the end.

The HMAC Key-id field allows for the simultaneous existence of several hash algorithms (SHA-256, SHA3-256 ... or future ones) as well as pre-shared keys. This allows for pre-shared key roll-over when two pre-shared keys are supported for a while when all SR nodes

converged to a fresher pre-shared key. The HMAC Key-id field is opaque, i.e., it has neither syntax not semantic except as an index to the right combination of pre-shared key and hash algorithm and except that a value of 0 means that there is no HMAC field. It could also allow for interoperation among different SR domains if allowed by local policy and assuming a collision-free Key Id allocation.

When a specific SRH is linked to a time-related service (such as turbo-QoS for a 1-hour period) where the DA, Segment ID (SID) are identical, then it is important to refresh the shared-secret frequently as the HMAC validity period expires only when the HMAC Key-id and its associated shared-secret expires.

3.1. Selecting a hash algorithm

The HMAC field in the SRH is 256 bit wide. Therefore, the HMAC MUST be based on a hash function whose output is at least 256 bits. If the output of the hash function is 256, then this output is simply inserted in the HMAC field. If the output of the hash function is larger than 256 bits, then the output value is truncated to 256 by taking the least-significant 256 bits and inserting them in the HMAC field.

SRH implementations can support multiple hash functions but MUST implement SHA-2 [[FIPS180-4](#)] in its SHA-256 variant.

NOTE: SHA-1 is currently used by some early implementations used for quick interoperations testing, the 160-bit hash value must then be right-hand padded with 96 bits set to 0. The authors understand that this is not secure but is ok for limited tests.

3.2. Performance impact of HMAC

While adding a HMAC to each and every SR packet increases the security, it has a performance impact. Nevertheless, it must be noted that:

- o the HMAC field is used only when SRH is inserted by a device (such as a home set-up box) which is outside of the segment routing domain. If the SRH is added by a router in the trusted segment

performance impact.

- o when present, the HMAC field MUST only be checked and validated by the first router of the segment routing domain, this router is named 'validating SR router'. Downstream routers MAY NOT inspect the HMAC field.
- o this validating router can also have a cache of <IPv6 header + SRH, HMAC field value> to improve the performance. It is not the same use case as in IPsec where HMAC value was unique per packet, in SRH, the HMAC value is unique per flow.
- o Last point, hash functions such as SHA-2 have been optimized for security and performance and there are multiple implementations with good performance.

With the above points in mind, the performance impact of using HMAC is minimized.

[3.3.](#) Pre-shared key management

The field HMAC Key-id allows for:

- o key roll-over: when there is a need to change the key (the hash pre-shared secret), then multiple pre-shared keys can be used simultaneously. The validating routing can have a table of <HMAC Key-id, pre-shared secret> for the currently active and future keys.
- o different algorithm: by extending the previous table to <HMAC Key-id, hash function, pre-shared secret>, the validating router can also support simultaneously several hash algorithms (see section [Section 3.1](#))

The pre-shared secret distribution can be done:

- o in the configuration of the validating routers, either by static configuration or any SDN oriented approach;
- o dynamically using a trusted key distribution such as [[RFC6407](#)]

The intent of this document is NOT to define yet-another-key-distribution-protocol.

[4.](#) Deployment Models

[4.1.](#) Nodes within the SR domain

A SR domain is defined as a set of interconnected routers where all routers at the perimeter are configured to insert and act on SRH. Some routers inside the SR domain can also act on SRH or simply forward IPv6 packets.

The routers inside a SR domain can be trusted to generate SRH and to process SRH received on interfaces that are part of the SR domain. These nodes **MUST** drop all SRH packets received on an interface that is not part of the SR domain and containing a SRH whose HMAC field cannot be validated by local policies. This includes obviously packet with a SRH generated by a non-cooperative SR domain.

If the validation fails, then these packets **MUST** be dropped, ICMP error messages (parameter problem) **SHOULD** be generated (but rate limited) and **SHOULD** be logged.

[4.2.](#) Nodes outside of the SR domain

Nodes outside of the SR domain cannot be trusted for physical security; hence, they need to request by some trusted means (outside of the scope of this document) a complete SRH for each new connection (i.e. new destination address). The received SRH **MUST** include a HMAC Key-id and HMAC field which is computed correctly (see [Section 3](#)).

When an outside node sends a packet with an SRH and towards a SR domain ingress node, the packet **MUST** contain the HMAC Key-id and HMAC field and the the destination address **MUST** be an address of a SR domain ingress node .

The ingress SR router, i.e., the router with an interface address equals to the destination address, **MUST** verify the HMAC field with respect to the HMAC Key-id.

If the validation is successful, then the packet is simply forwarded as usual for a SR packet. As long as the packet travels within the SR domain, no further HMAC check needs to be done. Subsequent routers in the SR domain **MAY** verify the HMAC field when they process the SRH (i.e. when they are the destination).

If the validation fails, then this packet **MUST** be dropped, an ICMP error message (parameter problem) **SHOULD** be generated (but rate limited) and **SHOULD** be logged.

Internet-Draft Pv6 Segment Routing Security Considerations February 2015

[4.3.](#) SR path exposure

As the intermediate SR nodes addresses appears in the SRH, if this SRH is visible to an outsider then he/she could reuse this knowledge to launch an attack on the intermediate SR nodes or get some insider knowledge on the topology. This is especially applicable when the path between the source node and the first SR domain ingress router is on the public Internet.

The first remark is to state that 'security by obscurity' is never enough; in other words, the security policy of the SR domain MUST assume that the internal topology and addressing is known by the attacker. A simple traceroute will also give the same information (with even more information as all intermediate nodes between SID will also be exposed). IPsec Encapsulating Security Payload [[RFC4303](#)] cannot be use to protect the SRH as per [RFC4303](#) the ESP header must appear after any routing header (including SRH).

To prevent a user to leverage the gained knowledge by intercepting SRH, it is recommended to apply an infrastructure Access Control List (iACL) at the edge of the SR domain. This iACL will drop all packets from outside the SR-domain whose destination is any address of any router inside the domain. This security policy should be tuned for local operations.

[4.4.](#) Impact of [BCP-38](#)

[BCP-38](#) [[RFC2827](#)], also known as "Network Ingress Filtering", checks whether the source address of packets received on an interface is valid for this interface. The use of loose source routing such as SRH forces packets to follow a path which differs from the expected routing. Therefore, if [BCP-38](#) was implemented in all routers inside the SR domain, then SR packets could be received by an interface which is not expected one and the packets could be dropped.

As a SR domain is usually a subset of one administrative domain, and as [BCP-38](#) is only deployed at the ingress routers of this administrative domain and as packets arriving at those ingress routers have been normally forwarded using the normal routing

information, then there is no reason why this ingress router should drop the SRH packet based on [BCP-38](#). Routers inside the domain commonly do not apply [BCP-38](#); so, this is not a problem.

[5.](#) IANA Considerations

There are no IANA request or impact in this document.

[6.](#) Manageability Considerations

TBD

[7.](#) Security Considerations

Security mechanisms applied to Segment Routing over IPv6 networks are detailed in [Section 3](#).

[8.](#) Acknowledgements

The authors would like to thank Dave Barach and Stewart Bryant for their contributions to this document.

[9.](#) References

[9.1.](#) Normative References

[FIPS180-4]

National Institute of Standards and Technology, "FIPS 180-4 Secure Hash Standard (SHS)", March 2012, <<http://csrc.nist.gov/publications/fips/fips180-4/fips-180-4.pdf>>.

[RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), March 1997.

[RFC2460] Deering, S. and R. Hinden, "Internet Protocol, Version 6 (IPv6) Specification", [RFC 2460](#), December 1998.

[RFC4303] Kent, S., "IP Encapsulating Security Payload (ESP)", [RFC 4303](#), December 2005.

- [RFC5095] Abley, J., Savola, P., and G. Neville-Neil, "Deprecation of Type 0 Routing Headers in IPv6", [RFC 5095](#), December 2007.
- [RFC6407] Weis, B., Rowles, S., and T. Hardjono, "The Group Domain of Interpretation", [RFC 6407](#), October 2011.

[9.2.](#) Informative References

Internet-Draft Pv6 Segment Routing Security Considerations February 2015

- [I-D.filsfils-spring-segment-routing-use-cases]
Filsfils, C., Francois, P., Previdi, S., Decraene, B., Litkowski, S., Horneffer, M., Milojevic, I., Shakir, R., Ytti, S., Henderickx, W., Tantsura, J., Kini, S., and E. Crabbe, "Segment Routing Use Cases", [draft-filsfils-spring-segment-routing-use-cases-01](#) (work in progress), October 2014.
- [I-D.ietf-isis-segment-routing-extensions]
Previdi, S., Filsfils, C., Bashandy, A., Gredler, H., Litkowski, S., Decraene, B., and J. Tantsura, "IS-IS Extensions for Segment Routing", [draft-ietf-isis-segment-routing-extensions-03](#) (work in progress), October 2014.
- [I-D.ietf-ospf-ospfv3-segment-routing-extensions]
Psenak, P., Previdi, S., Filsfils, C., Gredler, H., Shakir, R., Henderickx, W., and J. Tantsura, "OSPFv3 Extensions for Segment Routing", [draft-ietf-ospf-ospfv3-segment-routing-extensions-02](#) (work in progress), February 2015.
- [I-D.ietf-spring-ipv6-use-cases]
Brzozowski, J., Leddy, J., Leung, I., Previdi, S., Townsley, W., Martin, C., Filsfils, C., and R. Maglione, "IPv6 SPRING Use Cases", [draft-ietf-spring-ipv6-use-](#)

[cases-03](#) (work in progress), November 2014.

[I-D.ietf-spring-problem-statement]

Previdi, S., Filsfils, C., Decraene, B., Litkowski, S., Horneffer, M., and R. Shakir, "SPRING Problem Statement and Requirements", [draft-ietf-spring-problem-statement-03](#) (work in progress), October 2014.

[I-D.ietf-spring-segment-routing]

Filsfils, C., Previdi, S., Bashandy, A., Decraene, B., Litkowski, S., Horneffer, M., Shakir, R., Tantsura, J., and E. Crabbe, "Segment Routing Architecture", [draft-ietf-spring-segment-routing-01](#) (work in progress), February 2015.

[I-D.previdi-6man-segment-routing-header]

Previdi, S., Filsfils, C., Field, B., and I. Leung, "IPv6 Segment Routing Header (SRH)", [draft-previdi-6man-segment-routing-header-05](#) (work in progress), January 2015.

[RFC2104] Krawczyk, H., Bellare, M., and R. Canetti, "HMAC: Keyed-Hashing for Message Authentication", [RFC 2104](#), February 1997.

Vyncke, et al.

Expires August 29, 2015

[Page 12]

Internet-Draft Pv6 Segment Routing Security Considerations February 2015

[RFC2827] Ferguson, P. and D. Senie, "Network Ingress Filtering: Defeating Denial of Service Attacks which employ IP Source Address Spoofing", [BCP 38](#), [RFC 2827](#), May 2000.

[RFC4942] Davies, E., Krishnan, S., and P. Savola, "IPv6 Transition/Co-existence Security Considerations", [RFC 4942](#), September 2007.

[RFC6554] Hui, J., Vasseur, JP., Culler, D., and V. Manral, "An IPv6 Routing Header for Source Routes with the Routing Protocol for Low-Power and Lossy Networks (RPL)", [RFC 6554](#), March 2012.

Authors' Addresses

Eric Vyncke (editor)
Cisco Systems, Inc.
De Kleetlaan 6A

Diegem 1831
Belgium

Email: evyncke@cisco.com

Stefano Previdi
Cisco Systems, Inc.
Via Del Serafico, 200
Rome 00142
Italy

Email: sprevidi@cisco.com

David Lebrun
Universite Catholique de Louvain
Place Ste Barbe, 2
Louvain-la-Neuve, 1348
Belgium

Email: david.lebrun@uclouvain.be