

template
Internet-Draft
Intended status: Informational
Expires: October 31, 2015

D. Bird
W. Kumari
Google
April 29, 2015

**Captive Portal ICMP Destination Unreachable
draft-wkumari-capport-icmp-unreach-01**

Abstract

This document defines a multi-part ICMP extension to ICMP Destination Unreachable messages to signal that a user is behind a Captive Portal.

[Editor note: The IETF is currently discussing improvements in captive portal interactions and user experience improvements. See: <https://www.ietf.org/mailman/listinfo/captive-portals>]

[RFC Editor: Please remove this before publication. This document is being stored in github at <https://github.com/wkumari/draft-wkumari-capport-icmp-unreach> . Authors gratefully accept pull requests, and keep the latest (edit buffer) versions there, so commenters can follow along at home.]

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <http://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on October 31, 2015.

Copyright Notice

Copyright (c) 2015 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

Table of Contents

1.	Introduction	2
1.1.	Requirements notation	3
2.	ICMP Dest Unreachable Captive Portal Object	3
3.	IANA Considerations	4
4.	Security Considerations	4
5.	Acknowledgements	5
6.	References	5
6.1.	Normative References	5
6.2.	Informative References	5
Appendix A.	Changes / Author Notes.	5
	Authors' Addresses	6

[1.](#) Introduction

Captive Portals work by blocking (or redirecting) communications outside of a "walled garden" until the user has authenticated and / or acknowledged an Acceptable Use Policy (AUP). Depending on the captive portal implementation, connections other than HTTP will either timeout (packets dropped) or meet with a different, inaccurate, error condition (like a TCP reset or ICMP Destination Unreachable with existing codes).

A current option for captive portal networks is to reject traffic not in the walled garden returning the Destination Unreachable either Host or Network Administratively Prohibited. However, these codes are typically permanent policies and do not specifically indicate a captive portal is in use.

This document defines an extension object that can be appended to selected multi-part ICMP messages to inform the user that they are behind a captive portal. This informs the user after they have attempted an initial connection and is generated by the Captive Portal NAS itself.

[Editor note: This is complementary, but solves a different problem to: <https://tools.ietf.org/html/draft-wkumari-dhc-capport-12> -

W bit or C-Type We have currently specified a single bit (W) to indicate that the remaining lease time is running low, and the the connection will be interrupted sometime "soon". We could,

instead, use a different C-Type. I think a bit is cleaner (and we have reserved 7 bits for future flags), but could be convinced (or, better yet, bribed) I'm wrong. Or that the whole "warning" idea is a bad one...

Legacy interaction If we *do* return e.g ICMP Destination Unreachable, Communication Administratively Prohibited to a "legacy" (non-Dest Unreachable Captive Portal Object aware) client with the 'W' bit set, what happens? In the testing I did, nothing bad seemed to happen, but I *could* see that some hosts may stop sending to that address, or...

General concept Is this idea useful?

3. IANA Considerations

The IANA is requested to assign a Class-Num identifier for the Dest Unreachable Captive Portal Object from the ICMP Extension Object Classes and Class Sub-types registry.

The IANA is also requested to form and administer the corresponding class sub-type (C-Type) space, as follows:

Dest Unreachable Captive Portal Sub-types:

0 Reserved.

1 This message format.

0x02-0xF6 Available for assignment

0xF7-0xFF Reserved for private use

C-Type values are assignable on a first-come-first-serve (FCFS) basis.

[Editor note: Currently we are not using the C-Type for anything, but I filled this in anyway. Probably we would overload it at a version identifier type thing, but it could also allow further extension, for example, a pointer to a status page.]

4. Security Considerations

This method simply annotates existing ICMP Destination Unreachable messages to inform users why their connection was blocked. This technique can be used to inform captive portal detection probe software that there is a captive portal present (and potentially to connect to the URL handed out using [draft-wkumari-dhc-capport](#). We

anticipate that there will be a new solution devised (such as a well known URL / URI on captive portals) to allow the user / captive portal probe to do something more useful with this information.

5. Acknowledgements

The authors wish to thank the authors of [RFC4950](#) (especially Ron Bonica) - I stole much of his text when writing the extension definition.

6. References

6.1. Normative References

- [RFC0792] Postel, J., "Internet Control Message Protocol", STD 5, [RFC 792](#), September 1981.
- [RFC1122] Braden, R., "Requirements for Internet Hosts - Communication Layers", STD 3, [RFC 1122](#), October 1989.
- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), March 1997.
- [RFC3986] Berners-Lee, T., Fielding, R., and L. Masinter, "Uniform Resource Identifier (URI): Generic Syntax", STD 66, [RFC 3986](#), January 2005.
- [RFC4884] Bonica, R., Gan, D., Tappan, D., and C. Pignataro, "Extended ICMP to Support Multi-Part Messages", [RFC 4884](#), April 2007.

6.2. Informative References

- [I-D.ietf-sidr-iana-objects]
Manderson, T., Vegoda, L., and S. Kent, "RPKI Objects issued by IANA", [draft-ietf-sidr-iana-objects-03](#) (work in progress), May 2011.

[Appendix A](#). Changes / Author Notes.

[RFC Editor: Please remove this section before publication]

From -00 to 01.

- o Changed the Captive Portal URL to a URI, and specified that this can ONLY contain a path element, which is appended to `http://<gateway_ip>`. This is to prevent hijacking connections to other addresses.

- o Then removed the entire URL / URI scheme entirely.

From -genesis to -00.

- o Initial text.

Authors' Addresses

David Bird
Google
1600 Amphitheatre Parkway
Mountain View, CA 94043
US

Email: dbird@google.com

Warren Kumari
Google
1600 Amphitheatre Parkway
Mountain View, CA 94043
US

Email: warren@kumari.net

