BESS Working Group Internet-Draft Intended status: Standards Track Expires: May 3, 2020 M. Wang Q. Wu R. Even Huawei B. Wen Comcast C. Liu China Unicom H. Xu China Telecom October 31, 2019

A YANG Model for Network and VPN Service Performance Monitoring draft-www-bess-yang-vpn-service-pm-04

Abstract

The data model defined in [RFC8345] introduces vertical layering relationships between networks that can be augmented to cover network/service topologies. This document defines a YANG model for both Network Performance Monitoring and VPN Service Performance Monitoring that can be used to monitor and manage network performance on the topology at higher layer or the service topology between VPN sites. This model is an augmentation to the network topology YANG data model defined in [RFC8345].

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of <u>BCP 78</u> and <u>BCP 79</u>.

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <u>https://datatracker.ietf.org/drafts/current/</u>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on May 3, 2020.

Copyright Notice

Copyright (c) 2019 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to BCP 78 and the IETF Trust's Legal Provisions Relating to IETF Documents (https://trustee.ietf.org/license-info) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

Table of Contents

<u>1</u> . Introduction	 <u>2</u>
$\underline{2}$. Conventions used in this document	 <u>3</u>
<u>2.1</u> . Tree Diagrams	 <u>3</u>
<u>3</u> . Network and VPN service assurance module	 <u>3</u>
$\underline{4}$. Layering relationship between multiple layers of topology	 <u>4</u>
<u>5</u> . Model Usage Guideline	 <u>5</u>
<u>5.1</u> . Performance Monitoring Data Source	 <u>5</u>
<u>5.2</u> . Retrieval via I2RS Pub/Sub [<u>RFC7923</u>]	 <u>5</u>
5.3. On demand Retrieval via RPC model	 <u>5</u>
$\underline{6}$. Design of the Data Model	 <u>5</u>
<u>6.1</u> . Network Level	 <u>6</u>
<u>6.2</u> . Node Level	 <u>6</u>
<u>6.3</u> . Link and Termination Point Level	 7
<u>7</u> . Example of I2RS Pub/Sub Retrieval [<u>RFC7923</u>]	 <u>8</u>
8. Example of RPC model based Retrieval	 <u>10</u>
9. Network and VPN Service Assurance YANG Module	 <u>11</u>
<u>10</u> . Security Considerations	 <u>20</u>
<u>11</u> . IANA Considerations	 <u>21</u>
<u>12</u> . Normative References	 <u>22</u>
Authors' Addresses	 <u>23</u>

1. Introduction

[RFC8345] defines an abstract YANG data model for network/service topologies and inventories. Service topology described in [RFC8345] includes the a virtual topology for a service layer above the L1, L2, and L3 layers. This service topology has the generic topology elements of node, link, and terminating point. One typical example of a service topology is described in figure 3 of [RFC8345], two VPN service topologies instantiated over a common L3 topology. Each VPN

[Page 2]

Network and VPN Service PM YANG October 2019

service topology is mapped onto a subset of nodes from the common L3 topology.

In [RFC8299], 3 types of VPN service topologies are defined for the L3VPN service data model: any to any; hub and spoke; and hub and spoke disjoint. These VPN topology types can be used to describe how VPN sites communicate with each other.

This document defines a YANG Model for both Network performance monitoring and VPN Service Performance Monitoring that can be used to monitor and manage network Performance on the topology at higher layer or the service topology between VPN sites and it is an augmentation to the network topology YANG data model defined in [RFC8345].

2. Conventions used in this document

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [RFC2119]. In this document, these words will appear with that interpretation only when in ALL CAPS. Lower case uses of these words are not to be interpreted as carrying [<u>RFC2119</u>] significance.

2.1. Tree Diagrams

Tree diagrams used in this document follow the notation defined in [RFC8340].

3. Network and VPN service assurance module

This module defined in this document is a Network and VPN Service assurance module that can be used to monitor and manage the network Performance on the topology at higher layer layer or the service topology between VPN sites and it is an augmentation to the "ietfnetwork" and "ietf-network-topology" YANG data model [<u>RFC8345</u>]. The performance monitoring data is augmented to service topology.

+	+	+	+	
ietf-network	I	Network and	d VPN Service	
ietf-network-topology	<	Peformance	Monitoring	
+	+ augments	Moo	del	
		+	+	

[Page 3]

4. Layering relationship between multiple layers of topology

The data model defined in [<u>RFC8345</u>] can describe vertical layering relationships between networks. That model can be augmented to cover network/service topologies.

Figure 1 describes an example on topology mapping between the VPN service topology and the underlying network:

	V	/PN-SVO	21	VPN	I-SVC 2		
		/			Λ		
VPN-Se	ervice	e-topol	Logy 1	VPN-Se	ervice-top	ology-2	
/			\	/		\	
Site-14	A Site	e-1B Si	ite1-C	Site-2A	A Site-2B	Site-2C	Top-Down
		I					Service Topology
CE		CE	CE	CE	CE	CE	
PE		PE	PE	PE	PE	PE	
===== =====	=====	= ====	==== ==	===== ====	:===== ===	=== =====	
+	+		\	/	/		
Bottom-u	l qu		١	. /	/		
Network			/	<i>′</i> ∖	/		
topology	/		/	λ			
				I			
r	node1	node2	node3	node4	node5	node6	

Example of topology mapping between VPN Service Topo and Underlying network

As shown in Figure 1, Site-1A, Site-1B, and Site-1C are mapped to nodes 1, 2, and 3, while Site-2A, Site-2B, and Site-2C are mapped to nodes 4, 5, and 6 in the underlying physical network. In this figure, two VPN services topologies are both built on top of one common underlying physical network.

VPN-SVC 1: supporting hub-spoke communication for Customer 1 connecting the customers access at 3 sites

VPN-SVC 2: supporting hub-spoke disjoint communication for Customer 2 connecting the customers access at 3 sites

VPN service topology 1 is hub and spoke topology while VPN service topology 2 is hub and spoke disjoint topology. In VPN service topology 1, Site-1 A plays the role of hub while Site-2 B and C plays the role of spoke. In VPN service topoogy 2, Site-2 A and B play the role of hub while Site-2 C plays the role of spoke.

[Page 4]

5. Model Usage Guideline

An SP must be able to manage the capabilities and characteristics of their Network/VPN services when Network connection is established or VPN sites are setup to communicate with each other. VPN service topology such as hub and spoke describes how these VPN sites are communicating with each other.

5.1. Performance Monitoring Data Source

As described in <u>Section 4</u>, once the mapping between VPN Service topology and underlying physical network has been setup, the performance monitoring data per link in the underlying network can be collected using network performance measurement method such as MPLS Loss and Delay Measurement [RFC6374]. The performance monitoring information reflecting the quality of the Network or VPN service such as end to end network performance data between source node and destination node in the network or between VPN sites can be aggregated or calculated using PCEP solution [RFC5440] or LMAP solution [RFC8194]. The information can be fed into data source such as the management system or network devices. The measurement interval and report interval associated with these performance data usually depends on configuration parameters.

5.2. Retrieval via I2RS Pub/Sub [RFC7923]

Some applications such as service-assurance applications, which must maintain a continuous view of operational data and state, can use subscription model [I-D.ietf-netconf-yang-push] to subscribe to the Network performance data or VPN service performance data they are interested in, at the data source.

The data source can then use the Network and VPN service assurance model defined in this document and push model [I-D.ietf-netconf-yangpush] to distribute specific telemetry data to target recipients.

5.3. On demand Retrieval via RPC model

To obtain a snapshot of a large amount of performance data from the network element, service-assurance applications can also use polling based solution such as RPC model to fetch performance data on demand.

6. Design of the Data Model

This document defines the YANG module "ietf-network-vpn-pm", which has the following structure

[Page 5]

6.1. Network Level

```
module: ietf-network-vpn-pm
augment /nw:networks/nw:network/nw:network-types:
    +--rw network-technology-type* identityref
augment /nw:networks/nw:network:
    +--rw vpn-topo-attributes
    +--rw vpn-topo? identityref
```

Network Level View of the hierarchies

For VPN service performance monitoring, this model defines only the following minimal set of Network level network topology attributes:

- o Network-technology-type: Indicate the network technology type such as L3VPN, L2VPN, ISIS, OSPF. If the network-technology-type is VPN type,e.g.,L3VPN, L2VPN, the VPN-topo should be set.
- vpn-topo: The type of VPN service topology, this model supports any-to-any, Hub and Spoke (where Hubs can exchange traffic), and "Hub and Spoke disjoint" (where Hubs cannot exchange traffic).

For network performance monitoring, the attributes of "Network Level" that defined in [<u>RFC8345</u>] do not need to be extended.

6.2. Node Level

augment /nw:networks/nw:network/nw:node:

+--rw node-attributes +--rw node-type? identityref +--rw site-id? string +--rw site-role? Identityref

Node Level View of the hierarchies

The Network and VPN service performance monitoring model defines only the following minimal set of Node level network topology attributes and constraints:

- o Node-type (Attribute): Indicate the type of the node, such as PE or ASBR.
- o Site-id (Constraint): Uniquely identifies the site within the overall network infrastructure.
- o Site-role (Constraint): Defines the role of the site in a
 particular VPN topology.

[Page 6]

Internet-Draft

<u>6.3</u>. Link and Termination Point Level

```
augment /nw:networks/nw:network/nt:link:
 +--rw link-type?
                                         identityref
 +--ro link-telemetry-attributes
    +--ro loss-statistics
     | +--ro direction
                                         identityref
     +--ro packet-loss-count?
                                         uint32
     +--ro loss-ratio?
                                         percentage
     +--ro packet-reorder-count?
                                         uint32
    +--ro packets-out-of-seq-count?
                                         uint32
     +--ro packets-dup-count?
                                         uint32
    +--ro delay-statistics
     +--ro direction?
                                       identityref
    +--ro min-delay-value?
                                       uint32
     +--ro max-delay-value?
                                       uint32
     +--ro average-delay-value?
                                       uint32
    +--ro jitter-statistics
       +--ro direction?
                                       identityref
       +--ro min-jitter-value?
                                       uint32
       +--ro max-jitter-value?
                                       uint32
       +--ro average-jitter-value?
                                       uint32
augment /nw:networks/nw:network/nw:node/nt:termination-point:
 +--ro tp-telemetry-attributes
    +--ro in-octets?
                               uint32
    +--ro inbound-unicast?
                               uint32
    +--ro inbound-nunicast?
                               uint32
    +--ro inbound-discards?
                               uint32
    +--ro inbound-errors?
                               uint32
    +--ro inunknow-protos?
                               uint32
    +--ro out-octets?
                               uint32
    +--ro outbound-unicast?
                               uint32
    +--ro outbound-nunicast?
                               uint32
    +--ro outbound-discards?
                               uint32
    +--ro outbound-errors?
                               uint32
    +--ro outbound-glen?
                               uint32
```

Link and Termination point Level View of the hierarchies

The Network and VPN service performance monitoring model defines only the following minimal set of Link level network topology attributes:

- o Link-type (Attribute): Indicate the type of the link, such as GRE,IP in IP.
- o Loss Statistics: A set of loss statistics attributes that are used to measure end to end loss between VPN sites.

[Page 7]

- o Delay Statistics: A set of delay statistics attributes that are used to measure end to end latency between VPN sites.
- o Jitter Statistics: A set of jitter statistics attributes that are used to measure end to end jitter between VPN sites.

The Network and VPN service performance monitoring defines the following minimal set of Termination point level network topology attributes:

- o Inbound statistics: A set of inbound statistics attributes that are used to measure the inbound statistics of the termination point, such as "the total number of octets received on the termination point", "The number of inbound packets which were chosen to be discarded", "The number of inbound packets that contained errors", etc.
- o Outbound statistics: A set of outbound statistics attributes that are used to measure the outbound statistics of the termination point, such as "the total number of octets transmitted out of the termination point", "The number of outbound packets which were chosen to be discarded", "The number of outbound packets that contained errors", etc.

7. Example of I2RS Pub/Sub Retrieval [RFC7923]

This example shows the way for a client to subscribe for the Performance monitoring information between node A and node B in the L3 network topology built on top of the underlying network . The performance monitoring parameter that the client is interested in is end to end loss attribute.

```
<rpc netconf:message-id="101"
xmlns:netconf="urn:ietf:params:xml:ns:netconf:base:1.0">
<establish-subscription
xmlns="urn:ietf:params:xml:ns:yang:ietf-subscribed-notifications">
<stream-subtree-filter>
<networks xmlns="urn:ietf:params:xml:ns:yang:ietf-network-topo">
<networks xmlns="urn:ietf:params:xml:ns:yang:ietf-network-topo">
<network>
<network>
<network-id>l3-network</network-id>
<network-technology-type
xmlns="urn:ietf:params:xml:ns:yang:ietf-network-vpn-pm">
L3VPN
</network-technology-type>
<node>
</node>
</node-id>
</node-id>
</node-id>
</node-id>
</node-id>
</node-id>
</node-id>
</node-id>
</node-id>
</node-id=</pre>
```

```
network-vpn-pm">
```

<node-type>pe</node-type> </node-attribtues>

Wang, et al. Expires May 3, 2020

[Page 8]

```
Network and VPN Service PM YANG
Internet-Draft
                                                             October 2019
                   <termination-point xmlns="urn:ietf:params:xml:ns:yang:ietf-
network-topology">
                    <tp-id>1-0-1</tp-id>
                   <tp-telemetry-attributes
xmlns="urn:ietf:params:xml:ns:yang:ietf-network-vpn-pm">
                     <in-octets>100</in-octets>
                     <out-octets>150</out-octets>
                    </tp-telemetry-attributes>
                   </termination-point>
                  </node>
                  <node>
                   <node-id>B</node-id>
                   <node-attributes xmlns="urn:ietf:params:xml:ns:yang:ietf-
network-vpn-pm">
                    <node-type>pe</node-type>
                   </node-attribtues>
                   <termination-point xmlns="urn:ietf:params:xml:ns:yang:ietf-
network-topology">
                    <tp-id>2-0-1</tp-id>
                   <tp-telemetry-attributes
xmlns="urn:ietf:params:xml:ns:yang:ietf-network-vpn-pm">
                     <in-octets>150</in-octets>
                     <out-octets>100</out-octets>
                    </tp-telemetry-attributes>
                   </termination-point>
                  </node>
                  <link xmlns="urn:ietf:params:xml:ns:yang:ietf-network-
topology">
                   <link-id>A-B</link-id>
                   <source>
                    <source-node>A</source-node>
                   </source>
                   <destination>
                    <dest-node>B</dest-node>
                   </destination>
                    <link-type>mpls-te</link-type>
                    <link-telemetry-attributes
                     xmlns="urn:ietf:params:xml:ns:yang:ietf-network-vpn-pm">
                     <loss-statistics>
                      <packet-loss-count>100</packet-loss-count>
                     </loss-statistics>
                    </link-telemetry-attributes>
                   </link>
                </network>
             </networks>
          </stream-subtree-filter>
          <period xmlns="urn:ietf:params:xml:ns:yang:ietf-yang-push:1.0">500
period>
```

```
</establish-subscription>
</rpc>
```

Wang, et al. Expires May 3, 2020

[Page 9]

<u>8</u>. Example of RPC model based Retrieval

This example shows the way for the client to use RPC model to fetch performance data on demand,e.g., the client requests packet-loss-count between PE1 in site 1 and PE2 in site 2 belonging to the same VPN1.

```
<rpc xmlns="urn:ietf:params:xml:ns:netconf:base:1.0"

message-id="1">

<report xmlns="urn:ietf:params:xml:ns:yang:example-service-pm-report">

<networks xmlns="urn:ietf:params:xml:ns:yang:ietf-network-topo">

<networks xmlns="urn:ietf:params:xml:ns:yang:ietf-network-topo">

<network>

<network-id>vpn1</network-id>

<node>

<node-id>A</node-id>

<node-attributes xmlns="urn:ietf:params:xml:ns:yang:ietf-network-vpn-
```

pm">

```
<node-type>pe</node-type>
          </node-attribtues>
          <termination-point xmlns="urn:ietf:params:xml:ns:yang:ietf-network-</pre>
topology">
           <tp-id>1-0-1</tp-id>
           <tp-telemetry-attributes xmlns="urn:ietf:params:xml:ns:yang:ietf-
network-vpn-pm">
            <in-octets>100</in-octets>
            <out-octets>150</out-octets>
           </tp-telemetry-attributes>
          </termination-point>
         </node>
         <node>
          <node-id>B</node-id>
          <node-attributes xmlns="urn:ietf:params:xml:ns:yang:ietf-network-vpn-</pre>
pm">
          <node-type>pe</node-type>
          </node-attribtues>
          <termination-point xmlns="urn:ietf:params:xml:ns:yang:ietf-network-</pre>
topology">
           <tp-id>2-0-1</tp-id>
           <tp-telemetry-attributes xmlns="urn:ietf:params:xml:ns:yang:ietf-
network-vpn-pm">
            <in-octets>150</in-octets>
            <out-octets>100</out-octets>
           </tp-telemetry-attributes>
          </termination-point>
         </node>
         <link-id>A-B</link-id>
          <source>
           <source-node>A</source-node>
```

```
</source>
    <destination>
        <dest-node>B</dest-node>
        </destination>
        <link-type>mpls-te</link-type>
        <telemetry-attributes xmlns="urn:ietf:params:xml:ns:yang:ietf-
network-pm">
```

```
Wang, et al. Expires May 3, 2020 [Page 10]
```

```
<loss-statistics>
         <packet-loss-count>120</packet-loss-count>
        </loss-statistics>
       </telemetry-attributes>
      </link>
    </network>
  </report>
</rpc>
```

9. Network and VPN Service Assurance YANG Module

```
<CODE BEGINS> file "ietf-network-vpn-pm.yang"
module ietf-network-vpn-pm {
 yang-version 1.1;
 namespace "urn:ietf:params:xml:ns:yang:ietf-network-vpn-pm";
 prefix nvp;
  import ietf-network {
   prefix nw;
 }
  import ietf-network-topology {
    prefix nt;
 }
  import ietf-l3vpn-svc {
    prefix l3vpn-svc;
 }
 organization
    "IETF BESS Working Group";
 contact
    "Zitao Wang: wangzitao@huawei.com
     Qin Wu: bill.wu@huawei.com";
  description
    "This module defines a model for the VPN Service Performance monitoring.";
  revision 2019-03-01 {
    description
      "Initial revision.";
   reference
      "foo";
 }
 identity network-type {
    description
      "Base type for Overlay network topology";
 }
  identity l3vpn {
```

```
Internet-Draft Network and VPN Service PM YANG
```

```
base network-type;
  description
    "Indentity for layer3 vpn network type.";
}
identity l2vpn {
 base network-type;
  description
    "Identity for layer2 vpn network type.";
}
identity ospf {
  base network-type;
  description
    "Identity for OSPF network type.";
}
identity isis {
 base network-type;
  description
    "Identity for ISIS network type.";
}
identity node-type {
 description
    "Base identity for node type";
}
identity pe {
 base node-type;
  description
    "Identity for PE type";
}
identity ce {
 base node-type;
 description
    "Identity for CE type";
}
identity asbr {
  base node-type;
  description
   "Identity for ASBR type";
}
identity p {
  base node-type;
  description
```

```
Internet-Draft
                     Network and VPN Service PM YANG
                                                           October 2019
      "Identity for P type";
 }
  identity link-type {
    description
      "Base identity for link type, e.g., GRE, MPLS TE, VXLAN.";
 }
  identity gre {
   base link-type;
    description
      "Base identity for GRE Tunnel.";
  }
  identity VXLAN {
   base link-type;
    description
      "Base identity for VXLAN Tunnel.";
  }
  identity ip-in-ip {
    base link-type;
    description
      "Base identity for IP in IP Tunnel.";
  }
  identity direction {
    description
      "Base Identity for measurement direction including
       one way measurement and two way measurement.";
 }
  identity oneway {
    base direction;
    description
      "Identity for one way measurement.";
 }
 identity twoway {
    base direction;
    description
      "Identity for two way measurement.";
  }
  typedef percentage {
   type decimal64 {
     fraction-digits 5;
      range "0..100";
    }
    description
      "Percentage.";
  }
```

```
grouping link-error-statistics {
  description
    "Grouping for per link error statistics";
  container loss-statistics {
   description
      "Per link loss statistics.";
   leaf direction {
      type identityref {
        base direction;
      }
      default "oneway";
      description
        "Define measurement direction including one way
         measurement and two way measurement.";
   }
   leaf packet-loss-count {
      type uint32 {
        range "0..4294967295";
      }
      default "0";
      description
        "Total received packet drops count.
         The value of count will be set to zero (0)
         on creation and will thereafter increase
         monotonically until it reaches a maximum value
         of 2^32-1 (4294967295 decimal), when it wraps
         around and starts increasing again from zero.";
    }
   leaf loss-ratio {
      type percentage;
      description
        "Loss ratio of the packets. Express as percentage
         of packets lost with respect to packets sent.";
   }
   leaf packet-reorder-count {
      type uint32 {
        range "0..4294967295";
      }
      default "0";
      description
        "Total received packet reordered count.
         The value of count will be set to zero (0)
         on creation and will thereafter increase
         monotonically until it reaches a maximum value
         of 2^32-1 (4294967295 decimal), when it wraps
         around and starts increasing again from zero.";
    }
   leaf packets-out-of-seq-count {
```

```
type uint32 {
        range "0..4294967295";
      }
      description
        "Total received out of sequence count.
         The value of count will be set to zero (0)
         on creation and will thereafter increase
         monotonically until it reaches a maximum value
         of 2^32-1 (4294967295 decimal), when it wraps
         around and starts increasing again from zero..";
    }
   leaf packets-dup-count {
      type uint32 {
        range "0..4294967295";
      }
      description
        "Total received packet duplicates count.
         The value of count will be set to zero (0)
         on creation and will thereafter increase
         monotonically until it reaches a maximum value
         of 2^32-1 (4294967295 decimal), when it wraps
         around and starts increasing again from zero.";
   }
  }
}
grouping link-delay-statistics {
 description
    "Grouping for per link delay statistics";
  container delay-statistics {
   description
      "Link delay summarised information. By default,
       one way measurement protocol (e.g., OWAMP) is used
       to measure delay.";
   leaf direction {
      type identityref {
        base direction;
      }
      default "oneway";
      description
        "Define measurement direction including one way
        measurement and two way measurement.";
    }
   leaf min-delay-value {
      type uint32;
      description
        "Minimum delay value observed.";
   }
```

```
leaf max-delay-value {
        type uint32;
        description
          "Maximum delay value observed.";
      }
      leaf average-delay-value {
        type uint32;
        description
          "Average delay is calculated on all the packets of a sample
           and is a simple computation to be performed for single marking
method.";
      }
    }
  }
  grouping link-jitter-statistics {
    description
      "Grouping for per link jitter statistics";
    container jitter-statistics {
      description
        "Link jitter summarised information. By default,
         jitter is measured using IP Packet Delay Variation
         (IPDV) as defined in <u>RFC3393</u>.";
      leaf direction {
        type identityref {
          base direction;
        }
        default "oneway";
        description
          "Define measurement direction including one way
           measurement and two way measurement.";
      }
      leaf min-jitter-value {
        type uint32;
        description
          "Minimum jitter value observed.";
      }
      leaf max-jitter-value {
        type uint32;
        description
          "Maximum jitter value observed.";
      }
      leaf average-jitter-value {
        type uint32;
        description
          "Average jitter is calculated on all the packets of a sample
           and is a simple computation to be performed for single marking
method.";
```

} }

Wang, et al. Expires May 3, 2020

[Page 16]

```
}
grouping tp-svc-telemetry {
  leaf in-octets {
    type uint32;
    description
      "The total number of octets received on the
       interface, including framing characters.";
  }
  leaf inbound-unicast {
    type uint32;
    description
      "Inbound unicast packets were received, and delivered
       to a higher layer during the last period.";
  }
  leaf inbound-nunicast {
    type uint32;
    description
      "The number of non-unicast (i.e., subnetwork-
       broadcast or subnetwork-multicast) packets
       delivered to a higher-layer protocol.";
  }
  leaf inbound-discards {
    type uint32;
    description
      "The number of inbound packets which were chosen
       to be discarded even though no errors had been
       detected to prevent their being deliverable to a
       higher-layer protocol.";
  }
  leaf inbound-errors {
    type uint32;
    description
      "The number of inbound packets that contained
       errors preventing them from being deliverable to a
       higher-layer protocol.";
  }
  leaf inunknow-protos {
    type uint32;
    description
      "The number of packets received via the interface
       which were discarded because of an unknown or
       unsupported protocol";
  }
  leaf out-octets {
    type uint32;
    description
```

```
"The total number of octets transmitted out of the
       interface, including framing characters";
  }
  leaf outbound-unicast {
   type uint32;
   description
      "The total number of packets that higher-level
       protocols requested be transmitted to a
       subnetwork-unicast address, including those that
       were discarded or not sent.";
  }
  leaf outbound-nunicast {
    type uint32;
   description
      "The total number of packets that higher-level
       protocols requested be transmitted to a non-
       unicast (i.e., a subnetwork-broadcast or
       subnetwork-multicast) address, including those
       that were discarded or not sent.";
  }
 leaf outbound-discards {
   type uint32;
   description
      "The number of outbound packets which were chosen
       to be discarded even though no errors had been
       detected to prevent their being transmitted. One
       possible reason for discarding such a packet could
       be to free up buffer space.";
  }
  leaf outbound-errors {
    type uint32;
   description
      "The number of outbound packets that contained
       errors preventing them from being deliverable to a
       higher-layer protocol.";
  }
  leaf outbound-glen {
    type uint32;
    description
      " Length of the queue of the interface from where
        the packet is forwarded out. The queue depth could
         be the current number of memory buffers used by the
        queue and a packet can consume one or more memory buffers
        thus constituting device-level information.";
  }
  description
    "Grouping for interface service telemetry";
}
```

```
Network and VPN Service PM YANG
                                                      October 2019
Internet-Draft
 augment "/nw:networks/nw:network/nw:network-types" {
    description
      "Augment the network-types with service topologyies types";
    leaf-list network-technology-type {
     type identityref {
       base network-type;
     }
     description
        "Identify the network technology type,e.g.,L3VPN,L2VPN, ISIS, OSPF.";
    }
 }
 augment "/nw:networks/nw:network" {
   description
      "Augment the network with service topology attributes";
   container overlay-topo-attributes {
     leaf vpn-topology {
       type identityref {
          base l3vpn-svc:vpn-topology;
       }
       description
          "VPN service topology, e.g. hub-spoke, any-to-any, hub-spoke-
disjoint, etc";
      }
     description
       "Container for vpn services";
    }
 }
 augment "/nw:networks/nw:network/nw:node" {
    description
      "Augment the network node with overlay topology attributes";
   container node-attributes {
     leaf node-type {
       type identityref {
          base node-type;
       }
       description
          "Node type, e.g. PE, P, ASBR, etc";
      }
     leaf site-id {
       type string;
       description
          "Asscoiated vpn site";
      }
     leaf site-role {
       type identityref {
          base l3vpn-svc:site-role;
       }
       default "l3vpn-svc:any-to-any-role";
```

description

Wang, et al. Expires May 3, 2020 [Page 19]

```
Network and VPN Service PM YANG
                                                          October 2019
Internet-Draft
          "Role of the site in the VPN.";
      }
      description
        "Container for overlay topology attributes";
    }
  }
  augment "/nw:networks/nw:network/nt:link" {
    description
      "Augment the network topology link with overlay topology attributes";
     leaf link-type {
        type identityref {
          base link-type;
        }
        description
          "Link type, e.g. GRE, VXLAN, IP in IP, etc";
      }
    container link-telemetry-attributes {
      config false;
      uses link-error-statistics;
      uses link-delay-statistics;
      uses link-jitter-statistics;
      description
        "Container for service telemetry attributes";
    }
  }
  augment "/nw:networks/nw:network/nw:node/nt:termination-point" {
    description
      "Augment the network topology termination point with vpn service
attributes";
    container tp-telemetry-attributes {
      config false;
      uses tp-svc-telemetry;
      description
        "Container for termination point service telemetry attributes.";
    }
 }
}
```

<CODE ENDS>

<u>10</u>. Security Considerations

The YANG modules defined in this document MAY be accessed via the RESTCONF protocol [RFC8040] or NETCONF protocol ([RFC6241]). The lowest RESTCONF or NETCONF layer requires that the transport-layer protocol provides both data integrity and confidentiality, see Section 2 in [RFC8040] and [RFC6241]. The lowest NETCONF layer is the secure transport layer, and the mandatory-to-implement secure

transport is Secure Shell (SSH) [${\tt RFC6242}$] . The lowest <code>RESTCONF</code> layer

Wang, et al. Expires May 3, 2020

[Page 20]

Internet-Draft

Network and VPN Service PM YANG October 2019

is HTTPS, and the mandatory-to-implement secure transport is TLS [<u>RFC5246</u>].

The NETCONF access control model [RFC6536] provides the means to restrict access for particular NETCONF or RESTCONF users to a preconfigured subset of all available NETCONF or RESTCONF protocol operations and content.

There are a number of data nodes defined in this YANG module that are writable/creatable/deletable (i.e., config true, which is the default). These data nodes may be considered sensitive or vulnerable in some network environments. Write operations (e.g., edit-config) to these data nodes without proper protection can have a negative effect on network operations. These are the subtrees and data nodes and their sensitivity/vulnerability:

- o /nw:networks/nw:network/svc-topo:svc-telemetry-attributes
- o /nw:networks/nw:network/nw:node/svc-topo:node-attributes

11. IANA Considerations

This document registers a URI in the IETF XML registry [RFC3688]. Following the format in [<u>RFC3688</u>], the following registration is requested to be made:

URI: urn:ietf:params:xml:ns:yang:ietf-network-vpn-pm

Registrant Contact: The IESG.

XML: N/A, the requested URI is an XML namespace. _____

This document registers a YANG module in the YANG Module Names registry [RFC6020].

Name:	ietf-network-vpn-pm
Namespace:	urn:ietf:params:xml:ns:yang:ietf-network-vpn-pm
Prefix:	nvp
Reference:	RFC xxxx

12. Normative References

- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", March 1997.
- Mealling, M., "The IETF XML Registry", BCP 81, RFC 3688, [RFC3688] DOI 10.17487/RFC3688, January 2004, <https://www.rfc-editor.org/info/rfc3688>.
- [RFC5440] Vasseur, JP., Ed. and JL. Le Roux, Ed., "Path Computation Element (PCE) Communication Protocol (PCEP)", RFC 5440, DOI 10.17487/RFC5440, March 2009, <https://www.rfc-editor.org/info/rfc5440>.
- [RFC6020] Bjorklund, M., Ed., "YANG A Data Modeling Language for the Network Configuration Protocol (NETCONF)", RFC 6020, DOI 10.17487/RFC6020, October 2010, <https://www.rfc-editor.org/info/rfc6020>.
- [RFC6241] Enns, R., Ed., Bjorklund, M., Ed., Schoenwaelder, J., Ed., and A. Bierman, Ed., "Network Configuration Protocol (NETCONF)", <u>RFC 6241</u>, DOI 10.17487/RFC6241, June 2011, <https://www.rfc-editor.org/info/rfc6241>.
- [RFC6242] Wasserman, M., "Using the NETCONF Protocol over Secure Shell (SSH)", RFC 6242, DOI 10.17487/RFC6242, June 2011, <https://www.rfc-editor.org/info/rfc6242>.
- [RFC6370] Bocci, M., Swallow, G., and E. Gray, "MPLS Transport Profile (MPLS-TP) Identifiers", RFC 6370, DOI 10.17487/RFC6370, September 2011, <https://www.rfc-editor.org/info/rfc6370>.
- [RFC6374] Frost, D. and S. Bryant, "Packet Loss and Delay Measurement for MPLS Networks", RFC 6374, DOI 10.17487/RFC6374, September 2011, <https://www.rfc-editor.org/info/rfc6374>.
- Bierman, A. and M. Bjorklund, "Network Configuration [RFC6536] Protocol (NETCONF) Access Control Model", RFC 6536, DOI 10.17487/RFC6536, March 2012, <https://www.rfc-editor.org/info/rfc6536>.
- [RFC7923] Voit, E., Clemm, A., and A. Gonzalez Prieto, "Requirements for Subscription to YANG Datastores", <u>RFC 7923</u>, DOI 10.17487/RFC7923, June 2016, <https://www.rfc-editor.org/info/rfc7923>.

- [RFC7950] Bjorklund, M., Ed., "The YANG 1.1 Data Modeling Language", RFC 7950, DOI 10.17487/RFC7950, August 2016, <https://www.rfc-editor.org/info/rfc7950>.
- [RFC7952] Lhotka, L., "Defining and Using Metadata with YANG", RFC 7952, DOI 10.17487/RFC7952, August 2016, <https://www.rfc-editor.org/info/rfc7952>.
- [RFC8340] Bjorklund, M. and L. Berger, Ed., "YANG Tree Diagrams", BCP 215, RFC 8340, DOI 10.17487/RFC8340, March 2018, <https://www.rfc-editor.org/info/rfc8340>.
- [RFC8345] Clemm, A., Medved, J., Varga, R., Bahadur, N., Ananthakrishnan, H., and X. Liu, "A YANG Data Model for Network Topologies", RFC 8345, DOI 10.17487/RFC8345, March 2018, <https://www.rfc-editor.org/info/rfc8345>.

Authors' Addresses

Michael Wang Huawei Technologies, Co., Ltd 101 Software Avenue, Yuhua District Nanjing 210012 China

Email: wangzitao@huawei.com

Qin Wu Huawei 101 Software Avenue, Yuhua District Nanjing, Jiangsu 210012 China

Email: bill.wu@huawei.com

Roni Even Huawei Technologies, Co., Ltd Tel Aviv Israel

Email: roni.even@huawei.com

Wang, et al. Expires May 3, 2020 [Page 23]

Bin Wen Comcast

Email: bin_wen@comcast.com

Change Liu China Unicom

Email: liuc131@chinaunicom.cn

Honglei Xu China Telecom

Email: xuhl.bri@chinatelecom.cn