

DeNet WG
Internet-Draft
Intended status: Standards Track
Expires: May 4, 2020

Q. Xiong
Y. Han
ZTE Corporation
F. Qin
P. Liu
China Mobile
November 1, 2019

DetNet QoS Yang
draft-xiong-detnet-qos-yang-02

Abstract

This document defines a YANG data model for Deterministic Networking (DetNet) Quality of Service (QoS) based on the Differentiated Services (DiffServ) model.

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <https://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on May 4, 2020.

Copyright Notice

Copyright (c) 2019 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<https://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in [Section 4.e](#) of

Internet-Draft

DetNet QoS Yang

November 2019

the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

Table of Contents

1.	Introduction	2
1.1.	Requirements Language	2
1.2.	Terminology	2
2.	DetNet DiffServ QoS Model	3
2.1.	DetNet QoS Tree Structure	3
2.2.	DetNet QoS Module	4
3.	Security Considerations	13
4.	IANA Considerations	13
5.	Acknowledgements	13
6.	References	13
6.1.	Informative References	13
6.2.	Normative References	13
	Authors' Addresses	14

[1.](#) Introduction

Deterministic Networking (DetNet) as defined in [[RFC8655](#)], provides a capability to carry specified unicast or multicast data flows for real-time applications with extremely low data loss rates and bounded latency. In the meanwhile, DetNet and non-DetNet packets are allowed to be transmitted in the same network and more than one DetNet flows which has different priorities may be forwarded through the DetNet domain. As discussed in [[I-D.ietf-detnet-ip](#)] and [[I-D.xiong-detnet-qos-policy](#)], the Differentiated Services (DiffServ) can be used to provide Quality of Service (QoS) for DetNet services.

This document defines a YANG data model for DetNet QoS based on the DiffServ model.

[1.1.](#) Requirements Language

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [[RFC2119](#)].

[1.2.](#) Terminology

The terminology is defined as [[RFC8655](#)], [[RFC3270](#)], [[RFC2474](#)] and

[2.](#) DetNet DiffServ QoS Model

This document defines a YANG data module for DetNet DiffServ QoS Model as discussed in [[I-D.xiong-detnet-qos-policy](#)]. In the ietf-detnet-qos module, this is performed as one of the DetNet QoS policy.

[2.1.](#) DetNet QoS Tree Structure

DetNet DiffServ model is one type of the DetNet QoS policy and other policy types can be defined in detnet-policy-type.

[[I-D.xiong-detnet-qos-policy](#)] specified two types of classifiers including BA (Behavior Aggregate) and MF (Multi-Field) classifiers in detnet-classifier-type. DetNet IP BA classifier selects packets based on the DiffServ Code Point (DSCP) and DetNet MPLS BA classifier is based on the MPLS Traffic Class (TC) field. DetNet IP MF classifier selects packets based on the value of a combination of source address, destination address, DSCP, protocol ID, source port and destination port numbers and DetNet MPLS MF classifier is based on the MPLS TC , service label (S-Label) field and forwarding labels (F-Labels) of the header.

[[I-D.xiong-detnet-qos-policy](#)] defined a DetNet (DN) Per Hop Behavior (PHB) for DetNet forward other than existing PHBs including AF,EF,CS,DF etc. The PHB class information description is as qos-phb-class shown.

[[I-D.xiong-detnet-qos-policy](#)] defined two new types of action for DetNet traffic conditioning named order and scheduler action. Other actions including meter, shaper, dropper and marker as the detnet-action-type shown.

```
module: ietf-detnet-qos
  +--rw detnet-qos-policies
    +--rw detnet-policy-template* [detnet-policy-name]
      +--rw detnet-policy-name      string
```

```

+--rw detnet-policy-type?          detnet-policy-type
+--rw detnet-classifier-template* [detnet-classifier-name]
  +--rw detnet-classifier-name      string
  +--rw detnet-classifier-type?     detnet-classifier-type
  +--rw (classifier-type)?
    | +--:(ba)
    | | +--rw (encapsulation-type)?
    | | | +--:(MPLS)
    | | | | +--rw mpls-ba* [tc-value]
    | | | | | +--rw phb-class?   qos-phb-class
    | | | | | +--rw tc-value     uint8
    | | | +--:(IP)

```

```

    | | +--rw ip-ba* [dscp-value]
    | | | +--rw phb-class?   qos-phb-class
    | | | +--rw dscp-value   uint8
    | +--:(mf)
    | | +--rw (tunnel-type)?
    | | | +--:(MPLS)
    | | | | +--rw mpls-mf* [tc-value]
    | | | | | +--rw phb-class?   qos-phb-class
    | | | | | +--rw tc-value     uint8
    | | | | | +--rw s-label?     uint32
    | | | | | +--rw f-labels* [f-label-id]
    | | | | | +--rw f-label-id   uint32
    | +--:(IPv4)
    | | +--rw ipv4-mf* [dscp-value]
    | | | +--rw phb-class?           qos-phb-class
    | | | +--rw dscp-value           uint8
    | | | +--rw ipv4-source-address? inet:ipv4-address
    | | | +--rw ipv4-destination-address? inet:ipv4-address
    | | | +--rw protocol-ID?         uint8
    | | | +--rw source-port-numbers? inet:port-number
    | | | +--rw destination-port-numbers? inet:port-number
    | +--:(IPv6)
    | | +--rw ipv6-mf* [dscp-value]
    | | | +--rw phb-class?           qos-phb-class
    | | | +--rw dscp-value           uint8
    | | | +--rw ipv6-source-address? inet:ipv6-address
    | | | +--rw ipv6-destination-address? inet:ipv6-address
    | | | +--rw protocol-ID?         uint8
    | | | +--rw source-port-numbers? inet:port-number

```

```

|               +---rw destination-port-numbers?   inet:port-number
|               +---rw flow-label?                 inet:ipv6-flow-label
+---rw detnet-action* [detnet-action-type]
    +---rw detnet-action-type      detnet-action-type
    +---rw (actions)?
        +---:(meter)
        +---:(marker)
        +---:(shaper)
        +---:(dropper)
        +---:(order)
        +---:(scheduler)

```

2.2. DetNet QoS Module

```

<CODE BEGINS> file "detnet-diffserv-qos@2018-10-13.yang"
module ietf-detnet-qos {
    yang-version 1;
    namespace "urn:ietf:params:xml:ns:yang:ietf-detnet-qos";
    prefix detnet-qos;

```

```

    import ietf-inet-types{
    prefix "inet";
    }

    organization "IETF DetNet Working Group";
    contact
    "WG Web:   <http://tools.ietf.org/wg/detnet/>
    WG List:  <mailto:detnet@ietf.org>
    WG Chair: Lou Berger
              <mailto:lberger@labn.net>
              Janos Farkas
              <janos.farkas@ericsson.com>
    Editor:   Quan Xiong
              <mailto:xiong.quan@zte.com.cn>
    Editor:   Yufang Han
              <mailto:han.yufang1@zte.com.cn>";

    description
    "This YANG module describes the Deterministic Networking (DetNet)
    Quality of Service (QoS) based on the Differentiated Services (Diffs
    model.";

```

```

revision "2018-10-13" {
    description "initial revision";
    reference "RFC XXXX: draft-xiong-detnet-qos-yang-01";
}

typedef qos-phb-class {
    type enumeration {
        enum df {
            value 1 ;
            description "Default Forwarding for Best effort";
        }
        enum af1 {
            value 2 ;
            description "Assured forwarding class 1";
        }
        enum af2 {
            value 3 ;
            description "Assured forwarding class 2";
        }
        enum af3 {
            value 4 ;
            description "Assured forwarding class 3";
        }
        enum af4 {
            value 5 ;
            description "Assured forwarding class 4";
        }
    }
}

```

```

    }
    enum ef {
        value 6 ;
        description "Expedited forward";
    }
    enum cs6 {
        value 7 ;
        description "Internetwork control service class";
    }
    enum cs7 {
        value 8 ;
        description "Network control service class";
    }
    enum dn {
        value 9 ;
    }
}

```

```

        description "DetNet forward";
    }
}
    description
    "The PHB class including AF,EF,CS,DF,DN";
}

typedef detnet-policy-type {
    type enumeration {
        enum diffserv {
            value 1 ;
            description "DiffServ Policy";
        }
    }
    description
    "The DetNet policy type.";
}

typedef detnet-classifier-type {
    type enumeration {
        enum ba {
            value 1 ;
            description "DiffServ BA Classifier";
        }
        enum mf {
            value 2 ;
            description "DiffServ MF Classifier";
        }
    }
    description
    "The DetNet classifier type including BA and MF.";
}

```

```

typedef detnet-action-type {
    type enumeration {
        enum meter {
            value 1 ;
            description "DiffServ meter Action";
        }
        enum shaper {
            value 2 ;

```

```

        description "DiffServ shaper Action";
    }
    enum dropper {
    value 3 ;
        description "DiffServ dropper Action";
    }
    enum marker {
    value 4 ;
        description "DiffServ marker Action";
    }
    enum order {
    value 5 ;
        description "DiffServ order Action";
    }
    enum scheduler {
    value 6 ;
        description "DiffServ scheduler Action";
    }
}
description
"The DetNet classifier type including BA and MF.";
}

grouping mpls-tc {
description "MPLS TC Information";
leaf phb-class {
    type qos-phb-class;
    description "Specify phb class of PHB info, support [a"
+ "f1,af2,af3,af4,be,ef,cs6,cs7,dn]";
}
leaf tc-value {
    type uint8 {
        range 0..7 {
            description "MPLS-TC value, support [0-7]";
        }
    }
    mandatory true ;
    description "MPLS-TC value, support [0-7]";
}
}
}

```

```

grouping ip-dscp {

```



```

description "IP DSCP Information";
leaf phb-class {
    type qos-phb-class ;
    description "Specify server class of PHB info, support [a"
    + "f1,af2,af3,af4,be,ef,cs6,cs7,dn]";
}
leaf dscp-value {
    type uint8 {
        range 0..63 {
            description "IPv4/IPv6 DSCP value, support [0-63]";
        }
    }
    mandatory true ;
    description "IPv4/IPv6 DSCP value, support [0-63]";
}
}

grouping mpls-header-info {
    description "MPLS TC Information";
    leaf phb-class {
        type qos-phb-class ;
        description "Specify phb class of PHB info, support [a"
        + "f1,af2,af3,af4,be,ef,cs6,cs7,dn]";
    }
    leaf tc-value {
        type uint8 {
            range 0..7 {
                description "MPLS-TC value, support [0-7]";
            }
        }
        mandatory true ;
        description "MPLS-TC value, support [0-7]";
    }
    leaf s-label {
        type uint32;
        description "DetNet Flow ID value, support classifier MF";
    }
    list f-labels {
        key "f-label-id";
        description "DetNet forwarding label id, support classifi
        leaf f-label-id {
            type uint32;
            description "DetNet forwarding label value, sup
        }
    }
}
}

```

```
grouping ipv4-header-info {
  description "IP DSCP Information";
  leaf phb-class {
    type qos-phb-class ;
    description "Specify server class of PHB info, support [a"
      + "f1,af2,af3,af4,be,ef,cs6,cs7,dn]";
  }
  leaf dscp-value {
    type uint8 {
      range 0..63 {
        description "IPv4/IPv6 DSCP value, support [0-63]";
      }
    }
    mandatory true ;
    description "IPv4/IPv6 DSCP value, support [0-63]";
  }
  leaf ipv4-source-address {
    type inet:ipv4-address;
    description "source address value, support classifier MF";
  }
  leaf ipv4-destination-address {
    type inet:ipv4-address;
    description "destination address value, support classifier MF";
  }
  leaf protocol-ID {
    type uint8;
    description "protocol ID, support classifier MF";
  }
  leaf source-port-numbers {
    type inet:port-number;
    description "source port numbers, support classifier MF";
  }
  leaf destination-port-numbers {
    type inet:port-number;
    description "destination port numbers, support classifier MF";
  }
}

grouping ipv6-header-info {
  description "IPv6 DSCP Information";
  leaf phb-class {
    type qos-phb-class ;
    description "Specify server class of PHB info, support [a"
      + "f1,af2,af3,af4,be,ef,cs6,cs7,dn]";
  }
  leaf dscp-value {
```

```
type uint8 {
    range 0..63 {
```

```
        description "IPv4/IPv6 DSCP value, support [0-63]";
    }
}
mandatory true ;
        description "IPv4/IPv6 DSCP value, support [0-63]";
}
    leaf ipv6-source-address {
        type inet:ipv6-address;
        description "source address value, support classifier MF";
    }
    leaf ipv6-destination-address {
        type inet:ipv6-address;
        description "destination address value, support classifier M";
    }
    leaf protocol-ID {
        type uint8;
        description "protocol ID, support classifier MF";
    }
    leaf source-port-numbers {
        type inet:port-number;
        description "source port numbers, support classifier MF";
    }
    leaf destination-port-numbers {
        type inet:port-number;
        description "destination port numbers, support classifier M";
    }
    leaf flow-label {
type inet:ipv6-flow-label;
description
    "The flow label of the header.";
    }
}

grouping detnet-classifiers {
    description "Configure the DetNet classifiers";
    choice classifier-type {
        description "Choice of classifiers types";
        case ba {
            description "BA classifier";
```

```

        choice encapsulation-type {
description "Tunnel type includes: IP, MPLS.";
case MPLS {
        list mpls-ba {
            key "tc-value";
            description "MPLS-TC be mapped to P
        uses mpls-tc;
        }
    }
}

```

```

        case IP {
            list ip-ba {
                key "dscp-value";
                description "IPv4/IPv6 DSCP be mapp
            uses ip-dscp;
            }
        }
    }
    case mf {
        description "MF classifier";
        choice tunnel-type {
description
    "Tunnel type includes: IPv4, IPv6, MPLS.";
case MPLS {
            list mpls-mf {
                key "tc-value";
                description "MPLS-TC be mapped to P
            uses mpls-header-info;
            }
        }
    case IPv4 {
        list ipv4-mf {
            key "dscp-value";
            description "IPv4 DSCP be mapped to
        uses ipv4-header-info;
        }
    }
    case IPv6 {
        list ipv6-mf {
            key "dscp-value";
            description "IPv6 DSCP be mapped to

```

```

        uses ipv6-header-info;
    }
}

}

grouping detnet-actions {
description
    "DetNet Configuration about the actions";
list detnet-action {
    key "detnet-action-type";
    description "DetNet actions, to be defined.";
    leaf detnet-action-type {
        type detnet-action-type;
    }
}
}

```

```

        description "DetNet action types";
    }
    choice actions {
        description "Choice of action types";
        case meter {
            description "meter action";
        }
        case marker {
            description "marker action";
        }
        case shaper {
            description "shaper action";
        }
        case dropper {
            description "dropper action";
        }
        case order {
            description "order action";
        }
        case scheduler {
            description "scheduler action";
        }
    }
}
}

```


5. Acknowledgements

TBD.

6. References

6.1. Informative References

- [RFC2475] Blake, S., Black, D., Carlson, M., Davies, E., Wang, Z., and W. Weiss, "An Architecture for Differentiated Services", [RFC 2475](#), DOI 10.17487/RFC2475, December 1998, <<https://www.rfc-editor.org/info/rfc2475>>.

6.2. Normative References

- [I-D.ietf-detnet-ip]
Varga, B., Farkas, J., Berger, L., Fedyk, D., Malis, A., Bryant, S., and J. Korhonen, "DetNet Data Plane: IP", [draft-ietf-detnet-ip-03](#) (work in progress), October 2019.
- [I-D.xiong-detnet-qos-policy]
Xiong, Q. and Y. jinghai, "DetNet QoS Policy", [draft-xiong-detnet-qos-policy-01](#) (work in progress), March 2019.
- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), DOI 10.17487/RFC2119, March 1997, <<https://www.rfc-editor.org/info/rfc2119>>.

Xiong, et al.

Expires May 4, 2020

[Page 13]

Internet-Draft

DetNet QoS Yang

November 2019

- [RFC2474] Nichols, K., Blake, S., Baker, F., and D. Black, "Definition of the Differentiated Services Field (DS Field) in the IPv4 and IPv6 Headers", [RFC 2474](#), DOI 10.17487/RFC2474, December 1998, <<https://www.rfc-editor.org/info/rfc2474>>.
- [RFC3270] Le Faucheur, F., Wu, L., Davie, B., Davari, S., Vaananen, P., Krishnan, R., Cheval, P., and J. Heinanen, "Multi-Protocol Label Switching (MPLS) Support of Differentiated Services", [RFC 3270](#), DOI 10.17487/RFC3270, May 2002, <<https://www.rfc-editor.org/info/rfc3270>>.

- [RFC5462] Andersson, L. and R. Asati, "Multiprotocol Label Switching (MPLS) Label Stack Entry: "EXP" Field Renamed to "Traffic Class" Field", [RFC 5462](https://www.rfc-editor.org/info/rfc5462), DOI 10.17487/RFC5462, February 2009, <<https://www.rfc-editor.org/info/rfc5462>>.
- [RFC8655] Finn, N., Thubert, P., Varga, B., and J. Farkas, "Deterministic Networking Architecture", [RFC 8655](https://www.rfc-editor.org/info/rfc8655), DOI 10.17487/RFC8655, October 2019, <<https://www.rfc-editor.org/info/rfc8655>>.

Authors' Addresses

Quan Xiong
ZTE Corporation
No.6 Huashi Park Rd
Wuhan, Hubei 430223
China

Phone: +86 27 83531060
Email: xiong.quan@zte.com.cn

Yufang Han
ZTE Corporation
50 Software Avenue, YuHuaTai District
Nanjing, Jiangsu 210012
China

Phone: +86 15951984307
Email: han.yufang1@zte.com.cn

Fengwei Qin
China Mobile
Beijing
China

Email: qinfengwei@chinamobile.com

Peng Liu
China Mobile
Beijing 100053
China

Email: liupengyjy@chinamobile.com