

Deterministic Networking Working Group
Internet-Draft
Intended status: Informational
Expires: 2 September 2022

H. Yang
P. Liu
China Mobile
1 March 2022

One-way Delay Measurement Based on Deterministic Networking
draft-yang-detnet-deterministic-owd-measurement-00

Abstract

One-way delay is a key indicator to measure network quality. Some applications are one-way transmission in the network, such as some high-definition video services, and are very sensitive to one-way delay. Excessive delay will affect user experience greatly. To some extent, the network can't even be used, so it is very important to accurately measure the network transmission delay. The current one-way delay measurement method has problems such as high complexity and low measurement accuracy. In order to solve the problem of high-precision one-way delay measurement, a one-way delay measurement method based on deterministic networking is proposed in this document. The method takes advantage of the delay characteristics of the deterministic networking and does not depend on precise time synchronization. The method realizes the one-way delay measurement of any service flow between any network elements. Its technical advantages are: the network does not need to send measurement packets, can test all traffic types, does not change network status, does not change the format of traffic packets, and does not require network elements to support time synchronization protocols.

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <https://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on 2 September 2022.

Internet-Draft

Deterministic Networking

March 2022

Copyright Notice

Copyright (c) 2022 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<https://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Revised BSD License text as described in Section 4.e of the [Trust Legal Provisions](#) and are provided without warranty as described in the Revised BSD License.

Table of Contents

1.	Introduction	2
2.	Conventions Used in This Document	3
2.1.	Terminology	3
2.2.	Requirements Language	4
3.	One-way Delay Measurement Method Based on Deterministic Networking	4
4.	Procedures of the One-way Delay Measurement Method	7
5.	Security Considerations	8
6.	IANA Considerations	8
7.	Normative References	8
	Authors' Addresses	9

[1.](#) Introduction

One-way transmission delay is a key indicator to measure network quality. Some applications are based on one-way transmission in the network, such as some high-definition video services, and are very sensitive to one-way delay. Excessive one-way delay will affect user experience dramatically, so it is very important to accurately measure the one-way transmission delay of the network.

There are several kinds of methods to measure one-way delay. The first kind of methods is active measurement. A sender will send measurement protocol messages, such as Two-Way Active Measurement Protocol (TWAMP) [[RFC8186](#)] messages, to the network to measure the one-way delay of the sender and receiver. The advantage of active measurement is that it is flexible in application. The disadvantage

is that the measurement messages cannot measure the delay of real services, and the measurement of one-way delay requires sender and receiver to support time synchronization protocol, such as NTP [[RFC5905](#)] and PTP [[IEEE.1588.2008](#)]. The first kind of methods is passive measurement. The passive measurement devices will calculate

network delay by collecting actual business traffic. The advantage of passive measurement is that it can measure the one-way delay of real services. The disadvantage is that two passive measurement devices need to be deployed, and the two devices require time synchronization, which is difficult to implement. The third kind of methods is hybrid measurement. Hybrid measurement is a combination of active and passive measurements, that is, inserting some fields or flags in the service message to realize the delay measurement of the actual service. The disadvantage is that the message format of the actual service is changed, which will affect the forwarding behavior of the service and have observer effect. The network element needs to be able to recognize and forward the modified service message, and time synchronization of the network element is also required.

The above-mentioned one-way delay measurement methods have the following shortcomings. Firstly, if the measurement message is injected into actual network, it will occupy network bandwidth resources and interfere with the actual service flow, so the measured delay is not the delay of the actual service. Secondly, the measurement equipment or network elements need to support time synchronization protocols, which is difficult to implement and costly.

To address the following shortcomings of existing methods, this document presents the following technical solution. A high-precision one-way delay measurement method is proposed, which can be used to measure the one-way delay of actual service packets, without sending measurement messages, without changing the actual network status, without changing service messages, and without the need for network elements to support time synchronization protocols.

[2.](#) Conventions Used in This Document

[2.1.](#) Terminology

NTP Network Time Protocol

SLA Service Level Agreement

[Page 3]

March 2022

The diagram illustrates a centralized control node architecture. At the top, a dashed box labeled "Centralized Control Node" spans the width of the diagram. Below this node, there are four vertical dashed lines representing connections to different network elements. These connections are labeled T1, T2, T4, T3, and Tn from left to right. Each connection leads to a block labeled "Network". Inside each "Network" block, there is an "Element" (Element 1, Element 2, Element 4, Element n). The connections are shown as dashed lines with arrows pointing from the control node to the elements. Additionally, there is a connection from the control node to a "Network Element 3" block, which is also labeled T3. The diagram uses dashed lines and arrows to represent the communication links between the control node and the network elements.

Figure 1: Figure 1: A schematic diagram of the network topology structure

A schematic diagram of the network topology structure to describe the proposed method is shown in Figure 1. The network may be a SDN (Software Defined Network) or a traditional network. Whether it is SDN or traditional network, there is a centralized control node (or called a centralized management unit) for collecting network information sent by network elements and sending control information to the network. Taking SDN as an example, the centralized control node can be a SDN controller. For traditional networks, the centralized control node can be a network management system. The information from the network element to the centralized control node generally passes through the management network. In our solution, the management network from each network element to the centralized control node is required to use a delay deterministic network. As an example, the delay deterministic network may be a time sensitive network (TSN) or a deterministic Internet (Deterministic Internet

Network, DIP) [[RFC8655](#)], etc. Through the delay deterministic network, the transmission delay of the network element information from the network element to the centralized control node can be guaranteed to be fixed. $T_1 \sim T_n$ in Figure 1 represent the network element information delay from the network element to the centralized control node of network element 1 to n respectively.

As shown in Figure 1, suppose network traffic of a real service flow passes through network element 1, network element 2, ..., network element n in turn, and the time when network traffic passes through the network element is recorded as t_1, t_2, \dots, t_n . The timestamp maybe the ingress timestamp of network traffic entering the network element or the egress timestamp of network traffic flowing out of the network element after the forwarding is completed. Each network element transmits the flow information to the centralized control node through the delay deterministic network when real traffic passes, and the transmission delays of each network element to transmit the flow information to the centralized control node through the delay deterministic network are denoted as T_1, T_2, \dots, T_n , respectively. The timestamps when the centralized control node receives the flow information of each network element are t_1', t_2', \dots, t_n' .

Taking the calculation of the one-way transmission delay of traffic from network element 1 to network element 2 as an example, the one-way transmission delay can be calculated in the following way. Firstly, because the clocks of network element 1 and network element 2 are not synchronized, suppose the time deviation between the two is δ_t . Then the one-way transmission delay of traffic from network element 1 to network element 2 satisfies the following formula (1). Among them, Delay represents the one-way transmission delay of traffic from network element 1 to network element 2.

Formula (1): $\text{Delay} = t_2 - t_1 - \delta_t$

Secondly, because the clocks between network element 1 and the centralized control node are not synchronized, assuming that the time deviation between the two is $\delta_{t'}$, the time for the traffic information collected from the network element 1 to reach the centralized control node through the delay deterministic network satisfies the following formula (2).

Formula (2): $t_1' = t_1 + T_1 + \delta_{t'}$

Thirdly, the clocks between network element 2 and the centralized control node are not synchronized, and the time deviation between network element 2 and the centralized control node is $\delta_{t'} - \delta_t$. The time t_2' for the collected traffic to reach the centralized control node satisfies the following formula (3).

Formula (3): $t_2' = t_2 + T_2 + \delta_{t'} - \delta_t$

Forthly, subtracting the formula (2) from the above formula (3), we can obtain the following formula (4).

Formula (4): $t_2 - t_1 - \delta_t = t_2' - t_1' + T_1 - T_2$

Fifthly, substituting the above formula (4) into the above formula (1), the following formula (5) can be obtained.

Formula (5): $\text{Delay} = t_2' - t_1' + T_1 - T_2$

So far, the one-way transmission delay of traffic from network element 1 to network element 2 is obtained. Taking the calculation of one-way transmission delay of traffic from network element 1 to network element 3 as an example, the one-way transmission delay can be calculated in the following way: I) Referring to the above formula (5), the one-way transmission delay of traffic from network element 1 to network element 2 is: $\text{Delay}_{12} = t_2' - t_1' + T_1 - T_2$. II) Referring to the above formula (5), the one-way transmission delay of traffic from network element 2 to network element 3 is: $\text{Delay}_{23} = t_3' - t_2' + T_2 - T_3$. III) The one-way transmission delay of traffic from network element 1 to network element 3 is: $\text{Delay}_{13} = \text{Delay}_{12} + \text{Delay}_{23} = t_2' - t_1' + T_1 - T_2 + t_3' - t_2' + T_2 - T_3 = t_3' - t_1' + T_1 - T_3$. It can be seen that the one-way transmission delay between any two network elements can be calculated similarly to the above formula (5). For example, taking network element m and network element n as an example, the transmission delay of traffic from network element m to network element n is: $\text{Delay} = t_n' - t_m' + T_m - T_n$, where t_n' and t_m' are the time when the traffic information of network element m and network n reaches the centralized control node, and T_m and T_n are transmission delay of the traffic information from network element m and network element n to the centralized control node respectively through delay deterministic network.

[4.](#) Procedures of the One-way Delay Measurement Method

In this section, the procedures of the proposed one-way delay measurement method will be elaborated. Assume there are two network element. It is determined that the time when the centralized control node receives the first flow information is the first time, and the time when the second flow information is received by the centralized control node is determined to be the second time. The first flow

element or the time when traffic flows out of the first network element.

The second traffic information is sent by the second network element to the centralized control node via a delay deterministic network at the moment when the traffic passes through the second network element. And the time when the traffic passes through the second network element refers to the moment when traffic enters the second network element or the time when traffic flows out of the second network element.

It is determined that the transmission delay of the first traffic information from the first network element to the centralized control node is the first transmission delay, and it is determined that the transmission delay of the second traffic information from the second network element to the centralized control node is the second transmission delay. The transmission delay of traffic from the first network element to the second network element can be determined based on the following formula: $\text{Delay} = t_{n'} - t_m' + T_m - T_n$. Wherein, $t_{n'}$ represents the second time, t_m' represents the first time, T_m represents the first transmission delay, T_n represents the second transmission delay, and Delay represents transmission delay of the traffic from the first network element to the second network element. In the above method, the delay deterministic network is used to ensure that the first transmission delay and the second transmission delay are fixed delays.

5. Security Considerations

TBD.

6. IANA Considerations

TBD.

7. Normative References

- [IEEE.1588.2008]
IEEE, "IEEE Standard for a Precision Clock Synchronization Protocol for Networked Measurement and Control Systems", July 2008.
- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), DOI 10.17487/RFC2119, March 1997, <<https://www.rfc-editor.org/info/rfc2119>>.

- [RFC5905] Mills, D., Martin, J., Ed., Burbank, J., and W. Kasch, "Network Time Protocol Version 4: Protocol and Algorithms Specification", [RFC 5905](#), DOI 10.17487/RFC5905, June 2010, <<https://www.rfc-editor.org/info/rfc5905>>.
- [RFC8174] Leiba, B., "Ambiguity of Uppercase vs Lowercase in [RFC 2119](#) Key Words", [BCP 14](#), [RFC 8174](#), DOI 10.17487/RFC8174, May 2017, <<https://www.rfc-editor.org/info/rfc8174>>.
- [RFC8186] Mirsky, G. and I. Meilik, "Support of the IEEE 1588 Timestamp Format in a Two-Way Active Measurement Protocol (TWAMP)", [RFC 8186](#), DOI 10.17487/RFC8186, June 2017, <<https://www.rfc-editor.org/info/rfc8186>>.
- [RFC8655] Finn, N., Thubert, P., Varga, B., and J. Farkas, "Deterministic Networking Architecture", [RFC 8655](#), DOI 10.17487/RFC8655, October 2019, <<https://www.rfc-editor.org/info/rfc8655>>.

Authors' Addresses

Hongwei Yang
China Mobile
Beijing
100053
China
Email: yanghongwei@chinamobile.com

Peng Liu
China Mobile
Beijing
100053
China
Email: Liupengyjy@chinamobile.com

