

Network Working Group  
Internet-Draft  
Expires: August 7, 2003

F. Yergeau  
Alis Technologies  
February 6, 2003

UTF-8, a transformation format of ISO 10646  
draft-yergeau-rfc2279bis-03

## Status of this Memo

This document is an Internet-Draft and is in full conformance with all provisions of [Section 10 of RFC2026](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF), its areas, and its working groups. Note that other groups may also distribute working documents as Internet-Drafts.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

The list of current Internet-Drafts can be accessed at <http://www.ietf.org/ietf/lid-abstracts.txt>.

The list of Internet-Draft Shadow Directories can be accessed at <http://www.ietf.org/shadow.html>.

This Internet-Draft will expire on August 7, 2003.

## Copyright Notice

Copyright (C) The Internet Society (2003). All Rights Reserved.

## Abstract

ISO/IEC 10646-1 defines a large character set called the Universal Character Set (UCS) which encompasses most of the world's writing systems. The originally proposed encodings of the UCS, however, were not compatible with many current applications and protocols, and this has led to the development of UTF-8, the object of this memo. UTF-8 has the characteristic of preserving the full US-ASCII range, providing compatibility with file systems, parsers and other software that rely on US-ASCII values but are transparent to other values. This memo obsoletes and replaces [RFC 2279](#).

Discussion of this draft should take place on the [ietf-charsets@iana.org](mailto:ietf-charsets@iana.org) mailing list.

Internet-Draft

UTF-8

February 2003

## Table of Contents

<a href="#">1.</a>	Introduction . . . . .	<a href="#">3</a>
<a href="#">2.</a>	Notational conventions . . . . .	<a href="#">5</a>
<a href="#">3.</a>	UTF-8 definition . . . . .	<a href="#">6</a>
<a href="#">4.</a>	Syntax of UTF-8 Byte Sequences . . . . .	<a href="#">8</a>
<a href="#">5.</a>	Versions of the standards . . . . .	<a href="#">9</a>
<a href="#">6.</a>	Byte order mark (BOM) . . . . .	<a href="#">10</a>
<a href="#">7.</a>	Examples . . . . .	<a href="#">12</a>
<a href="#">8.</a>	MIME registration . . . . .	<a href="#">13</a>
<a href="#">9.</a>	IANA Considerations . . . . .	<a href="#">14</a>
<a href="#">10.</a>	Security Considerations . . . . .	<a href="#">15</a>
<a href="#">11.</a>	Acknowledgements . . . . .	<a href="#">16</a>
<a href="#">12.</a>	Changes from <a href="#">RFC 2279</a> . . . . .	<a href="#">17</a>
	Normative references . . . . .	<a href="#">19</a>
	Informative references . . . . .	<a href="#">20</a>
	Author's Address . . . . .	<a href="#">21</a>
	Full Copyright Statement . . . . .	<a href="#">22</a>

Internet-Draft

UTF-8

February 2003

## 1. Introduction

ISO/IEC 10646 [[ISO.10646](#)] defines a large character set called the Universal Character Set (UCS), which encompasses most of the world's writing systems. The same set of characters is defined by the Unicode standard [[UNICODE](#)], which further defines additional character properties and other application details of great interest to implementers. Up to the present time, changes in Unicode and amendments and additions to ISO/IEC 10646 have tracked each other, so that the character repertoires and code point assignments have remained in sync. The relevant standardization committees have committed to maintain this very useful synchronism.

ISO/IEC 10646 and Unicode define several encoding forms of their common repertoire: UTF-8, UCS-2, UTF-16, UCS-4 and UTF-32. In an encoding form, each character is represented as one or more encoding units. All standard UCS encoding forms except UTF-8 have an encoding unit larger than one octet, making them hard to use in many current applications and protocols that assume 8 or even 7 bit characters.

UTF-8, the object of this memo, has a one-octet encoding unit. It uses all bits of an octet, but has the quality of preserving the full US-ASCII [[US-ASCII](#)] range: US-ASCII characters are encoded in one octet having the normal US-ASCII value, and any octet with such a value can only stand for a US-ASCII character, and nothing else.

UTF-8 encodes UCS characters as a varying number of octets, where the number of octets, and the value of each, depend on the integer value assigned to the character in ISO/IEC 10646 (the character number, a.k.a. code point or Unicode scalar value). This encoding form has the following characteristics (all values are in hexadecimal):

- o Character numbers from U+0000 to U+007F (US-ASCII repertoire) correspond to octets 00 to 7F (7 bit US-ASCII values). A direct consequence is that a plain ASCII string is also a valid UTF-8

string.

- o US-ASCII octet values do not appear otherwise in a UTF-8 encoded character stream. This provides compatibility with file systems or other software (e.g. the printf() function in C libraries) that parse based on US-ASCII values but are transparent to other values.
- o Round-trip conversion is easy between UTF-8 and other encoding forms.
- o The first octet of a multi-octet sequence indicates the number of octets in the sequence.

- o The octet values C0, C1, FE and FF never appear. If the range of character numbers is restricted to U+0000..U+10FFFF (the UTF-16 accessible range), then the octet values F5..FD also never appear.
- o Character boundaries are easily found from anywhere in an octet stream.
- o The lexicographic sorting order of UTF-8 strings is the same as if ordered by character numbers. Of course this is of limited interest since a sort order based on character numbers is not culturally valid.
- o The Boyer-Moore fast search algorithm can be used with UTF-8 data.
- o UTF-8 strings can be fairly reliably recognized as such by a simple algorithm, i.e. the probability that a string of characters in any other encoding appears as valid UTF-8 is low, diminishing with increasing string length.

UTF-8 was originally a project of the X/Open Joint Internationalization Group X0JIG with the objective to specify a File System Safe UCS Transformation Format [[FSS UTF](#)] that is compatible with UNIX systems, supporting multilingual text in a single encoding. The original authors were Gary Miller, Greger Leijonhufvud and John Entenmann. Later, Ken Thompson and Rob Pike did significant work for the formal definition of UTF-8.

## 2. Notational conventions

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [[RFC2119](#)].

UCS characters are designated by the U+HHHH notation, where HHHH is a string of from 4 to 6 hexadecimal digits representing the character number in ISO/IEC 10646.

### [3.](#) UTF-8 definition

UTF-8 is defined by the Unicode Standard [[UNICODE](#)]. Descriptions and formulae can also be found in Annex D of ISO/IEC 10646-1 [[ISO.10646](#)]

In UTF-8, characters from the U+0000..U+10FFFF range (the UTF-16 accessible range) are encoded using sequences of 1 to 4 octets. The only octet of a "sequence" of one has the higher-order bit set to 0, the remaining 7 bits being used to encode the character number. In a sequence of n octets, n>1, the initial octet has the n higher-order bits set to 1, followed by a bit set to 0. The remaining bit(s) of that octet contain bits from the number of the character to be encoded. The following octet(s) all have the higher-order bit set to 1 and the following bit set to 0, leaving 6 bits in each to contain

bits from the character to be encoded.

The table below summarizes the format of these different octet types. The letter x indicates bits available for encoding bits of the character number.

Char. number range (hexadecimal)	UTF-8 octet sequence (binary)
0000 0000-0000 007F	0xxxxxxx
0000 0080-0000 07FF	110xxxxx 10xxxxxx
0000 0800-0000 FFFF	1110xxxx 10xxxxxx 10xxxxxx
0001 0000-0010 FFFF	11110xxx 10xxxxxx 10xxxxxx 10xxxxxx

Encoding a character to UTF-8 proceeds as follows:

1. Determine the number of octets required from the character number and the first column of the table above. It is important to note that the rows of the table are mutually exclusive, i.e. there is only one valid way to encode a given character.
2. Prepare the high-order bits of the octets as per the second column of the table.
3. Fill in the bits marked x from the bits of the character number, expressed in binary. Start by putting the lowest-order bit of the character number in the lowest-order position of the last octet of the sequence, then put the next higher-order bit of the character number in the next higher-order position of that octet, etc. When the x bits of the last octet are filled in, move on to the next to last octet, then to the preceding one, etc. until all x bits are filled in.

The definition of UTF-8 prohibits encoding character numbers between

U+D800 and U+DFFF, which are reserved for use with the UTF-16 encoding form (as surrogate pairs) and do not directly represent characters. When encoding in UTF-8 from UTF-16 data, it is necessary to first decode the UTF-16 data to obtain character numbers, which are then encoded in UTF-8 as described above. This contrasts with CESU-8 [\[CESU-8\]](#), which is a UTF-8-like encoding that is not meant for use on the Internet. CESU-8 operates similarly to UTF-8 but encodes

the UTF-16 code values (16-bit quantities) instead of the character number (code point). This leads to different results for character numbers above 0xFFFF; the CESU-8 encoding of those characters is NOT valid UTF-8.

Decoding a UTF-8 character proceeds as follows:

1. Initialize a binary number with all bits set to 0. Up to 21 bits may be needed.
2. Determine which bits encode the character number from the number of octets in the sequence and the second column of the table above (the bits marked x).
3. Distribute the bits from the sequence to the binary number, first the lower-order bits from the last octet of the sequence and proceeding to the left until no x bits are left. The binary number is now equal to the character number.

Implementations of the decoding algorithm above MUST protect against decoding invalid sequences. For instance, a naive implementation may decode the overlong UTF-8 sequence C0 80 into the character U+0000, or the surrogate pair ED A1 8C ED BE B4 into U+233B4. Decoding invalid sequences may have security consequences or cause other problems. See Security Considerations ([Section 10](#)) below.



#### [4.](#) Syntax of UTF-8 Byte Sequences

A UTF-8 string is a sequence of octets representing a sequence of UCS characters. An octet sequence is valid UTF-8 only if it matches the following syntax, which is derived from the rules for encoding UTF-8 and is expressed in the ABNF of [\[RFC2234\]](#).

```
UTF8-octets = *( UTF8-char )
UTF8-char   = UTF8-1 / UTF8-2 / UTF8-3 / UTF8-4
UTF8-1      = %x00-7F
UTF8-2      = %xC2-DF UTF8-tail
UTF8-3      = %xE0 %xA0-BF UTF8-tail / %xE1-EC 2( UTF8-tail ) /
              %xED %x80-9F UTF8-tail / %xEE-EF 2( UTF8-tail )
UTF8-4      = %xF0 %x90-BF 2( UTF8-tail ) / %xF1-F3 3( UTF8-tail ) /
              %xF4 %x80-8F 2( UTF8-tail )
UTF8-tail   = %x80-BF
```

Internet-Draft

UTF-8

February 2003

## [5](#). Versions of the standards

ISO/IEC 10646 is updated from time to time by publication of amendments and additional parts; similarly, new versions of the Unicode standard are published over time. Each new version obsoletes and replaces the previous one, but implementations, and more significantly data, are not updated instantly.

In general, the changes amount to adding new characters, which does not pose particular problems with old data. In 1996, Amendment 5 to the 1993 edition of ISO/IEC 10646 and Unicode 2.0 moved and expanded the Korean Hangul block, thereby making any previous data containing Hangul characters invalid under the new version. Unicode 2.0 has the same difference from Unicode 1.1. The justification for allowing such an incompatible change was that there were no major implementations and no significant amounts of data containing Hangul. The incident has been dubbed the "Korean mess", and the relevant committees have pledged to never, ever again make such an incompatible change (see Unicode Consortium Policies [[1](#)]).

New versions, and in particular any incompatible changes, have consequences regarding MIME charset labels, to be discussed in MIME registration ([Section 8](#)).

## [6.](#) Byte order mark (BOM)

The UCS character U+FEFF "ZERO WIDTH NO-BREAK SPACE" is also known informally as "BYTE ORDER MARK" (abbreviated "BOM"). This character can be used as a genuine "ZERO WIDTH NO-BREAK SPACE" within text, but the BOM name hints at a second possible usage of the character: to prepend a U+FEFF character to a stream of UCS characters as a "signature". A receiver of such a serialized stream may then use the initial character as a hint that the stream consists of UCS characters and also to recognize which UCS encoding is involved and, with encodings having a multi-octet encoding unit, as a way to recognize the serialization order of the octets. UTF-8 having a single-octet encoding unit, this last function is useless and the BOM will always appear as the octet sequence EF BB BF.

It is important to understand that the character U+FEFF appearing at any position other than the beginning of a stream **MUST** be interpreted with the semantics for the zero-width non-breaking space, and **MUST NOT** be interpreted as a signature. When interpreted as a signature, the Unicode standard suggests that an initial U+FEFF character may be stripped before processing the text. Such stripping is necessary in some cases (e.g. when concatenating two strings, because otherwise the resulting string may contain an unintended "ZERO WIDTH NO-BREAK SPACE" at the connection point), but might affect an external process at a different layer (such as a digital signature or a count of the characters) that is relying on the presence of all characters in the stream. It is therefore **RECOMMENDED** to avoid stripping an initial U+FEFF interpreted as a signature without a good reason, to ignore it instead of stripping it when appropriate (such as for display) and to strip it only when really necessary.

U+FEFF in the first position of a stream **MAY** be interpreted as a zero-width non-breaking space, and is not always a signature. In an attempt at diminishing this uncertainty, Unicode 3.2 adds a new character, U+2060 "WORD JOINER", with exactly the same semantics and usage as U+FEFF except for the signature function, and strongly

recommends its exclusive use for expressing word-joining semantics. Eventually, following this recommendation will make it all but certain that any initial U+FEFF is a signature, not an intended "ZERO WIDTH NO-BREAK SPACE".

In the meantime, the uncertainty unfortunately remains and may affect Internet protocols. Protocol specifications MAY restrict usage of U+FEFF as a signature in order to reduce or eliminate the potential ill effects of this uncertainty. In the interest of striking a balance between the advantages (reduction of uncertainty) and drawbacks (loss of the signature function) of such restrictions, it is useful to distinguish a few cases:

- o A protocol SHOULD forbid use of U+FEFF as a signature for those textual protocol elements that the protocol mandates to be always UTF-8, the signature function being totally useless in those cases.
- o A protocol SHOULD also forbid use of U+FEFF as a signature for those textual protocol elements for which the protocol provides character encoding identification mechanisms, when it is expected that implementations of the protocol will be in a position to always use the mechanisms properly. This will be the case when the protocol elements are maintained tightly under the control of the implementation from the time of their creation to the time of their (properly labeled) transmission.
- o A protocol SHOULD NOT forbid use of U+FEFF as a signature for those textual protocol elements for which the protocol does not provide character encoding identification mechanisms, when a ban would be unenforceable, or when it is expected that implementations of the protocol will not be in a position to always use the mechanisms properly. The latter two cases are likely to occur with larger protocol elements such as MIME entities, especially when implementations of the protocol will obtain such entities from file systems, from protocols that do not have encoding identification mechanisms for payloads (such as FTP) or from other protocols that do not guarantee proper identification of character encoding (such as HTTP).

When a protocol forbids use of U+FEFF as a signature for a certain protocol element, then any initial U+FEFF in that protocol element

MUST be interpreted as a "ZERO WIDTH NO-BREAK SPACE". When a protocol does NOT forbid use of U+FEFF as a signature for a certain protocol element, then implementations SHOULD be prepared to handle a signature in that element and react appropriately: using the signature to identify the character encoding as necessary and stripping or ignoring the signature as appropriate.

## [7](#). Examples

The character sequence U+0041 U+2262 U+0391 U+002E "A<NOT IDENTICAL TO><ALPHA>." is encoded in UTF-8 as follows:

```
--+-----+-----+--
41 E2 89 A2 CE 91 2E
--+-----+-----+--
```

The character sequence U+D55C U+AD6D U+C5B4 (Korean "hangugeo", meaning "the Korean language") is encoded in UTF-8 as follows:

```
-----+-----+-----
ED 95 9C EA B5 AD EC 96 B4
-----+-----+-----
```

The character sequence U+65E5 U+672C U+8A9E (Japanese "nihongo", meaning "the Japanese language") is encoded in UTF-8 as follows:

```
-----+-----+-----
E6 97 A5 E6 9C AC E8 AA 9E
-----+-----+-----
```

The character U+233B4 (a Chinese character meaning 'stump of tree'), prepended with a UTF-8 BOM, is encoded in UTF-8 as follows:

```
-----+-----  
EF BB BF F0 A3 8E B4  
-----+-----
```

## [8.](#) MIME registration

This memo serves as the basis for registration of the MIME charset parameter for UTF-8, according to [\[RFC2978\]](#). The charset parameter value is "UTF-8". This string labels media types containing text consisting of characters from the repertoire of ISO/IEC 10646 including all amendments at least up to amendment 5 of the 1993 edition (Korean block), encoded to a sequence of octets using the encoding scheme outlined above. UTF-8 is suitable for use in MIME content types under the "text" top-level type.

It is noteworthy that the label "UTF-8" does not contain a version identification, referring generically to ISO/IEC 10646. This is intentional, the rationale being as follows:

A MIME charset label is designed to give just the information needed to interpret a sequence of bytes received on the wire into a sequence of characters, nothing more (see [\[RFC2045\], section 2.2](#)). As long as a character set standard does not change incompatibly, version numbers serve no purpose, because one gains nothing by learning from the tag that newly assigned characters may be received that one doesn't know about. The tag itself doesn't teach anything about the new characters, which are going to be received anyway.

Hence, as long as the standards evolve compatibly, the apparent advantage of having labels that identify the versions is only that, apparent. But there is a disadvantage to such version-dependent labels: when an older application receives data accompanied by a newer, unknown label, it may fail to recognize the label and be completely unable to deal with the data, whereas a generic, known label would have triggered mostly correct processing of the data, which may well not contain any new characters.

Now the "Korean mess" (ISO/IEC 10646 amendment 5) is an incompatible change, in principle contradicting the appropriateness of a version independent MIME charset label as described above. But the compatibility problem can only appear with data containing Korean Hangul characters encoded according to Unicode 1.1 (or equivalently ISO/IEC 10646 before amendment 5), and there is arguably no such data to worry about, this being the very reason the incompatible change was deemed acceptable.

In practice, then, a version-independent label is warranted, provided the label is understood to refer to all versions after Amendment 5, and provided no incompatible change actually occurs. Should incompatible changes occur in a later version of ISO/IEC 10646, the MIME charset label defined here will stay aligned with the previous version until and unless the IETF specifically decides otherwise.

## [9.](#) IANA Considerations

The entry for UTF-8 in the IANA charset registry should be updated to point to this memo.





Implementers of UTF-8 need to consider the security aspects of how they handle illegal UTF-8 sequences. It is conceivable that in some circumstances an attacker would be able to exploit an incautious UTF-8 parser by sending it an octet sequence that is not permitted by the UTF-8 syntax.

A particularly subtle form of this attack can be carried out against a parser which performs security-critical validity checks against the UTF-8 encoded form of its input, but interprets certain illegal octet sequences as characters. For example, a parser might prohibit the NUL character when encoded as the single-octet sequence 00, but erroneously allow the illegal two-octet sequence C0 80 and interpret it as a NUL character. Another example might be a parser which prohibits the octet sequence 2F 2E 2E 2F ("/./"), yet permits the illegal octet sequence 2F C0 AE 2E 2F. This last exploit has actually been used in a widespread virus attacking Web servers in 2001; the security threat is thus very real.

Another security issue occurs when encoding to UTF-8: the ISO/IEC 10646 description of UTF-8 allows encoding character numbers up to U+7FFFFFFF, yielding sequences of up to 6 bytes. There is therefore a risk of buffer overflow if the range of character numbers is not explicitly limited to U+10FFFF or if buffer sizing doesn't take into account the possibility of 5- and 6-byte sequences.

## [11.](#) Acknowledgements

The following have participated in the drafting and discussion of this memo: James E. Agenbroad, Harald Alvestrand, Andries Brouwer, Mark Davis, Martin J. D erst, Patrick F  ltstr  m, Ned Freed, David Goldsmith, Tony Hansen, Edwin F. Hart, Paul Hoffman, David Hopwood, Simon Josefsson, Kent Karlsson, Markus Kuhn, Michael Kung, Alain LaBont  , Ira McDonald, Alexey Melnikov, John Gardiner Myers, Dan Oscarsson, Murray Sargent, Markus Scherer, Keld Simonsen, Arnold Winkler, Kenneth Whistler and Misha Wolf.

Internet-Draft

UTF-8

February 2003

## 12. Changes from [RFC 2279](#)

- o Restricted the range of characters to 0000-10FFFF (the UTF-16 accessible range).
- o Made Unicode the source of the normative definition of UTF-8, keeping ISO/IEC 10646 as the reference for characters.
- o Significantly shortened Introduction. No more mention of UTF-1 or UTF-7, of Transformation Formats.
- o Straightened out terminology. UTF-8 now described in terms of an encoding form of the character number. UCS-2 and UCS-4 almost disappeared.
- o Turned the note warning against decoding of invalid sequences into a normative MUST NOT.
- o Added a new section about the UTF-8 BOM, with advice for protocols.
- o Updated a couple of references (10646-1:2000, Unicode 3.2, [RFC 2978](#)).
- o Added TOC.
- o Removed suggested UNICODE-1-1-UTF-8 MIME charset registration.
- o Added new "Notational conventions" section about [RFC 2119](#) and U+HHHH notation.
- o Added pointer to Unicode Consortium Policies in "Versions of the standards" section.
- o Added a fourth example with a non-BMP character and a BOM.
- o Added a paragraph about U+2060 WORD JOINER.
- o Enumerate more byte values impossible in UTF-8, either as a result

of forbidding overlong sequences or of restricting to the UTF-16 accessible range.

- o Added "IANA Considerations" section to ask that the UTF-8 entry in the charset registry point to this memo.
- o Added an ABNF syntax for valid UTF-8 octet sequences
- o Added some warning language about CESU-8

Yergeau

Expires August 7, 2003

[Page 17]

---

Internet-Draft

UTF-8

February 2003

- o Split References into Normative and Informative

---

Internet-Draft

UTF-8

February 2003

## Normative references

- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), March 1997.
- [RFC2234] Crocker, D. and P. Overell, "Augmented BNF for Syntax Specifications: ABNF", [RFC 2234](#), November 1997.
- [ISO.10646] International Organization for Standardization, "Information Technology - Universal Multiple-octet coded Character Set (UCS)", ISO/IEC Standard 10646, comprised of ISO/IEC 10646-1:2000, "Information technology -- Universal Multiple-Octet Coded Character Set (UCS) -- Part 1: Architecture and Basic Multilingual Plane", ISO/IEC 10646-2:2001, "Information technology -- Universal Multiple-Octet Coded Character Set (UCS) -- Part 2: Supplementary Planes" and ISO/IEC 10646-1:2000/Amd 1:2002, "Mathematical symbols and other characters".
- [UNICODE] The Unicode Consortium, "The Unicode Standard -- Version 3.2", defined by The Unicode Standard, Version 3.0 (Reading, MA, Addison-Wesley, 2000. ISBN 0-201-61633-5), as amended by the Unicode Standard Annex #27: Unicode 3.1 (see <http://www.unicode.org/reports/tr27>) and by the Unicode Standard Annex #28: Unicode 3.2 (see

[www.unicode.org/reports/tr28](http://www.unicode.org/reports/tr28)), March 2002, <[http://www.unicode.org/unicode/standard/versions/enumeratedversions.html#Unicode\\_3\\_2\\_0](http://www.unicode.org/unicode/standard/versions/enumeratedversions.html#Unicode_3_2_0)>.

#### Informative references

- [CESU-8] Phipps, T., "Compatibility Encoding Scheme for UTF-16: 8-Bit (CESU-8)", UTR 26, April 2002, <<http://www.unicode.org/unicode/reports/tr26/>>.
- [FSS\_UTF] X/Open Company Ltd., "X/Open CAE Specification C501 -- File System Safe UCS Transformation Format (FSS\_UTF)", ISBN 1-85912-082-2, April 1995.
- [RFC2045] Freed, N. and N. Borenstein, "Multipurpose Internet Mail Extensions (MIME) Part One: Format of Internet Message Bodies", [RFC 2045](#), November 1996.
- [RFC2978] Freed, N. and J. Postel, "IANA Charset Registration Procedures", [BCP 19](#), [RFC 2978](#), October 2000.
- [US-ASCII] American National Standards Institute, "Coded Character

Set - 7-bit American Standard Code for Information Interchange", ANSI X3.4, 1986.

Yergeau

Expires August 7, 2003

[Page 20]

---

Internet-Draft

UTF-8

February 2003

URIs

[1] <<http://www.unicode.org/unicode/standard/policies.html>>

Author's Address

François Yergeau  
Alis Technologies  
100, boul. Alexis-Nihon, bureau 600  
Montréal, QC H4M 2P2

Canada

Phone: +1 514 747 2547

Fax: +1 514 747 2561

EMail: fyergeau@alis.com



This document and translations of it may be copied and furnished to others, and derivative works that comment on or otherwise explain it or assist in its implementation may be prepared, copied, published and distributed, in whole or in part, without restriction of any kind, provided that the above copyright notice and this paragraph are included on all such copies and derivative works. However, this document itself may not be modified in any way, such as by removing the copyright notice or references to the Internet Society or other Internet organizations, except as needed for the purpose of developing Internet standards in which case the procedures for copyrights defined in the Internet Standards process must be followed, or as required to translate it into languages other than English.

The limited permissions granted above are perpetual and will not be revoked by the Internet Society or its successors or assigns.

This document and the information contained herein is provided on an "AS IS" basis and THE INTERNET SOCIETY AND THE INTERNET ENGINEERING TASK FORCE DISCLAIMS ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY WARRANTY THAT THE USE OF THE INFORMATION HEREIN WILL NOT INFRINGE ANY RIGHTS OR ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

#### Acknowledgement

Funding for the RFC Editor function is currently provided by the Internet Society.