Network Working Group

Internet-Draft II

Intended status: Informational

Expires: 16 May 2022

IIJ Research Lab & Arrcus, Inc.

K. Patel

R. Bush

Arrcus, Inc.

P. Smith

PFS Internet Development Pty Ltd

M. Tinka

**SEACOM** 

12 November 2021

# RPKI Route Origin Validation Without Route Refresh draft-ymbk-sidrops-rov-no-rr-00

#### Abstract

A BGP Speaker performing RPKI-based Route Origin Validation should not issue Route Refresh to its neighbors when receiving new VRPs.

### Requirements Language

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "NOT RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in <a href="https://example.com/BCP14">BCP 14 [RFC2119]</a> [RFC8174] when, and only when, they appear in all capitals, as shown here.

## Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of  $\underline{BCP}$  78 and  $\underline{BCP}$  79.

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <a href="https://datatracker.ietf.org/drafts/current/">https://datatracker.ietf.org/drafts/current/</a>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on 16 May 2022.

## Copyright Notice

Copyright (c) 2021 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to <a href="BCP-78">BCP-78</a> and the IETF Trust's Legal Provisions Relating to IETF Documents (<a href="https://trustee.ietf.org/license-info">https://trustee.ietf.org/license-info</a>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Revised BSD License text as described in Section 4.e of the <a href="Trust Legal Provisions">Trust Legal Provisions</a> and are provided without warranty as described in the Revised BSD License.

#### Table of Contents

<u>1</u> .	Introduction	2
<u>2</u> .	Related Work	2
<u>3</u> .	Operational Considerations	2
<u>4</u> .	Security Considerations	<u>3</u>
<u>5</u> .	IANA Considerations	<u>3</u>
<u>6</u> .	References	<u>3</u>
	<u>1</u> . Normative References	
6	2. Informative References	<u>4</u>
Appe	<u>endix A</u> . Acknowledgements	<u>4</u>
Auth	nors' Addresses	4

#### 1. Introduction

Memory constraints in early routers caused classic [RFC4271] BGP implementations to not keep a full Adj-RIB-In (Sec. 1.1). When doing RPKI-based Route Origin Validation ([RFC6811] and [RFC8481]), if such a BGP speaker receives new ROAs/VRPs, it might not have kept paths previously marked as Invalid. Such an implementation must then request a Route Refresh [RFC7313] from its neighbors to recover the paths which might be covered by these new VRPs. This will be perceived as rude by those neighbors as it passes a serious resource burden on to them. This document recommends implementations keep but mark Invalidated paths so the Route Refresh is no longer needed.

## 2. Related Work

It is assumed that the reader understands BGP, [RFC4271] and Route Refresh [RFC7313], the RPKI [RFC6480], Route Origin Authorizations (ROAs), [RFC6482], The Resource Public Key Infrastructure (RPKI) to Router Protocol [I-D.ietf-sidrops-8210bis], RPKI-based Prefix Validation, [RFC6811], and Origin Validation Clarifications, [RFC8481].

#### 3. Operational Considerations

Operators deploying ROV SHOULD ensure that the router implementation is not causing unnecessary Route Refresh requests to neighbors.

Bush, et al. Expires 16 May 2022

[Page 2]

If the router does not implement the recommendations here, the operator SHOULD enable "soft reconfiguration inbound," which should cause the Adj-RIB-In to be effectively kept. The operator should then ensure that this stops unnecessary Route Refresh requests to neighbors.

If the router has insufficient resources to support this, it SHOULD not be used for Route Origin Validation.

## 4. Security Considerations

This document adds no additional security considerations to those already described by the referenced documents.

#### 5. IANA Considerations

None

#### 6. References

#### 6.1. Normative References

[I-D.ietf-sidrops-8210bis]

Bush, R. and R. Austein, "The Resource Public Key Infrastructure (RPKI) to Router Protocol, Version 2", Work in Progress, Internet-Draft, <a href="mailto:draft-ietf-sidrops-8210bis-03">draft-ietf-sidrops-8210bis-03</a>. 15 August 2021, <a href="mailto:https://www.ietf.org/archive/id/draft-ietf-sidrops-8210bis-03.txt">https://www.ietf.org/archive/id/draft-ietf-sidrops-8210bis-03.txt</a>.

- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate
  Requirement Levels", BCP 14, RFC 2119,
  DOI 10.17487/RFC2119, March 1997,
  <https://www.rfc-editor.org/info/rfc2119>.
- [RFC6482] Lepinski, M., Kent, S., and D. Kong, "A Profile for Route
   Origin Authorizations (ROAs)", RFC 6482,
   DOI 10.17487/RFC6482, February 2012,
   <a href="https://www.rfc-editor.org/info/rfc6482">https://www.rfc-editor.org/info/rfc6482</a>>.

Bush, et al. Expires 16 May 2022

[Page 3]

- [RFC8174] Leiba, B., "Ambiguity of Uppercase vs Lowercase in RFC
  2119 Key Words", BCP 14, RFC 8174, DOI 10.17487/RFC8174,
  May 2017, <a href="https://www.rfc-editor.org/info/rfc8174">https://www.rfc-editor.org/info/rfc8174</a>>.
- [RFC8481] Bush, R., "Clarifications to BGP Origin Validation Based
   on Resource Public Key Infrastructure (RPKI)", RFC 8481,
   DOI 10.17487/RFC8481, September 2018,
   <a href="https://www.rfc-editor.org/info/rfc8481">https://www.rfc-editor.org/info/rfc8481</a>>.

## 6.2. Informative References

[RFC6480] Lepinski, M. and S. Kent, "An Infrastructure to Support Secure Internet Routing", <u>RFC 6480</u>, DOI 10.17487/RFC6480, February 2012, <a href="https://www.rfc-editor.org/info/rfc6480">https://www.rfc-editor.org/info/rfc6480</a>>.

## Appendix A. Acknowledgements

The authors wish to thank Philip Smith and Mark Tinka.

Authors' Addresses

Randy Bush
IIJ Research Lab & Arrcus, Inc.
1856 SW Edgewood Dr
Portland, Oregon 97210
United States of America

Email: randy@psg.com

Keyur Patel Arrcus, Inc. 2077 Gateway Place, Suite #400 San Jose, CA 95119 United States of America

Email: keyur@arrcus.com

Philip Smith PFS Internet Development Pty Ltd PO Box 1908 Milton QLD 4064 Australia

Email: pfsinoz@gmail.com

Mark Tinka SEACOM Building 7, Design Quarter District, Leslie Avenue, Magaliessig Fourways, Gautang 2196 South Africa

Email: mark.tinka@seacom.com