

Network Working Group
Internet-Draft
Intended status: Informational
Expires: July 19, 2014

A. Yourtchenko
P. Aitken
B. Claise
Cisco Systems, Inc.
January 15, 2014

Cisco Specific Information Elements reused in IPFIX
draft-yourtchenko-cisco-ies-09

Abstract

This document describes some additional Information Elements of Cisco Systems, Inc. that are not listed in [RFC3954](#).

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <http://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on July 19, 2014.

Copyright Notice

Copyright (c) 2014 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

Internet-Draft

Cisco Information Elements

January 2014

Table of Contents

1.	Introduction	2
2.	Terminology	3
3.	Information Elements Overview	3
4.	Information Elements	3
4.1.	samplingInterval	3
4.2.	samplingAlgorithm	4
4.3.	engineType	4
4.4.	engineId	4
4.5.	ipv4RouterSc	5
4.6.	samplerId	5
4.7.	samplerMode	5
4.8.	samplerRandomInterval	5
4.9.	classId	6
4.10.	samplerName	6
4.11.	flagsAndSamplerId	6
4.12.	forwardingStatus	6
4.13.	srcTrafficIndex	8
4.14.	dstTrafficIndex	8
4.15.	className	8
4.16.	layer2packetSectionOffset	8
4.17.	layer2packetSectionSize	9
4.18.	layer2packetSectionData	9
5.	Other Information Elements	9
5.1.	Performance Metrics IEs	9
5.2.	Application Information IEs	9
5.3.	IEs assigned for NetFlow v9 compatibility	9
6.	IANA Considerations	10
7.	Security Considerations	10
8.	References	10
8.1.	Normative References	10
8.2.	Informative References	11
Appendix A.	XML Specification of IPFIX Information Elements	11
Appendix B.	Changes	18
Authors' Addresses		19

[1.](#) Introduction

The [section 4 of \[RFC7012\]](#) defines the IPFIX Information Elements in the range of 1-127 to be compatible with the NetFlow version 9 fields, as specified in the "Cisco Systems NetFlow Services Export Version 9" [\[RFC3954\]](#). As [\[RFC3954\]](#) was specified in 2004, it does

not contain all NetFlow version 9 specific fields in the range 1-127. The question was asked whether IPFIX Devices should exclusively report the IPFIX IANA IEs [[IPFIX-IANA](#)] ? In other words, when upgrading from a NetFlow metering process to an IPFIX Metering

Process, should the IPFIX Devices stop reporting NetFlow version 9 specific IEs that were not registered in IANA [[IPFIX-IANA](#)] ?

This document is intended to fill the gap in this IE range. That way, IPFIX implementations could export all the IEs specified in IANA, regardless of the range.

[2.](#) Terminology

IPFIX-specific terminology used in this document is defined in [Section 2 of \[RFC7011\]](#). As in [[RFC7011](#)], these IPFIX-specific terms have the first letter of a word capitalized when used in this document.

[3.](#) Information Elements Overview

The following Information Elements are discussed in the sections below:

ID	Name	ID	Name
34	samplingInterval	84	samplerName
35	samplingAlgorithm	87	flagsAndSamplerId
38	engineType	89	forwardingStatus
39	engineId	92	srcTrafficIndex
43	ipv4RouterSc	93	dstTrafficIndex
48	samplerId	100	className
49	samplerMode	102	layer2packetSectionOffset
50	samplerRandomInterval	103	layer2packetSectionSize
51	classId	104	layer2packetSectionData

Table 1

[4. Information Elements](#)

[4.1. samplingInterval](#)

Description:

Deprecated in favor of 305 samplingPacketInterval. When using sampled NetFlow, the rate at which packets are sampled - e.g. a value of 100 indicates that one of every 100 packets is sampled.

Abstract Data Type: unsigned32

ElementId: 34

Semantics: quantity

Status: deprecated

Yourtchenko, et al.

Expires July 19, 2014

[Page 3]

Internet-Draft

Cisco Information Elements

January 2014

Units: packets

[4.2. samplingAlgorithm](#)

Description:

Deprecated in favor of 304 selectorAlgorithm. The type of algorithm used for sampled NetFlow:

- 1 - Deterministic Sampling;
- 2 - Random Sampling.

The values are not compatible with the selectorAlgorithm IE, where "Deterministic" has been replaced by "Systematic count-based" (1) or "Systematic time-based" (2), and "Random" is (3). Conversion is required, see PSAMP parameters [[PSAMP-IANA](#)].

Abstract Data Type: unsigned8

ElementId: 35

Semantics: identifier

Status: deprecated

[4.3. engineType](#)

Description:

Type of flow switching engine in a router/switch:

- RP = 0,
- VIP/Line card = 1,
- PFC/DFC = 2.

Reserved for internal use on the collector.
Abstract Data Type: unsigned8
ElementId: 38
Semantics: identifier
Status: deprecated

[4.4.](#) engineId

Description:
VIP or line card slot number of the flow switching engine in a router/switch. Reserved for internal use on the collector.
Abstract Data Type: unsigned8
ElementId: 39
Semantics: identifier
Status: deprecated

[4.5.](#) ipv4RouterSc

Description:
This is a platform-specific field for Catalyst 5000/Catalyst 6000 family. It is used to store the address of a router that is being shortcut when performing MultiLayer Switching.
Abstract Data Type: ipv4Address
ElementId: 43
Semantics: identifier
Status: deprecated
Reference: [[CCO-MLS](#)] describes the MultiLayer Switching.

[4.6.](#) samplerId

Description:
Deprecated in favor of 302 selectorId. The unique identifier associated with samplerName.
Abstract Data Type: unsigned8
ElementId: 48
Semantics: identifier
Status: deprecated

[4.7.](#) samplerMode

Description:

Deprecated in favor of 304 selectorAlgorithm. The values are not compatible: selectorAlgorithm=3 is random sampling. The type of algorithm used for sampling data: 1 - deterministic, 2 - random sampling. Use with samplerRandomInterval.

Abstract Data Type: unsigned8

ElementId: 49

Semantics: identifier

Status: deprecated

[4.8.](#) samplerRandomInterval

Description:

Deprecated in favour of 305 samplingPacketInterval. Packet interval at which to sample - in case of random sampling. Used in connection with samplerMode 0x02 (random sampling) value.

Abstract Data Type: unsigned32

ElementId: 50

Semantics: quantity

Status: deprecated

[4.9.](#) classId

Description:

Deprecated in favour of 302 selectorId. Characterizes the traffic class, i.e. QoS treatment.

Abstract Data Type: unsigned8

ElementId: 51

Semantics: identifier

Status: deprecated

[4.10.](#) samplerName

Description:

Deprecated in favor of 335 selectorName. Name of the flow sampler.

Abstract Data Type: string
ElementId: 84
Status: deprecated

[4.11.](#) flagsAndSamplerId

Description:

Flow flags and the value of the sampler ID (samplerId) combined in one bitmapped field. Reserved for internal use on the collector.

Abstract Data Type: unsigned32
ElementId: 87
Semantics: identifier
Status: deprecated

[4.12.](#) forwardingStatus

Description:

This Information Element describes the forwarding status of the flow and any attached reasons. The Reduced Size Encoding rules as per [\[RFC7011\]](#) apply.

The basic encoding is 8 bits. The future extensions could add one or three bytes. The layout of the basic encoding is as follows:

MSB	-	0	1	2	3	4	5	6	7	-	LSB
+---+---+---+---+---+---+---+---+											
		Status		Reason code or flags							
+---+---+---+---+---+---+---+---+											

Status:

00b = Unknown

01b = Forwarded
10b = Dropped
11b = Consumed

Reason Code (status = 01b, Forwarded)

01 000000b = 64 = Unknown

01 000001b = 65 = Fragmented
01 000010b = 66 = Not Fragmented

Reason Code (status = 10b, Dropped)

10 000000b = 128 = Unknown
10 000001b = 129 = ACL deny
10 000010b = 130 = ACL drop
10 000011b = 131 = Unroutable
10 000100b = 132 = Adjacency
10 000101b = 133 = Fragmentation and DF set
10 000110b = 134 = Bad header checksum
10 000111b = 135 = Bad total Length
10 001000b = 136 = Bad header length
10 001001b = 137 = bad TTL
10 001010b = 138 = Policer
10 001011b = 139 = WRED
10 001100b = 140 = RPF
10 001101b = 141 = For us
10 001110b = 142 = Bad output interface
10 001111b = 143 = Hardware

Reason Code (status = 11b, Consumed)

11 000000b = 192 = Unknown
11 000001b = 193 = Punt Adjacency
11 000010b = 194 = Incomplete Adjacency
11 000011b = 195 = For us

Examples:

value : 0x40 = 64
binary: 01000000
decode: 01 -> Forward
 000000 -> No further information

value : 0x89 = 137
binary: 10001001
decode: 10 -> Drop
 001001 -> Fragmentation and DF set

ElementId: 89
Semantics: identifier
Status: current
Reference:
See [[CCO-NF9FMT](#)] - NetFlow Version 9 Record Format.

[4.13.](#) srcTrafficIndex

Description:
BGP Policy Accounting Source Traffic Index
Abstract Data Type: unsigned32
ElementId: 92
Semantics: identifier
Status: current
Reference:
BGP policy accounting as described in [[CCO-BGPPOL](#)]

[4.14.](#) dstTrafficIndex

Description:
BGP Policy Accounting Destination Traffic Index
Abstract Data Type: unsigned32
ElementId: 93
Semantics: identifier
Status: current
Reference:
BGP policy accounting as described in [[CCO-BGPPOL](#)]

[4.15.](#) className

Description:
Deprecated in favor of 335 selectorName. Traffic Class Name, associated with the classId Information Element.
Abstract Data Type: string
ElementId: 100
Status: deprecated

[4.16.](#) layer2packetSectionOffset

Description:
Deprecated in favor of sectionOffset (409). Layer 2 packet section offset. Potentially a generic packet section offset.
Abstract Data Type: unsigned16
ElementId: 102
Semantics: quantity
Status: deprecated

[4.17.](#) layer2packetSectionSize

Description:

Deprecated in favor of dataLinkFrameSize(312). Layer 2 packet section size. Potentially a generic packet section size.

Abstract Data Type: unsigned16

ElementId: 103

Semantics: quantity

Status: deprecated

[4.18.](#) layer2packetSectionData

Description:

Deprecated in favor of dataLinkFrameSection (315). Layer 2 packet section data.

Abstract Data Type: octetArray

ElementId: 104

Status: deprecated

[5.](#) Other Information Elements

[5.1.](#) Performance Metrics IEs

ElementId: 65 .. [69](#)

Performance metrics will need a consolidation in the industry, based on [RFC6390](#). Once this consolidation happens, via a separate document the IEs 65-69 will either be assigned in the IANA registry or their status will be deprecated.

[5.2.](#) Application Information IEs

ElementId: 101

ElementId: 94 .. [97](#)

Please refer to the [RFC 6759](#) [[RFC6759](#)]

[5.3.](#) IEs assigned for NetFlow v9 compatibility

ElementId: 105..126

These element IDs are not covered by this draft and left "as is", i.e. for Netflow v9 compatibility.

[6.](#) IANA Considerations

This document specifies several new IPFIX Information Elements in the IPFIX Information Element registry as defined in [Section 3](#) above. The following Information Elements must be assigned:

- o IE Number 34 for the samplingInterval IE
- o IE Number 35 for the samplingAlgorithm IE
- o IE Number 38 for the engineType IE
- o IE Number 39 for the engineId IE
- o IE Number 43 for the ipv4RouterSc IE
- o IE Number 48 for the samplerId IE
- o IE Number 49 for the samplerMode IE
- o IE Number 50 for the samplerRandomInterval IE
- o IE Number 51 for the classId IE
- o IE Number 84 for the samplerName IE
- o IE Number 87 for the flagsAndSamplerId IE
- o IE Number 89 for the forwardingStatus IE
- o IE Number 92 for the srcTrafficIndex IE
- o IE Number 93 for the dstTrafficIndex IE
- o IE Number 100 for the className IE
- o IE Number 102 for the layer2packetSectionOffset IE
- o IE Number 103 for the layer2packetSectionSize IE
- o IE Number 104 for the layer2packetSectionData IE

[7.](#) Security Considerations

This document specifies the definitions of several Information Elements and does not alter the security considerations of the base protocol. Please refer to the security considerations sections of [RFC 3954](#) [[RFC3954](#)] and [RFC 7012](#) [[RFC7012](#)].

However, the export of the sections of the packet payload may unintentionally change the security assumptions of other protocols.

[8.](#) References

[8.1.](#) Normative References

- [RFC7011] Claise, B., Trammell, B., and P. Aitken, "Specification of the IP Flow Information Export (IPFIX) Protocol for the Exchange of Flow Information", STD 77, [RFC 7011](#), September 2013.

Yourtchenko, et al.

Expires July 19, 2014

[Page 10]

Internet-Draft

Cisco Information Elements

January 2014

[8.2](#). Informative References

[CCO-BGPPOL]

Cisco, "BGP Policy Accounting and BGP Policy Accounting Output Interface Accounting Features", 2005, http://www.cisco.com/en/US/tech/tk365/technologies_tech_note09186a0080094e88.shtml.

[CCO-MLS]

Cisco, "IP MultiLayer Switching Sample Configuration", 2007, http://www.cisco.com/en/US/products/hw/switches/ps700/products_configuration_example09186a00800ab513.shtml.

[CCO-NF9FMT]

Cisco, "NetFlow version 9 Flow-Record format", 2011, http://www.cisco.com/en/US/technologies/tk648/tk362/technologies_white_paper09186a00800a3db9.html.

[IPFIX-IANA]

IANA, "IP Flow Information Export (IPFIX) Entities", 2013, <http://www.iana.org/assignments/ipfix/ipfix.xml>.

[PSAMP-IANA]

IANA, "Packet Sampling (PSAMP) Parameters", 2013, <http://www.iana.org/assignments/psamp-parameters/psamp-parameters.xml>.

[RFC3954]

Claise, B., "Cisco Systems NetFlow Services Export Version 9", [RFC 3954](#), October 2004.

[RFC6759]

Claise, B., Aitken, P., and N. Ben-Dvora, "Cisco Systems Export of Application Information in IP Flow Information

Export (IPFIX)", [RFC 6759](#), November 2012.

[RFC7012] Claise, B. and B. Trammell, "Information Model for IP Flow Information Export (IPFIX)", [RFC 7012](#), September 2013.

[Appendix A](#). XML Specification of IPFIX Information Elements

```
<?xml version="1.0" encoding="UTF-8"?>

<fieldDefinitions xmlns="urn:ietf:params:xml:ns:ipfix-info"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xsi:schemaLocation="urn:ietf:params:xml:ns:ipfix-info
    ipfix-info.xsd">

  <field name="samplingInterval" dataType="unsigned32"
    group=""
```

Yourtchenko, et al.

Expires July 19, 2014

[Page 11]

Internet-Draft

Cisco Information Elements

January 2014

```
    dataTypeSemantics="quantity"
    elementId="34" applicability="flow" status="deprecated">
<description>
  <paragraph>
    Deprecated in favor of 305 samplingPacketInterval. When using
    sampled NetFlow, the rate at which packets are sampled - e.g. a
    value of 100 indicates that one of every 100 packets is sampled.
  </paragraph>
</description>
</field>
<field name="samplingAlgorithm" dataType="unsigned8"
  group=""
  dataTypeSemantics="identifier"
  elementId="35" applicability="flow" status="deprecated">
<description>
  <paragraph>
    Deprecated in favor of 304 selectorAlgorithm. The type of
    algorithm used for sampled NetFlow: 1 - Deterministic Sampling;
    2 - Random Sampling. The values are not compatible with the
    selectorAlgorithm IE, where "Deterministic" has been replaced by
    "Systematic count-based" (1) or "Systematic time-based" (2), and
    "Random" is (3). Conversion is required, see
    <REF:PSAMP-IANA>PSAMP parameters.
  </paragraph>
</description>
```

```

</field>
<field name="engineType" dataType="unsigned8"
      group=""
      dataTypeSemantics="identifier"
      elementId="38" applicability="flow" status="deprecated">
  <description>
    <paragraph>
      Type of flow switching engine in a router/switch: RP = 0,
      VIP/Line card = 1, PFC/DFC = 2. Reserved for internal use on the
      collector.
    </paragraph>
  </description>
</field>
<field name="engineId" dataType="unsigned8"
      group=""
      dataTypeSemantics="identifier"
      elementId="39" applicability="flow" status="deprecated">
  <description>
    <paragraph>
      VIP or line card slot number of the flow switching engine in a
      router/switch. Reserved for internal use on the collector.
    </paragraph>
  </description>

```

```

</field>
<field name="ipv4RouterSc" dataType="ipv4Address"
      group=""
      dataTypeSemantics="identifier"
      elementId="43" applicability="flow" status="deprecated">
  <description>
    <paragraph>
      This is a platform-specific field for Catalyst 5000/Catalyst
      6000 family. It is used to store the address of a router that is
      being shortcut when performing MultiLayer Switching.
    </paragraph>
  </description>
  <reference>
http://www.cisco.com/en/US/products/hw/switches/ps

```

```

    700/products_configuration_example09186a00800ab513.shtml
    describes the MultiLayer Switching.
  </reference>
</field>
<field name="samplerId" dataType="unsigned8"
      group=""
      dataTypeSemantics="identifier"
      elementId="48" applicability="flow" status="deprecated">
  <description>
    <paragraph>
      Deprecated in favor of 302 selectorId. The unique identifier
      associated with samplerName.
    </paragraph>
  </description>
</field>
<field name="samplerMode" dataType="unsigned8"
      group=""
      dataTypeSemantics="identifier"
      elementId="49" applicability="flow" status="deprecated">
  <description>
    <paragraph>
      Deprecated in favor of 304 selectorAlgorithm. The values are not
      compatible: selectorAlgorithm=3 is random sampling. The type of
      algorithm used for sampling data: 1 - deterministic, 2 - random
      sampling. Use with samplerRandomInterval.
    </paragraph>
  </description>
</field>
<field name="samplerRandomInterval" dataType="unsigned32"
      group=""

```

```

      dataTypeSemantics="quantity"
      elementId="50" applicability="flow" status="deprecated">
  <description>
    <paragraph>
      Deprecated in favour of 305 samplingPacketInterval. Packet
      interval at which to sample - in case of random sampling. Used
      in connection with samplerMode 0x02 (random sampling) value.
    </paragraph>
  </description>
</field>
<field name="classId" dataType="unsigned8"

```

```

        group=""
        dataTypeSemantics="identifier"
        elementId="51" applicability="flow" status="deprecated">
<description>
  <paragraph>
    Deprecated in favour of 302 selectorId. Characterizes the
    traffic class, i.e. QoS treatment.
  </paragraph>
</description>
</field>
<field name="samplerName" dataType="string"
        group=""
        dataTypeSemantics=""
        elementId="84" applicability="flow" status="deprecated">
<description>
  <paragraph>
    Deprecated in favor of 335 selectorName. Name of the flow
    sampler.
  </paragraph>
</description>
</field>
<field name="flagsAndSamplerId" dataType="unsigned32"
        group=""
        dataTypeSemantics="identifier"
        elementId="87" applicability="flow" status="deprecated">
<description>
  <paragraph>
    Flow flags and the value of the sampler ID (samplerId) combined
    in one bitmapped field. Reserved for internal use on the
    collector.
  </paragraph>
</description>
</field>
<field name="forwardingStatus" dataType="unsigned32"
        group=""
        dataTypeSemantics="identifier"
        elementId="89" applicability="flow" status="current">

```

```

<description>
  <paragraph>
    This Information Element describes the forwarding status of the
    flow and any attached reasons. The Reduced Size Encoding rules

```


as per <REF:[RFC7011](#)> apply.

</paragraph>

<artwork>

The basic encoding is 8 bits. The future extensions could add one or three bytes. The layout of the basic encoding is as follows:

```
MSB - 0 1 2 3 4 5 6 7 - LSB
      +---+---+---+---+---+---+---+
      | Status| Reason code or flags |
      +---+---+---+---+---+---+---+
```

Status:

00b = Unknown

01b = Forwarded

10b = Dropped

11b = Consumed

Reason Code (status = 01b, Forwarded)

01 000000b = 64 = Unknown

01 000001b = 65 = Fragmented

01 000010b = 66 = Not Fragmented

Reason Code (status = 10b, Dropped)

10 000000b = 128 = Unknown

10 000001b = 129 = ACL deny

10 000010b = 130 = ACL drop

10 000011b = 131 = Unroutable

10 000100b = 132 = Adjacency

10 000101b = 133 = Fragmentation and DF set

10 000110b = 134 = Bad header checksum

10 000111b = 135 = Bad total Length

10 001000b = 136 = Bad header length

10 001001b = 137 = bad TTL

10 001010b = 138 = Policer

10 001011b = 139 = WRED

10 001100b = 140 = RPF

10 001101b = 141 = For us

10 001110b = 142 = Bad output interface

10 001111b = 143 = Hardware

Reason Code (status = 11b, Consumed)

11 000000b = 192 = Unknown
11 000001b = 193 = Punt Adjacency
11 000010b = 194 = Incomplete Adjacency
11 000011b = 195 = For us

Examples:

value : 0x40 = 64
binary: 01000000
decode: 01 -> Forward
 000000 -> No further information

value : 0x89 = 137
binary: 10001001
decode: 10 -> Drop
 001001 -> Fragmentation and DF set

```
</artwork>
</description>
<reference>
  See http:/
  /www.cisco
  .com/en/US
  /technolog
  ies/tk648/tk362/technologies_white_paper09186a00800a3db9.html -
  NetFlow Version 9 Record Format.
</reference>
</field>
<field name="srcTrafficIndex" dataType="unsigned32"
  group=""
  dataTypeSemantics="identifier"
  elementId="92" applicability="flow" status="current">
  <description>
    <paragraph>
      BGP Policy Accounting Source Traffic Index
    </paragraph>
  </description>
  <reference>
    BGP policy accounting as described in
    http://www
    .cisco.com
    /en/US/tech/tk365/technologies\_tech\_note09186a0080094e88.shtml
  </reference>
</field>
<field name="dstTrafficIndex" dataType="unsigned32"
  group=""
```

dataTypeSemantics="identifier"

```
        elementId="93" applicability="flow" status="current">
<description>
  <paragraph>
    BGP Policy Accounting Destination Traffic Index
  </paragraph>
</description>
<reference>
  BGP policy accounting as described in
  http://www.cisco.com/en/US/tech/tk365/technologies\_tech\_note09186a0080094e88.shtml
</reference>
</field>
<field name="className" dataType="string"
      group=""
      dataTypeSemantics=""
      elementId="100" applicability="flow" status="deprecated">
<description>
  <paragraph>
    Deprecated in favor of 335 selectorName. Traffic Class Name,
    associated with the classId Information Element.
  </paragraph>
</description>
</field>
<field name="layer2packetSectionOffset" dataType="unsigned16"
      group=""
      dataTypeSemantics="quantity"
      elementId="102" applicability="flow" status="deprecated">
<description>
  <paragraph>
    Deprecated in favor of 409 sectionOffset.
    Layer 2 packet section offset. Potentially a generic packet
    section offset.
  </paragraph>
</description>
</field>
<field name="layer2packetSectionSize" dataType="unsigned16"
      group=""
      dataTypeSemantics="quantity"
      elementId="103" applicability="flow" status="deprecated">
```

```
<description>
  <paragraph>
    Deprecated in favor of 312 dataLinkFrameSize.
    Layer 2 packet section size. Potentially a generic packet
    section size.
  </paragraph>
</description>
</field>
```

```
<field name="layer2packetSectionData" dataType="octetArray"
      group=""
      dataTypeSemantics=""
      elementId="104" applicability="flow" status="deprecated">
  <description>
    <paragraph>
      Deprecated in favor of 315 dataLinkFrameSection.
      Layer 2 packet section data.
    </paragraph>
  </description>
</field>
</fieldDefinitions>
```

[Appendix B](#). Changes

To be removed by RFC Editor before publication

01: initial revision presented at the IETF meeting.

02: removed "flow" from flowSamplerId, flowSamplerMode, and flowSamplerRandomInterval; updated the related drafts in references; added the "reference" column to the XML definitions; renamed fsFlowEntryTotalCount into deltaFlowCount to keep the naming in sync with [draft-trammell-ipfix-a9n](#). Also minor changes to formatting and added the IE overview table.

03: updated the references to [draft-claise-export-application-info-in-ipfix](#), slightly tweaked the title and removed the unused reference to [draft-ietf-ipfix-flow-selection-tech](#).

04: sync the references.

05: update references to [draft-claise-export-application-info-in-ipfix](#) with reference to [rfc6759](#), [draft-trammell-ipfix-a9n](#) to [draft-ietf-ipfix-a9n](#), [draft-kashima-ipfix-data-link-layer-monitoring](#) to [draft-ietf-ipfix-data-link-layer-monitoring](#).

06: sync the references.

07: Update per comment from Andrew Feren - change semantics of ipv4RouterSc to "identifier" and remove deltaFlowCount as it made it to IANA. Update references [RFC5101](#) to [RFC7011](#), [draft-ietf-ipfix-data-link-layer-monitoring](#) from -03 to -04.

08: restore the 84 samplerName after its accidental deletion from table 1 in -07; mark 101-103 IEs as deprecated, include the paragraph on IE 105..126 that are not discussed in this draft.

Yourtchenko, et al.

Expires July 19, 2014

[Page 18]

Internet-Draft

Cisco Information Elements

January 2014

09: now that IANA assigned the IPFIX Information Elements in [draft-ietf-ipfix-data-link-layer-monitoring](#), this draft is updated to simplify IANA's/editor's work, with changes as follows. TBD02 became 409 as sectionOffset is now assigned by IANA. Removed "EDITOR's NOTE" for layer2packetSectionOffset, layer2packetSectionSize, layer2packetSectionData, ietf-ipfix-data-link-layer-monitoring.

Authors' Addresses

Andrew Yourtchenko
Cisco Systems, Inc.
De Kleetlaan, 7
Brussels, Diegem B-1831
Belgium

Phone: +32 2 704 5494
Email: ayourtch@cisco.com

Paul Aitken
Cisco Systems, Inc.
96 Commercial Quay
Edinburgh EH6 6LX
Scotland

Phone: +44 131 561 3616

Email: paitken@cisco.com

Benoit Claise
Cisco Systems, Inc.
De Kleetlaan, 6a b1
Diegem B-1831
Belgium

Phone: +32 2 704 5622
Email: bclaise@cisco.com